
DICE Embeddings

Release 0.1.3.2

Caglar Demir

Nov 24, 2024

Contents:

1	Dicee Manual	2
2	Installation	3
2.1	Installation from Source	3
3	Download Knowledge Graphs	3
4	Knowledge Graph Embedding Models	3
5	How to Train	3
6	Creating an Embedding Vector Database	5
6.1	Learning Embeddings	5
6.2	Loading Embeddings into Qdrant Vector Database	6
6.3	Launching Webservice	6
7	Answering Complex Queries	6
8	Predicting Missing Links	8
9	Downloading Pretrained Models	8
10	How to Deploy	8
11	Docker	8
12	Coverage Report	8
13	How to cite	10
14	dicee	12
14.1	Submodules	12
14.2	Attributes	158
14.3	Classes	159
14.4	Functions	160
14.5	Package Contents	161
	Python Module Index	206

DICE Embeddings¹: Hardware-agnostic Framework for Large-scale Knowledge Graph Embeddings:

1 Dicee Manual

Version: dicee 0.1.3.2

GitHub repository: <https://github.com/dice-group/dice-embeddings>

Publisher and maintainer: Caglar Demir²

Contact: caglar.demir@upb.de

License: OSI Approved :: MIT License

Dicee is a hardware-agnostic framework for large-scale knowledge graph embeddings.

Knowledge graph embedding research has mainly focused on learning continuous representations of knowledge graphs towards the link prediction problem. Recently developed frameworks can be effectively applied in a wide range of research-related applications. Yet, using these frameworks in real-world applications becomes more challenging as the size of the knowledge graph grows

We developed the DICE Embeddings framework (dicee) to compute embeddings for large-scale knowledge graphs in a hardware-agnostic manner. To achieve this goal, we rely on

1. **Pandas**³ & Co. to use parallelism at preprocessing a large knowledge graph,
2. **PyTorch**⁴ & Co. to learn knowledge graph embeddings via multi-CPU, GPUs, TPUs or computing cluster, and
3. **Huggingface**⁵ to ease the deployment of pre-trained models.

Why Pandas⁶ & Co. ? A large knowledge graph can be read and preprocessed (e.g. removing literals) by pandas, modin, or polars in parallel. Through polars, a knowledge graph having more than 1 billion triples can be read in parallel fashion. Importantly, using these frameworks allow us to perform all necessary computations on a single CPU as well as a cluster of computers.

Why PyTorch⁷ & Co. ? PyTorch is one of the most popular machine learning frameworks available at the time of writing. PytorchLightning facilitates scaling the training procedure of PyTorch without boilerplate. In our framework, we combine **PyTorch**⁸ & **PytorchLightning**⁹. Users can choose the trainer class (e.g., DDP by Pytorch) to train large knowledge graph embedding models with billions of parameters. PytorchLightning allows us to use state-of-the-art model parallelism techniques (e.g. Fully Sharded Training, FairScale, or DeepSpeed) without extra effort. With our framework, practitioners can directly use PytorchLightning for model parallelism to train gigantic embedding models.

Why Hugging-face Gradio¹⁰? Deploy a pre-trained embedding model without writing a single line of code.

¹ <https://github.com/dice-group/dice-embeddings>

² <https://github.com/Demirrr>

³ <https://pandas.pydata.org/>

⁴ <https://pytorch.org/>

⁵ <https://huggingface.co/>

⁶ <https://pandas.pydata.org/>

⁷ <https://pytorch.org/>

⁸ <https://pytorch.org/>

⁹ <https://www.pytorchlightning.ai/>

¹⁰ <https://huggingface.co/gradio>

2 Installation

2.1 Installation from Source

```
git clone https://github.com/dice-group/dice-embeddings.git
conda create -n dice python=3.10.13 --no-default-packages && conda activate dice &&
↪ cd dice-embeddings &&
pip3 install -e .
```

or

```
pip install dicee
```

3 Download Knowledge Graphs

```
wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-
↪ certificate && unzip KGs.zip
```

To test the Installation

```
python -m pytest -p no:warnings -x # Runs >114 tests leading to > 15 mins
python -m pytest -p no:warnings --lf # run only the last failed test
python -m pytest -p no:warnings --ff # to run the failures first and then the rest of
↪ the tests.
```

4 Knowledge Graph Embedding Models

1. TransE, DistMult, ComplEx, ConEx, QMult, OMult, ConvO, ConvQ, Keci
2. All 44 models available in <https://github.com/pykeen/pykeen#models>

For more, please refer to examples.

5 How to Train

To Train a KGE model (KECI) and evaluate it on the train, validation, and test sets of the UMLS benchmark dataset.

```
from dicee.executer import Execute
from dicee.config import Namespace
args = Namespace()
args.model = 'Keci'
args.scoring_technique = "KvsAll" # 1vsAll, or AllvsAll, or NegSample
args.dataset_dir = "KGs/UMLS"
args.path_to_store_single_run = "Keci_UMLS"
args.num_epochs = 100
args.embedding_dim = 32
args.batch_size = 1024
reports = Execute(args).start()
print(reports["Train"]["MRR"]) # => 0.9912
print(reports["Test"]["MRR"]) # => 0.8155
# See the Keci_UMLS folder embeddings and all other files
```

where the data is in the following form

```
$ head -3 KGs/UMLS/train.txt
acquired_abnormality    location_of             experimental_model_of_disease
anatomical_abnormality  manifestation_of        physiologic_function
alga    isa      entity
```

A KGE model can also be trained from the command line

```
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

dicee automatically detects available GPUs and trains a model with distributed data parallels technique. Under the hood, dicee uses lightning as a default trainer.

```
# Train a model by only using the GPU-0
CUDA_VISIBLE_DEVICES=0 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model
↪ "train_val_test"
# Train a model by only using GPU-1
CUDA_VISIBLE_DEVICES=1 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model
↪ "train_val_test"
NCCL_P2P_DISABLE=1 CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL -
↪ --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

Under the hood, dicee executes run.py script and uses lightning as a default trainer

```
# Two equivalent executions
# (1)
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
↪ 9753123402351737}
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
↪ 'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
↪ 'MRR': 0.8064032293278861}

# (2)
CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL --dataset_dir "KGs/
↪ UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
↪ 9753123402351737}
# Evaluate Keci on Train set: Evaluate Keci on Train set
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
↪ 'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
↪ 'MRR': 0.8064032293278861}
```

Similarly, models can be easily trained with torchrun

```
torchrun --standalone --nnodes=1 --nproc_per_node=gpu dicee/scripts/run.py --trainer_
→torchDDP --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
→9753123402351737}
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
→'MRR': 0.8072499937521418}
# Evaluate Keci on Test set: Evaluate Keci on Test set
{'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
→'MRR': 0.8064032293278861}
```

You can also train a model in multi-node multi-gpu setting.

```
torchrun --nnodes 2 --nproc_per_node=gpu --node_rank 0 --rdzv_id 455 --rdzv_backend_
→c10d --rdzv_endpoint=nebula dicee/scripts/run.py --trainer torchDDP --dataset_dir_
→KGs/UMLS
torchrun --nnodes 2 --nproc_per_node=gpu --node_rank 1 --rdzv_id 455 --rdzv_backend_
→c10d --rdzv_endpoint=nebula dicee/scripts/run.py --trainer torchDDP --dataset_dir_
→KGs/UMLS
```

Train a KGE model by providing the path of a single file and store all parameters under newly created directory called KeciFamilyRun.

```
dicee --path_single_kg "KGs/Family/family-benchmark_rich_background.owl" --model Keci_
→--path_to_store_single_run KeciFamilyRun --backend rdflib
```

where the data is in the following form

```
$ head -3 KGs/Family/train.txt
_:1 <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://www.w3.org/2002/07/owl
→#Ontology> .
<http://www.benchmark.org/family#hasChild> <http://www.w3.org/1999/02/22-rdf-syntax-ns
→#type> <http://www.w3.org/2002/07/owl#ObjectProperty> .
<http://www.benchmark.org/family#hasParent> <http://www.w3.org/1999/02/22-rdf-syntax-
→ns#type> <http://www.w3.org/2002/07/owl#ObjectProperty> .
```

Apart from n-triples or standard link prediction dataset formats, we support ["owl", "nt", "turtle", "rdf/xml", "n3"]*. Moreover, a KGE model can be also trained by providing an endpoint of a triple store.

```
dicee --sparql_endpoint "http://localhost:3030/mutagenesis/" --model Keci
```

For more, please refer to examples.

6 Creating an Embedding Vector Database

6.1 Learning Embeddings

```
# Train an embedding model
dicee --dataset_dir KGs/Countries-S1 --path_to_store_single_run CountryEmbeddings --
→model Keci --p 0 --q 1 --embedding_dim 32 --adaptive_swa
```

6.2 Loading Embeddings into Qdrant Vector Database

```
# Ensure that Qdrant available
# docker pull qdrant/qdrant && docker run -p 6333:6333 -p 6334:6334 -v $(pwd)/
↪qdrant_storage:/qdrant/storage:z qdrant/qdrant
diceeindex --path_model "CountryEmbeddings" --collection_name "dummy" --location
↪"localhost"
```

6.3 Launching Webservice

```
diceeserve --path_model "CountryEmbeddings" --collection_name "dummy" --collection_
↪location "localhost"
```

Retrieve and Search

Get embedding of germany

```
curl -X 'GET' 'http://0.0.0.0:8000/api/get?q=germany' -H 'accept: application/json'
```

Get most similar things to europe

```
curl -X 'GET' 'http://0.0.0.0:8000/api/search?q=europe' -H 'accept: application/json'
{"result":[{"hit":"europe","score":1.0},
{"hit":"northern_europe","score":0.67126536},
{"hit":"western_europe","score":0.6010134},
{"hit":"puerto_rico","score":0.5051694},
{"hit":"southern_europe","score":0.4829831}]}
```

7 Answering Complex Queries

```
# pip install dicee
# wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-
↪certificate & unzip KGs.zip
from dicee.executer import Execute
from dicee.config import Namespace
from dicee.knowledge_graph_embeddings import KGE
# (1) Train a KGE model
args = Namespace()
args.model = 'Keci'
args.p=0
args.q=1
args.optim = 'Adam'
args.scoring_technique = "AllvsAll"
args.path_single_kg = "KGs/Family/family-benchmark_rich_background.owl"
args.backend = "rdflib"
args.num_epochs = 200
args.batch_size = 1024
args.lr = 0.1
args.embedding_dim = 512
result = Execute(args).start()
# (2) Load the pre-trained model
```

(continues on next page)

(continued from previous page)

```
pre_trained_kge = KGE(path=result['path_experiment_folder'])
# (3) Single-hop query answering
# Query: ?E : \exist E.hasSibling(E, F9M167)
# Question: Who are the siblings of F9M167?
# Answer: [F9M157, F9F141], as (F9M167, hasSibling, F9M157) and (F9M167, hasSibling, ↵
↵F9F141)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="1p",
                                                       query=('http://www.benchmark.org/
↵family#F9M167',
                                                       ('http://www.benchmark.
↵org/family#hasSibling',)),
                                                       tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9F141" in top_entities
assert "http://www.benchmark.org/family#F9M157" in top_entities
# (2) Two-hop query answering
# Query: ?D : \exist E.Married(D, E) \land hasSibling(E, F9M167)
# Question: To whom a sibling of F9M167 is married to?
# Answer: [F9F158, F9M142] as (F9M157 #married F9F158) and (F9F141 #married F9M142)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="2p",
                                                       query=("http://www.benchmark.org/
↵family#F9M167",
                                                       ("http://www.benchmark.
↵org/family#hasSibling",
                                                       "http://www.benchmark.
↵org/family#married")),
                                                       tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9M142" in top_entities
assert "http://www.benchmark.org/family#F9F158" in top_entities
# (3) Three-hop query answering
# Query: ?T : \exist D.type(D,T) \land Married(D,E) \land hasSibling(E, F9M167)
# Question: What are the type of people who are married to a sibling of F9M167?
# (3) Answer: [Person, Male, Father] since F9M157 is [Brother Father Grandfather ↵
↵Male] and F9M142 is [Male Grandfather Father]
predictions = pre_trained_kge.answer_multi_hop_query(query_type="3p", query=("http://
↵www.benchmark.org/family#F9M167",
                                                       ("http://
↵www.benchmark.org/family#hasSibling",
                                                       "http://
↵www.benchmark.org/family#married",
                                                       "http://
↵www.w3.org/1999/02/22-rdf-syntax-ns#type")),
                                                       tnorm="min", k=5)
top_entities = [topk_entity for topk_entity, query_score in predictions]
print(top_entities)
assert "http://www.benchmark.org/family#Person" in top_entities
assert "http://www.benchmark.org/family#Father" in top_entities
assert "http://www.benchmark.org/family#Male" in top_entities
```

For more, please refer to examples/multi_hop_query_answering.

8 Predicting Missing Links

```
from dicee import KGE
# (1) Train a knowledge graph embedding model..
# (2) Load a pretrained model
pre_trained_kge = KGE(path='../')
# (3) Predict missing links through head entity rankings
pre_trained_kge.predict_topk(h=[".."],r=[".."],topk=10)
# (4) Predict missing links through relation rankings
pre_trained_kge.predict_topk(h=[".."],t=[".."],topk=10)
# (5) Predict missing links through tail entity rankings
pre_trained_kge.predict_topk(r=[".."],t=[".."],topk=10)
```

9 Downloading Pretrained Models

```
from dicee import KGE
# (1) Load a pretrained ConEx on DBpedia
model = KGE(url="https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-
↳dim128-epoch256-KvsAll")
```

- For more please look at dice-research.org/projects/DiceEmbeddings/¹¹

10 How to Deploy

```
from dicee import KGE
KGE(path='../').deploy(share=True, top_k=10)
```

11 Docker

To build the Docker image:

```
docker build -t dice-embeddings .
```

To test the Docker image:

```
docker run --rm -v ~/.local/share/dicee/KGs:/dicee/KGs dice-embeddings ./main.py --
↳model AConEx --embedding_dim 16
```

12 Coverage Report

The coverage report is generated using `coverage.py`¹²:

Name	Stmts	Miss	Cover	Missing
-----	-----	-----	-----	-----
dicee/___init___ .py	7	0	100%	
dicee/abstracts.py	201	82	59%	104-105, 107-108, 110-111, 113-114, 116-117, 119-120, 122-123, 125-126, 128-129, 131-132, 134-135, 137-138, 140-141, 143-144, 146-147, 149-150, 152-153, 155-156, 158-159, 161-162, 164-165, 167-168, 170-171, 173-174, 176-177, 179-180, 182-183, 185-186, 188-189, 191-192, 194-195, 197-198, 200-201, 203-204, 206-207, 209-210, 212-213, 215-216, 218-219, 221-222, 224-225, 227-228, 230-231, 233-234, 236-237, 239-240, 242-243, 245-246, 248-249, 251-252, 254-255, 257-258, 260-261, 263-264, 266-267, 269-270, 272-273, 275-276, 278-279, 281-282, 284-285, 287-288, 290-291, 293-294, 296-297, 299-300, 302-303, 305-306, 308-309, 311-312, 314-315, 317-318, 320-321, 323-324, 326-327, 329-330, 332-333, 335-336, 338-339, 341-342, 344-345, 347-348, 350-351, 353-354, 356-357, 359-360, 362-363, 365-366, 368-369, 371-372, 374-375, 377-378, 380-381, 383-384, 386-387, 389-390, 392-393, 395-396, 398-399, 401-402, 404-405, 407-408, 410-411, 413-414, 416-417, 419-420, 422-423, 425-426, 428-429, 431-432, 434-435, 437-438, 440-441, 443-444, 446-447, 449-450, 452-453, 455-456, 458-459, 461-462, 464-465, 467-468, 470-471, 473-474, 476-477, 479-480, 482-483, 485-486, 488-489, 491-492, 494-495, 497-498, 500-501, 503-504, 506-507, 509-510, 512-513, 515-516, 518-519, 521-522, 524-525, 527-528, 530-531, 533-534, 536-537, 539-540, 542-543, 545-546, 548-549, 551-552, 554-555, 557-558, 560-561, 563-564, 566-567, 569-570, 572-573, 575-576, 578-579, 581-582, 584-585, 587-588, 590-591, 593-594, 596-597, 599-600, 602-603, 605-606, 608-609, 611-612, 614-615, 617-618, 620-621, 623-624, 626-627, 629-630, 632-633, 635-636, 638-639, 641-642, 644-645, 647-648, 650-651, 653-654, 656-657, 659-660, 662-663, 665-666, 668-669, 671-672, 674-675, 677-678, 680-681, 683-684, 686-687, 689-690, 692-693, 695-696, 698-699, 701-702, 704-705, 707-708, 710-711, 713-714, 716-717, 719-720, 722-723, 725-726, 728-729, 731-732, 734-735, 737-738, 740-741, 743-744, 746-747, 749-750, 752-753, 755-756, 758-759, 761-762, 764-765, 767-768, 770-771, 773-774, 776-777, 779-780, 782-783, 785-786, 788-789, 791-792, 794-795, 797-798, 800-801, 803-804, 806-807, 809-810, 812-813, 815-816, 818-819, 821-822, 824-825, 827-828, 830-831, 833-834, 836-837, 839-840, 842-843, 845-846, 848-849, 851-852, 854-855, 857-858, 860-861, 863-864, 866-867, 869-870, 872-873, 875-876, 878-879, 881-882, 884-885, 887-888, 890-891, 893-894, 896-897, 899-900, 902-903, 905-906, 908-909, 911-912, 914-915, 917-918, 920-921, 923-924, 926-927, 929-930, 932-933, 935-936, 938-939, 941-942, 944-945, 947-948, 950-951, 953-954, 956-957, 959-960, 962-963, 965-966, 968-969, 971-972, 974-975, 977-978, 980-981, 983-984, 986-987, 989-990, 992-993, 995-996, 998-999

(continues on next page)

¹¹ <https://files.dice-research.org/projects/DiceEmbeddings/>

¹² <https://coverage.readthedocs.io/en/7.6.0/>

(continued from previous page)

```
→123, 146-147, 152, 165, 197, 240-254, 257-260, 263-266, 301, 314-317, 320-324, 364-  
→375, 390-398, 413, 424-428, 555-575, 581-585, 589-591  
dicee/callbacks.py 245 102 58% 50-55,   
→67-73, 76, 88-93, 98-103, 106-109, 116-133, 138-142, 146-147, 276-280, 286-287, 305-  
→311, 314, 319-320, 332-338, 344-353, 358-360, 405, 416-429, 433-468, 480-486  
dicee/config.py 93 2 98% 141-142  
dicee/dataset_classes.py 299 74 75% 41, 54,   
→87, 93, 99-106, 109, 112, 115-139, 195-201, 204, 207-209, 314, 325-328, 344, 410-  
→411, 429, 528-536, 539, 543-557, 700-707, 710-714  
dicee/eval_static_funcs.py 227 95 58% 101, 106,  
→ 111, 258-353, 360-411  
dicee/evaluator.py 262 51 81% 46, 51,   
→56, 84, 89-90, 93, 109, 126, 137, 141, 146, 177-188, 195-206, 314, 344-367, 455,   
→465, 482-487  
dicee/executer.py 113 4 96% 116, 258-  
→259, 291  
dicee/knowledge_graph.py 65 3 95% 79, 110,   
→114  
dicee/knowledge_graph_embeddings.py 636 443 30% 27, 30-  
→31, 39-52, 57-90, 93-127, 131-139, 170-184, 215-228, 254-274, 324-327, 330-333, 346,  
→ 381-426, 484-486, 502-503, 509-517, 522-525, 528-533, 538, 547, 592-598, 630, 688-  
→1053, 1084-1145, 1149-1177, 1200, 1227-1265  
dicee/models/__init__.py 9 0 100%  
dicee/models/base_model.py 234 31 87% 54, 56,   
→82, 88-103, 157, 190, 230, 236, 245, 248, 252, 259, 263, 265, 280, 288-289, 296-297,  
→ 351, 354, 427, 439  
dicee/models/clifford.py 556 357 36% 31-42,   
→68-117, 122-133, 156-168, 190-220, 235, 237, 241, 248-249, 276-280, 303-311, 325-  
→327, 332-333, 364-384, 406, 413, 417-478, 495-499, 511, 514, 519, 524, 571-607, 625-  
→631, 644, 647, 652, 657, 686-692, 705, 708, 713, 718, 728-737, 753-754, 774-845,   
→856-859, 884-909, 933-966, 1002-1006, 1019, 1029, 1032, 1037, 1042, 1047, 1051,   
→1055, 1064-1065, 1095, 1102, 1107, 1135-1139, 1167-1176, 1186-1194, 1212-1214, 1232-  
→1234, 1250-1252  
dicee/models/complex.py 151 15 90% 86-109  
dicee/models/dualE.py 59 10 83% 93-102,   
→142-156  
dicee/models/function_space.py 262 221 16% 10-24,   
→28-37, 40-49, 53-70, 77-86, 89-98, 101-110, 114-126, 134-156, 159-165, 168-185, 188-  
→194, 197-205, 208, 213-234, 243-246, 250-254, 258-267, 271-292, 301-307, 311-328,   
→332-335, 344-352, 355, 366-372, 392-406, 424-438, 443-453, 461-465, 474-478  
dicee/models/octonion.py 227 83 63% 21-44,   
→320-329, 334-345, 348-370, 374-416, 426-474  
dicee/models/pykeen_models.py 50 5 90% 60-63,   
→118  
dicee/models/quaternion.py 192 69 64% 7-21, 30-  
→55, 68-72, 107, 185, 328-342, 345-364, 368-389, 399-426  
dicee/models/real.py 61 12 80% 36-39,   
→66-69, 87, 103-106  
dicee/models/static_funcs.py 10 0 100%  
dicee/models/transformers.py 236 189 20% 24-43,   
→46, 60-75, 84-102, 105-116, 123-125, 128, 134-151, 155-180, 186-190, 193-197, 203-  
→207, 210-212, 229-256, 265-268, 271-276, 279-304, 310-315, 319-372, 376-398, 404-414
```

(continues on next page)

(continued from previous page)

dicee/query_generator.py	374	346	7%	18-52, ↪
↪56, 62-65, 69-70, 78-92, 100-147, 155-188, 192-206, 212-269, 274-303, 307-443, 453-↪472, 480-501, 508-512, 517, 522-528				
dicee/read_preprocess_save_load_kg/___init___py	3	0	100%	
dicee/read_preprocess_save_load_kg/preprocess.py	256	41	84%	34, 40, ↪
↪78, 102-127, 133, 138-151, 184, 214, 388-389, 444				
dicee/read_preprocess_save_load_kg/read_from_disk.py	36	11	69%	33, 38-↪40, 47, 55, 58-72
dicee/read_preprocess_save_load_kg/save_load_disk.py	45	18	60%	39-60
dicee/read_preprocess_save_load_kg/util.py	219	126	42%	65-67, ↪
↪72-73, 91-97, 100-102, 107-109, 121, 134, 140-143, 148-156, 161-167, 172-177, 182-↪187, 199-220, 226-282, 286-290, 294-295, 299, 303-304, 334, 351, 356, 363-364				
dicee/sanity_checkers.py	54	23	57%	8-12, 21-↪31, 46, 51, 58, 64-79, 85, 89, 96
dicee/static_funcs.py	418	163	61%	40, 50, ↪
↪56-61, 83, 105-106, 115, 138, 152, 157-159, 163-165, 167, 194-198, 246, 254, 263-↪268, 290-304, 316-336, 340-357, 362, 386-387, 392-393, 410-411, 413-414, 416-417, ↪				
↪419-420, 428, 446-450, 467-470, 474-479, 483-487, 491-492, 498-500, 526-527, 539-↪542, 547-550, 559-610, 615-627, 644-658, 661-669				
dicee/static_funcs_training.py	123	63	49%	118-215, ↪
↪223-224				
dicee/static_preprocess_funcs.py	100	44	56%	17-25, ↪
↪52, 56, 64, 67, 78, 91-115, 120-123, 128-131, 136-139				
dicee/trainer/___init___py	1	0	100%	
dicee/trainer/dice_trainer.py	126	13	90%	27-32, ↪
↪91, 98, 103-108, 147				
dicee/trainer/torch_trainer.py	79	4	95%	31, 196, ↪
↪207-208				
dicee/trainer/torch_trainer_ddp.py	152	128	16%	13-14, ↪
↪43, 47-72, 83-112, 131-137, 140-149, 164-194, 204-217, 226-246, 251-260, 263-272, ↪				
↪275-299, 302-309				

TOTAL	6181	2828	54%	

13 How to cite

Currently, we are working on our manuscript describing our framework. If you really like our work and want to cite it now, feel free to chose one :)

```
# Keci
@inproceedings{demir2023clifford,
  title={Clifford Embeddings--A Generalized Approach for Embedding in Normed Algebras}
  ↪,
  author={Demir, Caglar and Ngonga Ngomo, Axel-Cyrille},
  booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in ↪
  ↪Databases},
  pages={567--582},
  year={2023},
  organization={Springer}
}
# LitCQD
```

(continues on next page)

```

@inproceedings{demir2023litcq,
  title={LitCQD: Multi-Hop Reasoning in Incomplete Knowledge Graphs with Numeric_
↪Literals},
  author={Demir, Caglar and Wiebesiek, Michel and Lu, Renzhong and Ngonga Ngomo, Axel-
↪Cyrille and Heindorf, Stefan},
  booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in_
↪Databases},
  pages={617--633},
  year={2023},
  organization={Springer}
}
# DICE Embedding Framework
@article{demir2022hardware,
  title={Hardware-agnostic computation for large-scale knowledge graph embeddings},
  author={Demir, Caglar and Ngomo, Axel-Cyrille Ngonga},
  journal={Software Impacts},
  year={2022},
  publisher={Elsevier}
}
# KronE
@inproceedings{demir2022kronecker,
  title={Kronecker decomposition for knowledge graph embeddings},
  author={Demir, Caglar and Lienen, Julian and Ngonga Ngomo, Axel-Cyrille},
  booktitle={Proceedings of the 33rd ACM Conference on Hypertext and Social Media},
  pages={1--10},
  year={2022}
}
# QMult, OMult, ConvQ, ConvO
@InProceedings{pmlr-v157-demir21a,
  title = {Convolutional Hypercomplex Embeddings for Link Prediction},
  author = {Demir, Caglar and Moussallem, Diego and Heindorf, Stefan and Ngonga_
↪Ngomo, Axel-Cyrille},
  booktitle = {Proceedings of The 13th Asian Conference on Machine Learning},
  pages = {656--671},
  year = {2021},
  editor = {Balasubramanian, Vineeth N. and Tsang, Ivor},
  volume = {157},
  series = {Proceedings of Machine Learning Research},
  month = {17--19 Nov},
  publisher = {PMLR},
  pdf = {https://proceedings.mlr.press/v157/demir21a/demir21a.pdf},
  url = {https://proceedings.mlr.press/v157/demir21a.html},
}
# ConEx
@inproceedings{demir2021convolutional,
  title={Convolutional Complex Knowledge Graph Embeddings},
  author={Caglar Demir and Axel-Cyrille Ngonga Ngomo},
  booktitle={Eighteenth Extended Semantic Web Conference - Research Track},
  year={2021},
  url={https://openreview.net/forum?id=6T45-4TFqaX}}
# Shallow
@inproceedings{demir2021shallow,

```

```

title={A shallow neural model for relation prediction},
author={Demir, Caglar and Moussallem, Diego and Ngomo, Axel-Cyrille Ngonga},
booktitle={2021 IEEE 15th International Conference on Semantic Computing (ICSC)},
pages={179--182},
year={2021},
organization={IEEE}

```

For any questions or wishes, please contact: caglar.demir@upb.de

14 dicee

14.1 Submodules

dicee.__main__

dicee.abstracts

Classes

<i>AbstractTrainer</i>	Abstract class for Trainer class for knowledge graph embedding models
<i>BaseInteractiveKGE</i>	Abstract/base class for using knowledge graph embedding models interactively.
<i>AbstractCallback</i>	Abstract class for Callback class for knowledge graph embedding models
<i>AbstractPPECallback</i>	Abstract class for Callback class for knowledge graph embedding models

Module Contents

class `dicee.abstracts.AbstractTrainer` (*args*, *callbacks*)

Abstract class for Trainer class for knowledge graph embedding models

Parameter

args

[str] ?

callbacks: list

?

attributes

callbacks

is_global_zero = True

global_rank = 0

local_rank = 0

strategy = None

on_fit_start (*args, **kwargs)

A function to call callbacks before the training starts.

Parameter

args

kwargs

rtype

None

on_fit_end (*args, **kwargs)

A function to call callbacks at the end of the training.

Parameter

args

kwargs

rtype

None

on_train_epoch_end (*args, **kwargs)

A function to call callbacks at the end of an epoch.

Parameter

args

kwargs

rtype

None

on_train_batch_end (*args, **kwargs)

A function to call callbacks at the end of each mini-batch during training.

Parameter

args

kwargs

rtype

None

static save_checkpoint (full_path: str, model) → None

A static function to save a model into disk

Parameter

full_path : str

model:

rtype

None

```
class dicee.abstracts.BaseInteractiveKGE (path: str = None, url: str = None,
    construct_ensemble: bool = False, model_name: str = None,
    apply_semantic_constraint: bool = False)
```

Abstract/base class for using knowledge graph embedding models interactively.

Parameter

path_of_pretrained_model_dir
[str] ?

construct_ensemble: boolean
?

model_name: str apply_semantic_constraint : boolean

construct_ensemble

apply_semantic_constraint

configs

get_eval_report () → dict

get_bpe_token_representation (str_entity_or_relation: List[str] | str) → List[List[int]] | List[int]

Parameters

str_entity_or_relation (corresponds to a str or a list of strings to be tokenized via BPE and shaped.)

Return type

A list integer(s) or a list of lists containing integer(s)

get_padded_bpe_triple_representation (triples: List[List[str]]) → Tuple[List, List, List]

Parameters

triples

set_model_train_mode () → None

Setting the model into training mode

Parameter

set_model_eval_mode () → None

Setting the model into eval mode

Parameter

property name

sample_entity (n: int) → List[str]

sample_relation (n: int) → List[str]

is_seen (entity: str = None, relation: str = None) → bool

save () → None

get_entity_index (x: str)

get_relation_index (*x: str*)

index_triple (*head_entity: List[str], relation: List[str], tail_entity: List[str]*)
→ Tuple[torch.LongTensor, torch.LongTensor, torch.LongTensor]

Index Triple

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

pytorch tensor of triple score

add_new_entity_embeddings (*entity_name: str = None, embeddings: torch.FloatTensor = None*)

get_entity_embeddings (*items: List[str]*)

Return embedding of an entity given its string representation

Parameter

items:

entities

get_relation_embeddings (*items: List[str]*)

Return embedding of a relation given its string representation

Parameter

items:

relations

construct_input_and_output (*head_entity: List[str], relation: List[str], tail_entity: List[str], labels*)

Construct a data point :param head_entity: :param relation: :param tail_entity: :param labels: :return:

parameters ()

class dicee.abstracts.**AbstractCallback**

Bases: abc.ABC, lightning.pytorch.callbacks.Callback

Abstract class for Callback class for knowledge graph embedding models

Parameter

on_init_start (**args, **kwargs*)

Parameter

trainer:

model:

rtype

None

on_init_end (**args, **kwargs*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

on_fit_start (*trainer, model*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

on_train_epoch_end (*trainer, model*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype

None

on_train_batch_end (**args, **kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype

None

on_fit_end (**args, **kwargs*)

Call at the end of the training.

Parameter

trainer:

model:

rtype

None

```
class dicee.abstracts.AbstractPPECallback (num_epochs, path, epoch_to_start,  
last_percent_to_consider)
```

Bases: [AbstractCallback](#)

Abstract class for Callback class for knowledge graph embedding models

Parameter

num_epochs

path

sample_counter = 0

epoch_count = 0

alphas = None

on_fit_start (trainer, model)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

on_fit_end (trainer, model)

Call at the end of the training.

Parameter

trainer:

model:

rtype

None

store_ensemble (param_ensemble) → None

dicee.analyse_experiments

This script should be moved to dicee/scripts

Classes

Experiment

Functions

get_default_arguments()

analyse(args)

Module Contents

`dicee.analyse_experiments.get_default_arguments()`

`class dicee.analyse_experiments.Experiment`

```
    model_name = []
    callbacks = []
    embedding_dim = []
    num_params = []
    num_epochs = []
    batch_size = []
    lr = []
    byte_pair_encoding = []
    aswa = []
    path_dataset_folder = []
    full_storage_path = []
    pq = []
    train_mrr = []
    train_h1 = []
    train_h3 = []
    train_h10 = []
    val_mrr = []
    val_h1 = []
    val_h3 = []
```

```

val_h10 = []

test_mrr = []

test_h1 = []

test_h3 = []

test_h10 = []

runtime = []

normalization = []

scoring_technique = []

save_experiment(x)

to_df()

```

```
dicee.analyse_experiments.analyse(args)
```

dicee.callbacks

Classes

<i>AccumulateEpochLossCallback</i>	Abstract class for Callback class for knowledge graph embedding models
<i>PrintCallback</i>	Abstract class for Callback class for knowledge graph embedding models
<i>KGESaveCallback</i>	Abstract class for Callback class for knowledge graph embedding models
<i>PseudoLabellingCallback</i>	Abstract class for Callback class for knowledge graph embedding models
<i>ASWA</i>	Adaptive stochastic weight averaging
<i>Eval</i>	Abstract class for Callback class for knowledge graph embedding models
<i>KronE</i>	Abstract class for Callback class for knowledge graph embedding models
<i>Perturb</i>	A callback for a three-Level Perturbation

Functions

<i>estimate_q</i> (eps)	estimate rate of convergence q from sequence esp
<i>compute_convergence</i> (seq, i)	

Module Contents

```
class dicee.callbacks.AccumulateEpochLossCallback (path: str)
```

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

path

on_fit_end (*trainer, model*) → None

Store epoch loss

Parameter

trainer:

model:

rtype

None

class `dicee.callbacks.PrintCallback`

Bases: `dicee.abstracts.AbstractCallback`

Abstract class for Callback class for knowledge graph embedding models

Parameter

start_time

on_fit_start (*trainer, pl_module*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

on_fit_end (*trainer, pl_module*)

Call at the end of the training.

Parameter

trainer:

model:

rtype

None

on_train_batch_end (**args, **kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end (*args, **kwargs)
Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.KGESaveCallback (every_x_epoch: int, max_epochs: int, path: str)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

every_x_epoch

max_epochs

epoch_counter = 0

path

on_train_batch_end (*args, **kwargs)
Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

on_fit_start (trainer, pl_module)
Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end (*args, **kwargs)
Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype

None

on_fit_end (*args, **kwargs)

Call at the end of the training.

Parameter

trainer:

model:

rtype

None

on_epoch_end (model, trainer, **kwargs)

class dicee.callbacks.**PseudoLabellingCallback** (data_module, kg, batch_size)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

data_module

kg

num_of_epochs = 0

unlabelled_size

batch_size

create_random_data ()

on_epoch_end (trainer, model)

`dicee.callbacks.estimate_q` (eps)

estimate rate of convergence q from sequence esp

`dicee.callbacks.compute_convergence` (seq, i)

class dicee.callbacks.**ASWA** (num_epochs, path)

Bases: *dicee.abstracts.AbstractCallback*

Adaptive stochastic weight averaging ASWE keeps track of the validation performance and update s the ensemble model accordingly.

path

num_epochs

initial_eval_setting = None

```
epoch_count = 0

alphas = []

val_aswa

on_fit_end(trainer, model)
    Call at the end of the training.
```

Parameter

trainer:

model:

rtype

None

```
static compute_mrr(trainer, model) → float
```

```
get_aswa_state_dict(model)
```

```
decide(running_model_state_dict, ensemble_state_dict, val_running_model,
        mrr_updated_ensemble_model)
```

Perform Hard Update, software or rejection

Parameters

- `running_model_state_dict`
- `ensemble_state_dict`
- `val_running_model`
- `mrr_updated_ensemble_model`

```
on_train_epoch_end(trainer, model)
```

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype

None

```
class dicee.callbacks.Eval(path, epoch_ratio: int = None)
```

Bases: `dicee.abstracts.AbstractCallback`

Abstract class for Callback class for knowledge graph embedding models

Parameter

path

reports = []

epoch_ratio

```
epoch_counter = 0
```

```
on_fit_start(trainer, model)
```

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

```
on_fit_end(trainer, model)
```

Call at the end of the training.

Parameter

trainer:

model:

rtype

None

```
on_train_epoch_end(trainer, model)
```

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype

None

```
on_train_batch_end(*args, **kwargs)
```

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype

None

```
class dicee.callbacks.KronE
```

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

f = None

static batch_kronecker_product (*a, b*)

Kronecker product of matrices a and b with leading batch dimensions. Batch dimensions are broadcast. The number of them must be the same :type a: torch.Tensor :type b: torch.Tensor :rtype: torch.Tensor

get_kronecker_triple_representation (*indexed_triple: torch.LongTensor*)

Get kronecker embeddings

on_fit_start (*trainer, model*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype

None

class dicee.callbacks.**Perturb** (*level: str = 'input', ratio: float = 0.0, method: str = None, scaler: float = None, frequency=None*)

Bases: *dicee.abstracts.AbstractCallback*

A callback for a three-Level Perturbation

Input Perturbation: During training an input x is perturbed by randomly replacing its element. In the context of knowledge graph embedding models, x can denote a triple, a tuple of an entity and a relation, or a tuple of two entities. A perturbation means that a component of x is randomly replaced by an entity or a relation.

Parameter Perturbation:

Output Perturbation:

level

ratio

method

scaler

frequency

on_train_batch_start (*trainer, model, batch, batch_idx*)

Called when the train batch begins.

dicee.config

Classes

Namespace

Simple object for storing attributes.

Module Contents

```
class dicee.config.Namespace (**kwargs)
```

Bases: argparse.Namespace

Simple object for storing attributes.

Implements equality by attribute names and values, and provides a simple string representation.

```
dataset_dir: str = None
```

The path of a folder containing train.txt, and/or valid.txt and/or test.txt

```
save_embeddings_as_csv: bool = False
```

Embeddings of entities and relations are stored into CSV files to facilitate easy usage.

```
storage_path: str = 'Experiments'
```

A directory named with time of execution under `storage_path` that contains related data about embeddings.

```
path_to_store_single_run: str = None
```

A single directory created that contains related data about embeddings.

```
path_single_kg = None
```

Path of a file corresponding to the input knowledge graph

```
sparql_endpoint = None
```

An endpoint of a triple store.

```
model: str = 'Keci'
```

KGE model

```
optim: str = 'Adam'
```

Optimizer

```
embedding_dim: int = 64
```

Size of continuous vector representation of an entity/relation

```
num_epochs: int = 150
```

Number of pass over the training data

```
batch_size: int = 1024
```

Mini-batch size if it is None, an automatic batch finder technique applied

```
lr: float = 0.1
```

Learning rate

```
add_noise_rate: float = None
```

The ratio of added random triples into training dataset

```
gpus = None
```

Number GPUs to be used during training

```
callbacks
```

```
10}}
```

Type

Callbacks, e.g., {“PPE”

Type

{ “last_percent_to_consider”

backend: str = 'pandas'

Backend to read, process, and index input knowledge graph. pandas, polars and rdflib available

separator: str = '\\s+'

separator for extracting head, relation and tail from a triple

trainer: str = 'torchCPUTrainer'

Trainer for knowledge graph embedding model

scoring_technique: str = 'KvsAll'

Scoring technique for knowledge graph embedding models

neg_ratio: int = 0

Negative ratio for a true triple in NegSample training_technique

weight_decay: float = 0.0

Weight decay for all trainable params

normalization: str = 'None'

LayerNorm, BatchNorm1d, or None

init_param: str = None

xavier_normal or None

gradient_accumulation_steps: int = 0

Not tested e

num_folds_for_cv: int = 0

Number of folds for CV

eval_model: str = 'train_val_test'

["None", "train", "train_val", "train_val_test", "test"]

Type

Evaluate trained model choices

save_model_at_every_epoch: int = None

Not tested

label_smoothing_rate: float = 0.0

num_core: int = 0

Number of CPUs to be used in the mini-batch loading process

random_seed: int = 0

Random Seed

sample_triples_ratio: float = None

Read some triples that are uniformly at random sampled. Ratio being between 0 and 1

read_only_few: int = None

Read only first few triples

pykeen_model_kwargs

Additional keyword arguments for pykeen models

kernel_size: int = 3

Size of a square kernel in a convolution operation

num_of_output_channels: int = 32
 Number of slices in the generated feature map by convolution.

p: int = 0
 P parameter of Clifford Embeddings

q: int = 1
 Q parameter of Clifford Embeddings

input_dropout_rate: float = 0.0
 Dropout rate on embeddings of input triples

hidden_dropout_rate: float = 0.0
 Dropout rate on hidden representations of input triples

feature_map_dropout_rate: float = 0.0
 Dropout rate on a feature map generated by a convolution operation

byte_pair_encoding: bool = False
 Byte pair encoding

Type
 WIP

adaptive_swa: bool = False
 Adaptive stochastic weight averaging

swa: bool = False
 Stochastic weight averaging

block_size: int = None
 block size of LLM

continual_learning = None
 Path of a pretrained model size of LLM

__iter__()

dicee.dataset_classes

Classes

<i>BPE_NegativeSamplingDataset</i>	An abstract class representing a Dataset.
<i>MultiLabelDataset</i>	An abstract class representing a Dataset.
<i>MultiClassClassificationDataset</i>	Dataset for the 1vsALL training strategy
<i>OnevsAllDataset</i>	Dataset for the 1vsALL training strategy
<i>KvsAll</i>	Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
<i>AllvsAll</i>	Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
<i>OnevsSample</i>	A custom PyTorch Dataset class for knowledge graph embeddings, which includes
<i>KvsSampleDataset</i>	KvsSample a Dataset:
<i>NegSampleDataset</i>	An abstract class representing a Dataset.
<i>TriplePredictionDataset</i>	Triple Dataset
<i>CVDDataModule</i>	Create a Dataset for cross validation

Functions

<code>reload_dataset(path, form_of_labelling, ...)</code>	Reload the files from disk to construct the Pytorch dataset
<code>construct_dataset(→ torch.utils.data.Dataset)</code>	

Module Contents

`dicee.dataset_classes.reload_dataset` (*path: str, form_of_labelling, scoring_technique, neg_ratio, label_smoothing_rate*)

Reload the files from disk to construct the Pytorch dataset

`dicee.dataset_classes.construct_dataset` (*, *train_set: numpy.ndarray | list, valid_set=None, test_set=None, ordered_bpe_entities=None, train_target_indices=None, target_dim: int = None, entity_to_idx: dict, relation_to_idx: dict, form_of_labelling: str, scoring_technique: str, neg_ratio: int, label_smoothing_rate: float, byte_pair_encoding=None, block_size: int = None*)
→ `torch.utils.data.Dataset`

class `dicee.dataset_classes.BPE_NegativeSamplingDataset` (*train_set: torch.LongTensor, ordered_shaped_bpe_entities: torch.LongTensor, neg_ratio: int*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

`train_set`

`ordered_bpe_entities`

`num_bpe_entities`

`neg_ratio`

`num_datapoints`

`__len__()`

`__getitem__(idx)`

`collate_fn` (*batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]]*)

class `dicee.dataset_classes.MultiLabelDataset` (*train_set: torch.LongTensor, train_indices_target: torch.LongTensor, target_dim: int, torch_ordered_shaped_bpe_entities: torch.LongTensor*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

`train_set`

`train_indices_target`

`target_dim`

`num_datapoints`

`torch_ordered_shaped_bpe_entities`

`collate_fn = None`

`__len__()`

`__getitem__(idx)`

```
class dicee.dataset_classes.MultiClassClassificationDataset(  
    subword_units: numpy.ndarray, block_size: int = 8)
```

Bases: `torch.utils.data.Dataset`

Dataset for the 1vsALL training strategy

Parameters

- `train_set_idx` – Indexed triples for the training.
- `entity_idx`s – mapping.
- `relation_idx`s – mapping.
- `form` – ?
- `num_workers` – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

`torch.utils.data.Dataset`

`train_data`

`block_size`

`num_of_data_points`

```
collate_fn = None
```

```
__len__()
```

```
__getitem__(idx)
```

```
class dicee.dataset_classes.OnevsAllDataset (train_set_idx: numpy.ndarray, entity_idx)
```

Bases: torch.utils.data.Dataset

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idx** – mapping.
- **relation_idx** – mapping.
- **form** – ?
- **num_workers** – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

torch.utils.data.Dataset

```
train_data
```

```
target_dim
```

```
collate_fn = None
```

```
__len__()
```

```
__getitem__(idx)
```

```
class dicee.dataset_classes.KvsAll (train_set_idx: numpy.ndarray, entity_idx, relation_idx, form,  
store=None, label_smoothing_rate: float = 0.0)
```

Bases: torch.utils.data.Dataset

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as $D := \{(x, y)_i\}_i^N$, where $x: (h, r)$ is a unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y : denotes a multi-label vector in $[0, 1]^{|E|}$ is a binary label.

orall $y_i = 1$ s.t. $(h \in E_i)$ in KG

Note

TODO

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idx

[dictionary] string representation of an entity to its integer id

relation_idx

[dictionary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = KvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

__len__()

__getitem__(idx)

```
class dicee.dataset_classes.AllvsAll (train_set_idx: numpy.ndarray, entity_idxes, relation_idxes,
    label_smoothing_rate=0.0)
```

Bases: torch.utils.data.Dataset

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as $D := \{(x, y)_i\}_i^N$, where $x: (h, r)$ is a possible unique tuple of an entity h in E and a relation r in R . Hence $N = |E| \times |R|$ y_i denotes a multi-label vector in $[0, 1]^{|E|}$ is a binary label.

forall $y_i = 1$ s.t. $(h, r) \in KG$

Note

AllvsAll extends KvsAll via none existing (h,r). Hence, it adds data points that are labelled without 1s, only with 0s.

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idxes

[dictionary] string representation of an entity to its integer id

relation_idxes

[dictionary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

`collate_fn = None`

`target_dim`

`__len__()`

`__getitem__(idx)`

`class dicee.dataset_classes.OnevsSample (train_set: numpy.ndarray, num_entities, num_relations, neg_sample_ratio: int = None, label_smoothing_rate: float = 0.0)`

Bases: `torch.utils.data.Dataset`

A custom PyTorch Dataset class for knowledge graph embeddings, which includes both positive and negative sampling for a given dataset for multi-class classification problem..

Parameters

- **train_set** (*np.ndarray*) – A numpy array containing triples of knowledge graph data. Each triple consists of (head_entity, relation, tail_entity).
- **num_entities** (*int*) – The number of unique entities in the knowledge graph.
- **num_relations** (*int*) – The number of unique relations in the knowledge graph.
- **neg_sample_ratio** (*int, optional*) – The number of negative samples to be generated per positive sample. Must be a positive integer and less than num_entities.
- **label_smoothing_rate** (*float, optional*) – A label smoothing rate to apply to the positive and negative labels. Defaults to 0.0.

train_data

The input data converted into a PyTorch tensor.

Type

`torch.Tensor`

num_entities

Number of entities in the dataset.

Type

`int`

num_relations

Number of relations in the dataset.

Type

`int`

neg_sample_ratio

Ratio of negative samples to be drawn for each positive sample.

Type

`int`

label_smoothing_rate

The smoothing factor applied to the labels.

Type

`torch.Tensor`

collate_fn

A function that can be used to collate data samples into batches (set to None by default).

Type

function, optional

train_data

num_entities

num_relations

neg_sample_ratio

label_smoothing_rate

collate_fn = None

__len__()

Returns the number of samples in the dataset.

__getitem__(idx)

Retrieves a single data sample from the dataset at the given index.

Parameters

idx (*int*) – The index of the sample to retrieve.

Returns

A tuple consisting of:

- **x** (torch.Tensor): The head and relation part of the triple.
- **y_idx** (torch.Tensor): The concatenated indices of the true object (tail entity) and the indices of the negative samples.
- **y_vec** (torch.Tensor): A vector containing the labels for the positive and negative samples, with label smoothing applied.

Return type

tuple

```
class dicee.dataset_classes.KvsSampleDataset (train_set_idx: numpy.ndarray, entity_idxes,
relation_idxes, form, store=None, neg_ratio=None, label_smoothing_rate: float = 0.0)
```

Bases: torch.utils.data.Dataset

KvsSample a Dataset:

D:= {(x,y)_i}_i ^N, where

. x:(h,r) is a unique h in E and a relation r in R and . y in [0,1]^{**|E|**} is a binary label.

forall y_i =1 s.t. (h r E_i) in KG

At each mini-batch construction, we subsample(y), hence n

|new_y| << |E| new_y contains all 1's if sum(y)< neg_sample ratio new_y contains

train_set_idx

Indexed triples for the training.

entity_idxes

mapping.

```

    relation_idx
    mapping.

    form
    ?

    store
    ?

    label_smoothing_rate
    ?

    torch.utils.data.Dataset

```

```

train_data = None

train_target = None

neg_ratio

num_entities

label_smoothing_rate

collate_fn = None

max_num_of_classes

__len__()

__getitem__(idx)

```

```

class dicee.dataset_classes.NegSampleDataset (train_set: numpy.ndarray, num_entities: int,
    num_relations: int, neg_sample_ratio: int = 1)

```

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

```

neg_sample_ratio

train_set

length

num_entities

num_relations

```

```

__len__()

__getitem__(idx)

class dicee.dataset_classes.TriplePredictionDataset (train_set: numpy.ndarray,
    num_entities: int, num_relations: int, neg_sample_ratio: int = 1, label_smoothing_rate: float = 0.0)
Bases: torch.utils.data.Dataset
    Triple Dataset
        D:= {(x)_i}_i ^N, where
            . x:(h,r, t) in KG is a unique h in E and a relation r in R and . collect_fn => Generates
            negative triples
        collect_fn:
orall (h,r,t) in G obtain, create negative triples {(h,r,x),(r,t),(h,m,t)}
        y:labels are represented in torch.float16

    train_set_idx
        Indexed triples for the training.

    entity_idxxs
        mapping.

    relation_idxxs
        mapping.

    form
        ?

    store
        ?

    label_smoothing_rate

    collate_fn: batch:List[torch.IntTensor] Returns —— torch.utils.data.Dataset

label_smoothing_rate

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(idx)

collate_fn (batch: List[torch.Tensor])

class dicee.dataset_classes.CVDDataModule (train_set_idx: numpy.ndarray, num_entities,
    num_relations, neg_sample_ratio, batch_size, num_workers)
Bases: pytorch_lightning.LightningDataModule
    Create a Dataset for cross validation

```

Parameters

- **train_set_idx** – Indexed triples for the training.
- **num_entities** – entity to index mapping.
- **num_relations** – relation to index mapping.
- **batch_size** – int
- **form** – ?
- **num_workers** – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

?

train_set_idx

num_entities

num_relations

neg_sample_ratio

batch_size

num_workers

train_dataloader() → torch.utils.data.DataLoader

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `fit()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

setup(*args, **kwargs)

Called at the beginning of fit (train + validate), validate, test, or predict. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

stage – either 'fit', 'validate', 'test', or 'predict'

Example:

```
class LitModel(...):
    def __init__(self):
        self.l1 = None

    def prepare_data(self):
        download_data()
        tokenize()

        # don't do this
        self.something = else

    def setup(self, stage):
        data = load_data(...)
        self.l1 = nn.Linear(28, data.num_classes)
```

transfer_batch_to_device(*args, **kwargs)

Override this hook if your `DataLoader` returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- `torch.Tensor` or anything that implements `.to(...)`
- `list`
- `dict`
- `tuple`

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, ...).

Note

This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use `self.trainer.training/testing/validating/predicting` so that you can add different logic as per your requirement.

Parameters

- **batch** – A batch of data that needs to be transferred to a new device.

- **device** – The target device as defined in PyTorch.
- **dataloader_idx** – The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_idx)
    return batch
```

➡ See also

- `move_data_to_device()`
- `apply_to_collection()`

`prepare_data(*args, **kwargs)`

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

⚠ Warning

DO NOT set state to the model (use `setup` instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

    # bad
    self.split = data_split
    self.some_state = some_other_state()
```

In a distributed environment, `prepare_data` can be called in two ways (using `prepare_data_per_node`)

1. Once per node. This is the default and is only called on `LOCAL_RANK=0`.
2. Once in total. Only called on `GLOBAL_RANK=0`.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True

# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

dicee.eval_static_funcs

Functions

```
evaluate_link_prediction_performance(→
Dict)
evaluate_link_prediction_performance_with_
evaluate_link_prediction_performance_with_
evaluate_link_prediction_performance_with_
...)
evaluate_lp_bpe_k_vs_all(model,      triples[,
er_vocab, ...])
```

Module Contents

```
dicee.eval_static_funcs.evaluate_link_prediction_performance(
    model: dicee.knowledge_graph_embeddings.KGE, triples, er_vocab: Dict[Tuple, List],
    re_vocab: Dict[Tuple, List]) → Dict
```

Parameters

- **model**
- **triples**
- **er_vocab**

- **re_vocab**

```
dicee.eval_static_funcs.evaluate_link_prediction_performance_with_reciprocals(
    model: dicee.knowledge_graph_embeddings.KGE, triples, er_vocab: Dict[Tuple, List])
```

```
dicee.eval_static_funcs.evaluate_link_prediction_performance_with_bpe_reciprocals(
    model: dicee.knowledge_graph_embeddings.KGE, within_entities: List[str], triples: List[List[str]],
    er_vocab: Dict[Tuple, List])
```

```
dicee.eval_static_funcs.evaluate_link_prediction_performance_with_bpe(
    model: dicee.knowledge_graph_embeddings.KGE, within_entities: List[str], triples: List[Tuple[str]],
    er_vocab: Dict[Tuple, List], re_vocab: Dict[Tuple, List])
```

Parameters

- **model**
- **triples**
- **within_entities**
- **er_vocab**
- **re_vocab**

```
dicee.eval_static_funcs.evaluate_lp_bpe_k_vs_all(model, triples: List[List[str]],
    er_vocab=None, batch_size=None, func_triple_to_bpe_representation: Callable = None,
    str_to_bpe_entity_to_idx=None)
```

dicee.evaluator

Classes

<i>Evaluator</i>	Evaluator class to evaluate KGE models in various downstream tasks
------------------	--------------------------------------------------------------------

Module Contents

```
class dicee.evaluator.Evaluator(args, is_continual_training=None)
```

Evaluator class to evaluate KGE models in various downstream tasks

Arguments

```
re_vocab = None
```

```
er_vocab = None
```

```
ee_vocab = None
```

```
func_triple_to_bpe_representation = None
```

```
is_continual_training
```

```
num_entities = None
```

```
num_relations = None
```

```
args
```

report

during_training = False

vocab_preparation (*dataset*) → None

A function to wait future objects for the attributes of executor

Return type

None

eval (*dataset: dicee.knowledge_graph.KG, trained_model, form_of_labelling, during_training=False*)
→ None

eval_rank_of_head_and_tail_entity (*, *train_set, valid_set=None, test_set=None, trained_model*)

eval_rank_of_head_and_tail_byte_pair_encoded_entity (*, *train_set=None, valid_set=None, test_set=None, ordered_bpe_entities, trained_model*)

eval_with_byte (*, *raw_train_set, raw_valid_set=None, raw_test_set=None, trained_model, form_of_labelling*) → None

Evaluate model after reciprocal triples are added

eval_with_bpe_vs_all (*, *raw_train_set, raw_valid_set=None, raw_test_set=None, trained_model, form_of_labelling*) → None

Evaluate model after reciprocal triples are added

eval_with_vs_all (*, *train_set, valid_set=None, test_set=None, trained_model, form_of_labelling*)
→ None

Evaluate model after reciprocal triples are added

evaluate_lp_k_vs_all (*model, triple_idx, info=None, form_of_labelling=None*)

Filtered link prediction evaluation. :param model: :param triple_idx: test triples :param info: :param form_of_labelling: :return:

evaluate_lp_with_byte (*model, triples: List[List[str]], info=None*)

evaluate_lp_bpe_k_vs_all (*model, triples: List[List[str]], info=None, form_of_labelling=None*)

Parameters

- **model**
- **triples** (*List of lists*)
- **info**
- **form_of_labelling**

evaluate_lp (*model, triple_idx, info: str*)

dummy_eval (*trained_model, form_of_labelling: str*)

eval_with_data (*dataset, trained_model, triple_idx: numpy.ndarray, form_of_labelling: str*)

dicee.executor

Classes

<i>Execute</i>	A class for Training, Retraining and Evaluation a model.
<i>ContinuousExecute</i>	A subclass of Execute Class for retraining

Module Contents

class dicee.executer.**Execute** (*args*, *continuous_training=False*)

A class for Training, Retraining and Evaluation a model.

- (1) Loading & Preprocessing & Serializing input data.
- (2) Training & Validation & Testing
- (3) Storing all necessary info

args

is_continual_training

trainer = None

trained_model = None

knowledge_graph = None

report

evaluator = None

start_time = None

setup_executor() → None

dept_read_preprocess_index_serialize_data() → None

Read & Preprocess & Index & Serialize Input Data

- (1) Read or load the data from disk into memory.
- (2) Store the statistics of the data.

Parameter

rtype

None

save_trained_model() → None

Save a knowledge graph embedding model

- (1) Send model to eval mode and cpu.
- (2) Store the memory footprint of the model.
- (3) Save the model into disk.
- (4) Update the stats of KG again ?

Parameter

rtype

None

end (*form_of_labelling: str*) → dict

End training

- (1) Store trained model.
- (2) Report runtimes.
- (3) Eval model if required.

Parameter

rtype

A dict containing information about the training and/or evaluation

write_report () → None

Report training related information in a report.json file

start () → dict

Start training

(1) Loading the Data # (2) Create an evaluator object. # (3) Create a trainer object. # (4) Start the training

Parameter

rtype

A dict containing information about the training and/or evaluation

class `dicee.executer.ContinuousExecute` (*args*)

Bases: *Execute*

A subclass of Execute Class for retraining

- (1) Loading & Preprocessing & Serializing input data.
- (2) Training & Validation & Testing
- (3) Storing all necessary info

During the continual learning we can only modify * **num_epochs** * parameter. Trained model stored in the same folder as the seed model for the training. Trained model is noted with the current time.

continual_start () → dict

Start Continual Training

- (1) Initialize training.
- (2) Start continual training.
- (3) Save trained model.

Parameter

rtype

A dict containing information about the training and/or evaluation

dicee.knowledge_graph

Classes

KG	Knowledge Graph
----	-----------------

Module Contents

```
class dicee.knowledge_graph.KG(dataset_dir: str = None, byte_pair_encoding: bool = False,  
padding: bool = False, add_noise_rate: float = None, sparql_endpoint: str = None,  
path_single_kg: str = None, path_for_deserialization: str = None, add_reciprocal: bool = None,  
eval_model: str = None, read_only_few: int = None, sample_triples_ratio: float = None,  
path_for_serialization: str = None, entity_to_idx=None, relation_to_idx=None, backend=None,  
training_technique: str = None, separator: str = None)
```

Knowledge Graph

dataset_dir

sparql_endpoint

path_single_kg

byte_pair_encoding

ordered_shaped_bpe_tokens = None

add_noise_rate

num_entities = None

num_relations = None

path_for_deserialization

add_reciprocal

eval_model

read_only_few

sample_triples_ratio

path_for_serialization

entity_to_idx

relation_to_idx

backend

training_technique

idx_entity_to_bpe_shaped

enc

num_tokens

```

num_bpe_entities = None

padding

dummy_id

max_length_subword_tokens = None

train_set_target = None

target_dim = None

train_target_indices = None

ordered_bpe_entities = None

separator

description_of_input = None

describe() → None

property entities_str: List

property relations_str: List

exists(h: str, r: str, t: str)

__iter__()

__len__()

func_triple_to_bpe_representation(triple: List[str])

```

dicee.knowledge_graph_embeddings

Classes

<i>KGE</i>	Knowledge Graph Embedding Class for interactive usage of pre-trained models
------------	-----------------------------------------------------------------------------

Module Contents

```

class dicee.knowledge_graph_embeddings.KGE (path=None, url=None, construct_ensemble=False,
      model_name=None)
    Bases: dicee.abstracts.BaseInteractiveKGE
    Knowledge Graph Embedding Class for interactive usage of pre-trained models
    __str__()
    to(device: str) → None
    get_transductive_entity_embeddings(indices: torch.LongTensor | List[str], as_pytorch=False,
      as_numpy=False, as_list=True) → torch.FloatTensor | numpy.ndarray | List[float]
    create_vector_database(collection_name: str, distance: str, location: str = 'localhost',
      port: int = 6333)

```

generate (*h=""*, *r=""*)

eval_lp_performance (*dataset=List[Tuple[str, str, str]]*, *filtered=True*)

predict_missing_head_entity (*relation: List[str] | str*, *tail_entity: List[str] | str*, *within=None*)
→ Tuple

Given a relation and a tail entity, return top k ranked head entity.

$\text{argmax}_{\{e \in E\}} f(e, r, t)$, where $r \in R$, $t \in E$.

Parameter

relation: Union[List[str], str]

String representation of selected relations.

tail_entity: Union[List[str], str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_relations (*head_entity: List[str] | str*, *tail_entity: List[str] | str*, *within=None*)
→ Tuple

Given a head entity and a tail entity, return top k ranked relations.

$\text{argmax}_{\{r \in R\}} f(h, r, t)$, where $h, t \in E$.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_tail_entity (*head_entity: List[str] | str*, *relation: List[str] | str*,
within: List[str] = None) → torch.FloatTensor

Given a head entity and a relation, return top k ranked entities

$\text{argmax}_{\{e \in E\}} f(h, r, e)$, where $h \in E$ and $r \in R$.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

predict (*, h: List[str] | str = None, r: List[str] | str = None, t: List[str] | str = None, within=None, logits=True) → torch.FloatTensor

Parameters

- **logits**
- **h**
- **r**
- **t**
- **within**

predict_topk (*, h: str | List[str] = None, r: str | List[str] = None, t: str | List[str] = None, topk: int = 10, within: List[str] = None)

Predict missing item in a given triple.

Parameter

head_entity: Union[str, List[str]]

String representation of selected entities.

relation: Union[str, List[str]]

String representation of selected relations.

tail_entity: Union[str, List[str]]

String representation of selected entities.

k: int

Highest ranked k item.

Returns: Tuple

Highest K scores and items

triple_score (h: List[str] | str = None, r: List[str] | str = None, t: List[str] | str = None, logits=False) → torch.FloatTensor

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

logits: bool

If logits is True, unnormalized score returned

Returns: Tuple

pytorch tensor of triple score

t_norm (*tens_1: torch.Tensor, tens_2: torch.Tensor, tnorm: str = 'min'*) → torch.Tensor

tensor_t_norm (*subquery_scores: torch.FloatTensor, tnorm: str = 'min'*) → torch.FloatTensor

Compute T-norm over $[0,1]^{n \times d}$ where n denotes the number of hops and d denotes number of entities

t_conorm (*tens_1: torch.Tensor, tens_2: torch.Tensor, tconorm: str = 'min'*) → torch.Tensor

negnorm (*tens_1: torch.Tensor, lambda_: float, neg_norm: str = 'standard'*) → torch.Tensor

return_multi_hop_query_results (*aggregated_query_for_all_entities, k: int, only_scores*)

single_hop_query_answering (*query: tuple, only_scores: bool = True, k: int = None*)

answer_multi_hop_query (*query_type: str = None, query: Tuple[str | Tuple[str, str], Ellipsis] = None, queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, tnorm: str = 'prod', neg_norm: str = 'standard', lambda_: float = 0.0, k: int = 10, only_scores=False*) → List[Tuple[str, torch.Tensor]]

@TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a static function

Find an answer set for EPFO queries including negation and disjunction

Parameter

query_type: str The type of the query, e.g., “2p”.

query: Union[str, Tuple[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.

queries: List of Tuple[Union[str, Tuple[str, str]], ...]

tnorm: str The t-norm operator.

neg_norm: str The negation norm.

lambda_: float lambda parameter for sugeno and yager negation norms

k: int The top-k substitutions for intermediate variables.

returns

- List[Tuple[str, torch.Tensor]]

- Entities and corresponding scores sorted in the descening order of scores

find_missing_triples (*confidence: float, entities: List[str] = None, relations: List[str] = None, topk: int = 10, at_most: int = sys.maxsize*) → Set

Find missing triples

Iterative over a set of entities E and a set of relation R :

orall e in E and orall r in R f(e,r,x)

Return (e,r,x)

otin G and f(e,r,x) > confidence

confidence: float

A threshold for an output of a sigmoid function given a triple.

topk: int

Highest ranked k item to select triples with f(e,r,x) > confidence .

at_most: int

Stop after finding at_most missing triples

{(e,r,x) | f(e,r,x) > confidence land (e,r,x)

otin G

deploy (*share: bool = False, top_k: int = 10*)

train_triples (*h: List[str], r: List[str], t: List[str], labels: List[float], iteration=2, optimizer=None*)

train_k_vs_all (*h, r, iteration=1, lr=0.001*)

Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:

train (*kg, lr=0.1, epoch=10, batch_size=32, neg_sample_ratio=10, num_workers=1*) → None

Retrained a pretrain model on an input KG via negative sampling.

dicee.models

Submodules

dicee.models.base_model

Classes

<i>BaseKGELightning</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>IdentityClass</i>	Base class for all neural network modules.

Module Contents

class dicee.models.base_model.**BaseKGELightning** (*args, **kwargs)

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

training_step_outputs = []

mem_of_model() → Dict

Size of model in MB and number of params

training_step (*batch, batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to ‘manual optimization’ and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches > 1`, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

loss_function (*yhat_batch: torch.FloatTensor, y_batch: torch.FloatTensor*)

Parameters

- **yhat_batch**
- **y_batch**

on_train_epoch_end (**args, **kwargs*)

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the `LightningModule` and access them in this hook:

```
class MyLightningModule(L.LightningModule):
    def __init__(self):
        super().__init__()
        self.training_step_outputs = []

    def training_step(self):
        loss = ...
        self.training_step_outputs.append(loss)
        return loss

    def on_train_epoch_end(self):
```

(continues on next page)

(continued from previous page)

```
# do something with all training_step outputs, for example:
epoch_mean = torch.stack(self.training_step_outputs).mean()
self.log("training_epoch_mean", epoch_mean)
# free up the memory
self.training_step_outputs.clear()
```

test_epoch_end(*outputs: List[Any]*)

test_dataloader() → None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `test()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Note

If you don't need a test dataset and a `test_step()`, you don't need to implement this method.

val_dataloader() → None

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs** to a positive integer.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `fit()`
- `validate()`

- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Note

If you don't need a validation dataset and a `validation_step()`, you don't need to implement this method.

`predict_dataloader()` → None

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `predict()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Returns

A `torch.utils.data.DataLoader` or a sequence of them specifying prediction samples.

`train_dataloader()` → None

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **`:param-ref:~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs``** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `fit()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

configure_optimizers (*parameters=None*)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- **Single optimizer.**
- **List or Tuple** of optimizers.
- **Two lists** - The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple `lr_scheduler_config`).
- **Dictionary**, with an "optimizer" key, and (optionally) a "lr_scheduler" key whose value is a single LR scheduler or `lr_scheduler_config`.
- **None** - Fit will run without any optimizer.

The `lr_scheduler_config` is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
    "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
    "interval": "epoch",
    # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
    "frequency": 1,
    # Metric to to monitor for schedulers like `ReduceLROnPlateau`
    "monitor": "val_loss",
    # If set to `True`, will enforce that the value specified 'monitor'
    # is available when the scheduler is updated, thus stopping
    # training if not found. If set to `False`, it will only produce a warning
    "strict": True,
    # If using the `LearningRateMonitor` callback to monitor the
    # learning rate progress, this keyword can be used to specify
    # a custom logged name
    "name": None,
}
```

When there are schedulers in which the `.step()` method is conditioned on a value, such as the `torch.optim.lr_scheduler.ReduceLROnPlateau` scheduler, Lightning requires that the `lr_scheduler_config` contains the keyword "monitor" set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using `self.log('metric_to_track', metric_val)` in your `LightningModule`.

Note

Some things to know:

- Lightning calls `.backward()` and `.step()` automatically in case of automatic optimization.
- If a learning rate scheduler is specified in `configure_optimizers()` with key "interval" (default "epoch") in the scheduler configuration, Lightning will call the scheduler's `.step()` method automatically in case of automatic optimization.
- If you use 16-bit precision (`precision=16`), Lightning will automatically handle the optimizer.
- If you use `torch.optim.LBFGS`, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the `optimizer_step()` hook.

```
class dicee.models.base_model.BaseKGE(args: dict)
```

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training` (*bool*) – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

`kernel_size = None`

`num_of_output_channels = None`

`weight_decay = None`

`loss`

`selected_optimizer = None`

`normalizer_class = None`

`normalize_head_entity_embeddings`

`normalize_relation_embeddings`

`normalize_tail_entity_embeddings`

`hidden_normalizer`

`param_init`

`input_dp_ent_real`

`input_dp_rel_real`

`hidden_dropout`

`loss_history = []`

`byte_pair_encoding`

`max_length_subword_tokens`

`block_size`

forward_byte_pair_encoded_k_vs_all (*x*: *torch.LongTensor*)

Parameters

x (*B* × 2 × *T*)

forward_byte_pair_encoded_triple (*x*: *Tuple*[*torch.LongTensor*, *torch.LongTensor*])

byte pair encoded neural link predictors

Parameters

init_params_with_sanity_checking ()

forward (*x*: *torch.LongTensor* | *Tuple*[*torch.LongTensor*, *torch.LongTensor*],
 y_idx: *torch.LongTensor* = *None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples (*x*: *torch.LongTensor*) → *torch.Tensor*

Parameters

x

forward_k_vs_all (**args*, ***kwargs*)

forward_k_vs_sample (**args*, ***kwargs*)

get_triple_representation (*idx_hrt*)

get_head_relation_representation (*indexed_triple*)

get_sentence_representation (*x*: *torch.LongTensor*)

Parameters

- (**b** (*x* *shape*)
- 3
- **t**)

get_bpe_head_and_relation_representation (*x*: *torch.LongTensor*)
→ *Tuple*[*torch.FloatTensor*, *torch.FloatTensor*]

Parameters

x (*B* × 2 × *T*)

get_embeddings () → *Tuple*[*numpy.ndarray*, *numpy.ndarray*]

class *dicee.models.base_model.IdentityClass* (*args*=*None*)

Bases: *torch.nn.Module*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__ (*x*)

static forward (*x*)

dicee.models.clifford

Classes

<i>Keci</i>	Base class for all neural network modules.
<i>KeciBase</i>	Without learning dimension scaling
<i>DeCaL</i>	Base class for all neural network modules.

Module Contents

class `dicee.models.clifford.Keci` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F
```

(continues on next page)

(continued from previous page)

```
class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp (*hp, rp*)

Compute $\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_{ir_k} - h_{kr_i}) e_i e_k$

σ_{pp} captures the interactions between along p bases For instance, let $p = e_1, e_2, e_3$, we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

 for k in range(i + 1, p):

 results.append($hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i]$)

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., $e_1 e_1, e_1 e_2, e_1 e_3$,

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_qq (*hq, rq*)

Compute $\sigma_{qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_{jr_k} - h_{kr_j}) e_j e_k \sigma_q$ captures the interactions between along q bases For instance, let $q = e_1, e_2, e_3$, we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

```

results = [] for j in range(q - 1):
    for k in range(j + 1, q):
        results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])
sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., e_1e_1 , e_1e_2 , e_1e_3 ,

```

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

```

Then select the triangular matrix without diagonals: e_1e_2 , e_1e_3 , e_2e_3 .

```

compute_sigma_pq(*, hp, hq, rp, rq)
sum_{i=1}^p sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
    for j in range(q):
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
print(sigma_pq.shape)

```

apply_coefficients (hp, hq, rp, rq)
 Multiplying a base vector with its scalar coefficient

clifford_multiplication ($h0, hp, hq, r0, rp, rq$)
 Compute our CL multiplication

$$h = h_0 + \sum_{i=1}^p h_i e_i + \sum_{j=p+1}^{p+q} h_j e_j \quad r = r_0 + \sum_{i=1}^p r_i e_i + \sum_{j=p+1}^{p+q} r_j e_j$$

$$e_i^2 = +1 \text{ for } i \leq p, \quad e_j^2 = -1 \text{ for } p < j \leq p+q, \quad e_i e_j = -e_j e_i \text{ for } i < j$$

$$eq_j$$

$$h r = \sigma_0 + \sigma_p + \sigma_q + \sigma_{pp} + \sigma_q + \sigma_{pq} \text{ where}$$

- (1) $\sigma_0 = h_0 r_0 + \sum_{i=1}^p (h_0 r_i - h_i r_0) e_i - \sum_{j=p+1}^{p+q} (h_j r_j) e_j$
- (2) $\sigma_p = \sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$
- (3) $\sigma_q = \sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$
- (4) $\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k$
- (5) $\sigma_{qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k$
- (6) $\sigma_{pq} = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$

```

construct_cl_multivector(x: torch.FloatTensor, r: int, p: int, q: int)
    → tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]
Construct a batch of multivectors  $Cl_{p,q}(\mathbb{R}^d)$ 

```

Parameter

x : torch.FloatTensor with (n, d) shape

returns

- **a0** (torch.FloatTensor with (n, r) shape)
- **ap** (torch.FloatTensor with (n, r, p) shape)
- **aq** (torch.FloatTensor with (n, r, q) shape)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations \mathbb{R}^d .
- (2) Construct head entity and relation embeddings according to $Cl_{\{p,q\}}(\mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter ——— *x: torch.LongTensor* with (n,2) shape :rtype: torch.FloatTensor with (n, **IEI**) shape

construct_batch_selected_cl_multivector (*x: torch.FloatTensor, r: int, p: int, q: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of batchs multivectors $Cl_{\{p,q\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (*torch.FloatTensor* with (n,k, m) shape)
- **ap** (*torch.FloatTensor* with (n,k, m, p) shape)
- **aq** (*torch.FloatTensor* with (n,k, m, q) shape)

forward_k_vs_sample (*x: torch.LongTensor, target_entity_idx: torch.LongTensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,2) shape

target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.

rtype

torch.FloatTensor with (n, k) shape

score (*h, r, t*)

forward_triples (*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype

torch.FloatTensor with (n) shape

class `dicce.models.clifford.KeciBase` (*args*)

Bases: *Keci*

Without learning dimension scaling

name = 'KeciBase'

```
requires_grad_for_interactions = False
```

```
class dicee.models.clifford.DeCaL(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation_embeddings

p

q

r

re

forward_triples (*x: torch.Tensor*) \rightarrow torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl_pqr (*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) → output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb, list_r_emb, list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^p h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^q (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i)$$

and return:

$$sigma_0 t = \sigma_0 \cdot t_0 = s0 + s1 - s2 s3, s4 \text{ and } s5$$

compute_sigmas_multivect (*list_h_emb, list_r_emb*)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (\text{model the interactions between } e_i \text{ and } e_{i'} \text{ for } 1 \leq i, i' \leq p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{j'} r_j)$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (\text{interactions between } e_i \text{ and } e_j \text{ for } 1 \leq i \leq p \text{ and } p+1 \leq j \leq p+q) \sigma_p r = \sum_{i=1}^p \sum_{r=p+q+1}^{p+q+r} (h_i r_r - h_r r_i)$$

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to $Cl_{\{p,q,r\}}(\mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, **IEI**) shape

apply_coefficients (*h0, hp, hq, hk, r0, rp, rq, rk*)

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (*x: torch.FloatTensor, re: int, p: int, q: int, r: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{\{p,q,r\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor)
- **ap** (torch.FloatTensor)
- **aq** (torch.FloatTensor)
- **ar** (torch.FloatTensor)

compute_sigma_pp (hp, rp)

Compute .. math:

$$\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (x_i y_{i'} - x_{i'} y_i)$$

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):

 results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq (hq, rq)

Compute

$$\sigma_{qq}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) \quad E q.16$$

sigma_{qq} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

 results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_rr (hk, rk)

$$\sigma_{rr}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^p (x_k y_{k'} - x_{k'} y_k)$$

```
compute_sigma_pq(*, hp, hq, rp, rq)
```

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

```
compute_sigma_pr(*, hp, hk, rp, rk)
```

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

```
compute_sigma_qr(*, hq, hk, rq, rk)
```

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

dicee.models.complex

Classes

<i>ConEx</i>	Convolutional ComplEx Knowledge Graph Embeddings
<i>AConEx</i>	Additive Convolutional ComplEx Knowledge Graph Embeddings
<i>Complex</i>	Base class for all neural network modules.

Module Contents

```
class dicee.models.complex.ConEx(args)
```

Bases: *dicee.models.base_model.BaseKGE*

Convolutional ComplEx Knowledge Graph Embeddings

```
name = 'ConEx'
```

```

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                      C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
    Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
    that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
    complex-valued embeddings :return:

forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor

forward_triples (x: torch.Tensor) → torch.FloatTensor

    Parameters
    x

forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

class dicee.models.complex.AConEx (args)
    Bases: dicee.models.base_model.BaseKGE
    Additive Convolutional ComplEx Knowledge Graph Embeddings
    name = 'AConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                      C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
    Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
    that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
    complex-valued embeddings :return:

forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor

forward_triples (x: torch.Tensor) → torch.FloatTensor

    Parameters
    x

forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

```

```
class dicee.models.complex.Complex(args)
    Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`name = 'Complex'`

`static score (head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor,
tail_ent_emb: torch.FloatTensor)`

`static k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor,
emb_E: torch.FloatTensor)`

Parameters

- `emb_h`
- `emb_r`
- `emb_E`

`forward_k_vs_all (x: torch.LongTensor) → torch.FloatTensor`

`forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)`

dicee.models.dualE

Classes

<i>DualE</i>	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)
--------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Module Contents

class dicee.models.dualE.**DualE**(args)

Bases: *dicee.models.base_model.BaseKGE*

Dual Quaternion Knowledge Graph Embeddings (<https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657>)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score(*e_1_h, e_2_h, e_3_h, e_4_h, e_5_h, e_6_h, e_7_h, e_8_h, e_1_t, e_2_t, e_3_t, e_4_t, e_5_t, e_6_t, e_7_t, e_8_t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8*) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples(*idx_triple: torch.tensor*) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_k_vs_all(*x*)

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

$\mathbf{T}(x: \text{torch.tensor}) \rightarrow \text{torch.tensor}$

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

dicee.models.ensemble

Classes

EnsembleKGE

Module Contents

```
class dicee.models.ensemble.EnsembleKGE(seed_model)
```

```
    models = []
```

```
    optimizers = []
```

```
    loss_history = []
```

```
    name
```

```
    train_mode = True
```

```
    named_children()
```

```
    property example_input_array
```

```
    parameters()
```

```
    modules()
```

```
    __iter__()
```

```
    __len__()
```

```
    eval()
```

```
    to(device)
```

```
    mem_of_model()
```

```
    __call__(x_batch)
```

```
    step()
```

```
    __str__()
```

dicее.models.function_space

Classes

<i>FMult</i>	Learning Knowledge Neural Graphs
<i>GFMult</i>	Learning Knowledge Neural Graphs
<i>FMult2</i>	Learning Knowledge Neural Graphs
<i>LFMult1</i>	Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
<i>LFMult</i>	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:

Module Contents

```
class dicее.models.function_space.FMult (args)
    Bases: dicее.models.base_model.BaseKGE
    Learning Knowledge Neural Graphs
    name = 'FMult'
    entity_embeddings
    relation_embeddings
    k
    num_sample = 50
    gamma
    roots
    weights
    compute_func (weights: torch.FloatTensor, x) → torch.FloatTensor
    chain_func (weights, x: torch.FloatTensor)
    forward_triples (idx_triple: torch.Tensor) → torch.Tensor
```

Parameters

x

```
class dicее.models.function_space.GFMult (args)
    Bases: dicее.models.base_model.BaseKGE
    Learning Knowledge Neural Graphs
    name = 'GFMult'
    entity_embeddings
    relation_embeddings
    k
    num_sample = 250
```

```

roots

weights

compute_func(weights: torch.FloatTensor, x) → torch.FloatTensor

chain_func(weights, x: torch.FloatTensor)

forward_triples(idx_triple: torch.Tensor) → torch.Tensor

```

Parameters

x

```

class dicee.models.function_space.FMult2(args)
    Bases: dicee.models.base_model.BaseKGE
    Learning Knowledge Neural Graphs
    name = 'FMult2'
    n_layers = 3
    k
    n = 50
    score_func = 'compositional'
    discrete_points
    entity_embeddings
    relation_embeddings
    build_func(Vec)
    build_chain_funcs(list_Vec)
    compute_func(W, b, x) → torch.FloatTensor
    function(list_W, list_b)
    trapezoid(list_W, list_b)
    forward_triples(idx_triple: torch.Tensor) → torch.Tensor

```

Parameters

x

```

class dicee.models.function_space.LFMult1(args)
    Bases: dicee.models.base_model.BaseKGE

    Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
 $f(x) = \sum_{k=0}^{k=d-1} w_k e^{kix}$ . and use the three differents scoring function as in the paper to evaluate
    the score

    name = 'LFMult1'

    entity_embeddings

    relation_embeddings

```


forward_triples (*idx_triple*)

Parameters

x

tri_score (*h, r, t*)

vtp_score (*h, r, t*)

class dicee.models.function_space.**LFMult** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: $f(x) = \sum_{i=0}^{d-1} a_i x^i$ and use the three differents scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

name = 'LFMult'

entity_embeddings

relation_embeddings

degree

m

x_values

forward_triples (*idx_triple*)

Parameters

x

construct_multi_coeff (*x*)

poly_NN (*x, coefh, coefr, coeft*)

Constructing a 2 layers NN to represent the embeddings. $h = \text{sigma}(wh^T x + bh)$, $r = \text{sigma}(wr^T x + br)$, $t = \text{sigma}(wt^T x + bt)$

linear (*x, w, b*)

scalar_batch_NN (*a, b, c*)

element wise multiplication between a,b and c: Inputs : a, b, c ==> torch.tensor of size batch_size x m x d Output : a tensor of size batch_size x d

tri_score (*coeff_h, coeff_r, coeff_t*)

this part implement the trilinear scoring techniques:

$\text{score}(h,r,t) = \int_0^1 h(x)r(x)t(x) dx = \sum_{i,j,k=0}^{d-1} \text{dfrac}\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$

1. generate the range for i,j and k from [0 d-1]
2. perform $\text{dfrac}\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$ in parallel for every batch
3. take the sum over each batch

vtp_score (*h, r, t*)

this part implement the vector triple product scoring techniques:

$\text{score}(h,r,t) = \int_0^1 h(x)r(x)t(x) dx = \sum_{i,j,k=0}^{d-1} \text{dfrac}\{a_i*c_j*b_k - b_i*c_j*a_k\}\{(1+(i+j)\%d)(1+k)\}$

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum
4. take the sum over each batch

comp_func (*h, r, t*)

this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial (*coeff, x, degree*)

This function takes a matrix tensor of coefficients (*coeff*), a tensor vector of points *x* and range of integer [0,1,...d] and return a vector tensor ($\text{coeff}[0][0] + \text{coeff}[0][1]x + \dots + \text{coeff}[0][d]x^d$,

$\text{coeff}[1][0] + \text{coeff}[1][1]x + \dots + \text{coeff}[1][d]x^d$)

pop (*coeff, x, degree*)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (*coeff*), a matrix tensor of points *x* and range of integer [0,1,...d]

and return a tensor ($\text{coeff}[0][0] + \text{coeff}[0][1]x + \dots + \text{coeff}[0][d]x^d$,

$\text{coeff}[1][0] + \text{coeff}[1][1]x + \dots + \text{coeff}[1][d]x^d$)

dicee.models.octonion

Classes

<i>OMult</i>	Base class for all neural network modules.
<i>ConvO</i>	Base class for all neural network modules.
<i>AConvO</i>	Additive Convolutional Octonion Knowledge Graph Em-beddings

Functions

<i>octonion_mul</i> (*, <i>O_1</i> , <i>O_2</i>)
<i>octonion_mul_norm</i> (*, <i>O_1</i> , <i>O_2</i>)

Module Contents

`dicee.models.octonion.octonion_mul(*, O_1, O_2)`

`dicee.models.octonion.octonion_mul_norm(*, O_1, O_2)`

class `dicee.models.octonion.OMult` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'OMult'

static octonion_normalizer (*emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4, emb_rel_e5, emb_rel_e6, emb_rel_e7*)

score (*head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor, tail_ent_emb: torch.FloatTensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

forward_k_vs_all (*x*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., $[score(h,r,x)|x \text{ in Entities}] \Rightarrow [0.0,0.1,...,0.8]$, shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class `dicee.models.octonion.ConvO` (*args: dict*)

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()

```

(continues on next page)

(continued from previous page)

```
self.conv1 = nn.Conv2d(1, 20, 5)
self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer (*emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4, emb_rel_e5, emb_rel_e6, emb_rel_e7*)

residual_convolution (*O_1, O_2*)

forward_triples (*x: torch.Tensor*) → torch.Tensor

Parameters

x

forward_k_vs_all (*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch, Entities)

class dicee.models.octonion.**AConvO** (*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Octonion Knowledge Graph Embeddings

name = 'AConvO'

conv2d

```

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                           emb_rel_e5, emb_rel_e6, emb_rel_e7)

residual_convolution(O_1, O_2)

forward_triples(x: torch.Tensor) → torch.Tensor

    Parameters
    x

forward_k_vs_all(x: torch.Tensor)
    Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
    [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
    Entities)

```

dicee.models.pykeen_models

Classes

<i>PykeenKGE</i>	A class for using knowledge graph embedding models implemented in Pykeen
------------------	--------------------------------------------------------------------------

Module Contents

```

class dicee.models.pykeen_models.PykeenKGE(args: dict)
    Bases: dicee.models.base_model.BaseKGE
    A class for using knowledge graph embedding models implemented in Pykeen
    Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Py-
    keen_HolE:

    model_kwargs

    name

    model

    loss_history = []

    args

    entity_embeddings = None

    relation_embeddings = None

```

```

forward_k_vs_all (x: torch.LongTensor)
    # => Explicit version by this we can apply bn and dropout

    # (1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r =
    self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:
        h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
        self.last_dim)

    # (3) Reshape all entities. if self.last_dim > 0:
        t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

    else:
        t = self.entity_embeddings.weight

    # (4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r,
    all_entities=t, slice_size=1)

forward_triples (x: torch.LongTensor) → torch.FloatTensor
    # => Explicit version by this we can apply bn and dropout

    # (1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t =
    self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:
        h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
        self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

    # (3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)

```

dicee.models.quaternion

Classes

<i>QMult</i>	Base class for all neural network modules.
<i>ConvQ</i>	Convolutional Quaternion Knowledge Graph Embeddings
<i>ACConvQ</i>	Additive Convolutional Quaternion Knowledge Graph Embeddings

Functions

```
quaternion_mul_with_unit_norm(*, Q_1, Q_2)
```

Module Contents

```
dicee.models.quaternion.quaternion_mul_with_unit_norm(*, Q_1, Q_2)
```

```
class dicee.models.quaternion.QMult (args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'QMult'

explicit = True

quaternion_multiplication_followed_by_inner_product (*h, r, t*)

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer (*x: torch.FloatTensor*) \rightarrow torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters

x – The vector.

Returns

The normalized vector.

score (*head_ent_emb*: torch.FloatTensor, *rel_ent_emb*: torch.FloatTensor,
tail_ent_emb: torch.FloatTensor)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

Parameters

- *bpe_head_ent_emb*
- *bpe_rel_ent_emb*
- *E*

forward_k_vs_all (*x*)

Parameters

x

forward_k_vs_sample (*x*, *target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e.,
[score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **|Entities|**) Given a batch of head entities and
relations => shape (size of batch,| Entities|)

class dicee.models.quaternion.ConvQ (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution (*Q_1*, *Q_2*)

forward_triples (*indexed_triple*: torch.Tensor) → torch.Tensor

Parameters

x

forward_k_vs_all (*x*: torch.Tensor)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
[0.0,0.1,...,0.8], shape=> (1, **|Entities|**) Given a batch of head entities and relations => shape (size of batch,|
Entities|)


```

class dicee.models.quaternion.AConvQ(args)
    Bases: dicee.models.base_model.BaseKGE
    Additive Convolutional Quaternion Knowledge Graph Embeddings
    name = 'AConvQ'
    entity_embeddings
    relation_embeddings
    conv2d
    fc_num_input
    fc1
    bn_conv1
    bn_conv2
    feature_map_dropout
    residual_convolution(Q_1, Q_2)
    forward_triples(indexed_triple: torch.Tensor) → torch.Tensor

    Parameters
    x
    forward_k_vs_all(x: torch.Tensor)
        Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
        [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
        Entities)

```

dicee.models.real

Classes

<i>DistMult</i>	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
<i>TransE</i>	Translating Embeddings for Modeling
<i>Shallom</i>	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
<i>Pyke</i>	A Physical Embedding Model for Knowledge Graphs

Module Contents

```

class dicee.models.real.DistMult(args)
    Bases: dicee.models.base_model.BaseKGE
    Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

    name = 'DistMult'

```

k_vs_all_score (*emb_h*: torch.FloatTensor, *emb_r*: torch.FloatTensor, *emb_E*: torch.FloatTensor)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all (*x*: torch.LongTensor)

forward_k_vs_sample (*x*: torch.LongTensor, *target_entity_idx*: torch.LongTensor)

score (*h*, *r*, *t*)

class dicee.models.real.**TransE** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Translating Embeddings for Modeling Multi-relational Data <https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf>

name = 'TransE'

margin = 4

score (*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_k_vs_all (*x*: torch.Tensor) → torch.FloatTensor

class dicee.models.real.**Shallom** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

A shallow neural model for relation prediction (<https://arxiv.org/abs/2101.09090>)

name = 'Shallom'

shallom

get_embeddings () → Tuple[numpy.ndarray, None]

forward_k_vs_all (*x*) → torch.FloatTensor

forward_triples (*x*) → torch.FloatTensor

Parameters

x

Returns

class dicee.models.real.**Pyke** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

A Physical Embedding Model for Knowledge Graphs

name = 'Pyke'

dist_func

margin = 1.0

forward_triples (*x*: torch.LongTensor)

Parameters

x

dicee.models.static_funcs

Functions

```
quaternion_mul(→ Tuple[torch.Tensor, torch.Tensor, ...])
```

Module Contents

```
dicee.models.static_funcs.quaternion_mul(*, Q_1, Q_2)
→ Tuple[torch.Tensor, torch.Tensor, torch.Tensor]
Perform quaternion multiplication :param Q_1: :param Q_2: :return:
```

dicee.models.transformers

Full definition of a GPT Language Model, all of it in this single file. References: 1) the official GPT-2 TensorFlow implementation released by OpenAI: <https://github.com/openai/gpt-2/blob/master/src/model.py> 2) huggingface/transformers PyTorch implementation: https://github.com/huggingface/transformers/blob/main/src/transformers/models/gpt2/modeling_gpt2.py

Classes

<i>ByteE</i>	Base class for all neural network modules.
<i>LayerNorm</i>	LayerNorm but with an optional bias. PyTorch doesn't support simply bias=False
<i>CausalSelfAttention</i>	Base class for all neural network modules.
<i>MLP</i>	Base class for all neural network modules.
<i>Block</i>	Base class for all neural network modules.
<i>GPTConfig</i>	
<i>GPT</i>	Base class for all neural network modules.

Module Contents

```
class dicee.models.transformers.ByteE(*args, **kwargs)
```

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

```
def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Byte'

config

temperature = 0.5

topk = 2

transformer

lm_head

loss_function (*yhat_batch, y_batch*)

Parameters

- **yhat_batch**
- **y_batch**

forward (*x: torch.LongTensor*)

Parameters

x (*B by T tensor*)

generate (*idx, max_new_tokens, temperature=1.0, top_k=None*)

Take a conditioning sequence of indices `idx` (LongTensor of shape (b,t)) and complete the sequence `max_new_tokens` times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in `model.eval()` mode of operation for this.

training_step (*batch, batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key `'loss'` in the case of automatic optimization.
- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches > 1`, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

```
class dicee.models.transformers.LayerNorm(ndim, bias)
```

Bases: `torch.nn.Module`

LayerNorm but with an optional bias. PyTorch doesn't support simply `bias=False`

weight

bias

forward (*input*)

```
class dicee.models.transformers.CausalSelfAttention(config)
```

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training` (*bool*) – Boolean represents whether this module is in training or evaluation mode.

`c_attn`

`c_proj`

`attn_dropout`

`resid_dropout`

`n_head`

`n_embd`

`dropout`

`flash`

`forward` (*x*)

```
class dicee.models.transformers.MLP(config)
```

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

c_fc

gelu

c_proj

dropout

forward (*x*)

class `dicee.models.transformers.Block` (*config*)

Bases: `torch.nn.Module`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

ln_1

attn

ln_2

mlp

forward (*x*)

```
class dicee.models.transformers.GPTConfig
```

```
    block_size: int = 1024
```

```
    vocab_size: int = 50304
```

```
    n_layer: int = 12
```

```
    n_head: int = 12
```

```
    n_embd: int = 768
```

```
    dropout: float = 0.0
```

```
    bias: bool = False
```

```
class dicee.models.transformers.GPT(config)
```

```
    Bases: torch.nn.Module
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
```

(continues on next page)

(continued from previous page)

```
def __init__(self) -> None:
    super().__init__()
    self.conv1 = nn.Conv2d(1, 20, 5)
    self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

config

transformer

lm_head

get_num_params (*non_embedding=True*)

Return the number of parameters in the model. For non-embedding count (default), the position embeddings get subtracted. The token embeddings would too, except due to the parameter sharing these params are actually used as weights in the final layer, so we include them.

forward (*idx, targets=None*)

crop_block_size (*block_size*)

classmethod from_pretrained (*model_type, override_args=None*)

configure_optimizers (*weight_decay, learning_rate, betas, device_type*)

estimate_mfu (*fwdbwd_per_iter, dt*)

estimate model flops utilization (MFU) in units of A100 bfloat16 peak FLOPS

Classes

<i>BaseKGELightning</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>IdentityClass</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>DistMult</i>	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
<i>TransE</i>	Translating Embeddings for Modeling

continues on next page

Table 1 – continued from previous page

<i>Shallom</i>	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
<i>Pyke</i>	A Physical Embedding Model for Knowledge Graphs
<i>BaseKGE</i>	Base class for all neural network modules.
<i>ConEx</i>	Convolutional ComplEx Knowledge Graph Embeddings
<i>AConEx</i>	Additive Convolutional ComplEx Knowledge Graph Embeddings
<i>ComplEx</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>IdentityClass</i>	Base class for all neural network modules.
<i>QMult</i>	Base class for all neural network modules.
<i>ConvQ</i>	Convolutional Quaternion Knowledge Graph Embeddings
<i>AConvQ</i>	Additive Convolutional Quaternion Knowledge Graph Embeddings
<i>BaseKGE</i>	Base class for all neural network modules.
<i>IdentityClass</i>	Base class for all neural network modules.
<i>OMult</i>	Base class for all neural network modules.
<i>ConvO</i>	Base class for all neural network modules.
<i>AConvO</i>	Additive Convolutional Octonion Knowledge Graph Embeddings
<i>Keci</i>	Base class for all neural network modules.
<i>KeciBase</i>	Without learning dimension scaling
<i>DeCaL</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>PykeenKGE</i>	A class for using knowledge graph embedding models implemented in Pykeen
<i>BaseKGE</i>	Base class for all neural network modules.
<i>FMult</i>	Learning Knowledge Neural Graphs
<i>GFMult</i>	Learning Knowledge Neural Graphs
<i>FMult2</i>	Learning Knowledge Neural Graphs
<i>LFMult1</i>	Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
<i>LFMult</i>	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
<i>DualE</i>	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

Functions

<code>quaternion_mul(→ Tuple[torch.Tensor, torch.Tensor, ...])</code>	Perform quaternion multiplication
<code>quaternion_mul_with_unit_norm(*, Q_1, Q_2)</code>	
<code>octonion_mul(*, O_1, O_2)</code>	
<code>octonion_mul_norm(*, O_1, O_2)</code>	

Package Contents

class dicee.models.**BaseKGELightning**(*args, **kwargs)

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

training_step_outputs = []

mem_of_model() → Dict

Size of model in MB and number of params

training_step (*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- **Tensor** - The loss tensor
- **dict** - A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.

- **None** - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches > 1`, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

loss_function (*yhat_batch: torch.FloatTensor, y_batch: torch.FloatTensor*)

Parameters

- **yhat_batch**
- **y_batch**

on_train_epoch_end (*args, **kwargs)

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the `LightningModule` and access them in this hook:

```
class MyLightningModule(L.LightningModule):
    def __init__(self):
        super().__init__()
```

(continues on next page)

(continued from previous page)

```
self.training_step_outputs = []

def training_step(self):
    loss = ...
    self.training_step_outputs.append(loss)
    return loss

def on_train_epoch_end(self):
    # do something with all training_step outputs, for example:
    epoch_mean = torch.stack(self.training_step_outputs).mean()
    self.log("training_epoch_mean", epoch_mean)
    # free up the memory
    self.training_step_outputs.clear()
```

test_epoch_end(*outputs: List[Any]*)

test_dataloader() → None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `test()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Note

If you don't need a test dataset and a `test_step()`, you don't need to implement this method.

val_dataloader() → None

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `fit()`
- `validate()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Note

If you don't need a validation dataset and a `validation_step()`, you don't need to implement this method.

`predict_dataloader()` → None

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `predict()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Returns

A `torch.utils.data.DataLoader` or a sequence of them specifying prediction samples.

`train_dataloader()` → None

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`

- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `fit()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

configure_optimizers (*parameters=None*)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- **Single optimizer.**
- **List or Tuple** of optimizers.
- **Two lists** - The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple `lr_scheduler_config`).
- **Dictionary**, with an "optimizer" key, and (optionally) a "lr_scheduler" key whose value is a single LR scheduler or `lr_scheduler_config`.
- **None** - Fit will run without any optimizer.

The `lr_scheduler_config` is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
    "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
    "interval": "epoch",
    # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
    "frequency": 1,
    # Metric to to monitor for schedulers like `ReduceLROnPlateau`
    "monitor": "val_loss",
```

(continues on next page)

(continued from previous page)

```
# If set to `True`, will enforce that the value specified 'monitor'
# is available when the scheduler is updated, thus stopping
# training if not found. If set to `False`, it will only produce a warning
"strict": True,
# If using the `LearningRateMonitor` callback to monitor the
# learning rate progress, this keyword can be used to specify
# a custom logged name
"name": None,
}
```

When there are schedulers in which the `.step()` method is conditioned on a value, such as the `torch.optim.lr_scheduler.ReduceLROnPlateau` scheduler, Lightning requires that the `lr_scheduler_config` contains the keyword "monitor" set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using `self.log('metric_to_track', metric_val)` in your `LightningModule`.

Note

Some things to know:

- Lightning calls `.backward()` and `.step()` automatically in case of automatic optimization.
- If a learning rate scheduler is specified in `configure_optimizers()` with key "interval" (default "epoch") in the scheduler configuration, Lightning will call the scheduler's `.step()` method automatically in case of automatic optimization.
- If you use 16-bit precision (`precision=16`), Lightning will automatically handle the optimizer.
- If you use `torch.optim.LBFGS`, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the `optimizer_step()` hook.

class `dicce.models.BaseKGE` (*args: dict*)

Bases: `BaseKGELightning`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)


```
def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

args

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

`kernel_size = None`

`num_of_output_channels = None`

`weight_decay = None`

loss

`selected_optimizer = None`

`normalizer_class = None`

`normalize_head_entity_embeddings`

`normalize_relation_embeddings`

`normalize_tail_entity_embeddings`

`hidden_normalizer`

```

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking ()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters

        •  $\mathbf{x}$ 

        •  $\mathbf{y\_idx}$ 

        • ordered_bpe_entities

forward_triples (x: torch.LongTensor) → torch.Tensor

    Parameters

         $\mathbf{x}$ 

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (x: torch.LongTensor)

    Parameters

        • ( $\mathbf{b}$  ( $\mathbf{x}$  shape)

        • 3

        •  $\mathbf{t}$ )

```

```
get_bpe_head_and_relation_representation(x: torch.LongTensor)
    → Tuple[torch.FloatTensor, torch.FloatTensor]
```

Parameters

$\mathbf{x} (B \times 2 \times T)$

```
get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]
```

```
class dicee.models.IdentityClass (args=None)
```

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__ (*x*)

static forward (*x*)

```
class dicee.models.BaseKGE (args: dict)
```

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

`kernel_size = None`

`num_of_output_channels = None`

`weight_decay = None`

`loss`

`selected_optimizer = None`

```

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters

    •  $\mathbf{x}$ 

    •  $\mathbf{y\_idx}$ 

    • ordered_bpe_entities

forward_triples (x: torch.LongTensor) → torch.Tensor

    Parameters
         $\mathbf{x}$ 

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

```

```

get_sentence_representation (x: torch.LongTensor)

    Parameters
    • (b (x shape)
    • 3
    • t)

get_bpe_head_and_relation_representation (x: torch.LongTensor)
    → Tuple[torch.FloatTensor, torch.FloatTensor]

    Parameters
    x (B × 2 × T)

get_embeddings () → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.DistMult (args)
    Bases: dicee.models.base_model.BaseKGE
    Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

    name = 'DistMult'

    k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor, emb_E: torch.FloatTensor)

        Parameters
        • emb_h
        • emb_r
        • emb_E

    forward_k_vs_all (x: torch.LongTensor)

    forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)

    score (h, r, t)

class dicee.models.TransE (args)
    Bases: dicee.models.base_model.BaseKGE
    Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf

    name = 'TransE'

    margin = 4

    score (head_ent_emb, rel_ent_emb, tail_ent_emb)

    forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor

class dicee.models.Shallom (args)
    Bases: dicee.models.base_model.BaseKGE
    A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)

    name = 'Shallom'

```

`shallow`

`get_embeddings()` \rightarrow `Tuple[numpy.ndarray, None]`

`forward_k_vs_all(x)` \rightarrow `torch.FloatTensor`

`forward_triples(x)` \rightarrow `torch.FloatTensor`

Parameters

x

Returns

`class dicee.models.Pyke(args)`

Bases: `dicee.models.base_model.BaseKGE`

A Physical Embedding Model for Knowledge Graphs

`name = 'Pyke'`

`dist_func`

`margin = 1.0`

`forward_triples(x: torch.LongTensor)`

Parameters

x

`class dicee.models.BaseKGE(args: dict)`

Bases: `BaseKGELightning`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training` (*bool*) – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim` = None

`num_entities` = None

`num_relations` = None

`num_tokens` = None

`learning_rate` = None

`apply_unit_norm` = None

`input_dropout_rate` = None

`hidden_dropout_rate` = None

`optimizer_name` = None

`feature_map_dropout_rate` = None

`kernel_size` = None

`num_of_output_channels` = None

`weight_decay` = None

`loss`

`selected_optimizer` = None

`normalizer_class` = None

`normalize_head_entity_embeddings`

`normalize_relation_embeddings`

`normalize_tail_entity_embeddings`

`hidden_normalizer`

`param_init`

`input_dp_ent_real`

`input_dp_rel_real`

`hidden_dropout`

`loss_history` = []

`byte_pair_encoding`

`max_length_subword_tokens`

`block_size`


```

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking ()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters

        •  $\mathbf{x}$ 

        •  $\mathbf{y\_idx}$ 

        •  $\mathbf{ordered\_bpe\_entities}$ 

forward_triples (x: torch.LongTensor) → torch.Tensor

    Parameters
         $\mathbf{x}$ 

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (x: torch.LongTensor)

    Parameters

        • ( $\mathbf{b}$  ( $x$  shape))

        • 3

        •  $\mathbf{t}$ )

get_bpe_head_and_relation_representation (x: torch.LongTensor)
    → Tuple[torch.FloatTensor, torch.FloatTensor]

    Parameters

         $\mathbf{x}$  ( $B \times 2 \times T$ )

get_embeddings () → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.ConEx (args)
    Bases: dicee.models.base_model.BaseKGE
    Convolutional ComplEx Knowledge Graph Embeddings

    name = 'ConEx'

conv2d

```

```

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                        C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
    Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
    that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
    complex-valued embeddings :return:

forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor

forward_triples (x: torch.Tensor) → torch.FloatTensor

    Parameters
        x

forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

class dicee.models.AConEx (args)
    Bases: dicee.models.base_model.BaseKGE
    Additive Convolutional ComplEx Knowledge Graph Embeddings
    name = 'AConEx'

    conv2d

    fc_num_input

    fc1

    norm_fc1

    bn_conv2d

    feature_map_dropout

    residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                            C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
        Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
        that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
        complex-valued embeddings :return:

    forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor

    forward_triples (x: torch.Tensor) → torch.FloatTensor

        Parameters
            x

    forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

```

```
class dicee.models.Complex(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

```
name = 'Complex'
```

```
static score(head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor,  
             tail_ent_emb: torch.FloatTensor)
```

```
static k_vs_all_score(emb_h: torch.FloatTensor, emb_r: torch.FloatTensor,  
                     emb_E: torch.FloatTensor)
```

Parameters

- `emb_h`
- `emb_r`
- `emb_E`

```
forward_k_vs_all(x: torch.LongTensor) → torch.FloatTensor
```

```
forward_k_vs_sample(x: torch.LongTensor, target_entity_idx: torch.LongTensor)
```

```
dicee.models.quaternion_mul(*, Q_1, Q_2)  
→ Tuple[torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor]
```

Perform quaternion multiplication :param `Q_1`: :param `Q_2`: :return:

```
class dicee.models.BaseKGE(args: dict)
```

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

```

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters
        •  $\mathbf{x}$ 
        •  $\mathbf{y\_idx}$ 
        •  $\mathbf{ordered\_bpe\_entities}$ 

```

forward_triples (x : torch.LongTensor) \rightarrow torch.Tensor

Parameters

x

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (x : torch.LongTensor)

Parameters

- (**b** (x shape)

- 3

- **t**)

get_bpe_head_and_relation_representation (x : torch.LongTensor)
 \rightarrow Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters

x ($B \times 2 \times T$)

get_embeddings () \rightarrow Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.IdentityClass (args=None)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`__call__(x)`

`static forward(x)`

```
dicee.models.quaternion_mul_with_unit_norm(*, Q_1, Q_2)
```

```
class dicee.models.QMult(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`name = 'QMult'`

`explicit = True`

quaternion_multiplication_followed_by_inner_product (*h, r, t*)

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer (*x: torch.FloatTensor*) → torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters

x – The vector.

Returns

The normalized vector.

score (*head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor, tail_ent_emb: torch.FloatTensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

Parameters

- **bpe_head_ent_emb**
- **bpe_rel_ent_emb**
- **E**

forward_k_vs_all (*x*)

Parameters

x

forward_k_vs_sample (*x, target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.ConvQ (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings


```

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(Q_1, Q_2)

forward_triples(indexed_triple: torch.Tensor) → torch.Tensor

    Parameters
    x

forward_k_vs_all(x: torch.Tensor)
    Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
    [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
    Entities|)

class dicee.models.AConvQ(args)
    Bases: dicee.models.base_model.BaseKGE
    Additive Convolutional Quaternion Knowledge Graph Embeddings
    name = 'AConvQ'
    entity_embeddings
    relation_embeddings
    conv2d
    fc_num_input
    fc1
    bn_conv1
    bn_conv2
    feature_map_dropout
    residual_convolution(Q_1, Q_2)
    forward_triples(indexed_triple: torch.Tensor) → torch.Tensor

    Parameters
    x

forward_k_vs_all(x: torch.Tensor)
    Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
    [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
    Entities|)

```

```
class dicee.models.BaseKGE (args: dict)
```

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

```

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters
        •  $\mathbf{x}$ 
        •  $\mathbf{y\_idx}$ 
        •  $\mathbf{ordered\_bpe\_entities}$ 

```

forward_triples (*x*: torch.LongTensor) → torch.Tensor

Parameters

x

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (*x*: torch.LongTensor)

Parameters

- (**b** (*x* shape)
- 3
- **t**)

get_bpe_head_and_relation_representation (*x*: torch.LongTensor)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters

x (*B* × 2 × *x* *T*)

get_embeddings () → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.IdentityClass (args=None)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`__call__(x)`

`static forward(x)`

```
dicee.models.octonion_mul(*, O_1, O_2)
```

```
dicee.models.octonion_mul_norm(*, O_1, O_2)
```

```
class dicee.models.OMult(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`name = 'OMult'`

```
static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                           emb_rel_e5, emb_rel_e6, emb_rel_e7)
```

```
score(head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor,
      tail_ent_emb: torch.FloatTensor)
```

```
k_vs_all_score(bpe_head_ent_emb, bpe_rel_ent_emb, E)
```

```
forward_k_vs_all(x)
```

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e.,
[score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and
relations => shape (size of batch,| Entities|)

```
class dicee.models.ConvO(args: dict)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`name = 'ConvO'`

`conv2d`

`fc_num_input`

`fc1`

`bn_conv2d`

```

norm_fc1

feature_map_dropout

static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                           emb_rel_e5, emb_rel_e6, emb_rel_e7)

residual_convolution(O_1, O_2)

forward_triples(x: torch.Tensor) → torch.Tensor

    Parameters
    x

forward_k_vs_all(x: torch.Tensor)
    Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
    [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
    Entities)

class dicee.models.AConvO(args: dict)
    Bases: dicee.models.base_model.BaseKGE

    Additive Convolutional Octonion Knowledge Graph Embeddings

    name = 'AConvO'

    conv2d

    fc_num_input

    fc1

    bn_conv2d

    norm_fc1

    feature_map_dropout

    static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                               emb_rel_e5, emb_rel_e6, emb_rel_e7)

    residual_convolution(O_1, O_2)

    forward_triples(x: torch.Tensor) → torch.Tensor

        Parameters
        x

    forward_k_vs_all(x: torch.Tensor)
        Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
        [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
        Entities)

class dicee.models.Keci(args)
    Bases: dicee.models.base_model.BaseKGE

    Base class for all neural network modules.

    Your models should also subclass this class.

    Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules
    as regular attributes:

```

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp (*hp, rp*)

Compute $\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_{ir_k} - h_{kr_i}) e_i e_k$

σ_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3 , we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

 for k in range(i + 1, p):

 results.append($hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i]$)

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., $e_1 e_1, e_1 e_2, e_1 e_3$,

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_qq (*hq, rq*)

Compute $\sigma_{qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_{jr_k} - h_{kr_j}) e_j e_k \sigma_q$ captures the interactions between along q bases For instance, let q e_1, e_2, e_3 , we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops


```

results = [] for j in range(q - 1):
    for k in range(j + 1, q):
        results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])
sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., e_1e_1 , e_1e_2 , e_1e_3 ,

e_2e_1 , e_2e_2 , e_2e_3 , e_3e_1 , e_3e_2 , e_3e_3

Then select the triangular matrix without diagonals: e_1e_2 , e_1e_3 , e_2e_3 .

```

compute_sigma_pq(*, hp, hq, rp, rq)
sum_{i=1}^p sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
    for j in range(q):
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
print(sigma_pq.shape)

```

apply_coefficients (hp, hq, rp, rq)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (h_0, hp, hq, r_0, rp, rq)

Compute our CL multiplication

$$h = h_0 + \sum_{i=1}^p h_i e_i + \sum_{j=p+1}^{p+q} h_j e_j \quad r = r_0 + \sum_{i=1}^p r_i e_i + \sum_{j=p+1}^{p+q} r_j e_j$$

$$e_i^2 = +1 \text{ for } i \leq p, \quad e_j^2 = -1 \text{ for } p < j \leq p+q, \quad e_i e_j = -e_j e_i \text{ for } i \neq j$$

eq j

$h r = \sigma_0 + \sigma_p + \sigma_q + \sigma_{pp} + \sigma_q + \sigma_{pq}$ where

(1) $\sigma_0 = h_0 r_0 + \sum_{i=1}^p (h_0 r_i - h_i r_0) e_i - \sum_{j=p+1}^{p+q} (h_j r_j) e_j$

(2) $\sigma_p = \sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$

(3) $\sigma_q = \sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$

(4) $\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k$

(5) $\sigma_{qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k$

(6) $\sigma_{pq} = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$

construct_cl_multivector (x : *torch.FloatTensor*, r : *int*, p : *int*, q : *int*)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $CL_{\{p,q\}}(\mathbb{R}^d)$

Parameter

x : torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor* with (n,r) shape)
- **ap** (*torch.FloatTensor* with (n,r,p) shape)
- **aq** (*torch.FloatTensor* with (n,r,q) shape)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations \mathbb{R}^d .
- (2) Construct head entity and relation embeddings according to $Cl_{\{p,q\}}(\mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter ——— *x: torch.LongTensor* with (n,2) shape :rtype: torch.FloatTensor with (n, **IEI**) shape

construct_batch_selected_cl_multivector (*x: torch.FloatTensor, r: int, p: int, q: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of batchs multivectors $Cl_{\{p,q\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (*torch.FloatTensor* with (n,k, m) shape)
- **ap** (*torch.FloatTensor* with (n,k, m, p) shape)
- **aq** (*torch.FloatTensor* with (n,k, m, q) shape)

forward_k_vs_sample (*x: torch.LongTensor, target_entity_idx: torch.LongTensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,2) shape

target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.

rtype

torch.FloatTensor with (n, k) shape

score (*h, r, t*)

forward_triples (*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype

torch.FloatTensor with (n) shape

class `dicee.models.KeciBase` (*args*)

Bases: *Keci*

Without learning dimension scaling

name = 'KeciBase'

```
requires_grad_for_interactions = False
```

```
class dicee.models.DeCaL(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation_embeddings

p

q

r

re

forward_triples (*x: torch.Tensor*) \rightarrow torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl_pqr (*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) → output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb, list_r_emb, list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^p h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^q (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i)$$

and return:

$$sigma_0 t = \sigma_0 \cdot t_0 = s0 + s1 - s2 s3, s4 \text{ and } s5$$

compute_sigmas_multivect (*list_h_emb, list_r_emb*)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (\text{model the interactions between } e_i \text{ and } e_{i'} \text{ for } 1 \leq i, i' \leq p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{j'} r_j)$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (\text{interactions between } e_i \text{ and } e_j \text{ for } 1 \leq i \leq p \text{ and } p+1 \leq j \leq p+q) \sigma_p r = \sum_{i=1}^p \sum_{r=p+q+1}^{p+q+r} (h_i r_r - h_r r_i)$$

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to $Cl_{\{p,q,r\}}(\mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, **IEI**) shape

apply_coefficients (*h0, hp, hq, hk, r0, rp, rq, rk*)

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (*x: torch.FloatTensor, re: int, p: int, q: int, r: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{\{p,q,r\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor)
- **ap** (torch.FloatTensor)
- **aq** (torch.FloatTensor)
- **ar** (torch.FloatTensor)

compute_sigma_pp (hp, rp)

Compute .. math:

$$\sigma_{pp} = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (x_i y_{i'} - x_{i'} y_i)$$

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):

 results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq (hq, rq)

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) E q.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

 results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_rr (hk, rk)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^p (x_k y_{k'} - x_{k'} y_k)$$

```
compute_sigma_pq(*, hp, hq, rp, rq)
```

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

```
compute_sigma_pr(*, hp, hk, rp, rk)
```

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

```
compute_sigma_qr(*, hq, hk, rq, rk)
```

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```
results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
```

```
    for j in range(q):
```

```
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
```

```
    print(sigma_pq.shape)
```

```
class dicee.models.BaseKGE(args: dict)
```

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training` (*bool*) – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim` = None

`num_entities` = None

`num_relations` = None

`num_tokens` = None

`learning_rate` = None

`apply_unit_norm` = None

`input_dropout_rate` = None

`hidden_dropout_rate` = None

`optimizer_name` = None

`feature_map_dropout_rate` = None

`kernel_size` = None

`num_of_output_channels` = None

`weight_decay` = None

`loss`

`selected_optimizer` = None

`normalizer_class` = None

`normalize_head_entity_embeddings`

`normalize_relation_embeddings`

`normalize_tail_entity_embeddings`

`hidden_normalizer`

`param_init`

`input_dp_ent_real`

`input_dp_rel_real`

```

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters

    •  $\mathbf{x}$ 

    •  $\mathbf{y\_idx}$ 

    • ordered_bpe_entities

forward_triples (x: torch.LongTensor) → torch.Tensor

    Parameters
         $\mathbf{x}$ 

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (x: torch.LongTensor)

    Parameters

    • ( $\mathbf{b}$  ( $x$  shape))

    • 3

    •  $\mathbf{t}$ )

get_bpe_head_and_relation_representation (x: torch.LongTensor)
    → Tuple[torch.FloatTensor, torch.FloatTensor]

    Parameters
         $\mathbf{x}$  ( $B \times 2 \times T$ )

```



```

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.PykeenKGE (args: dict)
    Bases: dicee.models.base_model.BaseKGE

    A class for using knowledge graph embedding models implemented in Pykeen

    Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Py-
    keen_HolE:

    model_kwargs

    name

    model

    loss_history = []

    args

    entity_embeddings = None

    relation_embeddings = None

    forward_k_vs_all (x: torch.LongTensor)
        # => Explicit version by this we can apply bn and dropout

        # (1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r =
        self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:

            h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
            self.last_dim)

        # (3) Reshape all entities. if self.last_dim > 0:

            t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

        else:

            t = self.entity_embeddings.weight

        # (4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r,
        all_entities=t, slice_size=1)

    forward_triples (x: torch.LongTensor) → torch.FloatTensor
        # => Explicit version by this we can apply bn and dropout

        # (1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t =
        self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

            h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
            self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

        # (3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

    abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)

class dicee.models.BaseKGE (args: dict)
    Bases: BaseKGELightning

    Base class for all neural network modules.

    Your models should also subclass this class.

```

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`args`

`embedding_dim = None`

`num_entities = None`

`num_relations = None`

`num_tokens = None`

`learning_rate = None`

`apply_unit_norm = None`

`input_dropout_rate = None`

`hidden_dropout_rate = None`

`optimizer_name = None`

`feature_map_dropout_rate = None`

`kernel_size = None`

`num_of_output_channels = None`

`weight_decay = None`

`loss`

```

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

    Parameters
         $\mathbf{x} (B \times 2 \times T)$ 

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking ()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
        y_idx: torch.LongTensor = None)

    Parameters

        •  $\mathbf{x}$ 

        •  $\mathbf{y\_idx}$ 

        •  $\mathbf{ordered\_bpe\_entities}$ 

forward_triples (x: torch.LongTensor)  $\rightarrow$  torch.Tensor

    Parameters
         $\mathbf{x}$ 

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

```

get_head_relation_representation (*indexed_triple*)

get_sentence_representation (*x: torch.LongTensor*)

Parameters

- (**b** (*x shape*))
- 3
- **t**)

get_bpe_head_and_relation_representation (*x: torch.LongTensor*)

→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters

x (*B x 2 x T*)

get_embeddings () → Tuple[numpy.ndarray, numpy.ndarray]

class `dicee.models.FMult` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Learning Knowledge Neural Graphs

name = 'FMult'

entity_embeddings

relation_embeddings

k

num_sample = 50

gamma

roots

weights

compute_func (*weights: torch.FloatTensor, x*) → torch.FloatTensor

chain_func (*weights, x: torch.FloatTensor*)

forward_triples (*idx_triple: torch.Tensor*) → torch.Tensor

Parameters

x

class `dicee.models.GFMult` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Learning Knowledge Neural Graphs

name = 'GFMult'

entity_embeddings

relation_embeddings

k

```

num_sample = 250

roots

weights

compute_func(weights: torch.FloatTensor, x) → torch.FloatTensor

chain_func(weights, x: torch.FloatTensor)

forward_triples(idx_triple: torch.Tensor) → torch.Tensor

```

Parameters

x

```

class dicee.models.FMult2(args)
    Bases: dicee.models.base_model.BaseKGE
    Learning Knowledge Neural Graphs
    name = 'FMult2'
    n_layers = 3
    k
    n = 50
    score_func = 'compositional'
    discrete_points
    entity_embeddings
    relation_embeddings
    build_func(Vec)
    build_chain_funcs(list_Vec)
    compute_func(W, b, x) → torch.FloatTensor
    function(list_W, list_b)
    trapezoid(list_W, list_b)
    forward_triples(idx_triple: torch.Tensor) → torch.Tensor

```

Parameters

x

```

class dicee.models.LFMult1(args)
    Bases: dicee.models.base_model.BaseKGE

    Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
 $f(x) = \sum_{k=0}^{d-1} w_k e^{kix}$ . and use the three differents scoring function as in the paper to evaluate the score

    name = 'LFMult1'
    entity_embeddings

```

```

relation_embeddings

forward_triples (idx_triple)

    Parameters
    x

tri_score (h, r, t)

vtp_score (h, r, t)

class dicee.models.LFMult (args)
    Bases: dicee.models.base_model.BaseKGE

    Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:  $f(x) = \sum_{i=0}^{d-1} a_i x^i$  and use the three different scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

    name = 'LFMult'

    entity_embeddings

    relation_embeddings

    degree

    m

    x_values

    forward_triples (idx_triple)

    Parameters
    x

    construct_multi_coeff (x)

    poly_NN (x, coefh, coefr, coeft)
        Constructing a 2 layers NN to represent the embeddings.  $h = \sigma(w_h^T x + b_h)$ ,  $r = \sigma(w_r^T x + b_r)$ ,  $t = \sigma(w_t^T x + b_t)$ 

    linear (x, w, b)

    scalar_batch_NN (a, b, c)
        element wise multiplication between a,b and c: Inputs : a, b, c ==> torch.tensor of size batch_size x m x d
        Output : a tensor of size batch_size x d

    tri_score (coeff_h, coeff_r, coeff_t)
        this part implement the trilinear scoring techniques:

        
$$\text{score}(h,r,t) = \int_0^1 h(x)r(x)t(x) dx = \sum_{i,j,k=0}^{d-1} \frac{a_i b_j c_k}{1+(i+j+k)d}$$


        1. generate the range for i,j and k from [0 d-1]
        2. perform  $\frac{a_i b_j c_k}{1+(i+j+k)d}$  in parallel for every batch
        3. take the sum over each batch

```

vtp_score (*h, r, t*)

this part implement the vector triple product scoring techniques:

$$\text{score}(h,r,t) = \int_{\{0\}^1} h(x)r(x)t(x) \, dx = \sum_{\{i,j,k = 0\}^{d-1}} \frac{a_i * c_j * b_k - b_i * c_j * a_k}{(1+(i+j)\%d)(1+k)}$$

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum
4. take the sum over each batch

comp_func (*h, r, t*)

this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial (*coeff, x, degree*)

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,...d] and return a vector tensor (coeff[0][0] + coeff[0][1]x +...+ coeff[0][d]x^d,

$$\text{coeff}[1][0] + \text{coeff}[1][1]x + \dots + \text{coeff}[1][d]x^d)$$

pop (*coeff, x, degree*)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,...d]

$$\text{and return a tensor } (\text{coeff}[0][0] + \text{coeff}[0][1]x + \dots + \text{coeff}[0][d]x^d,$$

$$\text{coeff}[1][0] + \text{coeff}[1][1]x + \dots + \text{coeff}[1][d]x^d)$$

class `dicee.models.DualE` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Dual Quaternion Knowledge Graph Embeddings (<https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657>)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score (*e_1_h, e_2_h, e_3_h, e_4_h, e_5_h, e_6_h, e_7_h, e_8_h, e_1_t, e_2_t, e_3_t, e_4_t, e_5_t, e_6_t, e_7_t, e_8_t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8*) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples (*idx_triple: torch.tensor*) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_k_vs_all (x)
KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T (x: *torch.tensor*) → torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

dicee.query_generator

Classes

QueryGenerator

Module Contents

```
class dicee.query_generator.QueryGenerator(train_path: str, val_path: str, test_path: str,  
                                           ent2id: Dict = None, rel2id: Dict = None, seed: int = 1, gen_valid: bool = False,  
                                           gen_test: bool = True)
```

train_path

val_path

test_path

gen_valid

gen_test

seed

max_ans_num = 1000000.0

mode

ent2id

rel2id: Dict


```

ent_in: Dict

ent_out: Dict

query_name_to_struct

list2tuple (list_data)

tuple2list (x: List | Tuple) → List | Tuple
    Convert a nested tuple to a nested list.

set_global_seed (seed: int)
    Set seed

construct_graph (paths: List[str]) → Tuple[Dict, Dict]
    Construct graph from triples Returns dicts with incoming and outgoing edges

fill_query (query_structure: List[str | List], ent_in: Dict, ent_out: Dict, answer: int) → bool
    Private method for fill_query logic.

achieve_answer (query: List[str | List], ent_in: Dict, ent_out: Dict) → set
    Private method for achieve_answer logic. @TODO: Document the code

write_links (ent_out, small_ent_out)

ground_queries (query_structure: List[str | List], ent_in: Dict, ent_out: Dict, small_ent_in: Dict,
                small_ent_out: Dict, gen_num: int, query_name: str)
    Generating queries and achieving answers

unmap (query_type, queries, tp_answers, fp_answers, fn_answers)

unmap_query (query_structure, query, id2ent, id2rel)

generate_queries (query_struct: List, gen_num: int, query_type: str)
    Passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting
    queries and answers in return @ TODO: create a class for each single query struct

save_queries (query_type: str, gen_num: int, save_path: str)

abstract load_queries (path)

get_queries (query_type: str, gen_num: int)

static save_queries_and_answers (path: str, data: List[Tuple[str, Tuple[collections.defaultdict]]])
    → None
    Save Queries into Disk

static load_queries_and_answers (path: str) → List[Tuple[str, Tuple[collections.defaultdict]]]
    Load Queries from Disk to Memory

```

dicee.read_preprocess_save_load_kg

Submodules

dicee.read_preprocess_save_load_kg.preprocess

Classes

Module Contents

class `dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG(kg)`

Preprocess the data in memory

kg

start () → None

Preprocess train, valid and test datasets stored in knowledge graph instance

Parameter

rtype

None

preprocess_with_byte_pair_encoding ()

preprocess_with_byte_pair_encoding_with_padding () → None

preprocess_with_pandas () → None

Preprocess train, valid and test datasets stored in knowledge graph instance with pandas

- (1) Add recipriocal or noisy triples
- (2) Construct vocabulary
- (3) Index datasets

Parameter

rtype

None

preprocess_with_polars () → None

sequential_vocabulary_construction () → None

- (1) Read input data into memory
- (2) Remove triples with a condition
- (3) **Serialize vocabularies in a pandas dataframe where**
=> the index is integer and => a single column is string (e.g. URI)

dicee.read_preprocess_save_load_kg.read_from_disk

Classes

ReadFromDisk

Read the data from disk into memory

Module Contents

class `dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk(kg)`

Read the data from disk into memory

kg

start() → None

Read a knowledge graph from disk into memory

Data will be available at the train_set, test_set, valid_set attributes.

Parameter

None

rtype

None

add_noisy_triples_into_training()

dicee.read_preprocess_save_load_kg.save_load_disk

Classes

LoadSaveToDisk

Module Contents

class dicee.read_preprocess_save_load_kg.save_load_disk.**LoadSaveToDisk**(kg)

kg

save()

load()

dicee.read_preprocess_save_load_kg.util

Functions

<code>polars_dataframe_indexer(→ polars.DataFrame)</code>	Replaces 'subject', 'relation', and 'object' columns in the input Polars DataFrame with their corresponding index values
<code>pandas_dataframe_indexer(→ pandas.DataFrame)</code>	Replaces 'subject', 'relation', and 'object' columns in the input Pandas DataFrame with their corresponding index values
<code>apply_reciprical_or_noise(add_reciprical, eval_model)</code> <code>timeit(func)</code>	
<code>read_with_polars(→ polars.DataFrame)</code>	Load and Preprocess via Polars
<code>read_with_pandas(data_path[, read_only_few, ...])</code>	
<code>read_from_disk(→ Tuple[polars.DataFrame, pandas.DataFrame])</code>	
<code>read_from_triple_store([endpoint])</code>	Read triples from triple store into pandas dataframe
<code>get_er_vocab(data[, file_path])</code>	
<code>get_re_vocab(data[, file_path])</code>	
<code>get_ee_vocab(data[, file_path])</code>	
<code>create_constraints(triples[, file_path])</code>	
<code>load_with_pandas(→ None)</code>	Deserialize data
<code>save_numpy_ndarray(*, data, file_path)</code>	
<code>load_numpy_ndarray(*, file_path)</code>	
<code>save_pickle(*, data[, file_path])</code>	
<code>load_pickle(*[, file_path])</code>	
<code>create_reciprical_triples(x)</code>	Add inverse triples into dask dataframe
<code>dataset_sanity_checking(→ None)</code>	

Module Contents

```
dicee.read_preprocess_save_load_kg.util.polars_dataframe_indexer(
    df_polars: polars.DataFrame, idx_entity: polars.DataFrame, idx_relation: polars.DataFrame)
    → polars.DataFrame
```

Replaces 'subject', 'relation', and 'object' columns in the input Polars DataFrame with their corresponding index values from the entity and relation index DataFrames.

This function processes the DataFrame in three main steps: 1. Replace the 'relation' values with the corresponding index from `idx_relation`. 2. Replace the 'subject' values with the corresponding index from `idx_entity`. 3. Replace the 'object' values with the corresponding index from `idx_entity`.

Parameters:

df_polars

[polars.DataFrame] The input Polars DataFrame containing columns: 'subject', 'relation', and 'object'.

idx_entity

[polars.DataFrame] A Polars DataFrame that contains the mapping between entity names and their corresponding indices. Must have columns: 'entity' and 'index'.

idx_relation

[polars.DataFrame] A Polars DataFrame that contains the mapping between relation names and their corresponding indices. Must have columns: 'relation' and 'index'.

Returns:

polars.DataFrame

A DataFrame with the 'subject', 'relation', and 'object' columns replaced by their corresponding indices.

Example Usage:

```
>>> df_polars = pl.DataFrame({
    "subject": ["Alice", "Bob", "Charlie"],
    "relation": ["knows", "works_with", "lives_in"],
    "object": ["Dave", "Eve", "Frank"]
})
>>> idx_entity = pl.DataFrame({
    "entity": ["Alice", "Bob", "Charlie", "Dave", "Eve", "Frank"],
    "index": [0, 1, 2, 3, 4, 5]
})
>>> idx_relation = pl.DataFrame({
    "relation": ["knows", "works_with", "lives_in"],
    "index": [0, 1, 2]
})
>>> polars_dataframe_indexer(df_polars, idx_entity, idx_relation)
```

Steps:

1. Join the input DataFrame *df_polars* on the 'relation' column with *idx_relation* to replace the relations with their indices.
2. Join on 'subject' to replace it with the corresponding entity index using a left join on *idx_entity*.
3. Join on 'object' to replace it with the corresponding entity index using a left join on *idx_entity*.
4. Select only the 'subject', 'relation', and 'object' columns to return the final result.

```
dicee.read_preprocess_save_load_kg.util.pandas_dataframe_indexer(
    df_pandas: pandas.DataFrame, idx_entity: pandas.DataFrame, idx_relation: pandas.DataFrame)
→ pandas.DataFrame
```

Replaces 'subject', 'relation', and 'object' columns in the input Pandas DataFrame with their corresponding index values from the entity and relation index DataFrames.

Parameters:

df_pandas

[pd.DataFrame] The input Pandas DataFrame containing columns: 'subject', 'relation', and 'object'.

idx_entity

[pd.DataFrame] A Pandas DataFrame that contains the mapping between entity names and their corresponding indices. Must have columns: 'entity' and 'index'.

idx_relation

[pd.DataFrame] A Pandas DataFrame that contains the mapping between relation names and their corresponding indices. Must have columns: 'relation' and 'index'.

Returns:

pd.DataFrame

A DataFrame with the 'subject', 'relation', and 'object' columns replaced by their corresponding indices.

```
dicee.read_preprocess_save_load_kg.util.apply_reciprical_or_noise (add_reciprical: bool,  
    eval_model: str, df: object = None, info: str = None)
```

(1) Add reciprocal triples (2) Add noisy triples

```
dicee.read_preprocess_save_load_kg.util.timeit (func)
```

```
dicee.read_preprocess_save_load_kg.util.read_with_polars (data_path,  
    read_only_few: int = None, sample_triples_ratio: float = None, separator: str = None)  
    → polars.DataFrame
```

Load and Preprocess via Polars

```
dicee.read_preprocess_save_load_kg.util.read_with_pandas (data_path,  
    read_only_few: int = None, sample_triples_ratio: float = None, separator: str = None)
```

```
dicee.read_preprocess_save_load_kg.util.read_from_disk (data_path: str,  
    read_only_few: int = None, sample_triples_ratio: float = None, backend: str = None,  
    separator: str = None) → Tuple[polars.DataFrame, pandas.DataFrame]
```

```
dicee.read_preprocess_save_load_kg.util.read_from_triple_store (endpoint: str = None)
```

Read triples from triple store into pandas dataframe

```
dicee.read_preprocess_save_load_kg.util.get_er_vocab (data, file_path: str = None)
```

```
dicee.read_preprocess_save_load_kg.util.get_re_vocab (data, file_path: str = None)
```

```
dicee.read_preprocess_save_load_kg.util.get_ee_vocab (data, file_path: str = None)
```

```
dicee.read_preprocess_save_load_kg.util.create_constraints (triples, file_path: str = None)
```

(1) Extract domains and ranges of relations

(2) Store a mapping from relations to entities that are outside of the domain and range. Create constrained entities based on the range of relations :param triples: :return: Tuple[dict, dict]

```
dicee.read_preprocess_save_load_kg.util.load_with_pandas (self) → None
```

Deserialize data

```
dicee.read_preprocess_save_load_kg.util.save_numpy_ndarray (*, data: numpy.ndarray,  
    file_path: str)
```

```

dicee.read_preprocess_save_load_kg.util.load_numpy_ndarray(* , file_path: str)
dicee.read_preprocess_save_load_kg.util.save_pickle(* , data: object, file_path=str)
dicee.read_preprocess_save_load_kg.util.load_pickle(* , file_path=str)
dicee.read_preprocess_save_load_kg.util.create_recipriocal_triples(x)
    Add inverse triples into dask dataframe :param x: :return:
dicee.read_preprocess_save_load_kg.util.dataset_sanity_checking(
    train_set: numpy.ndarray, num_entities: int, num_relations: int) → None

```

Parameters

- **train_set**
- **num_entities**
- **num_relations**

Returns

Classes

<i>PreprocessKG</i>	Preprocess the data in memory
<i>LoadSaveToDisk</i>	
<i>ReadFromDisk</i>	Read the data from disk into memory

Package Contents

```

class dicee.read_preprocess_save_load_kg.PreprocessKG(kg)
    Preprocess the data in memory
    kg
    start() → None
        Preprocess train, valid and test datasets stored in knowledge graph instance

```

Parameter

```

    rtype
        None

    preprocess_with_byte_pair_encoding()

    preprocess_with_byte_pair_encoding_with_padding() → None

    preprocess_with_pandas() → None
        Preprocess train, valid and test datasets stored in knowledge graph instance with pandas
        (1) Add recipriocal or noisy triples
        (2) Construct vocabulary
        (3) Index datasets

```

Parameter

rtype

None

preprocess_with_polars() → None

sequential_vocabulary_construction() → None

(1) Read input data into memory

(2) Remove triples with a condition

(3) **Serialize vocabularies in a pandas dataframe where**
=> the index is integer and => a single column is string (e.g. URI)

class dicee.read_preprocess_save_load_kg.**LoadSaveToDisk**(kg)

kg

save()

load()

class dicee.read_preprocess_save_load_kg.**ReadFromDisk**(kg)

Read the data from disk into memory

kg

start() → None

Read a knowledge graph from disk into memory

Data will be available at the train_set, test_set, valid_set attributes.

Parameter

None

rtype

None

add_noisy_triples_into_training()

dicee.sanity_checkers

Functions

```
is_sparql_endpoint_alive([sparql_endpoint])
```

```
validate_knowledge_graph(args)
```

Validating the source of knowledge graph

```
sanity_checking_with_arguments(args)
```

Module Contents

`dicee.sanity_checkers.is_sparql_endpoint_alive(sparql_endpoint: str = None)`

`dicee.sanity_checkers.validate_knowledge_graph (args)`

Validating the source of knowledge graph

`dicee.sanity_checkers.sanity_checking_with_arguments (args)`

dicee.scripts

Submodules

dicee.scripts.index

Functions

`get_default_arguments()`

`main()`

Module Contents

`dicee.scripts.index.get_default_arguments ()`

`dicee.scripts.index.main ()`

dicee.scripts.run

Functions

`get_default_arguments([description])`

Extends pytorch_lightning Trainer's arguments with ours

`main()`

Module Contents

`dicee.scripts.run.get_default_arguments (description=None)`

Extends pytorch_lightning Trainer's arguments with ours

`dicee.scripts.run.main ()`

dicee.scripts.serve

Attributes

`app`

`neural_searcher`

Classes

```
NeuralSearcher
```

Functions

```
get_default_arguments()
```

```
root()
```

```
search_embeddings(q)
```

```
retrieve_embeddings(q)
```

```
main()
```

Module Contents

```
dicee.scripts.serve.app
```

```
dicee.scripts.serve.neural_searcher = None
```

```
dicee.scripts.serve.get_default_arguments()
```

```
async dicee.scripts.serve.root()
```

```
async dicee.scripts.serve.search_embeddings(q: str)
```

```
async dicee.scripts.serve.retrieve_embeddings(q: str)
```

```
class dicee.scripts.serve.NeuralSearcher(args)
```

```
    collection_name
```

```
    model
```

```
    qdrant_client
```

```
    get(entity: str)
```

```
    search(entity: str)
```

```
dicee.scripts.serve.main()
```

`dicee.static_funcs`

Functions

```
create_recipriocal_triples(x)
```

```
Add inverse triples into dask dataframe
```

continues on next page

Table 2 – continued from previous page

<code>get_er_vocab(data[, file_path])</code>	
<code>get_re_vocab(data[, file_path])</code>	
<code>get_ee_vocab(data[, file_path])</code>	
<code>timeit(func)</code>	
<code>save_pickle(*[, data, file_path])</code>	
<code>load_pickle([file_path])</code>	
<code>load_term_mapping([file_path])</code>	
<code>select_model(args[, is_continual_training, storage_path])</code>	
<code>load_model(→ Tuple[object, Tuple[dict, dict]])</code>	Load weights and initialize pytorch module from namespace arguments
<code>load_model_ensemble(...)</code>	Construct Ensemble Of weights and initialize pytorch module from namespace arguments
<code>save_numpy_ndarray(*, data, file_path)</code>	
<code>numpy_data_type_changer(→ numpy.ndarray)</code>	Detect most efficient data type for a given triples
<code>save_checkpoint_model(→ None)</code>	Store Pytorch model into disk
<code>store(→ None)</code>	Store trained_model model and save embeddings into csv file.
<code>add_noisy_triples(→ pandas.DataFrame)</code>	Add randomly constructed triples
<code>read_or_load_kg(args, cls)</code>	
<code>intialize_model(→ Tuple[object, str])</code>	
<code>load_json(→ dict)</code>	
<code>save_embeddings(→ None)</code>	Save it as CSV if memory allows.
<code>random_prediction(pre_trained_kge)</code>	
<code>deploy_triple_prediction(pre_trained_kge, str_subject, ...)</code>	
<code>deploy_tail_entity_prediction(pre_trained_kge, ...)</code>	
<code>deploy_head_entity_prediction(pre_trained_kge, ...)</code>	
<code>deploy_relation_prediction(pre_trained_kge, ...)</code>	
<code>vocab_to_parquet(vocab_to_idx, name, ...)</code>	
<code>create_experiment_folder([folder_name])</code>	
<code>continual_training_setup_executor(→ None)</code>	
<code>exponential_function(→ torch.FloatTensor)</code>	

continues on next page

Table 2 – continued from previous page

<code>load_numpy(→ numpy.ndarray)</code>	
<code>evaluate(entity_to_idx, scores, easy_answers, # @TODO: CD: Renamed this function hard_answers)</code>	
<code>download_file(url[, destination_folder])</code>	
<code>download_files_from_url(→ None)</code>	
<code>download_pretrained_model(→ str)</code>	
<code>write_csv_from_model_parallel(→ None)</code>	Create
<code>from_pretrained_model_write_embeddings_int(None)</code>	

Module Contents

`dicee.static_funcs.create_recipriocal_triples(x)`

Add inverse triples into dask dataframe :param x: :return:

`dicee.static_funcs.get_er_vocab(data, file_path: str = None)`

`dicee.static_funcs.get_re_vocab(data, file_path: str = None)`

`dicee.static_funcs.get_ee_vocab(data, file_path: str = None)`

`dicee.static_funcs.timeit(func)`

`dicee.static_funcs.save_pickle(*, data: object = None, file_path=str)`

`dicee.static_funcs.load_pickle(file_path=str)`

`dicee.static_funcs.load_term_mapping(file_path=str)`

`dicee.static_funcs.select_model(args: dict, is_continual_training: bool = None,
storage_path: str = None)`

`dicee.static_funcs.load_model(path_of_experiment_folder: str, model_name='model.pt', verbose=0)
→ Tuple[object, Tuple[dict, dict]]`

Load weights and initialize pytorch module from namespace arguments

`dicee.static_funcs.load_model_ensemble(path_of_experiment_folder: str)
→ Tuple[dicee.models.base_model.BaseKGE, Tuple[pandas.DataFrame, pandas.DataFrame]]`

Construct Ensemble Of weights and initialize pytorch module from namespace arguments

- (1) Detect models under given path
- (2) Accumulate parameters of detected models
- (3) Normalize parameters
- (4) Insert (3) into model.

`dicee.static_funcs.save_numpy_ndarray(*, data: numpy.ndarray, file_path: str)`

`dicee.static_funcs.numpy_data_type_changer(train_set: numpy.ndarray, num: int)
→ numpy.ndarray`

Detect most efficient data type for a given triples :param train_set: :param num: :return:

`dicee.static_funcs.save_checkpoint_model(model, path: str) → None`
 Store Pytorch model into disk

`dicee.static_funcs.store(trainer, trained_model, model_name: str = 'model',
 full_storage_path: str = None, save_embeddings_as_csv=False) → None`
 Store trained_model model and save embeddings into csv file. :param trainer: an instance of trainer class :param
 full_storage_path: path to save parameters. :param model_name: string representation of the name of the model.
 :param trained_model: an instance of BaseKGE see core.models.base_model . :param save_embeddings_as_csv:
 for easy access of embeddings. :return:

`dicee.static_funcs.add_noisy_triples(train_set: pandas.DataFrame, add_noise_rate: float)
 → pandas.DataFrame`
 Add randomly constructed triples :param train_set: :param add_noise_rate: :return:

`dicee.static_funcs.read_or_load_kg(args, cls)`

`dicee.static_funcs.initialize_model(args: dict, verbose=0) → Tuple[object, str]`

`dicee.static_funcs.load_json(p: str) → dict`

`dicee.static_funcs.save_embeddings(embeddings: numpy.ndarray, indexes, path: str) → None`
 Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:

`dicee.static_funcs.random_prediction(pre_trained_kge)`

`dicee.static_funcs.deploy_triple_prediction(pre_trained_kge, str_subject, str_predicate,
 str_object)`

`dicee.static_funcs.deploy_tail_entity_prediction(pre_trained_kge, str_subject, str_predicate,
 top_k)`

`dicee.static_funcs.deploy_head_entity_prediction(pre_trained_kge, str_object, str_predicate,
 top_k)`

`dicee.static_funcs.deploy_relation_prediction(pre_trained_kge, str_subject, str_object, top_k)`

`dicee.static_funcs.vocab_to_parquet(vocab_to_idx, name, path_for_serialization, print_into)`

`dicee.static_funcs.create_experiment_folder(folder_name='Experiments')`

`dicee.static_funcs.continual_training_setup_executor(executor) → None`

`dicee.static_funcs.exponential_function(x: numpy.ndarray, lam: float, ascending_order=True)
 → torch.FloatTensor`

`dicee.static_funcs.load_numpy(path) → numpy.ndarray`

`dicee.static_funcs.evaluate(entity_to_idx, scores, easy_answers, hard_answers)`
 # @TODO: CD: Renamed this function Evaluate multi hop query answering on different query types

`dicee.static_funcs.download_file(url, destination_folder='.')`

`dicee.static_funcs.download_files_from_url(base_url: str, destination_folder='.') → None`

Parameters

- **base_url** (e.g. <https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-dim128-epoch256-KvsAll>)
- **destination_folder** (e.g. "KINSHIP-Keci-dim128-epoch256-KvsAll")

`dicee.static_funcs.download_pretrained_model(url: str) → str`

`dicee.static_funcs.write_csv_from_model_parallel(path: str) → None`

Create

`dicee.static_funcs.from_pretrained_model_write_embeddings_into_csv(path: str) → None`

dicee.static_funcs_training

Functions

`make_iterable_verbose(→ Iterable)`

`evaluate_lp(model, triple_idx, num_entities, Evaluate model in a standard link prediction task
er_vocab, ...)`

`evaluate_bpe_lp(model, triple_idx, ..., info)`

`efficient_zero_grad(model)`

Module Contents

`dicee.static_funcs_training.make_iterable_verbose(iterable_object, verbose, desc='Default',
position=None, leave=True) → Iterable`

`dicee.static_funcs_training.evaluate_lp(model, triple_idx, num_entities,
er_vocab: Dict[Tuple, List], re_vocab: Dict[Tuple, List], info='Eval Starts')`

Evaluate model in a standard link prediction task

for each triple the rank is computed by taking the mean of the filtered missing head entity rank and the filtered missing tail entity rank :param model: :param triple_idx: :param info: :return:

`dicee.static_funcs_training.evaluate_bpe_lp(model, triple_idx: List[Tuple],
all_bpe_shaped_entities, er_vocab: Dict[Tuple, List], re_vocab: Dict[Tuple, List],
info='Eval Starts')`

`dicee.static_funcs_training.efficient_zero_grad(model)`

dicee.static_preprocess_funcs

Attributes

`enable_log`

Functions

<code>timeit(func)</code>	
<code>preprocesses_input_args(args)</code>	Sanity Checking in input arguments
<code>create_constraints(→ Tuple[dict, dict, dict, dict])</code>	
<code>get_er_vocab(data)</code>	
<code>get_re_vocab(data)</code>	
<code>get_ee_vocab(data)</code>	
<code>mapping_from_first_two_cols_to_third(train_se</code>	

Module Contents

`dicee.static_preprocess_funcs.enable_log = False`

`dicee.static_preprocess_funcs.timeit (func)`

`dicee.static_preprocess_funcs.preprocesses_input_args (args)`

Sanity Checking in input arguments

`dicee.static_preprocess_funcs.create_constraints (triples: numpy.ndarray)
→ Tuple[dict, dict, dict, dict]`

(1) Extract domains and ranges of relations

(2) Store a mapping from relations to entities that are outside of the domain and range. Create constraints entities based on the range of relations :param triples: :return:

`dicee.static_preprocess_funcs.get_er_vocab (data)`

`dicee.static_preprocess_funcs.get_re_vocab (data)`

`dicee.static_preprocess_funcs.get_ee_vocab (data)`

`dicee.static_preprocess_funcs.mapping_from_first_two_cols_to_third (train_set_idx)`

`dicee.trainer`

Submodules

`dicee.trainer.dice_trainer`

Classes

<code>DICE_Trainer</code>	DICE_Trainer implement
---------------------------	------------------------

Functions

```
load_term_mapping([file_path])
```

```
initialize_trainer(...)
```

```
get_callbacks(args)
```

Module Contents

```
dicee.trainer.dice_trainer.load_term_mapping(file_path=str)
```

```
dicee.trainer.dice_trainer.initialize_trainer(args, callbacks)  
→ dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.model_parallelism.TensorParallel | dicee.trainer.torch_trainer_ddp
```

```
dicee.trainer.dice_trainer.get_callbacks(args)
```

```
class dicee.trainer.dice_trainer.DICE_Trainer(args, is_continual_training, storage_path,  
evaluator=None)
```

DICE_Trainer implement

- 1- Pytorch Lightning trainer (<https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html>)
- 2- Multi-GPU Trainer(<https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html>)
- 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start (knowledge_graph)

- (1) Initialize training.
- (2) Load model
- (3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

initialize_trainer (*callbacks: List*)

→ `lightning.Trainer` | `diccee.trainer.model_parallelism.TensorParallel` | `diccee.trainer.torch_trainer.TorchTrainer` | `diccee.t`

Initialize Trainer from input arguments

initialize_or_load_model ()

init_dataloader (*dataset: torch.utils.data.Dataset*) → `torch.utils.data.DataLoader`

init_dataset () → `torch.utils.data.Dataset`

start (*knowledge_graph: diccee.knowledge_graph.KG* | *numpy.memmap*)

→ `Tuple[diccee.models.base_model.BaseKGE, str]`

Start the training

- (1) Initialize Trainer
- (2) Initialize or load a pretrained KGE model

in DDP setup, we need to load the memory map of already read/index KG.

k_fold_cross_validation (*dataset*) → `Tuple[diccee.models.base_model.BaseKGE, str]`

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split,**
 - 2.1 initialize trainer and model
 - 2.2. Train model with configuration provided in args.
 - 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns

model

diccee.trainer.model_parallelism

Classes

TensorParallel

Abstract class for Trainer class for knowledge graph embedding models

Functions

<code>extract_input_outputs(z[, device])</code>	
<code>find_good_batch_size(train_loader, ensemble_model[, ...])</code>	ensem-
<code>forward_backward_update_loss(z, ensemble_model)</code>	ensem-

Module Contents

`dicee.trainer.model_parallelism.extract_input_outputs` (*z: list, device=None*)

`dicee.trainer.model_parallelism.find_good_batch_size` (*train_loader, ensemble_model, max_available_gpu_memory: float = 0.05*)

`dicee.trainer.model_parallelism.forward_backward_update_loss` (*z: Tuple, ensemble_model*)

class `dicee.trainer.model_parallelism.TensorParallel` (*args, callbacks*)

Bases: `dicee.abstracts.AbstractTrainer`

Abstract class for Trainer class for knowledge graph embedding models

Parameter

args

[str] ?

callbacks: list

?

models = []

get_ensemble()

fit (**args, **kwargs*)

Train model

batchwisefit (**args, **kwargs*)

Train model

torch_buggy_fit (**args, **kwargs*)

Train model

`dicee.trainer.torch_trainer`

Classes

<code>TorchTrainer</code>	TorchTrainer for using single GPU or multi CPUs on a single node
---------------------------	------------------------------------------------------------------

Module Contents

class `dicee.trainer.torch_trainer.TorchTrainer` (*args*, *callbacks*)

Bases: `dicee.abstracts.AbstractTrainer`

TorchTrainer for using single GPU or multi CPUs on a single node

Arguments

`callbacks`: list of Abstract callback instances

`loss_function` = None

`optimizer` = None

`model` = None

`train_dataloaders` = None

`training_step` = None

`process`

`fit` (**args*, *train_dataloaders*, ***kwargs*) → None

Training starts

Arguments

kwargs:Tuple

empty dictionary

Return type

batch loss (float)

forward_backward_update (*x_batch: torch.Tensor*, *y_batch: torch.Tensor*) → torch.Tensor

Compute forward, loss, backward, and parameter update

Arguments

Return type

batch loss (float)

extract_input_outputs_set_device (*batch: list*) → Tuple

Construct inputs and outputs from a batch of inputs with outputs From a batch of inputs and put

Arguments

Return type

(tuple) mini-batch on select device

dicee.trainer.torch_trainer_ddp

Classes

<code>TorchDDPTrainer</code>	A Trainer based on torch.nn.parallel.DistributedDataParallel
<code>NodeTrainer</code>	

Functions

<code>make_iterable_verbose</code> (\rightarrow Iterable)

Module Contents

`dicee.trainer.torch_trainer_ddp.make_iterable_verbose` (*iterable_object*, *verbose*,
desc='Default', *position*=None, *leave*=True) \rightarrow Iterable

class `dicee.trainer.torch_trainer_ddp.TorchDDPTrainer` (*args*, *callbacks*)

Bases: `dicee.abstracts.AbstractTrainer`

A Trainer based on torch.nn.parallel.DistributedDataParallel

Arguments

entity_idx
mapping.

relation_idx
mapping.

form
?

store
?

label_smoothing_rate
Using hard targets (0,1) drives weights to infinity. An outlier produces enormous gradients.

Return type
torch.utils.data.Dataset

fit (**args*, ***kwargs*)
Train model

class `dicee.trainer.torch_trainer_ddp.NodeTrainer` (*trainer*, *model*: torch.nn.Module,
train_dataset_loader: torch.utils.data.DataLoader, *callbacks*, *num_epochs*: int)

trainer

local_rank

global_rank

```

optimizer

train_dataset_loader

loss_func

callbacks

model

num_epochs

loss_history = []

ctx

scaler

extract_input_outputs(z: list)

train()
    Training loop for DDP

```

Classes

DICE_Trainer

DICE_Trainer implement

Package Contents

```
class dicee.trainer.DICE_Trainer(args, is_continual_training, storage_path, evaluator=None)
```

DICE_Trainer implement

- 1- Pytorch Lightning trainer (<https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html>)
- 2- Multi-GPU Trainer(<https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html>)
- 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start (*knowledge_graph*)

- (1) Initialize training.
- (2) Load model
- (3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

initialize_trainer (*callbacks: List*)

→ *lightning.Trainer* | *dicее.trainer.model_parallelism.TensorParallel* | *dicее.trainer.torch_trainer.TorchTrainer* | *dicее.t*

Initialize Trainer from input arguments

initialize_or_load_model ()

init_dataloader (*dataset: torch.utils.data.Dataset*) → *torch.utils.data.DataLoader*

init_dataset () → *torch.utils.data.Dataset*

start (*knowledge_graph: dicее.knowledge_graph.KG* | *numpy.memmap*)

→ *Tuple[dicее.models.base_model.BaseKGE, str]*

Start the training

- (1) Initialize Trainer
- (2) Initialize or load a pretrained KGE model

in DDP setup, we need to load the memory map of already read/index KG.

k_fold_cross_validation (*dataset*) → *Tuple[dicее.models.base_model.BaseKGE, str]*

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split,**
 - 2.1 initialize trainer and model
 - 2.2. Train model with configuration provided in args.
 - 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns

model

14.2 Attributes

`__version__`

14.3 Classes

<i>Pyke</i>	A Physical Embedding Model for Knowledge Graphs
<i>DistMult</i>	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
<i>KeciBase</i>	Without learning dimension scaling
<i>Keci</i>	Base class for all neural network modules.
<i>TransE</i>	Translating Embeddings for Modeling
<i>DeCaL</i>	Base class for all neural network modules.
<i>DualE</i>	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)
<i>ComplEx</i>	Base class for all neural network modules.
<i>AConEx</i>	Additive Convolutional ComplEx Knowledge Graph Embeddings
<i>AConvO</i>	Additive Convolutional Octonion Knowledge Graph Embeddings
<i>AConvQ</i>	Additive Convolutional Quaternion Knowledge Graph Embeddings
<i>ConvQ</i>	Convolutional Quaternion Knowledge Graph Embeddings
<i>ConvO</i>	Base class for all neural network modules.
<i>ConEx</i>	Convolutional ComplEx Knowledge Graph Embeddings
<i>QMult</i>	Base class for all neural network modules.
<i>OMult</i>	Base class for all neural network modules.
<i>Shallom</i>	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
<i>LFMult</i>	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
<i>PykeenKGE</i>	A class for using knowledge graph embedding models implemented in Pykeen
<i>Byte</i>	Base class for all neural network modules.
<i>BaseKGE</i>	Base class for all neural network modules.
<i>EnsembleKGE</i>	
<i>DICE_Trainer</i>	DICE_Trainer implement
<i>KGE</i>	Knowledge Graph Embedding Class for interactive usage of pre-trained models
<i>Execute</i>	A class for Training, Retraining and Evaluation a model.
<i>BPE_NegativeSamplingDataset</i>	An abstract class representing a Dataset.
<i>MultiLabelDataset</i>	An abstract class representing a Dataset.
<i>MultiClassClassificationDataset</i>	Dataset for the 1vsALL training strategy
<i>OnevsAllDataset</i>	Dataset for the 1vsALL training strategy
<i>KvsAll</i>	Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
<i>AllvsAll</i>	Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
<i>OnevsSample</i>	A custom PyTorch Dataset class for knowledge graph embeddings, which includes
<i>KvsSampleDataset</i>	KvsSample a Dataset:
<i>NegSampleDataset</i>	An abstract class representing a Dataset.
<i>TriplePredictionDataset</i>	Triple Dataset

continues on next page

Table 3 – continued from previous page

<i>CVDDataModule</i>	Create a Dataset for cross validation
<i>QueryGenerator</i>	

14.4 Functions

<i>create_recipriocal_triples</i> (x)	Add inverse triples into dask dataframe
<i>get_er_vocab</i> (data[, file_path])	
<i>get_re_vocab</i> (data[, file_path])	
<i>get_ee_vocab</i> (data[, file_path])	
<i>timeit</i> (func)	
<i>save_pickle</i> (*[, data, file_path])	
<i>load_pickle</i> ([file_path])	
<i>load_term_mapping</i> ([file_path])	
<i>select_model</i> (args[, is_continual_training, storage_path])	
<i>load_model</i> (→ Tuple[object, Tuple[dict, dict]])	Load weights and initialize pytorch module from namespace arguments
<i>load_model_ensemble</i> (...)	Construct Ensemble Of weights and initialize pytorch module from namespace arguments
<i>save_numpy_ndarray</i> (*[, data, file_path])	
<i>numpy_data_type_changer</i> (→ numpy.ndarray)	Detect most efficient data type for a given triples
<i>save_checkpoint_model</i> (→ None)	Store Pytorch model into disk
<i>store</i> (→ None)	Store trained_model model and save embeddings into csv file.
<i>add_noisy_triples</i> (→ pandas.DataFrame)	Add randomly constructed triples
<i>read_or_load_kg</i> (args, cls)	
<i>intialize_model</i> (→ Tuple[object, str])	
<i>load_json</i> (→ dict)	
<i>save_embeddings</i> (→ None)	Save it as CSV if memory allows.
<i>random_prediction</i> (pre_trained_kge)	
<i>deploy_triple_prediction</i> (pre_trained_kge, str_subject, ...)	
<i>deploy_tail_entity_prediction</i> (pre_trained_kge, ...)	
<i>deploy_head_entity_prediction</i> (pre_trained_kge, ...)	

continues on next page

Table 4 – continued from previous page

<code>deploy_relation_prediction(pre_trained_kge,</code>	
<code>...)</code>	
<code>vocab_to_parquet(vocab_to_idx, name, ...)</code>	
<code>create_experiment_folder([folder_name])</code>	
<code>continual_training_setup_executor(→ None)</code>	
<code>exponential_function(→ torch.FloatTensor)</code>	
<code>load_numpy(→ numpy.ndarray)</code>	
<code>evaluate(entity_to_idx, scores, easy_answers, # @TODO: CD: Renamed this function</code>	
<code>hard_answers)</code>	
<code>download_file(url[, destination_folder])</code>	
<code>download_files_from_url(→ None)</code>	
<code>download_pretrained_model(→ str)</code>	
<code>write_csv_from_model_parallel(→ None)</code>	Create
<code>from_pretrained_model_write_embeddings_into</code>	
<code>None)</code>	
<code>mapping_from_first_two_cols_to_third(train_se</code>	
<code>timeit(func)</code>	
<code>load_term_mapping([file_path])</code>	
<code>reload_dataset(path, form_of_labelling, ...)</code>	Reload the files from disk to construct the Pytorch dataset
<code>construct_dataset(→ torch.utils.data.Dataset)</code>	

14.5 Package Contents

class `dicee.Pyke` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

A Physical Embedding Model for Knowledge Graphs

name = 'Pyke'

dist_func

margin = 1.0

forward_triples (*x: torch.LongTensor*)

Parameters

x

class `dicee.DistMult` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

```
name = 'DistMult'
```

```
k_vs_all_score(emb_h: torch.FloatTensor, emb_r: torch.FloatTensor, emb_E: torch.FloatTensor)
```

Parameters

- `emb_h`
- `emb_r`
- `emb_E`

```
forward_k_vs_all(x: torch.LongTensor)
```

```
forward_k_vs_sample(x: torch.LongTensor, target_entity_idx: torch.LongTensor)
```

```
score(h, r, t)
```

```
class dicee.KeciBase(args)
```

Bases: `Keci`

Without learning dimension scaling

```
name = 'KeciBase'
```

```
requires_grad_for_interactions = False
```

```
class dicee.Keci(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp (*hp, rp*)

Compute $\text{sigma_pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k$

sigma_pp captures the interactions between along p bases For instance, let p e_1, e_2, e_3 , we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):

 results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., $e_1 e_1, e_1 e_2, e_1 e_3$,

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_qq (*hq, rq*)

Compute $\text{sigma_qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k$ sigma_qq captures the interactions between along q bases For instance, let q e_1, e_2, e_3 , we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

 results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., $e_1 e_1, e_1 e_2, e_1 e_3$,

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_pq (**, hp, hq, rp, rq*)

$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

 sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

apply_coefficients (*hp, hq, rp, rq*)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (*h0, hp, hq, r0, rp, rq*)

Compute our CL multiplication

$$h = h_0 + \sum_{i=1}^p h_i e_i + \sum_{j=p+1}^{p+q} h_j e_j \quad r = r_0 + \sum_{i=1}^p r_i e_i + \sum_{j=p+1}^{p+q} r_j e_j$$

$$e_i^2 = +1 \text{ for } i \leq p \quad e_j^2 = -1 \text{ for } p < j \leq p+q \quad e_i e_j = -e_j e_i \text{ for } i$$

e_j

$$h r = \sigma_0 + \sigma_p + \sigma_q + \sigma_{pp} + \sigma_q + \sigma_{pq} \text{ where}$$

$$(1) \sigma_0 = h_0 r_0 + \sum_{i=1}^p (h_0 r_i - h_i r_0) e_i - \sum_{j=p+1}^{p+q} (h_j r_j) e_j$$

$$(2) \sigma_p = \sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$$

$$(3) \sigma_q = \sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$$

$$(4) \sigma_{pp} = \sum_{i=1}^{p-1} \sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k$$

$$(5) \sigma_{qq} = \sum_{j=1}^{p+q-1} \sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k$$

$$(6) \sigma_{pq} = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

construct_cl_multivector (*x: torch.FloatTensor, r: int, p: int, q: int*)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{\{p,q\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor with (n,r) shape*)
- **ap** (*torch.FloatTensor with (n,r,p) shape*)
- **aq** (*torch.FloatTensor with (n,r,q) shape*)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations \mathbb{R}^d .
- (2) Construct head entity and relation embeddings according to $Cl_{\{p,q\}}(\mathbb{R}^d)$.
- (3) Perform CL multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical **Parameter** ——— x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n, **IEI**) shape

construct_batch_selected_cl_multivector (*x: torch.FloatTensor, r: int, p: int, q: int*)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of batches multivectors $Cl_{\{p,q\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (torch.FloatTensor with (n,k, m) shape)
- **ap** (torch.FloatTensor with (n,k, m, p) shape)
- **aq** (torch.FloatTensor with (n,k, m, q) shape)

forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,2) shape

target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.

rtype

torch.FloatTensor with (n, k) shape

score (h, r, t)

forward_triples (x: torch.Tensor) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype

torch.FloatTensor with (n) shape

```
class dicee.TransE (args)
```

Bases: `dicee.models.base_model.BaseKGE`

Translating Embeddings for Modeling Multi-relational Data <https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf>

```
name = 'TransE'
```

```
margin = 4
```

```
score (head_ent_emb, rel_ent_emb, tail_ent_emb)
```

```
forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor
```

```
class dicee.DeCaL (args)
```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
```

(continues on next page)

(continued from previous page)

```

def __init__(self) -> None:
    super().__init__()
    self.conv1 = nn.Conv2d(1, 20, 5)
    self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation_embeddings

p

q

r

re

forward_triples (*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl_pqr (*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) → output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb, list_r_emb, list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s_0 = h_0 r_0 t_0 s_1 = \sum_{i=1}^p h_i r_i t_0 s_2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s_3 = \sum_{i=1}^q (h_0 r_i t_i + h_i r_0 t_i) s_4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s_5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i)$$

and return:

$$sigma_0t = \sigma_0 \cdot t_0 = s0 + s1 - s2s3, s4ands5$$

```
compute_sigmas_multivect (list_h_emb, list_r_emb)
```

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (\text{model the interactions between } e_i \text{ and } e_{i'} \text{ for } 1 \leq i, i' \leq p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'})$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (\text{interactionsnbetween} e_i \text{and} e_j \text{for } 1 \leq i \leq p \text{ and } p+1 \leq j \leq p+q) \sigma_p r = \sum_{i=1}^p$$

$$\text{forward_k_vs_all}(x: \text{torch.Tensor}) \rightarrow \text{torch.FloatTensor}$$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to $\text{Cl}_{\{p, q, r\}}(\mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, **IE**) shape

apply_coefficients ($h0, hp, hq, hk, r0, rp, rq, rk$)

Multiplying a base vector with its scalar coefficient

```
construct_cl_multivector (x: torch.FloatTensor, re: int, p: int, q: int, r: int)
    → tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]
```

Construct a batch of multivectors $\text{Cl}_{\{p,q,r\}}(\mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor*)
- **ap** (*torch.FloatTensor*)
- **aq** (*torch.FloatTensor*)
- **ar** (*torch.FloatTensor*)

$$\text{compute_sigma_pp}(hp, rp)$$

Compute .. math:

$$\sigma_{p,p}^* = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (x_i y_{i'} - x_{i'} y_i)$$

$\text{sigma_}\{pp\}$ captures the interactions between along p bases For instance, let $p \in \{e_1, e_2, e_3\}$, we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

```

results = []
for i in range(p - 1):
    for k in range(i + 1, p):
        results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2)
assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., $e_1 e_1, e_1 e_2, e_1 e_3,$

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_qq (hq, rq)

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) E_{q,16}$$

$\text{sigma_}\{q\}$ captures the interactions between along q bases For instance, let $q \in \{e_1, e_2, e_3\}$, we compute interactions between $e_1 e_2, e_1 e_3$, and $e_2 e_3$ This can be implemented with a nested two for loops

```

results = []
for j in range(q - 1):
    for k in range(j + 1, q):
        results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2)
assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p , e.g., $e_1 e_1, e_1 e_2, e_1 e_3,$

$e_2 e_1, e_2 e_2, e_2 e_3, e_3 e_1, e_3 e_2, e_3 e_3$

Then select the triangular matrix without diagonals: $e_1 e_2, e_1 e_3, e_2 e_3$.

compute_sigma_rr (hk, rk)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^p (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq ($*, hp, hq, rp, rq$)

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

```

results = []
sigma_pq = torch.zeros(b, r, p, q)
for i in range(p):

```

```

    for j in range(q):
        sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

```

```

print(sigma_pq.shape)

```


compute_sigma_pr (*, hp, hk, rp, rk)

Compute

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

 sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_qr (*, hq, hk, rq, rk)

$$\sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

 sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

class dicee.DualE (args)

Bases: *dicee.models.base_model.BaseKGE*

Dual Quaternion Knowledge Graph Embeddings (<https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657>)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score (e_1_h, e_2_h, e_3_h, e_4_h, e_5_h, e_6_h, e_7_h, e_8_h, e_1_t, e_2_t, e_3_t, e_4_t, e_5_t, e_6_t, e_7_t, e_8_t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples (idx_triple: torch.tensor) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

`forward_k_vs_all(x)`

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

$\mathbf{T}(x: \text{torch.tensor}) \rightarrow \text{torch.tensor}$

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

`class dicee.Complex(args)`

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training (bool)` – Boolean represents whether this module is in training or evaluation mode.

`name = 'Complex'`

```
static score(head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor,
            tail_ent_emb: torch.FloatTensor)
```

```
static k_vs_all_score(emb_h: torch.FloatTensor, emb_r: torch.FloatTensor,
                    emb_E: torch.FloatTensor)
```

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

```
forward_k_vs_all(x: torch.LongTensor) → torch.FloatTensor
```

```
forward_k_vs_sample(x: torch.LongTensor, target_entity_idx: torch.LongTensor)
```

```
class dicee.AConEx(args)
```

Bases: `dicee.models.base_model.BaseKGE`

Additive Convolutional ComplEx Knowledge Graph Embeddings

```
name = 'AConEx'
```

```
conv2d
```

```
fc_num_input
```

```
fc1
```

```
norm_fc1
```

```
bn_conv2d
```

```
feature_map_dropout
```

```
residual_convolution(C_1: Tuple[torch.Tensor, torch.Tensor],
                    C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
```

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

```
forward_k_vs_all(x: torch.Tensor) → torch.FloatTensor
```

```
forward_triples(x: torch.Tensor) → torch.FloatTensor
```

Parameters

x

```
forward_k_vs_sample(x: torch.Tensor, target_entity_idx: torch.Tensor)
```

```
class dicee.AConvO(args: dict)
```

Bases: `dicee.models.base_model.BaseKGE`

Additive Convolutional Octonion Knowledge Graph Embeddings

```
name = 'AConvO'
```

```
conv2d
```

```
fc_num_input
```

```

    fc1

    bn_conv2d

    norm_fc1

    feature_map_dropout

    static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                               emb_rel_e5, emb_rel_e6, emb_rel_e7)

    residual_convolution(O_1, O_2)

    forward_triples(x: torch.Tensor) → torch.Tensor

    Parameters
    x

    forward_k_vs_all(x: torch.Tensor)
        Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
        [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
        Entities)
class dicee.AConvQ(args)
    Bases: dicee.models.base_model.BaseKGE
    Additive Convolutional Quaternion Knowledge Graph Embeddings

    name = 'AConvQ'

    entity_embeddings

    relation_embeddings

    conv2d

    fc_num_input

    fc1

    bn_conv1

    bn_conv2

    feature_map_dropout

    residual_convolution(Q_1, Q_2)

    forward_triples(indexed_triple: torch.Tensor) → torch.Tensor

    Parameters
    x

    forward_k_vs_all(x: torch.Tensor)
        Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
        [0.0,0.1,...,0.8], shape=> (1, Entities) Given a batch of head entities and relations => shape (size of batch,|
        Entities)

```

```

class dicee.ConvQ(args)
    Bases: dicee.models.base_model.BaseKGE
    Convolutional Quaternion Knowledge Graph Embeddings
    name = 'ConvQ'
    entity_embeddings
    relation_embeddings
    conv2d
    fc_num_input
    fc1
    bn_conv1
    bn_conv2
    feature_map_dropout
    residual_convolution(Q_1, Q_2)
    forward_triples(indexed_triple: torch.Tensor) → torch.Tensor

```

Parameters

x

forward_k_vs_all (*x*: torch.Tensor)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch, l Entities)

```

class dicee.ConvO(args: dict)

```

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer (*emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4, emb_rel_e5, emb_rel_e6, emb_rel_e7*)

residual_convolution (*O_1, O_2*)

forward_triples (*x: torch.Tensor*) → torch.Tensor

Parameters

x

forward_k_vs_all (*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.**ConEx** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional ComplEx Knowledge Graph Embeddings

name = 'ConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

```
residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                       C_2: Tuple[torch.Tensor, torch.Tensor]) → torch.FloatTensor
```

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

```
forward_k_vs_all (x: torch.Tensor) → torch.FloatTensor
```

```
forward_triples (x: torch.Tensor) → torch.FloatTensor
```

Parameters

x

```
forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)
```

```
class dicee.QMult (args)
```

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super ().__init__ ()
        self.conv1 = nn.Conv2d (1, 20, 5)
        self.conv2 = nn.Conv2d (20, 20, 5)

    def forward (self, x):
        x = F.relu (self.conv1 (x))
        return F.relu (self.conv2 (x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'QMult'
```

```
explicit = True
```

```
quaternion_multiplication_followed_by_inner_product (h, r, t)
```

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer (*x*: torch.FloatTensor) → torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters

x – The vector.

Returns

The normalized vector.

score (*head_ent_emb*: torch.FloatTensor, *rel_ent_emb*: torch.FloatTensor, *tail_ent_emb*: torch.FloatTensor)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

Parameters

- **bpe_head_ent_emb**
- **bpe_rel_ent_emb**
- **E**

forward_k_vs_all (*x*)

Parameters

x

forward_k_vs_sample (*x*, *target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, **Entities**) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.OMult (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:


```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'OMult'

static octonion_normalizer (*emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4, emb_rel_e5, emb_rel_e6, emb_rel_e7*)

score (*head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor, tail_ent_emb: torch.FloatTensor*)

k_vs_all_score (*bpe_head_ent_emb, bpe_rel_ent_emb, E*)

forward_k_vs_all (*x*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples, i.e., $[\text{score}(h,r,x) | x \text{ in Entities}] \Rightarrow [0.0, 0.1, \dots, 0.8]$, shape $\Rightarrow (1, |\text{Entities}|)$ Given a batch of head entities and relations \Rightarrow shape (size of batch, |Entities|)

class `dicee.Shallom` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

A shallow neural model for relation prediction (<https://arxiv.org/abs/2101.09090>)

name = 'Shallom'

shallom

get_embeddings () \rightarrow Tuple[numpy.ndarray, None]

forward_k_vs_all (*x*) \rightarrow torch.FloatTensor

forward_triples (*x*) \rightarrow torch.FloatTensor

Parameters

x

Returns

class `dicee.LFMult` (*args*)

Bases: `dicee.models.base_model.BaseKGE`

Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: $f(x) = \sum_{i=0}^{d-1} a_i x^i$ and use the three differents scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

name = 'LFMult'

entity_embeddings

relation_embeddings

degree

m

x_values

forward_triples (*idx_triple*)

Parameters

x

construct_multi_coeff (*x*)

poly_NN (*x, coefh, coefr, coeft*)

Constructing a 2 layers NN to represent the embeddings. $h = \sigma(wh^T x + bh)$, $r = \sigma(wr^T x + br)$, $t = \sigma(wt^T x + bt)$

linear (*x, w, b*)

scalar_batch_NN (*a, b, c*)

element wise multiplication between a,b and c: Inputs : a, b, c ==> torch.tensor of size batch_size x m x d
Output : a tensor of size batch_size x d

tri_score (*coeff_h, coeff_r, coeff_t*)

this part implement the trilinear scoring techniques:

$\text{score}(h,r,t) = \int_0^1 h(x)r(x)t(x) dx = \sum_{i,j,k=0}^{d-1} \text{dfrac}\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$

1. generate the range for i,j and k from [0 d-1]
2. perform $\text{dfrac}\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$ in parallel for every batch
3. take the sum over each batch

vtp_score (*h, r, t*)

this part implement the vector triple product scoring techniques:

$\text{score}(h,r,t) = \int_0^1 h(x)r(x)t(x) dx = \sum_{i,j,k=0}^{d-1} \text{dfrac}\{a_i*c_j*b_k - b_i*c_j*a_k\}\{(1+(i+j)\%d)(1+k)\}$

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum
4. take the sum over each batch

```

comp_func (h, r, t)
    this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial (coeff, x, degree)
    This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer
    [0,1,...d] and return a vector tensor (coeff[0][0] + coeff[0][1]x +...+ coeff[0][d]x^d,

        coeff[1][0] + coeff[1][1]x +...+ coeff[1][d]x^d)

pop (coeff, x, degree)
    This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix
    tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,...d]

        and return a tensor (coeff[0][0] + coeff[0][1]x +...+ coeff[0][d]x^d,

        coeff[1][0] + coeff[1][1]x +...+ coeff[1][d]x^d)

class dicee.PykeenKGE (args: dict)
    Bases: dicee.models.base_model.BaseKGE
    A class for using knowledge graph embedding models implemented in Pykeen
    Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Py-
    keen_HolE:

    model_kwargs

    name

    model

    loss_history = []

    args

    entity_embeddings = None

    relation_embeddings = None

    forward_k_vs_all (x: torch.LongTensor)
        # => Explicit version by this we can apply bn and dropout

        # (1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r =
        self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:

            h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
            self.last_dim)

        # (3) Reshape all entities. if self.last_dim > 0:

            t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

        else:

            t = self.entity_embeddings.weight

        # (4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r,
        all_entities=t, slice_size=1)

```

```

forward_triples (x: torch.LongTensor) → torch.FloatTensor
    # => Explicit version by this we can apply bn and dropout

    # (1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t =
    self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:
        h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
        self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

    # (3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)

```

```

class dicee.ByteE(*args, **kwargs)

```

Bases: `dicee.models.base_model.BaseKGE`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```

import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super() __init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))

```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ByteE'

config

temperature = 0.5

topk = 2

transformer

lm_head

loss_function(*yhat_batch*, *y_batch*)

Parameters

- **yhat_batch**
- **y_batch**

forward(*x*: *torch.LongTensor*)

Parameters

x (*B by T tensor*)

generate(*idx*, *max_new_tokens*, *temperature=1.0*, *top_k=None*)

Take a conditioning sequence of indices *idx* (LongTensor of shape (b,t)) and complete the sequence *max_new_tokens* times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in `model.eval()` mode of operation for this.

training_step(*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- **Tensor** - The loss tensor
- **dict** - A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- **None** - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False
```

(continues on next page)

(continued from previous page)

```
# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches > 1`, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

```
class dicee.BaseKGE (args: dict)
```

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

```

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)

```

Parameters

$\mathbf{x} (B \times 2 \times T)$

```

forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors

    Parameters
    -----

init_params_with_sanity_checking()

forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
         y_idx: torch.LongTensor = None)

    Parameters
    -----
    • x
    • y_idx
    • ordered_bpe_entities

forward_triples (x: torch.LongTensor) → torch.Tensor

    Parameters
    -----
    • x

forward_k_vs_all (*args, **kwargs)

forward_k_vs_sample (*args, **kwargs)

get_triple_representation (idx_hrt)

get_head_relation_representation (indexed_triple)

get_sentence_representation (x: torch.LongTensor)

    Parameters
    -----
    • (b (x shape)
    • 3
    • t)

get_bpe_head_and_relation_representation (x: torch.LongTensor)
    → Tuple[torch.FloatTensor, torch.FloatTensor]

    Parameters
    -----
    • x (B x 2 x T)

get_embeddings () → Tuple[numpy.ndarray, numpy.ndarray]

dicee.create_recipriocal_triples (x)
    Add inverse triples into dask dataframe :param x: :return:

dicee.get_er_vocab (data, file_path: str = None)

dicee.get_re_vocab (data, file_path: str = None)

dicee.get_ee_vocab (data, file_path: str = None)

dicee.timeit (func)

dicee.save_pickle (*, data: object = None, file_path=str)

```



```

dicee.load_pickle (file_path=str)

dicee.load_term_mapping (file_path=str)

dicee.select_model (args: dict, is_continual_training: bool = None, storage_path: str = None)

dicee.load_model (path_of_experiment_folder: str, model_name='model.pt', verbose=0)
    → Tuple[object, Tuple[dict, dict]]
    Load weights and initialize pytorch module from namespace arguments

dicee.load_model_ensemble (path_of_experiment_folder: str)
    → Tuple[dicee.models.base_model.BaseKGE, Tuple[pandas.DataFrame, pandas.DataFrame]]
    Construct Ensemble Of weights and initialize pytorch module from namespace arguments
    (1) Detect models under given path
    (2) Accumulate parameters of detected models
    (3) Normalize parameters
    (4) Insert (3) into model.

dicee.save_numpy_ndarray (*, data: numpy.ndarray, file_path: str)

dicee.numpy_data_type_changer (train_set: numpy.ndarray, num: int) → numpy.ndarray
    Detect most efficient data type for a given triples :param train_set: :param num: :return:

class dicee.EnsembleKGE (seed_model)

    models = []

    optimizers = []

    loss_history = []

    name

    train_mode = True

    named_children()

    property example_input_array

    parameters()

    modules()

    __iter__()

    __len__()

    eval()

    to(device)

    mem_of_model()

    __call__(x_batch)

    step()

```

```

__str__()

dicee.save_checkpoint_model(model, path: str) → None
    Store Pytorch model into disk

dicee.store(trainer, trained_model, model_name: str = 'model', full_storage_path: str = None,
            save_embeddings_as_csv=False) → None
    Store trained_model model and save embeddings into csv file. :param trainer: an instance of trainer class :param
    full_storage_path: path to save parameters. :param model_name: string representation of the name of the model.
    :param trained_model: an instance of BaseKGE see core.models.base_model . :param save_embeddings_as_csv:
    for easy access of embeddings. :return:

dicee.add_noisy_triples(train_set: pandas.DataFrame, add_noise_rate: float) → pandas.DataFrame
    Add randomly constructed triples :param train_set: :param add_noise_rate: :return:

dicee.read_or_load_kg(args, cls)

dicee.intialize_model(args: dict, verbose=0) → Tuple[object, str]

dicee.load_json(p: str) → dict

dicee.save_embeddings(embeddings: numpy.ndarray, indexes, path: str) → None
    Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:

dicee.random_prediction(pre_trained_kge)

dicee.deploy_triple_prediction(pre_trained_kge, str_subject, str_predicate, str_object)

dicee.deploy_tail_entity_prediction(pre_trained_kge, str_subject, str_predicate, top_k)

dicee.deploy_head_entity_prediction(pre_trained_kge, str_object, str_predicate, top_k)

dicee.deploy_relation_prediction(pre_trained_kge, str_subject, str_object, top_k)

dicee.vocab_to_parquet(vocab_to_idx, name, path_for_serialization, print_into)

dicee.create_experiment_folder(folder_name='Experiments')

dicee.continual_training_setup_executor(executor) → None

dicee.exponential_function(x: numpy.ndarray, lam: float, ascending_order=True) → torch.FloatTensor

dicee.load_numpy(path) → numpy.ndarray

dicee.evaluate(entity_to_idx, scores, easy_answers, hard_answers)
    # @TODO: CD: Renamed this function Evaluate multi hop query answering on different query types

dicee.download_file(url, destination_folder='.')

dicee.download_files_from_url(base_url: str, destination_folder='.') → None

```

Parameters

- **base_url** (e.g. <https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-dim128-epoch256-KvsAll>)
- **destination_folder** (e.g. "KINSHIP-Keci-dim128-epoch256-KvsAll")

```

dicee.download_pretrained_model(url: str) → str

```

`dicee.write_csv_from_model_parallel(path: str) → None`

Create

`dicee.from_pretrained_model_write_embeddings_into_csv(path: str) → None`

`class dicee.DICE_Trainer(args, is_continual_training, storage_path, evaluator=None)`

DICE_Trainer implement

- 1- Pytorch Lightning trainer (<https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html>)
- 2- Multi-GPU Trainer(<https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html>)
- 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start (knowledge_graph)

- (1) Initialize training.
- (2) Load model
- (3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

`initialize_trainer(callbacks: List)`

→ `lightning.Trainer` | `dicee.trainer.model_parallelism.TensorParallel` | `dicee.trainer.torch_trainer.TorchTrainer` | `dicee.t`

Initialize Trainer from input arguments

`initialize_or_load_model()`

`init_dataloader(dataset: torch.utils.data.Dataset) → torch.utils.data.DataLoader`

`init_dataset() → torch.utils.data.Dataset`

start (*knowledge_graph: dicee.knowledge_graph.KG | numpy.memmap*)
 → Tuple[*dicee.models.base_model.BaseKGE*, str]

Start the training

- (1) Initialize Trainer
- (2) Initialize or load a pretrained KGE model

in DDP setup, we need to load the memory map of already read/index KG.

k_fold_cross_validation (*dataset*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split**,
 2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns

model

class *dicee.KGE* (*path=None, url=None, construct_ensemble=False, model_name=None*)

Bases: *dicee.abstracts.BaseInteractiveKGE*

Knowledge Graph Embedding Class for interactive usage of pre-trained models

__str__ ()

to (*device: str*) → None

get_transductive_entity_embeddings (*indices: torch.LongTensor | List[str], as_pytorch=False, as_numpy=False, as_list=True*) → torch.FloatTensor | numpy.ndarray | List[float]

create_vector_database (*collection_name: str, distance: str, location: str = 'localhost', port: int = 6333*)

generate (*h="", r=""*)

eval_lp_performance (*dataset=List[Tuple[str, str, str]], filtered=True*)

predict_missing_head_entity (*relation: List[str] | str, tail_entity: List[str] | str, within=None*)
 → Tuple

Given a relation and a tail entity, return top k ranked head entity.

$\text{argmax}_{\{e \in E\}} f(e, r, t)$, where $r \in R, t \in E$.

Parameter

relation: Union[List[str], str]

String representation of selected relations.

tail_entity: Union[List[str], str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_relations (*head_entity: List[str] | str, tail_entity: List[str] | str, within=None*)
→ Tuple

Given a head entity and a tail entity, return top k ranked relations.

$\text{argmax}_{\{r \in R\}} f(h,r,t)$, where h, t in E.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_tail_entity (*head_entity: List[str] | str, relation: List[str] | str, within: List[str] = None*) → torch.FloatTensor

Given a head entity and a relation, return top k ranked entities

$\text{argmax}_{\{e \in E\}} f(h,r,e)$, where h in E and r in R.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

predict (*, *h: List[str] | str = None, r: List[str] | str = None, t: List[str] | str = None, within=None, logits=True*) → torch.FloatTensor

Parameters

- **logits**
- **h**
- **r**

- **t**
- **within**

predict_topk (*, *h*: *str* | *List[str]* = *None*, *r*: *str* | *List[str]* = *None*, *t*: *str* | *List[str]* = *None*, *topk*: *int* = 10, *within*: *List[str]* = *None*)

Predict missing item in a given triple.

Parameter

head_entity: Union[str, List[str]]

String representation of selected entities.

relation: Union[str, List[str]]

String representation of selected relations.

tail_entity: Union[str, List[str]]

String representation of selected entities.

k: int

Highest ranked k item.

Returns: Tuple

Highest K scores and items

triple_score (*h*: *List[str]* | *str* = *None*, *r*: *List[str]* | *str* = *None*, *t*: *List[str]* | *str* = *None*, *logits*=*False*)
→ torch.FloatTensor

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

logits: bool

If logits is True, unnormalized score returned

Returns: Tuple

pytorch tensor of triple score

t_norm (*tens_1*: torch.Tensor, *tens_2*: torch.Tensor, *tnorm*: *str* = 'min') → torch.Tensor

tensor_t_norm (*subquery_scores*: torch.FloatTensor, *tnorm*: *str* = 'min') → torch.FloatTensor

Compute T-norm over [0,1] ^{n imes d} where n denotes the number of hops and d denotes number of entities

t_conorm (*tens_1*: torch.Tensor, *tens_2*: torch.Tensor, *tconorm*: *str* = 'min') → torch.Tensor

```

negnorm (tens_1: torch.Tensor, lambda_: float, neg_norm: str = 'standard') → torch.Tensor

return_multi_hop_query_results (aggregated_query_for_all_entities, k: int, only_scores)

single_hop_query_answering (query: tuple, only_scores: bool = True, k: int = None)

answer_multi_hop_query (query_type: str = None, query: Tuple[str | Tuple[str, str], Ellipsis] = None,
    queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, tnorm: str = 'prod',
    neg_norm: str = 'standard', lambda_: float = 0.0, k: int = 10, only_scores=False)
    → List[Tuple[str, torch.Tensor]]

# @TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a
static function

Find an answer set for EPFO queries including negation and disjunction

```

Parameter

query_type: str The type of the query, e.g., “2p”.

query: Union[str, Tuple[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.

queries: List of Tuple[Union[str, Tuple[str, str]], ...]

tnorm: str The t-norm operator.

neg_norm: str The negation norm.

lambda_: float lambda parameter for sugeno and yager negation norms

k: int The top-k substitutions for intermediate variables.

returns

- List[Tuple[str, torch.Tensor]]
- Entities and corresponding scores sorted in the descening order of scores

```

find_missing_triples (confidence: float, entities: List[str] = None, relations: List[str] = None,
    topk: int = 10, at_most: int = sys.maxsize) → Set

```

Find missing triples

Iterative over a set of entities E and a set of relation R :

orall e in E and orall r in R f(e,r,x)

Return (e,r,x)

otin G and f(e,r,x) > confidence

confidence: float

A threshold for an output of a sigmoid function given a triple.

topk: int

Highest ranked k item to select triples with f(e,r,x) > confidence .

at_most: int

Stop after finding at_most missing triples

{(e,r,x) | f(e,r,x) > confidence land (e,r,x)

otin G

```

deploy (share: bool = False, top_k: int = 10)

train_triples (h: List[str], r: List[str], t: List[str], labels: List[float], iteration=2, optimizer=None)

train_k_vs_all (h, r, iteration=1, lr=0.001)
    Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:

train (kg, lr=0.1, epoch=10, batch_size=32, neg_sample_ratio=10, num_workers=1) → None
    Retrained a pretrain model on an input KG via negative sampling.

class dicee.Execute (args, continuous_training=False)
    A class for Training, Retraining and Evaluation a model.
    (1) Loading & Preprocessing & Serializing input data.
    (2) Training & Validation & Testing
    (3) Storing all necessary info

args

is_continual_training

trainer = None

trained_model = None

knowledge_graph = None

report

evaluator = None

start_time = None

setup_executor () → None

dept_read_preprocess_index_serialize_data () → None
    Read & Preprocess & Index & Serialize Input Data
    (1) Read or load the data from disk into memory.
    (2) Store the statistics of the data.

```

Parameter

```

    rtype
        None

save_trained_model () → None
    Save a knowledge graph embedding model
    (1) Send model to eval mode and cpu.
    (2) Store the memory footprint of the model.
    (3) Save the model into disk.
    (4) Update the stats of KG again ?

```


Parameter

rtype

None

end (*form_of_labelling: str*) → dict

End training

(1) Store trained model.

(2) Report runtimes.

(3) Eval model if required.

Parameter

rtype

A dict containing information about the training and/or evaluation

write_report () → None

Report training related information in a report.json file

start () → dict

Start training

(1) Loading the Data # (2) Create an evaluator object. # (3) Create a trainer object. # (4) Start the training

Parameter

rtype

A dict containing information about the training and/or evaluation

`dicee.mapping_from_first_two_cols_to_third(train_set_idx)`

`dicee.timeit(func)`

`dicee.load_term_mapping(file_path=str)`

`dicee.reload_dataset(path: str, form_of_labelling, scoring_technique, neg_ratio, label_smoothing_rate)`

Reload the files from disk to construct the Pytorch dataset

`dicee.construct_dataset(*, train_set: numpy.ndarray | list, valid_set=None, test_set=None, ordered_bpe_entities=None, train_target_indices=None, target_dim: int = None, entity_to_idx: dict, relation_to_idx: dict, form_of_labelling: str, scoring_technique: str, neg_ratio: int, label_smoothing_rate: float, byte_pair_encoding=None, block_size: int = None) → torch.utils.data.Dataset`

class `dicee.BPE_NegativeSamplingDataset(train_set: torch.LongTensor, ordered_shaped_bpe_entities: torch.LongTensor, neg_ratio: int)`

Bases: `torch.utils.data.Dataset`

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set
ordered_bpe_entities
num_bpe_entities
neg_ratio
num_datapoints
__len__()
__getitem__(idx)
collate_fn(batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]])
```

```
class dicee.MultiLabelDataset (train_set: torch.LongTensor, train_indices_target: torch.LongTensor,
                               target_dim: int, torch_ordered_shaped_bpe_entities: torch.LongTensor)
```

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set
train_indices_target
target_dim
num_datapoints
torch_ordered_shaped_bpe_entities
collate_fn = None
__len__()
__getitem__(idx)
```

```
class dicee.MultiClassClassificationDataset (subword_units: numpy.ndarray, block_size: int = 8)
```

```
Bases: torch.utils.data.Dataset
```

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

torch.utils.data.Dataset

```
train_data
```

```
block_size
```

```
num_of_data_points
```

```
collate_fn = None
```

```
__len__()
```

```
__getitem__(idx)
```

```
class dicee.OnevsAllDataset (train_set_idx: numpy.ndarray, entity_idxs)
```

```
Bases: torch.utils.data.Dataset
```

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

torch.utils.data.Dataset

```
train_data
```

```
target_dim
```

```
collate_fn = None
```

```
__len__()
```

```
__getitem__(idx)
```

```
class dicee.KvsAll (train_set_idx: numpy.ndarray, entity_idxxs, relation_idxxs, form, store=None,  
                   label_smoothing_rate: float = 0.0)
```

Bases: torch.utils.data.Dataset

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as $D := \{(x, y)_i\}_i^N$, where $x: (h, r)$ is a unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y : denotes a multi-label vector in $[0, 1]^{|E|}$ $\{ |E| \}$ is a binary label.

orall $y_i = 1$ s.t. $(h \ r \ E_i)$ in KG

Note

TODO

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idxxs

[dictionary] string representation of an entity to its integer id

relation_idxxs

[dictionary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = KvsAll()  
>>> a  
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

__len__()

__getitem__(idx)

```
class dicee.AllvsAll (train_set_idx: numpy.ndarray, entity_idxxs, relation_idxxs, label_smoothing_rate=0.0)
```

Bases: torch.utils.data.Dataset

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as $D := \{(x, y)_i\}_i^N$, where $x: (h, r)$ is a possible unique tuple of an entity h in E and a relation r in R . Hence $N = |E| \times |R|$ y : denotes a multi-label vector in $[0, 1]^{|E|}$ $\{ |E| \}$ is a binary label.

orall $y_i = 1$ s.t. $(h \ r \ E_i)$ in KG

Note

AllvsAll extends **KvsAll** via **none** existing (**h,r**). Hence, it adds data points that are labelled without **1s**, only with **0s**.

train_set_idx
[numpy.ndarray] n by 3 array representing n triples

entity_idx
[dictionary] string representation of an entity to its integer id

relation_idx
[dictionary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

target_dim

__len__()

__getitem__(idx)

class dicee.**OnevsSample**(train_set: numpy.ndarray, num_entities, num_relations,
neg_sample_ratio: int = None, label_smoothing_rate: float = 0.0)

Bases: torch.utils.data.Dataset

A custom PyTorch Dataset class for knowledge graph embeddings, which includes both positive and negative sampling for a given dataset for multi-class classification problem..

Parameters

- **train_set** (np.ndarray) – A numpy array containing triples of knowledge graph data. Each triple consists of (head_entity, relation, tail_entity).
- **num_entities** (int) – The number of unique entities in the knowledge graph.
- **num_relations** (int) – The number of unique relations in the knowledge graph.
- **neg_sample_ratio** (int, optional) – The number of negative samples to be generated per positive sample. Must be a positive integer and less than num_entities.
- **label_smoothing_rate** (float, optional) – A label smoothing rate to apply to the positive and negative labels. Defaults to 0.0.

train_data

The input data converted into a PyTorch tensor.

Type

torch.Tensor

num_entities

Number of entities in the dataset.

Type

int

num_relations

Number of relations in the dataset.

Type

int

neg_sample_ratio

Ratio of negative samples to be drawn for each positive sample.

Type

int

label_smoothing_rate

The smoothing factor applied to the labels.

Type

torch.Tensor

collate_fn

A function that can be used to collate data samples into batches (set to None by default).

Type

function, optional

train_data

num_entities

num_relations

neg_sample_ratio

label_smoothing_rate

collate_fn = None

__len__()

Returns the number of samples in the dataset.

__getitem__(idx)

Retrieves a single data sample from the dataset at the given index.

Parameters

idx (*int*) – The index of the sample to retrieve.

Returns

A tuple consisting of:

- **x** (torch.Tensor): The head and relation part of the triple.
- **y_idx** (torch.Tensor): The concatenated indices of the true object (tail entity) and the indices of the negative samples.
- **y_vec** (torch.Tensor): A vector containing the labels for the positive and negative samples, with label smoothing applied.

Return type
tuple

```
class dicee.KvsSampleDataset (train_set_idx: numpy.ndarray, entity_idxxs, relation_idxxs, form,
                             store=None, neg_ratio=None, label_smoothing_rate: float = 0.0)
```

Bases: torch.utils.data.Dataset

KvsSample a Dataset:

D:= {(x,y)_i}_i ^N, where
· x:(h,r) is a unique h in E and a relation r in R and · y in [0,1]^{**|E|**} is a binary label.

forall y_i =1 s.t. (h r E_i) in KG

At each mini-batch construction, we subsample(y), hence n

new_y! << |E| new_y contains all 1's if sum(y)< neg_sample ratio new_y contains

train_set_idx
Indexed triples for the training.

entity_idxxs
mapping.

relation_idxxs
mapping.

form
?

store
?

label_smoothing_rate
?

torch.utils.data.Dataset

train_data = None

train_target = None

neg_ratio

num_entities

label_smoothing_rate

collate_fn = None

max_num_of_classes

__len__()

__getitem__ (idx)

```
class dicee.NegSampleDataset (train_set: numpy.ndarray, num_entities: int, num_relations: int,
                              neg_sample_ratio: int = 1)
```

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite `__getitem__()`, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite `__len__()`, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(idx)

class `dicee.TriplePredictionDataset` (*train_set: numpy.ndarray, num_entities: int, num_relations: int, neg_sample_ratio: int = 1, label_smoothing_rate: float = 0.0*)

Bases: `torch.utils.data.Dataset`

Triple Dataset

D:= {(x)_i}_i ^N, where

. $x:(h,r, t)$ in KG is a unique h in E and a relation r in R and . `collect_fn =>` Generates negative triples

`collect_fn:`

orall (h,r,t) in G obtain, create negative triples $\{(h,r,x),(r,t),(h,m,t)\}$

`y:labels` are represented in `torch.float16`

train_set_idx

Indexed triples for the training.

entity_idxxs

mapping.

relation_idxxs

mapping.

form

?

store

?

`label_smoothing_rate`

`collate_fn: batch:List[torch.IntTensor]` Returns `torch.utils.data.Dataset`


```

label_smoothing_rate
neg_sample_ratio
train_set
length
num_entities
num_relations
__len__()
__getitem__(idx)
collate_fn(batch: List[torch.Tensor])

```

```

class dicee.CVDDataModule(train_set_idx: numpy.ndarray, num_entities, num_relations, neg_sample_ratio,
                           batch_size, num_workers)

```

Bases: `pytorch_lightning.LightningDataModule`

Create a Dataset for cross validation

Parameters

- **train_set_idx** – Indexed triples for the training.
- **num_entities** – entity to index mapping.
- **num_relations** – relation to index mapping.
- **batch_size** – int
- **form** – ?
- **num_workers** – int for <https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader>

Return type

?

```

train_set_idx
num_entities
num_relations
neg_sample_ratio
batch_size
num_workers

```

```
train_dataloader() → torch.utils.data.DataLoader
```

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in `prepare_data`

- `fit()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

`setup(*args, **kwargs)`

Called at the beginning of `fit` (train + validate), `validate`, `test`, or `predict`. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

stage – either 'fit', 'validate', 'test', or 'predict'

Example:

```
class LitModel(...):
    def __init__(self):
        self.l1 = None

    def prepare_data(self):
        download_data()
        tokenize()

        # don't do this
        self.something = else

    def setup(self, stage):
        data = load_data(...)
        self.l1 = nn.Linear(28, data.num_classes)
```

`transfer_batch_to_device(*args, **kwargs)`

Override this hook if your `DataLoader` returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- `torch.Tensor` or anything that implements `.to(...)`
- `list`
- `dict`

- tuple

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, ...).

Note

This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use `self.trainer.training/testing/validating/predicting` so that you can add different logic as per your requirement.

Parameters

- **batch** – A batch of data that needs to be transferred to a new device.
- **device** – The target device as defined in PyTorch.
- **dataloader_idx** – The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_
↪idx)
    return batch
```

See also

- `move_data_to_device()`
- `apply_to_collection()`

prepare_data (*args, **kwargs)

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

Warning

DO NOT set state to the model (use `setup` instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

    # bad
    self.split = data_split
    self.some_state = some_other_state()
```

In a distributed environment, `prepare_data` can be called in two ways (using `prepare_data_per_node`)

1. Once per node. This is the default and is only called on `LOCAL_RANK=0`.
2. Once in total. Only called on `GLOBAL_RANK=0`.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True

# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

```
class dicee.QueryGenerator(train_path: str, val_path: str, test_path: str, ent2id: Dict = None,
                           rel2id: Dict = None, seed: int = 1, gen_valid: bool = False, gen_test: bool = True)
```

`train_path`

`val_path`

`test_path`

`gen_valid`

`gen_test`

`seed`

```

max_ans_num = 1000000.0

mode

ent2id

rel2id: Dict

ent_in: Dict

ent_out: Dict

query_name_to_struct

list2tuple(list_data)

tuple2list(x: List | Tuple) → List | Tuple
    Convert a nested tuple to a nested list.

set_global_seed(seed: int)
    Set seed

construct_graph(paths: List[str]) → Tuple[Dict, Dict]
    Construct graph from triples Returns dicts with incoming and outgoing edges

fill_query(query_structure: List[str | List], ent_in: Dict, ent_out: Dict, answer: int) → bool
    Private method for fill_query logic.

achieve_answer(query: List[str | List], ent_in: Dict, ent_out: Dict) → set
    Private method for achieve_answer logic. @TODO: Document the code

write_links(ent_out, small_ent_out)

ground_queries(query_structure: List[str | List], ent_in: Dict, ent_out: Dict, small_ent_in: Dict,
               small_ent_out: Dict, gen_num: int, query_name: str)
    Generating queries and achieving answers

unmap(query_type, queries, tp_answers, fp_answers, fn_answers)

unmap_query(query_structure, query, id2ent, id2rel)

generate_queries(query_struct: List, gen_num: int, query_type: str)
    Passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting
    queries and answers in return @ TODO: create a class for each single query struct

save_queries(query_type: str, gen_num: int, save_path: str)

abstract load_queries(path)

get_queries(query_type: str, gen_num: int)

static save_queries_and_answers(path: str, data: List[Tuple[str, Tuple[collections.defaultdict]]])
    → None
    Save Queries into Disk

static load_queries_and_answers(path: str) → List[Tuple[str, Tuple[collections.defaultdict]]]
    Load Queries from Disk to Memory

dicee.__version__ = '0.1.5'

```

Python Module Index

d

- [dicee](#), 12
- [dicee.__main__](#), 12
- [dicee.abstracts](#), 12
- [dicee.analyse_experiments](#), 17
- [dicee.callbacks](#), 19
- [dicee.config](#), 25
- [dicee.dataset_classes](#), 28
- [dicee.eval_static_funcs](#), 40
- [dicee.evaluator](#), 41
- [dicee.executer](#), 42
- [dicee.knowledge_graph](#), 45
- [dicee.knowledge_graph_embeddings](#), 46
- [dicee.models](#), 50
 - [dicee.models.base_model](#), 50
 - [dicee.models.clifford](#), 59
 - [dicee.models.complex](#), 66
 - [dicee.models.dualE](#), 69
 - [dicee.models.ensemble](#), 70
 - [dicee.models.function_space](#), 71
 - [dicee.models.octonion](#), 74
 - [dicee.models.pykeen_models](#), 77
 - [dicee.models.quaternion](#), 78
 - [dicee.models.real](#), 81
 - [dicee.models.static_funcs](#), 83
 - [dicee.models.transformers](#), 83
- [dicee.query_generator](#), 136
- [dicee.read_preprocess_save_load_kg](#), 137
- [dicee.read_preprocess_save_load_kg.preprocess](#), 137
- [dicee.read_preprocess_save_load_kg.read_from_disk](#), 138
- [dicee.read_preprocess_save_load_kg.save_load_disk](#), 139
- [dicee.read_preprocess_save_load_kg.util](#), 139
- [dicee.sanity_checkers](#), 144
- [dicee.scripts](#), 145
 - [dicee.scripts.index](#), 145
 - [dicee.scripts.run](#), 145
 - [dicee.scripts.serve](#), 145
- [dicee.static_funcs](#), 146
- [dicee.static_funcs_training](#), 150
- [dicee.static_preprocess_funcs](#), 150
- [dicee.trainer](#), 151
 - [dicee.trainer.dice_trainer](#), 151
 - [dicee.trainer.model_parallelism](#), 153
 - [dicee.trainer.torch_trainer](#), 154
 - [dicee.trainer.torch_trainer_ddp](#), 156

Index

Non-alphabetical

`__call__()` (*dicee.EnsembleKGE method*), 185
`__call__()` (*dicee.models.base_model.IdentityClass method*), 59
`__call__()` (*dicee.models.ensemble.EnsembleKGE method*), 70
`__call__()` (*dicee.models.IdentityClass method*), 99, 111, 117
`__getitem__()` (*dicee.AllvsAll method*), 197
`__getitem__()` (*dicee.BPE_NegativeSamplingDataset method*), 194
`__getitem__()` (*dicee.dataset_classes.AllvsAll method*), 33
`__getitem__()` (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 29
`__getitem__()` (*dicee.dataset_classes.KvsAll method*), 32
`__getitem__()` (*dicee.dataset_classes.KvsSampleDataset method*), 35
`__getitem__()` (*dicee.dataset_classes.MultiClassClassificationDataset method*), 31
`__getitem__()` (*dicee.dataset_classes.MultiLabelDataset method*), 30
`__getitem__()` (*dicee.dataset_classes.NegSampleDataset method*), 36
`__getitem__()` (*dicee.dataset_classes.OnevsAllDataset method*), 31
`__getitem__()` (*dicee.dataset_classes.OnevsSample method*), 34
`__getitem__()` (*dicee.dataset_classes.TriplePredictionDataset method*), 36
`__getitem__()` (*dicee.KvsAll method*), 196
`__getitem__()` (*dicee.KvsSampleDataset method*), 199
`__getitem__()` (*dicee.MultiClassClassificationDataset method*), 195
`__getitem__()` (*dicee.MultiLabelDataset method*), 194
`__getitem__()` (*dicee.NegSampleDataset method*), 200
`__getitem__()` (*dicee.OnevsAllDataset method*), 195
`__getitem__()` (*dicee.OnevsSample method*), 198
`__getitem__()` (*dicee.TriplePredictionDataset method*), 201
`__iter__()` (*dicee.config.Namespace method*), 28
`__iter__()` (*dicee.EnsembleKGE method*), 185
`__iter__()` (*dicee.knowledge_graph.KG method*), 46
`__iter__()` (*dicee.models.ensemble.EnsembleKGE method*), 70
`__len__()` (*dicee.AllvsAll method*), 197
`__len__()` (*dicee.BPE_NegativeSamplingDataset method*), 194
`__len__()` (*dicee.dataset_classes.AllvsAll method*), 33
`__len__()` (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 29
`__len__()` (*dicee.dataset_classes.KvsAll method*), 32
`__len__()` (*dicee.dataset_classes.KvsSampleDataset method*), 35
`__len__()` (*dicee.dataset_classes.MultiClassClassificationDataset method*), 31
`__len__()` (*dicee.dataset_classes.MultiLabelDataset method*), 30
`__len__()` (*dicee.dataset_classes.NegSampleDataset method*), 35
`__len__()` (*dicee.dataset_classes.OnevsAllDataset method*), 31
`__len__()` (*dicee.dataset_classes.OnevsSample method*), 34
`__len__()` (*dicee.dataset_classes.TriplePredictionDataset method*), 36
`__len__()` (*dicee.EnsembleKGE method*), 185
`__len__()` (*dicee.knowledge_graph.KG method*), 46
`__len__()` (*dicee.KvsAll method*), 196
`__len__()` (*dicee.KvsSampleDataset method*), 199
`__len__()` (*dicee.models.ensemble.EnsembleKGE method*), 70
`__len__()` (*dicee.MultiClassClassificationDataset method*), 195
`__len__()` (*dicee.MultiLabelDataset method*), 194
`__len__()` (*dicee.NegSampleDataset method*), 200
`__len__()` (*dicee.OnevsAllDataset method*), 195
`__len__()` (*dicee.OnevsSample method*), 198
`__len__()` (*dicee.TriplePredictionDataset method*), 201
`__str__()` (*dicee.EnsembleKGE method*), 185
`__str__()` (*dicee.KGE method*), 188
`__str__()` (*dicee.knowledge_graph_embeddings.KGE method*), 46
`__str__()` (*dicee.models.ensemble.EnsembleKGE method*), 70
`__version__` (*in module dicee*), 205

A

`AbstractCallback` (*class in dicee.abstracts*), 15
`AbstractPPECallback` (*class in dicee.abstracts*), 17
`AbstractTrainer` (*class in dicee.abstracts*), 12
`AccumulateEpochLossCallback` (*class in dicee.callbacks*), 19
`achieve_answer()` (*dicee.query_generator.QueryGenerator method*), 137
`achieve_answer()` (*dicee.QueryGenerator method*), 205

AConEx (class in *dicee*), 171
 AConEx (class in *dicee.models*), 106
 AConEx (class in *dicee.models.complex*), 67
 AConvO (class in *dicee*), 171
 AConvO (class in *dicee.models*), 119
 AConvO (class in *dicee.models.octonion*), 76
 AConvQ (class in *dicee*), 172
 AConvQ (class in *dicee.models*), 113
 AConvQ (class in *dicee.models.quaternion*), 80
 adaptive_swa (*dicee.config.Namespace* attribute), 28
 add_new_entity_embeddings() (*dicee.abstracts.BaseInteractiveKGE* method), 15
 add_noise_rate (*dicee.config.Namespace* attribute), 26
 add_noise_rate (*dicee.knowledge_graph.KG* attribute), 45
 add_noisy_triples() (in module *dicee*), 186
 add_noisy_triples() (in module *dicee.static_funcs*), 149
 add_noisy_triples_into_training() (*dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk* method), 139
 add_noisy_triples_into_training() (*dicee.read_preprocess_save_load_kg.ReadFromDisk* method), 144
 add_reciprocal (*dicee.knowledge_graph.KG* attribute), 45
 AllvsAll (class in *dicee*), 196
 AllvsAll (class in *dicee.dataset_classes*), 32
 alphas (*dicee.abstracts.AbstractPPECallback* attribute), 17
 alphas (*dicee.callbacks.ASWA* attribute), 23
 analyse() (in module *dicee.analyse_experiments*), 19
 answer_multi_hop_query() (*dicee.KGE* method), 191
 answer_multi_hop_query() (*dicee.knowledge_graph_embeddings.KGE* method), 49
 app (in module *dicee.scripts.serve*), 146
 apply_coefficients() (*dicee.DeCaL* method), 167
 apply_coefficients() (*dicee.Keci* method), 163
 apply_coefficients() (*dicee.models.clifford.DeCaL* method), 64
 apply_coefficients() (*dicee.models.clifford.Keci* method), 61
 apply_coefficients() (*dicee.models.DeCaL* method), 124
 apply_coefficients() (*dicee.models.Keci* method), 121
 apply_reciprical_or_noise() (in module *dicee.read_preprocess_save_load_kg.util*), 142
 apply_semantic_constraint (*dicee.abstracts.BaseInteractiveKGE* attribute), 14
 apply_unit_norm (*dicee.BaseKGE* attribute), 183
 apply_unit_norm (*dicee.models.base_model.BaseKGE* attribute), 57
 apply_unit_norm (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
 args (*dicee.BaseKGE* attribute), 182
 args (*dicee.DICE_Trainer* attribute), 187
 args (*dicee.evaluator.Evaluator* attribute), 41
 args (*dicee.Execute* attribute), 192
 args (*dicee.executer.Execute* attribute), 43
 args (*dicee.models.base_model.BaseKGE* attribute), 57
 args (*dicee.models.base_model.IdentityClass* attribute), 59
 args (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
 args (*dicee.models.IdentityClass* attribute), 99, 111, 117
 args (*dicee.models.pykeen_models.PykeenKGE* attribute), 77
 args (*dicee.models.PykeenKGE* attribute), 129
 args (*dicee.PykeenKGE* attribute), 179
 args (*dicee.trainer.DICE_Trainer* attribute), 157
 args (*dicee.trainer.dice_trainer.DICE_Trainer* attribute), 152
 ASWA (class in *dicee.callbacks*), 22
 aswa (*dicee.analyse_experiments.Experiment* attribute), 18
 attn (*dicee.models.transformers.Block* attribute), 88
 attn_dropout (*dicee.models.transformers.CausalSelfAttention* attribute), 86
 attributes (*dicee.abstracts.AbstractTrainer* attribute), 12

B

backend (*dicee.config.Namespace* attribute), 26
 backend (*dicee.knowledge_graph.KG* attribute), 45
 BaseInteractiveKGE (class in *dicee.abstracts*), 13
 BaseKGE (class in *dicee*), 182
 BaseKGE (class in *dicee.models*), 96, 99, 103, 107, 113, 126, 129
 BaseKGE (class in *dicee.models.base_model*), 56
 BaseKGELightning (class in *dicee.models*), 91
 BaseKGELightning (class in *dicee.models.base_model*), 50
 batch_kronecker_product() (*dicee.callbacks.KronE* static method), 25

batch_size (*dicee.analyse_experiments.Experiment* attribute), 18
 batch_size (*dicee.callbacks.PseudoLabellingCallback* attribute), 22
 batch_size (*dicee.config.Namespace* attribute), 26
 batch_size (*dicee.CVDataModule* attribute), 201
 batch_size (*dicee.dataset_classes.CVDataModule* attribute), 37
 batchwisefit () (*dicee.trainer.model_parallelism.TensorParallel* method), 154
 bias (*dicee.models.transformers.GPTConfig* attribute), 88
 bias (*dicee.models.transformers.LayerNorm* attribute), 85
 Block (class in *dicee.models.transformers*), 87
 block_size (*dicee.BaseKGE* attribute), 183
 block_size (*dicee.config.Namespace* attribute), 28
 block_size (*dicee.dataset_classes.MultiClassClassificationDataset* attribute), 30
 block_size (*dicee.models.base_model.BaseKGE* attribute), 57
 block_size (*dicee.models.BaseKGE* attribute), 98, 101, 104, 109, 115, 128, 131
 block_size (*dicee.models.transformers.GPTConfig* attribute), 88
 block_size (*dicee.MultiClassClassificationDataset* attribute), 195
 bn_conv1 (*dicee.AConvQ* attribute), 172
 bn_conv1 (*dicee.ConvQ* attribute), 173
 bn_conv1 (*dicee.models.AConvQ* attribute), 113
 bn_conv1 (*dicee.models.ConvQ* attribute), 113
 bn_conv1 (*dicee.models.quaternion.AConvQ* attribute), 81
 bn_conv1 (*dicee.models.quaternion.ConvQ* attribute), 80
 bn_conv2 (*dicee.AConvQ* attribute), 172
 bn_conv2 (*dicee.ConvQ* attribute), 173
 bn_conv2 (*dicee.models.AConvQ* attribute), 113
 bn_conv2 (*dicee.models.ConvQ* attribute), 113
 bn_conv2 (*dicee.models.quaternion.AConvQ* attribute), 81
 bn_conv2 (*dicee.models.quaternion.ConvQ* attribute), 80
 bn_conv2d (*dicee.AConEx* attribute), 171
 bn_conv2d (*dicee.AConvO* attribute), 172
 bn_conv2d (*dicee.ConEx* attribute), 174
 bn_conv2d (*dicee.ConvO* attribute), 174
 bn_conv2d (*dicee.models.AConEx* attribute), 106
 bn_conv2d (*dicee.models.AConvO* attribute), 119
 bn_conv2d (*dicee.models.complex.AConEx* attribute), 67
 bn_conv2d (*dicee.models.complex.ConEx* attribute), 67
 bn_conv2d (*dicee.models.ConEx* attribute), 106
 bn_conv2d (*dicee.models.ConvO* attribute), 118
 bn_conv2d (*dicee.models.octonion.AConvO* attribute), 77
 bn_conv2d (*dicee.models.octonion.ConvO* attribute), 76
 BPE_NegativeSamplingDataset (class in *dicee.dataset_classes*), 29
 build_chain_funcs () (*dicee.models.FMult2* method), 133
 build_chain_funcs () (*dicee.models.function_space.FMult2* method), 72
 build_func () (*dicee.models.FMult2* method), 133
 build_func () (*dicee.models.function_space.FMult2* method), 72
 Byte (class in *dicee*), 180
 Byte (class in *dicee.models.transformers*), 83
 byte_pair_encoding (*dicee.analyse_experiments.Experiment* attribute), 18
 byte_pair_encoding (*dicee.BaseKGE* attribute), 183
 byte_pair_encoding (*dicee.config.Namespace* attribute), 28
 byte_pair_encoding (*dicee.knowledge_graph.KG* attribute), 45
 byte_pair_encoding (*dicee.models.base_model.BaseKGE* attribute), 57
 byte_pair_encoding (*dicee.models.BaseKGE* attribute), 98, 101, 104, 109, 115, 128, 131

C

c_attn (*dicee.models.transformers.CausalSelfAttention* attribute), 86
 c_fc (*dicee.models.transformers.MLP* attribute), 87
 c_proj (*dicee.models.transformers.CausalSelfAttention* attribute), 86
 c_proj (*dicee.models.transformers.MLP* attribute), 87
 callbacks (*dicee.abstracts.AbstractTrainer* attribute), 12
 callbacks (*dicee.analyse_experiments.Experiment* attribute), 18
 callbacks (*dicee.config.Namespace* attribute), 26
 callbacks (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
 CausalSelfAttention (class in *dicee.models.transformers*), 85
 chain_func () (*dicee.models.FMult* method), 132
 chain_func () (*dicee.models.function_space.FMult* method), 71

`chain_func()` (*dicee.models.function_space.GFMult method*), 72
`chain_func()` (*dicee.models.GFMult method*), 133
`cl_pqr()` (*dicee.DeCaL method*), 166
`cl_pqr()` (*dicee.models.clifford.DeCaL method*), 64
`cl_pqr()` (*dicee.models.DeCaL method*), 124
`clifford_multiplication()` (*dicee.Keci method*), 164
`clifford_multiplication()` (*dicee.models.clifford.Keci method*), 61
`clifford_multiplication()` (*dicee.models.Keci method*), 121
`collate_fn` (*dicee.AllvsAll attribute*), 197
`collate_fn` (*dicee.dataset_classes.AllvsAll attribute*), 32
`collate_fn` (*dicee.dataset_classes.KvsAll attribute*), 32
`collate_fn` (*dicee.dataset_classes.KvsSampleDataset attribute*), 35
`collate_fn` (*dicee.dataset_classes.MultiClassClassificationDataset attribute*), 30
`collate_fn` (*dicee.dataset_classes.MultiLabelDataset attribute*), 30
`collate_fn` (*dicee.dataset_classes.OnevsAllDataset attribute*), 31
`collate_fn` (*dicee.dataset_classes.OnevsSample attribute*), 33, 34
`collate_fn` (*dicee.KvsAll attribute*), 196
`collate_fn` (*dicee.KvsSampleDataset attribute*), 199
`collate_fn` (*dicee.MultiClassClassificationDataset attribute*), 195
`collate_fn` (*dicee.MultiLabelDataset attribute*), 194
`collate_fn` (*dicee.OnevsAllDataset attribute*), 195
`collate_fn` (*dicee.OnevsSample attribute*), 198
`collate_fn()` (*dicee.BPE_NegativeSamplingDataset method*), 194
`collate_fn()` (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 29
`collate_fn()` (*dicee.dataset_classes.TriplePredictionDataset method*), 36
`collate_fn()` (*dicee.TriplePredictionDataset method*), 201
`collection_name` (*dicee.scripts.serve.NeuralSearcher attribute*), 146
`comp_func()` (*dicee.LFMult method*), 178
`comp_func()` (*dicee.models.function_space.LFMult method*), 74
`comp_func()` (*dicee.models.LFMult method*), 135
`Complex` (*class in dicee*), 170
`Complex` (*class in dicee.models*), 106
`Complex` (*class in dicee.models.complex*), 67
`compute_convergence()` (*in module dicee.callbacks*), 22
`compute_func()` (*dicee.models.FMult method*), 132
`compute_func()` (*dicee.models.FMult2 method*), 133
`compute_func()` (*dicee.models.function_space.FMult method*), 71
`compute_func()` (*dicee.models.function_space.FMult2 method*), 72
`compute_func()` (*dicee.models.function_space.GFMult method*), 72
`compute_func()` (*dicee.models.GFMult method*), 133
`compute_mrr()` (*dicee.callbacks.ASWA static method*), 23
`compute_sigma_pp()` (*dicee.DeCaL method*), 167
`compute_sigma_pp()` (*dicee.Keci method*), 163
`compute_sigma_pp()` (*dicee.models.clifford.DeCaL method*), 65
`compute_sigma_pp()` (*dicee.models.clifford.Keci method*), 60
`compute_sigma_pp()` (*dicee.models.DeCaL method*), 125
`compute_sigma_pp()` (*dicee.models.Keci method*), 120
`compute_sigma_pq()` (*dicee.DeCaL method*), 168
`compute_sigma_pq()` (*dicee.Keci method*), 163
`compute_sigma_pq()` (*dicee.models.clifford.DeCaL method*), 66
`compute_sigma_pq()` (*dicee.models.clifford.Keci method*), 61
`compute_sigma_pq()` (*dicee.models.DeCaL method*), 126
`compute_sigma_pq()` (*dicee.models.Keci method*), 121
`compute_sigma_pr()` (*dicee.DeCaL method*), 168
`compute_sigma_pr()` (*dicee.models.clifford.DeCaL method*), 66
`compute_sigma_pr()` (*dicee.models.DeCaL method*), 126
`compute_sigma_qq()` (*dicee.DeCaL method*), 168
`compute_sigma_qq()` (*dicee.Keci method*), 163
`compute_sigma_qq()` (*dicee.models.clifford.DeCaL method*), 65
`compute_sigma_qq()` (*dicee.models.clifford.Keci method*), 60
`compute_sigma_qq()` (*dicee.models.DeCaL method*), 125
`compute_sigma_qq()` (*dicee.models.Keci method*), 120
`compute_sigma_qr()` (*dicee.DeCaL method*), 169
`compute_sigma_qr()` (*dicee.models.clifford.DeCaL method*), 66
`compute_sigma_qr()` (*dicee.models.DeCaL method*), 126
`compute_sigma_rr()` (*dicee.DeCaL method*), 168
`compute_sigma_rr()` (*dicee.models.clifford.DeCaL method*), 65
`compute_sigma_rr()` (*dicee.models.DeCaL method*), 125

`compute_sigmas_multivect()` (*dicee.DeCaL method*), 167
`compute_sigmas_multivect()` (*dicee.models.clifford.DeCaL method*), 64
`compute_sigmas_multivect()` (*dicee.models.DeCaL method*), 124
`compute_sigmas_single()` (*dicee.DeCaL method*), 166
`compute_sigmas_single()` (*dicee.models.clifford.DeCaL method*), 64
`compute_sigmas_single()` (*dicee.models.DeCaL method*), 124
`ConEx` (*class in dicee*), 174
`ConEx` (*class in dicee.models*), 105
`ConEx` (*class in dicee.models.complex*), 66
`config` (*dicee.BytE attribute*), 180
`config` (*dicee.models.transformers.BytE attribute*), 84
`config` (*dicee.models.transformers.GPT attribute*), 89
`configs` (*dicee.abstracts.BaseInteractiveKGE attribute*), 14
`configure_optimizers()` (*dicee.models.base_model.BaseKGELightning method*), 55
`configure_optimizers()` (*dicee.models.BaseKGELightning method*), 95
`configure_optimizers()` (*dicee.models.transformers.GPT method*), 89
`construct_batch_selected_cl_multivector()` (*dicee.Keci method*), 164
`construct_batch_selected_cl_multivector()` (*dicee.models.clifford.Keci method*), 62
`construct_batch_selected_cl_multivector()` (*dicee.models.Keci method*), 122
`construct_cl_multivector()` (*dicee.DeCaL method*), 167
`construct_cl_multivector()` (*dicee.Keci method*), 164
`construct_cl_multivector()` (*dicee.models.clifford.DeCaL method*), 64
`construct_cl_multivector()` (*dicee.models.clifford.Keci method*), 61
`construct_cl_multivector()` (*dicee.models.DeCaL method*), 124
`construct_cl_multivector()` (*dicee.models.Keci method*), 121
`construct_dataset()` (*in module dicee*), 193
`construct_dataset()` (*in module dicee.dataset_classes*), 29
`construct_ensemble` (*dicee.abstracts.BaseInteractiveKGE attribute*), 14
`construct_graph()` (*dicee.query_generator.QueryGenerator method*), 137
`construct_graph()` (*dicee.QueryGenerator method*), 205
`construct_input_and_output()` (*dicee.abstracts.BaseInteractiveKGE method*), 15
`construct_multi_coeff()` (*dicee.LFMMult method*), 178
`construct_multi_coeff()` (*dicee.models.function_space.LFMMult method*), 73
`construct_multi_coeff()` (*dicee.models.LFMMult method*), 134
`continual_learning` (*dicee.config.Namespace attribute*), 28
`continual_start()` (*dicee.DICE_Trainer method*), 187
`continual_start()` (*dicee.executer.ContinuousExecute method*), 44
`continual_start()` (*dicee.trainer.DICE_Trainer method*), 157
`continual_start()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 152
`continual_training_setup_executor()` (*in module dicee*), 186
`continual_training_setup_executor()` (*in module dicee.static_funcs*), 149
`ContinuousExecute` (*class in dicee.executer*), 44
`conv2d` (*dicee.AConEx attribute*), 171
`conv2d` (*dicee.AConvO attribute*), 171
`conv2d` (*dicee.AConvQ attribute*), 172
`conv2d` (*dicee.ConEx attribute*), 174
`conv2d` (*dicee.ConvO attribute*), 174
`conv2d` (*dicee.ConvQ attribute*), 173
`conv2d` (*dicee.models.AConEx attribute*), 106
`conv2d` (*dicee.models.AConvO attribute*), 119
`conv2d` (*dicee.models.AConvQ attribute*), 113
`conv2d` (*dicee.models.complex.AConEx attribute*), 67
`conv2d` (*dicee.models.complex.ConEx attribute*), 66
`conv2d` (*dicee.models.ConEx attribute*), 105
`conv2d` (*dicee.models.ConvO attribute*), 118
`conv2d` (*dicee.models.ConvQ attribute*), 113
`conv2d` (*dicee.models.octonion.AConvO attribute*), 76
`conv2d` (*dicee.models.octonion.ConvO attribute*), 76
`conv2d` (*dicee.models.quaternion.AConvQ attribute*), 81
`conv2d` (*dicee.models.quaternion.ConvQ attribute*), 80
`ConvO` (*class in dicee*), 173
`ConvO` (*class in dicee.models*), 118
`ConvO` (*class in dicee.models.octonion*), 75
`ConvQ` (*class in dicee*), 172
`ConvQ` (*class in dicee.models*), 112
`ConvQ` (*class in dicee.models.quaternion*), 80
`create_constraints()` (*in module dicee.read_preprocess_save_load_kg.util*), 142
`create_constraints()` (*in module dicee.static_preprocess_funcs*), 151

- `create_experiment_folder()` (in module *dicee*), 186
- `create_experiment_folder()` (in module *dicee.static_funcs*), 149
- `create_random_data()` (*dicee.callbacks.PseudoLabellingCallback* method), 22
- `create_recipriocal_triples()` (in module *dicee*), 184
- `create_recipriocal_triples()` (in module *dicee.read_preprocess_save_load_kg.util*), 143
- `create_recipriocal_triples()` (in module *dicee.static_funcs*), 148
- `create_vector_database()` (*dicee.KGE* method), 188
- `create_vector_database()` (*dicee.knowledge_graph_embeddings.KGE* method), 46
- `crop_block_size()` (*dicee.models.transformers.GPT* method), 89
- `ctx` (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
- CVDataModule* (class in *dicee*), 201
- CVDataModule* (class in *dicee.dataset_classes*), 36

D

- data_module* (*dicee.callbacks.PseudoLabellingCallback* attribute), 22
- dataset_dir* (*dicee.config.Namespace* attribute), 26
- dataset_dir* (*dicee.knowledge_graph.KG* attribute), 45
- `dataset_sanity_checking()` (in module *dicee.read_preprocess_save_load_kg.util*), 143
- DeCaL* (class in *dicee*), 165
- DeCaL* (class in *dicee.models*), 123
- DeCaL* (class in *dicee.models.clifford*), 63
- `decide()` (*dicee.callbacks.ASWA* method), 23
- degree* (*dicee.LFMult* attribute), 178
- degree* (*dicee.models.function_space.LFMult* attribute), 73
- degree* (*dicee.models.LFMult* attribute), 134
- `deploy()` (*dicee.KGE* method), 191
- `deploy()` (*dicee.knowledge_graph_embeddings.KGE* method), 50
- `deploy_head_entity_prediction()` (in module *dicee*), 186
- `deploy_head_entity_prediction()` (in module *dicee.static_funcs*), 149
- `deploy_relation_prediction()` (in module *dicee*), 186
- `deploy_relation_prediction()` (in module *dicee.static_funcs*), 149
- `deploy_tail_entity_prediction()` (in module *dicee*), 186
- `deploy_tail_entity_prediction()` (in module *dicee.static_funcs*), 149
- `deploy_triple_prediction()` (in module *dicee*), 186
- `deploy_triple_prediction()` (in module *dicee.static_funcs*), 149
- `dept_read_preprocess_index_serialize_data()` (*dicee.Execute* method), 192
- `dept_read_preprocess_index_serialize_data()` (*dicee.executer.Execute* method), 43
- `describe()` (*dicee.knowledge_graph.KG* method), 46
- `description_of_input` (*dicee.knowledge_graph.KG* attribute), 46
- DICE_Trainer* (class in *dicee*), 187
- DICE_Trainer* (class in *dicee.trainer*), 157
- DICE_Trainer* (class in *dicee.trainer.dice_trainer*), 152
- dicee*
 - module, 12
- dicee.__main__*
 - module, 12
- dicee.abstracts*
 - module, 12
- dicee.analyse_experiments*
 - module, 17
- dicee.callbacks*
 - module, 19
- dicee.config*
 - module, 25
- dicee.dataset_classes*
 - module, 28
- dicee.eval_static_funcs*
 - module, 40
- dicee.evaluator*
 - module, 41
- dicee.executer*
 - module, 42
- dicee.knowledge_graph*
 - module, 45
- dicee.knowledge_graph_embeddings*
 - module, 46
- dicee.models*

- module, 50
- dicee.models.base_model
 - module, 50
- dicee.models.clifford
 - module, 59
- dicee.models.complex
 - module, 66
- dicee.models.dualE
 - module, 69
- dicee.models.ensemble
 - module, 70
- dicee.models.function_space
 - module, 71
- dicee.models.octonion
 - module, 74
- dicee.models.pykeen_models
 - module, 77
- dicee.models.quaternion
 - module, 78
- dicee.models.real
 - module, 81
- dicee.models.static_funcs
 - module, 83
- dicee.models.transformers
 - module, 83
- dicee.query_generator
 - module, 136
- dicee.read_preprocess_save_load_kg
 - module, 137
- dicee.read_preprocess_save_load_kg.preprocess
 - module, 137
- dicee.read_preprocess_save_load_kg.read_from_disk
 - module, 138
- dicee.read_preprocess_save_load_kg.save_load_disk
 - module, 139
- dicee.read_preprocess_save_load_kg.util
 - module, 139
- dicee.sanity_checkers
 - module, 144
- dicee.scripts
 - module, 145
- dicee.scripts.index
 - module, 145
- dicee.scripts.run
 - module, 145
- dicee.scripts.serve
 - module, 145
- dicee.static_funcs
 - module, 146
- dicee.static_funcs_training
 - module, 150
- dicee.static_preprocess_funcs
 - module, 150
- dicee.trainer
 - module, 151
- dicee.trainer.dice_trainer
 - module, 151
- dicee.trainer.model_parallelism
 - module, 153
- dicee.trainer.torch_trainer
 - module, 154
- dicee.trainer.torch_trainer_ddp
 - module, 156
- discrete_points (*dicee.models.FMult2 attribute*), 133
- discrete_points (*dicee.models.function_space.FMult2 attribute*), 72
- dist_func (*dicee.models.Pyke attribute*), 103
- dist_func (*dicee.models.real.Pyke attribute*), 82
- dist_func (*dicee.Pyke attribute*), 161

DistMult (*class in dicee*), 161
 DistMult (*class in dicee.models*), 102
 DistMult (*class in dicee.models.real*), 81
 download_file() (*in module dicee*), 186
 download_file() (*in module dicee.static_funcs*), 149
 download_files_from_url() (*in module dicee*), 186
 download_files_from_url() (*in module dicee.static_funcs*), 149
 download_pretrained_model() (*in module dicee*), 186
 download_pretrained_model() (*in module dicee.static_funcs*), 149
 dropout (*dicee.models.transformers.CausalSelfAttention attribute*), 86
 dropout (*dicee.models.transformers.GPTConfig attribute*), 88
 dropout (*dicee.models.transformers.MLP attribute*), 87
 DualE (*class in dicee*), 169
 DualE (*class in dicee.models*), 135
 DualE (*class in dicee.models.dualE*), 69
 dummy_eval() (*dicee.evaluator.Evaluator method*), 42
 dummy_id (*dicee.knowledge_graph.KG attribute*), 46
 during_training (*dicee.evaluator.Evaluator attribute*), 42

E

ee_vocab (*dicee.evaluator.Evaluator attribute*), 41
 efficient_zero_grad() (*in module dicee.static_funcs_training*), 150
 embedding_dim (*dicee.analyse_experiments.Experiment attribute*), 18
 embedding_dim (*dicee.BaseKGE attribute*), 182
 embedding_dim (*dicee.config.Namespace attribute*), 26
 embedding_dim (*dicee.models.base_model.BaseKGE attribute*), 57
 embedding_dim (*dicee.models.BaseKGE attribute*), 97, 100, 104, 108, 114, 127, 130
 enable_log (*in module dicee.static_preprocess_funcs*), 151
 enc (*dicee.knowledge_graph.KG attribute*), 45
 end() (*dicee.Execute method*), 193
 end() (*dicee.executer.Execute method*), 43
 EnsembleKGE (*class in dicee*), 185
 EnsembleKGE (*class in dicee.models.ensemble*), 70
 ent2id (*dicee.query_generator.QueryGenerator attribute*), 136
 ent2id (*dicee.QueryGenerator attribute*), 205
 ent_in (*dicee.query_generator.QueryGenerator attribute*), 136
 ent_in (*dicee.QueryGenerator attribute*), 205
 ent_out (*dicee.query_generator.QueryGenerator attribute*), 137
 ent_out (*dicee.QueryGenerator attribute*), 205
 entities_str (*dicee.knowledge_graph.KG property*), 46
 entity_embeddings (*dicee.AConvQ attribute*), 172
 entity_embeddings (*dicee.ConvQ attribute*), 173
 entity_embeddings (*dicee.DeCaL attribute*), 166
 entity_embeddings (*dicee.DualE attribute*), 169
 entity_embeddings (*dicee.LFMult attribute*), 178
 entity_embeddings (*dicee.models.AConvQ attribute*), 113
 entity_embeddings (*dicee.models.clifford.DeCaL attribute*), 63
 entity_embeddings (*dicee.models.ConvQ attribute*), 112
 entity_embeddings (*dicee.models.DeCaL attribute*), 123
 entity_embeddings (*dicee.models.DualE attribute*), 135
 entity_embeddings (*dicee.models.dualE.DualE attribute*), 69
 entity_embeddings (*dicee.models.FMult attribute*), 132
 entity_embeddings (*dicee.models.FMult2 attribute*), 133
 entity_embeddings (*dicee.models.function_space.FMult attribute*), 71
 entity_embeddings (*dicee.models.function_space.FMult2 attribute*), 72
 entity_embeddings (*dicee.models.function_space.GFMult attribute*), 71
 entity_embeddings (*dicee.models.function_space.LFMult attribute*), 73
 entity_embeddings (*dicee.models.function_space.LFMult1 attribute*), 72
 entity_embeddings (*dicee.models.GFMult attribute*), 132
 entity_embeddings (*dicee.models.LFMult attribute*), 134
 entity_embeddings (*dicee.models.LFMult1 attribute*), 133
 entity_embeddings (*dicee.models.pykeen_models.PykeenKGE attribute*), 77
 entity_embeddings (*dicee.models.PykeenKGE attribute*), 129
 entity_embeddings (*dicee.models.quaternion.AConvQ attribute*), 81
 entity_embeddings (*dicee.models.quaternion.ConvQ attribute*), 80
 entity_embeddings (*dicee.PykeenKGE attribute*), 179
 entity_to_idx (*dicee.knowledge_graph.KG attribute*), 45

epoch_count (*dicee.abstracts.AbstractPPECallback* attribute), 17
 epoch_count (*dicee.callbacks.ASWA* attribute), 22
 epoch_counter (*dicee.callbacks.Eval* attribute), 23
 epoch_counter (*dicee.callbacks.KGESaveCallback* attribute), 21
 epoch_ratio (*dicee.callbacks.Eval* attribute), 23
 er_vocab (*dicee.evaluator.Evaluator* attribute), 41
 estimate_mfu() (*dicee.models.transformers.GPT* method), 89
 estimate_q() (in module *dicee.callbacks*), 22
 Eval (class in *dicee.callbacks*), 23
 eval() (*dicee.EnsembleKGE* method), 185
 eval() (*dicee.evaluator.Evaluator* method), 42
 eval() (*dicee.models.ensemble.EnsembleKGE* method), 70
 eval_lp_performance() (*dicee.KGE* method), 188
 eval_lp_performance() (*dicee.knowledge_graph_embeddings.KGE* method), 47
 eval_model (*dicee.config.Namespace* attribute), 27
 eval_model (*dicee.knowledge_graph.KG* attribute), 45
 eval_rank_of_head_and_tail_byte_pair_encoded_entity() (*dicee.evaluator.Evaluator* method), 42
 eval_rank_of_head_and_tail_entity() (*dicee.evaluator.Evaluator* method), 42
 eval_with_bpe_vs_all() (*dicee.evaluator.Evaluator* method), 42
 eval_with_byte() (*dicee.evaluator.Evaluator* method), 42
 eval_with_data() (*dicee.evaluator.Evaluator* method), 42
 eval_with_vs_all() (*dicee.evaluator.Evaluator* method), 42
 evaluate() (in module *dicee*), 186
 evaluate() (in module *dicee.static_funcs*), 149
 evaluate_bpe_lp() (in module *dicee.static_funcs_training*), 150
 evaluate_link_prediction_performance() (in module *dicee.eval_static_funcs*), 40
 evaluate_link_prediction_performance_with_bpe() (in module *dicee.eval_static_funcs*), 41
 evaluate_link_prediction_performance_with_bpe_reciprocals() (in module *dicee.eval_static_funcs*), 41
 evaluate_link_prediction_performance_with_reciprocals() (in module *dicee.eval_static_funcs*), 41
 evaluate_lp() (*dicee.evaluator.Evaluator* method), 42
 evaluate_lp() (in module *dicee.static_funcs_training*), 150
 evaluate_lp_bpe_k_vs_all() (*dicee.evaluator.Evaluator* method), 42
 evaluate_lp_bpe_k_vs_all() (in module *dicee.eval_static_funcs*), 41
 evaluate_lp_k_vs_all() (*dicee.evaluator.Evaluator* method), 42
 evaluate_lp_with_byte() (*dicee.evaluator.Evaluator* method), 42
 Evaluator (class in *dicee.evaluator*), 41
 evaluator (*dicee.DICE_Trainer* attribute), 187
 evaluator (*dicee.Execute* attribute), 192
 evaluator (*dicee.executer.Execute* attribute), 43
 evaluator (*dicee.trainer.DICE_Trainer* attribute), 157
 evaluator (*dicee.trainer.dice_trainer.DICE_Trainer* attribute), 152
 every_x_epoch (*dicee.callbacks.KGESaveCallback* attribute), 21
 example_input_array (*dicee.EnsembleKGE* property), 185
 example_input_array (*dicee.models.ensemble.EnsembleKGE* property), 70
 Execute (class in *dicee*), 192
 Execute (class in *dicee.executer*), 43
 exists() (*dicee.knowledge_graph.KG* method), 46
 Experiment (class in *dicee.analyse_experiments*), 18
 explicit (*dicee.models.QMult* attribute), 111
 explicit (*dicee.models.quaternion.QMult* attribute), 79
 explicit (*dicee.QMult* attribute), 175
 exponential_function() (in module *dicee*), 186
 exponential_function() (in module *dicee.static_funcs*), 149
 extract_input_outputs() (*dicee.trainer.torch_trainer_ddp.NodeTrainer* method), 157
 extract_input_outputs() (in module *dicee.trainer.model_parallelism*), 154
 extract_input_outputs_set_device() (*dicee.trainer.torch_trainer.TorchTrainer* method), 155

F

f (*dicee.callbacks.KronE* attribute), 25
 fc1 (*dicee.AConEx* attribute), 171
 fc1 (*dicee.AConvO* attribute), 171
 fc1 (*dicee.AConvQ* attribute), 172
 fc1 (*dicee.ConEx* attribute), 174
 fc1 (*dicee.ConvO* attribute), 174
 fc1 (*dicee.ConvQ* attribute), 173
 fc1 (*dicee.models.AConEx* attribute), 106
 fc1 (*dicee.models.AConvO* attribute), 119

`fc1` (*dicee.models.AConvQ* attribute), 113
`fc1` (*dicee.models.complex.AConEx* attribute), 67
`fc1` (*dicee.models.complex.ConEx* attribute), 67
`fc1` (*dicee.models.ConEx* attribute), 106
`fc1` (*dicee.models.ConvO* attribute), 118
`fc1` (*dicee.models.ConvQ* attribute), 113
`fc1` (*dicee.models.octonion.AConvO* attribute), 77
`fc1` (*dicee.models.octonion.ConvO* attribute), 76
`fc1` (*dicee.models.quaternion.AConvQ* attribute), 81
`fc1` (*dicee.models.quaternion.ConvQ* attribute), 80
`fc_num_input` (*dicee.AConEx* attribute), 171
`fc_num_input` (*dicee.AConvO* attribute), 171
`fc_num_input` (*dicee.AConvQ* attribute), 172
`fc_num_input` (*dicee.ConEx* attribute), 174
`fc_num_input` (*dicee.ConvO* attribute), 174
`fc_num_input` (*dicee.ConvQ* attribute), 173
`fc_num_input` (*dicee.models.AConEx* attribute), 106
`fc_num_input` (*dicee.models.AConvO* attribute), 119
`fc_num_input` (*dicee.models.AConvQ* attribute), 113
`fc_num_input` (*dicee.models.complex.AConEx* attribute), 67
`fc_num_input` (*dicee.models.complex.ConEx* attribute), 67
`fc_num_input` (*dicee.models.ConEx* attribute), 105
`fc_num_input` (*dicee.models.ConvO* attribute), 118
`fc_num_input` (*dicee.models.ConvQ* attribute), 113
`fc_num_input` (*dicee.models.octonion.AConvO* attribute), 76
`fc_num_input` (*dicee.models.octonion.ConvO* attribute), 76
`fc_num_input` (*dicee.models.quaternion.AConvQ* attribute), 81
`fc_num_input` (*dicee.models.quaternion.ConvQ* attribute), 80
`feature_map_dropout` (*dicee.AConEx* attribute), 171
`feature_map_dropout` (*dicee.AConvO* attribute), 172
`feature_map_dropout` (*dicee.AConvQ* attribute), 172
`feature_map_dropout` (*dicee.ConEx* attribute), 174
`feature_map_dropout` (*dicee.ConvO* attribute), 174
`feature_map_dropout` (*dicee.ConvQ* attribute), 173
`feature_map_dropout` (*dicee.models.AConEx* attribute), 106
`feature_map_dropout` (*dicee.models.AConvO* attribute), 119
`feature_map_dropout` (*dicee.models.AConvQ* attribute), 113
`feature_map_dropout` (*dicee.models.complex.AConEx* attribute), 67
`feature_map_dropout` (*dicee.models.complex.ConEx* attribute), 67
`feature_map_dropout` (*dicee.models.ConEx* attribute), 106
`feature_map_dropout` (*dicee.models.ConvO* attribute), 119
`feature_map_dropout` (*dicee.models.ConvQ* attribute), 113
`feature_map_dropout` (*dicee.models.octonion.AConvO* attribute), 77
`feature_map_dropout` (*dicee.models.octonion.ConvO* attribute), 76
`feature_map_dropout` (*dicee.models.quaternion.AConvQ* attribute), 81
`feature_map_dropout` (*dicee.models.quaternion.ConvQ* attribute), 80
`feature_map_dropout_rate` (*dicee.BaseKGE* attribute), 183
`feature_map_dropout_rate` (*dicee.config.Namespace* attribute), 28
`feature_map_dropout_rate` (*dicee.models.base_model.BaseKGE* attribute), 57
`feature_map_dropout_rate` (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
`fill_query()` (*dicee.query_generator.QueryGenerator* method), 137
`fill_query()` (*dicee.QueryGenerator* method), 205
`find_good_batch_size()` (in module *dicee.trainer.model_parallelism*), 154
`find_missing_triples()` (*dicee.KGE* method), 191
`find_missing_triples()` (*dicee.knowledge_graph_embeddings.KGE* method), 50
`fit()` (*dicee.trainer.model_parallelism.TensorParallel* method), 154
`fit()` (*dicee.trainer.torch_trainer_ddp.TorchDDPTrainer* method), 156
`fit()` (*dicee.trainer.torch_trainer.TorchTrainer* method), 155
`flash` (*dicee.models.transformers.CausalSelfAttention* attribute), 86
`FMult` (class in *dicee.models*), 132
`FMult` (class in *dicee.models.function_space*), 71
`FMult2` (class in *dicee.models*), 133
`FMult2` (class in *dicee.models.function_space*), 72
`form_of_labelling` (*dicee.DICE_Trainer* attribute), 187
`form_of_labelling` (*dicee.trainer.DICE_Trainer* attribute), 157
`form_of_labelling` (*dicee.trainer.dice_trainer.DICE_Trainer* attribute), 152
`forward()` (*dicee.BaseKGE* method), 184
`forward()` (*dicee.BytE* method), 181

`forward()` (*dicee.models.base_model.BaseKGE method*), 58
`forward()` (*dicee.models.base_model.IdentityClass static method*), 59
`forward()` (*dicee.models.BaseKGE method*), 98, 101, 105, 109, 115, 128, 131
`forward()` (*dicee.models.IdentityClass static method*), 99, 111, 117
`forward()` (*dicee.models.transformers.Block method*), 88
`forward()` (*dicee.models.transformers.Byte method*), 84
`forward()` (*dicee.models.transformers.CausalSelfAttention method*), 86
`forward()` (*dicee.models.transformers.GPT method*), 89
`forward()` (*dicee.models.transformers.LayerNorm method*), 85
`forward()` (*dicee.models.transformers.MLP method*), 87
`forward_backward_update()` (*dicee.trainer.torch_trainer.TorchTrainer method*), 155
`forward_backward_update_loss()` (*in module dicee.trainer.model_parallelism*), 154
`forward_byte_pair_encoded_k_vs_all()` (*dicee.BaseKGE method*), 183
`forward_byte_pair_encoded_k_vs_all()` (*dicee.models.base_model.BaseKGE method*), 57
`forward_byte_pair_encoded_k_vs_all()` (*dicee.models.BaseKGE method*), 98, 101, 104, 109, 115, 128, 131
`forward_byte_pair_encoded_triple()` (*dicee.BaseKGE method*), 183
`forward_byte_pair_encoded_triple()` (*dicee.models.base_model.BaseKGE method*), 58
`forward_byte_pair_encoded_triple()` (*dicee.models.BaseKGE method*), 98, 101, 105, 109, 115, 128, 131
`forward_k_vs_all()` (*dicee.AConEx method*), 171
`forward_k_vs_all()` (*dicee.AConvO method*), 172
`forward_k_vs_all()` (*dicee.AConvQ method*), 172
`forward_k_vs_all()` (*dicee.BaseKGE method*), 184
`forward_k_vs_all()` (*dicee.ComplEx method*), 171
`forward_k_vs_all()` (*dicee.ConEx method*), 175
`forward_k_vs_all()` (*dicee.ConvO method*), 174
`forward_k_vs_all()` (*dicee.ConvQ method*), 173
`forward_k_vs_all()` (*dicee.DeCaL method*), 167
`forward_k_vs_all()` (*dicee.DistMult method*), 162
`forward_k_vs_all()` (*dicee.DualE method*), 170
`forward_k_vs_all()` (*dicee.Keci method*), 164
`forward_k_vs_all()` (*dicee.models.AConEx method*), 106
`forward_k_vs_all()` (*dicee.models.AConvO method*), 119
`forward_k_vs_all()` (*dicee.models.AConvQ method*), 113
`forward_k_vs_all()` (*dicee.models.base_model.BaseKGE method*), 58
`forward_k_vs_all()` (*dicee.models.BaseKGE method*), 98, 101, 105, 110, 116, 128, 131
`forward_k_vs_all()` (*dicee.models.clifford.DeCaL method*), 64
`forward_k_vs_all()` (*dicee.models.clifford.Keci method*), 62
`forward_k_vs_all()` (*dicee.models.ComplEx method*), 107
`forward_k_vs_all()` (*dicee.models.complex.AConEx method*), 67
`forward_k_vs_all()` (*dicee.models.complex.ComplEx method*), 68
`forward_k_vs_all()` (*dicee.models.complex.ConEx method*), 67
`forward_k_vs_all()` (*dicee.models.ConEx method*), 106
`forward_k_vs_all()` (*dicee.models.ConvO method*), 119
`forward_k_vs_all()` (*dicee.models.ConvQ method*), 113
`forward_k_vs_all()` (*dicee.models.DeCaL method*), 124
`forward_k_vs_all()` (*dicee.models.DistMult method*), 102
`forward_k_vs_all()` (*dicee.models.DualE method*), 136
`forward_k_vs_all()` (*dicee.models.dualE.DualE method*), 69
`forward_k_vs_all()` (*dicee.models.Keci method*), 122
`forward_k_vs_all()` (*dicee.models.octonion.AConvO method*), 77
`forward_k_vs_all()` (*dicee.models.octonion.ConvO method*), 76
`forward_k_vs_all()` (*dicee.models.octonion.OMult method*), 75
`forward_k_vs_all()` (*dicee.models.OMult method*), 118
`forward_k_vs_all()` (*dicee.models.pykeen_models.PykeenKGE method*), 77
`forward_k_vs_all()` (*dicee.models.PykeenKGE method*), 129
`forward_k_vs_all()` (*dicee.models.QMult method*), 112
`forward_k_vs_all()` (*dicee.models.quaternion.AConvQ method*), 81
`forward_k_vs_all()` (*dicee.models.quaternion.ConvQ method*), 80
`forward_k_vs_all()` (*dicee.models.quaternion.QMult method*), 80
`forward_k_vs_all()` (*dicee.models.real.DistMult method*), 82
`forward_k_vs_all()` (*dicee.models.real.Shallom method*), 82
`forward_k_vs_all()` (*dicee.models.real.TransE method*), 82
`forward_k_vs_all()` (*dicee.models.Shallom method*), 103
`forward_k_vs_all()` (*dicee.models.TransE method*), 102
`forward_k_vs_all()` (*dicee.OMult method*), 177
`forward_k_vs_all()` (*dicee.PykeenKGE method*), 179
`forward_k_vs_all()` (*dicee.QMult method*), 176
`forward_k_vs_all()` (*dicee.Shallom method*), 177

`forward_k_vs_all()` (*dicee.TransE method*), 165
`forward_k_vs_sample()` (*dicee.AConEx method*), 171
`forward_k_vs_sample()` (*dicee.BaseKGE method*), 184
`forward_k_vs_sample()` (*dicee.ComplEx method*), 171
`forward_k_vs_sample()` (*dicee.ConEx method*), 175
`forward_k_vs_sample()` (*dicee.DistMult method*), 162
`forward_k_vs_sample()` (*dicee.Keci method*), 165
`forward_k_vs_sample()` (*dicee.models.AConEx method*), 106
`forward_k_vs_sample()` (*dicee.models.base_model.BaseKGE method*), 58
`forward_k_vs_sample()` (*dicee.models.BaseKGE method*), 98, 101, 105, 110, 116, 128, 131
`forward_k_vs_sample()` (*dicee.models.clifford.Keci method*), 62
`forward_k_vs_sample()` (*dicee.models.ComplEx method*), 107
`forward_k_vs_sample()` (*dicee.models.complex.AConEx method*), 67
`forward_k_vs_sample()` (*dicee.models.complex.ComplEx method*), 68
`forward_k_vs_sample()` (*dicee.models.complex.ConEx method*), 67
`forward_k_vs_sample()` (*dicee.models.ConEx method*), 106
`forward_k_vs_sample()` (*dicee.models.DistMult method*), 102
`forward_k_vs_sample()` (*dicee.models.Keci method*), 122
`forward_k_vs_sample()` (*dicee.models.pykeen_models.PykeenKGE method*), 78
`forward_k_vs_sample()` (*dicee.models.PykeenKGE method*), 129
`forward_k_vs_sample()` (*dicee.models.QMult method*), 112
`forward_k_vs_sample()` (*dicee.models.quaternion.QMult method*), 80
`forward_k_vs_sample()` (*dicee.models.real.DistMult method*), 82
`forward_k_vs_sample()` (*dicee.PykeenKGE method*), 180
`forward_k_vs_sample()` (*dicee.QMult method*), 176
`forward_k_vs_with_explicit()` (*dicee.Keci method*), 164
`forward_k_vs_with_explicit()` (*dicee.models.clifford.Keci method*), 61
`forward_k_vs_with_explicit()` (*dicee.models.Keci method*), 121
`forward_triples()` (*dicee.AConEx method*), 171
`forward_triples()` (*dicee.AConvO method*), 172
`forward_triples()` (*dicee.AConvQ method*), 172
`forward_triples()` (*dicee.BaseKGE method*), 184
`forward_triples()` (*dicee.ConEx method*), 175
`forward_triples()` (*dicee.ConvO method*), 174
`forward_triples()` (*dicee.ConvQ method*), 173
`forward_triples()` (*dicee.DeCaL method*), 166
`forward_triples()` (*dicee.DualE method*), 169
`forward_triples()` (*dicee.Keci method*), 165
`forward_triples()` (*dicee.LFMult method*), 178
`forward_triples()` (*dicee.models.AConEx method*), 106
`forward_triples()` (*dicee.models.AConvO method*), 119
`forward_triples()` (*dicee.models.AConvQ method*), 113
`forward_triples()` (*dicee.models.base_model.BaseKGE method*), 58
`forward_triples()` (*dicee.models.BaseKGE method*), 98, 101, 105, 109, 115, 128, 131
`forward_triples()` (*dicee.models.clifford.DeCaL method*), 63
`forward_triples()` (*dicee.models.clifford.Keci method*), 62
`forward_triples()` (*dicee.models.complex.AConEx method*), 67
`forward_triples()` (*dicee.models.complex.ConEx method*), 67
`forward_triples()` (*dicee.models.ConEx method*), 106
`forward_triples()` (*dicee.models.ConvO method*), 119
`forward_triples()` (*dicee.models.ConvQ method*), 113
`forward_triples()` (*dicee.models.DeCaL method*), 123
`forward_triples()` (*dicee.models.DualE method*), 135
`forward_triples()` (*dicee.models.dualE.DualE method*), 69
`forward_triples()` (*dicee.models.FMult method*), 132
`forward_triples()` (*dicee.models.FMult2 method*), 133
`forward_triples()` (*dicee.models.function_space.FMult method*), 71
`forward_triples()` (*dicee.models.function_space.FMult2 method*), 72
`forward_triples()` (*dicee.models.function_space.GFMult method*), 72
`forward_triples()` (*dicee.models.function_space.LFMult method*), 73
`forward_triples()` (*dicee.models.function_space.LFMult1 method*), 72
`forward_triples()` (*dicee.models.GFMult method*), 133
`forward_triples()` (*dicee.models.Keci method*), 122
`forward_triples()` (*dicee.models.LFMult method*), 134
`forward_triples()` (*dicee.models.LFMult1 method*), 134
`forward_triples()` (*dicee.models.octonion.AConvO method*), 77
`forward_triples()` (*dicee.models.octonion.ConvO method*), 76
`forward_triples()` (*dicee.models.Pyke method*), 103

`forward_triples()` (*dicee.models.pykeen_models.PykeenKGE method*), 78
`forward_triples()` (*dicee.models.PykeenKGE method*), 129
`forward_triples()` (*dicee.models.quaternion.AConvQ method*), 81
`forward_triples()` (*dicee.models.quaternion.ConvQ method*), 80
`forward_triples()` (*dicee.models.real.Pyke method*), 82
`forward_triples()` (*dicee.models.real.Shallom method*), 82
`forward_triples()` (*dicee.models.Shallom method*), 103
`forward_triples()` (*dicee.Pyke method*), 161
`forward_triples()` (*dicee.PykeenKGE method*), 179
`forward_triples()` (*dicee.Shallom method*), 177
`frequency` (*dicee.callbacks.Perturb attribute*), 25
`from_pretrained()` (*dicee.models.transformers.GPT class method*), 89
`from_pretrained_model_write_embeddings_into_csv()` (*in module dicee*), 187
`from_pretrained_model_write_embeddings_into_csv()` (*in module dicee.static_funcs*), 150
`full_storage_path` (*dicee.analyse_experiments.Experiment attribute*), 18
`func_triple_to_bpe_representation` (*dicee.evaluator.Evaluator attribute*), 41
`func_triple_to_bpe_representation()` (*dicee.knowledge_graph.KG method*), 46
`function()` (*dicee.models.FMult2 method*), 133
`function()` (*dicee.models.function_space.FMult2 method*), 72

G

`gamma` (*dicee.models.FMult attribute*), 132
`gamma` (*dicee.models.function_space.FMult attribute*), 71
`gelu` (*dicee.models.transformers.MLP attribute*), 87
`gen_test` (*dicee.query_generator.QueryGenerator attribute*), 136
`gen_test` (*dicee.QueryGenerator attribute*), 204
`gen_valid` (*dicee.query_generator.QueryGenerator attribute*), 136
`gen_valid` (*dicee.QueryGenerator attribute*), 204
`generate()` (*dicee.BytE method*), 181
`generate()` (*dicee.KGE method*), 188
`generate()` (*dicee.knowledge_graph_embeddings.KGE method*), 46
`generate()` (*dicee.models.transformers.BytE method*), 84
`generate_queries()` (*dicee.query_generator.QueryGenerator method*), 137
`generate_queries()` (*dicee.QueryGenerator method*), 205
`get()` (*dicee.scripts.serve.NeuralSearcher method*), 146
`get_aswa_state_dict()` (*dicee.callbacks.ASWA method*), 23
`get_bpe_head_and_relation_representation()` (*dicee.BaseKGE method*), 184
`get_bpe_head_and_relation_representation()` (*dicee.models.base_model.BaseKGE method*), 58
`get_bpe_head_and_relation_representation()` (*dicee.models.BaseKGE method*), 98, 102, 105, 110, 116, 128, 132
`get_bpe_token_representation()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
`get_callbacks()` (*in module dicee.trainer.dice_trainer*), 152
`get_default_arguments()` (*in module dicee.analyse_experiments*), 18
`get_default_arguments()` (*in module dicee.scripts.index*), 145
`get_default_arguments()` (*in module dicee.scripts.run*), 145
`get_default_arguments()` (*in module dicee.scripts.serve*), 146
`get_ee_vocab()` (*in module dicee*), 184
`get_ee_vocab()` (*in module dicee.read_preprocess_save_load_kg.util*), 142
`get_ee_vocab()` (*in module dicee.static_funcs*), 148
`get_ee_vocab()` (*in module dicee.static_preprocess_funcs*), 151
`get_embeddings()` (*dicee.BaseKGE method*), 184
`get_embeddings()` (*dicee.models.base_model.BaseKGE method*), 58
`get_embeddings()` (*dicee.models.BaseKGE method*), 99, 102, 105, 110, 116, 128, 132
`get_embeddings()` (*dicee.models.real.Shallom method*), 82
`get_embeddings()` (*dicee.models.Shallom method*), 103
`get_embeddings()` (*dicee.Shallom method*), 177
`get_ensemble()` (*dicee.trainer.model_parallelism.TensorParallel method*), 154
`get_entity_embeddings()` (*dicee.abstracts.BaseInteractiveKGE method*), 15
`get_entity_index()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
`get_er_vocab()` (*in module dicee*), 184
`get_er_vocab()` (*in module dicee.read_preprocess_save_load_kg.util*), 142
`get_er_vocab()` (*in module dicee.static_funcs*), 148
`get_er_vocab()` (*in module dicee.static_preprocess_funcs*), 151
`get_eval_report()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
`get_head_relation_representation()` (*dicee.BaseKGE method*), 184
`get_head_relation_representation()` (*dicee.models.base_model.BaseKGE method*), 58
`get_head_relation_representation()` (*dicee.models.BaseKGE method*), 98, 101, 105, 110, 116, 128, 131
`get_kronecker_triple_representation()` (*dicee.callbacks.KronE method*), 25

`get_num_params()` (*dicee.models.transformers.GPT method*), 89
`get_padded_bpe_triple_representation()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
`get_queries()` (*dicee.query_generator.QueryGenerator method*), 137
`get_queries()` (*dicee.QueryGenerator method*), 205
`get_re_vocab()` (*in module dicee*), 184
`get_re_vocab()` (*in module dicee.read_preprocess_save_load_kg.util*), 142
`get_re_vocab()` (*in module dicee.static_funcs*), 148
`get_re_vocab()` (*in module dicee.static_preprocess_funcs*), 151
`get_relation_embeddings()` (*dicee.abstracts.BaseInteractiveKGE method*), 15
`get_relation_index()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
`get_sentence_representation()` (*dicee.BaseKGE method*), 184
`get_sentence_representation()` (*dicee.models.base_model.BaseKGE method*), 58
`get_sentence_representation()` (*dicee.models.BaseKGE method*), 98, 101, 105, 110, 116, 128, 132
`get_transductive_entity_embeddings()` (*dicee.KGE method*), 188
`get_transductive_entity_embeddings()` (*dicee.knowledge_graph_embeddings.KGE method*), 46
`get_triple_representation()` (*dicee.BaseKGE method*), 184
`get_triple_representation()` (*dicee.models.base_model.BaseKGE method*), 58
`get_triple_representation()` (*dicee.models.BaseKGE method*), 98, 101, 105, 110, 116, 128, 131
`GFMult` (*class in dicee.models*), 132
`GFMult` (*class in dicee.models.function_space*), 71
`global_rank` (*dicee.abstracts.AbstractTrainer attribute*), 12
`global_rank` (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 156
`GPT` (*class in dicee.models.transformers*), 88
`GPTConfig` (*class in dicee.models.transformers*), 88
`gpus` (*dicee.config.Namespace attribute*), 26
`gradient_accumulation_steps` (*dicee.config.Namespace attribute*), 27
`ground_queries()` (*dicee.query_generator.QueryGenerator method*), 137
`ground_queries()` (*dicee.QueryGenerator method*), 205

H

`hidden_dropout` (*dicee.BaseKGE attribute*), 183
`hidden_dropout` (*dicee.models.base_model.BaseKGE attribute*), 57
`hidden_dropout` (*dicee.models.BaseKGE attribute*), 98, 101, 104, 109, 115, 127, 131
`hidden_dropout_rate` (*dicee.BaseKGE attribute*), 183
`hidden_dropout_rate` (*dicee.config.Namespace attribute*), 28
`hidden_dropout_rate` (*dicee.models.base_model.BaseKGE attribute*), 57
`hidden_dropout_rate` (*dicee.models.BaseKGE attribute*), 97, 100, 104, 108, 114, 127, 130
`hidden_normalizer` (*dicee.BaseKGE attribute*), 183
`hidden_normalizer` (*dicee.models.base_model.BaseKGE attribute*), 57
`hidden_normalizer` (*dicee.models.BaseKGE attribute*), 97, 101, 104, 109, 115, 127, 131

I

`IdentityClass` (*class in dicee.models*), 99, 110, 116
`IdentityClass` (*class in dicee.models.base_model*), 58
`idx_entity_to_bpe_shaped` (*dicee.knowledge_graph.KG attribute*), 45
`index_triple()` (*dicee.abstracts.BaseInteractiveKGE method*), 15
`init_dataloader()` (*dicee.DICE_Trainer method*), 187
`init_dataloader()` (*dicee.trainer.DICE_Trainer method*), 158
`init_dataloader()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 153
`init_dataset()` (*dicee.DICE_Trainer method*), 187
`init_dataset()` (*dicee.trainer.DICE_Trainer method*), 158
`init_dataset()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 153
`init_param` (*dicee.config.Namespace attribute*), 27
`init_params_with_sanity_checking()` (*dicee.BaseKGE method*), 184
`init_params_with_sanity_checking()` (*dicee.models.base_model.BaseKGE method*), 58
`init_params_with_sanity_checking()` (*dicee.models.BaseKGE method*), 98, 101, 105, 109, 115, 128, 131
`initial_eval_setting` (*dicee.callbacks.ASWA attribute*), 22
`initialize_or_load_model()` (*dicee.DICE_Trainer method*), 187
`initialize_or_load_model()` (*dicee.trainer.DICE_Trainer method*), 158
`initialize_or_load_model()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 153
`initialize_trainer()` (*dicee.DICE_Trainer method*), 187
`initialize_trainer()` (*dicee.trainer.DICE_Trainer method*), 158
`initialize_trainer()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 153
`initialize_trainer()` (*in module dicee.trainer.dice_trainer*), 152
`input_dp_ent_real` (*dicee.BaseKGE attribute*), 183
`input_dp_ent_real` (*dicee.models.base_model.BaseKGE attribute*), 57
`input_dp_ent_real` (*dicee.models.BaseKGE attribute*), 98, 101, 104, 109, 115, 127, 131

- `input_dp_rel_real` (*dicee.BaseKGE attribute*), 183
- `input_dp_rel_real` (*dicee.models.base_model.BaseKGE attribute*), 57
- `input_dp_rel_real` (*dicee.models.BaseKGE attribute*), 98, 101, 104, 109, 115, 127, 131
- `input_dropout_rate` (*dicee.BaseKGE attribute*), 183
- `input_dropout_rate` (*dicee.config.Namespace attribute*), 28
- `input_dropout_rate` (*dicee.models.base_model.BaseKGE attribute*), 57
- `input_dropout_rate` (*dicee.models.BaseKGE attribute*), 97, 100, 104, 108, 114, 127, 130
- `intialize_model()` (in module *dicee*), 186
- `intialize_model()` (in module *dicee.static_funcs*), 149
- `is_continual_training` (*dicee.DICE_Trainer attribute*), 187
- `is_continual_training` (*dicee.evaluator.Evaluator attribute*), 41
- `is_continual_training` (*dicee.Execute attribute*), 192
- `is_continual_training` (*dicee.executer.Execute attribute*), 43
- `is_continual_training` (*dicee.trainer.DICE_Trainer attribute*), 157
- `is_continual_training` (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 152
- `is_global_zero` (*dicee.abstracts.AbstractTrainer attribute*), 12
- `is_seen()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
- `is_sparql_endpoint_alive()` (in module *dicee.sanity_checkers*), 144

K

- `k` (*dicee.models.FMult attribute*), 132
- `k` (*dicee.models.FMult2 attribute*), 133
- `k` (*dicee.models.function_space.FMult attribute*), 71
- `k` (*dicee.models.function_space.FMult2 attribute*), 72
- `k` (*dicee.models.function_space.GFMult attribute*), 71
- `k` (*dicee.models.GFMult attribute*), 132
- `k_fold_cross_validation()` (*dicee.DICE_Trainer method*), 188
- `k_fold_cross_validation()` (*dicee.trainer.DICE_Trainer method*), 158
- `k_fold_cross_validation()` (*dicee.trainer.dice_trainer.DICE_Trainer method*), 153
- `k_vs_all_score()` (*dicee.ComplEx static method*), 171
- `k_vs_all_score()` (*dicee.DistMult method*), 162
- `k_vs_all_score()` (*dicee.Keci method*), 164
- `k_vs_all_score()` (*dicee.models.clifford.Keci method*), 62
- `k_vs_all_score()` (*dicee.models.ComplEx static method*), 107
- `k_vs_all_score()` (*dicee.models.complex.ComplEx static method*), 68
- `k_vs_all_score()` (*dicee.models.DistMult method*), 102
- `k_vs_all_score()` (*dicee.models.Keci method*), 122
- `k_vs_all_score()` (*dicee.models.octonion.OMult method*), 75
- `k_vs_all_score()` (*dicee.models.OMult method*), 118
- `k_vs_all_score()` (*dicee.models.QMult method*), 112
- `k_vs_all_score()` (*dicee.models.quaternion.QMult method*), 80
- `k_vs_all_score()` (*dicee.models.real.DistMult method*), 81
- `k_vs_all_score()` (*dicee.OMult method*), 177
- `k_vs_all_score()` (*dicee.QMult method*), 176
- `Keci` (class in *dicee*), 162
- `Keci` (class in *dicee.models*), 119
- `Keci` (class in *dicee.models.clifford*), 59
- `KeciBase` (class in *dicee*), 162
- `KeciBase` (class in *dicee.models*), 122
- `KeciBase` (class in *dicee.models.clifford*), 62
- `kernel_size` (*dicee.BaseKGE attribute*), 183
- `kernel_size` (*dicee.config.Namespace attribute*), 27
- `kernel_size` (*dicee.models.base_model.BaseKGE attribute*), 57
- `kernel_size` (*dicee.models.BaseKGE attribute*), 97, 100, 104, 108, 114, 127, 130
- `KG` (class in *dicee.knowledge_graph*), 45
- `kg` (*dicee.callbacks.PseudoLabellingCallback attribute*), 22
- `kg` (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk attribute*), 144
- `kg` (*dicee.read_preprocess_save_load_kg.PreprocessKG attribute*), 143
- `kg` (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG attribute*), 138
- `kg` (*dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk attribute*), 138
- `kg` (*dicee.read_preprocess_save_load_kg.ReadFromDisk attribute*), 144
- `kg` (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk attribute*), 139
- `KGE` (class in *dicee*), 188
- `KGE` (class in *dicee.knowledge_graph_embeddings*), 46
- `KGESaveCallback` (class in *dicee.callbacks*), 21
- `knowledge_graph` (*dicee.Execute attribute*), 192
- `knowledge_graph` (*dicee.executer.Execute attribute*), 43

KronE (class in *dicee.callbacks*), 24
 KvsAll (class in *dicee*), 195
 KvsAll (class in *dicee.dataset_classes*), 31
 kvsall_score() (*dicee.DualE* method), 169
 kvsall_score() (*dicee.models.DualE* method), 135
 kvsall_score() (*dicee.models.dualE.DualE* method), 69
 KvsSampleDataset (class in *dicee*), 199
 KvsSampleDataset (class in *dicee.dataset_classes*), 34

L

label_smoothing_rate (*dicee.AllvsAll* attribute), 197
 label_smoothing_rate (*dicee.config.Namespace* attribute), 27
 label_smoothing_rate (*dicee.dataset_classes.AllvsAll* attribute), 32
 label_smoothing_rate (*dicee.dataset_classes.KvsAll* attribute), 32
 label_smoothing_rate (*dicee.dataset_classes.KvsSampleDataset* attribute), 35
 label_smoothing_rate (*dicee.dataset_classes.OnevsSample* attribute), 33, 34
 label_smoothing_rate (*dicee.dataset_classes.TriplePredictionDataset* attribute), 36
 label_smoothing_rate (*dicee.KvsAll* attribute), 196
 label_smoothing_rate (*dicee.KvsSampleDataset* attribute), 199
 label_smoothing_rate (*dicee.OnevsSample* attribute), 198
 label_smoothing_rate (*dicee.TriplePredictionDataset* attribute), 200
 LayerNorm (class in *dicee.models.transformers*), 85
 learning_rate (*dicee.BaseKGE* attribute), 183
 learning_rate (*dicee.models.base_model.BaseKGE* attribute), 57
 learning_rate (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
 length (*dicee.dataset_classes.NegSampleDataset* attribute), 35
 length (*dicee.dataset_classes.TriplePredictionDataset* attribute), 36
 length (*dicee.NegSampleDataset* attribute), 200
 length (*dicee.TriplePredictionDataset* attribute), 201
 level (*dicee.callbacks.Perturb* attribute), 25
 LFMult (class in *dicee*), 178
 LFMult (class in *dicee.models*), 134
 LFMult (class in *dicee.models.function_space*), 73
 LFMult1 (class in *dicee.models*), 133
 LFMult1 (class in *dicee.models.function_space*), 72
 linear() (*dicee.LFMult* method), 178
 linear() (*dicee.models.function_space.LFMult* method), 73
 linear() (*dicee.models.LFMult* method), 134
 list2tuple() (*dicee.query_generator.QueryGenerator* method), 137
 list2tuple() (*dicee.QueryGenerator* method), 205
 lm_head (*dicee.BytE* attribute), 180
 lm_head (*dicee.models.transformers.BytE* attribute), 84
 lm_head (*dicee.models.transformers.GPT* attribute), 89
 ln_1 (*dicee.models.transformers.Block* attribute), 88
 ln_2 (*dicee.models.transformers.Block* attribute), 88
 load() (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk* method), 144
 load() (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk* method), 139
 load_json() (in module *dicee*), 186
 load_json() (in module *dicee.static_funcs*), 149
 load_model() (in module *dicee*), 185
 load_model() (in module *dicee.static_funcs*), 148
 load_model_ensemble() (in module *dicee*), 185
 load_model_ensemble() (in module *dicee.static_funcs*), 148
 load_numpy() (in module *dicee*), 186
 load_numpy() (in module *dicee.static_funcs*), 149
 load_numpy_ndarray() (in module *dicee.read_preprocess_save_load_kg.util*), 142
 load_pickle() (in module *dicee*), 184
 load_pickle() (in module *dicee.read_preprocess_save_load_kg.util*), 143
 load_pickle() (in module *dicee.static_funcs*), 148
 load_queries() (*dicee.query_generator.QueryGenerator* method), 137
 load_queries() (*dicee.QueryGenerator* method), 205
 load_queries_and_answers() (*dicee.query_generator.QueryGenerator* static method), 137
 load_queries_and_answers() (*dicee.QueryGenerator* static method), 205
 load_term_mapping() (in module *dicee*), 185, 193
 load_term_mapping() (in module *dicee.static_funcs*), 148
 load_term_mapping() (in module *dicee.trainer.dice_trainer*), 152
 load_with_pandas() (in module *dicee.read_preprocess_save_load_kg.util*), 142

LoadSaveToDisk (class in *dicee.read_preprocess_save_load_kg*), 144
 LoadSaveToDisk (class in *dicee.read_preprocess_save_load_kg.save_load_disk*), 139
 local_rank (*dicee.abstracts.AbstractTrainer* attribute), 12
 local_rank (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 156
 loss (*dicee.BaseKGE* attribute), 183
 loss (*dicee.models.base_model.BaseKGE* attribute), 57
 loss (*dicee.models.BaseKGE* attribute), 97, 100, 104, 109, 115, 127, 130
 loss_func (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
 loss_function (*dicee.trainer.torch_trainer.TorchTrainer* attribute), 155
 loss_function() (*dicee.BytE* method), 181
 loss_function() (*dicee.models.base_model.BaseKGELightning* method), 52
 loss_function() (*dicee.models.BaseKGELightning* method), 92
 loss_function() (*dicee.models.transformers.BytE* method), 84
 loss_history (*dicee.BaseKGE* attribute), 183
 loss_history (*dicee.EnsembleKGE* attribute), 185
 loss_history (*dicee.models.base_model.BaseKGE* attribute), 57
 loss_history (*dicee.models.BaseKGE* attribute), 98, 101, 104, 109, 115, 128, 131
 loss_history (*dicee.models.ensemble.EnsembleKGE* attribute), 70
 loss_history (*dicee.models.pykeen_models.PykeenKGE* attribute), 77
 loss_history (*dicee.models.PykeenKGE* attribute), 129
 loss_history (*dicee.PykeenKGE* attribute), 179
 loss_history (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
 lr (*dicee.analyse_experiments.Experiment* attribute), 18
 lr (*dicee.config.Namespace* attribute), 26

M

m (*dicee.LFMult* attribute), 178
 m (*dicee.models.function_space.LFMult* attribute), 73
 m (*dicee.models.LFMult* attribute), 134
 main() (in module *dicee.scripts.index*), 145
 main() (in module *dicee.scripts.run*), 145
 main() (in module *dicee.scripts.serve*), 146
 make_iterable_verbose() (in module *dicee.static_funcs_training*), 150
 make_iterable_verbose() (in module *dicee.trainer.torch_trainer_ddp*), 156
 mapping_from_first_two_cols_to_third() (in module *dicee*), 193
 mapping_from_first_two_cols_to_third() (in module *dicee.static_preprocess_funcs*), 151
 margin (*dicee.models.Pyke* attribute), 103
 margin (*dicee.models.real.Pyke* attribute), 82
 margin (*dicee.models.real.TransE* attribute), 82
 margin (*dicee.models.TransE* attribute), 102
 margin (*dicee.Pyke* attribute), 161
 margin (*dicee.TransE* attribute), 165
 max_ans_num (*dicee.query_generator.QueryGenerator* attribute), 136
 max_ans_num (*dicee.QueryGenerator* attribute), 204
 max_epochs (*dicee.callbacks.KGESaveCallback* attribute), 21
 max_length_subword_tokens (*dicee.BaseKGE* attribute), 183
 max_length_subword_tokens (*dicee.knowledge_graph.KG* attribute), 46
 max_length_subword_tokens (*dicee.models.base_model.BaseKGE* attribute), 57
 max_length_subword_tokens (*dicee.models.BaseKGE* attribute), 98, 101, 104, 109, 115, 128, 131
 max_num_of_classes (*dicee.dataset_classes.KvsSampleDataset* attribute), 35
 max_num_of_classes (*dicee.KvsSampleDataset* attribute), 199
 mem_of_model() (*dicee.EnsembleKGE* method), 185
 mem_of_model() (*dicee.models.base_model.BaseKGELightning* method), 51
 mem_of_model() (*dicee.models.BaseKGELightning* method), 91
 mem_of_model() (*dicee.models.ensemble.EnsembleKGE* method), 70
 method (*dicee.callbacks.Perturb* attribute), 25
 MLP (class in *dicee.models.transformers*), 86
 mlp (*dicee.models.transformers.Block* attribute), 88
 mode (*dicee.query_generator.QueryGenerator* attribute), 136
 mode (*dicee.QueryGenerator* attribute), 205
 model (*dicee.config.Namespace* attribute), 26
 model (*dicee.models.pykeen_models.PykeenKGE* attribute), 77
 model (*dicee.models.PykeenKGE* attribute), 129
 model (*dicee.PykeenKGE* attribute), 179
 model (*dicee.scripts.serve.NeuralSearcher* attribute), 146
 model (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
 model (*dicee.trainer.torch_trainer.TorchTrainer* attribute), 155

- model_kwargs (*dicee.models.pykeen_models.PykeenKGE attribute*), 77
- model_kwargs (*dicee.models.PykeenKGE attribute*), 129
- model_kwargs (*dicee.PykeenKGE attribute*), 179
- model_name (*dicee.analyse_experiments.Experiment attribute*), 18
- models (*dicee.EnsembleKGE attribute*), 185
- models (*dicee.models.ensemble.EnsembleKGE attribute*), 70
- models (*dicee.trainer.model_parallelism.TensorParallel attribute*), 154
- module
 - dicee, 12
 - dicee.__main__, 12
 - dicee.abstracts, 12
 - dicee.analyse_experiments, 17
 - dicee.callbacks, 19
 - dicee.config, 25
 - dicee.dataset_classes, 28
 - dicee.eval_static_funcs, 40
 - dicee.evaluator, 41
 - dicee.executer, 42
 - dicee.knowledge_graph, 45
 - dicee.knowledge_graph_embeddings, 46
 - dicee.models, 50
 - dicee.models.base_model, 50
 - dicee.models.clifford, 59
 - dicee.models.complex, 66
 - dicee.models.dualE, 69
 - dicee.models.ensemble, 70
 - dicee.models.function_space, 71
 - dicee.models.octonion, 74
 - dicee.models.pykeen_models, 77
 - dicee.models.quaternion, 78
 - dicee.models.real, 81
 - dicee.models.static_funcs, 83
 - dicee.models.transformers, 83
 - dicee.query_generator, 136
 - dicee.read_preprocess_save_load_kg, 137
 - dicee.read_preprocess_save_load_kg.preprocess, 137
 - dicee.read_preprocess_save_load_kg.read_from_disk, 138
 - dicee.read_preprocess_save_load_kg.save_load_disk, 139
 - dicee.read_preprocess_save_load_kg.util, 139
 - dicee.sanity_checkers, 144
 - dicee.scripts, 145
 - dicee.scripts.index, 145
 - dicee.scripts.run, 145
 - dicee.scripts.serve, 145
 - dicee.static_funcs, 146
 - dicee.static_funcs_training, 150
 - dicee.static_preprocess_funcs, 150
 - dicee.trainer, 151
 - dicee.trainer.dice_trainer, 151
 - dicee.trainer.model_parallelism, 153
 - dicee.trainer.torch_trainer, 154
 - dicee.trainer.torch_trainer_ddp, 156
- modules () (*dicee.EnsembleKGE method*), 185
- modules () (*dicee.models.ensemble.EnsembleKGE method*), 70
- MultiClassClassificationDataset (*class in dicee*), 194
- MultiClassClassificationDataset (*class in dicee.dataset_classes*), 30
- MultiLabelDataset (*class in dicee*), 194
- MultiLabelDataset (*class in dicee.dataset_classes*), 29

N

- n (*dicee.models.FMult2 attribute*), 133
- n (*dicee.models.function_space.FMult2 attribute*), 72
- n_embd (*dicee.models.transformers.CausalSelfAttention attribute*), 86
- n_embd (*dicee.models.transformers.GPTConfig attribute*), 88
- n_head (*dicee.models.transformers.CausalSelfAttention attribute*), 86
- n_head (*dicee.models.transformers.GPTConfig attribute*), 88
- n_layer (*dicee.models.transformers.GPTConfig attribute*), 88

n_layers (*dicee.models.FMult2* attribute), 133
n_layers (*dicee.models.function_space.FMult2* attribute), 72
name (*dicee.abstracts.BaseInteractiveKGE* property), 14
name (*dicee.AConEx* attribute), 171
name (*dicee.AConvO* attribute), 171
name (*dicee.AConvQ* attribute), 172
name (*dicee.BytE* attribute), 180
name (*dicee.ComplEx* attribute), 170
name (*dicee.ConEx* attribute), 174
name (*dicee.ConvO* attribute), 174
name (*dicee.ConvQ* attribute), 173
name (*dicee.DeCaL* attribute), 166
name (*dicee.DistMult* attribute), 162
name (*dicee.DualE* attribute), 169
name (*dicee.EnsembleKGE* attribute), 185
name (*dicee.Keci* attribute), 163
name (*dicee.KeciBase* attribute), 162
name (*dicee.LFMult* attribute), 178
name (*dicee.models.AConEx* attribute), 106
name (*dicee.models.AConvO* attribute), 119
name (*dicee.models.AConvQ* attribute), 113
name (*dicee.models.clifford.DeCaL* attribute), 63
name (*dicee.models.clifford.Keci* attribute), 60
name (*dicee.models.clifford.KeciBase* attribute), 62
name (*dicee.models.ComplEx* attribute), 107
name (*dicee.models.complex.AConEx* attribute), 67
name (*dicee.models.complex.ComplEx* attribute), 68
name (*dicee.models.complex.ConEx* attribute), 66
name (*dicee.models.ConEx* attribute), 105
name (*dicee.models.ConvO* attribute), 118
name (*dicee.models.ConvQ* attribute), 112
name (*dicee.models.DeCaL* attribute), 123
name (*dicee.models.DistMult* attribute), 102
name (*dicee.models.DualE* attribute), 135
name (*dicee.models.dualE.DualE* attribute), 69
name (*dicee.models.ensemble.EnsembleKGE* attribute), 70
name (*dicee.models.FMult* attribute), 132
name (*dicee.models.FMult2* attribute), 133
name (*dicee.models.function_space.FMult* attribute), 71
name (*dicee.models.function_space.FMult2* attribute), 72
name (*dicee.models.function_space.GFMult* attribute), 71
name (*dicee.models.function_space.LFMult* attribute), 73
name (*dicee.models.function_space.LFMult1* attribute), 72
name (*dicee.models.GFMult* attribute), 132
name (*dicee.models.Keci* attribute), 120
name (*dicee.models.KeciBase* attribute), 122
name (*dicee.models.LFMult* attribute), 134
name (*dicee.models.LFMult1* attribute), 133
name (*dicee.models.octonion.AConvO* attribute), 76
name (*dicee.models.octonion.ConvO* attribute), 76
name (*dicee.models.octonion.OMult* attribute), 75
name (*dicee.models.OMult* attribute), 117
name (*dicee.models.Pyke* attribute), 103
name (*dicee.models.pykeen_models.PykeenKGE* attribute), 77
name (*dicee.models.PykeenKGE* attribute), 129
name (*dicee.models.QMult* attribute), 111
name (*dicee.models.quaternion.AConvQ* attribute), 81
name (*dicee.models.quaternion.ConvQ* attribute), 80
name (*dicee.models.quaternion.QMult* attribute), 79
name (*dicee.models.real.DistMult* attribute), 81
name (*dicee.models.real.Pyke* attribute), 82
name (*dicee.models.real.Shallom* attribute), 82
name (*dicee.models.real.TransE* attribute), 82
name (*dicee.models.Shallom* attribute), 102
name (*dicee.models.TransE* attribute), 102
name (*dicee.models.transformers.BytE* attribute), 84
name (*dicee.OMult* attribute), 177
name (*dicee.Pyke* attribute), 161

name (*dicee.PykeenKGE attribute*), 179
 name (*dicee.QMult attribute*), 175
 name (*dicee.Shallom attribute*), 177
 name (*dicee.TransE attribute*), 165
 named_children() (*dicee.EnsembleKGE method*), 185
 named_children() (*dicee.models.ensemble.EnsembleKGE method*), 70
 Namespace (*class in dicee.config*), 26
 neg_ratio (*dicee.BPE_NegativeSamplingDataset attribute*), 194
 neg_ratio (*dicee.config.Namespace attribute*), 27
 neg_ratio (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 29
 neg_ratio (*dicee.dataset_classes.KvsSampleDataset attribute*), 35
 neg_ratio (*dicee.KvsSampleDataset attribute*), 199
 neg_sample_ratio (*dicee.CVDataModule attribute*), 201
 neg_sample_ratio (*dicee.dataset_classes.CVDataModule attribute*), 37
 neg_sample_ratio (*dicee.dataset_classes.NegSampleDataset attribute*), 35
 neg_sample_ratio (*dicee.dataset_classes.OnevsSample attribute*), 33, 34
 neg_sample_ratio (*dicee.dataset_classes.TriplePredictionDataset attribute*), 36
 neg_sample_ratio (*dicee.NegSampleDataset attribute*), 200
 neg_sample_ratio (*dicee.OnevsSample attribute*), 198
 neg_sample_ratio (*dicee.TriplePredictionDataset attribute*), 201
 negnorm() (*dicee.KGE method*), 190
 negnorm() (*dicee.knowledge_graph_embeddings.KGE method*), 49
 NegSampleDataset (*class in dicee*), 199
 NegSampleDataset (*class in dicee.dataset_classes*), 35
 neural_searcher (*in module dicee.scripts.serve*), 146
 NeuralSearcher (*class in dicee.scripts.serve*), 146
 NodeTrainer (*class in dicee.trainer.torch_trainer_ddp*), 156
 norm_fc1 (*dicee.AConEx attribute*), 171
 norm_fc1 (*dicee.AConvO attribute*), 172
 norm_fc1 (*dicee.ConEx attribute*), 174
 norm_fc1 (*dicee.ConvO attribute*), 174
 norm_fc1 (*dicee.models.AConEx attribute*), 106
 norm_fc1 (*dicee.models.AConvO attribute*), 119
 norm_fc1 (*dicee.models.complex.AConEx attribute*), 67
 norm_fc1 (*dicee.models.complex.ConEx attribute*), 67
 norm_fc1 (*dicee.models.ConEx attribute*), 106
 norm_fc1 (*dicee.models.ConvO attribute*), 118
 norm_fc1 (*dicee.models.octonion.AConvO attribute*), 77
 norm_fc1 (*dicee.models.octonion.ConvO attribute*), 76
 normalization (*dicee.analyse_experiments.Experiment attribute*), 19
 normalization (*dicee.config.Namespace attribute*), 27
 normalize_head_entity_embeddings (*dicee.BaseKGE attribute*), 183
 normalize_head_entity_embeddings (*dicee.models.base_model.BaseKGE attribute*), 57
 normalize_head_entity_embeddings (*dicee.models.BaseKGE attribute*), 97, 101, 104, 109, 115, 127, 131
 normalize_relation_embeddings (*dicee.BaseKGE attribute*), 183
 normalize_relation_embeddings (*dicee.models.base_model.BaseKGE attribute*), 57
 normalize_relation_embeddings (*dicee.models.BaseKGE attribute*), 97, 101, 104, 109, 115, 127, 131
 normalize_tail_entity_embeddings (*dicee.BaseKGE attribute*), 183
 normalize_tail_entity_embeddings (*dicee.models.base_model.BaseKGE attribute*), 57
 normalize_tail_entity_embeddings (*dicee.models.BaseKGE attribute*), 97, 101, 104, 109, 115, 127, 131
 normalizer_class (*dicee.BaseKGE attribute*), 183
 normalizer_class (*dicee.models.base_model.BaseKGE attribute*), 57
 normalizer_class (*dicee.models.BaseKGE attribute*), 97, 100, 104, 109, 115, 127, 131
 num_bpe_entities (*dicee.BPE_NegativeSamplingDataset attribute*), 194
 num_bpe_entities (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 29
 num_bpe_entities (*dicee.knowledge_graph.KG attribute*), 45
 num_core (*dicee.config.Namespace attribute*), 27
 num_datapoints (*dicee.BPE_NegativeSamplingDataset attribute*), 194
 num_datapoints (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 29
 num_datapoints (*dicee.dataset_classes.MultiLabelDataset attribute*), 30
 num_datapoints (*dicee.MultiLabelDataset attribute*), 194
 num_ent (*dicee.DualE attribute*), 169
 num_ent (*dicee.models.DualE attribute*), 135
 num_ent (*dicee.models.dualE.DualE attribute*), 69
 num_entities (*dicee.BaseKGE attribute*), 183
 num_entities (*dicee.CVDataModule attribute*), 201
 num_entities (*dicee.dataset_classes.CVDataModule attribute*), 37
 num_entities (*dicee.dataset_classes.KvsSampleDataset attribute*), 35

`num_entities` (*dicee.dataset_classes.NegSampleDataset* attribute), 35
`num_entities` (*dicee.dataset_classes.OnevsSample* attribute), 33, 34
`num_entities` (*dicee.dataset_classes.TriplePredictionDataset* attribute), 36
`num_entities` (*dicee.evaluator.Evaluator* attribute), 41
`num_entities` (*dicee.knowledge_graph.KG* attribute), 45
`num_entities` (*dicee.KvsSampleDataset* attribute), 199
`num_entities` (*dicee.models.base_model.BaseKGE* attribute), 57
`num_entities` (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
`num_entities` (*dicee.NegSampleDataset* attribute), 200
`num_entities` (*dicee.OnevsSample* attribute), 197, 198
`num_entities` (*dicee.TriplePredictionDataset* attribute), 201
`num_epochs` (*dicee.abstracts.AbstractPPECallback* attribute), 17
`num_epochs` (*dicee.analyse_experiments.Experiment* attribute), 18
`num_epochs` (*dicee.callbacks.ASWA* attribute), 22
`num_epochs` (*dicee.config.Namespace* attribute), 26
`num_epochs` (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
`num_folds_for_cv` (*dicee.config.Namespace* attribute), 27
`num_of_data_points` (*dicee.dataset_classes.MultiClassClassificationDataset* attribute), 30
`num_of_data_points` (*dicee.MultiClassClassificationDataset* attribute), 195
`num_of_epochs` (*dicee.callbacks.PseudoLabellingCallback* attribute), 22
`num_of_output_channels` (*dicee.BaseKGE* attribute), 183
`num_of_output_channels` (*dicee.config.Namespace* attribute), 27
`num_of_output_channels` (*dicee.models.base_model.BaseKGE* attribute), 57
`num_of_output_channels` (*dicee.models.BaseKGE* attribute), 97, 100, 104, 109, 115, 127, 130
`num_params` (*dicee.analyse_experiments.Experiment* attribute), 18
`num_relations` (*dicee.BaseKGE* attribute), 183
`num_relations` (*dicee.CVDDataModule* attribute), 201
`num_relations` (*dicee.dataset_classes.CVDDataModule* attribute), 37
`num_relations` (*dicee.dataset_classes.NegSampleDataset* attribute), 35
`num_relations` (*dicee.dataset_classes.OnevsSample* attribute), 33, 34
`num_relations` (*dicee.dataset_classes.TriplePredictionDataset* attribute), 36
`num_relations` (*dicee.evaluator.Evaluator* attribute), 41
`num_relations` (*dicee.knowledge_graph.KG* attribute), 45
`num_relations` (*dicee.models.base_model.BaseKGE* attribute), 57
`num_relations` (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
`num_relations` (*dicee.NegSampleDataset* attribute), 200
`num_relations` (*dicee.OnevsSample* attribute), 198
`num_relations` (*dicee.TriplePredictionDataset* attribute), 201
`num_sample` (*dicee.models.FMult* attribute), 132
`num_sample` (*dicee.models.function_space.FMult* attribute), 71
`num_sample` (*dicee.models.function_space.GFMult* attribute), 71
`num_sample` (*dicee.models.GFMult* attribute), 132
`num_tokens` (*dicee.BaseKGE* attribute), 183
`num_tokens` (*dicee.knowledge_graph.KG* attribute), 45
`num_tokens` (*dicee.models.base_model.BaseKGE* attribute), 57
`num_tokens` (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
`num_workers` (*dicee.CVDDataModule* attribute), 201
`num_workers` (*dicee.dataset_classes.CVDDataModule* attribute), 37
`numpy_data_type_changer()` (in module *dicee*), 185
`numpy_data_type_changer()` (in module *dicee.static_funcs*), 148

O

`octonion_mul()` (in module *dicee.models*), 117
`octonion_mul()` (in module *dicee.models.octonion*), 74
`octonion_mul_norm()` (in module *dicee.models*), 117
`octonion_mul_norm()` (in module *dicee.models.octonion*), 74
`octonion_normalizer()` (*dicee.AConvO* static method), 172
`octonion_normalizer()` (*dicee.ConvO* static method), 174
`octonion_normalizer()` (*dicee.models.AConvO* static method), 119
`octonion_normalizer()` (*dicee.models.ConvO* static method), 119
`octonion_normalizer()` (*dicee.models.octonion.AConvO* static method), 77
`octonion_normalizer()` (*dicee.models.octonion.ConvO* static method), 76
`octonion_normalizer()` (*dicee.models.octonion.OMult* static method), 75
`octonion_normalizer()` (*dicee.models.OMult* static method), 117
`octonion_normalizer()` (*dicee.OMult* static method), 177
`OMult` (class in *dicee*), 176
`OMult` (class in *dicee.models*), 117

OMult (class in *dicee.models.octonion*), 74
 on_epoch_end() (*dicee.callbacks.KGESaveCallback* method), 22
 on_epoch_end() (*dicee.callbacks.PseudoLabellingCallback* method), 22
 on_fit_end() (*dicee.abstracts.AbstractCallback* method), 16
 on_fit_end() (*dicee.abstracts.AbstractPPECallback* method), 17
 on_fit_end() (*dicee.abstracts.AbstractTrainer* method), 13
 on_fit_end() (*dicee.callbacks.AccumulateEpochLossCallback* method), 20
 on_fit_end() (*dicee.callbacks.ASWA* method), 23
 on_fit_end() (*dicee.callbacks.Eval* method), 24
 on_fit_end() (*dicee.callbacks.KGESaveCallback* method), 22
 on_fit_end() (*dicee.callbacks.PrintCallback* method), 20
 on_fit_start() (*dicee.abstracts.AbstractCallback* method), 16
 on_fit_start() (*dicee.abstracts.AbstractPPECallback* method), 17
 on_fit_start() (*dicee.abstracts.AbstractTrainer* method), 12
 on_fit_start() (*dicee.callbacks.Eval* method), 24
 on_fit_start() (*dicee.callbacks.KGESaveCallback* method), 21
 on_fit_start() (*dicee.callbacks.KronE* method), 25
 on_fit_start() (*dicee.callbacks.PrintCallback* method), 20
 on_init_end() (*dicee.abstracts.AbstractCallback* method), 16
 on_init_start() (*dicee.abstracts.AbstractCallback* method), 15
 on_train_batch_end() (*dicee.abstracts.AbstractCallback* method), 16
 on_train_batch_end() (*dicee.abstracts.AbstractTrainer* method), 13
 on_train_batch_end() (*dicee.callbacks.Eval* method), 24
 on_train_batch_end() (*dicee.callbacks.KGESaveCallback* method), 21
 on_train_batch_end() (*dicee.callbacks.PrintCallback* method), 20
 on_train_batch_start() (*dicee.callbacks.Perturb* method), 25
 on_train_epoch_end() (*dicee.abstracts.AbstractCallback* method), 16
 on_train_epoch_end() (*dicee.abstracts.AbstractTrainer* method), 13
 on_train_epoch_end() (*dicee.callbacks.ASWA* method), 23
 on_train_epoch_end() (*dicee.callbacks.Eval* method), 24
 on_train_epoch_end() (*dicee.callbacks.KGESaveCallback* method), 21
 on_train_epoch_end() (*dicee.callbacks.PrintCallback* method), 21
 on_train_epoch_end() (*dicee.models.base_model.BaseKGELightning* method), 52
 on_train_epoch_end() (*dicee.models.BaseKGELightning* method), 92
 OnevsAllDataset (class in *dicee*), 195
 OnevsAllDataset (class in *dicee.dataset_classes*), 31
 OnevsSample (class in *dicee*), 197
 OnevsSample (class in *dicee.dataset_classes*), 33
 optim (*dicee.config.Namespace* attribute), 26
 optimizer (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 156
 optimizer (*dicee.trainer.torch_trainer.TorchTrainer* attribute), 155
 optimizer_name (*dicee.BaseKGE* attribute), 183
 optimizer_name (*dicee.models.base_model.BaseKGE* attribute), 57
 optimizer_name (*dicee.models.BaseKGE* attribute), 97, 100, 104, 108, 114, 127, 130
 optimizers (*dicee.EnsembleKGE* attribute), 185
 optimizers (*dicee.models.ensemble.EnsembleKGE* attribute), 70
 ordered_bpe_entities (*dicee.BPE_NegativeSamplingDataset* attribute), 194
 ordered_bpe_entities (*dicee.dataset_classes.BPE_NegativeSamplingDataset* attribute), 29
 ordered_bpe_entities (*dicee.knowledge_graph.KG* attribute), 46
 ordered_shaped_bpe_tokens (*dicee.knowledge_graph.KG* attribute), 45

P

p (*dicee.config.Namespace* attribute), 28
 p (*dicee.DeCaL* attribute), 166
 p (*dicee.Keci* attribute), 163
 p (*dicee.models.clifford.DeCaL* attribute), 63
 p (*dicee.models.clifford.Keci* attribute), 60
 p (*dicee.models.DeCaL* attribute), 123
 p (*dicee.models.Keci* attribute), 120
 padding (*dicee.knowledge_graph.KG* attribute), 46
 pandas_dataframe_indexer() (in module *dicee.read_preprocess_save_load_kg.util*), 141
 param_init (*dicee.BaseKGE* attribute), 183
 param_init (*dicee.models.base_model.BaseKGE* attribute), 57
 param_init (*dicee.models.BaseKGE* attribute), 97, 101, 104, 109, 115, 127, 131
 parameters() (*dicee.abstracts.BaseInteractiveKGE* method), 15
 parameters() (*dicee.EnsembleKGE* method), 185
 parameters() (*dicee.models.ensemble.EnsembleKGE* method), 70

path (*dicee.abstracts.AbstractPPECallback* attribute), 17
 path (*dicee.callbacks.AccumulateEpochLossCallback* attribute), 20
 path (*dicee.callbacks.ASWA* attribute), 22
 path (*dicee.callbacks.Eval* attribute), 23
 path (*dicee.callbacks.KGESaveCallback* attribute), 21
 path_dataset_folder (*dicee.analyse_experiments.Experiment* attribute), 18
 path_for_deserialization (*dicee.knowledge_graph.KG* attribute), 45
 path_for_serialization (*dicee.knowledge_graph.KG* attribute), 45
 path_single_kg (*dicee.config.Namespace* attribute), 26
 path_single_kg (*dicee.knowledge_graph.KG* attribute), 45
 path_to_store_single_run (*dicee.config.Namespace* attribute), 26
 Perturb (*class in dicee.callbacks*), 25
 polars_dataframe_indexer() (in module *dicee.read_preprocess_save_load_kg.util*), 140
 poly_NN() (*dicee.LFMMult* method), 178
 poly_NN() (*dicee.models.function_space.LFMMult* method), 73
 poly_NN() (*dicee.models.LFMMult* method), 134
 polynomial() (*dicee.LFMMult* method), 179
 polynomial() (*dicee.models.function_space.LFMMult* method), 74
 polynomial() (*dicee.models.LFMMult* method), 135
 pop() (*dicee.LFMMult* method), 179
 pop() (*dicee.models.function_space.LFMMult* method), 74
 pop() (*dicee.models.LFMMult* method), 135
 pq (*dicee.analyse_experiments.Experiment* attribute), 18
 predict() (*dicee.KGE* method), 189
 predict() (*dicee.knowledge_graph_embeddings.KGE* method), 48
 predict_data_loader() (*dicee.models.base_model.BaseKGELightning* method), 54
 predict_data_loader() (*dicee.models.BaseKGELightning* method), 94
 predict_missing_head_entity() (*dicee.KGE* method), 188
 predict_missing_head_entity() (*dicee.knowledge_graph_embeddings.KGE* method), 47
 predict_missing_relations() (*dicee.KGE* method), 189
 predict_missing_relations() (*dicee.knowledge_graph_embeddings.KGE* method), 47
 predict_missing_tail_entity() (*dicee.KGE* method), 189
 predict_missing_tail_entity() (*dicee.knowledge_graph_embeddings.KGE* method), 47
 predict_topk() (*dicee.KGE* method), 190
 predict_topk() (*dicee.knowledge_graph_embeddings.KGE* method), 48
 prepare_data() (*dicee.CVDataModule* method), 203
 prepare_data() (*dicee.dataset_classes.CVDataModule* method), 39
 preprocess_with_byte_pair_encoding() (*dicee.read_preprocess_save_load_kg.PreprocessKG* method), 143
 preprocess_with_byte_pair_encoding() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG* method), 138
 preprocess_with_byte_pair_encoding_with_padding() (*dicee.read_preprocess_save_load_kg.PreprocessKG* method), 143
 preprocess_with_byte_pair_encoding_with_padding() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG* method), 138
 preprocess_with_pandas() (*dicee.read_preprocess_save_load_kg.PreprocessKG* method), 143
 preprocess_with_pandas() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG* method), 138
 preprocess_with_polars() (*dicee.read_preprocess_save_load_kg.PreprocessKG* method), 144
 preprocess_with_polars() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG* method), 138
 preprocesses_input_args() (in module *dicee.static_preprocess_funcs*), 151
 PreprocessKG (*class in dicee.read_preprocess_save_load_kg*), 143
 PreprocessKG (*class in dicee.read_preprocess_save_load_kg.preprocess*), 138
 PrintCallback (*class in dicee.callbacks*), 20
 process (*dicee.trainer.torch_trainer.TorchTrainer* attribute), 155
 PseudoLabellingCallback (*class in dicee.callbacks*), 22
 Pyke (*class in dicee*), 161
 Pyke (*class in dicee.models*), 103
 Pyke (*class in dicee.models.real*), 82
 pykeen_model_kwargs (*dicee.config.Namespace* attribute), 27
 PykeenKGE (*class in dicee*), 179
 PykeenKGE (*class in dicee.models*), 129
 PykeenKGE (*class in dicee.models.pykeen_models*), 77

Q

q (*dicee.config.Namespace* attribute), 28
 q (*dicee.DeCaL* attribute), 166
 q (*dicee.Keci* attribute), 163
 q (*dicee.models.clifford.DeCaL* attribute), 63
 q (*dicee.models.clifford.Keci* attribute), 60
 q (*dicee.models.DeCaL* attribute), 123
 q (*dicee.models.Keci* attribute), 120

qdrant_client (*dicee.scripts.serve.NeuralSearcher* attribute), 146
 QMult (*class in dicee*), 175
 QMult (*class in dicee.models*), 111
 QMult (*class in dicee.models.quaternion*), 78
 quaternion_mul () (*in module dicee.models*), 107
 quaternion_mul () (*in module dicee.models.static_funcs*), 83
 quaternion_mul_with_unit_norm () (*in module dicee.models*), 111
 quaternion_mul_with_unit_norm () (*in module dicee.models.quaternion*), 78
 quaternion_multiplication_followed_by_inner_product () (*dicee.models.QMult* method), 111
 quaternion_multiplication_followed_by_inner_product () (*dicee.models.quaternion.QMult* method), 79
 quaternion_multiplication_followed_by_inner_product () (*dicee.QMult* method), 175
 quaternion_normalizer () (*dicee.models.QMult* static method), 112
 quaternion_normalizer () (*dicee.models.quaternion.QMult* static method), 79
 quaternion_normalizer () (*dicee.QMult* static method), 176
 query_name_to_struct (*dicee.query_generator.QueryGenerator* attribute), 137
 query_name_to_struct (*dicee.QueryGenerator* attribute), 205
 QueryGenerator (*class in dicee*), 204
 QueryGenerator (*class in dicee.query_generator*), 136

R

r (*dicee.DeCaL* attribute), 166
 r (*dicee.Keci* attribute), 163
 r (*dicee.models.clifford.DeCaL* attribute), 63
 r (*dicee.models.clifford.Keci* attribute), 60
 r (*dicee.models.DeCaL* attribute), 123
 r (*dicee.models.Keci* attribute), 120
 random_prediction () (*in module dicee*), 186
 random_prediction () (*in module dicee.static_funcs*), 149
 random_seed (*dicee.config.Namespace* attribute), 27
 ratio (*dicee.callbacks.Perturb* attribute), 25
 re (*dicee.DeCaL* attribute), 166
 re (*dicee.models.clifford.DeCaL* attribute), 63
 re (*dicee.models.DeCaL* attribute), 123
 re_vocab (*dicee.evaluator.Evaluator* attribute), 41
 read_from_disk () (*in module dicee.read_preprocess_save_load_kg.util*), 142
 read_from_triple_store () (*in module dicee.read_preprocess_save_load_kg.util*), 142
 read_only_few (*dicee.config.Namespace* attribute), 27
 read_only_few (*dicee.knowledge_graph.KG* attribute), 45
 read_or_load_kg () (*in module dicee*), 186
 read_or_load_kg () (*in module dicee.static_funcs*), 149
 read_with_pandas () (*in module dicee.read_preprocess_save_load_kg.util*), 142
 read_with_polars () (*in module dicee.read_preprocess_save_load_kg.util*), 142
 ReadFromDisk (*class in dicee.read_preprocess_save_load_kg*), 144
 ReadFromDisk (*class in dicee.read_preprocess_save_load_kg.read_from_disk*), 138
 rel2id (*dicee.query_generator.QueryGenerator* attribute), 136
 rel2id (*dicee.QueryGenerator* attribute), 205
 relation_embeddings (*dicee.AConvQ* attribute), 172
 relation_embeddings (*dicee.ConvQ* attribute), 173
 relation_embeddings (*dicee.DeCaL* attribute), 166
 relation_embeddings (*dicee.DualE* attribute), 169
 relation_embeddings (*dicee.LFMult* attribute), 178
 relation_embeddings (*dicee.models.AConvQ* attribute), 113
 relation_embeddings (*dicee.models.clifford.DeCaL* attribute), 63
 relation_embeddings (*dicee.models.ConvQ* attribute), 112
 relation_embeddings (*dicee.models.DeCaL* attribute), 123
 relation_embeddings (*dicee.models.DualE* attribute), 135
 relation_embeddings (*dicee.models.dualE.DualE* attribute), 69
 relation_embeddings (*dicee.models.FMult* attribute), 132
 relation_embeddings (*dicee.models.FMult2* attribute), 133
 relation_embeddings (*dicee.models.function_space.FMult* attribute), 71
 relation_embeddings (*dicee.models.function_space.FMult2* attribute), 72
 relation_embeddings (*dicee.models.function_space.GFMult* attribute), 71
 relation_embeddings (*dicee.models.function_space.LFMult* attribute), 73
 relation_embeddings (*dicee.models.function_space.LFMult1* attribute), 72
 relation_embeddings (*dicee.models.GFMult* attribute), 132
 relation_embeddings (*dicee.models.LFMult* attribute), 134
 relation_embeddings (*dicee.models.LFMult1* attribute), 133

- `relation_embeddings` (*dicee.models.pykeen_models.PykeenKGE attribute*), 77
- `relation_embeddings` (*dicee.models.PykeenKGE attribute*), 129
- `relation_embeddings` (*dicee.models.quaternion.AConvQ attribute*), 81
- `relation_embeddings` (*dicee.models.quaternion.ConvQ attribute*), 80
- `relation_embeddings` (*dicee.PykeenKGE attribute*), 179
- `relation_to_idx` (*dicee.knowledge_graph.KG attribute*), 45
- `relations_str` (*dicee.knowledge_graph.KG property*), 46
- `reload_dataset()` (*in module dicee*), 193
- `reload_dataset()` (*in module dicee.dataset_classes*), 29
- `report` (*dicee.DICE_Trainer attribute*), 187
- `report` (*dicee.evaluator.Evaluator attribute*), 41
- `report` (*dicee.Execute attribute*), 192
- `report` (*dicee.executer.Execute attribute*), 43
- `report` (*dicee.trainer.DICE_Trainer attribute*), 157
- `report` (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 152
- `reports` (*dicee.callbacks.Eval attribute*), 23
- `requires_grad_for_interactions` (*dicee.Keci attribute*), 163
- `requires_grad_for_interactions` (*dicee.KeciBase attribute*), 162
- `requires_grad_for_interactions` (*dicee.models.clifford.Keci attribute*), 60
- `requires_grad_for_interactions` (*dicee.models.clifford.KeciBase attribute*), 62
- `requires_grad_for_interactions` (*dicee.models.Keci attribute*), 120
- `requires_grad_for_interactions` (*dicee.models.KeciBase attribute*), 122
- `resid_dropout` (*dicee.models.transformers.CausalSelfAttention attribute*), 86
- `residual_convolution()` (*dicee.AConEx method*), 171
- `residual_convolution()` (*dicee.AConvO method*), 172
- `residual_convolution()` (*dicee.AConvQ method*), 172
- `residual_convolution()` (*dicee.ConEx method*), 174
- `residual_convolution()` (*dicee.ConvO method*), 174
- `residual_convolution()` (*dicee.ConvQ method*), 173
- `residual_convolution()` (*dicee.models.AConEx method*), 106
- `residual_convolution()` (*dicee.models.AConvO method*), 119
- `residual_convolution()` (*dicee.models.AConvQ method*), 113
- `residual_convolution()` (*dicee.models.complex.AConEx method*), 67
- `residual_convolution()` (*dicee.models.complex.ConEx method*), 67
- `residual_convolution()` (*dicee.models.ConEx method*), 106
- `residual_convolution()` (*dicee.models.ConvO method*), 119
- `residual_convolution()` (*dicee.models.ConvQ method*), 113
- `residual_convolution()` (*dicee.models.octonion.AConvO method*), 77
- `residual_convolution()` (*dicee.models.octonion.ConvO method*), 76
- `residual_convolution()` (*dicee.models.quaternion.AConvQ method*), 81
- `residual_convolution()` (*dicee.models.quaternion.ConvQ method*), 80
- `retrieve_embeddings()` (*in module dicee.scripts.serve*), 146
- `return_multi_hop_query_results()` (*dicee.KGE method*), 191
- `return_multi_hop_query_results()` (*dicee.knowledge_graph_embeddings.KGE method*), 49
- `root()` (*in module dicee.scripts.serve*), 146
- `roots` (*dicee.models.FMult attribute*), 132
- `roots` (*dicee.models.function_space.FMult attribute*), 71
- `roots` (*dicee.models.function_space.GFMult attribute*), 71
- `roots` (*dicee.models.GFMult attribute*), 133
- `runtime` (*dicee.analyse_experiments.Experiment attribute*), 19

S

- `sample_counter` (*dicee.abstracts.AbstractPPECallback attribute*), 17
- `sample_entity()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
- `sample_relation()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
- `sample_triples_ratio` (*dicee.config.Namespace attribute*), 27
- `sample_triples_ratio` (*dicee.knowledge_graph.KG attribute*), 45
- `sanity_checking_with_arguments()` (*in module dicee.sanity_checkers*), 145
- `save()` (*dicee.abstracts.BaseInteractiveKGE method*), 14
- `save()` (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk method*), 144
- `save()` (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk method*), 139
- `save_checkpoint()` (*dicee.abstracts.AbstractTrainer static method*), 13
- `save_checkpoint_model()` (*in module dicee*), 186
- `save_checkpoint_model()` (*in module dicee.static_funcs*), 148
- `save_embeddings()` (*in module dicee*), 186
- `save_embeddings()` (*in module dicee.static_funcs*), 149
- `save_embeddings_as_csv` (*dicee.config.Namespace attribute*), 26

save_experiment() (*dicее.analyse_experiments.Experiment method*), 19
 save_model_at_every_epoch (*dicее.config.Namespace attribute*), 27
 save_numpy_ndarray() (*in module dicее*), 185
 save_numpy_ndarray() (*in module dicее.read_preprocess_save_load_kg.util*), 142
 save_numpy_ndarray() (*in module dicее.static_funcs*), 148
 save_pickle() (*in module dicее*), 184
 save_pickle() (*in module dicее.read_preprocess_save_load_kg.util*), 143
 save_pickle() (*in module dicее.static_funcs*), 148
 save_queries() (*dicее.query_generator.QueryGenerator method*), 137
 save_queries() (*dicее.QueryGenerator method*), 205
 save_queries_and_answers() (*dicее.query_generator.QueryGenerator static method*), 137
 save_queries_and_answers() (*dicее.QueryGenerator static method*), 205
 save_trained_model() (*dicее.Execute method*), 192
 save_trained_model() (*dicее.executer.Execute method*), 43
 scalar_batch_NN() (*dicее.LFMMult method*), 178
 scalar_batch_NN() (*dicее.models.function_space.LFMMult method*), 73
 scalar_batch_NN() (*dicее.models.LFMMult method*), 134
 scaler (*dicее.callbacks.Perturb attribute*), 25
 scaler (*dicее.trainer.torch_trainer_ddp.NodeTrainer attribute*), 157
 score() (*dicее.ComplEx static method*), 170
 score() (*dicее.DistMult method*), 162
 score() (*dicее.Keci method*), 165
 score() (*dicее.models.clifford.Keci method*), 62
 score() (*dicее.models.ComplEx static method*), 107
 score() (*dicее.models.complex.ComplEx static method*), 68
 score() (*dicее.models.DistMult method*), 102
 score() (*dicее.models.Keci method*), 122
 score() (*dicее.models.octonion.OMult method*), 75
 score() (*dicее.models.OMult method*), 118
 score() (*dicее.models.QMult method*), 112
 score() (*dicее.models.quaternion.QMult method*), 80
 score() (*dicее.models.real.DistMult method*), 82
 score() (*dicее.models.real.TransE method*), 82
 score() (*dicее.models.TransE method*), 102
 score() (*dicее.OMult method*), 177
 score() (*dicее.QMult method*), 176
 score() (*dicее.TransE method*), 165
 score_func (*dicее.models.FMMult2 attribute*), 133
 score_func (*dicее.models.function_space.FMMult2 attribute*), 72
 scoring_technique (*dicее.analyse_experiments.Experiment attribute*), 19
 scoring_technique (*dicее.config.Namespace attribute*), 27
 search() (*dicее.scripts.serve.NeuralSearcher method*), 146
 search_embeddings() (*in module dicее.scripts.serve*), 146
 seed (*dicее.query_generator.QueryGenerator attribute*), 136
 seed (*dicее.QueryGenerator attribute*), 204
 select_model() (*in module dicее*), 185
 select_model() (*in module dicее.static_funcs*), 148
 selected_optimizer (*dicее.BaseKGE attribute*), 183
 selected_optimizer (*dicее.models.base_model.BaseKGE attribute*), 57
 selected_optimizer (*dicее.models.BaseKGE attribute*), 97, 100, 104, 109, 115, 127, 130
 separator (*dicее.config.Namespace attribute*), 27
 separator (*dicее.knowledge_graph.KG attribute*), 46
 sequential_vocabulary_construction() (*dicее.read_preprocess_save_load_kg.PreprocessKG method*), 144
 sequential_vocabulary_construction() (*dicее.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 138
 set_global_seed() (*dicее.query_generator.QueryGenerator method*), 137
 set_global_seed() (*dicее.QueryGenerator method*), 205
 set_model_eval_mode() (*dicее.abstracts.BaseInteractiveKGE method*), 14
 set_model_train_mode() (*dicее.abstracts.BaseInteractiveKGE method*), 14
 setup() (*dicее.CVDataModule method*), 202
 setup() (*dicее.dataset_classes.CVDataModule method*), 38
 setup_executor() (*dicее.Execute method*), 192
 setup_executor() (*dicее.executer.Execute method*), 43
 Shallom (*class in dicее*), 177
 Shallom (*class in dicее.models*), 102
 Shallom (*class in dicее.models.real*), 82
 shallom (*dicее.models.real.Shallom attribute*), 82
 shallom (*dicее.models.Shallom attribute*), 102
 shallom (*dicее.Shallom attribute*), 177

single_hop_query_answering() (*diccee.KGE method*), 191
 single_hop_query_answering() (*diccee.knowledge_graph_embeddings.KGE method*), 49
 sparql_endpoint (*diccee.config.Namespace attribute*), 26
 sparql_endpoint (*diccee.knowledge_graph.KG attribute*), 45
 start() (*diccee.DICE_Trainer method*), 187
 start() (*diccee.Execute method*), 193
 start() (*diccee.executer.Execute method*), 44
 start() (*diccee.read_preprocess_save_load_kg.PreprocessKG method*), 143
 start() (*diccee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 138
 start() (*diccee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk method*), 138
 start() (*diccee.read_preprocess_save_load_kg.ReadFromDisk method*), 144
 start() (*diccee.trainer.DICE_Trainer method*), 158
 start() (*diccee.trainer.dice_trainer.DICE_Trainer method*), 153
 start_time (*diccee.callbacks.PrintCallback attribute*), 20
 start_time (*diccee.Execute attribute*), 192
 start_time (*diccee.executer.Execute attribute*), 43
 step() (*diccee.EnsembleKGE method*), 185
 step() (*diccee.models.ensemble.EnsembleKGE method*), 70
 storage_path (*diccee.config.Namespace attribute*), 26
 storage_path (*diccee.DICE_Trainer attribute*), 187
 storage_path (*diccee.trainer.DICE_Trainer attribute*), 157
 storage_path (*diccee.trainer.dice_trainer.DICE_Trainer attribute*), 152
 store() (*in module diccee*), 186
 store() (*in module diccee.static_funcs*), 149
 store_ensemble() (*diccee.abstracts.AbstractPPECallback method*), 17
 strategy (*diccee.abstracts.AbstractTrainer attribute*), 12
 swa (*diccee.config.Namespace attribute*), 28

T

T() (*diccee.DualE method*), 170
 T() (*diccee.models.DualE method*), 136
 T() (*diccee.models.dualE.DualE method*), 70
 t_conorm() (*diccee.KGE method*), 190
 t_conorm() (*diccee.knowledge_graph_embeddings.KGE method*), 49
 t_norm() (*diccee.KGE method*), 190
 t_norm() (*diccee.knowledge_graph_embeddings.KGE method*), 49
 target_dim (*diccee.AllvsAll attribute*), 197
 target_dim (*diccee.dataset_classes.AllvsAll attribute*), 33
 target_dim (*diccee.dataset_classes.MultiLabelDataset attribute*), 30
 target_dim (*diccee.dataset_classes.OnevsAllDataset attribute*), 31
 target_dim (*diccee.knowledge_graph.KG attribute*), 46
 target_dim (*diccee.MultiLabelDataset attribute*), 194
 target_dim (*diccee.OnevsAllDataset attribute*), 195
 temperature (*diccee.BytE attribute*), 180
 temperature (*diccee.models.transformers.BytE attribute*), 84
 tensor_t_norm() (*diccee.KGE method*), 190
 tensor_t_norm() (*diccee.knowledge_graph_embeddings.KGE method*), 49
 TensorParallel (*class in diccee.trainer.model_parallelism*), 154
 test_data_loader() (*diccee.models.base_model.BaseKGELightning method*), 53
 test_data_loader() (*diccee.models.BaseKGELightning method*), 93
 test_epoch_end() (*diccee.models.base_model.BaseKGELightning method*), 53
 test_epoch_end() (*diccee.models.BaseKGELightning method*), 93
 test_h1 (*diccee.analyse_experiments.Experiment attribute*), 19
 test_h3 (*diccee.analyse_experiments.Experiment attribute*), 19
 test_h10 (*diccee.analyse_experiments.Experiment attribute*), 19
 test_mrr (*diccee.analyse_experiments.Experiment attribute*), 19
 test_path (*diccee.query_generator.QueryGenerator attribute*), 136
 test_path (*diccee.QueryGenerator attribute*), 204
 timeit() (*in module diccee*), 184, 193
 timeit() (*in module diccee.read_preprocess_save_load_kg.util*), 142
 timeit() (*in module diccee.static_funcs*), 148
 timeit() (*in module diccee.static_preprocess_funcs*), 151
 to() (*diccee.EnsembleKGE method*), 185
 to() (*diccee.KGE method*), 188
 to() (*diccee.knowledge_graph_embeddings.KGE method*), 46
 to() (*diccee.models.ensemble.EnsembleKGE method*), 70
 to_df() (*diccee.analyse_experiments.Experiment method*), 19

topk (*dicee.BytE* attribute), 180
 topk (*dicee.models.transformers.BytE* attribute), 84
 torch_buggy_fit () (*dicee.trainer.model_parallelism.TensorParallel* method), 154
 torch_ordered_shaped_bpe_entities (*dicee.dataset_classes.MultiLabelDataset* attribute), 30
 torch_ordered_shaped_bpe_entities (*dicee.MultiLabelDataset* attribute), 194
 TorchDDPTrainer (class in *dicee.trainer.torch_trainer_ddp*), 156
 TorchTrainer (class in *dicee.trainer.torch_trainer*), 155
 train () (*dicee.KGE* method), 192
 train () (*dicee.knowledge_graph_embeddings.KGE* method), 50
 train () (*dicee.trainer.torch_trainer_ddp.NodeTrainer* method), 157
 train_data (*dicee.AllvsAll* attribute), 197
 train_data (*dicee.dataset_classes.AllvsAll* attribute), 32
 train_data (*dicee.dataset_classes.KvsAll* attribute), 32
 train_data (*dicee.dataset_classes.KvsSampleDataset* attribute), 35
 train_data (*dicee.dataset_classes.MultiClassClassificationDataset* attribute), 30
 train_data (*dicee.dataset_classes.OnevsAllDataset* attribute), 31
 train_data (*dicee.dataset_classes.OnevsSample* attribute), 33, 34
 train_data (*dicee.KvsAll* attribute), 196
 train_data (*dicee.KvsSampleDataset* attribute), 199
 train_data (*dicee.MultiClassClassificationDataset* attribute), 195
 train_data (*dicee.OnevsAllDataset* attribute), 195
 train_data (*dicee.OnevsSample* attribute), 197, 198
 train_data_loader () (*dicee.CVDDataModule* method), 201
 train_data_loader () (*dicee.dataset_classes.CVDDataModule* method), 37
 train_data_loader () (*dicee.models.base_model.BaseKGELightning* method), 54
 train_data_loader () (*dicee.models.BaseKGELightning* method), 94
 train_data_loaders (*dicee.trainer.torch_trainer.TorchTrainer* attribute), 155
 train_dataset_loader (*dicee.trainer.torch_trainer_ddp.NodeTrainer* attribute), 157
 train_h1 (*dicee.analyse_experiments.Experiment* attribute), 18
 train_h3 (*dicee.analyse_experiments.Experiment* attribute), 18
 train_h10 (*dicee.analyse_experiments.Experiment* attribute), 18
 train_indices_target (*dicee.dataset_classes.MultiLabelDataset* attribute), 30
 train_indices_target (*dicee.MultiLabelDataset* attribute), 194
 train_k_vs_all () (*dicee.KGE* method), 192
 train_k_vs_all () (*dicee.knowledge_graph_embeddings.KGE* method), 50
 train_mode (*dicee.EnsembleKGE* attribute), 185
 train_mode (*dicee.models.ensemble.EnsembleKGE* attribute), 70
 train_mrr (*dicee.analyse_experiments.Experiment* attribute), 18
 train_path (*dicee.query_generator.QueryGenerator* attribute), 136
 train_path (*dicee.QueryGenerator* attribute), 204
 train_set (*dicee.BPE_NegativeSamplingDataset* attribute), 194
 train_set (*dicee.dataset_classes.BPE_NegativeSamplingDataset* attribute), 29
 train_set (*dicee.dataset_classes.MultiLabelDataset* attribute), 30
 train_set (*dicee.dataset_classes.NegSampleDataset* attribute), 35
 train_set (*dicee.dataset_classes.TriplePredictionDataset* attribute), 36
 train_set (*dicee.MultiLabelDataset* attribute), 194
 train_set (*dicee.NegSampleDataset* attribute), 200
 train_set (*dicee.TriplePredictionDataset* attribute), 201
 train_set_idx (*dicee.CVDDataModule* attribute), 201
 train_set_idx (*dicee.dataset_classes.CVDDataModule* attribute), 37
 train_set_target (*dicee.knowledge_graph.KG* attribute), 46
 train_target (*dicee.AllvsAll* attribute), 197
 train_target (*dicee.dataset_classes.AllvsAll* attribute), 32
 train_target (*dicee.dataset_classes.KvsAll* attribute), 32
 train_target (*dicee.dataset_classes.KvsSampleDataset* attribute), 35
 train_target (*dicee.KvsAll* attribute), 196
 train_target (*dicee.KvsSampleDataset* attribute), 199
 train_target_indices (*dicee.knowledge_graph.KG* attribute), 46
 train_triples () (*dicee.KGE* method), 192
 train_triples () (*dicee.knowledge_graph_embeddings.KGE* method), 50
 trained_model (*dicee.Execute* attribute), 192
 trained_model (*dicee.executer.Execute* attribute), 43
 trainer (*dicee.config.Namespace* attribute), 27
 trainer (*dicee.DICE_Trainer* attribute), 187
 trainer (*dicee.Execute* attribute), 192
 trainer (*dicee.executer.Execute* attribute), 43
 trainer (*dicee.trainer.DICE_Trainer* attribute), 157
 trainer (*dicee.trainer.dice_trainer.DICE_Trainer* attribute), 152

trainer (*dicее.trainer.torch_trainer_ddp.NodeTrainer attribute*), 156
 training_step (*dicее.trainer.torch_trainer.TorchTrainer attribute*), 155
 training_step() (*dicее.BytE method*), 181
 training_step() (*dicее.models.base_model.BaseKGELightning method*), 51
 training_step() (*dicее.models.BaseKGELightning method*), 91
 training_step() (*dicее.models.transformers.BytE method*), 84
 training_step_outputs (*dicее.models.base_model.BaseKGELightning attribute*), 51
 training_step_outputs (*dicее.models.BaseKGELightning attribute*), 91
 training_technique (*dicее.knowledge_graph.KG attribute*), 45
 TransE (*class in dicее*), 165
 TransE (*class in dicее.models*), 102
 TransE (*class in dicее.models.real*), 82
 transfer_batch_to_device() (*dicее.CVDDataModule method*), 202
 transfer_batch_to_device() (*dicее.dataset_classes.CVDDataModule method*), 38
 transformer (*dicее.BytE attribute*), 180
 transformer (*dicее.models.transformers.BytE attribute*), 84
 transformer (*dicее.models.transformers.GPT attribute*), 89
 trapezoid() (*dicее.models.FMult2 method*), 133
 trapezoid() (*dicее.models.function_space.FMult2 method*), 72
 tri_score() (*dicее.LFMult method*), 178
 tri_score() (*dicее.models.function_space.LFMult method*), 73
 tri_score() (*dicее.models.function_space.LFMult1 method*), 73
 tri_score() (*dicее.models.LFMult method*), 134
 tri_score() (*dicее.models.LFMult1 method*), 134
 triple_score() (*dicее.KGE method*), 190
 triple_score() (*dicее.knowledge_graph_embeddings.KGE method*), 48
 TriplePredictionDataset (*class in dicее*), 200
 TriplePredictionDataset (*class in dicее.dataset_classes*), 36
 tuple2list() (*dicее.query_generator.QueryGenerator method*), 137
 tuple2list() (*dicее.QueryGenerator method*), 205

U

unlabelled_size (*dicее.callbacks.PseudoLabellingCallback attribute*), 22
 unmap() (*dicее.query_generator.QueryGenerator method*), 137
 unmap() (*dicее.QueryGenerator method*), 205
 unmap_query() (*dicее.query_generator.QueryGenerator method*), 137
 unmap_query() (*dicее.QueryGenerator method*), 205

V

val_aswa (*dicее.callbacks.ASWA attribute*), 23
 val_dataloader() (*dicее.models.base_model.BaseKGELightning method*), 53
 val_dataloader() (*dicее.models.BaseKGELightning method*), 93
 val_h1 (*dicее.analyse_experiments.Experiment attribute*), 18
 val_h3 (*dicее.analyse_experiments.Experiment attribute*), 18
 val_h10 (*dicее.analyse_experiments.Experiment attribute*), 18
 val_mrr (*dicее.analyse_experiments.Experiment attribute*), 18
 val_path (*dicее.query_generator.QueryGenerator attribute*), 136
 val_path (*dicее.QueryGenerator attribute*), 204
 validate_knowledge_graph() (*in module dicее.sanity_checkers*), 144
 vocab_preparation() (*dicее.evaluator.Evaluator method*), 42
 vocab_size (*dicее.models.transformers.GPTConfig attribute*), 88
 vocab_to_parquet() (*in module dicее*), 186
 vocab_to_parquet() (*in module dicее.static_funcs*), 149
 vtp_score() (*dicее.LFMult method*), 178
 vtp_score() (*dicее.models.function_space.LFMult method*), 73
 vtp_score() (*dicее.models.function_space.LFMult1 method*), 73
 vtp_score() (*dicее.models.LFMult method*), 134
 vtp_score() (*dicее.models.LFMult1 method*), 134

W

weight (*dicее.models.transformers.LayerNorm attribute*), 85
 weight_decay (*dicее.BaseKGE attribute*), 183
 weight_decay (*dicее.config.Namespace attribute*), 27
 weight_decay (*dicее.models.base_model.BaseKGE attribute*), 57
 weight_decay (*dicее.models.BaseKGE attribute*), 97, 100, 104, 109, 115, 127, 130
 weights (*dicее.models.FMult attribute*), 132

`weights` (*dicee.models.function_space.FMult attribute*), 71
`weights` (*dicee.models.function_space.GFMult attribute*), 72
`weights` (*dicee.models.GFMult attribute*), 133
`write_csv_from_model_parallel()` (*in module dicee*), 186
`write_csv_from_model_parallel()` (*in module dicee.static_funcs*), 150
`write_links()` (*dicee.query_generator.QueryGenerator method*), 137
`write_links()` (*dicee.QueryGenerator method*), 205
`write_report()` (*dicee.Execute method*), 193
`write_report()` (*dicee.executer.Execute method*), 44

X

`x_values` (*dicee.LFMult attribute*), 178
`x_values` (*dicee.models.function_space.LFMult attribute*), 73
`x_values` (*dicee.models.LFMult attribute*), 134