DICE Embeddings

Release 0.1.3.2

Caglar Demir

Jun 06, 2025

Contents:

1	Dicee Manual	2
2	Installation 2.1 Installation from Source	3 3
3	Download Knowledge Graphs	3
4	Knowledge Graph Embedding Models	3
5	How to Train	3
6	Creating an Embedding Vector Database 6.1 Learning Embeddings	5 5 6 6
7	Answering Complex Queries	6
8	Predicting Missing Links	8
9	Downloading Pretrained Models	8
10	How to Deploy	8
11	Docker	8
12	Coverage Report	8
13	How to cite	10
14	dicee 14.1 Submodules 14.2 Attributes 14.3 Classes 14.4 Functions 14.5 Package Contents	12 165 166 167 168
Py	thon Module Index	213

Index 214

DICE Embeddings¹: Hardware-agnostic Framework for Large-scale Knowledge Graph Embeddings:

1 Dicee Manual

Version: dicee 0.1.3.2

GitHub repository: https://github.com/dice-group/dice-embeddings

Publisher and maintainer: Caglar Demir²

Contact: caglar.demir@upb.de

License: OSI Approved :: MIT License

Dicee is a hardware-agnostic framework for large-scale knowledge graph embeddings.

Knowledge graph embedding research has mainly focused on learning continuous representations of knowledge graphs towards the link prediction problem. Recently developed frameworks can be effectively applied in a wide range of research-related applications. Yet, using these frameworks in real-world applications becomes more challenging as the size of the knowledge graph grows

We developed the DICE Embeddings framework (dicee) to compute embeddings for large-scale knowledge graphs in a hardware-agnostic manner. To achieve this goal, we rely on

- 1. Pandas³ & Co. to use parallelism at preprocessing a large knowledge graph,
- 2. PyTorch⁴ & Co. to learn knowledge graph embeddings via multi-CPUs, GPUs, TPUs or computing cluster, and
- 3. **Huggingface**⁵ to ease the deployment of pre-trained models.

Why Pandas⁶ & Co. ? A large knowledge graph can be read and preprocessed (e.g. removing literals) by pandas, modin, or polars in parallel. Through polars, a knowledge graph having more than 1 billion triples can be read in parallel fashion. Importantly, using these frameworks allow us to perform all necessary computations on a single CPU as well as a cluster of computers.

Why PyTorch⁷ & Co. ? PyTorch is one of the most popular machine learning frameworks available at the time of writing. PytorchLightning facilitates scaling the training procedure of PyTorch without boilerplate. In our framework, we combine PyTorch⁸ & PytorchLightning⁹. Users can choose the trainer class (e.g., DDP by Pytorch) to train large knowledge graph embedding models with billions of parameters. PytorchLightning allows us to use state-of-the-art model parallelism techniques (e.g. Fully Sharded Training, FairScale, or DeepSpeed) without extra effort. With our framework, practitioners can directly use PytorchLightning for model parallelism to train gigantic embedding models.

Why Hugging-face Gradio¹⁰? Deploy a pre-trained embedding model without writing a single line of code.

- ¹ https://github.com/dice-group/dice-embeddings
- ² https://github.com/Demirrr
- 3 https://pandas.pydata.org/
- 4 https://pytorch.org/
- ⁵ https://huggingface.co/
- 6 https://pandas.pydata.org/
- ⁷ https://pytorch.org/
- 8 https://pytorch.org/
- 9 https://www.pytorchlightning.ai/
- 10 https://huggingface.co/gradio

2 Installation

2.1 Installation from Source

```
git clone https://github.com/dice-group/dice-embeddings.git conda create -n dice python=3.10.13 --no-default-packages && conda activate dice &&_ 
cd dice-embeddings && 
pip3 install -e .
```

or

```
pip install dicee
```

3 Download Knowledge Graphs

```
wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-

→certificate && unzip KGs.zip
```

To test the Installation

```
python -m pytest -p no:warnings -x # Runs >114 tests leading to > 15 mins

python -m pytest -p no:warnings --lf # run only the last failed test

python -m pytest -p no:warnings --ff # to run the failures first and then the rest of the tests.
```

4 Knowledge Graph Embedding Models

- 1. TransE, DistMult, ComplEx, ConEx, QMult, OMult, ConvO, ConvQ, Keci
- 2. All 44 models available in https://github.com/pykeen/pykeen#models For more, please refer to examples.

5 How to Train

To Train a KGE model (KECI) and evaluate it on the train, validation, and test sets of the UMLS benchmark dataset.

```
from dicee.executer import Execute
from dicee.config import Namespace
args = Namespace()
args.model = 'Keci'
args.scoring_technique = "KvsAll" # 1vsAll, or AllvsAll, or NegSample
args.dataset_dir = "KGs/UMLS"
args.path_to_store_single_run = "Keci_UMLS"
args.num_epochs = 100
args.embedding_dim = 32
args.batch_size = 1024
reports = Execute(args).start()
print(reports["Train"]["MRR"]) # => 0.9912
print(reports["Trest"]["MRR"]) # => 0.8155
# See the Keci_UMLS folder embeddings and all other files
```

where the data is in the following form

```
$ head -3 KGs/UMLS/train.txt
acquired_abnormality location_of experimental_model_of_disease
anatomical_abnormality manifestation_of physiologic_function
alga isa entity
```

A KGE model can also be trained from the command line

```
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

dicee automaticaly detects available GPUs and trains a model with distributed data parallels technique. Under the hood, dicee uses lighning as a default trainer.

```
# Train a model by only using the GPU-0

CUDA_VISIBLE_DEVICES=0 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model

--"train_val_test"

# Train a model by only using GPU-1

CUDA_VISIBLE_DEVICES=1 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model

--"train_val_test"

NCCL_P2P_DISABLE=1 CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL -

--dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

Under the hood, dicee executes run.py script and uses lighning as a default trainer

```
# Two equivalent executions
# (1)
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H01': 0.9518788343558282, 'H03': 0.9988496932515337, 'H010': 1.0, 'MRR': 0.
→9753123402351737}
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
→ 'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H01': 0.6951588502269289, 'H03': 0.9039334341906202, 'H010': 0.9750378214826021,
→ 'MRR': 0.8064032293278861}
# (2)
CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL --dataset_dir "KGs/
→UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H01': 0.9518788343558282, 'H03': 0.9988496932515337, 'H010': 1.0, 'MRR': 0.
\leftrightarrow 9753123402351737}
# Evaluate Keci on Train set: Evaluate Keci on Train set
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
→ 'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
→ 'MRR': 0.8064032293278861}
```

Similarly, models can be easily trained with torchrun

```
torchrun --standalone --nnodes=1 --nproc_per_node=gpu dicee/scripts/run.py --trainer_
→torchDDP --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"

# Evaluate Keci on Train set: Evaluate Keci on Train set: Evaluate Keci on Train set

# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.

→9753123402351737}

# Evaluate Keci on Validation set: Evaluate Keci on Validation set

# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,

→'MRR': 0.8072499937521418}

# Evaluate Keci on Test set: Evaluate Keci on Test set

{'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,

→'MRR': 0.8064032293278861}
```

You can also train a model in multi-node multi-gpu setting.

```
torchrun --nnodes 2 --nproc_per_node=gpu --node_rank 0 --rdzv_id 455 --rdzv_backend_

--c10d --rdzv_endpoint=nebula dicee/scripts/run.py --trainer torchDDP --dataset_dir_

--KGS/UMLS

torchrun --nnodes 2 --nproc_per_node=gpu --node_rank 1 --rdzv_id 455 --rdzv_backend_

--c10d --rdzv_endpoint=nebula dicee/scripts/run.py --trainer torchDDP --dataset_dir_

--KGS/UMLS
```

Train a KGE model by providing the path of a single file and store all parameters under newly created directory called KeciFamilyRun.

```
dicee --path_single_kg "KGs/Family/family-benchmark_rich_background.owl" --model Keci--path_to_store_single_run KeciFamilyRun --backend rdflib
```

where the data is in the following form

Apart from n-triples or standard link prediction dataset formats, we support ["owl", "nt", "turtle", "rdf/xml", "n3"]*. Moreover, a KGE model can be also trained by providing an endpoint of a triple store.

```
dicee --sparql_endpoint "http://localhost:3030/mutagenesis/" --model Keci
```

For more, please refer to examples.

6 Creating an Embedding Vector Database

6.1 Learning Embeddings

```
# Train an embedding model
dicee --dataset_dir KGs/Countries-S1 --path_to_store_single_run CountryEmbeddings --
wmodel Keci --p 0 --q 1 --embedding_dim 32 --adaptive_swa
```

6.2 Loading Embeddings into Qdrant Vector Database

6.3 Launching Webservice

```
diceeserve --path_model "CountryEmbeddings" --collection_name "dummy" --collection_

→location "localhost"
```

Retrieve and Search

Get embedding of germany

```
curl -X 'GET' 'http://0.0.0.8000/api/get?q=germany' -H 'accept: application/json'
```

Get most similar things to europe

```
curl -X 'GET' 'http://0.0.0.0:8000/api/search?q=europe' -H 'accept: application/json'
{"result":[{"hit":"europe", "score":1.0},
{"hit":"northern_europe", "score":0.67126536},
{"hit":"western_europe", "score":0.6010134},
{"hit":"puerto_rico", "score":0.5051694},
{"hit":"southern_europe", "score":0.4829831}]}
```

7 Answering Complex Queries

```
# pip install dicee
# wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-
→certificate & unzip KGs.zip
from dicee.executer import Execute
from dicee.config import Namespace
from dicee.knowledge_graph_embeddings import KGE
# (1) Train a KGE model
args = Namespace()
args.model = 'Keci'
args.p=0
args.q=1
args.optim = 'Adam'
args.scoring_technique = "AllvsAll"
args.path_single_kg = "KGs/Family/family-benchmark_rich_background.owl"
args.backend = "rdflib"
args.num_epochs = 200
args.batch_size = 1024
args.lr = 0.1
args.embedding_dim = 512
result = Execute(args).start()
# (2) Load the pre-trained model
```

```
pre_trained_kge = KGE(path=result['path_experiment_folder'])
# (3) Single-hop query answering
# Query: ?E : \exist E.hasSibling(E, F9M167)
# Question: Who are the siblings of F9M167?
# Answer: [F9M157, F9F141], as (F9M167, hasSibling, F9M157) and (F9M167, hasSibling,
\hookrightarrow F9F141)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="1p",
                                                      query=('http://www.benchmark.org/
→family#F9M167',
                                                             ('http://www.benchmark.
→org/family#hasSibling',)),
                                                      tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9F141" in top_entities
assert "http://www.benchmark.org/family#F9M157" in top_entities
# (2) Two-hop query answering
# Query: ?D : \exist E.Married(D, E) \land hasSibling(E, F9M167)
# Question: To whom a sibling of F9M167 is married to?
# Answer: [F9F158, F9M142] as (F9M157 #married F9F158) and (F9F141 #married F9M142)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="2p",
                                                      query=("http://www.benchmark.org/
→family#F9M167",
                                                             ("http://www.benchmark.
→org/family#hasSibling",
                                                              "http://www.benchmark.
→org/family#married")),
                                                     tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9M142" in top_entities
assert "http://www.benchmark.org/family#F9F158" in top_entities
# (3) Three-hop query answering
# Query: ?T : \exist D.type(D,T) \land Married(D,E) \land hasSibling(E, F9M167)
# Question: What are the type of people who are married to a sibling of F9M167?
# (3) Answer: [Person, Male, Father] since F9M157 is [Brother Father Grandfather_
→Male] and F9M142 is [Male Grandfather Father]
predictions = pre_trained_kge.answer_multi_hop_query(query_type="3p", query=("http://
→www.benchmark.org/family#F9M167",
                                                                               ("http://
→www.benchmark.org/family#hasSibling",
                                                                              "http://
→www.benchmark.org/family#married",
                                                                              "http://
\rightarrowwww.w3.org/1999/02/22-rdf-syntax-ns#type")),
                                                     tnorm="min", k=5)
top_entities = [topk_entity for topk_entity, query_score in predictions]
print (top_entities)
assert "http://www.benchmark.org/family#Person" in top_entities
assert "http://www.benchmark.org/family#Father" in top_entities
assert "http://www.benchmark.org/family#Male" in top_entities
```

For more, please refer to examples/multi_hop_query_answering.

8 Predicting Missing Links

```
from dicee import KGE
# (1) Train a knowledge graph embedding model..
# (2) Load a pretrained model
pre_trained_kge = KGE(path='..')
# (3) Predict missing links through head entity rankings
pre_trained_kge.predict_topk(h=[".."],r=[".."],topk=10)
# (4) Predict missing links through relation rankings
pre_trained_kge.predict_topk(h=[".."],t=[".."],topk=10)
# (5) Predict missing links through tail entity rankings
pre_trained_kge.predict_topk(r=[".."],t=[".."],topk=10)
```

9 Downloading Pretrained Models

```
from dicee import KGE
# (1) Load a pretrained ConEx on DBpedia
model = KGE(url="https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-
-dim128-epoch256-KvsAll")
```

For more please look at dice-research.org/projects/DiceEmbeddings/¹¹

10 How to Deploy

```
from dicee import KGE
KGE (path='...').deploy(share=True,top_k=10)
```

11 Docker

To build the Docker image:

```
docker build -t dice-embeddings .
```

To test the Docker image:

```
docker run --rm -v ~/.local/share/dicee/KGs:/dicee/KGs dice-embeddings ./main.py --
→model AConEx --embedding_dim 16
```

12 Coverage Report

The coverage report is generated using coverage.py¹²:

Name	Stmts	Miss	Cover	Missing
dicee/initpy	7		100%	
dicee/abstracts.py	201	82		104–105, Litinues on next page)

¹¹ https://files.dice-research.org/projects/DiceEmbeddings/

¹² https://coverage.readthedocs.io/en/7.6.0/

```
→123, 146-147, 152, 165, 197, 240-254, 257-260, 263-266, 301, 314-317, 320-324, 364-
\Rightarrow375, 390-398, 413, 424-428, 555-575, 581-585, 589-591
dicee/callbacks.py
                                                           245
                                                                  102
\hookrightarrow67-73, 76, 88-93, 98-103, 106-109, 116-133, 138-142, 146-147, 276-280, 286-287, 305-
→311, 314, 319-320, 332-338, 344-353, 358-360, 405, 416-429, 433-468, 480-486
dicee/config.py
                                                            93
                                                                    2
                                                                         98%
                                                                                141-142
dicee/dataset_classes.py
                                                           299
                                                                   74
                                                                         75%
                                                                                41, 54, ...
→87, 93, 99-106, 109, 112, 115-139, 195-201, 204, 207-209, 314, 325-328, 344, 410-

→411, 429, 528-536, 539, 543-557, 700-707, 710-714

dicee/eval_static_funcs.py
                                                           227
                                                                   95
                                                                         58%
                                                                                101, 106,
→ 111, 258-353, 360-411
dicee/evaluator.py
                                                           262
                                                                   51
                                                                         81%
                                                                                46, 51,_
→56, 84, 89-90, 93, 109, 126, 137, 141, 146, 177-188, 195-206, 314, 344-367, 455, □
→465, 482-487
dicee/executer.py
                                                                         96%
                                                                                116, 258-
                                                           113
⇒259, 291
dicee/knowledge_graph.py
                                                            65
                                                                    3
                                                                         95%
                                                                                79, 110, _
⇔114
dicee/knowledge_graph_embeddings.py
                                                           636
                                                                  443
                                                                         30%
                                                                                27, 30-
→31, 39-52, 57-90, 93-127, 131-139, 170-184, 215-228, 254-274, 324-327, 330-333, 346,
→ 381-426, 484-486, 502-503, 509-517, 522-525, 528-533, 538, 547, 592-598, 630, 688-
→1053, 1084-1145, 1149-1177, 1200, 1227-1265
dicee/models/__init__.py
                                                             9
                                                                        100%
                                                           234
                                                                   31
                                                                         87%
dicee/models/base_model.py
                                                                                54, 56, ...
→82, 88-103, 157, 190, 230, 236, 245, 248, 252, 259, 263, 265, 280, 288-289, 296-297,
→ 351, 354, 427, 439
dicee/models/clifford.py
                                                                  357
→68-117, 122-133, 156-168, 190-220, 235, 237, 241, 248-249, 276-280, 303-311, 325-
→327, 332-333, 364-384, 406, 413, 417-478, 495-499, 511, 514, 519, 524, 571-607, 625-
→631, 644, 647, 652, 657, 686-692, 705, 708, 713, 718, 728-737, 753-754, 774-845, □
→856-859, 884-909, 933-966, 1002-1006, 1019, 1029, 1032, 1037, 1042, 1047, 1051, □
→1055, 1064-1065, 1095, 1102, 1107, 1135-1139, 1167-1176, 1186-1194, 1212-1214, 1232-
→1234, 1250-1252
dicee/models/complex.py
                                                           151
                                                                   15
                                                                         90%
                                                                                86-109
dicee/models/dualE.py
                                                            59
                                                                   10
                                                                         83%
                                                                                93-102,_
→142-156
                                                           262
                                                                  221
dicee/models/function_space.py
                                                                         16%
                                                                                10-24, _
\Rightarrow28-37, 40-49, 53-70, 77-86, 89-98, 101-110, 114-126, 134-156, 159-165, 168-185, 188-
→194, 197-205, 208, 213-234, 243-246, 250-254, 258-267, 271-292, 301-307, 311-328, □
→332-335, 344-352, 355, 366-372, 392-406, 424-438, 443-453, 461-465, 474-478
                                                           227
                                                                   83
                                                                         63%
dicee/models/octonion.py
                                                                                21-44,_
\Rightarrow320-329, 334-345, 348-370, 374-416, 426-474
dicee/models/pykeen_models.py
                                                            50
                                                                    5
                                                                         90%
                                                                                60-63, _
dicee/models/quaternion.py
                                                                                7-21, 30-
                                                           192
                                                                   69
                                                                         64%
→55, 68-72, 107, 185, 328-342, 345-364, 368-389, 399-426
dicee/models/real.py
                                                            61
                                                                   12
                                                                         80%
                                                                                36-39, _
\leftrightarrow 66-69, 87, 103-106
dicee/models/static_funcs.py
                                                            10
                                                                    0
                                                                        100%
dicee/models/transformers.py
                                                           236
                                                                  189
→46, 60-75, 84-102, 105-116, 123-125, 128, 134-151, 155-180, 186-190, 193-197, 203-
→207, 210-212, 229-256, 265-268, 271-276, 279-304, 310-315, 319-372, 376-398, 404-414
```

```
dicee/query_generator.py
                                                              374
                                                                      346
                                                                               7%
                                                                                    18-52,_
\hookrightarrow56, 62-65, 69-70, 78-92, 100-147, 155-188, 192-206, 212-269, 274-303, 307-443, 453-
\hookrightarrow472, 480-501, 508-512, 517, 522-528
                                                                3
                                                                        0
                                                                            100%
dicee/read_preprocess_save_load_kg/__init__.py
dicee/read_preprocess_save_load_kg/preprocess.py
                                                              256
                                                                       41
                                                                             84%
                                                                                    34, 40, _
\hookrightarrow78, 102-127, 133, 138-151, 184, 214, 388-389, 444
dicee/read_preprocess_save_load_kg/read_from_disk.py
                                                               36
                                                                       11
                                                                             69%
                                                                                    33, 38-
\hookrightarrow40, 47, 55, 58-72
dicee/read_preprocess_save_load_kg/save_load_disk.py
                                                               45
                                                                       18
                                                                             60%
                                                                                    39-60
dicee/read_preprocess_save_load_kg/util.py
                                                              219
                                                                      126
                                                                              42%
                                                                                    65-67.
→72-73, 91-97, 100-102, 107-109, 121, 134, 140-143, 148-156, 161-167, 172-177, 182-
→187, 199-220, 226-282, 286-290, 294-295, 299, 303-304, 334, 351, 356, 363-364
                                                                       23
                                                                             57%
dicee/sanity_checkers.py
                                                               54
                                                                                    8-12, 21-
\rightarrow31, 46, 51, 58, 64-79, 85, 89, 96
dicee/static_funcs.py
                                                                      163
                                                                             61%
                                                                                    40, 50, ...
                                                              418
→56-61, 83, 105-106, 115, 138, 152, 157-159, 163-165, 167, 194-198, 246, 254, 263-
→268, 290-304, 316-336, 340-357, 362, 386-387, 392-393, 410-411, 413-414, 416-417, □
→419-420, 428, 446-450, 467-470, 474-479, 483-487, 491-492, 498-500, 526-527, 539-
\hookrightarrow 542, 547-550, 559-610, 615-627, 644-658, 661-669
dicee/static_funcs_training.py
                                                              123
                                                                       63
                                                                             49%
                                                                                    118-215, _
⇔223-224
dicee/static_preprocess_funcs.py
                                                              100
                                                                       44
                                                                             56%
                                                                                    17-25.
\hookrightarrow 52, 56, 64, 67, 78, 91-115, 120-123, 128-131, 136-139
dicee/trainer/__init__.py
                                                                        0
                                                                            100%
                                                                1
dicee/trainer/dice_trainer.py
                                                              126
                                                                       13
                                                                             90%
                                                                                    27-32, _
\hookrightarrow 91, 98, 103-108, 147
dicee/trainer/torch_trainer.py
                                                               79
                                                                              95%
                                                                                    31, 196, _
→207-208
dicee/trainer/torch_trainer_ddp.py
                                                              152
                                                                      128
                                                                             16%
                                                                                    13-14,_
→43, 47-72, 83-112, 131-137, 140-149, 164-194, 204-217, 226-246, 251-260, 263-272, □
⇒275-299, 302-309
TOTAL
                                                             6181
                                                                     2828
                                                                             54%
```

13 How to cite

Currently, we are working on our manuscript describing our framework. If you really like our work and want to cite it now, feel free to chose one:)

```
# Keci
@inproceedings{demir2023clifford,
    title={Clifford Embeddings--A Generalized Approach for Embedding in Normed Algebras}

.,
    author={Demir, Caglar and Ngonga Ngomo, Axel-Cyrille},
    booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in_
.Databases},
    pages={567--582},
    year={2023},
    organization={Springer}
}
# LitCQD
```

```
@inproceedings{demir2023litcqd,
 title={LitCQD: Multi-Hop Reasoning in Incomplete Knowledge Graphs with Numeric_
→Literals},
 author={Demir, Caglar and Wiebesiek, Michel and Lu, Renzhong and Ngonga Ngomo, Axel-
→Cyrille and Heindorf, Stefan},
 booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in_
→Databases},
 pages={617--633},
 year={2023},
 organization={Springer}
# DICE Embedding Framework
@article{demir2022hardware,
 title={Hardware-agnostic computation for large-scale knowledge graph embeddings},
 author={Demir, Caglar and Ngomo, Axel-Cyrille Ngonga},
 journal={Software Impacts},
 year={2022},
 publisher={Elsevier}
# KronE
@inproceedings{demir2022kronecker,
 title={Kronecker decomposition for knowledge graph embeddings},
 author={Demir, Caglar and Lienen, Julian and Ngonga Ngomo, Axel-Cyrille},
 booktitle={Proceedings of the 33rd ACM Conference on Hypertext and Social Media},
 pages={1--10},
 year={2022}
# QMult, OMult, ConvQ, ConvO
@InProceedings{pmlr-v157-demir21a,
                   {Convolutional Hypercomplex Embeddings for Link Prediction},
 title =
                 {Demir, Caglar and Moussallem, Diego and Heindorf, Stefan and Ngonga
 author =
→Ngomo, Axel-Cyrille},
 booktitle =
                       {Proceedings of The 13th Asian Conference on Machine Learning},
 pages =
                  {656--671},
 year =
                  {2021},
 editor =
                    {Balasubramanian, Vineeth N. and Tsang, Ivor},
 volume =
                    {157}.
 series =
                   {Proceedings of Machine Learning Research},
 month =
                   \{17--19 \text{ Nov}\},
 publisher =
                 {PMLR},
                 {https://proceedings.mlr.press/v157/demir21a/demir21a.pdf},
 pdf =
 url =
                 {https://proceedings.mlr.press/v157/demir21a.html},
# ConEx
@inproceedings{demir2021convolutional,
title={Convolutional Complex Knowledge Graph Embeddings},
author={Caglar Demir and Axel-Cyrille Ngonga Ngomo},
booktitle={Eighteenth Extended Semantic Web Conference - Research Track},
year={2021},
url={https://openreview.net/forum?id=6T45-4TFqaX}}
# Shallom
@inproceedings{demir2021shallow,
```

```
title={A shallow neural model for relation prediction},
  author={Demir, Caglar and Moussallem, Diego and Ngomo, Axel-Cyrille Ngonga},
  booktitle={2021 IEEE 15th International Conference on Semantic Computing (ICSC)},
  pages={179--182},
  year={2021},
  organization={IEEE}
```

For any questions or wishes, please contact: caglar.demir@upb.de

14 dicee

14.1 Submodules

dicee.__main__

dicee.abstracts

Classes

AbstractTrainer	Abstract class for Trainer class for knowledge graph embedding models
BaseInteractiveKGE	Abstract/base class for using knowledge graph embedding models interactively.
InteractiveQueryDecomposition	
AbstractCallback	Abstract class for Callback class for knowledge graph embedding models
AbstractPPECallback	Abstract class for Callback class for knowledge graph embedding models

Module Contents

class dicee.abstracts.AbstractTrainer(args, callbacks)

Abstract class for Trainer class for knowledge graph embedding models

Parameter

```
args
    [str] ?

callbacks: list
    ?

attributes

callbacks
is_global_zero = True
global_rank = 0

local_rank = 0
```

```
strategy = None
on_fit_start(*args, **kwargs)
     A function to call callbacks before the training starts.
     Parameter
     args
     kwargs
          rtype
              None
on_fit_end(*args, **kwargs)
     A function to call callbacks at the ned of the training.
     Parameter
     args
     kwargs
          rtype
              None
on_train_epoch_end(*args, **kwargs)
     A function to call callbacks at the end of an epoch.
     Parameter
     args
     kwargs
          rtype
              None
on_train_batch_end(*args, **kwargs)
     A function to call callbacks at the end of each mini-batch during training.
     Parameter
     args
     kwargs
          rtype
              None
\mathtt{static}\ \mathtt{save\_checkpoint}\ (\mathit{full\_path}: \mathit{str}, \mathit{model}) \ 	o \ \mathsf{None}
     A static function to save a model into disk
     Parameter
     full_path: str
     model:
```

```
rtype
```

None

```
class dicee.abstracts.BaseInteractiveKGE (path: str = None, url: str = N
                                  construct_ensemble: bool = False, model_name: str = None,
                                  apply_semantic_constraint: bool = False)
                Abstract/base class for using knowledge graph embedding models interactively.
                Parameter
                path_of_pretrained_model_dir
                              [str]?
                construct_ensemble: boolean
                model_name: str apply_semantic_constraint : boolean
                construct_ensemble = False
                apply_semantic_constraint = False
                configs
                \texttt{get\_eval\_report}() \rightarrow dict
                \texttt{get\_bpe\_token\_representation} (\textit{str\_entity\_or\_relation: List[str]} \mid \textit{str}) \rightarrow List[List[int]] \mid List[int]
                                          Parameters
                                                     str_entity_or_relation(corresponds to a str or a list of strings to
                                                     be tokenized via BPE and shaped.)
                                          Return type
                                                     A list integer(s) or a list of lists containing integer(s)
                \texttt{get\_padded\_bpe\_triple\_representation} (\textit{triples: List[List[str]]}) \rightarrow \texttt{Tuple[List, List, List]}
                                          Parameters
                                                     triples
                \mathtt{set\_model\_train\_mode}() \rightarrow None
                              Setting the model into training mode
                              Parameter
                \mathtt{set}\_\mathtt{model}\_\mathtt{eval}\_\mathtt{mode}\,(\,) \, \to None
                              Setting the model into eval mode
                              Parameter
                property name
                sample\_entity(n:int) \rightarrow List[str]
                sample\_relation(n: int) \rightarrow List[str]
                is\_seen(entity: str = None, relation: str = None) \rightarrow bool
```

```
save() \rightarrow None
      get_entity_index (x: str)
      get_relation_index (X: Str)
      index_triple (head_entity: List[str], relation: List[str], tail_entity: List[str])
                    → Tuple[torch.LongTensor, torch.LongTensor, torch.LongTensor]
           Index Triple
           Parameter
           head_entity: List[str]
           String representation of selected entities.
           relation: List[str]
           String representation of selected relations.
           tail entity: List[str]
           String representation of selected entities.
           Returns: Tuple
           pytorch tensor of triple score
      add_new_entity_embeddings (entity_name: str = None, embeddings: torch.FloatTensor = None)
      get_entity_embeddings (items: List[str])
           Return embedding of an entity given its string representation
           Parameter
           items:
                entities
      get_relation_embeddings (items: List[str])
           Return embedding of a relation given its string representation
           Parameter
           items:
                relations
      construct_input_and_output (head_entity: List[str], relation: List[str], tail_entity: List[str], labels)
           Construct a data point :param head_entity: :param relation: :param tail_entity: :param labels: :return:
      parameters()
class dicee.abstracts.InteractiveQueryDecomposition
      t_norm(tens_1: torch.Tensor, tens_2: torch.Tensor, tnorm: str = 'min') \rightarrow torch.Tensor
      tensor_t_norm(subquery\_scores: torch.FloatTensor, tnorm: str = 'min') \rightarrow torch.FloatTensor
           Compute T-norm over [0,1] ^{n imes d} where n denotes the number of hops and d denotes number of
           entities
```

```
t_{conorm} (tens_1: torch.Tensor, tens_2: torch.Tensor, tconorm: str = 'min') \rightarrow torch.Tensor
      negnorm(tens\_1: torch.Tensor, lambda\_: float, neg\_norm: str = 'standard') \rightarrow torch.Tensor
class dicee.abstracts.AbstractCallback
      Bases: abc.ABC, lightning.pytorch.callbacks.Callback
      Abstract class for Callback class for knowledge graph embedding models
      Parameter
      on_init_start(*args, **kwargs)
           Parameter
           trainer:
           model:
               rtype
                   None
      on_init_end(*args, **kwargs)
           Call at the beginning of the training.
           Parameter
           trainer:
           model:
               rtype
                   None
      on_fit_start(trainer, model)
           Call at the beginning of the training.
           Parameter
           trainer:
           model:
               rtype
                   None
      on_train_epoch_end(trainer, model)
           Call at the end of each epoch during training.
           Parameter
           trainer:
           model:
               rtype
                   None
      on_train_batch_end(*args, **kwargs)
           Call at the end of each mini-batch during the training.
```

```
trainer:
          model:
              rtype
                  None
     on_fit_end(*args, **kwargs)
          Call at the end of the training.
          Parameter
          trainer:
          model:
              rtype
                  None
class dicee.abstracts.AbstractPPECallback(num_epochs, path, epoch_to_start,
            last_percent_to_consider)
     Bases: AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     num_epochs
     path
     sample_counter = 0
     epoch_count = 0
     alphas = None
     on_fit_start (trainer, model)
          Call at the beginning of the training.
          Parameter
          trainer:
          model:
              rtype
                  None
     on_fit_end(trainer, model)
          Call at the end of the training.
          Parameter
          trainer:
          model:
```

Parameter

rtype

None

 $\verb|store_ensemble| (param_ensemble)| \rightarrow None$

dicee.analyse_experiments

This script should be moved to dicee/scripts Example: python dicee/analyse_experiments.py -dir Experiments -features "model" "trainMRR" "testMRR"

Classes

```
Experiment
```

Functions

```
get_default_arguments()
analyse(args)
```

Module Contents

```
dicee.analyse_experiments.get_default_arguments()
class dicee.analyse_experiments.Experiment
    model_name = []
    callbacks = []
    embedding_dim = []
    num_params = []
    num_epochs = []
    batch_size = []
    lr = []
    byte_pair_encoding = []
    aswa = []
    path_dataset_folder = []
    full_storage_path = []
    pq = []
    train_mrr = []
```

```
train_h1 = []
    train_h3 = []
    train_h10 = []
    val_mrr = []
    val_h1 = []
    val_h3 = []
    val_h10 = []
    test_mrr = []
    test_h1 = []
    test_h3 = []
    test_h10 = []
    runtime = []
    normalization = []
    scoring_technique = []
    save\_experiment(X)
    to_df()
\verb|dicee.analyse_experiments.analyse| (args)
```

dicee.callbacks

Classes

AccumulateEpochLossCallback	Abstract class for Callback class for knowledge graph embedding models
PrintCallback	Abstract class for Callback class for knowledge graph embedding models
KGESaveCallback	Abstract class for Callback class for knowledge graph embedding models
PseudoLabellingCallback	Abstract class for Callback class for knowledge graph embedding models
ASWA	Adaptive stochastic weight averaging
Eval	Abstract class for Callback class for knowledge graph embedding models
KronE	Abstract class for Callback class for knowledge graph embedding models
Perturb	A callback for a three-Level Perturbation

Functions

```
estimate rate of convergence q from sequence esp
 estimate_q(eps)
 compute_convergence(seq, i)
Module Contents
class dicee.callbacks.AccumulateEpochLossCallback(path: str)
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     path
     on\_fit\_end(\mathit{trainer}, \mathit{model}) \rightarrow None
          Store epoch loss
          Parameter
          trainer:
          model:
               rtype
                   None
class dicee.callbacks.PrintCallback
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     start_time
     on_fit_start (trainer, pl_module)
          Call at the beginning of the training.
          Parameter
          trainer:
          model:
               rtype
                   None
```

on_fit_end(trainer, pl_module)

Call at the end of the training.

```
Parameter
          trainer:
          model:
              rtype
                  None
     on_train_batch_end(*args, **kwargs)
          Call at the end of each mini-batch during the training.
          Parameter
          trainer:
          model:
              rtype
                  None
     on_train_epoch_end(*args, **kwargs)
          Call at the end of each epoch during training.
          Parameter
          trainer:
          model:
              rtype
                  None
class dicee.callbacks.KGESaveCallback (every_x_epoch: int, max_epochs: int, path: str)
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     every_x_epoch
     max_epochs
     epoch_counter = 0
     path
     on_train_batch_end(*args, **kwargs)
          Call at the end of each mini-batch during the training.
          Parameter
          trainer:
          model:
              rtype
                  None
```

```
on_fit_start (trainer, pl_module)
          Call at the beginning of the training.
          Parameter
          trainer:
          model:
               rtype
                   None
     on_train_epoch_end(*args, **kwargs)
          Call at the end of each epoch during training.
          Parameter
          trainer:
          model:
               rtype
                   None
     on_fit_end(*args, **kwargs)
          Call at the end of the training.
          Parameter
          trainer:
          model:
               rtype
                   None
     on_epoch_end (model, trainer, **kwargs)
class dicee.callbacks.PseudoLabellingCallback (data_module, kg, batch_size)
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     data_module
     kg
     num_of_epochs = 0
     unlabelled_size
     batch_size
     create_random_data()
     \verb"on_epoch_end" (\textit{trainer}, \textit{model})
```

```
dicee.callbacks.estimate_q(eps)
     estimate rate of convergence q from sequence esp
dicee.callbacks.compute_convergence (seq, i)
class dicee.callbacks.ASWA (num_epochs, path)
     Bases: dicee.abstracts.AbstractCallback
     Adaptive stochastic weight averaging ASWE keeps track of the validation performance and update s the ensemble
     model accordingly.
     path
     num_epochs
     initial_eval_setting = None
     epoch_count = 0
     alphas = []
     val_aswa = -1
     on_fit_end(trainer, model)
           Call at the end of the training.
           Parameter
          trainer:
           model:
               rtvpe
                   None
     \texttt{static compute\_mrr}(\textit{trainer}, model) \rightarrow \texttt{float}
     {\tt get\_aswa\_state\_dict} \ (model)
     decide (running_model_state_dict, ensemble_state_dict, val_running_model,
                  mrr_updated_ensemble_model)
           Perform Hard Update, software or rejection
               Parameters
                   • running_model_state_dict
                   • ensemble_state_dict
                   • val_running_model
                   • mrr_updated_ensemble_model
     on_train_epoch_end(trainer, model)
           Call at the end of each epoch during training.
```

```
Parameter
          trainer:
          model:
              rtype
                  None
class dicee.callbacks.Eval (path, epoch_ratio: int = None)
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     path
     reports = []
     epoch_ratio = None
     epoch_counter = 0
     on_fit_start(trainer, model)
          Call at the beginning of the training.
          Parameter
          trainer:
          model:
              rtype
                  None
     on_fit_end(trainer, model)
          Call at the end of the training.
          Parameter
          trainer:
          model:
              rtype
                  None
     on_train_epoch_end(trainer, model)
          Call at the end of each epoch during training.
          Parameter
          trainer:
          model:
              rtype
                  None
```

```
on_train_batch_end(*args, **kwargs)
          Call at the end of each mini-batch during the training.
          Parameter
          trainer:
          model:
               rtype
                   None
class dicee.callbacks.KronE
     Bases: dicee.abstracts.AbstractCallback
     Abstract class for Callback class for knowledge graph embedding models
     Parameter
     f = None
     static batch_kronecker_product(a, b)
          Kronecker product of matrices a and b with leading batch dimensions. Batch dimensions are broadcast. The
          number of them mush :type a: torch.Tensor :type b: torch.Tensor :rtype: torch.Tensor
     get_kronecker_triple_representation (indexed_triple: torch.LongTensor)
          Get kronecker embeddings
     on_fit_start(trainer, model)
          Call at the beginning of the training.
          Parameter
          trainer:
          model:
               rtype
class dicee.callbacks.Perturb(level: str = 'input', ratio: float = 0.0, method: str = None,
            scaler: float = None, frequency=None)
     Bases: dicee.abstracts.AbstractCallback
```

A callback for a three-Level Perturbation

Input Perturbation: During training an input x is perturbed by randomly replacing its element. In the context of knowledge graph embedding models, x can denote a triple, a tuple of an entity and a relation, or a tuple of two entities. A perturbation means that a component of x is randomly replaced by an entity or a relation.

Parameter Perturbation:

```
Output Perturbation:

level = 'input'

ratio = 0.0

method = None
```

dicee.config

Classes

Namespace

Simple object for storing attributes.

Module Contents

Learning rate

```
class dicee.config.Namespace(**kwargs)
     Bases: argparse.Namespace
     Simple object for storing attributes.
     Implements equality by attribute names and values, and provides a simple string representation.
     dataset_dir: str = None
          The path of a folder containing train.txt, and/or valid.txt and/or test.txt
     save_embeddings_as_csv: bool = False
          Embeddings of entities and relations are stored into CSV files to facilitate easy usage.
     storage_path: str = 'Experiments'
          A directory named with time of execution under -storage_path that contains related data about embeddings.
     path_to_store_single_run: str = None
          A single directory created that contains related data about embeddings.
     path_single_kg = None
          Path of a file corresponding to the input knowledge graph
     sparql_endpoint = None
          An endpoint of a triple store.
     model: str = 'Keci'
          KGE model
     optim: str = 'Adam'
          Optimizer
     embedding_dim: int = 64
          Size of continuous vector representation of an entity/relation
     num_epochs: int = 150
          Number of pass over the training data
     batch_size: int = 1024
          Mini-batch size if it is None, an automatic batch finder technique applied
     lr: float = 0.1
```

```
add_noise_rate: float = None
     The ratio of added random triples into training dataset
gpus = None
     Number GPUs to be used during training
callbacks
     10}}
         Type
            Callbacks, e.g., {"PPE"
         Type
             { "last_percent_to_consider"
backend: str = 'pandas'
     Backend to read, process, and index input knowledge graph. pandas, polars and rdflib available
separator: str = '\\s+'
     separator for extracting head, relation and tail from a triple
trainer: str = 'torchCPUTrainer'
     Trainer for knowledge graph embedding model
scoring_technique: str = 'KvsAll'
     Scoring technique for knowledge graph embedding models
neg_ratio: int = 0
     Negative ratio for a true triple in NegSample training_technique
weight_decay: float = 0.0
     Weight decay for all trainable params
normalization: str = 'None'
     LayerNorm, BatchNorm1d, or None
init_param: str = None
    xavier_normal or None
gradient_accumulation_steps: int = 0
    Not tested e
num_folds_for_cv: int = 0
    Number of folds for CV
eval_model: str = 'train_val_test'
     ["None", "train", "train_val", "train_val_test", "test"]
         Type
            Evaluate trained model choices
save_model_at_every_epoch: int = None
     Not tested
label_smoothing_rate: float = 0.0
num_core: int = 0
     Number of CPUs to be used in the mini-batch loading process
```

```
random seed: int = 0
    Random Seed
sample_triples_ratio: float = None
    Read some triples that are uniformly at random sampled. Ratio being between 0 and 1
read only few: int = None
    Read only first few triples
pykeen_model_kwargs
    Additional keyword arguments for pykeen models
kernel_size: int = 3
    Size of a square kernel in a convolution operation
num_of_output_channels: int = 32
    Number of slices in the generated feature map by convolution.
p: int = 0
    P parameter of Clifford Embeddings
q: int = 1
    Q parameter of Clifford Embeddings
input_dropout_rate: float = 0.0
    Dropout rate on embeddings of input triples
hidden_dropout_rate: float = 0.0
    Dropout rate on hidden representations of input triples
feature_map_dropout_rate: float = 0.0
    Dropout rate on a feature map generated by a convolution operation
byte_pair_encoding: bool = False
    Byte pair encoding
        Type
            WIP
adaptive_swa: bool = False
    Adaptive stochastic weight averaging
swa: bool = False
    Stochastic weight averaging
block size: int = None
    block size of LLM
continual_learning = None
    Path of a pretrained model size of LLM
auto_batch_finding = False
```

A flag for using auto batch finding

__iter__()

dicee.dataset classes

Classes

BPE_NegativeSamplingDataset	An abstract class representing a Dataset.
MultiLabelDataset	An abstract class representing a Dataset.
MultiClassClassificationDataset	Dataset for the 1vsALL training strategy
OnevsAllDataset	Dataset for the 1vsALL training strategy
KvsAll	Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
AllvsAll	Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
OnevsSample	A custom PyTorch Dataset class for knowledge graph embeddings, which includes
KvsSampleDataset	KvsSample a Dataset:
NegSampleDataset	An abstract class representing a Dataset.
TriplePredictionDataset	Triple Dataset
CVDataModule	Create a Dataset for cross validation

Functions

reload_dataset(path, form_of_labelling,)	Reload the files from disk to construct the Pytorch dataset
$construct_dataset(\rightarrow torch.utils.data.Dataset)$	

Module Contents

Reload the files from disk to construct the Pytorch dataset

dicee.dataset_classes.construct_dataset (*, train_set: numpy.ndarray | list, valid_set=None, test_set=None, ordered_bpe_entities=None, train_target_indices=None, target_dim: int = None, entity_to_idx: dict, relation_to_idx: dict, form_of_labelling: str, scoring_technique: str, neg_ratio: int, label_smoothing_rate: float, byte_pair_encoding=None, block_size: int = None)

→ torch.utils.data.Dataset

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite <code>__getitem__()</code>, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite <code>__len__()</code>, which is expected to return the size of the dataset by many <code>Sampler</code> implementations and the default options of <code>DataLoader</code>. Subclasses could also optionally implement <code>__getitems__()</code>, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.



DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set
  ordered_bpe_entities
num_bpe_entities
neg_ratio
num_datapoints
  __len__()
  __getitem__(idx)
collate_fn(batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]])
class dicee.dataset_classes.MultiLabelDataset(train_set: torch.LongTensor, train_indices_target: torch.LongTensor, target_dim: int, torch_ordered_shaped_bpe_entities: torch.LongTensor)
Bases: torch.utils.data.Dataset
```

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite __getitem__(), supporting fetching a data sample for a given key. Subclasses could also optionally overwrite __len__(), which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

1 Note

DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set

train_indices_target

target_dim

num_datapoints

torch_ordered_shaped_bpe_entities

collate_fn = None

__len__()
__getitem__(idx)
```

```
subword_units: numpy.ndarray, block_size: int = 8)
     Bases: torch.utils.data.Dataset
     Dataset for the 1vsALL training strategy
          Parameters
                • train_set_idx - Indexed triples for the training.
                • entity_idxs - mapping.
                • relation_idxs - mapping.
                • form - ?
                • num_workers - int for
                                                https://pytorch.org/docs/stable/data.html#torch.utils.data.
                  DataLoader
          Return type
              torch.utils.data.Dataset
     train_data
     block_size = 8
     num_of_data_points
     collate fn = None
     __len__()
     \__getitem__(idx)
class dicee.dataset_classes.OnevsAllDataset (train_set_idx: numpy.ndarray, entity_idxs)
     Bases: torch.utils.data.Dataset
     Dataset for the 1vsALL training strategy
          Parameters
                • train_set_idx - Indexed triples for the training.
                • entity_idxs - mapping.
                • relation_idxs - mapping.
                • form - ?
                • num_workers - int
                                          for
                                                 https://pytorch.org/docs/stable/data.html#torch.utils.data.
                  DataLoader
          Return type
              torch.utils.data.Dataset
     train_data
     target_dim
     collate_fn = None
     __len__()
     \__{getitem}_{\_}(idx)
```

class dicee.dataset_classes.MultiClassClassificationDataset(

class dicee.dataset_classes. KvsAll (train_set_idx: numpy.ndarray, entity_idxs, relation_idxs, form, store=None, label_smoothing_rate: float = 0.0)

Bases: torch.utils.data.Dataset

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as D:= $\{(x,y)_i\}_i$ ^N, where x: (h,r) is an unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y: denotes a multi-label vector in $[0,1]^{\{E\}}$ is a binary label.

orall $y_i = 1$ s.t. (h r E_i) in KG



TODO

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self: torch.utils.data.Dataset

```
>>> a = KvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```


```
train_data = None
train_target = None
label_smoothing_rate
collate_fn = None
__len__()
__getitem__(idx)
```

Bases: torch.utils.data.Dataset

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as D:= $\{(x,y)_i\}_i^n$, where x: (h,r) is a possible unique tuple of an entity h in E and a relation r in R. Hence $N = |E| \times |R|$ y: denotes a multi-label vector in $[0,1]^{\{|E|\}}$ is a binary label.

orall $y_i = 1$ s.t. (h r E_i) in KG



AllysAll extends KysAll via none existing (h,r). Hence, it adds data points that are labelled without 1s,

only with 0s.

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self: torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

```
train_data = None
train_target = None
label_smoothing_rate
collate_fn = None
target_dim
__len__()
__getitem__(idx)
```

class dicee.dataset_classes.OnevsSample ($train_set$: numpy.ndarray, $num_entities$, $num_relations$, neg_sample_ratio : int = None, $label_smoothing_rate$: float = 0.0)

Bases: torch.utils.data.Dataset

A custom PyTorch Dataset class for knowledge graph embeddings, which includes both positive and negative sampling for a given dataset for multi-class classification problem..

Parameters

- train_set (np.ndarray) A numpy array containing triples of knowledge graph data. Each triple consists of (head_entity, relation, tail_entity).
- num_entities (int) The number of unique entities in the knowledge graph.
- num_relations (int) The number of unique relations in the knowledge graph.
- neg_sample_ratio (int, optional) The number of negative samples to be generated per positive sample. Must be a positive integer and less than num_entities.
- label_smoothing_rate (float, optional) A label smoothing rate to apply to the positive and negative labels. Defaults to 0.0.

train_data

The input data converted into a PyTorch tensor.

Type

torch.Tensor

```
num_entities
```

Number of entities in the dataset.

```
Type
```

int

num_relations

Number of relations in the dataset.

Type

int

neg_sample_ratio

Ratio of negative samples to be drawn for each positive sample.

Type

int

label_smoothing_rate

The smoothing factor applied to the labels.

Type

torch.Tensor

collate_fn

A function that can be used to collate data samples into batches (set to None by default).

Type

function, optional

train_data

num_entities

num_relations

neg_sample_ratio = None

label_smoothing_rate

collate_fn = None

__len__()

Returns the number of samples in the dataset.

 $__getitem__(idx)$

Retrieves a single data sample from the dataset at the given index.

Parameters

idx (int) – The index of the sample to retrieve.

Returns

A tuple consisting of:

- x (torch.Tensor): The head and relation part of the triple.
- y_idx (torch.Tensor): The concatenated indices of the true object (tail entity) and the indices of the negative samples.
- y_vec (torch.Tensor): A vector containing the labels for the positive and negative samples, with label smoothing applied.

```
Return type
                 tuple
class dicee.dataset_classes.KvsSampleDataset (train_set_idx: numpy.ndarray, entity_idxs,
           relation_idxs, form, store=None, neg_ratio=None, label_smoothing_rate: float = 0.0)
     Bases: torch.utils.data.Dataset
          KvsSample a Dataset:
              D := \{(x,y)_i\}_i ^N, where
                 . x:(h,r) is a unique h in E and a relation r in R and . y in [0,1]^{\{|E|\}} is a binary label.
     orall y_i = 1 s.t. (h r E_i) in KG
              At each mini-batch construction, we subsample(y), hence n
                 train_set_idx
             Indexed triples for the training.
          entity_idxs
              mapping.
          relation_idxs
              mapping.
          form
          store
          label_smoothing_rate
          torch.utils.data.Dataset
     train_data = None
     train_target = None
     neg_ratio = None
     num_entities
     label_smoothing_rate
     collate_fn = None
     max_num_of_classes
     __len__()
     \__{\texttt{getitem}} (idx)
class dicee.dataset_classes.NegSampleDataset (train_set: numpy.ndarray, num_entities: int,
           num_relations: int, neg_sample_ratio: int = 1)
```

Bases: torch.utils.data.Dataset
An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite __getitem__(), supporting fetching a data sample for a given key. Subclasses could also optionally overwrite __len__(), which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.



DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
neg_sample_ratio
      train_set
      length
      num_entities
      num relations
      __len__()
      getitem (idx)
class dicee.dataset_classes.TriplePredictionDataset (train_set: numpy.ndarray,
             num entities: int, num relations: int, neg sample ratio: int = 1, label smoothing rate: float = 0.0)
      Bases: torch.utils.data.Dataset
           Triple Dataset
                D := \{(x)_i\}_i \ ^N, \text{ where }
                    . x:(h,r, t) in KG is a unique h in E and a relation r in R and . collact_fn => Generates
                    negative triples
                collect_fn:
      orall (h,r,t) in G obtain, create negative triples \{(h,r,x),(r,t),(h,m,t)\}
                y:labels are represented in torch.float16
           train_set_idx
                Indexed triples for the training.
           entity idxs
                mapping.
           relation_idxs
                mapping.
           form
           store
           label_smoothing_rate
           collate_fn: batch:List[torch.IntTensor] Returns ——- torch.utils.data.Dataset
```

```
label_smoothing_rate
     neg_sample_ratio
     train_set
     length
     num_entities
     num_relations
     __len__()
     \__getitem__(idx)
     collate_fn (batch: List[torch.Tensor])
class dicee.dataset_classes.CVDataModule(train_set_idx: numpy.ndarray, num_entities,
            num_relations, neg_sample_ratio, batch_size, num_workers)
     Bases: pytorch_lightning.LightningDataModule
     Create a Dataset for cross validation
          Parameters
                • train_set_idx - Indexed triples for the training.
                • num_entities — entity to index mapping.
                • num_relations - relation to index mapping.
                • batch size - int
                • form - ?
                • num_workers -
                                                 https://pytorch.org/docs/stable/data.html#torch.utils.data.
                                       int
                                            for
                  DataLoader
          Return type
              ?
     train_set_idx
     num_entities
     num_relations
     neg_sample_ratio
     batch_size
     num_workers
     train_dataloader() → torch.utils.data.DataLoader
          An iterable or collection of iterables specifying training samples.
          For more information about multiple dataloaders, see this section.
                 dataloader
                              you
                                     return
                                              will
                                                     not
                                                           be
                                                                 reloaded
                                                                             unless
                                                                                      you
                                                                                                   :param-
          ref: ~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs to a positive
          integer.
          For data processing use the following pattern:
```

- download in prepare_data()
- process and split in setup ()

However, the above are only necessary for distributed processing.

Marning

do not assign state in prepare_data

- fit()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

```
setup(*args, **kwargs)
```

Called at the beginning of fit (train + validate), validate, test, or predict. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

```
stage - either 'fit', 'validate', 'test', or 'predict'
```

Example:

```
class LitModel(...):
    def __init__(self):
        self.11 = None

def prepare_data(self):
        download_data()
        tokenize()

# don't do this
        self.something = else

def setup(self, stage):
        data = load_data(...)
        self.11 = nn.Linear(28, data.num_classes)
```

transfer_batch_to_device(*args, **kwargs)

Override this hook if your DataLoader returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- torch. Tensor or anything that implements .to(...)
- list
- dict

• tuple

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, ...).



This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use <code>self.trainer.training/testing/validating/predicting</code> so that you can add different logic as per your requirement.

Parameters

- batch A batch of data that needs to be transferred to a new device.
- device The target device as defined in PyTorch.
- dataloader idx The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_
    →idx)
    return batch
```

See also

- move_data_to_device()
- apply_to_collection()

prepare_data(*args, **kwargs)

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

Warning

DO NOT set state to the model (use setup instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

# bad
self.split = data_split
self.some_state = some_other_state()
```

In a distributed environment, prepare_data can be called in two ways (using prepare_data_per_node)

- 1. Once per node. This is the default and is only called on LOCAL_RANK=0.
- 2. Once in total. Only called on GLOBAL_RANK=0.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True

# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

dicee.eval_static_funcs

Functions

```
evaluate_link_prediction_performance(→
Dict)
evaluate_link_prediction_performance_with_.

evaluate_link_prediction_performance_with_i

evaluate_link_prediction_performance_with_i
...)
evaluate_lp_bpe_k_vs_all(model, triples[, er_vocab, ...])
```

Module Contents

Parameters

- model
- triples
- er_vocab
- re_vocab

Parameters

- model
- triples
- within_entities
- er_vocab
- re_vocab

dicee.evaluator

Classes

Evaluator

Evaluator class to evaluate KGE models in various downstream tasks

Module Contents

```
class dicee.evaluator.Evaluator(args, is_continual_training=None)
          Evaluator class to evaluate KGE models in various downstream tasks
          Arguments
     re_vocab = None
     er_vocab = None
     ee_vocab = None
     func_triple_to_bpe_representation = None
     is_continual_training = None
     num_entities = None
     num_relations = None
     args
     report
     during_training = False
     vocab preparation (dataset) \rightarrow None
          A function to wait future objects for the attributes of executor
               Return type
                   None
     eval (dataset: dicee.knowledge_graph.KG, trained_model, form_of_labelling, during_training=False)
     eval_rank_of_head_and_tail_entity(*, train_set, valid_set=None, test_set=None, trained_model)
     eval_rank_of_head_and_tail_byte_pair_encoded_entity(*, train_set=None, valid_set=None,
                  test_set=None, ordered_bpe_entities, trained_model)
     eval_with_byte(*, raw_train_set, raw_valid_set=None, raw_test_set=None, trained_model,
                 form\_of\_labelling) \rightarrow None
          Evaluate model after reciprocal triples are added
     eval_with_bpe_vs_all (*, raw_train_set, raw_valid_set=None, raw_test_set=None, trained_model,
                 form\_of\_labelling) \rightarrow None
          Evaluate model after reciprocal triples are added
```

dicee.executer

Classes

Execute	A class for Training, Retraining and Evaluation a model.
ContinuousExecute	A subclass of Execute Class for retraining

eval_with_data(dataset, trained_model, triple_idx: numpy.ndarray, form_of_labelling: str)

Module Contents

class dicee.executer.Execute(args, continuous_training=False)

A class for Training, Retraining and Evaluation a model.

- (1) Loading & Preprocessing & Serializing input data.
- (2) Training & Validation & Testing
- (3) Storing all necessary info

args

```
is_continual_training = False
trainer = None
trained_model = None
knowledge_graph = None
report
evaluator = None
```

```
start_time = None
```

 $\mathtt{setup_executor}() \to None$

 ${\tt save_trained_model}\,()\,\to None$

Save a knowledge graph embedding model

- (1) Send model to eval mode and cpu.
- (2) Store the memory footprint of the model.
- (3) Save the model into disk.
- (4) Update the stats of KG again?

Parameter

rtype

None

 $end(form_of_labelling: str) \rightarrow dict$

End training

- (1) Store trained model.
- (2) Report runtimes.
- (3) Eval model if required.

Parameter

rtype

A dict containing information about the training and/or evaluation

```
write report() \rightarrow None
```

Report training related information in a report. json file

 $\mathtt{start}() \rightarrow \mathrm{dict}$

Start training

(1) Loading the Data # (2) Create an evaluator object. # (3) Create a trainer object. # (4) Start the training

Parameter

rtype

A dict containing information about the training and/or evaluation

class dicee.executer.ContinuousExecute(args)

Bases: Execute

A subclass of Execute Class for retraining

- (1) Loading & Preprocessing & Serializing input data.
- (2) Training & Validation & Testing
- (3) Storing all necessary info

During the continual learning we can only modify * num_epochs * parameter. Trained model stored in the same folder as the seed model for the training. Trained model is noted with the current time.

```
continual\_start() \rightarrow dict
```

Start Continual Training

- (1) Initialize training.
- (2) Start continual training.
- (3) Save trained model.

Parameter

rtype

A dict containing information about the training and/or evaluation

dicee.knowledge graph

Classes

KG

Knowledge Graph

Module Contents

```
class dicee.knowledge_graph.KG (dataset_dir: str = None, byte_pair_encoding: bool = False,
           padding: bool = False, add_noise_rate: float = None, sparql_endpoint: str = None,
           path\_single\_kg: str = None, path\_for\_deserialization: str = None, add\_reciprocal: bool = None,
           eval_model: str = None, read_only_few: int = None, sample_triples_ratio: float = None,
           path_for_serialization: str = None, entity_to_idx=None, relation_to_idx=None, backend=None,
           training\_technique: str = None, separator: str = None)
     Knowledge Graph
     dataset_dir = None
     sparql_endpoint = None
     path_single_kg = None
     byte_pair_encoding = False
     ordered_shaped_bpe_tokens = None
     add_noise_rate = None
     num_entities = None
     num_relations = None
     path_for_deserialization = None
     add_reciprocal = None
     eval_model = None
     read_only_few = None
     sample_triples_ratio = None
     path_for_serialization = None
```

```
entity_to_idx = None
relation_to_idx = None
backend = 'pandas'
training_technique = None
idx_entity_to_bpe_shaped
enc
num_tokens
num_bpe_entities = None
padding = False
dummy_id
max_length_subword_tokens = None
train_set_target = None
target_dim = None
train_target_indices = None
ordered_bpe_entities = None
separator = None
description_of_input = None
\texttt{describe}\,()\,\to None
property entities_str: List
property relations_str: List
exists (h: str, r: str, t: str)
__iter__()
__len__()
func_triple_to_bpe_representation(triple: List[str])
```

dicee.knowledge_graph_embeddings

Classes

KGE Knowledge Graph Embedding Class for interactive usage of pre-trained models

Module Contents

```
class dicee.knowledge_graph_embeddings.KGE (path=None, url=None, construct_ensemble=False,
             model_name=None)
      Bases:
                                     dicee.abstracts.BaseInteractiveKGE,
                                                                                                dicee.abstracts.
      InteractiveQueryDecomposition
      Knowledge Graph Embedding Class for interactive usage of pre-trained models
      __str__()
      to (device: str) \rightarrow None
      get_transductive_entity_embeddings (indices: torch.LongTensor | List[str], as_pytorch=False,
                   as\_numpy = False, as\_list = True) \rightarrow torch.FloatTensor | numpy.ndarray | List[float]
      create_vector_database (collection_name: str, distance: str, location: str = 'localhost',
                   port: int = 6333)
      generate (h=", r=")
      eval_lp_performance (dataset=List[Tuple[str, str, str]], filtered=True)
      predict_missing_head_entity(relation: List[str] | str, tail_entity: List[str] | str, within=None,
                   batch\_size=2, topk=1, return\_indices=False) \rightarrow Tuple
           Given a relation and a tail entity, return top k ranked head entity.
           argmax_{e} in E \} f(e,r,t), where r in R, t in E.
           Parameter
           relation: Union[List[str], str]
           String representation of selected relations.
           tail_entity: Union[List[str], str]
           String representation of selected entities.
           k: int
           Highest ranked k entities.
           Returns: Tuple
           Highest K scores and entities
      predict_missing_relations (head_entity: List[str] | str, tail_entity: List[str] | str, within=None,
                   batch\_size=2, topk=1, return\_indices=False) \rightarrow Tuple
           Given a head entity and a tail entity, return top k ranked relations.
           argmax_{r} in R \} f(h,r,t), where h, t in E.
           Parameter
           head_entity: List[str]
           String representation of selected entities.
           tail_entity: List[str]
```

String representation of selected entities.

```
k: int
```

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

```
predict_missing_tail_entity (head_entity: List[str] | str, relation: List[str] | str, within: List[str] = None, batch_size=2, topk=1, return_indices=False) \rightarrow torch.FloatTensor Given a head entity and a relation, return top k ranked entities
```

 $argmax_{e} in E$ f(h,r,e), where h in E and r in R.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

 $predict(*, h: List[str] | str = None, r: List[str] | str = None, t: List[str] | str = None, within=None, logits=True) <math>\rightarrow$ torch. Float Tensor

Parameters

- logits
- h
- r
- t
- within

Predict missing item in a given triple.

Returns

- If you query a single (h, r, ?) or (?, r, t) or (h, ?, t), returns List[(item, score)]
- If you query a batch of B, returns List of B such lists.

```
\label{eq:core} \begin{split} \texttt{triple\_score} \ (h: List[str] \mid str = None, \, r: \, List[str] \mid str = None, \, t: \, List[str] \mid str = None, \, logits = False) \\ &\rightarrow \mathsf{torch}. FloatTensor \end{split}
```

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

```
relation: List[str]
     String representation of selected relations.
     tail_entity: List[str]
     String representation of selected entities.
     logits: bool
     If logits is True, unnormalized score returned
     Returns: Tuple
     pytorch tensor of triple score
return_multi_hop_query_results (aggregated_query_for_all_entities, k: int, only_scores)
single_hop_query_answering (query: tuple, only_scores: bool = True, k: int = None)
answer multi hop query (query type: str = None, query: Tuple[str | Tuple[str, str], Ellipsis] = None,
             queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, tnorm: str = 'prod',
             neg_norm: str = 'standard', lambda_: float = 0.0, k: int = 10, only_scores=False)
              \rightarrow List[Tuple[str, torch.Tensor]]
     # @TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a
     static function
     Find an answer set for EPFO queries including negation and disjunction
     Parameter
     query_type: str The type of the query, e.g., "2p".
     query: Union[str, Tuple[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.
     queries: List of Tuple[Union[str, Tuple[str, str]], ...]
     tnorm: str The t-norm operator.
     neg_norm: str The negation norm.
     lambda_: float lambda parameter for sugeno and yager negation norms
     k: int The top-k substitutions for intermediate variables.
          returns
               • List[Tuple[str, torch.Tensor]]
               • Entities and corresponding scores sorted in the descening order of scores
find_missing_triples (confidence: float, entities: List[str] = None, relations: List[str] = None,
             topk: int = 10, at most: int = sys.maxsize) \rightarrow Set
          Find missing triples
          Iterative over a set of entities E and a set of relation R:
```

orall e in E and orall r in R f(e,r,x)

otin G and f(e,r,x) > confidence

Return (e,r,x)

```
confidence: float
```

A threshold for an output of a sigmoid function given a triple.

topk: int

Highest ranked k item to select triples with f(e,r,x) > confidence.

at_most: int

Stop after finding at_most missing triples

 $\{(e,r,x) \mid f(e,r,x) > \text{confidence land } (e,r,x)\}$

otin G

 $deploy(share: bool = False, top_k: int = 10)$

train_triples (h: List[str], r: List[str], t: List[str], labels: List[float], iteration=2, optimizer=None)

 $train_k_vs_all(h, r, iteration=1, lr=0.001)$

Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:

train (kg, lr=0.1, epoch=10, $batch_size=32$, $neg_sample_ratio=10$, $num_workers=1$) \rightarrow None Retrained a pretrain model on an input KG via negative sampling.

train_literals (train_file_path: str = None, num_epochs: int = 100, lit_lr: float = 0.001, eval_litreal_preds: bool = True, eval_file_path: str = None, lit_normalization_type: str = 'z-norm', batch_size: int = 1024, sampling_ratio: float = None, random_seed=1, loader_backend: str = 'pandas', freeze_entity_embeddings: bool = True, gate residual: bool = True)

Trains the Literal Embeddings model using literal data.

Parameters

- train_file_path (str) Path to the training data file.
- num_epochs (int) Number of training epochs.
- lit_lr (float) Learning rate for the literal model.
- eval_litreal_preds (bool) If True, evaluate the model after training.
- eval_file_path (str) Path to evaluation data file.
- norm_type (str) Normalization type to use ('z-norm', 'min-max', or None).
- batch_size (int) Batch size for training.
- sampling_ratio (float) Ratio of training triples to use.
- loader_backend (str) Backend for loading the dataset ('pandas' or 'rdflib').
- freeze_entity_embeddings (bool) If True, freeze the entity embeddings during training.
- gate_residual (bool) If True, use gate residual connections in the model.

```
\label{eq:continuous_like_str} \begin{split} \texttt{predict\_literals} \; (\textit{entity: List[str]} \; | \; \textit{str} = \textit{None}, \; \textit{attribute: List[str]} \; | \; \textit{str} = \textit{None}, \\ & \textit{denormalize\_preds: bool} = \textit{True}) \; \rightarrow \text{numpy.ndarray} \end{split}
```

Predicts literal values for given entities and attributes.

Parameters

• **entity** (*Union* [*List* [*str*], *str*]) – Entity or list of entities to predict literals for.

- attribute (Union[List[str], str]) Attribute or list of attributes to predict literals for.
- denormalize_preds (bool) If True, denormalizes the predictions.

Returns

Predictions for the given entities and attributes.

Return type

torch.FloatTensor

Evaluates the trained literal prediction model on a test file.

Parameters

- eval_file_path (str) Path to the evaluation file.
- store_lit_preds (bool) If True, stores the predictions in a CSV file.
- eval_literals (bool) If True, evaluates the literal predictions and prints error metrics.
- loader_backend (str) Backend for loading the dataset ('pandas' or 'rdflib').

Returns

None

dicee.literal classes

Classes

GatedLinearUnit GatedLinearUnit	Applies a gated linear unit (GLU) operation:
LiteralEmbeddings	A model for learning and predicting numerical literals using pre-trained KGE.
LiteralDataset	Dataset for loading and processing literal data for training Literal Embedding model.

Module Contents

```
class dicee.literal_classes.GatedLinearUnit(input_dim, gated_residual=True)
    Bases: torch.nn.Module
```

Applies a gated linear unit (GLU) operation: Splits the input in half along the last dimension, applies a sigmoid gate to one half and multiplies it with the other.

```
proj

gate_residual = True

forward(x1, x2)

class dicee.literal class
```

```
\begin{tabular}{ll} {\bf class} & {\tt dicee.literal\_classes.LiteralEmbeddings} \ (num\_of\_data\_properties: int,\\ & embedding\_dims: int, entity\_embeddings: torch.tensor, dropout: float = 0.3, gate\_residual=True,\\ & freeze\_entity\_embeddings=True) \end{tabular}
```

Bases: torch.nn.Module

A model for learning and predicting numerical literals using pre-trained KGE.

```
num_of_data_properties
    Number of data properties (attributes).
        Type
            int
embedding_dims
    Dimension of the embeddings.
        Type
            int
entity_embeddings
    Pre-trained entity embeddings.
         Type
            torch.tensor
dropout
    Dropout rate for regularization.
         Type
            float
gate_residual
    Whether to use gated residual connections.
         Type
            bool
freeze_entity_embeddings
    Whether to freeze the entity embeddings during training.
         Type
            bool
embedding_dim
num_of_data_properties
hidden_dim
entity_embeddings
data_property_embeddings
fc
fc_out
dropout
residual
layer_norm
forward (entity_idx, attr_idx)
```

Parameters

• entity_idx (Tensor) - Entity indices (batch).

```
• attr_idx (Tensor) - Attribute (Data property) indices (batch).
```

Returns

scalar predictions.

Return type

Tensor

Bases: torch.utils.data.Dataset

Dataset for loading and processing literal data for training Literal Embedding model. This dataset handles the loading, normalization, and preparation of triples for training a literal embedding model.

Extends torch.utils.data.Dataset for supporting PyTorch dataloaders.

train_file_path

Path to the training data file.

Type

str

normalization

Type of normalization to apply ('z-norm', 'min-max', or None).

Type

str

normalization_params

Parameters used for normalization.

Type

dict

sampling_ratio

Fraction of the training set to use for ablations.

Type

float

entity_to_idx

Mapping of entities to their indices.

Type

dict

num_entities

Total number of entities.

Type

int

data_property_to_idx

Mapping of data properties to their indices.

Type

dict

num_data_properties

Total number of data properties.

```
Type
            int
loader_backend
    Backend to use for loading data ('pandas' or 'rdflib').
            str
train_file_path
loader_backend = 'pandas'
normalization_type = 'z-norm'
normalization_params
sampling_ratio = None
entity_to_idx = None
num_entities
__getitem__(index)
__len__()
static load_and_validate_literal_data (file_path: str = None, loader_backend: str = 'pandas')
            \rightarrow pandas.DataFrame
```

Loads and validates the literal data file. :param file_path: Path to the literal data file. :type file_path: str

Returns

DataFrame containing the loaded and validated data.

Return type

pd.DataFrame

 $static denormalize(preds_norm, attributes, normalization_params) \rightarrow numpy.ndarray$

Denormalizes the predictions based on the normalization type.

Args: preds_norm (np.ndarray): Normalized predictions to be denormalized. attributes (list): List of attributes corresponding to the predictions. normalization_params (dict): Dictionary containing normalization parameters for each attribute.

Returns

Denormalized predictions.

Return type

np.ndarray

dicee.models

Submodules

dicee.models.adopt

Classes

ADOPT

Base class for all optimizers.

Functions

adopt(params,	grads,	exp_avgs,	exp_avg_sqs,	Functional API that performs ADOPT algorithm compu-
state_steps)				tation.

Module Contents

```
class dicee.models.adopt.ADOPT (params: torch.optim.optimizer.ParamsT,
             lr: float \mid torch.Tensor = 0.001, betas: Tuple[float, float] = (0.9, 0.9999), eps: float = 1e-06,
             clip_lambda: Callable[[int], float] \ None = lambda step: ..., weight_decay: float = 0.0,
             decouple: bool = False, *, foreach: bool | None = None, maximize: bool = False,
             capturable: bool = False, differentiable: bool = False, fused: bool | None = None)
```

Bases: torch.optim.optimizer.Optimizer

Base class for all optimizers.



Warning

Parameters need to be specified as collections that have a deterministic ordering that is consistent between runs. Examples of objects that don't satisfy those properties are sets and iterators over values of dictionaries.

Parameters

- params (iterable) an iterable of torch. Tensor s or dict s. Specifies what Tensors should be optimized.
- defaults (dict): a dict containing default values of optimization options (used when a parameter group doesn't specify them).

```
clip_lambda
__setstate__(state)
step(closure=None)
     Perform a single optimization step.
```

Parameters

closure (Callable, optional) - A closure that reevaluates the model and returns the

```
dicee.models.adopt.adopt(params: List[torch.Tensor], grads: List[torch.Tensor],
             exp avgs: List[torch.Tensor], exp avg sqs: List[torch.Tensor], state steps: List[torch.Tensor],
             foreach: bool | None = None, capturable: bool = False, differentiable: bool = False,
             fused: bool | None = None, grad_scale: torch. Tensor | None = None,
             found_inf: torch.Tensor | None = None, has_complex: bool = False, *, beta1: float, beta2: float,
             lr: float | torch. Tensor, clip_lambda: Callable[[int], float] | None, weight_decay: float,
             decouple: bool, eps: float, maximize: bool)
```

Functional API that performs ADOPT algorithm computation.

dicee.models.base_model

Classes

BaseKGELightning	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
IdentityClass	Base class for all neural network modules.

Module Contents

```
class dicee.models.base_model.BaseKGELightning(*args, **kwargs)
```

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an $__init__()$ call to the parent class must be made before assignment on the child.

Variables

 $\textbf{training} \ (\textit{bool}) - Boolean \ represents \ whether \ this \ module \ is \ in \ training \ or \ evaluation \ mode.$

```
training_step_outputs = []
```

 $mem_of_model() \rightarrow Dict$

Size of model in MB and number of params

 $\verb|training_step|(batch, batch_idx=None)|$

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

• batch - The output of your data iterable, normally a DataLoader.

- batch idx The index of this batch.
- dataloader_idx The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- Tensor The loss tensor
- dict A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- None In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

# do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

1 Note

When $accumulate_grad_batches > 1$, the loss returned here will be automatically normalized by $accumulate_grad_batches$ internally.

 $loss_function(yhat_batch: torch.FloatTensor, y_batch: torch.FloatTensor)$

Parameters

- yhat_batch
- y_batch

```
on_train_epoch_end(*args, **kwargs)
```

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the LightningModule and access them in this hook:

```
class MyLightningModule(L.LightningModule):
   def __init__(self):
        super().__init__()
        self.training_step_outputs = []
   def training_step(self):
        loss = ...
        self.training_step_outputs.append(loss)
        return loss
   def on_train_epoch_end(self):
        # do something with all training_step outputs, for example:
        epoch_mean = torch.stack(self.training_step_outputs).mean()
        self.log("training_epoch_mean", epoch_mean)
        # free up the memory
        self.training_step_outputs.clear()
```

test_epoch_end(outputs: List[Any])

test dataloader() \rightarrow None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in prepare_data()
- process and split in setup()

However, the above are only necessary for distributed processing.

Warning

do not assign state in prepare_data

- test()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

1 Note

If you don't need a test dataset and a test_step(), you don't need to implement this method.

$val_dataloader() \rightarrow None$

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:**~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs` to a positive integer.

It's recommended that all data downloads and preparation happen in prepare_data().

- fit()
- validate()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

1 Note

If you don't need a validation dataset and a validation_step(), you don't need to implement this method.

$predict_dataloader() \rightarrow None$

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in prepare_data().

- predict()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Returns

A torch.utils.data.DataLoader or a sequence of them specifying prediction samples.

$train_dataloader() \rightarrow None$

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

dataloader will be reloaded you return not unless you set :paramref: `~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs` to a positive integer.

For data processing use the following pattern:

- download in prepare_data()
- process and split in setup()

However, the above are only necessary for distributed processing.



🛕 Warning

do not assign state in prepare_data

- fit()
- prepare_data()
- setup()



1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

configure_optimizers (parameters=None)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- · Single optimizer.
- List or Tuple of optimizers.
- Two lists The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple lr_scheduler_config).
- Dictionary, with an "optimizer" key, and (optionally) a "lr_scheduler" key whose value is a single LR scheduler or lr_scheduler_config.
- None Fit will run without any optimizer.

The lr_scheduler_config is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
   "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
   "interval": "epoch",
   # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
   "frequency": 1,
    # Metric to monitor for schedulers like `ReduceLROnPlateau`
   "monitor": "val_loss",
   # If set to `True`, will enforce that the value specified 'monitor'
    # is available when the scheduler is updated, thus stopping
    # training if not found. If set to `False`, it will only produce a warning
   "strict": True,
    # If using the `LearningRateMonitor` callback to monitor the
    # learning rate progress, this keyword can be used to specify
    # a custom logged name
    "name": None,
```

When there are schedulers in which the .step() method is conditioned on a value, such as the torch.optim.lr_scheduler.ReduceLROnPlateau scheduler, Lightning requires that the lr_scheduler_config contains the keyword "monitor" set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using self.log('metric_to_track', metric_val) in your LightningModule.

1 Note

Some things to know:

- Lightning calls .backward() and .step() automatically in case of automatic optimization.
- If a learning rate scheduler is specified in <code>configure_optimizers()</code> with key "interval" (default "epoch") in the scheduler configuration, Lightning will call the scheduler's <code>.step()</code> method automatically in case of automatic optimization.
- If you use 16-bit precision (precision=16), Lightning will automatically handle the optimizer.
- If you use torch.optim.LBFGS, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the optimizer_step() hook.

class dicee.models.base_model.BaseKGE (args: dict)

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
```

```
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
            x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
     byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
           y_idx: torch.LongTensor = None)
        Parameters
            • x
            • y_idx
            • ordered_bpe_entities
\textbf{forward\_triples}~(\textit{x:torch.LongTensor})~\rightarrow torch.Tensor
        Parameters
forward_k_vs_all(*args, **kwargs)
forward_k_vs_sample(*args, **kwargs)
{\tt get\_triple\_representation}\,(idx\_hrt)
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args = None
_call__(x)
static forward(x)
```

dicee.models.clifford

Classes

Keci	Base class for all neural network modules.
CKeci	Without learning dimension scaling
DeCaL	Base class for all neural network modules.

Module Contents

```
class dicee.models.clifford.Keci(args)
Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an $__init__()$ call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'Keci'
p
q
r
requires_grad_for_interactions = True
```

```
compute\_sigma\_pp(hp, rp)
          Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k
          sigma {pp} captures the interactions between along p bases For instance, let p e 1, e 2, e 3, we compute
          interactions between e 1 e 2, e 1 e 3, and e 2 e 3 This can be implemented with a nested two for loops
                  results = [] for i in range(p - 1):
                          for k in range(i + 1, p):
                               results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])
                  sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))
          Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1,
          e1e2, e1e3,
                  e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
          Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.
compute\_sigma\_qq(hq, rq)
          Compute sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q}
          captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions
          between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops
                  results = [] for j in range(q - 1):
                          for k in range(j + 1, q):
                              results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])
                  sigma qq = torch.stack(results, dim=2) assert sigma qq.shape == (b, r, int((q * (q - 1)) / 2))
          Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1,
          e1e2, e1e3,
                  e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
          Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.
compute_sigma_pq(*, hp, hq, rp, rq)
          sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j
          results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
                  for j in range(q):
                          sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
          print(sigma_pq.shape)
apply_coefficients(hp, hq, rp, rq)
          Multiplying a base vector with its scalar coefficient
clifford_multiplication (h0, hp, hq, r0, rp, rq)
          Compute our CL multiplication
                  sum_{j=p+1}^{p+q} r_j e_j
                  ei ^2 = +1 for i = < i = < p ej ^2 = -1 for p < j = < p+q ei ej = -eje1 for i
          eq j
                  h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q} + sig
```

(1) $sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i - sum_{j=p+1}^{p+q} (h_j r_j) e_j$

- (2) $sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$
- (3) $sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$
- (4) $sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k h_k r_i) e_i e_k$
- (5) $sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k h_k r_j) e_j e_k$
- (6) $sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j h_j r_i) e_i e_j$

construct cl multivector(x: torch.FloatTensor, r: int, p: int, q: int)

 \rightarrow tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl \{p,q\}(mathbb\{R\}^{\wedge}d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor with (n,r) shape)
- **ap** (*torch.FloatTensor with* (*n,r,p*) *shape*)
- aq $(torch.FloatTensor\ with\ (n,r,q)\ shape)$

forward_k_vs_with_explicit(x: torch.Tensor)

k_vs_all_score(bpe_head_ent_emb, bpe_rel_ent_emb, E)

 $forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations mathbb $\{R\}^d$.
- (2) Construct head entity and relation embeddings according to $Cl_{p,q}(mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter — x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n,|E|) shape

construct_batch_selected_cl_multivector(x: torch.FloatTensor, r: int, p: int, q: int)

 \rightarrow tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of batchs multivectors $Cl_{p,q}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (torch.FloatTensor with (n,k, m) shape)
- **ap** (torch.FloatTensor with (n,k, m, p) shape)
- aq (torch.FloatTensor with (n,k, m, q) shape)

 $forward_k_vs_sample$ (x: torch.LongTensor, target_entity_idx: torch.LongTensor) \rightarrow torch.FloatTensor

Parameter

```
x: torch.LongTensor with (n,2) shape
           target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.
               rtype
                   torch.FloatTensor with (n, k) shape
     score(h, r, t)
     forward\_triples(x: torch.Tensor) \rightarrow torch.FloatTensor
           Parameter
           x: torch.LongTensor with (n,3) shape
               rtype
                   torch.FloatTensor with (n) shape
class dicee.models.clifford.CKeci(args)
     Bases: Keci
     Without learning dimension scaling
     name = 'CKeci'
     requires_grad_for_interactions = False
class dicee.models.clifford.DeCaL(args)
```

Base class for all neural network modules.

Bases: dicee.models.base_model.BaseKGE

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an $__{init}_{_}()$ call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation embeddings

p

q

r

re

forward_triples (x: torch.Tensor) \rightarrow torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl pqr (a: torch.tensor) \rightarrow torch.tensor

Input: tensor(batch_size, emb_dim) \longrightarrow output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

 $\verb|compute_sigmas_single| (\textit{list}_h_\textit{emb}, \textit{list}_r_\textit{emb}, \textit{list}_t_\textit{emb})|$

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^{p} h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^{q} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}$$

and return:

$$sigma_0t = \sigma_0 \cdot t_0 = s0 + s1 - s2s3, s4ands5$$

compute_sigmas_multivect (list_h_emb, list_r_emb)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q-1} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q-1} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q-1} (h_j r_{j'} - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q-1} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= i, i'$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_j - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= i <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= i <= p and p + 1 <= i <= p and p and$$

 $forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to Cl {p,q, r}(mathbb{R}^d).
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter — x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

 $apply_coefficients(h0, hp, hq, hk, r0, rp, rq, rk)$

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (x: torch.FloatTensor, re: int, p: int, q: int, r: int)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{p,q,r}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor)
- **ap** (torch.FloatTensor)
- **aq** (torch.FloatTensor)
- **ar** (torch.FloatTensor)

 $compute_sigma_pp(hp, rp)$

Compute .. math:

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

```
results = [] for i in range(p - 1):
```

```
for k in range(i + 1, p):
```

$$results.append(hp[:,:,i]*rp[:,:,k] - hp[:,:,k]*rp[:,:,i])$$

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

 $\texttt{compute_sigma_qq}\,(hq,rq)$

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) Eq.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

 $sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))$

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

 $compute_sigma_rr(hk, rk)$

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^{p} (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq(*, hp, hq, rp, rq)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for i in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

 $compute_sigma_pr(*, hp, hk, rp, rk)$

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

 $compute_sigma_qr(*, hq, hk, rq, rk)$

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for i in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

dicee.models.complex

Classes

ConEx	Convolutional ComplEx Knowledge Graph Embeddings
AConEx	Additive Convolutional ComplEx Knowledge Graph Em-
	beddings
ComplEx	Base class for all neural network modules.

Module Contents

```
class dicee.models.complex.ConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Convolutional ComplEx Knowledge Graph Embeddings
     name = 'ConEx'
     conv2d
     fc_num_input
     fc1
     norm_fc1
     bn_conv2d
     feature_map_dropout
     residual\_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                 C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
          Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
          that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
          complex-valued embeddings :return:
     forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
     forward\_triples(x: torch.Tensor) \rightarrow torch.FloatTensor
              Parameters
     forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)
class dicee.models.complex.AConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional ComplEx Knowledge Graph Embeddings
     name = 'AConEx'
     conv2d
     fc_num_input
     fc1
```

```
norm_fc1
```

bn_conv2d

feature_map_dropout

```
residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor], C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
```

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

```
forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
```

 $forward_triples(x: torch.Tensor) \rightarrow torch.FloatTensor$

Parameters

x

forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

```
class dicee.models.complex.ComplEx(args)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'ComplEx'
```

Parameters

- emb_h
- emb_r
- emb E

 $forward_k_vs_all(x: torch.LongTensor) \rightarrow torch.FloatTensor$

forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)

dicee.models.dualE

Classes

DualE	Dual Quaternion Knowledge Graph Embeddings
	(https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

Module Contents

```
class dicee.models.dualE.DualE(args)
```

Bases: dicee.models.base_model.BaseKGE

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent = None

kvsall_score ($e_1h, e_2h, e_3h, e_4h, e_5h, e_6h, e_7h, e_8h, e_1t, e_2t, e_3t, e_4t, e_5t, e_6t, e_7t, e_8t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) o$ torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

 $forward_triples(idx_triple: torch.tensor) \rightarrow torch.tensor$

Negative Sampling forward pass:

Input

```
x: torch.LongTensor with (n, ) shape
```

Output

```
torch.FloatTensor with (n) shape
```

```
{\tt forward\_k\_vs\_all}\;(\mathcal{X})
```

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T (x: torch.tensor) \rightarrow torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

dicee.models.ensemble

Classes

EnsembleKGE

Module Contents

```
class dicee.models.ensemble.EnsembleKGE (seed_model=None, pretrained_models: List = None)
```

```
name
```

```
train_mode = True
named_children()
property example_input_array
parameters()
modules()
__iter__()
__len__()
eval()
to (device)
```

mem_of_model()

```
__call__(x_batch)
step()
get_embeddings()
__str__()
```

dicee.models.function_space

Classes

FMult	Learning Knowledge Neural Graphs
GFMult	Learning Knowledge Neural Graphs
FMult2	Learning Knowledge Neural Graphs
LFMult1	Embedding with trigonometric functions. We represent
	all entities and relations in the complex number space as:
LFMult	Embedding with polynomial functions. We represent all
	entities and relations in the polynomial space as:

Module Contents

```
class dicee.models.function_space.FMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Learning Knowledge Neural Graphs
     name = 'FMult'
     entity_embeddings
     relation_embeddings
     num_sample = 50
     gamma
     roots
     weights
     compute\_func(weights: torch.FloatTensor, x) \rightarrow torch.FloatTensor
     chain_func(weights, x: torch.FloatTensor)
     \textbf{forward\_triples} (\textit{idx\_triple: torch.Tensor}) \rightarrow \text{torch.Tensor}
               Parameters
class dicee.models.function_space.GFMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Learning Knowledge Neural Graphs
```

```
name = 'GFMult'
      entity_embeddings
      relation_embeddings
      num_sample = 250
      roots
      weights
      compute\_func(weights: torch.FloatTensor, x) \rightarrow torch.FloatTensor
      chain_func (weights, x: torch.FloatTensor)
      forward\_triples(idx\_triple: torch.Tensor) \rightarrow torch.Tensor
                Parameters
                    x
class dicee.models.function_space.FMult2(args)
      Bases: dicee.models.base_model.BaseKGE
      Learning Knowledge Neural Graphs
      name = 'FMult2'
      n_{ayers} = 3
      n = 50
      score_func = 'compositional'
      discrete_points
      entity_embeddings
      relation_embeddings
      {\tt build\_func}\,(\textit{Vec}\,)
      build_chain_funcs (list_Vec)
      compute\_func(W, b, x) \rightarrow torch.FloatTensor
      function (list_W, list_b)
      trapezoid(list_W, list_b)
      \textbf{forward\_triples} \ (\textit{idx\_triple: torch.Tensor}) \ \rightarrow \textbf{torch.Tensor} \\
               Parameters
                    x
```

77

```
class dicee.models.function_space.LFMult1(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
     f(x) = sum_{k=0}^{k=0}^{k=d-1}wk e^{kix}, and use the three differents scoring function as in the paper to evaluate
     the score
     name = 'LFMult1'
     entity_embeddings
     relation_embeddings
     forward_triples (idx_triple)
               Parameters
     \verb|tri_score|(h,r,t)
     \mathtt{vtp\_score}(h, r, t)
class dicee.models.function_space.LFMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) =
     sum \{i=0\}^{d-1} a k x^{i} and use the three differents scoring function as in the paper to evaluate the score.
     We also consider combining with Neural Networks.
     name = 'LFMult'
     entity_embeddings
     relation_embeddings
     degree
     x_values
     forward_triples (idx_triple)
               Parameters
     construct_multi_coeff(x)
     poly_NN(x, coefh, coefr, coeft)
           Constructing a 2 layers NN to represent the embeddings. h = sigma(wh^T x + bh), r = sigma(wr^T x + br),
           t = sigma(wt^T x + bt)
     linear(x, w, b)
     scalar_batch_NN(a, b, c)
           element wise multiplication between a,b and c: Inputs: a, b, c ====> torch.tensor of size batch_size x m x
           d Output: a tensor of size batch_size x d
```

```
tri_score (coeff_h, coeff_r, coeff_t)
```

this part implement the trilinear scoring techniques:

```
score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k} = 0 ^{d-1} dfrac\{a_i*b_j*c_k\}\{1 + (i+j+k)\%d\}
```

- 1. generate the range for i, j and k from [0 d-1]
- 2. perform $dfrac\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$ in parallel for every batch
- 3. take the sum over each batch

$\mathtt{vtp_score}(h, r, t)$

this part implement the vector triple product scoring techniques:

```
score(h,r,t) = int_{0}{1} \quad h(x)r(x)t(x) \quad dx = sum_{i,j,k} = 0^{d-1} \quad dfrac_{a_i*c_j*b_k} - b_i*c_j*a_k}{(1+(i+j)\%d)(1+k)}
```

- 1. generate the range for i,j and k from [0 d-1]
- 2. Compute the first and second terms of the sum
- 3. Multiply with then denominator and take the sum
- 4. take the sum over each batch

$comp_func(h, r, t)$

this part implement the function composition scoring techniques: i.e. score = <hor, t>

```
polynomial(coeff, x, degree)
```

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,...d] and return a vector tensor (coeff $[0][0] + \text{coeff}[0][1]x + ... + \text{coeff}[0][d]x^d$,

$$coeff[1][0] + coeff[1][1]x + ... + coeff[1][d]x^d$$

```
pop (coeff, x, degree)
```

This function allow us to evaluate the composition of two polynomes without for loops:) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,...d]

dicee.models.octonion

Classes

OMult	Base class for all neural network modules.
ConvO	Base class for all neural network modules.
AConv0	Additive Convolutional Octonion Knowledge Graph Em-
	beddings

Functions

```
octonion_mul(*, O_1, O_2)
octonion_mul_norm(*, O_1, O_2)
```

Module Contents

```
dicee.models.octonion.octonion_mul(*, O_1, O_2)
dicee.models.octonion.octonion_mul_norm(*, O_1, O_2)
class dicee.models.octonion.OMult(args)
    Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

```
class dicee.models.octonion.ConvO(args: dict)
    Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F
class Model(nn.Module):
    def __init__(self) -> None:
       super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
name = 'ConvO'
conv2d
fc_num_input
fc1
bn_conv2d
norm_fc1
feature_map_dropout
static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
           emb_rel_e5, emb_rel_e6, emb_rel_e7)
residual_convolution (O_1, O_2)
forward triples (x: torch.Tensor) \rightarrow torch.Tensor
```

Parameters

x

```
forward_k_vs_all (x: torch.Tensor)
          Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
          [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,)
          Entities()
class dicee.models.octonion.AConvO(args: dict)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional Octonion Knowledge Graph Embeddings
     name = 'AConvO'
     conv2d
     fc_num_input
     fc1
     bn_conv2d
     norm_fc1
     feature_map_dropout
     static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                  emb_rel_e5, emb_rel_e6, emb_rel_e7)
     residual\_convolution(O_1, O_2)
     forward\_triples(x: torch.Tensor) \rightarrow torch.Tensor
               Parameters
                   x
     forward_k_vs_all (x: torch.Tensor)
```

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

dicee.models.pykeen models

Classes

PykeenKGE	A class for using knowledge graph embedding models im-
	plemented in Pykeen

Module Contents

```
class dicee.models.pykeen_models.PykeenKGE(args: dict)
```

Bases: dicee.models.base_model.BaseKGE

A class for using knowledge graph embedding models implemented in Pykeen

Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Pykeen_HolE: Pykeen_TransD: Pykeen_TransE: Pykeen_TransF: Pykeen_TransH: Pykeen_TransR:

```
model_kwargs
name
model
loss_history = []
args
entity_embeddings = None
relation_embeddings = None
forward_k_vs_all (x: torch.LongTensor)
     # => Explicit version by this we can apply bn and dropout
     # (1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r =
     self.get_head_relation_representation(x) \# (2) Reshape (1). if self.last_dim > 0:
          h = h.reshape(len(x), self.embedding dim, self.last dim) r = r.reshape(len(x), self.embedding dim,
          self.last dim)
     \# (3) Reshape all entities. if self.last_dim > 0:
          t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)
     else:
          t = self.entity_embeddings.weight
     # (4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r,
     all_entities=t, slice_size=1)
forward\_triples(x: torch.LongTensor) \rightarrow torch.FloatTensor
     # => Explicit version by this we can apply bn and dropout
     # (1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t =
     self.get_triple_representation(x) \# (2) Reshape (1). if self.last_dim > 0:
          h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
          self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)
     # (3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice size=None, slice dim=0)
abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)
```

dicee.models.quaternion

Classes

QMult	Base class for all neural network modules.
ConvQ	Convolutional Quaternion Knowledge Graph Embeddings
AConvQ	Additive Convolutional Quaternion Knowledge Graph Embeddings

Functions

```
quaternion_mul_with_unit_norm(*, Q_1, Q_2)
```

Module Contents

```
dicee.models.quaternion.quaternion_mul_with_unit_norm(*, Q_1, Q_2)

class dicee.models.quaternion.QMult(args)

Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an <u>__init__()</u> call to the parent class must be made before assignment on the child.

Variables

 $\textbf{training} \ (\textit{bool}) - Boolean \ represents \ whether \ this \ module \ is \ in \ training \ or \ evaluation \ mode.$

```
\label{eq:name} \begin{tabular}{ll} name &= 'QMult' \\ \\ explicit &= True \\ \\ quaternion_multiplication_followed_by_inner_product $(h,r,t)$ \\ \\ \end{tabular}
```

- h shape: (*batch_dims, dim) The head representations.
- **r** shape: (*batch_dims, dim) The head representations.
- t shape: (*batch_dims, dim) The tail representations.

Returns

Triple scores.

 $static quaternion_normalizer(x: torch.FloatTensor) \rightarrow torch.FloatTensor$

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a+bi+cj+dk| = \sqrt{a^2+b^2+c^2+d^2}$$

L2 norm of quaternion vector:

$$||x||^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i \cdot re^2 + x_i \cdot im_1^2 + x_i \cdot im_2^2 + x_i \cdot im_3^2)$$

Parameters

 \mathbf{x} – The vector.

Returns

The normalized vector.

 $k_vs_all_score$ (bpe_head_ent_emb, bpe_rel_ent_emb, E)

Parameters

- bpe_head_ent_emb
- bpe_rel_ent_emb
- E

 $forward_k_vs_all(x)$

Parameters

x

forward_k_vs_sample (x, target_entity_idx)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.quaternion.ConvQ(args)

Bases: dicee.models.base_model.BaseKGE

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings

relation_embeddings

conv2d

fc num input

fc1

```
bn_conv1
     bn_conv2
     feature_map_dropout
     residual_convolution (Q_1, Q_2)
     forward\_triples (indexed\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities|)
class dicee.models.quaternion.AConvQ(args)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional Quaternion Knowledge Graph Embeddings
     name = 'AConvQ'
     entity_embeddings
     relation_embeddings
     conv2d
     fc_num_input
     fc1
     bn_conv1
     bn_conv2
     feature_map_dropout
     residual_convolution (Q_1, Q_2)
     forward\_triples (indexed\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
                   х
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities|)
```

dicee.models.real

Classes

DistMult	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
TransE	Translating Embeddings for Modeling
Shallom	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
Pyke	A Physical Embedding Model for Knowledge Graphs

Module Contents

```
class dicee.models.real.DistMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575
     name = 'DistMult'
     k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor, emb_E: torch.FloatTensor)
              Parameters
                   • emb h
                   • emb_r
                   • emb_E
     forward_k_vs_all (x: torch.LongTensor)
     forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)
     \mathtt{score}\left(h,r,t\right)
class dicee.models.real.TransE(args)
     Bases: dicee.models.base_model.BaseKGE
     Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/
     1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf
     name = 'TransE'
     margin = 4
     score (head_ent_emb, rel_ent_emb, tail_ent_emb)
     forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
class dicee.models.real.Shallom(args)
     Bases: dicee.models.base_model.BaseKGE
     A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
     name = 'Shallom'
     shallom
```

dicee.models.static_funcs

Functions

```
quaternion\_mul(\rightarrow Tuple[torch.Tensor, torch.Tensor, Perform quaternion multiplication ...)
```

Module Contents

```
dicee.models.static_funcs.quaternion_mul(*, Q_1, Q_2) \rightarrow Tuple[torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor] Perform quaternion multiplication:param Q_1::param Q_2::return:
```

dicee.models.transformers

Full definition of a GPT Language Model, all of it in this single file. References: 1) the official GPT-2 TensorFlow implementation released by OpenAI: https://github.com/openai/gpt-2/blob/master/src/model.py 2) hugging-face/transformers PyTorch implementation: https://github.com/huggingface/transformers/blob/main/src/transformers/models/gpt2/modeling_gpt2.py

Classes

BytE	Base class for all neural network modules.
LayerNorm	LayerNorm but with an optional bias. PyTorch doesn't support simply bias=False
CausalSelfAttention	Base class for all neural network modules.
MLP	Base class for all neural network modules.
Block	Base class for all neural network modules.
GPTConfig	
GPT	Base class for all neural network modules.

Module Contents

```
class dicee.models.transformers.BytE(*args, **kwargs)
Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an $__init__()$ call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'BytE'
config
temperature = 0.5
```

```
topk = 2
```

transformer

1m head

loss_function(yhat_batch, y_batch)

Parameters

- yhat_batch
- y_batch

forward(x: torch.LongTensor)

Parameters

```
\mathbf{x} (B by T tensor)
```

```
generate (idx, max_new_tokens, temperature=1.0, top_k=None)
```

Take a conditioning sequence of indices idx (LongTensor of shape (b,t)) and complete the sequence max_new_tokens times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in model.eval() mode of operation for this.

```
training_step(batch, batch_idx=None)
```

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- batch The output of your data iterable, normally a DataLoader.
- batch_idx The index of this batch.
- dataloader_idx The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- Tensor The loss tensor
- dict A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- None In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

# do training_step with encoder
    ...
    opt1.step()
# do training_step with decoder
    ...
    opt2.step()
```

1 Note

When accumulate_grad_batches > 1, the loss returned here will be automatically normalized by accumulate_grad_batches internally.

class dicee.models.transformers.LayerNorm(ndim, bias)

Bases: torch.nn.Module

LayerNorm but with an optional bias. PyTorch doesn't support simply bias=False

weight

bias

forward(input)

class dicee.models.transformers.CausalSelfAttention(config)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.



c_attn

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ \circ 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
c_proj
attn_dropout
resid_dropout
n_head
n_embd
dropout
flash = True
forward(x)
class dicee.models.transformers.MLP(config)
Bases: torch.nn.Module
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an <u>__init__()</u> call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
c_fc
gelu
c_proj
dropout
forward(x)
class dicee.models.transformers.Block(config)
```

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an <u>__init__()</u> call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

ln_1

```
attn
ln_2
mlp
forward(x)

class dicee.models.transformers.GPTConfig

block_size: int = 1024

vocab_size: int = 50304

n_layer: int = 12

n_head: int = 12

n_embd: int = 768

dropout: float = 0.0

bias: bool = False

class dicee.models.transformers.GPT(config)

Bases: torch.nn.Module
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

config

transformer

lm_head

```
get_num_params (non_embedding=True)
```

Return the number of parameters in the model. For non-embedding count (default), the position embeddings get subtracted. The token embeddings would too, except due to the parameter sharing these params are actually used as weights in the final layer, so we include them.

Classes

ADOPT Base class for all optimizers. BaseKGELightning Base class for all neural network modules. Base Class for all neural network modules. IdentityClass Base class for all neural network modules. BaseKGE Base class for all neural network modules. DistMult Embedding Entities and Relations for Learning and Inference in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. Conex Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. QMult Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings AconvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base class for all neural network modules. OMult Base class for all neural network modules.		
Base RGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. Base RGE Base class for all neural network modules. DistMult Embedding Entities and Relations for Learning and Inference in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. ConeEx Convolutional ComplEx Knowledge Graph Embeddings AConex Additive Convolutional ComplEx Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. QMult Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base class for all neural network modules. Own Base class for all neural network modules. Base class for all neural network modules. Base class for all neural network modules.	ADOPT	
IdentityClass Base class for all neural network modules. BaseKGE Base class for all neural network modules. DistMult Embedding Entities and Relations for Learning and Inference in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. ConEx Convolutional ComplEx Knowledge Graph Embeddings AConEx Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. QMult Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. AconvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base class for all neural network modules. ConvQ Base class for all neural network modules. Base class for all neural network modules. ConvQ Base class for all n	BaseKGELightning	Base class for all neural network modules.
Base Class for all neural network modules. DistMult Embedding Entities and Relations for Learning and Inference in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. ConEx Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings BaseClass for all neural network modules. Omalt OMult Base class for all neural network modules. OMult Base class for all neural network modules. ConvO Base class for all neural network modules. AConvO Base class for all neural network modules. AConvO Base class for all neural network modules. AConvO Base clas	BaseKGE	Base class for all neural network modules.
DistMult Embedding Entities and Relations for Learning and Inference in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. ConEx Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. QMult Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base Class for all neural network modules. OMult Base class for all neural network modules. ConvQ Base class for all neural network modules. OMult Base class for all neural network modules. AConvQ Base class for all neural network modules. AConvQ Base class for all neural network modules. OMult Base class for all neural network modules. ConvQ Base class for al	IdentityClass	Base class for all neural network modules.
ence in Knowledge Bases TransE Translating Embeddings for Modeling Shallom A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs Base Class for all neural network modules. Conex Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base Class for all neural network modules. Base class for all neural network modules. Base class for all neural network modules. IdentityClass Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings ACONVQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base KGE Base class for all neural network modules. ConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base KGE Base class for all neural network modules. ACONVQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base Class for all neural network modules. AconvO Base class for all neural network modules. AconvO Base class for all neural network modules. AconvO Base class for all neural network modules. Additive Convolutional Octonion Knowledge Graph Embeddings	BaseKGE	Base class for all neural network modules.
TransETranslating Embeddings for ModelingShallomA shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)PykeA Physical Embedding Model for Knowledge GraphsBase KGEBase class for all neural network modules.ConexConvolutional ComplEx Knowledge Graph EmbeddingsAConExAdditive Convolutional ComplEx Knowledge Graph EmbeddingsComplExBase class for all neural network modules.Base KGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvQBase class for all neural network modules.ConvQBase class for all neural network modules.AConvQBase class for all neural network modules.AConvQBase class for all neural network modules.ConvQBase class for all neural network modules.ConvQAdditive Convolutional Octonion Knowledge Graph Embeddings	DistMult	Embedding Entities and Relations for Learning and Infer-
A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090) Pyke A Physical Embedding Model for Knowledge Graphs BaseKGE Base class for all neural network modules. ConEx Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings ACONVQ Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. ConvQ Laternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. Base class for all neural network modules. Additive Convolutional Quaternion Knowledge Graph Embeddings Base class for all neural network modules. AconvO Base class for all neural network modules. Additive Convolutional Octonion Knowledge Graph Embeddings		ence in Knowledge Bases
Marxiv.org/abs/2101.09090) Pyke	TransE	Translating Embeddings for Modeling
PykeA Physical Embedding Model for Knowledge GraphsBaseKGEBase class for all neural network modules.ConExConvolutional ComplEx Knowledge Graph EmbeddingsAConExAdditive Convolutional ComplEx Knowledge Graph EmbeddingsComplExBase class for all neural network modules.BaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBase KGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	Shallom	A shallow neural model for relation prediction (https:
BaseKGE Base class for all neural network modules. ConEx Convolutional ComplEx Knowledge Graph Embeddings ACONEX Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. QMult Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMult Base class for all neural network modules. ConvO Base class for all neural network modules. ACONVO Base class for all neural network modules. ACONVO Base class for all neural network modules. ACONVO Additive Convolutional Octonion Knowledge Graph Embeddings		//arxiv.org/abs/2101.09090)
ConExConvolutional ComplEx Knowledge Graph EmbeddingsAConExAdditive Convolutional ComplEx Knowledge Graph EmbeddingsComplExBase class for all neural network modules.BaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBase Class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	Pyke	A Physical Embedding Model for Knowledge Graphs
Additive Convolutional ComplEx Knowledge Graph Embeddings ComplEx Base class for all neural network modules. Base class for all neural network modules. Base class for all neural network modules. IdentityClass Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base KGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMult Base class for all neural network modules. OMult Base class for all neural network modules. AConvO Base class for all neural network modules. Additive Convolutional Octonion Knowledge Graph Embeddings	BaseKGE	Base class for all neural network modules.
beddings Complex Base class for all neural network modules. Base class for all neural network modules. Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMULT Base class for all neural network modules. ConvQ Convolutional Quaternion Knowledge Graph Embeddings ACONVQ Additive Convolutional Quaternion Knowledge Graph Embeddings Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMULT Base class for all neural network modules. OMULT Base class for all neural network modules. ACONVO Additive Convolutional Octonion Knowledge Graph Embeddings	ConEx	Convolutional ComplEx Knowledge Graph Embeddings
ComplexBase class for all neural network modules.BaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	AConEx	Additive Convolutional ComplEx Knowledge Graph Em-
BaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings		beddings
IdentityClassBase class for all neural network modules.QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	ComplEx	Base class for all neural network modules.
QMultBase class for all neural network modules.ConvQConvolutional Quaternion Knowledge Graph EmbeddingsAConvQAdditive Convolutional Quaternion Knowledge Graph EmbeddingsBaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	BaseKGE	Base class for all neural network modules.
ConvQ Convolutional Quaternion Knowledge Graph Embeddings AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass OMult Base class for all neural network modules. ConvO Base class for all neural network modules. AConvO Additive Convolutional Octonion Knowledge Graph Embeddings	IdentityClass	Base class for all neural network modules.
AConvQ Additive Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMult Base class for all neural network modules. ConvO Base class for all neural network modules. AConvO Additive Convolutional Octonion Knowledge Graph Embeddings	QMult	Base class for all neural network modules.
Additive Convolutional Quaternion Knowledge Graph Embeddings BaseKGE Base class for all neural network modules. IdentityClass Base class for all neural network modules. OMult Base class for all neural network modules. ConvO Base class for all neural network modules. AconvO Additive Convolutional Octonion Knowledge Graph Embeddings	ConvQ	Convolutional Quaternion Knowledge Graph Embed-
Embeddings Base KGE Base class for all neural network modules. IdentityClass OMult Base class for all neural network modules. Base class for all neural network modules. Base class for all neural network modules. AconvO Additive Convolutional Octonion Knowledge Graph Embeddings		dings
BaseKGEBase class for all neural network modules.IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings	AConvQ	Additive Convolutional Quaternion Knowledge Graph
IdentityClassBase class for all neural network modules.OMultBase class for all neural network modules.ConvOBase class for all neural network modules.AConvOAdditive Convolutional Octonion Knowledge Graph Embeddings		Embeddings
OMult ConvO Base class for all neural network modules. Base class for all neural network modules. AConvO Additive Convolutional Octonion Knowledge Graph Embeddings	BaseKGE	Base class for all neural network modules.
ConvO Base class for all neural network modules. AConvO Additive Convolutional Octonion Knowledge Graph Embeddings	IdentityClass	Base class for all neural network modules.
ACONVO Additive Convolutional Octonion Knowledge Graph Embeddings	OMult	Base class for all neural network modules.
beddings	Conv0	Base class for all neural network modules.
ϵ	AConv0	Additive Convolutional Octonion Knowledge Graph Em-
Base class for all neural network modules.		beddings
	Keci	Base class for all neural network modules.

continues on next page

Table 1 - continued from previous page

	1 0
CKeci	Without learning dimension scaling
DeCaL	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
PykeenKGE	A class for using knowledge graph embedding models implemented in Pykeen
BaseKGE	Base class for all neural network modules.
FMult	Learning Knowledge Neural Graphs
GFMult	Learning Knowledge Neural Graphs
FMult2	Learning Knowledge Neural Graphs
LFMult1	Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
LFMult	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
DualE	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

Functions

```
\begin{array}{ll} \textit{quaternion\_mul}(\rightarrow \text{Tuple[torch.Tensor, torch.Tensor,} & \textit{Perform quaternion multiplication} \\ \textit{...}) \\ \textit{quaternion\_mul\_with\_unit\_norm}(^*, Q_1, Q_2) \\ \\ \textit{octonion\_mul}(^*, O_1, O_2) \\ \\ \textit{octonion\_mul\_norm}(^*, O_1, O_2) \\ \\ \end{array}
```

Package Contents

```
class dicee.models.ADOPT (params: torch.optim.optimizer.ParamsT, lr: float | torch.Tensor = 0.001, betas: Tuple[float, float] = (0.9, 0.9999), eps: float = 1e-06, clip_lambda: Callable[[int], float] | None = lambda step: ..., weight_decay: float = 0.0, decouple: bool = False, *, foreach: bool | None = None, maximize: bool = False, capturable: bool = False, differentiable: bool = False, fused: bool | None = None)
```

 $Bases: \verb|torch.optim.optimizer.Optimizer| \\$

Base class for all optimizers.



Parameters need to be specified as collections that have a deterministic ordering that is consistent between runs. Examples of objects that don't satisfy those properties are sets and iterators over values of dictionaries.

- params (*iterable*) an iterable of torch. Tensor s or dict s. Specifies what Tensors should be optimized.
- **defaults** (dict): a dict containing default values of optimization options (used when a parameter group doesn't specify them).

```
clip_lambda
```

```
__setstate__(state)
```

step(closure=None)

Perform a single optimization step.

Parameters

closure (Callable, optional) - A closure that reevaluates the model and returns the loss

```
class dicee.models.BaseKGELightning(*args, **kwargs)
```

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
training_step_outputs = []
```

```
mem\_of\_model() \rightarrow Dict
```

Size of model in MB and number of params

```
training_step(batch, batch_idx=None)
```

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

- batch The output of your data iterable, normally a DataLoader.
- batch_idx The index of this batch.

• dataloader_idx - The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- Tensor The loss tensor
- dict A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- None In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__ (self):
    super().__init__()
    self.automatic_optimization = False

# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

# do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

1 Note

When accumulate_grad_batches > 1, the loss returned here will be automatically normalized by accumulate_grad_batches internally.

loss_function(yhat_batch: torch.FloatTensor, y_batch: torch.FloatTensor)

- yhat_batch
- y_batch

```
on_train_epoch_end(*args, **kwargs)
```

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the LightningModule and access them in this hook:

```
class MyLightningModule(L.LightningModule):
   def __init__(self):
        super().__init__()
        self.training_step_outputs = []
   def training_step(self):
        loss = ...
        self.training_step_outputs.append(loss)
        return loss
   def on_train_epoch_end(self):
        # do something with all training_step outputs, for example:
        epoch_mean = torch.stack(self.training_step_outputs).mean()
        self.log("training_epoch_mean", epoch_mean)
        # free up the memory
        self.training_step_outputs.clear()
```

test_epoch_end(outputs: List[Any])

test dataloader() \rightarrow None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in prepare_data()
- process and split in setup()

However, the above are only necessary for distributed processing.

Warning

do not assign state in prepare_data

- test()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

1 Note

If you don't need a test dataset and a test_step(), you don't need to implement this method.

$val_dataloader() \rightarrow None$

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:**~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs` to a positive integer.

It's recommended that all data downloads and preparation happen in prepare_data().

- fit()
- validate()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

1 Note

If you don't need a validation dataset and a validation_step(), you don't need to implement this method.

$predict_dataloader() \rightarrow None$

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in prepare_data().

- predict()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Returns

A torch.utils.data.DataLoader or a sequence of them specifying prediction samples.

$train_dataloader() \rightarrow None$

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

dataloader will be reloaded you return not unless you set :paramref: `~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs` to a positive integer.

For data processing use the following pattern:

- download in prepare_data()
- process and split in setup()

However, the above are only necessary for distributed processing.



🛕 Warning

do not assign state in prepare_data

- fit()
- prepare_data()
- setup()



1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

configure_optimizers (parameters=None)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- · Single optimizer.
- List or Tuple of optimizers.
- Two lists The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple lr_scheduler_config).
- Dictionary, with an "optimizer" key, and (optionally) a "lr_scheduler" key whose value is a single LR scheduler or lr_scheduler_config.
- None Fit will run without any optimizer.

The lr_scheduler_config is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
   "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
   "interval": "epoch",
   # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
   "frequency": 1,
    # Metric to monitor for schedulers like `ReduceLROnPlateau`
   "monitor": "val_loss",
   # If set to `True`, will enforce that the value specified 'monitor'
    # is available when the scheduler is updated, thus stopping
    # training if not found. If set to `False`, it will only produce a warning
   "strict": True,
    # If using the `LearningRateMonitor` callback to monitor the
    # learning rate progress, this keyword can be used to specify
    # a custom logged name
    "name": None,
```

When there are schedulers in which the .step() method is conditioned on a value, such as the torch.optim.lr_scheduler.ReduceLROnPlateau scheduler, Lightning requires that the lr_scheduler_config contains the keyword "monitor" set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using self.log('metric_to_track', metric_val) in your LightningModule.

1 Note

Some things to know:

- Lightning calls .backward() and .step() automatically in case of automatic optimization.
- If a learning rate scheduler is specified in <code>configure_optimizers()</code> with key "interval" (default "epoch") in the scheduler configuration, Lightning will call the scheduler's <code>.step()</code> method automatically in case of automatic optimization.
- If you use 16-bit precision (precision=16), Lightning will automatically handle the optimizer.
- If you use torch.optim.LBFGS, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the optimizer_step() hook.

class dicee.models.BaseKGE(args: dict)

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
```

```
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
            x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
     byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
           y_idx: torch.LongTensor = None)
        Parameters
            • x
            • y_idx
            • ordered_bpe_entities
\textbf{forward\_triples}~(\textit{x:torch.LongTensor})~\rightarrow torch.Tensor
        Parameters
forward_k_vs_all(*args, **kwargs)
forward_k_vs_sample(*args, **kwargs)
{\tt get\_triple\_representation}\,(idx\_hrt)
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an <u>__init__()</u> call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
args = None
__call__(x)
```

```
static forward (x)
```

```
class dicee.models.BaseKGE (args: dict)
    Bases: BaseKGELightning
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

args

```
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
```

```
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
           x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
forward(x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
           y_idx: torch.LongTensor = None
        Parameters
            • x
            • y_idx
            • ordered_bpe_entities
```

```
forward_triples (x: torch.LongTensor) \rightarrow torch.Tensor
              Parameters
     forward_k_vs_all(*args, **kwargs)
     forward_k_vs_sample(*args, **kwargs)
     get_triple_representation(idx_hrt)
     get_head_relation_representation(indexed_triple)
     get_sentence_representation(x: torch.LongTensor)
              Parameters
                  • (b (x shape)
                  • 3
                  • t)
     get_bpe_head_and_relation_representation (x: torch.LongTensor)
                  → Tuple[torch.FloatTensor, torch.FloatTensor]
              Parameters
                  x (B x 2 x T)
     \mathtt{get\_embeddings}() \rightarrow Tuple[numpy.ndarray, numpy.ndarray]
class dicee.models.DistMult (args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575
     name = 'DistMult'
     k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor, emb_E: torch.FloatTensor)
              Parameters
                  • emb_h
                  emb_r
                  emb_E
     forward_k_vs_all (x: torch.LongTensor)
     forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)
     score (h, r, t)
class dicee.models.TransE(args)
     Bases: dicee.models.base_model.BaseKGE
     Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/
     1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf
     name = 'TransE'
```

```
margin = 4
     score (head_ent_emb, rel_ent_emb, tail_ent_emb)
     forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
class dicee.models.Shallom(args)
     Bases: dicee.models.base_model.BaseKGE
     A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
     name = 'Shallom'
     shallom
     get_embeddings() → Tuple[numpy.ndarray, None]
     forward_k_vs_all(x) \rightarrow torch.FloatTensor
     forward_triples (x) \rightarrow \text{torch.FloatTensor}
              Parameters
                  x
              Returns
class dicee.models.Pyke(args)
     Bases: dicee.models.base_model.BaseKGE
     A Physical Embedding Model for Knowledge Graphs
     name = 'Pyke'
     dist_func
     margin = 1.0
     forward_triples (x: torch.LongTensor)
              Parameters
class dicee.models.BaseKGE (args: dict)
     Bases: BaseKGELightning
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
```

```
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
            x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
           y_idx: torch.LongTensor = None
        Parameters
            • x
            • y_idx
            • ordered_bpe_entities
forward\_triples(x: torch.LongTensor) \rightarrow torch.Tensor
        Parameters
forward_k_vs_all(*args, **kwargs)
forward_k_vs_sample(*args, **kwargs)
get\_triple\_representation(idx\_hrt)
get_head_relation_representation(indexed_triple)
get_sentence_representation(x: torch.LongTensor)
        Parameters
            • (b(x shape)
            • 3
            • t)
```

```
get_bpe_head_and_relation_representation(x: torch.LongTensor)
                  → Tuple[torch.FloatTensor, torch.FloatTensor]
               Parameters
                  x (B x 2 x T)
     \mathtt{get\_embeddings}() \rightarrow Tuple[numpy.ndarray, numpy.ndarray]
class dicee.models.ConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Convolutional ComplEx Knowledge Graph Embeddings
     name = 'ConEx'
     conv2d
     fc_num_input
     fc1
     norm_fc1
     bn_conv2d
     feature_map_dropout
     residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],
                 C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
          Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
          that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
          complex-valued embeddings :return:
     forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
     forward\_triples(x: torch.Tensor) \rightarrow torch.FloatTensor
               Parameters
     forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)
class dicee.models.AConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional ComplEx Knowledge Graph Embeddings
     name = 'AConEx'
     conv2d
     fc_num_input
     fc1
     norm_fc1
     bn conv2d
     feature_map_dropout
```

```
residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor],

C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
```

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

```
\label{eq:continuous_continuous} \textbf{forward_k\_vs\_all} \ (x: torch.Tensor) \ \to \ torch.FloatTensor \\ \textbf{forward\_triples} \ (x: torch.Tensor) \ \to \ torch.FloatTensor \\
```

Parameters

x

forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)

```
class dicee.models.ComplEx (args)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

Parameters

- emb h
- emb_r
- emb_E

 $forward_k_vs_all(x: torch.LongTensor) \rightarrow torch.FloatTensor$

forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)

```
dicee.models.quaternion_mul(*,Q_1,Q_2)
```

→ Tuple[torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor]

Perform quaternion multiplication :param Q_1: :param Q_2: :return:

```
class dicee.models.BaseKGE (args: dict)
```

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

args

```
embedding_dim = None
num_entities = None
num_relations = None
```

```
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
           x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
```

```
forward (x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
                 y idx: torch.LongTensor = None)
              Parameters
                  • x
                   y_idx
                   • ordered_bpe_entities
     \texttt{forward\_triples} \ (x: torch.LongTensor) \ \to torch.Tensor
              Parameters
     forward_k_vs_all(*args, **kwargs)
     forward_k_vs_sample(*args, **kwargs)
     get_triple_representation(idx_hrt)
     get_head_relation_representation(indexed_triple)
     get_sentence_representation(x: torch.LongTensor)
              Parameters
                   • (b (x shape)
                  • 3
                   • t)
     get_bpe_head_and_relation_representation(x: torch.LongTensor)
                  → Tuple[torch.FloatTensor, torch.FloatTensor]
              Parameters
                  x (B x 2 x T)
     get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]
class dicee.models.IdentityClass(args=None)
     Bases: torch.nn.Module
     Base class for all neural network modules.
     Your models should also subclass this class.
     Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-
     modules as regular attributes:
```

init_params_with_sanity_checking()

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args = None
__call__(x)
static forward(x)

dicee.models.quaternion_mul_with_unit_norm(*, Q_1, Q_2)

class dicee.models.QMult(args)

Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an $__{init}_{_}()$ call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

name = 'QMult'

explicit = True

 $quaternion_multiplication_followed_by_inner_product(h, r, t)$

Parameters

- h shape: (*batch_dims, dim) The head representations.
- **r** shape: (*batch_dims, dim) The head representations.
- t shape: (*batch_dims, dim) The tail representations.

Returns

Triple scores.

 $static quaternion_normalizer(x: torch.FloatTensor) \rightarrow torch.FloatTensor$

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a+bi+cj+dk| = \sqrt{a^2+b^2+c^2+d^2}$$

L2 norm of quaternion vector:

$$||x||^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i \cdot re^2 + x_i \cdot im_1^2 + x_i \cdot im_2^2 + x_i \cdot im_3^2)$$

Parameters

 \mathbf{x} – The vector.

Returns

The normalized vector.

k_vs_all_score (bpe_head_ent_emb, bpe_rel_ent_emb, E)

Parameters

- bpe_head_ent_emb
- bpe_rel_ent_emb
- E

forward_k_vs_all(X)

Parameters

x

forward_k_vs_sample (x, target_entity_idx)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

```
class dicee.models.ConvQ(args)
     Bases: dicee.models.base_model.BaseKGE
     Convolutional Quaternion Knowledge Graph Embeddings
     name = 'ConvQ'
     entity_embeddings
     relation embeddings
     conv2d
     fc_num_input
     fc1
     bn_conv1
     bn_conv2
     feature_map_dropout
     \verb"residual_convolution" (Q\_1, Q\_2)
     forward\_triples (indexed\_triple: torch.Tensor) \rightarrow torch.Tensor
              Parameters
     forward_k_vs_all (x: torch.Tensor)
          Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
          [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
          Entities()
class dicee.models.AConvQ(args)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional Quaternion Knowledge Graph Embeddings
     name = 'AConvQ'
     entity_embeddings
     relation_embeddings
     conv2d
     fc_num_input
     fc1
     bn_conv1
     bn_conv2
     feature_map_dropout
     residual\_convolution(Q_1, Q_2)
```

forward_triples (*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters

x

```
forward_k_vs_all (x: torch.Tensor)
```

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.BaseKGE (args: dict)

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

args

```
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning rate = None
```

```
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
       Parameters
           x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
```

```
forward(x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
            y_idx: torch.LongTensor = None)
         Parameters
             • x
             • y_idx
             • ordered_bpe_entities
forward\_triples(x: torch.LongTensor) \rightarrow torch.Tensor
         Parameters
forward_k_vs_all(*args, **kwargs)
forward_k_vs_sample(*args, **kwargs)
get_triple_representation(idx_hrt)
get_head_relation_representation(indexed_triple)
get_sentence_representation(x: torch.LongTensor)
         Parameters
             • (b (x shape)
             • 3
             • t)
get_bpe_head_and_relation_representation(x: torch.LongTensor)
            \rightarrow Tuple[torch.FloatTensor, torch.FloatTensor]
```

Parameters

x (B x 2 x T)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.IdentityClass(args=None)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F
class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
    def forward(self, x):
```

(continues on next page)

(continued from previous page)

```
x = F.relu(self.conv1(x))
return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an <u>__init__</u>() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
args = None
__call__(x)
static forward(x)

dicee.models.octonion_mul(*, O_1, O_2)

dicee.models.octonion_mul_norm(*, O_1, O_2)

class dicee.models.OMult(args)

Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

```
class dicee.models.ConvO(args: dict)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
name = 'ConvO'
conv2d
```

```
fc_num_input
     fc1
     bn_conv2d
     norm_fc1
     feature_map_dropout
     static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                  emb_rel_e5, emb_rel_e6, emb_rel_e7)
     residual\_convolution(O\_1, O\_2)
     forward\_triples(x: torch.Tensor) \rightarrow torch.Tensor
               Parameters
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities()
class dicee.models.AConvO(args: dict)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional Octonion Knowledge Graph Embeddings
     name = 'AConvO'
     conv2d
     fc_num_input
     fc1
     bn_conv2d
     norm_fc1
     feature_map_dropout
     static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                  emb_rel_e5, emb_rel_e6, emb_rel_e7)
     residual_convolution (O_1, O_2)
     forward_triples (x: torch.Tensor) \rightarrow torch.Tensor
               Parameters
                   x
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities l)
```

```
class dicee.models.Keci(args)
Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an <u>__init___()</u> call to the parent class must be made before assignment on the child.

Variables

training $(b \circ \circ 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
name = 'Keci'
p
q
r
requires_grad_for_interactions = True
compute_sigma_pp (hp, rp)
   Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k
   sigma_{pp} = satures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops
   results = [] for i in range(p - 1):
        for k in range(i + 1, p):
            results.append(hp[:, :, i] * rp[:, :, k] * rp[:, :, i])
        sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))
```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

```
e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
```

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

```
compute\_sigma\_qq(hq, rq)
```

Compute $sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q}$ captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

```
results = [] for j in range(q - 1):
```

for k in range(j + 1, q):

```
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])
```

```
sigma_q = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))
```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

```
e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
```

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

```
compute_sigma_pq(*, hp, hq, rp, rq)
```

```
sum \{i=1\}^{p} sum \{j=p+1\}^{p+q} (h ir j-h jr i) e ie j
```

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

apply_coefficients(hp, hq, rp, rq)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (h0, hp, hq, r0, rp, rq)

Compute our CL multiplication

```
 h = h_0 + sum_{i=1}^p h_i e_i + sum_{j=p+1}^p h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^p h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^p h_j e_j r = r_0 + sum_{i=1}^p h_j e_j r = r_0 + sum_{i=1}^p h_j e_i + sum_{i=1}^p h_j e_j r = r_0 + sum_{i=1}^p h_j e_j
```

ei
$$^2 = +1$$
 for i =< i =< p ej $^2 = -1$ for p < j =< p+q ei ej = -eje1 for i

eq j

 $h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q} + sig$

- (1) $sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i sum_{j=p+1}^{p+q} (h_j r_j) e_j$
- (2) $sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$
- (3) $sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$
- (4) $sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k h_k r_i) e_i e_k$
- (5) $sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k h_k r_j) e_j e_k$
- (6) $sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j h_j r_i) e_i e_j$

$\verb"construct_cl_multivector"\,(x:\,torch.FloatTensor,\,r:\,int,\,p:\,int,\,q:\,int)$

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{p,q}(mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor with (n,r) shape)
- **ap** (torch.FloatTensor with (n,r,p) shape)
- aq (torch.FloatTensor with (n,r,q) shape)

forward_k_vs_with_explicit (x: torch.Tensor)

k_vs_all_score (bpe_head_ent_emb, bpe_rel_ent_emb, E)

 $\texttt{forward_k_vs_all} \ (x: torch.Tensor) \ \rightarrow \text{torch.FloatTensor}$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations mathbb $\{R\}^d$.
- (2) Construct head entity and relation embeddings according to $Cl_{p,q}(mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter — x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n,|E|) shape

construct_batch_selected_cl_multivector(x: torch.FloatTensor, r: int, p: int, q: int)

 $\rightarrow tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]$

Construct a batch of batchs multivectors $Cl_{p,q}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (torch.FloatTensor with (n,k, m) shape)
- **ap** (torch.FloatTensor with (n,k, m, p) shape)
- **aq** (torch.FloatTensor with (n,k, m, q) shape)

 $\textbf{forward_k_vs_sample} \ (x: torch.LongTensor, target_entity_idx: torch.LongTensor) \ \rightarrow \\ \textbf{torch.FloatTensor}$

Parameter

x: torch.LongTensor with (n,2) shape

target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.

rtype

torch.FloatTensor with (n, k) shape

 $\mathtt{score}\,(h,r,t)$

 $forward_triples$ (x: torch.Tensor) \rightarrow torch.FloatTensor

Parameter

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'DeCaL'
entity_embeddings
relation_embeddings
p
```

q

r

re

forward_triples (x: torch.Tensor) \rightarrow torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl pqr (a: torch.tensor) \rightarrow torch.tensor

Input: tensor(batch_size, emb_dim) \longrightarrow output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (list_h_emb, list_r_emb, list_t_emb)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^p h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^q (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r}$$

and return:

$$sigma_0t = \sigma_0 \cdot t_0 = s0 + s1 - s2s3, s4ands5$$

compute_sigmas_multivect(list_h_emb, list_r_emb)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j'=p+1}^{p+q} \sum_{j'=j+1}^{p+q} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j'=p+1}^{p+q} \sum_{j'=j+1}^{p+q} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j'=p+1}^{p+q} \sum_{j'=j+1}^{p+q} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j'=p+1}^{p+q} \sum_{j'=j+1}^{p+q} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j'=p+1}^{p+q} \sum_{j'=j+1}^{p+q} (h_j r_j - h_{i'} r_j) (models the interactions between e_i and e_i' for 1 <= i, i' <=$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_j - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= j <= p + q) \sigma_p r = \sum_{i=1}^p (h_i r_i - h_j r_i) (interactions n between e_i and e_j for 1 <= i <= p and p + 1 <= p and p + 1 <= p and p an$$

 $forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to Cl {p,q, r}(mathbb{R}^d).
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter — x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

 $\verb"apply_coefficients" (h0, hp, hq, hk, r0, rp, rq, rk)$

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (x: torch.FloatTensor, re: int, p: int, q: int, r: int)

 \rightarrow tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{p,q,r}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor)
- **ap** (torch.FloatTensor)
- aq (torch.FloatTensor)
- **ar** (torch.FloatTensor)

 $compute_sigma_pp(hp, rp)$

Compute .. math:

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

```
results = [] for i in range(p - 1):
```

for k in range(i + 1, p):

```
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])
```

```
sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))
```

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

 $compute_sigma_qq(hq, rq)$

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) Eq.16$$

sigma $_{q}$ captures the interactions between along q bases For instance, let q e $_{1}$, e $_{2}$, e $_{3}$, we compute interactions between e $_{1}$ e $_{2}$, e $_{1}$ e $_{3}$, and e $_{2}$ e $_{3}$ This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

results.append(hq[:, :,
$$i$$
] * rq[:, :, k] - hq[:, :, k] * rq[:, :, i])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

 $compute_sigma_rr(hk, rk)$

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^{p} (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq(*, hp, hq, rp, rq)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

compute_sigma_pr(*, hp, hk, rp, rk)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

 $results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):$

for j in range(q):

$$sigma_pq[:,:,i,j] = hp[:,:,i] * rq[:,:,j] - hq[:,:,j] * rp[:,:,i]$$

print(sigma_pq.shape)

compute_sigma_qr(*, hq, hk, rq, rk)

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

class dicee.models.BaseKGE (args: dict)

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an $__{init}$ __() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

args

```
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
```

```
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
            x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
forward(x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
           y_idx: torch.LongTensor = None)
        Parameters
            • x
            • y_idx
            • ordered_bpe_entities
forward\_triples(x: torch.LongTensor) \rightarrow torch.Tensor
        Parameters
forward_k_vs_all(*args, **kwargs)
forward_k_vs_sample(*args, **kwargs)
get_triple_representation(idx_hrt)
{\tt get\_head\_relation\_representation}\ (indexed\_triple)
```

```
get_sentence_representation(x: torch.LongTensor)
               Parameters
                   • (b (x shape)
                   • 3
                   • t)
     get bpe head and relation representation(x: torch.LongTensor)
                  → Tuple[torch.FloatTensor, torch.FloatTensor]
               Parameters
                  x (B x 2 x T)
     get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]
class dicee.models.PykeenKGE(args: dict)
     Bases: dicee.models.base_model.BaseKGE
     A class for using knowledge graph embedding models implemented in Pykeen
     Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Py-
     keen_HolE: Pykeen_TransD: Pykeen_TransE: Pykeen_TransF: Pykeen_TransH: Pykeen_TransR:
     model_kwargs
     name
     model
     loss_history = []
     args
     entity_embeddings = None
     relation_embeddings = None
     forward_k_vs_all (x: torch.LongTensor)
          # => Explicit version by this we can apply bn and dropout
          # (1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r =
          self.get_head_relation_representation(x) \# (2) Reshape (1). if self.last_dim > 0:
               h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim,
               self.last_dim)
          \# (3) Reshape all entities. if self.last dim > 0:
               t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)
          else:
               t = self.entity_embeddings.weight
          # (4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r,
          all_entities=t, slice_size=1)
```

```
forward_triples (x: torch.LongTensor) \rightarrow torch.FloatTensor
```

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t = self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

```
h = h.reshape(len(x), self.embedding\_dim, self.last\_dim) r = r.reshape(len(x), self.embedding\_dim, self.last\_dim) t = t.reshape(len(x), self.embedding\_dim, self.last\_dim)
```

(3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice size=None, slice dim=0)

abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)

```
class dicee.models.BaseKGE (args: dict)
    Bases: BaseKGELightning
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
args
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
```

```
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
        Parameters
           x (B x 2 x T)
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
    byte pair encoded neural link predictors
        Parameters
init_params_with_sanity_checking()
```

```
y_idx: torch.LongTensor = None)
              Parameters
                  • x
                  • y_idx
                  • ordered_bpe_entities
     forward\_triples(x: torch.LongTensor) \rightarrow torch.Tensor
              Parameters
     forward_k_vs_all(*args, **kwargs)
     forward_k_vs_sample(*args, **kwargs)
     get_triple_representation(idx_hrt)
     get_head_relation_representation(indexed_triple)
     get_sentence_representation(x: torch.LongTensor)
              Parameters
                  • (b (x shape)
                  • 3
                  • t)
     get_bpe_head_and_relation_representation(x: torch.LongTensor)
                 → Tuple[torch.FloatTensor, torch.FloatTensor]
              Parameters
                 x (B x 2 x T)
     \verb"get_embeddings"() \rightarrow Tuple[numpy.ndarray, numpy.ndarray]
class dicee.models.FMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Learning Knowledge Neural Graphs
     name = 'FMult'
     entity_embeddings
     relation_embeddings
     num_sample = 50
     gamma
     roots
     weights
```

forward(x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],

```
compute\_func(weights: torch.FloatTensor, x) \rightarrow torch.FloatTensor
     chain_func (weights, x: torch.FloatTensor)
     \textbf{forward\_triples} (\textit{idx\_triple: torch.Tensor}) \rightarrow \text{torch.Tensor}) \rightarrow \text{torch.Tensor}
               Parameters
                   x
class dicee.models.GFMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Learning Knowledge Neural Graphs
     name = 'GFMult'
     entity_embeddings
     relation_embeddings
     k
     num_sample = 250
     roots
     weights
     compute\_func(weights: torch.FloatTensor, x) \rightarrow torch.FloatTensor
     chain_func (weights, x: torch.FloatTensor)
     forward\_triples(idx\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
class dicee.models.FMult2(args)
     Bases: dicee.models.base_model.BaseKGE
     Learning Knowledge Neural Graphs
     name = 'FMult2'
     n_{ayers} = 3
     n = 50
     score_func = 'compositional'
     discrete_points
     entity_embeddings
     relation_embeddings
     build_func(Vec)
     build_chain_funcs(list_Vec)
```

```
compute_func (W, b, x) \rightarrow \text{torch.FloatTensor}
     function(list_W, list_b)
     trapezoid(list_W, list_b)
     forward_triples (idx\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
                   x
class dicee.models.LFMult1(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
     f(x) = sum_{k=0}^{k=0}^{k=d-1}wk e^{kix}, and use the three differents scoring function as in the paper to evaluate
     the score
     name = 'LFMult1'
     entity_embeddings
     relation_embeddings
     forward_triples (idx_triple)
               Parameters
     tri_score(h, r, t)
     \mathtt{vtp\_score}(h, r, t)
class dicee.models.LFMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) =
     sum_{i=0}^{d-1} a_k x^{i\%d} and use the three differents scoring function as in the paper to evaluate the score.
     We also consider combining with Neural Networks.
     name = 'LFMult'
     entity_embeddings
     relation_embeddings
     degree
     m
     x_values
     forward_triples (idx_triple)
               Parameters
                   x
     construct_multi_coeff(x)
```

```
poly_NN(x, coefh, coefr, coeft)
```

Constructing a 2 layers NN to represent the embeddings. $h = sigma(wh^T x + bh)$, $r = sigma(wr^T x + br)$, $t = sigma(wt^T x + bt)$

linear (x, w, b)

$scalar_batch_NN(a, b, c)$

element wise multiplication between a,b and c: Inputs : a, b, c ====> torch.tensor of size batch_size x m x d Output : a tensor of size batch_size x d

tri_score (coeff_h, coeff_r, coeff_t)

this part implement the trilinear scoring techniques:

```
score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k} = 0 \\  ^{d-1} dfrac{a_i*b_j*c_k}{1+(i+j+k)\%d}
```

- 1. generate the range for i, j and k from [0 d-1]
- 2. perform $dfrac\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\}$ in parallel for every batch
- 3. take the sum over each batch

$\mathtt{vtp_score}\,(h,r,t)$

this part implement the vector triple product scoring techniques:

```
score(h,r,t) = int_{0}{1} \quad h(x)r(x)t(x) \quad dx = sum_{i,j,k} = 0^{d-1} \quad dfrac_{a_i*c_j*b_k} - b_i*c_j*a_k}{(1+(i+j)\%d)(1+k)}
```

- 1. generate the range for i,j and k from [0 d-1]
- 2. Compute the first and second terms of the sum
- 3. Multiply with then denominator and take the sum
- 4. take the sum over each batch

```
\mathtt{comp\_func}\,(h,\,r,\,t)
```

this part implement the function composition scoring techniques: i.e. score = <hor, t>

```
polynomial(coeff, x, degree)
```

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,...d] and return a vector tensor (coeff $[0][0] + \text{coeff}[0][1]x + ... + \text{coeff}[0][d]x^d$,

$$coeff[1][0] + coeff[1][1]x + ... + coeff[1][d]x^d$$

pop (coeff, x, degree)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,...d]

```
and return a tensor (coeff[0][0] + coeff[0][1]x + ... + coeff[0][d]x^d, coeff[1][0] + coeff[1][1]x + ... + coeff[1][d]x^d
```

```
class dicee.models.DualE(args)
```

Bases: dicee.models.base_model.BaseKGE

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

```
relation_embeddings
num_ent = None
{\tt kvsall\_score}\,(e\_1\_h,e\_2\_h,e\_3\_h,e\_4\_h,e\_5\_h,e\_6\_h,e\_7\_h,e\_8\_h,e\_1\_t,e\_2\_t,e\_3\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e\_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_t,e_4\_
                                                          e_5_t, e_6_t, e_7_t, e_8_t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) \rightarrow \text{torch.tensor}
                        KvsAll scoring function
                        Input
                        x: torch.LongTensor with (n, ) shape
                        Output
                        torch.FloatTensor with (n) shape
forward\_triples(idx\_triple: torch.tensor) \rightarrow torch.tensor
                        Negative Sampling forward pass:
                        Input
                        x: torch.LongTensor with (n, ) shape
                        Output
                        torch.FloatTensor with (n) shape
forward_k_vs_all(x)
                        KvsAll forward pass
                        Input
                        x: torch.LongTensor with (n, ) shape
                        Output
                        torch.FloatTensor with (n) shape
T (x: torch.tensor) \rightarrow torch.tensor
                        Transpose function
                        Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)
```

dicee.query_generator

Classes

QueryGenerator

Module Contents

```
class dicee.query_generator.QueryGenerator(train_path, val_path: str, test_path: str,
             ent2id: Dict = None, rel2id: Dict = None, seed: int = 1, gen_valid: bool = False,
             gen\_test: bool = True)
      train_path
      val_path
      test_path
      gen_valid = False
      gen_test = True
      seed = 1
      max_ans_num = 1000000.0
      mode
      ent2id = None
      rel2id: Dict = None
      ent_in: Dict
      ent_out: Dict
      query_name_to_struct
      list2tuple(list_data)
      tuple2list(x: List | Tuple) \rightarrow List | Tuple
           Convert a nested tuple to a nested list.
      set_global_seed (seed: int)
           Set seed
      construct\_graph(paths: List[str]) \rightarrow Tuple[Dict, Dict]
           Construct graph from triples Returns dicts with incoming and outgoing edges
      fill_query(query\_structure: List[str | List], ent_in: Dict, ent_out: Dict, answer: int) \rightarrow bool
           Private method for fill_query logic.
      achieve\_answer(query: List[str | List], ent\_in: Dict, ent\_out: Dict) \rightarrow set
           Private method for achieve_answer logic. @TODO: Document the code
      write_links (ent_out, small_ent_out)
      ground_queries (query_structure: List[str | List], ent_in: Dict, ent_out: Dict, small_ent_in: Dict,
                   small_ent_out: Dict, gen_num: int, query_name: str)
           Generating queries and achieving answers
      unmap (query_type, queries, tp_answers, fp_answers, fn_answers)
      unmap_query (query_structure, query, id2ent, id2rel)
```

```
passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting queries and answers in return @ TODO: create a class for each single query struct

save_queries (query_type: str, gen_num: int, save_path: str)

abstract load_queries (path)

get_queries (query_type: str, gen_num: int)

static save_queries_and_answers (path: str, data: List[Tuple[str, Tuple[collections.defaultdict]]])

→ None

Save Queries into Disk

static load_queries_and_answers (path: str) → List[Tuple[str, Tuple[collections.defaultdict]]]]

Load Queries from Disk to Memory

dicee.read_preprocess_save_load_kg

Submodules

dicee.read_preprocess_save_load_kg.preprocess

Classes
```

PreprocessKG

Preprocess the data in memory

Module Contents

```
class dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG(kg)

Preprocess the data in memory

kg

start() → None

Preprocess train, valid and test datasets stored in knowledge graph instance

Parameter

rtype

None

preprocess_with_byte_pair_encoding()

preprocess_with_byte_pair_encoding_with_padding() → None

preprocess_with_pandas() → None

Preprocess train, valid and test datasets stored in knowledge graph instance with pandas

(1) Add recipriocal or noisy triples
```

(3) Index datasets

Parameter

rtype

None

```
{\tt preprocess\_with\_polars}\,()\,\to None
```

 $\verb"sequential_vocabulary_construction"\,(\,)\,\to None$

- (1) Read input data into memory
- (2) Remove triples with a condition
- (3) Serialize vocabularies in a pandas dataframe where

=> the index is integer and => a single column is string (e.g. URI)

dicee.read_preprocess_save_load_kg.read_from_disk

Classes

ReadFromDisk

Read the data from disk into memory

Module Contents

```
\verb|class| dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk| (kg) |
```

Read the data from disk into memory

kg

 $\mathtt{start}() \to None$

Read a knowledge graph from disk into memory

Data will be available at the train_set, test_set, valid_set attributes.

Parameter

None

rtype

None

add_noisy_triples_into_training()

dicee.read_preprocess_save_load_kg.save_load_disk

Classes

LoadSaveToDisk

Module Contents

```
class dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk(kg)
    kg
    save()
    load()
```

dicee.read_preprocess_save_load_kg.util

Functions

polars_dataframe_indexer(→ polars.DataFrame)	Replaces 'subject', 'relation', and 'object' columns in the input Polars DataFrame with their corresponding index values
<pre>pandas_dataframe_indexer(→ pandas.DataFrame)</pre>	Replaces 'subject', 'relation', and 'object' columns in the input Pandas DataFrame with their corresponding index values
<pre>apply_reciprical_or_noise(add_reciprical, eval_model)</pre>	
timeit(func)	
read_with_polars(→ polars.DataFrame)	Load and Preprocess via Polars
<pre>read_with_pandas(data_path[, read_only_few,])</pre>	
$read_from_disk(\rightarrow Tuple[polars.DataFrame, pan-$	
das.DataFrame])	
<pre>read_from_triple_store([endpoint])</pre>	Read triples from triple store into pandas dataframe
<pre>get_er_vocab(data[, file_path])</pre>	
<pre>get_re_vocab(data[, file_path])</pre>	
<pre>get_ee_vocab(data[, file_path])</pre>	
<pre>create_constraints(triples[, file_path])</pre>	
$load_with_pandas(\rightarrow None)$	Deserialize data
<pre>save_numpy_ndarray(*, data, file_path)</pre>	
<pre>load_numpy_ndarray(*, file_path)</pre>	
<pre>save_pickle(*, data[, file_path])</pre>	
load_pickle(*[, file_path])	
create_recipriocal_triples(x)	Add inverse triples into dask dataframe
$dataset_sanity_checking(\rightarrow None)$	

Module Contents

Replaces 'subject', 'relation', and 'object' columns in the input Polars DataFrame with their corresponding index values from the entity and relation index DataFrames.

This function processes the DataFrame in three main steps: 1. Replace the 'relation' values with the corresponding index from *idx_relation*. 2. Replace the 'subject' values with the corresponding index from *idx_entity*. 3. Replace the 'object' values with the corresponding index from *idx_entity*.

Parameters:

df_polars

[polars.DataFrame] The input Polars DataFrame containing columns: 'subject', 'relation', and 'object'.

idx entity

[polars.DataFrame] A Polars DataFrame that contains the mapping between entity names and their corresponding indices. Must have columns: 'entity' and 'index'.

idx relation

[polars.DataFrame] A Polars DataFrame that contains the mapping between relation names and their corresponding indices. Must have columns: 'relation' and 'index'.

Returns:

polars.DataFrame

A DataFrame with the 'subject', 'relation', and 'object' columns replaced by their corresponding indices.

Example Usage:

```
>>> df_polars = pl.DataFrame({
        "subject": ["Alice", "Bob", "Charlie"],
        "relation": ["knows", "works_with", "lives_in"],
        "object": ["Dave", "Eve", "Frank"]
})
>>> idx_entity = pl.DataFrame({
        "entity": ["Alice", "Bob", "Charlie", "Dave", "Eve", "Frank"],
        "index": [0, 1, 2, 3, 4, 5]
})
>>> idx_relation = pl.DataFrame({
        "relation": ["knows", "works_with", "lives_in"],
        "index": [0, 1, 2]
})
>>> polars_dataframe_indexer(df_polars, idx_entity, idx_relation)
```

Steps:

- 1. Join the input DataFrame *df_polars* on the 'relation' column with *idx_relation* to replace the relations with their indices.
- 2. Join on 'subject' to replace it with the corresponding entity index using a left join on idx_entity.
- 3. Join on 'object' to replace it with the corresponding entity index using a left join on idx_entity.

4. Select only the 'subject', 'relation', and 'object' columns to return the final result.

```
dicee.read_preprocess_save_load_kg.util.pandas_dataframe_indexer( df_pandas: pandas.DataFrame, idx_entity: pandas.DataFrame, idx_relation: pandas.DataFrame) <math>\rightarrow pandas.DataFrame
```

Replaces 'subject', 'relation', and 'object' columns in the input Pandas DataFrame with their corresponding index values from the entity and relation index DataFrames.

Parameters:

df pandas

[pd.DataFrame] The input Pandas DataFrame containing columns: 'subject', 'relation', and 'object'.

idx_entity

[pd.DataFrame] A Pandas DataFrame that contains the mapping between entity names and their corresponding indices. Must have columns: 'entity' and 'index'.

idx_relation

[pd.DataFrame] A Pandas DataFrame that contains the mapping between relation names and their corresponding indices. Must have columns: 'relation' and 'index'.

Returns:

pd.DataFrame

A DataFrame with the 'subject', 'relation', and 'object' columns replaced by their corresponding indices.

```
dicee.read_preprocess_save_load_kg.util.apply_reciprical_or_noise(add_reciprical: bool, eval model: str, df: object = None, info: str = None)
```

(1) Add reciprocal triples (2) Add noisy triples

Load and Preprocess via Polars

```
dicee.read_preprocess_save_load_kg.util.get_er_vocab(data, file_path: str = None)
dicee.read_preprocess_save_load_kg.util.get_re_vocab(data, file_path: str = None)
dicee.read_preprocess_save_load_kg.util.get_ee_vocab(data, file_path: str = None)
dicee.read_preprocess_save_load_kg.util.create_constraints(triples, file_path: str = None)
```

(1) Extract domains and ranges of relations

(2) Store a mapping from relations to entities that are outside of the domain and range. Crete constrainted entities based on the range of relations :param triples: :return: Tuple[dict, dict]

```
\verb|dicee.read_preprocess_save_load_kg.util.load_with_pandas| (self) \rightarrow None
     Deserialize data
dicee.read_preprocess_save_load_kg.util.save_numpy_ndarray(*, data: numpy.ndarray,
           file_path: str)
dicee.read_preprocess_save_load_kg.util.load_numpy_ndarray(*, file_path: str)
dicee.read_preprocess_save_load_kg.util.save_pickle(*, data: object, file_path=str)
dicee.read_preprocess_save_load_kq.util.load_pickle(*, file path=str)
dicee.read_preprocess_save_load_kg.util.create_recipriocal_triples(X)
     Add inverse triples into dask dataframe :param x: :return:
dicee.read_preprocess_save_load_kg.util.dataset_sanity_checking(
           train\_set: numpy.ndarray, num\_entities: int, num\_relations: int) \rightarrow None
          Parameters
                train_set
                num_entities
               • num_relations
          Returns
```

Classes

PreprocessKG	Preprocess the data in memory
LoadSaveToDisk	
ReadFromDisk	Read the data from disk into memory

Package Contents

```
Preprocess train, valid and test datasets stored in knowledge graph instance with pandas
           (1) Add recipriocal or noisy triples
           (2) Construct vocabulary
           (3) Index datasets
           Parameter
               rtype
                   None
     {\tt preprocess\_with\_polars}\, () \, \to None
     \verb|sequential_vocabulary_construction|()| \rightarrow None
           (1) Read input data into memory
           (2) Remove triples with a condition
           (3) Serialize vocabularies in a pandas dataframe where
                   => the index is integer and => a single column is string (e.g. URI)
class dicee.read_preprocess_save_load_kg.LoadSaveToDisk(kg)
     kg
     save()
     load()
class dicee.read_preprocess_save_load_kg.ReadFromDisk(kg)
     Read the data from disk into memory
     \mathtt{start}() \to None
           Read a knowledge graph from disk into memory
           Data will be available at the train_set, test_set, valid_set attributes.
           Parameter
           None
               rtype
                   None
     add_noisy_triples_into_training()
dicee.sanity checkers
```

 $preprocess_with_pandas() \rightarrow None$

Functions

Module Contents

```
dicee.sanity_checkers.is_sparql_endpoint_alive(sparql_endpoint: str = None)
dicee.sanity_checkers.validate_knowledge_graph(args)
    Validating the source of knowledge graph
dicee.sanity_checkers.sanity_checking_with_arguments(args)
```

dicee.scripts

Submodules

dicee.scripts.index_serve

\$ docker pull qdrant/qdrant && docker run -p 6333:6333 -p 6334:6334 -v \$(pwd)/qdrant_storage:/qdrant/storage:z qdrant/qdrant \$ dicee_vector_db -index -serve -path CountryEmbeddings -collection "countries_vdb"

Attributes

```
app
neural_searcher
```

Classes

NeuralSearcher	
StringListRequest	!!! abstract "Usage Documentation"

Functions

```
get_default_arguments()
index(args)

root()

search_embeddings(q)

retrieve_embeddings(q)

search_embeddings_batch(request)

serve(args)

main()
```

Module Contents

```
dicee.scripts.index_serve.get_default_arguments()
dicee.scripts.index_serve.index(args)
dicee.scripts.index_serve.app
dicee.scripts.index_serve.neural_searcher = None
class dicee.scripts.index_serve.NeuralSearcher(args)
     collection_name
     entity_to_idx = None
     qdrant_client
     topk = 5
     retrieve_embedding(entity: str = None, entities: List[str] = None) \rightarrow List
     search (entity: str)
async dicee.scripts.index_serve.root()
async dicee.scripts.index_serve.search_embeddings(q: str)
async dicee.scripts.index_serve.retrieve_embeddings(q: str)
class dicee.scripts.index_serve.StringListRequest(/, **data: Any)
     Bases: {\tt pydantic.BaseModel}
     !!! abstract "Usage Documentation"
         [Models](../concepts/models.md)
     A base class for creating Pydantic models.
```

```
__class_vars__
     The names of the class variables defined on the model.
__private_attributes__
     Metadata about the private attributes of the model.
     The synthesized __init__ [Signature][inspect.Signature] of the model.
pydantic_complete_
     Whether model building is completed, or if there are still undefined fields.
pydantic core schema
     The core schema of the model.
__pydantic_custom_init__
     Whether the model has a custom __init__ function.
__pydantic_decorators__
     Metadata containing the decorators defined on the model. This replaces Model. validators and
     Model.__root_validators__ from Pydantic V1.
__pydantic_generic_metadata__
     Metadata for generic models; contains data used for a similar purpose to __args__, __origin__, __parame-
     ters__ in typing-module generics. May eventually be replaced by these.
__pydantic_parent_namespace__
     Parent namespace of the model, used for automatic rebuilding of models.
__pydantic_post_init__
     The name of the post-init method for the model, if defined.
__pydantic_root_model__
     Whether the model is a [RootModel][pydantic.root_model.RootModel].
__pydantic_serializer__
     The pydantic-core SchemaSerializer used to dump instances of the model.
pydantic_validator_
     The pydantic-core Schema Validator used to validate instances of the model.
__pydantic_fields__
     A dictionary of field names and their corresponding [FieldInfo][pydantic.fields.FieldInfo] objects.
__pydantic_computed_fields__
          dictionary
                      of
                            computed
                                         field
                                                                their
                                                                        corresponding
                                                                                        [ComputedField-
                                                names
                                                         and
     Info][pydantic.fields.ComputedFieldInfo] objects.
__pydantic_extra__
     A dictionary containing extra values, if [extra][pydantic.config.ConfigDict.extra] is set to 'allow'.
__pydantic_fields_set__
     The names of fields explicitly set during instantiation.
__pydantic_private__
     Values of private attributes set on the model instance.
```

queries: List[str]

```
reducer: str | None = None
async dicee.scripts.index_serve.search_embeddings_batch (request: StringListRequest)
dicee.scripts.index_serve.serve(args)
dicee.scripts.index_serve.main()
```

dicee.scripts.run

Functions

```
get_default_arguments([description])
                                                      Extends pytorch_lightning Trainer's arguments with ours
main()
```

Module Contents

```
dicee.scripts.run.get_default_arguments(description=None)
     Extends pytorch_lightning Trainer's arguments with ours
dicee.scripts.run.main()
```

dicee.static_funcs

Functions

```
Add inverse triples into dask dataframe
create_recipriocal_triples(x)
get_er_vocab(data[, file_path])
get_re_vocab(data[, file_path])
get_ee_vocab(data[, file_path])
timeit(func)
save_pickle(*[, data, file_path])
load_pickle([file_path])
load_term_mapping([file_path])
select_model(args[,
                        is_continual_training,
                                               stor-
age path])
                                                      Load weights and initialize pytorch module from names-
load_model(→ Tuple[object, Tuple[dict, dict]])
                                                      pace arguments
load_model_ensemble(...)
                                                      Construct Ensemble Of weights and initialize pytorch
                                                      module from namespace arguments
save_numpy_ndarray(*, data, file_path)
                                                      Detect most efficient data type for a given triples
numpy_data_type_changer(→ numpy.ndarray)
```

continues on next page

Table 2 - continued from previous page

```
save\_checkpoint\_model(\rightarrow None)
                                                        Store Pytorch model into disk
store(\rightarrow None)
                                                        Add randomly constructed triples
add\_noisy\_triples(\rightarrow pandas.DataFrame)
read_or_load_kg(args, cls)
intialize\_model(\rightarrow Tuple[object, str])
load_json(\rightarrow dict)
                                                        Save it as CSV if memory allows.
save\_embeddings(\rightarrow None)
random_prediction(pre_trained_kge)
deploy_triple_prediction(pre_trained_kge,
str_subject, ...)
deploy_tail_entity_prediction(pre_trained_kge,
deploy_head_entity_prediction(pre_trained_kge,
deploy_relation_prediction(pre_trained_kge,
vocab_to_parquet(vocab_to_idx, name, ...)
create_experiment_folder([folder_name])
continual\_training\_setup\_executor(\rightarrow None)
exponential\_function(\rightarrow torch.FloatTensor)
load_numpy(→ numpy.ndarray)
                                                        # @TODO: CD: Renamed this function
evaluate(entity_to_idx,
                             scores,
                                        easy answers,
hard answers)
download_file(url[, destination_folder])
download\_files\_from\_url(\rightarrow None)
download\_pretrained\_model(\rightarrow str)
write_csv_from_model_parallel(path)
                                                        Create
from_pretrained_model_write_embeddings_int
None)
```

Module Contents

```
dicee.static_funcs.create_recipriocal_triples(x)

Add inverse triples into dask dataframe :param x: :return:

dicee.static_funcs.get_er_vocab(data, file_path: str = None)

dicee.static_funcs.get_re_vocab(data, file_path: str = None)

dicee.static_funcs.get_ee_vocab(data, file_path: str = None)
```

```
dicee.static_funcs.timeit(func)
dicee.static_funcs.save_pickle(*, data: object = None, file_path=str)
dicee.static_funcs.load_pickle(file_path=str)
dicee.static_funcs.load_term_mapping(file_path=str)
dicee.static_funcs.select_model(args: dict, is_continual_training: bool = None,
            storage\_path: str = None)
dicee.static_funcs.load_model(path_of_experiment_folder: str, model_name='model.pt', verbose=0)
             → Tuple[object, Tuple[dict, dict]]
     Load weights and initialize pytorch module from namespace arguments
dicee.static_funcs.load_model_ensemble(path_of_experiment_folder: str)
             → Tuple[dicee.models.base_model.BaseKGE, Tuple[pandas.DataFrame, pandas.DataFrame]]
     Construct Ensemble Of weights and initialize pytorch module from namespace arguments
       (1) Detect models under given path
      (2) Accumulate parameters of detected models
       (3) Normalize parameters
       (4) Insert (3) into model.
dicee.static_funcs.save_numpy_ndarray(*, data: numpy.ndarray, file_path: str)
dicee.static_funcs.numpy_data_type_changer(train_set: numpy.ndarray, num: int)
             \rightarrow numpy.ndarray
     Detect most efficient data type for a given triples :param train_set: :param num: :return:
dicee.static_funcs.save_checkpoint_model(model, path: str) \rightarrow None
     Store Pytorch model into disk
dicee.static_funcs.store(trained model, model name: str = 'model', full storage path: str = None,
            save\_embeddings\_as\_csv=False) \rightarrow None
dicee.static_funcs.add_noisy_triples(train_set: pandas.DataFrame, add_noise_rate: float)
             \rightarrow pandas.DataFrame
     Add randomly constructed triples :param train_set: :param add_noise_rate: :return:
dicee.static_funcs.read_or_load_kg(args, cls)
dicee.static_funcs.intialize model(args: dict, verbose=0) \rightarrow Tuple[object, str]
dicee.static_funcs.load_json(p: str) \rightarrow dict
dicee.static_funcs.save_embeddings (embeddings: numpy.ndarray, indexes, path: str) \rightarrow None
     Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:
dicee.static_funcs.random_prediction(pre_trained_kge)
dicee.static_funcs.deploy_triple_prediction(pre_trained_kge, str_subject, str_predicate,
            str_object)
dicee.static_funcs.deploy_tail_entity_prediction(pre_trained_kge, str_subject, str_predicate,
            top_k)
```

```
dicee.static_funcs.deploy_head_entity_prediction(pre_trained_kge, str_object, str_predicate,
           top_k)
dicee.static_funcs.deploy_relation_prediction(pre_trained_kge, str_subject, str_object, top_k)
dicee.static_funcs.vocab_to_parquet(vocab_to_idx, name, path_for_serialization, print_into)
dicee.static_funcs.create_experiment_folder(folder_name='Experiments')
dicee.static_funcs.continual_training_setup_executor(executor) \rightarrow None
dicee.static_funcs.exponential function (x: numpy.ndarray, lam: float, ascending order=True)
            → torch.FloatTensor
dicee.static_funcs.load_numpy(path) \rightarrow numpy.ndarray
dicee.static_funcs.evaluate(entity_to_idx, scores, easy_answers, hard_answers)
     # @TODO: CD: Renamed this function Evaluate multi hop query answering on different query types
dicee.static_funcs.download_file(url, destination_folder='.')
dicee.static_funcs.download_files_from_url(base\_url: str, destination\_folder='.') \rightarrow None
          Parameters
                                                "https://files.dice-research.org/projects/DiceEmbeddings/
                • base_url
                                (e.g.
                  KINSHIP-Keci-dim128-epoch256-KvsAll")
                • destination_folder (e.g. "KINSHIP-Keci-dim128-epoch256-KvsA11")
dicee.static_funcs.download_pretrained_model(url: str) \rightarrow str
dicee.static_funcs.write_csv_from_model_parallel(path: str)
     Create
dicee.static_funcs.from_pretrained_model_write_embeddings_into_csv(path: str) \rightarrow None
```

dicee.static funcs training

Functions

```
make\_iterable\_verbose(\rightarrow Iterable)
evaluate\_lp([model, triple\_idx, num\_entities, ...])
evaluate\_bpe\_lp(model, triple\_idx, ...[, info])
efficient\_zero\_grad(model)
```

Module Contents

dicee.static_funcs_training.make_iterable_verbose(iterable_object, verbose, desc='Default', position=None, leave=True) \rightarrow Iterable

dicee.static_preprocess_funcs

Attributes

enable_log

Functions

```
timeit(func)
preprocesses\_input\_args(args) \qquad Sanity Checking in input arguments
create\_constraints(\rightarrow Tuple[dict, dict, dict])
get\_er\_vocab(data)
get\_re\_vocab(data)
get\_ee\_vocab(data)
mapping\_from\_first\_two\_cols\_to\_third(train\_se)
```

Module Contents

- (1) Extract domains and ranges of relations
- (2) Store a mapping from relations to entities that are outside of the domain and range. Create constraints entities based on the range of relations :param triples: :return:

```
dicee.static_preprocess_funcs.get_er_vocab(data)
dicee.static_preprocess_funcs.get_re_vocab(data)
```

```
dicee.static_preprocess_funcs.get_ee_vocab(data)
dicee.static_preprocess_funcs.mapping_from_first_two_cols_to_third(train_set_idx)
```

dicee.trainer

Submodules

dicee.trainer.dice_trainer

Classes

```
DICE_Trainer implement
```

Functions

```
load_term_mapping([file_path])
initialize_trainer(...)
get_callbacks(args)
```

Module Contents

```
dicee.trainer.dice_trainer.load_term_mapping(file_path=str)
dicee.trainer.dice_trainer.initialize_trainer(args, callbacks)
             \rightarrow dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.model_parallelism.TensorParallel | dicee.trainer.torch_trainer_ddp
\verb|dicee.trainer.dice_trainer.get_callbacks|| (args)
class dicee.trainer.dice_trainer.DICE_Trainer (args, is_continual_training: bool, storage_path,
            evaluator=None)
     DICE_Trainer implement
           1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html)
           2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.
           html) 3- CPU Trainer
           args
           is_continual_training:bool
           storage_path:str
           evaluator:
           report:dict
     report
     args
     trainer = None
```

```
is_continual_training
storage_path
evaluator = None
form_of_labelling = None
continual_start (knowledge_graph)
              (1) Initialize training.
              (2) Load model
             (3) Load trainer (3) Fit model
             Parameter
                        returns

    model

                                   • form of labelling (str)
initialize_trainer(callbacks: List)
                                  → lightning.Trainer | dicee.trainer.model_parallelism.TensorParallel | dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_traine
             Initialize Trainer from input arguments
initialize_or_load_model()
init_dataloader (dataset: torch.utils.data.Dataset) → torch.utils.data.DataLoader
init_dataset() → torch.utils.data.Dataset
start (knowledge_graph: dicee.knowledge_graph.KG | numpy.memmap)
                                  → Tuple[dicee.models.base_model.BaseKGE, str]
             Start the training
              (1) Initialize Trainer
              (2) Initialize or load a pretrained KGE model
             in DDP setup, we need to load the memory map of already read/index KG.
k\_fold\_cross\_validation(dataset) \rightarrow Tuple[dicee.models.base\_model.BaseKGE, str]
             Perform K-fold Cross-Validation
                 1. Obtain K train and test splits.
                 2. For each split,
                                  2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute
                                  the mean reciprocal rank (MRR) score of the model on the test respective split.
                 3. Report the mean and average MRR.
                        Parameters
                                   • self
                                   • dataset
```

Returns model

dicee.trainer.model_parallelism

Classes

TensorParallel	Abstract class for Trainer class for knowledge graph em-
	bedding models

Functions

```
extract_input_outputs(z[, device])

find_good_batch_size(train_loader,

tp_ensemble_model)

forward_backward_update_loss(→ float)
```

Module Contents

```
args
[str] ?

callbacks: list
?

fit (*args, **kwargs)
Train model
```

dicee.trainer.torch_trainer

Classes

TorchTrainer	TorchTrainer for using single GPU or multi CPUs on a
	single node

Module Contents

```
class dicee.trainer.torch_trainer.TorchTrainer(args, callbacks)
     Bases: dicee.abstracts.AbstractTrainer
           TorchTrainer for using single GPU or multi CPUs on a single node
           Arguments
     callbacks: list of Abstract callback instances
     loss_function = None
     optimizer = None
     model = None
     train_dataloaders = None
     training_step = None
     process
     fit (*args, train\_dataloaders, **kwargs) \rightarrow None
               Training starts
               Arguments
           kwargs:Tuple
               empty dictionary
               Return type
                   batch loss (float)
     forward\_backward\_update(x\_batch: torch.Tensor, y\_batch: torch.Tensor) \rightarrow torch.Tensor
               Compute forward, loss, backward, and parameter update
               Arguments
               Return type
                   batch loss (float)
     \verb|extract_input_outputs_set_device| (\textit{batch: list}) \rightarrow Tuple
               Construct inputs and outputs from a batch of inputs with outputs From a batch of inputs and put
               Arguments
               Return type
                   (tuple) mini-batch on select device
```

dicee.trainer.torch_trainer_ddp

Classes

```
TorchDDPTrainer A Trainer based on torch.nn.parallel.DistributedDataParallel
NodeTrainer
```

Functions

```
make\_iterable\_verbose(\rightarrow Iterable)
```

Module Contents

```
dicee.trainer.torch_trainer_ddp.make_iterable_verbose(iterable_object, verbose,
            desc='Default', position=None, leave=True) \rightarrow Iterable
class dicee.trainer.torch_trainer_ddp.TorchDDPTrainer(args, callbacks)
     Bases: dicee.abstracts.AbstractTrainer
          A Trainer based on torch.nn.parallel.DistributedDataParallel
          Arguments
     entity_idxs
          mapping.
     relation_idxs
          mapping.
     form
     store
     label_smoothing_rate
          Using hard targets (0,1) drives weights to infinity. An outlier produces enormous gradients.
          Return type
              torch.utils.data.Dataset
     fit (*args, **kwargs)
          Train model
class dicee.trainer.torch_trainer_ddp.NodeTrainer(trainer, model: torch.nn.Module,
            train_dataset_loader: torch.utils.data.DataLoader, callbacks, num_epochs: int)
     trainer
     local_rank
     global_rank
```

```
optimizer

train_dataset_loader

loss_func

callbacks

model

num_epochs

loss_history = []

ctx

scaler

extract_input_outputs(z: list)

train()

Training loop for DDP
```

Classes

DICE_Trainer

DICE_Trainer implement

Package Contents

class dicee.trainer.DICE_Trainer(args, is_continual_training: bool, storage_path, evaluator=None)

DICE_Trainer implement

- 1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html)
- 2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel. html) 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator = None

form_of_labelling = None

```
continual_start (knowledge_graph)
                  (1) Initialize training.
                  (2) Load model
                (3) Load trainer (3) Fit model
                Parameter
                              returns

    model

                                            • form_of_labelling (str)
initialize_trainer(callbacks: List)
                                           → lightning.Trainer | dicee.trainer.model_parallelism.TensorParallel | dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_traine
                Initialize Trainer from input arguments
initialize_or_load_model()
\verb"init_dataloader" (dataset: torch.utils.data.Dataset") 	o torch.utils.data.DataLoader
\verb"init_dataset"() \rightarrow torch.utils.data.Dataset"
start (knowledge_graph: dicee.knowledge_graph.KG | numpy.memmap)
                                           → Tuple[dicee.models.base_model.BaseKGE, str]
                Start the training
                  (1) Initialize Trainer
                  (2) Initialize or load a pretrained KGE model
                in DDP setup, we need to load the memory map of already read/index KG.
k\_fold\_cross\_validation(dataset) \rightarrow Tuple[dicee.models.base\_model.BaseKGE, str]
                Perform K-fold Cross-Validation
                     1. Obtain K train and test splits.
```

- 2. For each split,
 - 2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
- 3. Report the mean and average MRR.

Parameters

- self
- dataset

Returns

model

14.2 Attributes

_version__

14.3 Classes

A Physical Embedding Model for Knowledge Graphs
Embedding Entities and Relations for Learning and Infer-
ence in Knowledge Bases
Without learning dimension scaling
Base class for all neural network modules.
Translating Embeddings for Modeling
Base class for all neural network modules.
Dual Quaternion Knowledge Graph Embeddings
(https://ojs.aaai.org/index.php/AAAI/article/download/ 16850/16657)
Base class for all neural network modules.
Additive Convolutional ComplEx Knowledge Graph Embeddings
Additive Convolutional Octonion Knowledge Graph Em-
beddings
Additive Convolutional Quaternion Knowledge Graph
Embeddings
Convolutional Quaternion Knowledge Graph Embed-
dings
Base class for all neural network modules.
Convolutional ComplEx Knowledge Graph Embeddings
Base class for all neural network modules.
Base class for all neural network modules.
A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
A class for using knowledge graph embedding models implemented in Pykeen
Base class for all neural network modules.
Base class for all neural network modules.
DICE_Trainer implement
Knowledge Graph Embedding Class for interactive usage of pre-trained models
An abstract class representing a Dataset.
An abstract class representing a Dataset.
Dataset for the 1vsALL training strategy
Dataset for the 1vsALL training strategy
Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
A custom PyTorch Dataset class for knowledge graph embeddings, which includes
KvsSample a Dataset:
An abstract class representing a Dataset.
Triple Dataset
Create a Dataset for cross validation
Create a Dataset for cross validation continues on next page

continues on next page

QueryGenerator

14.4 Functions

```
Add inverse triples into dask dataframe
create_recipriocal_triples(x)
get_er_vocab(data[, file_path])
get_re_vocab(data[, file_path])
get_ee_vocab(data[, file_path])
timeit(func)
save_pickle(*[, data, file_path])
load_pickle([file_path])
load_term_mapping([file_path])
select_model(args[,
                         is_continual_training,
                                                 stor-
age_path])
load_model(→ Tuple[object, Tuple[dict, dict]])
                                                        Load weights and initialize pytorch module from names-
                                                        pace arguments
                                                        Construct Ensemble Of weights and initialize pytorch
load_model_ensemble(...)
                                                        module from namespace arguments
save_numpy_ndarray(*, data, file_path)
numpy_data_type_changer(→ numpy.ndarray)
                                                        Detect most efficient data type for a given triples
save\_checkpoint\_model(\rightarrow None)
                                                        Store Pytorch model into disk
store(\rightarrow None)
add\_noisy\_triples(\rightarrow pandas.DataFrame)
                                                        Add randomly constructed triples
read_or_load_kg(args, cls)
intialize\_model(\rightarrow Tuple[object, str])
load_json(\rightarrow dict)
                                                        Save it as CSV if memory allows.
save\_embeddings(\rightarrow None)
random_prediction(pre_trained_kge)
deploy_triple_prediction(pre_trained_kge,
str_subject, ...)
{\it deploy\_tail\_entity\_prediction} (pre\_trained\_kge,
deploy_head_entity_prediction(pre_trained_kge,
deploy_relation_prediction(pre_trained_kge,
...)
```

continues on next page

Table 4 - continued from previous page

```
vocab_to_parquet(vocab_to_idx, name, ...)
create_experiment_folder([folder_name])
continual\_training\_setup\_executor(\rightarrow None)
exponential\_function( \rightarrow torch.FloatTensor)
load_numpy(→ numpy.ndarray)
                                                      # @TODO: CD: Renamed this function
evaluate(entity_to_idx,
                            scores,
                                       easy_answers,
hard_answers)
download_file(url[, destination_folder])
download\_files\_from\_url(\rightarrow None)
download\_pretrained\_model(\rightarrow str)
write_csv_from_model_parallel(path)
                                                      Create
from_pretrained_model_write_embeddings_int
mapping_from_first_two_cols_to_third(train_se
timeit(func)
load_term_mapping([file_path])
reload_dataset(path, form_of_labelling, ...)
                                                      Reload the files from disk to construct the Pytorch dataset
construct_dataset(→ torch.utils.data.Dataset)
```

14.5 Package Contents

Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

```
name = 'DistMult'
     k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor, emb_E: torch.FloatTensor)
              Parameters
                  • emb h
                  • emb_r
                  • emb_E
     forward_k_vs_all (x: torch.LongTensor)
     forward_k_vs_sample(x: torch.LongTensor, target_entity_idx: torch.LongTensor)
     score(h, r, t)
class dicee.CKeci(args)
     Bases: Keci
     Without learning dimension scaling
     name = 'CKeci'
     requires_grad_for_interactions = False
class dicee.Keci(args)
     Bases: dicee.models.base_model.BaseKGE
```

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

```
Variables
```

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
name = 'Keci'
p
q
r
requires_grad_for_interactions = True
compute\_sigma\_pp(hp, rp)
     Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k
     sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute
     interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops
          results = [] for i in range(p - 1):
              for k in range(i + 1, p):
                results.append(hp[:,:,i]*rp[:,:,k] - hp[:,:,k]*rp[:,:,i]) \\
          sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))
     Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1,
     e1e2, e1e3,
          e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
     Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.
compute\_sigma\_qq(hq, rq)
     Compute sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q}
     captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions
     between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops
          results = [] for j in range(q - 1):
              for k in range(j + 1, q):
                 results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])
          sigma qq = torch.stack(results, dim=2) assert sigma qq.shape == (b, r, int((q * (q - 1)) / 2))
     Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1,
     e1e2, e1e3,
          e2e1, e2e2, e2e3, e3e1, e3e2, e3e3
     Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.
compute_sigma_pq(*, hp, hq, rp, rq)
     sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j
     results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):
          for j in range(q):
              sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]
     print(sigma_pq.shape)
```

```
apply_coefficients(hp, hq, rp, rq)
```

Multiplying a base vector with its scalar coefficient

clifford_multiplication(h0, hp, hq, r0, rp, rq)

Compute our CL multiplication

$$h = h_0 + sum_{i=1}^p h_i e_i + sum_{j=p+1}^{p+q} h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^{p+q} r_j e_j$$

ei
2
 = +1 for i =< i =< p ej 2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

 $h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q} + sig$

- (1) $sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i sum_{j=p+1}^{p+q} (h_j r_j) e_j$
- (2) $sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i$
- (3) $sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j$
- (4) $sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k h_k r_i) e_i e_k$
- (5) $sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k h_k r_j) e_j e_k$
- (6) $sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j h_j r_i) e_i e_j$

 ${\tt construct_cl_multivector}$ (x: torch.FloatTensor, r: int, p: int, q: int)

 \rightarrow tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{p,q}(mathbb{R}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor with (n,r) shape)
- **ap** $(torch.FloatTensor\ with\ (n,r,p)\ shape)$
- aq (torch.FloatTensor with (n,r,q) shape)

forward_k_vs_with_explicit(x: torch.Tensor)

 $\verb+k_vs_all_score+ (bpe_head_ent_emb, bpe_rel_ent_emb, E)$

 $\textbf{forward_k_vs_all} \ (\textit{x: torch.Tensor}) \ \rightarrow \text{torch.FloatTensor}$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations mathbb $\{R\}^d$.
- (2) Construct head entity and relation embeddings according to $Cl_{p,q}(\mathbf{mathbb}\{R\}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this functions are identical Parameter — x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n,|E|) shape

construct_batch_selected_cl_multivector(x: torch.FloatTensor, r: int, p: int, q: int)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of batchs multivectors $Cl_{p,q}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,k, d) shape

returns

- **a0** (torch.FloatTensor with (n,k, m) shape)
- **ap** (torch.FloatTensor with (n,k, m, p) shape)
- **aq** (torch.FloatTensor with (n,k, m, q) shape)

 $\textbf{forward_k_vs_sample} \ (x: torch.LongTensor, target_entity_idx: torch.LongTensor) \ \rightarrow \\ \textbf{torch.FloatTensor}$

Parameter

```
x: torch.LongTensor with (n,2) shape
```

target_entity_idx: torch.LongTensor with (n, k) shape k denotes the selected number of examples.

rtvpe

torch.FloatTensor with (n, k) shape

score (*h*, *r*, *t*)

forward_triples (x: torch.Tensor) \rightarrow torch.FloatTensor

Parameter

```
x: torch.LongTensor with (n,3) shape
```

rtype

torch.FloatTensor with (n) shape

class dicee.TransE(args)

Bases: dicee.models.base_model.BaseKGE

Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf

```
name = 'TransE'
margin = 4
score(head_ent_emb, rel_ent_emb, tail_ent_emb)
```

 $forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor$

class dicee.DeCaL(args)

 $Bases: \ \textit{dicee.models.base_model.BaseKGE}$

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
```

(continues on next page)

(continued from previous page)

```
def __init__ (self) -> None:
    super().__init__()
    self.conv1 = nn.Conv2d(1, 20, 5)
    self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'DeCaL'
entity_embeddings
relation_embeddings
p
q
r
re
forward_triples(x: torch.Tensor) → torch.FloatTensor
```

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

 $cl_pqr(a: torch.tensor) \rightarrow torch.tensor$

Input: tensor(batch_size, emb_dim) \longrightarrow output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q + r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

 $\verb|compute_sigmas_single| (\textit{list}_h_\textit{emb}, \textit{list}_r_\textit{emb}, \textit{list}_t_\textit{emb})$

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^p h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^q (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+q+r}^{p+q+r}$$

and return:

$$sigma_0t = \sigma_0 \cdot t_0 = s0 + s1 - s2s3, s4ands5$$

compute_sigmas_multivect (list_h_emb, list_r_emb)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^p (h_i r_{i'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p) \\ \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'} - h_{i'} r_i) (models the interactions between e_i and e_i' for 1 <= i, i' <= p)$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (interactionsnbetween e_i and e_j for 1 <= i <= pand p+1 <= j <= p+q) \\ \sigma_p r = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (interactionsnbetween e_i and e_j for 1 <= i <= pand p+1 <= j <= p+q) \\ \sigma_p r = \sum_{i=1}^p \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) (interactionsnbetween e_i and e_j for 1 <= i <= pand p+1 <= j <= p+q)$$

 $forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor$

Kvsall training

- (1) Retrieve real-valued embedding vectors for heads and relations
- (2) Construct head entity and relation embeddings according to $Cl_{p,q, r}(mathbb{R}^d)$.
- (3) Perform Cl multiplication
- (4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter — x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

 $apply_coefficients(h0, hp, hq, hk, r0, rp, rq, rk)$

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (x: torch.FloatTensor, re: int, p: int, q: int, r: int)

→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors $Cl_{p,q,r}(mathbb\{R\}^d)$

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (torch.FloatTensor)
- **ap** (torch.FloatTensor)
- aq (torch.FloatTensor)
- ar (torch.FloatTensor)

 $compute_sigma_pp(hp, rp)$

Compute .. math:

$$\label{eq:sigma_{p,p}^* = \sum_{i=1}^{p-1}\sum_{i'=i+1}^{p} (x_iy_{i'}-x_{i'}y_i)} $$ $$ \sum_{i'=i+1}^{p} (x_iy_{i'}-x_{i'}y_i) $$ $$$$

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):

 $sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))$

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

 $compute_sigma_qq(hq, rq)$

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) Eq.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3, and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):

 $sigma_q = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))$

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute sigma rr(hk, rk)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^{p} (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq(*, hp, hq, rp, rq)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] $sigma_pq = torch.zeros(b, r, p, q)$ for i in range(p):

for j in range(q):

sigma
$$pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

compute_sigma_pr(*, hp, hk, rp, rk)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

 $compute_sigma_qr(*, hq, hk, rq, rk)$

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):

$$sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]$$

print(sigma_pq.shape)

class dicee.DualE(args)

Bases: dicee.models.base_model.BaseKGE

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent = None

kvsall_score ($e_1h, e_2h, e_3h, e_4h, e_5h, e_6h, e_7h, e_8h, e_1t, e_2t, e_3t, e_4t, e_5t, e_6t, e_7t, e_8t, r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) o$ torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

 $forward_triples(idx_triple: torch.tensor) \rightarrow torch.tensor$

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

```
forward_k_vs_all(x)
```

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T (x: torch.tensor) \rightarrow torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

```
class dicee.ComplEx(args)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

 $\textbf{training} \ (\textit{bool}) - Boolean \ represents \ whether \ this \ module \ is \ in \ training \ or \ evaluation \ mode.$

```
name = 'ComplEx'
```

```
static score (head_ent_emb: torch.FloatTensor, rel_ent_emb: torch.FloatTensor,
                  tail_ent_emb: torch.FloatTensor)
     static k_vs_all_score (emb_h: torch.FloatTensor, emb_r: torch.FloatTensor,
                  emb E: torch.FloatTensor)
               Parameters
                   • emb h
                   • emb_r
                   • emb E
     forward_k_vs_all(x: torch.LongTensor) \rightarrow torch.FloatTensor
     forward_k_vs_sample (x: torch.LongTensor, target_entity_idx: torch.LongTensor)
class dicee.AConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional ComplEx Knowledge Graph Embeddings
     name = 'AConEx'
     conv2d
     fc_num_input
     fc1
     norm_fc1
     bn_conv2d
     feature_map_dropout
     residual_convolution(C_1: Tuple[torch.Tensor, torch.Tensor],
                  C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
           Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors
           that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds
           complex-valued embeddings :return:
     forward_k_vs_all(x: torch.Tensor) \rightarrow torch.FloatTensor
     forward triples (x: torch. Tensor) \rightarrow torch. FloatTensor
               Parameters
                   x
     forward_k_vs_sample (x: torch.Tensor, target_entity_idx: torch.Tensor)
class dicee.AConvO(args: dict)
     Bases: dicee.models.base_model.BaseKGE
     Additive Convolutional Octonion Knowledge Graph Embeddings
     name = 'AConvO'
     conv2d
     fc_num_input
```

```
fc1
     bn_conv2d
     norm_fc1
     feature_map_dropout
     static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                  emb_rel_e5, emb_rel_e6, emb_rel_e7)
     residual\_convolution(O\_1, O\_2)
     forward\_triples(x: torch.Tensor) \rightarrow torch.Tensor
               Parameters
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities l)
class dicee.AConvQ(args)
     Bases: dicee.models.base model.BaseKGE
     Additive Convolutional Quaternion Knowledge Graph Embeddings
     name = 'AConvQ'
     entity_embeddings
     relation_embeddings
     conv2d
     fc_num_input
     fc1
     bn_conv1
     bn_conv2
     feature_map_dropout
     residual_convolution (Q_1, Q_2)
     forward\_triples (indexed\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
                   x
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
```

Entities|)

```
class dicee.ConvQ(args)
     Bases: dicee.models.base_model.BaseKGE
     Convolutional Quaternion Knowledge Graph Embeddings
     name = 'ConvQ'
     entity_embeddings
     relation embeddings
     conv2d
     fc_num_input
     fc1
     bn_conv1
     bn_conv2
     feature_map_dropout
     {\tt residual\_convolution}\,(Q\_I,\,Q\_2)
     forward\_triples (indexed\_triple: torch.Tensor) \rightarrow torch.Tensor
               Parameters
     forward_k_vs_all (x: torch.Tensor)
           Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
           [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|
           Entities()
class dicee.ConvO(args: dict)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model (nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.



1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the

Variables

feature_map_dropout

```
training (b \circ o 1) – Boolean represents whether this module is in training or evaluation mode.
```

```
name = 'ConvO'
     conv2d
     fc_num_input
     fc1
     bn_conv2d
     norm_fc1
     feature_map_dropout
     static octonion_normalizer(emb_rel_e0, emb_rel_e1, emb_rel_e2, emb_rel_e3, emb_rel_e4,
                 emb_rel_e5, emb_rel_e6, emb_rel_e7)
     residual\_convolution(O\_1, O\_2)
     forward\_triples(x: torch.Tensor) \rightarrow torch.Tensor
               Parameters
     forward_k_vs_all (x: torch.Tensor)
          Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] =>
          [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,)
          Entities l)
class dicee.ConEx(args)
     Bases: dicee.models.base_model.BaseKGE
     Convolutional ComplEx Knowledge Graph Embeddings
     name = 'ConEx'
     conv2d
     fc_num_input
     fc1
     norm_fc1
     bn_conv2d
```

```
residual_convolution (C_1: Tuple[torch.Tensor, torch.Tensor], C_2: Tuple[torch.Tensor, torch.Tensor]) \rightarrow torch.FloatTensor
```

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

class dicee.QMult(args)

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training $(b \circ o 1)$ – Boolean represents whether this module is in training or evaluation mode.

```
\label{eq:name} \begin{tabular}{ll} name &= 'QMult' \\ \\ explicit &= True \\ \\ quaternion_multiplication_followed_by_inner_product $(h,r,t)$ \\ \\ \end{tabular}
```

Parameters

- h shape: (*batch_dims, dim) The head representations.
- **r** shape: (**batch_dims*, dim) The head representations.
- t shape: (*batch_dims, dim) The tail representations.

Returns

Triple scores.

$\mathtt{static}\ \mathtt{quaternion_normalizer}\ (x:\ torch.FloatTensor) \ o \ torch.FloatTensor$

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$||x||^2 = \sum_{i=1}^d |x_i|^2 = \sum_{i=1}^d (x_i \cdot re^2 + x_i \cdot im_1^2 + x_i \cdot im_2^2 + x_i \cdot im_3^2)$$

Parameters

 \mathbf{x} – The vector.

Returns

The normalized vector.

k_vs_all_score (bpe_head_ent_emb, bpe_rel_ent_emb, E)

Parameters

- bpe_head_ent_emb
- bpe rel ent emb
- E

 ${\tt forward_k_vs_all}\;(\mathcal{X})$

Parameters

x

forward_k_vs_sample (x, target_entity_idx)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.OMult(args)

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__ ()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to(), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,...,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

```
class dicee.Shallom(args)
```

Bases: dicee.models.base_model.BaseKGE

A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)

```
name = 'Shallom'
shallom
get_embeddings() \rightarrow Tuple[numpy.ndarray, None]
forward_k_vs_all(x) \rightarrow torch.FloatTensor
forward_triples(x) \rightarrow torch.FloatTensor
```

Parameters

x

Returns

```
class dicee.LFMult(args)
     Bases: dicee.models.base_model.BaseKGE
     Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) =
     sum_{i=0}^{d-1} a_k x^{i\%d} and use the three differents scoring function as in the paper to evaluate the score.
     We also consider combining with Neural Networks.
     name = 'LFMult'
     entity_embeddings
     relation_embeddings
     degree
     x_values
     forward_triples (idx_triple)
               Parameters
     construct multi coeff(X)
     poly_NN(x, coefh, coefr, coeft)
           Constructing a 2 layers NN to represent the embeddings. h = sigma(wh^T x + bh), r = sigma(wr^T x + br),
           t = sigma(wt^T x + bt)
     linear(x, w, b)
     scalar_batch_NN(a, b, c)
           element wise multiplication between a,b and c: Inputs: a, b, c ====> torch.tensor of size batch_size x m x
           d Output: a tensor of size batch_size x d
     tri_score (coeff_h, coeff_r, coeff_t)
           this part implement the trilinear scoring techniques:
           score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k} = 0}^{d-1} dfrac{a_i*b_j*c_k}{1+(i+j+k)%d}
            1. generate the range for i, j and k from [0 d-1]
           2. perform dfrac\{a_i*b_j*c_k\}\{1+(i+j+k)\%d\} in parallel for every batch
            3. take the sum over each batch
     vtp score (h, r, t)
           this part implement the vector triple product scoring techniques:
           score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k} = 0}^{d-1} dfrac{a_i*c_j*b_k}{-1}
           b_i*c_j*a_k{(1+(i+j)%d)(1+k)}
            1. generate the range for i,j and k from [0 d-1]
            2. Compute the first and second terms of the sum
```

3. Multiply with then denominator and take the sum

4. take the sum over each batch

```
comp\_func(h, r, t)
```

this part implement the function composition scoring techniques: i.e. score = <hor, t>

```
polynomial(coeff, x, degree)
```

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,...d] and return a vector tensor (coeff $[0][0] + \text{coeff}[0][1]x + ... + \text{coeff}[0][d]x^d$,

```
coeff[1][0] + coeff[1][1]x + ... + coeff[1][d]x^d
```

```
pop (coeff, x, degree)
```

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,...d]

```
and return a tensor (coeff[0][0] + coeff[0][1]x + ... + coeff[0][d]x^d,
```

```
coeff[1][0] + coeff[1][1]x + ... + coeff[1][d]x^d
```

```
class dicee.PykeenKGE(args: dict)
```

Bases: dicee.models.base_model.BaseKGE

A class for using knowledge graph embedding models implemented in Pykeen

Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Pykeen_HolE: Pykeen_TransD: Pykeen_TransE: Pykeen_TransF: Pykeen_TransH: Pykeen_TransR:

```
model_kwargs
```

model

loss_history = []

args

entity_embeddings = None

relation_embeddings = None

forward_k_vs_all (x: torch.LongTensor)

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, $r = self.get_head_relation_representation(x) # (2) Reshape (1). if <math>self.last_dim > 0$:

 $h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim)$

(3) Reshape all entities. if self.last_dim > 0:

t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

else:

t = self.entity_embeddings.weight

(4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r, all_entities=t, slice_size=1)

```
forward_triples (x: torch.LongTensor) \rightarrow torch.FloatTensor
```

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t = self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

```
h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)
```

(3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice size=None, slice dim=0)

abstract forward_k_vs_sample (x: torch.LongTensor, target_entity_idx)

```
class dicee.BytE(*args, **kwargs)
```

Bases: dicee.models.base_model.BaseKGE

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

```
name = 'BytE'
config
temperature = 0.5
topk = 2
transformer
```

1m head

loss_function(yhat_batch, y_batch)

Parameters

- · yhat batch
- y_batch

forward (x: torch.LongTensor)

Parameters

```
\mathbf{x} (B by T tensor)
```

generate (idx, max_new_tokens, temperature=1.0, top_k=None)

Take a conditioning sequence of indices idx (LongTensor of shape (b,t)) and complete the sequence max_new_tokens times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in model.eval() mode of operation for this.

```
training_step(batch, batch_idx=None)
```

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- batch The output of your data iterable, normally a DataLoader.
- batch_idx The index of this batch.
- dataloader_idx The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- Tensor The loss tensor
- dict A dictionary which can include any keys, but must include the key 'loss' in the case of automatic optimization.
- None In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False
```

(continues on next page)

(continued from previous page)

```
# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

# do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

1 Note

When $accumulate_grad_batches > 1$, the loss returned here will be automatically normalized by $accumulate_grad_batches$ internally.

class dicee.BaseKGE(args: dict)

Bases: BaseKGELightning

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing them to be nested in a tree structure. You can assign the sub-modules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__ (self) -> None:
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

def forward(self, x):
    x = F.relu(self.conv1(x))
    return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will also have their parameters converted when you call to (), etc.

1 Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (bool) – Boolean represents whether this module is in training or evaluation mode.

args

```
embedding_dim = None
num_entities = None
num_relations = None
num_tokens = None
learning_rate = None
apply_unit_norm = None
input_dropout_rate = None
hidden_dropout_rate = None
optimizer_name = None
feature_map_dropout_rate = None
kernel_size = None
num_of_output_channels = None
weight_decay = None
loss
selected_optimizer = None
normalizer_class = None
normalize_head_entity_embeddings
normalize_relation_embeddings
normalize_tail_entity_embeddings
hidden_normalizer
param_init
input_dp_ent_real
input_dp_rel_real
hidden_dropout
loss_history = []
byte_pair_encoding
max_length_subword_tokens
block_size
forward_byte_pair_encoded_k_vs_all (x: torch.LongTensor)
       Parameters
          x (B x 2 x T)
```

```
forward_byte_pair_encoded_triple (x: Tuple[torch.LongTensor, torch.LongTensor])
          byte pair encoded neural link predictors
              Parameters
     init_params_with_sanity_checking()
     forward(x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor],
                 y_idx: torch.LongTensor = None
              Parameters
                  • x
                  • y_idx
                  • ordered_bpe_entities
     forward\_triples(x: torch.LongTensor) \rightarrow torch.Tensor
              Parameters
     forward_k_vs_all(*args, **kwargs)
     forward_k_vs_sample(*args, **kwargs)
     get_triple_representation(idx_hrt)
     get_head_relation_representation(indexed_triple)
     get_sentence_representation(x: torch.LongTensor)
              Parameters
                  • (b (x shape)
                  • 3
                  • t)
     get_bpe_head_and_relation_representation(x: torch.LongTensor)
                  \rightarrow Tuple[torch.FloatTensor, torch.FloatTensor]
              Parameters
                  x (B x 2 x T)
     \mathtt{get\_embeddings}() \rightarrow Tuple[numpy.ndarray, numpy.ndarray]
class dicee.EnsembleKGE (seed_model=None, pretrained_models: List = None)
     name
     train_mode = True
     named_children()
     property example_input_array
     parameters()
     modules()
```

```
__iter__()
      __len__()
     eval()
     to (device)
     mem_of_model()
     __call__(x_batch)
     step()
     get_embeddings()
     __str__()
dicee.create_recipriocal_triples(x)
     Add inverse triples into dask dataframe :param x: :return:
dicee.get_er_vocab(data, file_path: str = None)
dicee.get_re_vocab(data, file_path: str = None)
dicee.get_ee_vocab(data, file_path: str = None)
dicee.timeit(func)
dicee.save_pickle(*, data: object = None, file_path=str)
dicee.load_pickle(file_path=str)
dicee.load_term_mapping(file_path=str)
dicee.select_model(args: dict, is_continual_training: bool = None, storage_path: str = None)
dicee.load_model(path_of_experiment_folder: str, model_name='model.pt', verbose=0)
             → Tuple[object, Tuple[dict, dict]]
     Load weights and initialize pytorch module from namespace arguments
dicee.load_model_ensemble(path_of_experiment_folder: str)
             → Tuple[dicee.models.base_model.BaseKGE, Tuple[pandas.DataFrame, pandas.DataFrame]]
     Construct Ensemble Of weights and initialize pytorch module from namespace arguments
       (1) Detect models under given path
       (2) Accumulate parameters of detected models
       (3) Normalize parameters
       (4) Insert (3) into model.
dicee.save_numpy_ndarray(*, data: numpy.ndarray, file_path: str)
dicee.numpy_data_type_changer(train\_set: numpy.ndarray, num: int) \rightarrow numpy.ndarray
     Detect most efficient data type for a given triples :param train_set: :param num: :return:
\texttt{dicee.save\_checkpoint\_model} \ (\textit{model}, \textit{path: str}) \ \rightarrow None
     Store Pytorch model into disk
```

```
dicee.store(trained_model, model_name: str = 'model', full_storage_path: str = None,
            save\_embeddings\_as\_csv=False) \rightarrow None
dicee.add\_noisy\_triples (train_set: pandas.DataFrame, add_noise_rate: float) \rightarrow pandas.DataFrame
     Add randomly constructed triples :param train_set: :param add_noise_rate: :return:
dicee.read_or_load_kg(args, cls)
dicee.intialize_model(args: dict, verbose=0) \rightarrow Tuple[object, str]
dicee.load_json(p: str) \rightarrow dict
dicee.save_embeddings(embeddings: numpy.ndarray, indexes, path: str) \rightarrow None
     Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:
dicee.random_prediction(pre_trained_kge)
dicee.deploy_triple_prediction(pre_trained_kge, str_subject, str_predicate, str_object)
dicee.deploy_tail_entity_prediction(pre_trained_kge, str_subject, str_predicate, top_k)
dicee.deploy_head_entity_prediction(pre_trained_kge, str_object, str_predicate, top_k)
dicee.deploy_relation_prediction(pre_trained_kge, str_subject, str_object, top_k)
dicee.vocab_to_parquet(vocab_to_idx, name, path_for_serialization, print_into)
dicee.create_experiment_folder(folder_name='Experiments')
dicee.continual\_training\_setup\_executor(executor) \rightarrow None
dicee.exponential_function (x: numpy.ndarray, lam: float, ascending\_order=True) \rightarrow torch.FloatTensor
dicee.load_numpy(path) \rightarrow numpy.ndarray
dicee.evaluate(entity_to_idx, scores, easy_answers, hard_answers)
     # @TODO: CD: Renamed this function Evaluate multi hop query answering on different query types
dicee.download_file(url, destination_folder='.')
dicee.download_files_from_url(base_url: str, destination_folder='.') \rightarrow None
           Parameters
                                                   "https://files.dice-research.org/projects/DiceEmbeddings/

    base_url

                                  (e.g.
                   KINSHIP-Keci-dim128-epoch256-KvsAll")
                 • destination_folder (e.g. "KINSHIP-Keci-dim128-epoch256-KvsA11")
dicee.download\_pretrained\_model(\mathit{url:str}) \rightarrow str
dicee.write_csv_from_model_parallel(path: str)
dicee.from_pretrained_model_write_embeddings_into_csv(path:str) \rightarrow None
```

```
DICE_Trainer implement
              1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html)
              2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.
              html) 3- CPU Trainer
              args
              is continual training:bool
              storage_path:str
              evaluator:
              report:dict
report
args
trainer = None
is_continual_training
storage path
evaluator = None
form_of_labelling = None
continual_start (knowledge_graph)
               (1) Initialize training.
               (2) Load model
              (3) Load trainer (3) Fit model
              Parameter
                          returns

    model

                                       • form_of_labelling (str)
initialize_trainer(callbacks: List)
                                     \rightarrow lightning.Trainer | dicee.trainer.model_parallelism.TensorParallel | dicee.trainer.torch_trainer.TorchTrainer | dicee.trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_trainer.torch_train
              Initialize Trainer from input arguments
initialize_or_load_model()
init\_dataloader (dataset: torch.utils.data.Dataset) \rightarrow torch.utils.data.DataLoader
init_dataset() \rightarrow torch.utils.data.Dataset
start (knowledge_graph: dicee.knowledge_graph.KG | numpy.memmap)
                                     → Tuple[dicee.models.base_model.BaseKGE, str]
              Start the training
               (1) Initialize Trainer
```

(2) Initialize or load a pretrained KGE model

in DDP setup, we need to load the memory map of already read/index KG.

 $k_fold_cross_validation(dataset) \rightarrow Tuple[dicee.models.base_model.BaseKGE, str]$

Perform K-fold Cross-Validation

- 1. Obtain K train and test splits.
- 2. For each split,
 - 2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.

dicee.abstracts.

3. Report the mean and average MRR.

Parameters

- self
- dataset

Returns

model

```
class dicee.KGE (path=None, url=None, construct_ensemble=False, model_name=None)
```

Bases: dicee.abstracts.BaseInteractiveKGE,

InteractiveQueryDecomposition

Knowledge Graph Embedding Class for interactive usage of pre-trained models

```
__str__()
```

to (device: str) \rightarrow None

 $get_transductive_entity_embeddings$ (indices: torch.LongTensor | List[str], as_pytorch=False, as_numpy=False, as_list=True) \rightarrow torch.FloatTensor | numpy.ndarray | List[float]

 $create_vector_database$ (collection_name: str, distance: str, location: str = 'localhost', port: int = 6333)

generate (h=", r=")

 $\verb|eval_lp_performance|| (dataset=List[Tuple[str, str, str]], filtered=True)|$

 $\label{limiting_head_entity} $$predict_missing_head_entity$$ (relation: List[str] \mid str, tail_entity: List[str] \mid str, within=None, \\ batch_size=2, topk=1, return_indices=False) $$\to $$Tuple$

Given a relation and a tail entity, return top k ranked head entity.

 $argmax_{e} in E$ f(e,r,t), where r in R, t in E.

Parameter

relation: Union[List[str], str]

String representation of selected relations.

tail_entity: Union[List[str], str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

```
Highest K scores and entities
```

```
predict_missing_relations (head_entity: List[str] | str, tail_entity: List[str] | str, within=None, batch_size=2, topk=1, return_indices=False) \rightarrow Tuple
```

Given a head entity and a tail entity, return top k ranked relations.

```
argmax_{r in R} f(h,r,t), where h, t in E.
```

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

```
predict_missing_tail_entity (head_entity: List[str] | str, relation: List[str] | str, within: List[str] = None, batch_size=2, topk=1, return_indices=False) \rightarrow torch.FloatTensor Given a head entity and a relation, return top k ranked entities argmax_{e in E} f(h,r,e), where h in E and r in R.
```

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

```
predict(*, h: List[str] | str = None, r: List[str] | str = None, t: List[str] | str = None, within=None, logits=True) <math>\rightarrow torch.FloatTensor
```

Parameters

- logits
- h
- r
- t
- within

Predict missing item in a given triple.

Returns

- If you query a single (h, r, ?) or (?, r, t) or (h, ?, t), returns List[(item, score)]
- If you query a batch of B, returns List of B such lists.

```
\label{eq:core} \begin{split} \texttt{triple\_score} \; (h: List[str] \mid str = None, \, r: \, List[str] \mid str = None, \, logits = False) \\ &\rightarrow \mathsf{torch}. \\ \mathsf{FloatTensor} \end{split}
```

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

logits: bool

If logits is True, unnormalized score returned

Returns: Tuple

pytorch tensor of triple score

```
return_multi_hop_query_results (aggregated_query_for_all_entities, k: int, only_scores)
```

```
single_hop_query_answering(query: tuple, only_scores: bool = True, k: int = None)
```

```
answer_multi_hop_query (query_type: str = None, query: Tuple[str | Tuple[str, str], Ellipsis] = None, queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, tnorm: str = 'prod', neg_norm: str = 'standard', lambda_: float = 0.0, k: int = 10, only_scores=False)

→ List[Tuple[str, torch.Tensor]]
```

@TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a static function

Find an answer set for EPFO queries including negation and disjunction

Parameter

```
query_type: str The type of the query, e.g., "2p".
```

query: Union[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.

queries: List of Tuple[Union[str, Tuple[str, str]], ...]

tnorm: str The t-norm operator.

neg_norm: str The negation norm.

lambda_: float lambda parameter for sugeno and yager negation norms

k: int The top-k substitutions for intermediate variables.

returns

```
• List[Tuple[str, torch.Tensor]]
               • Entities and corresponding scores sorted in the descening order of scores
find_missing_triples (confidence: float, entities: List[str] = None, relations: List[str] = None,
              topk: int = 10, at most: int = sys.maxsize) \rightarrow Set
          Find missing triples
          Iterative over a set of entities E and a set of relation R:
     orall e in E and orall r in R f(e.r.x)
          Return (e,r,x)
     otin G and f(e,r,x) > confidence
          confidence: float
          A threshold for an output of a sigmoid function given a triple.
          topk: int
          Highest ranked k item to select triples with f(e,r,x) > confidence.
          at most: int
          Stop after finding at_most missing triples
          \{(e,r,x) \mid f(e,r,x) > \text{confidence land } (e,r,x)\}
     otin G
deploy(share: bool = False, top \ k: int = 10)
train triples (h: List[str], r: List[str], t: List[str], labels: List[float], iteration=2, optimizer=None)
train_k_vs_all(h, r, iteration=1, lr=0.001)
     Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:
train(kg, lr=0.1, epoch=10, batch\_size=32, neg\_sample\_ratio=10, num\_workers=1) \rightarrow None
     Retrained a pretrain model on an input KG via negative sampling.
train_literals (train_file_path: str = None, num_epochs: int = 100, lit_lr: float = 0.001,
              eval_litreal_preds: bool = True, eval_file_path: str = None,
              lit_normalization_type: str = 'z-norm', batch_size: int = 1024, sampling_ratio: float = None,
             random seed=1, loader backend: str = 'pandas', freeze entity embeddings: bool = True,
              gate residual: bool = True
     Trains the Literal Embeddings model using literal data.
          Parameters
               • train_file_path (str) - Path to the training data file.
               • num_epochs (int) - Number of training epochs.
               • lit lr (float) - Learning rate for the literal model.
               • eval_litreal_preds (bool) - If True, evaluate the model after training.
               • eval_file_path (str) - Path to evaluation data file.
```

• batch_size (int) - Batch size for training.

• norm_type (str) - Normalization type to use ('z-norm', 'min-max', or None).

- sampling_ratio (float) Ratio of training triples to use.
- loader_backend (str) Backend for loading the dataset ('pandas' or 'rdflib').
- **freeze_entity_embeddings** (bool) If True, freeze the entity embeddings during training.
- gate_residual (bool) If True, use gate residual connections in the model.

```
predict_literals (entity: List[str] | str = None, attribute: List[str] | str = None, denormalize_preds: bool = True) \rightarrow numpy.ndarray
```

Predicts literal values for given entities and attributes.

Parameters

- entity (Union[List[str], str]) Entity or list of entities to predict literals for.
- attribute (Union[List[str], str]) Attribute or list of attributes to predict literals for.
- denormalize_preds (bool) If True, denormalizes the predictions.

Returns

Predictions for the given entities and attributes.

Return type

torch.FloatTensor

Evaluates the trained literal prediction model on a test file.

Parameters

- **eval_file_path** (*str*) Path to the evaluation file.
- store_lit_preds (bool) If True, stores the predictions in a CSV file.
- eval_literals (bool) If True, evaluates the literal predictions and prints error metrics.
- loader_backend (str) Backend for loading the dataset ('pandas' or 'rdflib').

Returns

None

```
dicee.mapping_from_first_two_cols_to_third(train_set_idx)
dicee.timeit(func)
dicee.load_term_mapping(file_path=str)
dicee.reload_dataset(path: str, form_of_labelling, scoring_technique, neg_ratio, label_smoothing_rate)
    Reload the files from disk to construct the Pytorch dataset
dicee_genet_rupt_dataset(* train_set; numpny_ndarray| list_valid_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test_set=None_test
```

```
class dicee.BPE NegativeSamplingDataset (train set: torch.LongTensor,
            ordered_shaped_bpe_entities: torch.LongTensor, neg_ratio: int)
```

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite __getitem__(), supporting fetching a data sample for a given key. Subclasses could also optionally overwrite __len__(), which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

1 Note

DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set
ordered_bpe_entities
num_bpe_entities
neg_ratio
num_datapoints
__len__()
\__getitem\__(idx)
collate_fn (batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]])
```

class dicee.MultiLabelDataset (train_set: torch.LongTensor, train_indices_target: torch.LongTensor, target_dim: int, torch_ordered_shaped_bpe_entities: torch.LongTensor)

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite __getitem__(), supporting fetching a data sample for a given key. Subclasses could also optionally overwrite _len__ (), which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

1 Note

DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
train_set
train_indices_target
target_dim
```

```
num_datapoints
     torch_ordered_shaped_bpe_entities
     collate_fn = None
     __len__()
     \__getitem__(idx)
class dicee.MultiClassClassificationDataset (subword_units: numpy.ndarray, block_size: int = 8)
     Bases: torch.utils.data.Dataset
     Dataset for the 1vsALL training strategy
          Parameters
                • train_set_idx - Indexed triples for the training.
                • entity_idxs - mapping.
                • relation_idxs - mapping.
                • form - ?
                                                https://pytorch.org/docs/stable/data.html#torch.utils.data.
                • num_workers -
                                           for
                                      int
                  DataLoader
          Return type
              torch.utils.data.Dataset
     train_data
     block_size = 8
     num_of_data_points
     collate_fn = None
     __len__()
     \__{getitem}_{\_}(idx)
class dicee.OnevsAllDataset (train_set_idx: numpy.ndarray, entity_idxs)
     Bases: torch.utils.data.Dataset
     Dataset for the 1vsALL training strategy
          Parameters
                • train_set_idx - Indexed triples for the training.
                • entity_idxs - mapping.
                • relation_idxs - mapping.
                • form - ?
                • num_workers - int for https://pytorch.org/docs/stable/data.html#torch.utils.data.
                  DataLoader
```

Return type

torch.utils.data.Dataset

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as D:= $\{(x,y)_i\}_i ^N$, where x: (h,r) is an unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y: denotes a multi-label vector in $[0,1]^{\{E\}}$ is a binary label.

orall y_i =1 s.t. (h r E_i) in KG



train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self: torch.utils.data.Dataset

```
>>> a = KvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

```
train_data = None
train_target = None
label_smoothing_rate
collate_fn = None
__len__()
__getitem__(idx)
```

class dicee.AllvsAll (train_set_idx: numpy.ndarray, entity_idxs, relation_idxs, label_smoothing_rate=0.0)

Bases: torch.utils.data.Dataset

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as D:= $\{(x,y)_i\}_i^n N$, where x: (h,r) is a possible unique tuple of an entity h in E and a relation r in R. Hence $N = |E| \times |R| y$: denotes a multi-label vector in $[0,1]^{\{|E|\}}$ is a binary label.



1 Note

AllysAll extends KysAll via none existing (h,r). Hence, it adds data points that are labelled without 1s.

only with 0s.

train set idx

[numpy.ndarray] n by 3 array representing n triples

entity idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self: torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
```

```
train_data = None
train_target = None
label_smoothing_rate
collate_fn = None
target_dim
__len__()
\__{getitem}_{\_}(idx)
```

class dicee.OnevsSample(train_set: numpy.ndarray, num_entities, num_relations, neg_sample_ratio: int = None, label_smoothing_rate: float = 0.0)

Bases: torch.utils.data.Dataset

A custom PyTorch Dataset class for knowledge graph embeddings, which includes both positive and negative sampling for a given dataset for multi-class classification problem..

Parameters

- train_set (np.ndarray) A numpy array containing triples of knowledge graph data. Each triple consists of (head_entity, relation, tail_entity).
- num_entities (int) The number of unique entities in the knowledge graph.
- num_relations (int) The number of unique relations in the knowledge graph.
- neg sample ratio (int, optional) The number of negative samples to be generated per positive sample. Must be a positive integer and less than num_entities.
- label_smoothing_rate (float, optional) A label smoothing rate to apply to the positive and negative labels. Defaults to 0.0.

```
train_data
```

The input data converted into a PyTorch tensor.

Type

torch.Tensor

num_entities

Number of entities in the dataset.

Type

int

num_relations

Number of relations in the dataset.

Type

int

neg_sample_ratio

Ratio of negative samples to be drawn for each positive sample.

Type

int

label_smoothing_rate

The smoothing factor applied to the labels.

Type

torch.Tensor

collate_fn

A function that can be used to collate data samples into batches (set to None by default).

Type

function, optional

train_data

num_entities

num_relations

neg_sample_ratio = None

label_smoothing_rate

collate_fn = None

__len__()

Returns the number of samples in the dataset.

 $__getitem__(idx)$

Retrieves a single data sample from the dataset at the given index.

idx (int) – The index of the sample to retrieve.

Returns

A tuple consisting of:

• x (torch.Tensor): The head and relation part of the triple.

- y_idx (torch.Tensor): The concatenated indices of the true object (tail entity) and the indices of the negative samples.
- y_vec (torch.Tensor): A vector containing the labels for the positive and negative samples, with label smoothing applied.

```
Return type tuple
```

 $__getitem__(idx)$

```
class dicee.KvsSampleDataset(train_set_idx: numpy.ndarray, entity_idxs, relation_idxs, form,
            store=None, neg_ratio=None, label_smoothing_rate: float = 0.0)
     Bases: torch.utils.data.Dataset
           KvsSample a Dataset:
               D := \{(x,y)_i\}_i \ ^N, where
                   . x:(h,r) is a unique h in E and a relation r in R and . y in [0,1]^{\{E\}} is a binary label.
     orall y_i = 1 s.t. (h r E_i) in KG
               At each mini-batch construction, we subsample(y), hence n
                   lnew_yl << |E| new_y contains all 1's if sum(y)< neg_sample ratio new_y contains</pre>
           train_set_idx
               Indexed triples for the training.
           entity_idxs
               mapping.
           relation_idxs
               mapping.
           form
           store
           label_smoothing_rate
           torch.utils.data.Dataset
     train_data = None
     train_target = None
     neg_ratio = None
     num_entities
     label_smoothing_rate
     collate_fn = None
     max_num_of_classes
     __len__()
```

```
class dicee. NegSampleDataset (train_set: numpy.ndarray, num_entities: int, num_relations: int,
             neg\_sample\_ratio: int = 1)
```

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite __getitem__(), supporting fetching a data sample for a given key. Subclasses could also optionally overwrite __len__(), which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

1 Note

DataLoader by default constructs an index sampler that yields integral indices. To make it work with a mapstyle dataset with non-integral indices/keys, a custom sampler must be provided.

```
neg_sample_ratio
      train_set
      length
      num_entities
      num_relations
      __len__()
      \__{\texttt{getitem}}__(idx)
class dicee. TriplePredictionDataset (train_set: numpy.ndarray, num_entities: int, num_relations: int,
             neg\_sample\_ratio: int = 1, label\_smoothing\_rate: float = 0.0)
      Bases: torch.utils.data.Dataset
            Triple Dataset
                D:=\{(x) \mid i \mid i \mid N, \text{ where }
                     . x:(h,r,t) in KG is a unique h in E and a relation r in R and . collact_fn => Generates
                     negative triples
                collect fn:
      orall (h,r,t) in G obtain, create negative triples \{(h,r,x),(r,t),(h,m,t)\}
                y:labels are represented in torch.float16
            train_set_idx
                Indexed triples for the training.
            entity idxs
                mapping.
            relation_idxs
                mapping.
            form
```

```
store
          label_smoothing_rate
          collate_fn: batch:List[torch.IntTensor] Returns ——- torch.utils.data.Dataset
     label_smoothing_rate
     neg_sample_ratio
     train_set
     length
     num_entities
     num_relations
     __len__()
     \__{getitem}_{\_}(idx)
     collate_fn (batch: List[torch.Tensor])
class dicee. CVDataModule (train_set_idx: numpy.ndarray, num_entities, num_relations, neg_sample_ratio,
            batch_size, num_workers)
     Bases: pytorch_lightning.LightningDataModule
     Create a Dataset for cross validation
          Parameters
                • train_set_idx - Indexed triples for the training.
                • num_entities - entity to index mapping.
                • num_relations - relation to index mapping.
                • batch_size - int
                • form - ?
                                          for https://pytorch.org/docs/stable/data.html#torch.utils.data.
                • num_workers - int
                  DataLoader
          Return type
              ?
     train_set_idx
     num_entities
     num_relations
     neg_sample_ratio
     batch_size
     num_workers
```

train_dataloader() → torch.utils.data.DataLoader

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:param-ref:~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs**` to a positive integer.

For data processing use the following pattern:

- download in prepare_data()
- process and split in setup ()

However, the above are only necessary for distributed processing.

A Warning

do not assign state in prepare_data

- fit()
- prepare_data()
- setup()

1 Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

```
setup(*args, **kwargs)
```

Called at the beginning of fit (train + validate), validate, test, or predict. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

```
stage - either 'fit', 'validate', 'test', or 'predict'
```

Example:

```
class LitModel(...):
    def __init__(self):
        self.l1 = None

def prepare_data(self):
        download_data()
        tokenize()

# don't do this
        self.something = else

def setup(self, stage):
        data = load_data(...)
        self.l1 = nn.Linear(28, data.num_classes)
```

transfer_batch_to_device(*args, **kwargs)

Override this hook if your DataLoader returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- torch. Tensor or anything that implements .to(...)
- list
- dict
- tuple

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, ...).



This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use self.trainer.training/testing/validating/predicting so that you can add different logic as per your requirement.

Parameters

- batch A batch of data that needs to be transferred to a new device.
- **device** The target device as defined in PyTorch.
- dataloader_idx The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_
    →idx)
    return batch
```

See also

- move_data_to_device()
- apply_to_collection()

```
prepare_data(*args, **kwargs)
```

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

A Warning

DO NOT set state to the model (use setup instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

# bad
self.split = data_split
self.some_state = some_other_state()
```

In a distributed environment, prepare_data can be called in two ways (using prepare_data_per_node)

- 1. Once per node. This is the default and is only called on LOCAL_RANK=0.
- 2. Once in total. Only called on GLOBAL_RANK=0.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True

# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

class dicee.QueryGenerator(train_path, val_path: str, test_path: str, ent2id: Dict = None, rel2id: Dict = None, seed: int = 1, gen_valid: bool = False, gen_test: bool = True)

```
train_path
val_path
test_path
gen_valid = False
gen_test = True
seed = 1
max_ans_num = 1000000.0
mode
ent2id = None
rel2id: Dict = None
ent_in: Dict
ent_out: Dict
query_name_to_struct
list2tuple(list data)
tuple2list(x: List | Tuple) \rightarrow List | Tuple
     Convert a nested tuple to a nested list.
set_global_seed (seed: int)
     Set seed
construct\_graph(paths: List[str]) \rightarrow Tuple[Dict, Dict]
     Construct graph from triples Returns dicts with incoming and outgoing edges
fill_query(query\_structure: List[str | List], ent_in: Dict, ent_out: Dict, answer: int) \rightarrow bool
     Private method for fill_query logic.
achieve\_answer(query: List[str \mid List], ent\_in: Dict, ent\_out: Dict) \rightarrow set
     Private method for achieve_answer logic. @TODO: Document the code
write_links (ent_out, small_ent_out)
ground_queries (query_structure: List[str | List], ent_in: Dict, ent_out: Dict, small_ent_in: Dict,
             small_ent_out: Dict, gen_num: int, query_name: str)
     Generating queries and achieving answers
unmap (query_type, queries, tp_answers, fp_answers, fn_answers)
unmap_query (query_structure, query, id2ent, id2rel)
generate_queries (query_struct: List, gen_num: int, query_type: str)
     Passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting
     queries and answers in return @ TODO: create a class for each single query struct
save_queries (query_type: str, gen_num: int, save_path: str)
abstract load_queries(path)
```

Python Module Index

d

```
dicee, 12
dicee.__main__,12
dicee.abstracts, 12
dicee.analyse_experiments, 18
dicee.callbacks, 19
dicee.config, 26
dicee.dataset_classes, 29
dicee.eval_static_funcs, 40
dicee.evaluator, 42
dicee.executer, 43
dicee.knowledge_graph, 45
dicee.knowledge_graph_embeddings,46
dicee.literal_classes, 51
dicee.models, 54
dicee.models.adopt, 54
dicee.models.base_model, 56
dicee.models.clifford, 65
dicee.models.complex, 72
dicee.models.dualE, 74
dicee.models.ensemble, 75
dicee.models.function_space, 76
dicee.models.octonion, 79
dicee.models.pykeen_models, 82
dicee.models.quaternion, 83
dicee.models.real, 87
dicee.models.static_funcs, 88
dicee.models.transformers, 88
dicee.query_generator, 142
dicee.read_preprocess_save_load_kg, 144
dicee.read_preprocess_save_load_kg.preprocess,
dicee.read_preprocess_save_load_kg.read_from_disk,
        145
dicee.read_preprocess_save_load_kg.save_load_disk,
dicee.read_preprocess_save_load_kg.util,
       146
dicee.sanity_checkers, 150
dicee.scripts, 151
dicee.scripts.index_serve, 151
dicee.scripts.run, 154
dicee.static_funcs, 154
dicee.static_funcs_training, 157
dicee.static_preprocess_funcs, 158
dicee.trainer, 159
dicee.trainer.dice_trainer, 159
dicee.trainer.model_parallelism, 161
dicee.trainer.torch_trainer, 161
dicee.trainer.torch_trainer_ddp, 163
```

Index

Non-alphabetical

```
__call__() (dicee.EnsembleKGE method), 192
 _call__() (dicee.models.base_model.IdentityClass method), 64
__call__() (dicee.models.ensemble.EnsembleKGE method), 75
__call__() (dicee.models.IdentityClass method), 105, 117, 123
__class_vars__ (dicee.scripts.index_serve.StringListRequest attribute), 152
__getitem__() (dicee.AllvsAll method), 203
__getitem__() (dicee.BPE_NegativeSamplingDataset method), 200
__getitem__() (dicee.dataset_classes.AllvsAll method), 33
\verb|\__getitem__()| (\textit{dicee.dataset\_classes.BPE\_NegativeSamplingDataset method}), 30
__getitem__() (dicee.dataset_classes.KvsAll method), 32
__getitem__() (dicee.dataset_classes.KvsSampleDataset method), 35
__getitem__() (dicee.dataset_classes.MultiClassClassificationDataset method), 31
__getitem__() (dicee.dataset_classes.MultiLabelDataset method), 30
__getitem__() (dicee.dataset_classes.NegSampleDataset method), 36
__getitem__() (dicee.dataset_classes.OnevsAllDataset method), 31
__getitem__() (dicee.dataset_classes.OnevsSample method), 34
__getitem__() (dicee.dataset_classes.TriplePredictionDataset method), 37
__getitem__() (dicee.KvsAll method), 202
__getitem__() (dicee.KvsSampleDataset method), 205
__getitem__() (dicee.literal_classes.LiteralDataset method), 54
__getitem__() (dicee.MultiClassClassificationDataset method), 201
__getitem__() (dicee.MultiLabelDataset method), 201
__getitem__() (dicee.NegSampleDataset method), 206
__getitem__() (dicee.OnevsAllDataset method), 202
__getitem__() (dicee.OnevsSample method), 204
__getitem__() (dicee.TriplePredictionDataset method), 207
__iter__() (dicee.config.Namespace method), 28
__iter__() (dicee.EnsembleKGE method), 191
__iter__() (dicee.knowledge_graph.KG method), 46
__iter__() (dicee.models.ensemble.EnsembleKGE method), 75
__len__() (dicee.AllvsAll method), 203
__len__() (dicee.BPE_NegativeSamplingDataset method), 200
__len__() (dicee.dataset_classes.AllvsAll method), 33
__len__() (dicee.dataset_classes.BPE_NegativeSamplingDataset method), 30
__len__() (dicee.dataset_classes.KvsAll method), 32
__len__() (dicee.dataset_classes.KvsSampleDataset method), 35
__len__() (dicee.dataset_classes.MultiClassClassificationDataset method), 31
__len__() (dicee.dataset_classes.MultiLabelDataset method), 30
__len__() (dicee.dataset_classes.NegSampleDataset method), 36
__len__() (dicee.dataset_classes.OnevsAllDataset method), 31
__len__() (dicee.dataset_classes.OnevsSample method), 34
__len__() (dicee.dataset_classes.TriplePredictionDataset method), 37
__len__() (dicee.EnsembleKGE method), 192
__len__() (dicee.knowledge_graph.KG method), 46
  _len__() (dicee.KvsAll method), 202
__len__() (dicee.KvsSampleDataset method), 205
__len__() (dicee.literal_classes.LiteralDataset method), 54
__len__() (dicee.models.ensemble.EnsembleKGE method), 75
__len__() (dicee.MultiClassClassificationDataset method), 201
__len__() (dicee.MultiLabelDataset method), 201
__len__() (dicee.NegSampleDataset method), 206
__len__() (dicee.OnevsAllDataset method), 202
__len__() (dicee.OnevsSample method), 204
__len__() (dicee.TriplePredictionDataset method), 207
__private_attributes__(dicee.scripts.index_serve.StringListRequest attribute). 153
__pydantic_complete__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_computed_fields__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_core_schema__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_custom_init__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_decorators__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_extra__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_fields__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_fields_set__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_generic_metadata__ (dicee.scripts.index_serve.StringListRequest attribute), 153
```

```
__pydantic_parent_namespace__(dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_post_init__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_private__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_root_model__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_serializer__(dicee.scripts.index_serve.StringListRequest attribute), 153
__pydantic_validator__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__setstate__() (dicee.models.ADOPT method), 97
__setstate__() (dicee.models.adopt.ADOPT method), 55
__signature__ (dicee.scripts.index_serve.StringListRequest attribute), 153
__str__() (dicee.EnsembleKGE method), 192
__str__() (dicee.KGE method), 195
__str__() (dicee.knowledge_graph_embeddings.KGE method), 47
__str__() (dicee.models.ensemble.EnsembleKGE method), 76
__version__ (in module dicee), 212
Α
AbstractCallback (class in dicee.abstracts), 16
AbstractPPECallback (class in dicee.abstracts), 17
AbstractTrainer (class in dicee.abstracts), 12
AccumulateEpochLossCallback (class in dicee.callbacks), 20
achieve_answer() (dicee.query_generator.QueryGenerator method), 143
achieve_answer() (dicee.QueryGenerator method), 211
AConEx (class in dicee), 178
AConEx (class in dicee.models), 112
AConEx (class in dicee.models.complex), 72
AConvo (class in dicee), 178
AConvO (class in dicee.models), 125
AConvo (class in dicee.models.octonion), 82
AConvQ (class in dicee), 179
AConvQ (class in dicee.models), 119
AConvQ (class in dicee.models.quaternion), 86
adaptive_swa (dicee.config.Namespace attribute), 28
\verb|add_new_entity_embeddings()| \textit{(dicee.abstracts.BaseInteractiveKGE method)}, 15
add_noise_rate (dicee.config.Namespace attribute), 26
add_noise_rate (dicee.knowledge_graph.KG attribute), 45
add_noisy_triples() (in module dicee), 193
add_noisy_triples() (in module dicee.static_funcs), 156
add_noisy_triples_into_training() (dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk_method), 145
add_noisy_triples_into_training() (dicee.read_preprocess_save_load_kg.ReadFromDisk method), 150
add_reciprocal (dicee.knowledge_graph.KG attribute), 45
ADOPT (class in dicee.models), 96
ADOPT (class in dicee.models.adopt), 55
adopt () (in module dicee.models.adopt), 55
AllvsAll (class in dicee), 202
AllvsAll (class in dicee.dataset_classes), 32
alphas (dicee.abstracts.AbstractPPECallback attribute), 17
alphas (dicee.callbacks.ASWA attribute), 23
analyse () (in module dicee.analyse experiments), 19
\verb"answer_multi_hop_query()" (\textit{dicee.KGE method}), 197
\verb"answer_multi_hop_query" () \textit{ (dicee.knowledge\_graph\_embeddings.KGE method)}, 49
app (in module dicee.scripts.index_serve), 152
apply_coefficients() (dicee.DeCaL method), 174
apply_coefficients() (dicee.Keci method), 170
apply_coefficients() (dicee.models.clifford.DeCaL method), 70
apply_coefficients() (dicee.models.clifford.Keci method), 66
apply_coefficients() (dicee.models.DeCaL method), 131
apply_coefficients() (dicee.models.Keci method), 127
apply_reciprical_or_noise() (in module dicee.read_preprocess_save_load_kg.util), 148
apply_semantic_constraint (dicee.abstracts.BaseInteractiveKGE attribute), 14
apply_unit_norm (dicee.BaseKGE attribute), 190
apply_unit_norm (dicee.models.base_model.BaseKGE attribute), 62
apply_unit_norm (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 120, 133, 137
args (dicee.BaseKGE attribute), 189
args (dicee.DICE_Trainer attribute), 194
args (dicee.evaluator.Evaluator attribute), 42
args (dicee.executer.Execute attribute), 43
args (dicee.models.base_model.BaseKGE attribute), 62
```

```
args (dicee.models.base model.IdentityClass attribute), 64
args (dicee.models.BaseKGE attribute), 103, 106, 110, 114, 120, 133, 136
args (dicee.models.IdentityClass attribute), 105, 117, 123
args (dicee.models.pykeen_models.PykeenKGE attribute), 83
args (dicee.models.PykeenKGE attribute), 135
args (dicee.PykeenKGE attribute), 186
args (dicee.trainer.DICE_Trainer attribute), 164
args (dicee.trainer.dice_trainer.DICE_Trainer attribute), 159
ASWA (class in dicee.callbacks), 23
aswa (dicee.analyse_experiments.Experiment attribute), 18
attn (dicee.models.transformers.Block attribute), 93
\verb|attn_dropout| \textit{(dicee.models.transformers.CausalSelfAttention attribute)}, 92
attributes (dicee.abstracts.AbstractTrainer attribute), 12
auto_batch_finding (dicee.config.Namespace attribute), 28
В
backend (dicee.config.Namespace attribute), 27
backend (dicee.knowledge_graph.KG attribute), 46
BaseInteractiveKGE (class in dicee.abstracts), 14
BaseKGE (class in dicee), 189
BaseKGE (class in dicee.models), 102, 106, 109, 114, 120, 132, 136
BaseKGE (class in dicee.models.base_model), 61
BaseKGELightning (class in dicee.models), 97
BaseKGELightning (class in dicee.models.base_model), 56
batch_kronecker_product() (dicee.callbacks.KronE static method), 25
batch_size (dicee.analyse_experiments.Experiment attribute), 18
batch_size (dicee.callbacks.PseudoLabellingCallback attribute), 22
batch_size (dicee.config.Namespace attribute), 26
batch_size (dicee.CVDataModule attribute), 207
batch_size (dicee.dataset_classes.CVDataModule attribute), 37
bias (dicee.models.transformers.GPTConfig attribute), 94
bias (dicee.models.transformers.LayerNorm attribute), 91
Block (class in dicee.models.transformers), 93
block_size (dicee.BaseKGE attribute), 190
block_size (dicee.config.Namespace attribute), 28
block_size (dicee.dataset_classes.MultiClassClassificationDataset attribute), 31
block_size (dicee.models.base_model.BaseKGE attribute), 63
block_size (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
block_size (dicee.models.transformers.GPTConfig attribute), 94
block_size (dicee.MultiClassClassificationDataset attribute), 201
bn conv1 (dicee.AConvO attribute), 179
bn_conv1 (dicee.ConvQ attribute), 180
bn_conv1 (dicee.models.AConvQ attribute), 119
bn_conv1 (dicee.models.ConvQ attribute), 119
bn_conv1 (dicee.models.quaternion.AConvQ attribute), 86
bn_conv1 (dicee.models.quaternion.ConvQ attribute), 85
bn_conv2 (dicee.AConvQ attribute), 179
bn_conv2 (dicee.ConvQ attribute), 180
bn_conv2 (dicee.models.AConvQ attribute), 119
bn_conv2 (dicee.models.ConvQ attribute), 119
bn_conv2 (dicee.models.quaternion.AConvQ attribute), 86
bn\_conv2 (dicee.models.quaternion.ConvQ attribute), 86
bn_conv2d (dicee.AConEx attribute), 178
bn_conv2d (dicee.AConvO attribute), 179
bn_conv2d (dicee.ConEx attribute), 181
bn_conv2d (dicee.ConvO attribute), 181
bn_conv2d (dicee.models.AConEx attribute), 112
bn_conv2d (dicee.models.AConvO attribute), 125
bn_conv2d (dicee.models.complex.AConEx attribute), 73
bn_conv2d (dicee.models.complex.ConEx attribute), 72
bn_conv2d (dicee.models.ConEx attribute), 112
bn_conv2d (dicee.models.ConvO attribute), 125
bn_conv2d (dicee.models.octonion.AConvO attribute), 82
bn_conv2d (dicee.models.octonion.ConvO attribute), 81
BPE_NegativeSamplingDataset (class in dicee), 199
BPE_NegativeSamplingDataset (class in dicee.dataset_classes), 29
build_chain_funcs() (dicee.models.FMult2 method), 139
```

```
build chain funcs () (dicee.models.function space.FMult2 method), 77
build_func() (dicee.models.FMult2 method), 139
build_func() (dicee.models.function_space.FMult2 method), 77
BytE (class in dicee), 187
BytE (class in dicee.models.transformers), 89
byte_pair_encoding (dicee.analyse_experiments.Experiment attribute), 18
byte_pair_encoding (dicee.BaseKGE attribute), 190
byte pair encoding (dicee.config.Namespace attribute), 28
byte_pair_encoding (dicee.knowledge_graph.KG attribute), 45
byte_pair_encoding (dicee.models.base_model.BaseKGE attribute), 63
byte_pair_encoding (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
С
c_attn (dicee.models.transformers.CausalSelfAttention attribute), 92
c_fc (dicee.models.transformers.MLP attribute), 93
c_proj (dicee.models.transformers.CausalSelfAttention attribute), 92
c_proj (dicee.models.transformers.MLP attribute), 93
callbacks (dicee.abstracts.AbstractTrainer attribute), 12
callbacks (dicee.analyse_experiments.Experiment attribute), 18
callbacks (dicee.config.Namespace attribute), 27
callbacks (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 164
CausalSelfAttention (class in dicee.models.transformers), 91
chain_func() (dicee.models.FMult method), 139
chain_func() (dicee.models.function_space.FMult method), 76
chain_func() (dicee.models.function_space.GFMult method), 77
chain_func() (dicee.models.GFMult method), 139
CKeci (class in dicee), 169
CKeci (class in dicee.models), 129
CKeci (class in dicee.models.clifford), 68
cl_pqr() (dicee.DeCaL method), 173
cl_pgr() (dicee.models.clifford.DeCaL method), 69
cl_pqr() (dicee.models.DeCaL method), 130
clifford_multiplication() (dicee.Keci method), 171
clifford_multiplication() (dicee.models.clifford.Keci method), 66
clifford_multiplication() (dicee.models.Keci method), 127
clip_lambda (dicee.models.ADOPT attribute), 97
clip_lambda (dicee.models.adopt.ADOPT attribute), 55
collate fn (dicee. Allvs All attribute), 203
collate_fn (dicee.dataset_classes.AllvsAll attribute), 33
collate_fn (dicee.dataset_classes.KvsAll attribute), 32
collate fn (dicee.dataset classes.KvsSampleDataset attribute), 35
collate_fn (dicee.dataset_classes.MultiClassClassificationDataset attribute), 31
collate_fn (dicee.dataset_classes.MultiLabelDataset attribute), 30
collate_fn (dicee.dataset_classes.OnevsAllDataset attribute), 31
collate_fn (dicee.dataset_classes.OnevsSample attribute), 34
collate_fn (dicee.KvsAll attribute), 202
\verb"collate_fn" (\textit{dicee.KvsSampleDataset attribute}), 205
collate fn (dicee.MultiClassClassificationDataset attribute), 201
collate_fn (dicee.MultiLabelDataset attribute), 201
collate_fn (dicee.OnevsAllDataset attribute), 202
collate_fn (dicee.OnevsSample attribute), 204
collate_fn() (dicee.BPE_NegativeSamplingDataset method), 200
collate_fn() (dicee.dataset_classes.BPE_NegativeSamplingDataset method), 30
collate_fn() (dicee.dataset_classes.TriplePredictionDataset method), 37
collate_fn() (dicee.TriplePredictionDataset method), 207
collection_name (dicee.scripts.index_serve.NeuralSearcher attribute), 152
comp_func() (dicee.LFMult method), 185
comp_func() (dicee.models.function_space.LFMult method), 79
comp_func() (dicee.models.LFMult method), 141
Complex (class in dicee), 177
Complex (class in dicee.models), 113
Complex (class in dicee.models.complex), 73
compute_convergence() (in module dicee.callbacks), 23
compute_func() (dicee.models.FMult method), 138
compute_func() (dicee.models.FMult2 method), 139
compute_func() (dicee.models.function_space.FMult method), 76
compute_func() (dicee.models.function_space.FMult2 method), 77
```

```
compute func() (dicee.models.function space.GFMult method), 77
compute_func() (dicee.models.GFMult method), 139
compute_mrr() (dicee.callbacks.ASWA static method), 23
compute_sigma_pp() (dicee.DeCaL method), 174
compute_sigma_pp() (dicee.Keci method), 170
compute_sigma_pp() (dicee.models.clifford.DeCaL method), 70
compute_sigma_pp() (dicee.models.clifford.Keci method), 65
compute_sigma_pp() (dicee.models.DeCaL method), 131
compute_sigma_pp() (dicee.models.Keci method), 126
compute_sigma_pq() (dicee.DeCaL method), 175
compute_sigma_pq() (dicee.Keci method), 170
\verb|compute_sigma_pq()| \textit{ (dicee.models.clifford.DeCaL method)}, 71
compute_sigma_pq() (dicee.models.clifford.Keci method), 66
compute_sigma_pq() (dicee.models.DeCaL method), 132
compute_sigma_pq() (dicee.models.Keci method), 127
compute_sigma_pr() (dicee.DeCaL method), 175
compute_sigma_pr() (dicee.models.clifford.DeCaL method), 71
compute_sigma_pr() (dicee.models.DeCaL method), 132
compute_sigma_qq() (dicee.DeCaL method), 175
compute_sigma_qq() (dicee.Keci method), 170
compute_sigma_qq() (dicee.models.clifford.DeCaL method), 70
compute_sigma_qq() (dicee.models.clifford.Keci method), 66
compute_sigma_gq() (dicee.models.DeCaL method), 131
compute_sigma_qq() (dicee.models.Keci method), 127
compute_sigma_gr() (dicee.DeCaL method), 176
compute_sigma_qr() (dicee.models.clifford.DeCaL method), 71
compute_sigma_qr() (dicee.models.DeCaL method), 132
compute_sigma_rr() (dicee.DeCaL method), 175
\verb|compute_sigma_rr()| \textit{ (dicee.models.clifford.DeCaL method)}, 71
compute_sigma_rr() (dicee.models.DeCaL method), 132
compute_sigmas_multivect() (dicee.DeCaL method), 174
compute_sigmas_multivect() (dicee.models.clifford.DeCaL method), 69
compute_sigmas_multivect() (dicee.models.DeCaL method), 130
compute_sigmas_single() (dicee.DeCaL method), 173
compute_sigmas_single() (dicee.models.clifford.DeCaL method), 69
\verb|compute_sigmas_single()| \textit{(dicee.models.DeCaL method)}, 130
ConEx (class in dicee), 181
ConEx (class in dicee.models), 112
ConEx (class in dicee.models.complex), 72
config (dicee.BytE attribute), 187
config (dicee.models.transformers.BytE attribute), 89
config (dicee.models.transformers.GPT attribute), 94
configs (dicee.abstracts.BaseInteractiveKGE attribute), 14
configure_optimizers() (dicee.models.base_model.BaseKGELightning method), 60
configure_optimizers() (dicee.models.BaseKGELightning method), 101
configure_optimizers() (dicee.models.transformers.GPT method), 95
construct_batch_selected_cl_multivector() (dicee.Keci method), 171
construct_batch_selected_cl_multivector() (dicee.models.clifford.Keci method), 67
construct_batch_selected_cl_multivector() (dicee.models.Keci method), 128
construct_cl_multivector() (dicee.DeCaL method), 174
construct_cl_multivector() (dicee.Keci method), 171
construct_cl_multivector() (dicee.models.clifford.DeCaL method), 70
construct_cl_multivector() (dicee.models.clifford.Keci method), 67
construct_cl_multivector() (dicee.models.DeCaL method), 131
construct_cl_multivector() (dicee.models.Keci method), 127
construct_dataset() (in module dicee), 199
construct_dataset() (in module dicee.dataset_classes), 29
construct_ensemble (dicee.abstracts.BaseInteractiveKGE attribute), 14
construct_graph() (dicee.query_generator.QueryGenerator method), 143
construct_graph() (dicee.QueryGenerator method), 211
construct_input_and_output() (dicee.abstracts.BaseInteractiveKGE method), 15
construct_multi_coeff() (dicee.LFMult method), 185
construct_multi_coeff() (dicee.models.function_space.LFMult method), 78
construct_multi_coeff() (dicee.models.LFMult method), 140
continual_learning (dicee.config.Namespace attribute), 28
continual_start() (dicee.DICE_Trainer method), 194
continual_start() (dicee.executer.ContinuousExecute method), 44
continual_start() (dicee.trainer.DICE_Trainer method), 164
```

```
continual start() (dicee.trainer.dice trainer.DICE Trainer method), 160
continual_training_setup_executor() (in module dicee), 193
continual_training_setup_executor() (in module dicee.static_funcs), 157
Continuous Execute (class in dicee.executer), 44
conv2d (dicee.AConEx attribute), 178
conv2d (dicee.AConvO attribute), 178
conv2d (dicee.AConvQ attribute), 179
conv2d (dicee.ConEx attribute), 181
conv2d (dicee.ConvO attribute), 181
conv2d (dicee.ConvQ attribute), 180
conv2d (dicee.models.AConEx attribute), 112
conv2d (dicee.models.AConvO attribute), 125
conv2d (dicee.models.AConvQ attribute), 119
conv2d (dicee.models.complex.AConEx attribute), 72
conv2d (dicee.models.complex.ConEx attribute), 72
conv2d (dicee.models.ConEx attribute), 112
conv2d (dicee.models.ConvO attribute), 124
conv2d (dicee.models.ConvQ attribute), 119
conv2d (dicee.models.octonion.AConvO attribute), 82
conv2d (dicee.models.octonion.ConvO attribute), 81
conv2d (dicee.models.quaternion.AConvQ attribute), 86
conv2d (dicee.models.quaternion.ConvQ attribute), 85
ConvO (class in dicee), 180
ConvO (class in dicee.models), 124
ConvO (class in dicee.models.octonion), 80
ConvQ (class in dicee), 179
ConvQ (class in dicee.models), 118
ConvQ (class in dicee.models.quaternion), 85
create_constraints() (in module dicee.read_preprocess_save_load_kg.util), 148
create_constraints() (in module dicee.static_preprocess_funcs), 158
create_experiment_folder() (in module dicee), 193
create_experiment_folder() (in module dicee.static_funcs), 157
create_random_data() (dicee.callbacks.PseudoLabellingCallback method), 22
create_recipriocal_triples() (in module dicee), 192
create_recipriocal_triples() (in module dicee.read_preprocess_save_load_kg.util), 149
create_recipriocal_triples() (in module dicee.static_funcs), 155
create_vector_database() (dicee.KGE method), 195
create_vector_database() (dicee.knowledge_graph_embeddings.KGE method), 47
crop_block_size() (dicee.models.transformers.GPT method), 95
ctx (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 164
CVDataModule (class in dicee), 207
CVDataModule (class in dicee.dataset_classes), 37
D
\verb|data_module| (\textit{dicee.callbacks.PseudoLabellingCallback attribute}), 22
data_property_embeddings (dicee.literal_classes.LiteralEmbeddings attribute), 52
data_property_to_idx (dicee.literal_classes.LiteralDataset attribute), 53
dataset_dir (dicee.config.Namespace attribute), 26
dataset_dir (dicee.knowledge_graph.KG attribute), 45
dataset_sanity_checking() (in module dicee.read_preprocess_save_load_kg.util), 149
DeCaL (class in dicee), 172
DeCaL (class in dicee.models), 129
DeCal (class in dicee.models.clifford), 68
decide() (dicee.callbacks.ASWA method), 23
degree (dicee.LFMult attribute), 185
degree (dicee.models.function_space.LFMult attribute), 78
degree (dicee.models.LFMult attribute), 140
denormalize() (dicee.literal_classes.LiteralDataset static method), 54
deploy() (dicee.KGE method), 198
deploy() (dicee.knowledge_graph_embeddings.KGE method), 50
deploy_head_entity_prediction() (in module dicee), 193
deploy_head_entity_prediction() (in module dicee.static_funcs), 156
deploy_relation_prediction() (in module dicee), 193
deploy_relation_prediction() (in module dicee.static_funcs), 157
deploy_tail_entity_prediction() (in module dicee), 193
deploy_tail_entity_prediction() (in module dicee.static_funcs), 156
deploy_triple_prediction() (in module dicee), 193
```

```
deploy_triple_prediction() (in module dicee.static_funcs), 156
describe() (dicee.knowledge_graph.KG method), 46
description_of_input (dicee.knowledge_graph.KG attribute), 46
DICE_Trainer (class in dicee), 193
DICE_Trainer (class in dicee.trainer), 164
DICE_Trainer (class in dicee.trainer.dice_trainer), 159
dicee
    module, 12
dicee.___main__
    module, 12
dicee.abstracts
    module, 12
dicee.analyse_experiments
    module, 18
dicee.callbacks
    module, 19
dicee.config
    module, 26
dicee.dataset_classes
    module, 29
dicee.eval_static_funcs
    module, 40
dicee.evaluator
    module, 42
dicee.executer
    module, 43
{\tt dicee.knowledge\_graph}
    module, 45
\verb|dicee.knowledge_graph_embeddings|
    module, 46
dicee.literal_classes
    module, 51
dicee.models
    module, 54
dicee.models.adopt
    module, 54
dicee.models.base_model
    module, 56
dicee.models.clifford
    module, 65
dicee.models.complex
    module, 72
dicee.models.dualE
    module, 74
dicee.models.ensemble
    module, 75
dicee.models.function_space
    module, 76
dicee.models.octonion
    module, 79
dicee.models.pykeen_models
    module, 82
dicee.models.quaternion
    module, 83
dicee.models.real
    module, 87
dicee.models.static_funcs
    module, 88
dicee.models.transformers
    module, 88
dicee.query_generator
    module, 142
dicee.read_preprocess_save_load_kg
    module, 144
dicee.read_preprocess_save_load_kg.preprocess
    module, 144
dicee.read_preprocess_save_load_kg.read_from_disk
    module, 145
```

```
dicee.read_preprocess_save_load_kg.save_load_disk
     module, 145
dicee.read_preprocess_save_load_kg.util
     module, 146
dicee.sanity_checkers
     module, 150
dicee.scripts
    module, 151
dicee.scripts.index_serve
     module, 151
dicee.scripts.run
     module, 154
dicee.static_funcs
     module, 154
dicee.static_funcs_training
     module, 157
dicee.static_preprocess_funcs
    module, 158
dicee.trainer
     module, 159
dicee.trainer.dice_trainer
     module, 159
dicee.trainer.model_parallelism
     module, 161
dicee.trainer.torch_trainer
     module, 161
dicee.trainer.torch_trainer_ddp
     module, 163
discrete_points (dicee.models.FMult2 attribute), 139
discrete_points (dicee.models.function_space.FMult2 attribute), 77
dist_func (dicee.models.Pyke attribute), 109
dist func (dicee.models.real.Pyke attribute), 88
dist_func (dicee.Pyke attribute), 168
DistMult (class in dicee), 168
DistMult (class in dicee.models), 108
DistMult (class in dicee.models.real), 87
download file() (in module dicee), 193
download_file() (in module dicee.static_funcs), 157
download_files_from_url() (in module dicee), 193
download_files_from_url() (in module dicee.static_funcs), 157
download_pretrained_model() (in module dicee), 193
download_pretrained_model() (in module dicee.static_funcs), 157
dropout (dicee.literal_classes.LiteralEmbeddings attribute), 52
dropout (dicee.models.transformers.CausalSelfAttention attribute), 92
dropout (dicee.models.transformers.GPTConfig attribute), 94
dropout (dicee.models.transformers.MLP attribute), 93
DualE (class in dicee), 176
DualE (class in dicee.models), 141
DualE (class in dicee.models.dualE), 74
dummy_eval() (dicee.evaluator.Evaluator method), 43
\verb|dummy_id| (\textit{dicee.knowledge\_graph.KG attribute}), 46
during_training (dicee.evaluator.Evaluator attribute), 42
Ε
ee vocab (dicee.evaluator.Evaluator attribute), 42
efficient_zero_grad() (in module dicee.static_funcs_training), 158
embedding_dim (dicee.analyse_experiments.Experiment attribute), 18
embedding_dim (dicee.BaseKGE attribute), 189
embedding_dim (dicee.config.Namespace attribute), 26
embedding_dim (dicee.literal_classes.LiteralEmbeddings attribute), 52
embedding_dim (dicee.models.base_model.BaseKGE attribute), 62
embedding_dim (dicee.models.BaseKGE attribute), 103, 106, 110, 114, 120, 133, 136
embedding_dims (dicee.literal_classes.LiteralEmbeddings attribute), 52
enable_log (in module dicee.static_preprocess_funcs), 158
enc (dicee.knowledge_graph.KG attribute), 46
end() (dicee.executer.Execute method), 44
EnsembleKGE (class in dicee), 191
```

```
EnsembleKGE (class in dicee.models.ensemble), 75
ent2id (dicee.query_generator.QueryGenerator attribute), 143
ent2id (dicee.QueryGenerator attribute), 211
ent_in (dicee.query_generator.QueryGenerator attribute), 143
ent_in (dicee.QueryGenerator attribute), 211
ent_out (dicee.query_generator.QueryGenerator attribute), 143
ent_out (dicee.QueryGenerator attribute), 211
entities_str (dicee.knowledge_graph.KG property), 46
entity_embeddings (dicee.AConvQ attribute), 179
entity_embeddings (dicee.ConvQ attribute), 180
entity_embeddings (dicee.DeCaL attribute), 173
entity_embeddings (dicee.DualE attribute), 176
entity_embeddings (dicee.LFMult attribute), 185
entity_embeddings (dicee.literal_classes.LiteralEmbeddings attribute), 52
entity_embeddings (dicee.models.AConvQ attribute), 119
entity_embeddings (dicee.models.clifford.DeCaL attribute), 69
entity_embeddings (dicee.models.ConvQ attribute), 119
entity_embeddings (dicee.models.DeCaL attribute), 129
entity_embeddings (dicee.models.DualE attribute), 141
entity_embeddings (dicee.models.dualE.DualE attribute), 74
entity_embeddings (dicee.models.FMult attribute), 138
entity_embeddings (dicee.models.FMult2 attribute), 139
entity_embeddings (dicee.models.function_space.FMult attribute), 76
entity_embeddings (dicee.models.function_space.FMult2 attribute), 77
entity_embeddings (dicee.models.function_space.GFMult attribute), 77
entity_embeddings (dicee.models.function_space.LFMult attribute), 78
entity_embeddings (dicee.models.function_space.LFMult1 attribute), 78
entity_embeddings (dicee.models.GFMult attribute), 139
entity_embeddings (dicee.models.LFMult attribute), 140
entity_embeddings (dicee.models.LFMult1 attribute), 140
entity_embeddings (dicee.models.pykeen_models.PykeenKGE attribute), 83
entity embeddings (dicee.models.PykeenKGE attribute), 135
entity_embeddings (dicee.models.quaternion.AConvQ attribute), 86
entity_embeddings (dicee.models.quaternion.ConvQ attribute), 85
entity_embeddings (dicee.PykeenKGE attribute), 186
\verb"entity_to_idx" (\textit{dicee.knowledge\_graph.KG"} attribute), 45
entity to idx (dicee.literal classes.LiteralDataset attribute), 53, 54
entity_to_idx (dicee.scripts.index_serve.NeuralSearcher attribute), 152
epoch_count (dicee.abstracts.AbstractPPECallback attribute), 17
epoch_count (dicee.callbacks.ASWA attribute), 23
epoch_counter (dicee.callbacks.Eval attribute), 24
epoch_counter (dicee.callbacks.KGESaveCallback attribute), 21
epoch_ratio (dicee.callbacks.Eval attribute), 24
er_vocab (dicee.evaluator.Evaluator attribute), 42
estimate_mfu() (dicee.models.transformers.GPT method), 95
estimate_q() (in module dicee.callbacks), 22
Eval (class in dicee.callbacks), 24
eval() (dicee.EnsembleKGE method), 192
eval () (dicee.evaluator.Evaluator method), 42
eval() (dicee.models.ensemble.EnsembleKGE method), 75
eval_lp_performance() (dicee.KGE method), 195
eval_lp_performance() (dicee.knowledge_graph_embeddings.KGE method), 47
eval_model (dicee.config.Namespace attribute), 27
eval_model (dicee.knowledge_graph.KG attribute), 45
eval_rank_of_head_and_tail_byte_pair_encoded_entity() (dicee.evaluator.Evaluator method), 42
eval_rank_of_head_and_tail_entity() (dicee.evaluator.Evaluator method), 42
eval_with_bpe_vs_all() (dicee.evaluator.Evaluator method), 42
\verb| eval_with_byte()| \textit{ (dicee. evaluator. Evaluator method)}, 42
eval_with_data() (dicee.evaluator.Evaluator method), 43
eval_with_vs_all() (dicee.evaluator.Evaluator method), 42
evaluate () (in module dicee), 193
evaluate() (in module dicee.static_funcs), 157
\verb|evaluate_bpe_lp()| \textit{(in module dicee.static\_funcs\_training)}, 158
evaluate_link_prediction_performance() (in module dicee.eval_static_funcs), 41
evaluate_link_prediction_performance_with_bpe() (in module dicee.eval_static_funcs), 41
evaluate\_link\_prediction\_performance\_with\_bpe\_reciprocals () \textit{ (in module dicee.eval\_static\_funcs)}, 41
evaluate_link_prediction_performance_with_reciprocals() (in module dicee.eval_static_funcs), 41
evaluate_literal_prediction() (dicee.KGE method), 199
```

```
evaluate_literal_prediction() (dicee.knowledge_graph_embeddings.KGE method), 51
evaluate_lp() (dicee.evaluator.Evaluator method), 43
evaluate_lp() (in module dicee.static_funcs_training), 157
evaluate_lp_bpe_k_vs_all() (dicee.evaluator.Evaluator method), 43
evaluate_lp_bpe_k_vs_all() (in module dicee.eval_static_funcs), 41
evaluate_lp_k_vs_all() (dicee.evaluator.Evaluator method), 43
evaluate_lp_with_byte() (dicee.evaluator.Evaluator method), 43
Evaluator (class in dicee.evaluator), 42
evaluator (dicee.DICE_Trainer attribute), 194
evaluator (dicee.executer.Execute attribute), 43
evaluator (dicee.trainer.DICE_Trainer attribute), 164
\verb|evaluator| \textit{(dicee.trainer.dice\_trainer.DICE\_Trainer attribute)}, 160
every_x_epoch (dicee.callbacks.KGESaveCallback attribute), 21
example_input_array (dicee.EnsembleKGE property), 191
\verb|example_input_array| (\textit{dicee.models.ensemble.EnsembleKGE property}), 75
Execute (class in dicee.executer), 43
\verb|exists()| (\textit{dicee.knowledge\_graph.KG method}), 46
Experiment (class in dicee.analyse_experiments), 18
explicit (dicee.models.QMult attribute), 118
explicit (dicee.models.quaternion.QMult attribute), 84
explicit (dicee.QMult attribute), 182
exponential_function() (in module dicee), 193
exponential_function() (in module dicee.static_funcs), 157
\verb|extract_input_outputs()| \textit{(dicee.trainer.torch\_trainer\_ddp.NodeTrainer method)}, 164
extract_input_outputs() (in module dicee.trainer.model_parallelism), 161
extract_input_outputs_set_device() (dicee.trainer.torch_trainer.TorchTrainer method), 162
F
f (dicee.callbacks.KronE attribute), 25
fc (dicee.literal_classes.LiteralEmbeddings attribute), 52
fc1 (dicee.AConEx attribute), 178
fc1 (dicee.AConvO attribute), 178
fc1 (dicee.AConvQ attribute), 179
fc1 (dicee.ConEx attribute), 181
fc1 (dicee.ConvO attribute), 181
fc1 (dicee.ConvQ attribute), 180
fc1 (dicee.models.AConEx attribute), 112
fc1 (dicee.models.AConvO attribute), 125
fc1 (dicee.models.AConvQ attribute), 119
fc1 (dicee.models.complex.AConEx attribute), 72
fc1 (dicee.models.complex.ConEx attribute), 72
fc1 (dicee.models.ConEx attribute), 112
fc1 (dicee.models.ConvO attribute), 125
fc1 (dicee.models.ConvQ attribute), 119
fc1 (dicee.models.octonion.AConvO attribute), 82
fc1 (dicee.models.octonion.ConvO attribute), 81
fc1 (dicee.models.quaternion.AConvQ attribute), 86
fc1 (dicee.models.quaternion.ConvO attribute), 85
fc_num_input (dicee.AConEx attribute), 178
fc_num_input (dicee.AConvO attribute), 178
fc_num_input (dicee.AConvQ attribute), 179
fc_num_input (dicee.ConEx attribute), 181
fc_num_input (dicee.ConvO attribute), 181
fc_num_input (dicee.ConvQ attribute), 180
fc_num_input (dicee.models.AConEx attribute), 112
fc_num_input (dicee.models.AConvO attribute), 125
fc_num_input (dicee.models.AConvQ attribute), 119
fc_num_input (dicee.models.complex.AConEx attribute), 72
fc_num_input (dicee.models.complex.ConEx attribute), 72
fc_num_input (dicee.models.ConEx attribute), 112
fc_num_input (dicee.models.ConvO attribute), 124
fc_num_input (dicee.models.ConvQ attribute), 119
fc_num_input (dicee.models.octonion.AConvO attribute), 82
fc_num_input (dicee.models.octonion.ConvO attribute), 81
fc_num_input (dicee.models.quaternion.AConvQ attribute), 86
fc_num_input (dicee.models.quaternion.ConvQ attribute), 85
fc_out (dicee.literal_classes.LiteralEmbeddings attribute), 52
```

```
feature_map_dropout (dicee.AConEx attribute), 178
feature_map_dropout (dicee.AConvO attribute), 179
{\tt feature\_map\_dropout}~(\textit{dicee.AConvQ attribute}),~179
feature_map_dropout (dicee.ConEx attribute), 181
feature_map_dropout (dicee.ConvO attribute), 181
feature_map_dropout (dicee.ConvQ attribute), 180
feature_map_dropout (dicee.models.AConEx attribute), 112
feature_map_dropout (dicee.models.AConvO attribute), 125
feature_map_dropout (dicee.models.AConvQ attribute), 119
feature_map_dropout (dicee.models.complex.AConEx attribute), 73
feature_map_dropout (dicee.models.complex.ConEx attribute), 72
feature_map_dropout (dicee.models.ConEx attribute), 112
feature_map_dropout (dicee.models.ConvO attribute), 125
feature_map_dropout (dicee.models.ConvQ attribute), 119
feature_map_dropout (dicee.models.octonion.AConvO attribute), 82
feature_map_dropout (dicee.models.octonion.ConvO attribute), 81
feature_map_dropout (dicee.models.quaternion.AConvQ attribute), 86
feature_map_dropout (dicee.models.quaternion.ConvQ attribute), 86
feature_map_dropout_rate (dicee.BaseKGE attribute), 190
feature_map_dropout_rate (dicee.config.Namespace attribute), 28
feature_map_dropout_rate (dicee.models.base_model.BaseKGE attribute), 62
feature_map_dropout_rate (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 121, 133, 137
fill_query() (dicee.query_generator.QueryGenerator method), 143
fill_query() (dicee.QueryGenerator method), 211
find_good_batch_size() (in module dicee.trainer.model_parallelism), 161
find_missing_triples() (dicee.KGE method), 198
\verb|find_missing_triples()| (\textit{dicee.knowledge\_graph\_embeddings.KGE method}), 49
fit () (dicee.trainer.model_parallelism.TensorParallel method), 161
fit () (dicee.trainer.torch_trainer_ddp.TorchDDPTrainer method), 163
fit () (dicee.trainer.torch_trainer.TorchTrainer method), 162
flash (dicee.models.transformers.CausalSelfAttention attribute), 92
FMult (class in dicee.models), 138
FMult (class in dicee.models.function_space), 76
FMult2 (class in dicee.models), 139
FMult2 (class in dicee.models.function_space), 77
form_of_labelling (dicee.DICE_Trainer attribute), 194
form of labelling (dicee.trainer.DICE Trainer attribute), 164
form_of_labelling (dicee.trainer.dice_trainer.DICE_Trainer attribute), 160
forward() (dicee.BaseKGE method), 191
forward() (dicee.BytE method), 188
forward() (dicee.literal_classes.GatedLinearUnit method), 51
forward() (dicee.literal_classes.LiteralEmbeddings method), 52
forward() (dicee.models.base_model.BaseKGE method), 63
forward() (dicee.models.base_model.IdentityClass static method), 64
forward() (dicee.models.BaseKGE method), 104, 107, 111, 116, 121, 134, 137
forward() (dicee.models.IdentityClass static method), 105, 117, 123
forward() (dicee.models.transformers.Block method), 94
forward() (dicee.models.transformers.BytE method), 90
forward() (dicee.models.transformers.CausalSelfAttention method), 92
forward() (dicee.models.transformers.GPT method), 95
forward () (dicee.models.transformers.LayerNorm method), 91
forward() (dicee.models.transformers.MLP method), 93
\verb|forward_backward_update()| \textit{(dicee.trainer.torch\_trainer.TorchTrainer method)}, 162
forward_backward_update_loss() (in module dicee.trainer.model_parallelism), 161
forward_byte_pair_encoded_k_vs_all() (dicee.BaseKGE method), 190
\verb|forward_byte_pair_encoded_k_vs_all()| \textit{(dicee.models.base\_model.BaseKGE method)}, 63
forward_byte_pair_encoded_k_vs_all() (dicee.models.BaseKGE method), 104, 107, 111, 115, 121, 134, 137
{\tt forward\_byte\_pair\_encoded\_triple()} \ (\textit{dicee.BaseKGE method}), 190
forward_byte_pair_encoded_triple() (dicee.models.base_model.BaseKGE method), 63
forward_byte_pair_encoded_triple() (dicee.models.BaseKGE method), 104, 107, 111, 115, 121, 134, 137
forward_k_vs_all() (dicee.AConEx method), 178
forward_k_vs_all() (dicee.AConvO method), 179
forward_k_vs_all() (dicee.AConvQ method), 179
forward_k_vs_all() (dicee.BaseKGE method), 191
forward_k_vs_all() (dicee.ComplEx method), 178
forward_k_vs_all() (dicee.ConEx method), 182
forward_k_vs_all() (dicee.ConvO method), 181
forward_k\_vs\_all() (dicee.ConvQ method), 180
```

```
forward_k_vs_all() (dicee.DeCaL method), 174
forward_k_vs_all() (dicee.DistMult method), 169
forward_k_vs_all() (dicee.DualE method), 177
forward_k_vs_all() (dicee.Keci method), 171
forward_k_vs_all() (dicee.models.AConEx method), 113
forward_k_vs_all() (dicee.models.AConvO method), 125
forward_k_vs_all() (dicee.models.AConvQ method), 120
forward k vs all() (dicee.models.base model.BaseKGE method), 63
forward_k_vs_all() (dicee.models.BaseKGE method), 104, 108, 111, 116, 122, 134, 138
forward_k_vs_all() (dicee.models.clifford.DeCaL method), 69
forward_k_vs_all() (dicee.models.clifford.Keci method), 67
forward_k_vs_all() (dicee.models.ComplEx method), 114
forward_k_vs_all() (dicee.models.complex.AConEx method), 73
forward_k_vs_all() (dicee.models.complex.ComplEx method), 74
forward_k_vs_all() (dicee.models.complex.ConEx method), 72
forward_k_vs_all() (dicee.models.ConEx method), 112
forward_k_vs_all() (dicee.models.ConvO method), 125
forward_k_vs_all() (dicee.models.ConvQ method), 119
forward_k_vs_all() (dicee.models.DeCaL method), 130
forward_k_vs_all() (dicee.models.DistMult method), 108
forward_k_vs_all() (dicee.models.DualE method), 142
forward_k_vs_all() (dicee.models.dualE.DualE method), 75
forward_k_vs_all() (dicee.models.Keci method), 128
forward_k_vs_all() (dicee.models.octonion.AConvO method), 82
forward_k_vs_all() (dicee.models.octonion.ConvO method), 81
forward_k_vs_all() (dicee.models.octonion.OMult method), 80
forward_k_vs_all() (dicee.models.OMult method), 124
forward_k_vs_all() (dicee.models.pykeen_models.PykeenKGE method), 83
forward_k_vs_all() (dicee.models.PykeenKGE method), 135
forward_k_vs_all() (dicee.models.QMult method), 118
forward_k_vs_all() (dicee.models.quaternion.AConvQ method), 86
forward_k_vs_all() (dicee.models.quaternion.ConvQ method), 86
forward_k_vs_all() (dicee.models.quaternion.QMult method), 85
forward_k_vs_all() (dicee.models.real.DistMult method), 87
forward_k_vs_all() (dicee.models.real.Shallom method), 88
forward_k_vs_all() (dicee.models.real.TransE method), 87
forward k vs all() (dicee.models.Shallom method), 109
forward_k_vs_all() (dicee.models.TransE method), 109
forward_k_vs_all() (dicee.OMult method), 184
forward_k_vs_all() (dicee.PykeenKGE method), 186
forward_k_vs_all() (dicee.QMult method), 183
forward_k_vs_all() (dicee.Shallom method), 184
forward_k_vs_all() (dicee.TransE method), 172
forward_k_vs_sample() (dicee.AConEx method), 178
forward_k_vs_sample() (dicee.BaseKGE method), 191
forward_k_vs_sample() (dicee.ComplEx method), 178
forward_k_vs_sample() (dicee.ConEx method), 182
forward_k_vs_sample() (dicee.DistMult method), 169
forward_k_vs_sample() (dicee.Keci method), 172
forward_k_vs_sample() (dicee.models.AConEx method), 113
forward_k_vs_sample() (dicee.models.base_model.BaseKGE method), 63
forward_k_vs_sample() (dicee.models.BaseKGE method), 104, 108, 111, 116, 122, 134, 138
forward_k_vs_sample() (dicee.models.clifford.Keci method), 67
forward_k_vs_sample() (dicee.models.ComplEx method), 114
forward_k_vs_sample() (dicee.models.complex.AConEx method), 73
forward_k_vs_sample() (dicee.models.complex.ComplEx method), 74
forward_k_vs_sample() (dicee.models.complex.ConEx method), 72
forward_k_vs_sample() (dicee.models.ConEx method), 112
forward_k_vs_sample() (dicee.models.DistMult method), 108
forward_k_vs_sample() (dicee.models.Keci method), 128
forward_k_vs_sample() (dicee.models.pykeen_models.PykeenKGE method), 83
forward_k_vs_sample() (dicee.models.PykeenKGE method), 136
forward_k_vs_sample() (dicee.models.QMult method), 118
forward_k_vs_sample() (dicee.models.quaternion.QMult method), 85
forward_k_vs_sample() (dicee.models.real.DistMult method), 87
forward_k_vs_sample() (dicee.PykeenKGE method), 187
forward_k_vs_sample() (dicee.QMult method), 183
forward_k_vs_with_explicit() (dicee.Keci method), 171
```

```
forward_k_vs_with_explicit() (dicee.models.clifford.Keci method), 67
forward_k_vs_with_explicit() (dicee.models.Keci method), 128
forward_triples() (dicee.AConEx method), 178
forward_triples() (dicee.AConvO method), 179
forward_triples() (dicee.AConvQ method), 179
forward_triples() (dicee.BaseKGE method), 191
forward_triples() (dicee.ConEx method), 182
forward triples() (dicee.ConvO method), 181
forward_triples() (dicee.ConvQ method), 180
forward_triples() (dicee.DeCaL method), 173
forward_triples() (dicee.DualE method), 176
forward_triples() (dicee.Keci method), 172
forward_triples() (dicee.LFMult method), 185
forward_triples() (dicee.models.AConEx method), 113
forward_triples() (dicee.models.AConvO method), 125
forward_triples() (dicee.models.AConvQ method), 119
forward_triples() (dicee.models.base_model.BaseKGE method), 63
forward_triples() (dicee.models.BaseKGE method), 104, 107, 111, 116, 122, 134, 138
forward_triples() (dicee.models.clifford.DeCaL method), 69
forward_triples() (dicee.models.clifford.Keci method), 68
forward_triples() (dicee.models.complex.AConEx method), 73
forward_triples() (dicee.models.complex.ConEx method), 72
forward_triples() (dicee.models.ConEx method), 112
forward_triples() (dicee.models.ConvO method), 125
forward_triples() (dicee.models.ConvQ method), 119
forward_triples() (dicee.models.DeCaL method), 130
forward_triples() (dicee.models.DualE method), 142
forward_triples() (dicee.models.dualE.DualE method), 74
forward_triples() (dicee.models.FMult method), 139
forward_triples() (dicee.models.FMult2 method), 140
forward_triples() (dicee.models.function_space.FMult method), 76
forward_triples() (dicee.models.function_space.FMult2 method), 77
forward_triples() (dicee.models.function_space.GFMult method), 77
{\tt forward\_triples()} \ (\textit{dicee.models.function\_space.LFMult method}), 78
forward_triples() (dicee.models.function_space.LFMult1 method), 78
forward_triples() (dicee.models.GFMult method), 139
forward triples() (dicee.models.Keci method), 128
forward_triples() (dicee.models.LFMult method), 140
forward_triples() (dicee.models.LFMult1 method), 140
forward_triples() (dicee.models.octonion.AConvO method), 82
forward_triples() (dicee.models.octonion.ConvO method), 81
forward_triples() (dicee.models.Pyke method), 109
forward_triples() (dicee.models.pykeen_models.PykeenKGE method), 83
forward_triples() (dicee.models.PykeenKGE method), 135
forward_triples() (dicee.models.quaternion.AConvQ method), 86
forward_triples() (dicee.models.quaternion.ConvQ method), 86
forward_triples() (dicee.models.real.Pyke method), 88
forward_triples() (dicee.models.real.Shallom method), 88
forward_triples() (dicee.models.Shallom method), 109
forward_triples() (dicee.Pyke method), 168
forward_triples() (dicee.PykeenKGE method), 186
forward_triples() (dicee.Shallom method), 184
{\tt freeze\_entity\_embeddings}~(\textit{dicee.literal\_classes.LiteralEmbeddings}~attribute), 52
frequency (dicee.callbacks.Perturb attribute), 26
from_pretrained() (dicee.models.transformers.GPT class method), 95
from_pretrained_model_write_embeddings_into_csv() (in module dicee), 193
from_pretrained_model_write_embeddings_into_csv() (in module dicee.static_funcs), 157
full_storage_path (dicee.analyse_experiments.Experiment attribute), 18
func_triple_to_bpe_representation (dicee.evaluator.Evaluator attribute), 42
func_triple_to_bpe_representation() (dicee.knowledge_graph.KG method), 46
function() (dicee.models.FMult2 method), 140
function() (dicee.models.function_space.FMult2 method), 77
G
gamma (dicee.models.FMult attribute), 138
gamma (dicee.models.function_space.FMult attribute), 76
gate_residual (dicee.literal_classes.GatedLinearUnit attribute), 51
```

```
gate residual (dicee.literal classes.LiteralEmbeddings attribute), 52
GatedLinearUnit (class in dicee.literal_classes), 51
gelu (dicee.models.transformers.MLP attribute), 93
gen_test (dicee.query_generator.QueryGenerator attribute), 143
gen_test (dicee.QueryGenerator attribute), 211
gen_valid (dicee.query_generator.QueryGenerator attribute), 143
gen_valid (dicee.QueryGenerator attribute), 211
generate() (dicee.BytE method), 188
generate() (dicee.KGE method), 195
generate() (dicee.knowledge_graph_embeddings.KGE method), 47
generate() (dicee.models.transformers.BytE method), 90
generate_queries() (dicee.query_generator.QueryGenerator method), 143
generate_queries() (dicee.QueryGenerator method), 211
get_aswa_state_dict() (dicee.callbacks.ASWA method), 23
get_bpe_head_and_relation_representation() (dicee.BaseKGE method), 191
get_bpe_head_and_relation_representation() (dicee.models.base_model.BaseKGE method), 64
get_bpe_token_representation() (dicee.abstracts.BaseInteractiveKGE method), 14
get_callbacks() (in module dicee.trainer.dice_trainer), 159
get_default_arguments() (in module dicee.analyse_experiments), 18
get_default_arguments() (in module dicee.scripts.index_serve), 152
get_default_arguments() (in module dicee.scripts.run), 154
get_ee_vocab() (in module dicee), 192
get_ee_vocab() (in module dicee.read_preprocess_save_load_kg.util), 148
get_ee_vocab() (in module dicee.static_funcs), 155
get_ee_vocab() (in module dicee.static_preprocess_funcs), 158
get_embeddings() (dicee.BaseKGE method), 191
get_embeddings() (dicee.EnsembleKGE method), 192
\verb"get_embeddings" () \textit{ (dicee.models.base\_model.BaseKGE method)}, 64
get_embeddings() (dicee.models.BaseKGE method), 105, 108, 112, 116, 122, 135, 138
get_embeddings() (dicee.models.ensemble.EnsembleKGE method), 76
get embeddings() (dicee.models.real.Shallom method), 87
get_embeddings() (dicee.models.Shallom method), 109
get_embeddings() (dicee.Shallom method), 184
get_entity_embeddings() (dicee.abstracts.BaseInteractiveKGE method), 15
get_entity_index() (dicee.abstracts.BaseInteractiveKGE method), 15
get er vocab() (in module dicee), 192
get_er_vocab() (in module dicee.read_preprocess_save_load_kg.util), 148
get_er_vocab() (in module dicee.static_funcs), 155
get_er_vocab() (in module dicee.static_preprocess_funcs), 158
get_eval_report() (dicee.abstracts.BaseInteractiveKGE method), 14
get_head_relation_representation() (dicee.BaseKGE method), 191
get_head_relation_representation() (dicee.models.base_model.BaseKGE method), 63
get_head_relation_representation() (dicee.models.BaseKGE method), 104, 108, 111, 116, 122, 134, 138
get_kronecker_triple_representation() (dicee.callbacks.KronE method), 25
get_num_params() (dicee.models.transformers.GPT method), 95
qet_padded_bpe_triple_representation() (dicee.abstracts.BaseInteractiveKGE method), 14
get_queries() (dicee.query_generator.QueryGenerator method), 144
get_queries() (dicee.QueryGenerator method), 211
get_re_vocab() (in module dicee), 192
get_re_vocab() (in module dicee.read_preprocess_save_load_kg.util), 148
get_re_vocab() (in module dicee.static_funcs), 155
get_re_vocab() (in module dicee.static_preprocess_funcs), 158
get_relation_embeddings() (dicee.abstracts.BaseInteractiveKGE method), 15
get_relation_index() (dicee.abstracts.BaseInteractiveKGE method), 15
get_sentence_representation() (dicee.BaseKGE method), 191
get_sentence_representation() (dicee.models.base_model.BaseKGE method), 64
get_sentence_representation() (dicee.models.BaseKGE method), 105, 108, 111, 116, 122, 134, 138
get_transductive_entity_embeddings() (dicee.KGE method), 195
get_transductive_entity_embeddings() (dicee.knowledge_graph_embeddings.KGE method), 47
get_triple_representation() (dicee.BaseKGE method), 191
get_triple_representation() (dicee.models.base_model.BaseKGE method), 63
get_triple_representation() (dicee.models.BaseKGE method), 104, 108, 111, 116, 122, 134, 138
GFMult (class in dicee.models), 139
GFMult (class in dicee.models.function_space), 76
global_rank (dicee.abstracts.AbstractTrainer attribute), 12
global_rank (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 163
GPT (class in dicee.models.transformers), 94
```

```
GPTConfig (class in dicee.models.transformers), 94
gpus (dicee.config.Namespace attribute), 27
gradient_accumulation_steps (dicee.config.Namespace attribute), 27
ground_queries() (dicee.query_generator.QueryGenerator method), 143
ground_queries() (dicee.QueryGenerator method), 211
Н
hidden_dim (dicee.literal_classes.LiteralEmbeddings attribute), 52
hidden_dropout (dicee.BaseKGE attribute), 190
hidden_dropout (dicee.models.base_model.BaseKGE attribute), 63
hidden_dropout (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
hidden_dropout_rate (dicee.BaseKGE attribute), 190
hidden_dropout_rate (dicee.config.Namespace attribute), 28
hidden_dropout_rate (dicee.models.base_model.BaseKGE attribute), 62
hidden_dropout_rate (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 121, 133, 137
hidden_normalizer (dicee.BaseKGE attribute), 190
hidden_normalizer (dicee.models.base_model.BaseKGE attribute), 63
hidden_normalizer (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 134, 137
IdentityClass (class in dicee.models), 105, 116, 122
IdentityClass (class in dicee.models.base_model), 64
idx_entity_to_bpe_shaped (dicee.knowledge_graph.KG attribute), 46
index() (in module dicee.scripts.index_serve), 152
\verb|index_triple(|)| \textit{(dicee.abstracts.BaseInteractiveKGE method)}, 15
init_dataloader() (dicee.DICE_Trainer method), 194
init_dataloader() (dicee.trainer.DICE_Trainer method), 165
init_dataloader() (dicee.trainer.dice_trainer.DICE_Trainer method), 160
init_dataset() (dicee.DICE_Trainer method), 194
init_dataset() (dicee.trainer.DICE_Trainer method), 165
init_dataset() (dicee.trainer.dice_trainer.DICE_Trainer method), 160
init_param (dicee.config.Namespace attribute), 27
\verb|init_params_with_sanity_checking()| \textit{(dicee.BaseKGE method)}, 191
init_params_with_sanity_checking() (dicee.models.base_model.BaseKGE method), 63
\verb|init_params_with_sanity_checking()| \textit{(dicee.models.BaseKGE method)}, 104, 107, 111, 115, 121, 134, 137 \\
initial_eval_setting (dicee.callbacks.ASWA attribute), 23
initialize_or_load_model() (dicee.DICE_Trainer method), 194
initialize_or_load_model() (dicee.trainer.DICE_Trainer method), 165
initialize_or_load_model() (dicee.trainer.dice_trainer.DICE_Trainer method), 160
initialize_trainer() (dicee.DICE_Trainer method), 194
initialize_trainer() (dicee.trainer.DICE_Trainer method), 165
initialize_trainer() (dicee.trainer.dice_trainer.DICE_Trainer method), 160
initialize_trainer() (in module dicee.trainer.dice_trainer), 159
input_dp_ent_real (dicee.BaseKGE attribute), 190
input_dp_ent_real (dicee.models.base_model.BaseKGE attribute), 63
input_dp_ent_real (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
input_dp_rel_real (dicee.BaseKGE attribute), 190
input_dp_rel_real (dicee.models.base_model.BaseKGE attribute), 63
input_dp_rel_real (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
input dropout rate (dicee.BaseKGE attribute), 190
input_dropout_rate (dicee.config.Namespace attribute), 28
input_dropout_rate (dicee.models.base_model.BaseKGE attribute), 62
input_dropout_rate (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 121, 133, 137
InteractiveQueryDecomposition (class in dicee.abstracts), 15
intialize_model() (in module dicee), 193
intialize_model() (in module dicee.static_funcs), 156
is_continual_training (dicee.DICE_Trainer attribute), 194
is_continual_training (dicee.evaluator.Evaluator attribute), 42
is_continual_training (dicee.executer.Execute attribute), 43
is_continual_training (dicee.trainer.DICE_Trainer attribute), 164
is_continual_training (dicee.trainer.dice_trainer.DICE_Trainer attribute), 159
is_global_zero (dicee.abstracts.AbstractTrainer attribute), 12
is_seen() (dicee.abstracts.BaseInteractiveKGE method), 14
is_sparql_endpoint_alive() (in module dicee.sanity_checkers), 151
Κ
```

```
k (dicee.models.FMult2 attribute), 139
k (dicee.models.function_space.FMult attribute), 76
k (dicee.models.function_space.FMult2 attribute), 77
k (dicee.models.function_space.GFMult attribute), 77
k (dicee.models.GFMult attribute), 139
k_fold_cross_validation() (dicee.DICE_Trainer method), 195
k_fold_cross_validation() (dicee.trainer.DICE_Trainer method), 165
k_fold_cross_validation() (dicee.trainer.dice_trainer.DICE_Trainer method), 160
k_vs_all_score() (dicee.ComplEx static method), 178
k_vs_all_score() (dicee.DistMult method), 169
k_vs_all_score() (dicee.Keci method), 171
k_vs_all_score() (dicee.models.clifford.Keci method), 67
k_vs_all_score() (dicee.models.ComplEx static method), 113
k_vs_all_score() (dicee.models.complex.ComplEx static method), 74
k_vs_all_score() (dicee.models.DistMult method), 108
k_vs_all_score() (dicee.models.Keci method), 128
k_vs_all_score() (dicee.models.octonion.OMult method), 80
k_vs_all_score() (dicee.models.OMult method), 124
k_vs_all_score() (dicee.models.QMult method), 118
k_vs_all_score() (dicee.models.quaternion.QMult method), 85
k_vs_all_score() (dicee.models.real.DistMult method), 87
k_vs_all_score() (dicee.OMult method), 184
k_vs_all_score() (dicee.QMult method), 183
Keci (class in dicee), 169
Keci (class in dicee.models), 125
Keci (class in dicee.models.clifford), 65
kernel_size (dicee.BaseKGE attribute), 190
kernel_size (dicee.config.Namespace attribute), 28
kernel_size (dicee.models.base_model.BaseKGE attribute), 62
kernel_size (dicee.models.BaseKGE attribute), 103, 107, 110, 115, 121, 133, 137
KG (class in dicee.knowledge_graph), 45
kg (dicee.callbacks.PseudoLabellingCallback attribute), 22
kg (dicee.read_preprocess_save_load_kg.LoadSaveToDisk attribute), 150
kg (dicee.read_preprocess_save_load_kg.PreprocessKG attribute), 149
kg (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG attribute), 144
kg (dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk attribute), 145
kg (dicee.read preprocess save load kg.ReadFromDisk attribute), 150
kg (dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk attribute), 146
KGE (class in dicee), 195
KGE (class in dicee.knowledge_graph_embeddings), 47
KGESaveCallback (class in dicee.callbacks), 21
knowledge_graph (dicee.executer.Execute attribute), 43
KronE (class in dicee.callbacks), 25
KvsAll (class in dicee), 202
KvsAll (class in dicee.dataset_classes), 31
kvsall_score() (dicee.DualE method), 176
kvsall_score() (dicee.models.DualE method), 142
kvsall_score() (dicee.models.dualE.DualE method), 74
KvsSampleDataset (class in dicee), 205
KvsSampleDataset (class in dicee.dataset_classes), 35
label_smoothing_rate (dicee.AllvsAll attribute), 203
label_smoothing_rate (dicee.config.Namespace attribute), 27
label_smoothing_rate (dicee.dataset_classes.AllvsAll attribute), 33
label_smoothing_rate (dicee.dataset_classes.KvsAll attribute), 32
label_smoothing_rate (dicee.dataset_classes.KvsSampleDataset attribute), 35
label_smoothing_rate (dicee.dataset_classes.OnevsSample attribute), 34
label_smoothing_rate (dicee.dataset_classes.TriplePredictionDataset attribute), 36
label_smoothing_rate (dicee.KvsAll attribute), 202
label_smoothing_rate (dicee.KvsSampleDataset attribute), 205
label_smoothing_rate (dicee.OnevsSample attribute), 204
label_smoothing_rate (dicee. TriplePredictionDataset attribute), 207
layer_norm (dicee.literal_classes.LiteralEmbeddings attribute), 52
LayerNorm (class in dicee.models.transformers), 91
learning_rate (dicee.BaseKGE attribute), 190
learning_rate (dicee.models.base_model.BaseKGE attribute), 62
```

```
learning rate (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 120, 133, 136
length (dicee.dataset_classes.NegSampleDataset attribute), 36
length (dicee.dataset_classes.TriplePredictionDataset attribute), 37
length (dicee.NegSampleDataset attribute), 206
length (dicee. TriplePredictionDataset attribute), 207
level (dicee.callbacks.Perturb attribute), 25
LFMult (class in dicee), 185
LFMult (class in dicee.models), 140
LFMult (class in dicee.models.function_space), 78
LFMult1 (class in dicee.models), 140
LFMult1 (class in dicee.models.function_space), 77
linear() (dicee.LFMult method), 185
linear() (dicee.models.function_space.LFMult method), 78
linear() (dicee.models.LFMult method), 141
list2tuple() (dicee.query_generator.QueryGenerator method), 143
list2tuple() (dicee.QueryGenerator method), 211
LiteralDataset (class in dicee.literal_classes), 53
LiteralEmbeddings (class in dicee.literal_classes), 51
lm_head (dicee.BytE attribute), 187
lm_head (dicee.models.transformers.BytE attribute), 90
lm_head (dicee.models.transformers.GPT attribute), 95
ln_1 (dicee.models.transformers.Block attribute), 93
ln_2 (dicee.models.transformers.Block attribute), 94
load() (dicee.read_preprocess_save_load_kg.LoadSaveToDisk method), 150
load() (dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk method), 146
load_and_validate_literal_data() (dicee.literal_classes.LiteralDataset static method), 54
load_json() (in module dicee), 193
load_json() (in module dicee.static_funcs), 156
load_model() (in module dicee), 192
load_model() (in module dicee.static_funcs), 156
load_model_ensemble() (in module dicee), 192
load_model_ensemble() (in module dicee.static_funcs), 156
load_numpy() (in module dicee), 193
load_numpy() (in module dicee.static_funcs), 157
load_numpy_ndarray() (in module dicee.read_preprocess_save_load_kg.util), 149
load_pickle() (in module dicee), 192
load_pickle() (in module dicee.read_preprocess_save_load_kg.util), 149
load_pickle() (in module dicee.static_funcs), 156
load_queries() (dicee.query_generator.QueryGenerator method), 144
load_queries() (dicee.QueryGenerator method), 211
load_queries_and_answers() (dicee.query_generator.QueryGenerator static method), 144
load_queries_and_answers() (dicee.QueryGenerator static method), 212
load_term_mapping() (in module dicee), 192, 199
load_term_mapping() (in module dicee.static_funcs), 156
load_term_mapping() (in module dicee.trainer.dice_trainer), 159
load_with_pandas() (in module dicee.read_preprocess_save_load_kg.util), 149
loader_backend (dicee.literal_classes.LiteralDataset attribute), 54
LoadSaveToDisk (class in dicee.read_preprocess_save_load_kg), 150
LoadSaveToDisk (class in dicee.read_preprocess_save_load_kg.save_load_disk), 146
local_rank (dicee.abstracts.AbstractTrainer attribute), 12
local_rank (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 163
loss (dicee.BaseKGE attribute), 190
loss (dicee.models.base_model.BaseKGE attribute), 62
loss (dicee.models.BaseKGE attribute), 103, 107, 110, 115, 121, 133, 137
loss_func (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 164
loss_function (dicee.trainer.torch_trainer.TorchTrainer attribute), 162
loss_function() (dicee.BytE method), 188
{\tt loss\_function()} \ (\textit{dicee.models.base\_model.BaseKGELightning method}), 57
loss_function() (dicee.models.BaseKGELightning method), 98
loss_function() (dicee.models.transformers.BytE method), 90
loss_history (dicee.BaseKGE attribute), 190
loss_history (dicee.models.base_model.BaseKGE attribute), 63
loss_history (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
loss_history (dicee.models.pykeen_models.PykeenKGE attribute), 83
loss_history (dicee.models.PykeenKGE attribute), 135
loss_history (dicee.PykeenKGE attribute), 186
loss_history (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 164
{\tt lr}~(dicee. analyse\_experiments. Experiment~attribute),~18
```

M

```
m (dicee.LFMult attribute), 185
m (dicee.models.function_space.LFMult attribute), 78
m (dicee.models.LFMult attribute), 140
main() (in module dicee.scripts.index_serve), 154
main() (in module dicee.scripts.run), 154
make_iterable_verbose() (in module dicee.static_funcs_training), 157
make_iterable_verbose() (in module dicee.trainer.torch_trainer_ddp), 163
mapping_from_first_two_cols_to_third() (in module dicee), 199
mapping_from_first_two_cols_to_third() (in module dicee.static_preprocess_funcs), 159
margin (dicee.models.Pyke attribute), 109
margin (dicee.models.real.Pyke attribute), 88
margin (dicee.models.real.TransE attribute), 87
margin (dicee.models.TransE attribute), 108
margin (dicee. Pyke attribute), 168
margin (dicee. TransE attribute), 172
max_ans_num (dicee.query_generator.QueryGenerator attribute), 143
max_ans_num (dicee.QueryGenerator attribute), 211
max_epochs (dicee.callbacks.KGESaveCallback attribute), 21
max_length_subword_tokens (dicee.BaseKGE attribute), 190
\verb|max_length_subword_tokens| (\textit{dicee.knowledge\_graph.KG attribute}), 46
max_length_subword_tokens (dicee.models.base_model.BaseKGE attribute), 63
max_length_subword_tokens (dicee.models.BaseKGE attribute), 104, 107, 111, 115, 121, 134, 137
max_num_of_classes (dicee.dataset_classes.KvsSampleDataset attribute), 35
max_num_of_classes (dicee.KvsSampleDataset attribute), 205
mem_of_model() (dicee.EnsembleKGE method), 192
mem_of_model() (dicee.models.base_model.BaseKGELightning method), 56
mem_of_model() (dicee.models.BaseKGELightning method), 97
mem_of_model() (dicee.models.ensemble.EnsembleKGE method), 75
method (dicee.callbacks.Perturb attribute), 25
MLP (class in dicee.models.transformers), 92
mlp (dicee.models.transformers.Block attribute), 94
mode (dicee.query_generator.QueryGenerator attribute), 143
mode (dicee. Query Generator attribute), 211
model (dicee.config.Namespace attribute), 26
model (dicee.models.pykeen_models.PykeenKGE attribute), 83
model (dicee.models.PykeenKGE attribute), 135
model (dicee.PykeenKGE attribute), 186
model (dicee.trainer.torch trainer ddp.NodeTrainer attribute), 164
model (dicee.trainer.torch_trainer.TorchTrainer attribute), 162
model_kwargs (dicee.models.pykeen_models.PykeenKGE attribute), 82
model_kwargs (dicee.models.PykeenKGE attribute), 135
model_kwargs (dicee.PykeenKGE attribute), 186
model_name (dicee.analyse_experiments.Experiment attribute), 18
module
     dicee, 12
     dicee.__main__, 12
     dicee.abstracts, 12
     dicee.analyse_experiments, 18
     dicee.callbacks, 19
     dicee.config. 26
     dicee.dataset_classes, 29
     dicee.eval_static_funcs, 40
     dicee.evaluator, 42
     dicee.executer, 43
     dicee.knowledge_graph, 45
     dicee.knowledge_graph_embeddings,46
     dicee.literal_classes, 51
     dicee.models, 54
     dicee.models.adopt, 54
     dicee.models.base_model, 56
     dicee.models.clifford, 65
     dicee.models.complex, 72
     dicee.models.dualE,74
     dicee.models.ensemble, 75
```

```
dicee.models.function_space, 76
     dicee.models.octonion, 79
     {\tt dicee.models.pykeen\_models, 82}
     dicee.models.quaternion, 83
     dicee.models.real, 87
     dicee.models.static_funcs, 88
     dicee.models.transformers, 88
     dicee.query_generator, 142
     dicee.read_preprocess_save_load_kg, 144
     dicee.read_preprocess_save_load_kg.preprocess, 144
     dicee.read_preprocess_save_load_kg.read_from_disk, 145
     dicee.read_preprocess_save_load_kg.save_load_disk, 145
     dicee.read_preprocess_save_load_kg.util, 146
     dicee.sanity_checkers, 150
     dicee.scripts, 151
     dicee.scripts.index_serve, 151
     dicee.scripts.run, 154
     dicee.static_funcs, 154
     dicee.static_funcs_training, 157
     dicee.static_preprocess_funcs, 158
     dicee.trainer, 159
     dicee.trainer.dice_trainer, 159
     dicee.trainer.model_parallelism, 161
     dicee.trainer.torch_trainer, 161
     dicee.trainer.torch_trainer_ddp, 163
modules () (dicee. Ensemble KGE method), 191
modules () (dicee.models.ensemble.EnsembleKGE method), 75
MultiClassClassificationDataset (class in dicee), 201
MultiClassClassificationDataset (class in dicee.dataset_classes), 30
MultiLabelDataset (class in dicee), 200
MultiLabelDataset (class in dicee.dataset_classes), 30
Ν
n (dicee.models.FMult2 attribute), 139
n (dicee.models.function_space.FMult2 attribute), 77
n_embd (dicee.models.transformers.CausalSelfAttention attribute), 92
n_embd (dicee.models.transformers.GPTConfig attribute), 94
n_head (dicee.models.transformers.CausalSelfAttention attribute), 92
n_head (dicee.models.transformers.GPTConfig attribute), 94
n_layer (dicee.models.transformers.GPTConfig attribute), 94
n_layers (dicee.models.FMult2 attribute), 139
n_layers (dicee.models.function_space.FMult2 attribute), 77
name (dicee.abstracts.BaseInteractiveKGE property), 14
name (dicee.AConEx attribute), 178
name (dicee.AConvO attribute), 178
name (dicee.AConvQ attribute), 179
name (dicee.BytE attribute), 187
name (dicee. CKeci attribute), 169
name (dicee.ComplEx attribute), 177
name (dicee.ConEx attribute), 181
name (dicee.ConvO attribute), 181
name (dicee.ConvQ attribute), 180
name (dicee.DeCaL attribute), 173
name (dicee.DistMult attribute), 168
name (dicee.DualE attribute), 176
name (dicee. Ensemble KGE attribute), 191
name (dicee.Keci attribute), 170
name (dicee.LFMult attribute), 185
name (dicee.models.AConEx attribute), 112
name (dicee.models.AConvO attribute), 125
name (dicee.models.AConvQ attribute), 119
name (dicee.models.CKeci attribute), 129
name (dicee.models.clifford.CKeci attribute), 68
name (dicee.models.clifford.DeCaL attribute), 69
name (dicee.models.clifford.Keci attribute), 65
name (dicee.models.ComplEx attribute), 113
name (dicee.models.complex.AConEx attribute), 72
```

```
name (dicee.models.complex.ComplEx attribute), 73
name (dicee.models.complex.ConEx attribute), 72
name (dicee.models.ConEx attribute), 112
name (dicee.models.ConvO attribute), 124
name (dicee.models.ConvQ attribute), 119
name (dicee.models.DeCaL attribute), 129
name (dicee.models.DistMult attribute), 108
name (dicee.models.DualE attribute), 141
name (dicee.models.dualE.DualE attribute), 74
name (dicee.models.ensemble.EnsembleKGE attribute), 75
name (dicee.models.FMult attribute), 138
name (dicee.models.FMult2 attribute), 139
name (dicee.models.function_space.FMult attribute), 76
name (dicee.models.function_space.FMult2 attribute), 77
name (dicee.models.function_space.GFMult attribute), 76
name (dicee.models.function_space.LFMult attribute), 78
name (dicee.models.function_space.LFMult1 attribute), 78
name (dicee.models.GFMult attribute), 139
name (dicee.models.Keci attribute), 126
name (dicee.models.LFMult attribute), 140
name (dicee.models.LFMult1 attribute), 140
name (dicee.models.octonion.AConvO attribute), 82
name (dicee.models.octonion.ConvO attribute), 81
name (dicee.models.octonion.OMult attribute), 80
name (dicee.models.OMult attribute), 124
name (dicee.models.Pyke attribute), 109
name (dicee.models.pykeen_models.PykeenKGE attribute), 83
name (dicee.models.PykeenKGE attribute), 135
name (dicee.models.QMult attribute), 118
name (dicee.models.quaternion.AConvQ attribute), 86
name (dicee.models.quaternion.ConvQ attribute), 85
name (dicee.models.quaternion.OMult attribute), 84
name (dicee.models.real.DistMult attribute), 87
name (dicee.models.real.Pyke attribute), 88
name (dicee.models.real.Shallom attribute), 87
name (dicee.models.real.TransE attribute), 87
name (dicee.models.Shallom attribute), 109
name (dicee.models.TransE attribute), 108
name (dicee.models.transformers.BytE attribute), 89
name (dicee.OMult attribute), 184
name (dicee.Pyke attribute), 168
name (dicee.PykeenKGE attribute), 186
name (dicee.QMult attribute), 182
name (dicee.Shallom attribute), 184
name (dicee.TransE attribute), 172
named_children() (dicee.EnsembleKGE method), 191
named_children() (dicee.models.ensemble.EnsembleKGE method), 75
Namespace (class in dicee.config), 26
neg_ratio (dicee.BPE_NegativeSamplingDataset attribute), 200
neg_ratio (dicee.config.Namespace attribute), 27
neg_ratio (dicee.dataset_classes.BPE_NegativeSamplingDataset attribute), 30
neg_ratio (dicee.dataset_classes.KvsSampleDataset attribute), 35
neg_ratio (dicee.KvsSampleDataset attribute), 205
neg_sample_ratio (dicee.CVDataModule attribute), 207
neg_sample_ratio (dicee.dataset_classes.CVDataModule attribute), 37
neg_sample_ratio (dicee.dataset_classes.NegSampleDataset attribute), 36
neg_sample_ratio (dicee.dataset_classes.OnevsSample attribute), 34
\verb|neg_sample_ratio| (\textit{dicee.dataset\_classes.TriplePredictionDataset\ attribute}), 37
neg_sample_ratio (dicee.NegSampleDataset attribute), 206
neg_sample_ratio (dicee.OnevsSample attribute), 204
neg sample ratio (dicee. TriplePredictionDataset attribute), 207
negnorm() (dicee.abstracts.InteractiveQueryDecomposition method), 16
NegSampleDataset (class in dicee), 205
NegSampleDataset (class in dicee.dataset_classes), 35
neural_searcher (in module dicee.scripts.index_serve), 152
Neural Searcher (class in dicee.scripts.index_serve), 152
NodeTrainer (class in dicee.trainer.torch_trainer_ddp), 163
norm_fc1 (dicee.AConEx attribute), 178
```

```
norm fc1 (dicee. AConvO attribute), 179
norm_fc1 (dicee.ConEx attribute), 181
norm_fc1 (dicee, ConvO attribute), 181
norm_fc1 (dicee.models.AConEx attribute), 112
norm_fc1 (dicee.models.AConvO attribute), 125
norm_fc1 (dicee.models.complex.AConEx attribute), 72
norm_fc1 (dicee.models.complex.ConEx attribute), 72
norm fc1 (dicee.models.ConEx attribute), 112
norm_fc1 (dicee.models.ConvO attribute), 125
norm_fc1 (dicee.models.octonion.AConvO attribute), 82
norm_fc1 (dicee.models.octonion.ConvO attribute), 81
normalization (dicee.analyse_experiments.Experiment attribute), 19
normalization (dicee.config.Namespace attribute), 27
normalization (dicee.literal_classes.LiteralDataset attribute), 53
normalization_params (dicee.literal_classes.LiteralDataset attribute), 53, 54
normalization_type (dicee.literal_classes.LiteralDataset attribute), 54
{\tt normalize\_head\_entity\_embeddings}~(\textit{dicee.BaseKGE attribute}),~190
normalize_head_entity_embeddings (dicee.models.base_model.BaseKGE attribute), 63
normalize_head_entity_embeddings (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 134, 137
normalize_relation_embeddings (dicee.BaseKGE attribute), 190
normalize_relation_embeddings (dicee.models.base_model.BaseKGE attribute), 63
normalize_relation_embeddings (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 134, 137
normalize_tail_entity_embeddings (dicee.BaseKGE attribute), 190
\verb|normalize_tail_entity_embeddings| \textit{(dicee.models.base\_model.BaseKGE attribute)}, 63
normalize_tail_entity_embeddings (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 134, 137
normalizer_class (dicee.BaseKGE attribute), 190
normalizer_class (dicee.models.base_model.BaseKGE attribute), 63
normalizer_class (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 133, 137
num_bpe_entities (dicee.BPE_NegativeSamplingDataset attribute), 200
num_bpe_entities (dicee.dataset_classes.BPE_NegativeSamplingDataset attribute), 30
num_bpe_entities (dicee.knowledge_graph.KG attribute), 46
num_core (dicee.config.Namespace attribute), 27
num_data_properties (dicee.literal_classes.LiteralDataset attribute), 53
num_datapoints (dicee.BPE_NegativeSamplingDataset attribute), 200
num_datapoints (dicee.dataset_classes.BPE_NegativeSamplingDataset attribute), 30
num_datapoints (dicee.dataset_classes.MultiLabelDataset attribute), 30
num datapoints (dicee.MultiLabelDataset attribute), 200
num_ent (dicee.DualE attribute), 176
num_ent (dicee.models.DualE attribute), 142
num_ent (dicee.models.dualE.DualE attribute), 74
num_entities (dicee.BaseKGE attribute), 190
num_entities (dicee.CVDataModule attribute), 207
num_entities (dicee.dataset_classes.CVDataModule attribute), 37
\verb|num_entities| (\textit{dicee.dataset\_classes.KvsSampleDataset attribute}), 35
num_entities (dicee.dataset_classes.NegSampleDataset attribute), 36
num_entities (dicee.dataset_classes.OnevsSample attribute), 33, 34
num_entities (dicee.dataset_classes.TriplePredictionDataset attribute), 37
num_entities (dicee.evaluator.Evaluator attribute), 42
num_entities (dicee.knowledge_graph.KG attribute), 45
num_entities (dicee.KvsSampleDataset attribute), 205
num entities (dicee.literal classes.LiteralDataset attribute), 53, 54
num_entities (dicee.models.base_model.BaseKGE attribute), 62
num_entities (dicee.models.BaseKGE attribute), 103, 106, 110, 114, 120, 133, 136
num_entities (dicee.NegSampleDataset attribute), 206
num_entities (dicee. OnevsSample attribute), 204
num_entities (dicee. TriplePredictionDataset attribute), 207
num_epochs (dicee.abstracts.AbstractPPECallback attribute), 17
num_epochs (dicee.analyse_experiments.Experiment attribute), 18
num_epochs (dicee.callbacks.ASWA attribute), 23
num_epochs (dicee.config.Namespace attribute), 26
num epochs (dicee.trainer.torch trainer ddp.NodeTrainer attribute), 164
num_folds_for_cv (dicee.config.Namespace attribute), 27
num_of_data_points (dicee.dataset_classes.MultiClassClassificationDataset attribute), 31
num_of_data_points (dicee.MultiClassClassificationDataset attribute), 201
num_of_data_properties (dicee.literal_classes.LiteralEmbeddings attribute), 51, 52
num_of_epochs (dicee.callbacks.PseudoLabellingCallback attribute), 22
num_of_output_channels (dicee.BaseKGE attribute), 190
num_of_output_channels (dicee.config.Namespace attribute), 28
```

```
num of output channels (dicee.models.base model.BaseKGE attribute), 62
num_of_output_channels (dicee.models.BaseKGE attribute), 103, 107, 110, 115, 121, 133, 137
num_params (dicee.analyse_experiments.Experiment attribute), 18
num_relations (dicee.BaseKGE attribute), 190
num_relations (dicee.CVDataModule attribute), 207
num_relations (dicee.dataset_classes.CVDataModule attribute), 37
num_relations (dicee.dataset_classes.NegSampleDataset attribute), 36
num relations (dicee.dataset classes.OnevsSample attribute), 34
num_relations (dicee.dataset_classes.TriplePredictionDataset attribute), 37
num_relations (dicee.evaluator.Evaluator attribute), 42
num_relations (dicee.knowledge_graph.KG attribute), 45
num_relations (dicee.models.base_model.BaseKGE attribute), 62
num_relations (dicee.models.BaseKGE attribute), 103, 106, 110, 114, 120, 133, 136
num_relations (dicee.NegSampleDataset attribute), 206
num_relations (dicee. Onevs Sample attribute), 204
num_relations (dicee. TriplePredictionDataset attribute), 207
\verb|num_sample| (\textit{dicee.models.FMult attribute}), 138
num_sample (dicee.models.function_space.FMult attribute), 76
num_sample (dicee.models.function_space.GFMult attribute), 77
num_sample (dicee.models.GFMult attribute), 139
num_tokens (dicee.BaseKGE attribute), 190
\verb|num_tokens| (\textit{dicee.knowledge\_graph.KG attribute}), 46
num_tokens (dicee.models.base_model.BaseKGE attribute), 62
num_tokens (dicee.models.BaseKGE attribute), 103, 106, 110, 114, 120, 133, 136
num_workers (dicee.CVDataModule attribute), 207
num_workers (dicee.dataset_classes.CVDataModule attribute), 37
numpy_data_type_changer() (in module dicee), 192
numpy_data_type_changer() (in module dicee.static_funcs), 156
\cap
octonion_mul() (in module dicee.models), 123
octonion_mul() (in module dicee.models.octonion), 80
octonion_mul_norm() (in module dicee.models), 123
octonion_mul_norm() (in module dicee.models.octonion), 80
octonion_normalizer() (dicee.AConvO static method), 179
octonion_normalizer() (dicee.ConvO static method), 181
octonion_normalizer() (dicee.models.AConvO static method), 125
octonion_normalizer() (dicee.models.ConvO static method), 125
octonion_normalizer() (dicee.models.octonion.AConvO static method), 82
octonion_normalizer() (dicee.models.octonion.ConvO static method), 81
octonion_normalizer() (dicee.models.octonion.OMult static method), 80
octonion_normalizer() (dicee.models.OMult static method), 124
octonion_normalizer() (dicee.OMult static method), 184
OMult (class in dicee), 183
OMult (class in dicee.models), 123
OMult (class in dicee.models.octonion), 80
on_epoch_end() (dicee.callbacks.KGESaveCallback method), 22
on_epoch_end() (dicee.callbacks.PseudoLabellingCallback method), 22
on_fit_end() (dicee.abstracts.AbstractCallback method), 17
on_fit_end() (dicee.abstracts.AbstractPPECallback method), 17
on_fit_end() (dicee.abstracts.AbstractTrainer method), 13
on_fit_end() (dicee.callbacks.AccumulateEpochLossCallback method), 20
on_fit_end() (dicee.callbacks.ASWA method), 23
on_fit_end() (dicee.callbacks.Eval method), 24
on_fit_end() (dicee.callbacks.KGESaveCallback method), 22
on_fit_end() (dicee.callbacks.PrintCallback method), 20
on_fit_start() (dicee.abstracts.AbstractCallback method), 16
on_fit_start() (dicee.abstracts.AbstractPPECallback method), 17
on_fit_start() (dicee.abstracts.AbstractTrainer method), 13
on_fit_start() (dicee.callbacks.Eval method), 24
on_fit_start() (dicee.callbacks.KGESaveCallback method), 21
on_fit_start() (dicee.callbacks.KronE method), 25
on_fit_start() (dicee.callbacks.PrintCallback method), 20
on_init_end() (dicee.abstracts.AbstractCallback method), 16
on_init_start() (dicee.abstracts.AbstractCallback method), 16
on_train_batch_end() (dicee.abstracts.AbstractCallback method), 16
on_train_batch_end() (dicee.abstracts.AbstractTrainer method), 13
```

```
on train batch end() (dicee.callbacks.Eval method), 24
on_train_batch_end() (dicee.callbacks.KGESaveCallback method), 21
on_train_batch_end() (dicee.callbacks.PrintCallback method), 21
on_train_batch_start() (dicee.callbacks.Perturb method), 26
on_train_epoch_end() (dicee.abstracts.AbstractCallback method), 16
on_train_epoch_end() (dicee.abstracts.AbstractTrainer method), 13
on_train_epoch_end() (dicee.callbacks.ASWA method), 23
on train epoch end() (dicee.callbacks.Eval method), 24
on_train_epoch_end() (dicee.callbacks.KGESaveCallback method), 22
\verb"on_train_epoch_end()" (\textit{dicee.callbacks.PrintCallback method}), 21
on_train_epoch_end() (dicee.models.base_model.BaseKGELightning method), 57
\verb"on_train_epoch_end"()" \textit{ (dicee.models.BaseKGELightning method}), 98
OnevsAllDataset (class in dicee), 201
OnevsAllDataset (class in dicee.dataset_classes), 31
OnevsSample (class in dicee), 203
OnevsSample (class in dicee.dataset_classes), 33
optim (dicee.config.Namespace attribute), 26
optimizer (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 163
optimizer (dicee.trainer.torch_trainer.TorchTrainer attribute), 162
optimizer_name (dicee.BaseKGE attribute), 190
optimizer_name (dicee.models.base_model.BaseKGE attribute), 62
optimizer_name (dicee.models.BaseKGE attribute), 103, 106, 110, 115, 121, 133, 137
ordered_bpe_entities (dicee.BPE_NegativeSamplingDataset attribute), 200
ordered_bpe_entities (dicee.dataset_classes.BPE_NegativeSamplingDataset attribute), 30
ordered_bpe_entities (dicee.knowledge_graph.KG attribute), 46
ordered_shaped_bpe_tokens (dicee.knowledge_graph.KG attribute), 45
P
p (dicee.config.Namespace attribute), 28
p (dicee.DeCaL attribute), 173
p (dicee.Keci attribute), 170
p (dicee.models.clifford.DeCaL attribute), 69
p (dicee.models.clifford.Keci attribute), 65
p (dicee.models.DeCaL attribute), 129
p (dicee.models.Keci attribute), 126
padding (dicee.knowledge_graph.KG attribute), 46
pandas_dataframe_indexer() (in module dicee.read_preprocess_save_load_kg.util), 148
param_init (dicee.BaseKGE attribute), 190
param_init (dicee.models.base_model.BaseKGE attribute), 63
param_init (dicee.models.BaseKGE attribute), 104, 107, 110, 115, 121, 134, 137
parameters () (dicee.abstracts.BaseInteractiveKGE method), 15
parameters () (dicee. Ensemble KGE method), 191
parameters () (dicee.models.ensemble.EnsembleKGE method), 75
path (dicee.abstracts.AbstractPPECallback attribute), 17
path (dicee.callbacks.AccumulateEpochLossCallback attribute), 20
path (dicee.callbacks.ASWA attribute), 23
path (dicee.callbacks.Eval attribute), 24
path (dicee.callbacks.KGESaveCallback attribute), 21
path_dataset_folder (dicee.analyse_experiments.Experiment attribute), 18
path_for_deserialization (dicee.knowledge_graph.KG attribute), 45
path_for_serialization (dicee.knowledge_graph.KG attribute), 45
path_single_kg (dicee.config.Namespace attribute), 26
path_single_kg (dicee.knowledge_graph.KG attribute), 45
path_to_store_single_run (dicee.config.Namespace attribute), 26
Perturb (class in dicee.callbacks), 25
polars_dataframe_indexer() (in module dicee.read_preprocess_save_load_kg.util), 147
poly_NN() (dicee.LFMult method), 185
poly_NN() (dicee.models.function_space.LFMult method), 78
poly_NN() (dicee.models.LFMult method), 140
polynomial () (dicee.LFMult method), 186
polynomial() (dicee.models.function_space.LFMult method), 79
\verb"polynomial"() \textit{ (dicee.models.LFMult method)}, 141
pop () (dicee.LFMult method), 186
pop() (dicee.models.function_space.LFMult method), 79
pop() (dicee.models.LFMult method), 141
pq (dicee.analyse_experiments.Experiment attribute), 18
predict() (dicee.KGE method), 196
```

```
predict () (dicee.knowledge graph embeddings.KGE method), 48
predict_dataloader() (dicee.models.base_model.BaseKGELightning method), 59
predict_dataloader() (dicee.models.BaseKGELightning method), 100
predict_literals() (dicee.KGE method), 199
\verb|predict_literals()| (\textit{dicee.knowledge\_graph\_embeddings.KGE method}), 50
predict_missing_head_entity() (dicee.KGE method), 195
predict_missing_head_entity() (dicee.knowledge_graph_embeddings.KGE method), 47
predict missing relations() (dicee.KGE method), 196
\verb|predict_missing_relations()| \textit{(dicee.knowledge\_graph\_embeddings.KGE method)}, 47
predict_missing_tail_entity() (dicee.KGE method), 196
predict_missing_tail_entity() (dicee.knowledge_graph_embeddings.KGE method), 48
predict_topk() (dicee.KGE method), 196
predict_topk() (dicee.knowledge_graph_embeddings.KGE method), 48
prepare_data() (dicee.CVDataModule method), 209
prepare_data() (dicee.dataset_classes.CVDataModule method), 39
preprocess_with_byte_pair_encoding() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 149
preprocess_with_byte_pair_encoding() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 144
preprocess_with_byte_pair_encoding_with_padding() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 149
preprocess_with_byte_pair_encoding_with_padding() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 144
preprocess_with_pandas() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 149
preprocess_with_pandas() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 144
preprocess_with_polars() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 150
preprocess_with_polars() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 145
preprocesses_input_args() (in module dicee.static_preprocess_funcs), 158
PreprocessKG (class in dicee.read_preprocess_save_load_kg), 149
PreprocessKG (class in dicee.read_preprocess_save_load_kg.preprocess), 144
PrintCallback (class in dicee.callbacks), 20
process (dicee.trainer.torch_trainer.TorchTrainer attribute), 162
proj (dicee.literal_classes.GatedLinearUnit attribute), 51
PseudoLabellingCallback (class in dicee.callbacks), 22
Pyke (class in dicee), 168
Pyke (class in dicee.models), 109
Pyke (class in dicee.models.real), 88
pykeen_model_kwargs (dicee.config.Namespace attribute), 28
PykeenKGE (class in dicee), 186
PykeenKGE (class in dicee.models), 135
PykeenKGE (class in dicee.models.pykeen models), 82
q (dicee.config.Namespace attribute), 28
g (dicee.DeCaL attribute), 173
q (dicee.Keci attribute), 170
q (dicee.models.clifford.DeCaL attribute), 69
q (dicee.models.clifford.Keci attribute), 65
q (dicee.models.DeCaL attribute), 129
q (dicee.models.Keci attribute), 126
qdrant_client (dicee.scripts.index_serve.NeuralSearcher attribute), 152
OMult (class in dicee), 182
QMult (class in dicee.models), 117
QMult (class in dicee.models.quaternion), 84
quaternion_mul() (in module dicee.models), 114
quaternion_mul() (in module dicee.models.static_funcs), 88
quaternion_mul_with_unit_norm() (in module dicee.models), 117
quaternion_mul_with_unit_norm() (in module dicee.models.quaternion), 84
\verb|quaternion_multiplication_followed_by_inner_product()| \textit{(dicee.models.QMult method)}, 118
quaternion_multiplication_followed_by_inner_product() (dicee.models.quaternion.QMult method), 84
quaternion_multiplication_followed_by_inner_product() (dicee.QMult method), 182
quaternion_normalizer() (dicee.models.QMult static method), 118
quaternion_normalizer() (dicee.models.quaternion.QMult static method), 85
quaternion_normalizer() (dicee.QMult static method), 183
queries (dicee.scripts.index_serve.StringListRequest attribute), 153
query_name_to_struct (dicee.query_generator.QueryGenerator attribute), 143
query_name_to_struct (dicee.QueryGenerator attribute), 211
QueryGenerator (class in dicee), 210
QueryGenerator (class in dicee.query_generator), 143
```

R

```
r (dicee.DeCaL attribute), 173
r (dicee.Keci attribute), 170
r (dicee.models.clifford.DeCaL attribute), 69
r (dicee.models.clifford.Keci attribute), 65
r (dicee.models.DeCaL attribute), 130
r (dicee.models.Keci attribute), 126
random_prediction() (in module dicee), 193
random_prediction() (in module dicee.static_funcs), 156
random_seed (dicee.config.Namespace attribute), 27
ratio (dicee.callbacks.Perturb attribute), 25
re (dicee.DeCaL attribute), 173
re (dicee.models.clifford.DeCaL attribute), 69
re (dicee.models.DeCaL attribute), 130
re_vocab (dicee.evaluator.Evaluator attribute), 42
read_from_disk() (in module dicee.read_preprocess_save_load_kg.util), 148
read_from_triple_store() (in module dicee.read_preprocess_save_load_kg.util), 148
\verb"read_only_few" (\textit{dicee.config.Namespace attribute}), 28
read_only_few (dicee.knowledge_graph.KG attribute), 45
read_or_load_kg() (in module dicee), 193
read_or_load_kg() (in module dicee.static_funcs), 156
read_with_pandas() (in module dicee.read_preprocess_save_load_kg.util), 148
read_with_polars() (in module dicee.read_preprocess_save_load_kg.util), 148
ReadFromDisk (class in dicee.read_preprocess_save_load_kg), 150
{\tt ReadFromDisk}~(\textit{class in dicee.read\_preprocess\_save\_load\_kg.read\_from\_disk}),~145
reducer (dicee.scripts.index_serve.StringListRequest attribute), 153
rel2id (dicee.query_generator.QueryGenerator attribute), 143
rel2id (dicee. Ouery Generator attribute), 211
relation_embeddings (dicee.AConvQ attribute), 179
relation_embeddings (dicee.ConvQ attribute), 180
relation_embeddings (dicee.DeCaL attribute), 173
relation_embeddings (dicee.DualE attribute), 176
relation_embeddings (dicee.LFMult attribute), 185
relation_embeddings (dicee.models.AConvQ attribute), 119
relation_embeddings (dicee.models.clifford.DeCaL attribute), 69
relation_embeddings (dicee.models.ConvQ attribute), 119
relation_embeddings (dicee.models.DeCaL attribute), 129
relation_embeddings (dicee.models.DualE attribute), 141
relation_embeddings (dicee.models.dualE.DualE attribute), 74
relation_embeddings (dicee.models.FMult attribute), 138
relation_embeddings (dicee.models.FMult2 attribute), 139
{\tt relation\_embeddings}~(\textit{dicee.models.function\_space.FMult~attribute}), 76
relation_embeddings (dicee.models.function_space.FMult2 attribute), 77
{\tt relation\_embeddings}~({\it dicee.models.function\_space.GFMult~attribute}), 77
relation_embeddings (dicee.models.function_space.LFMult attribute), 78
relation_embeddings (dicee.models.function_space.LFMult1 attribute), 78
relation_embeddings (dicee.models.GFMult attribute), 139
relation_embeddings (dicee.models.LFMult attribute), 140
relation_embeddings (dicee.models.LFMult1 attribute), 140
relation_embeddings (dicee.models.pykeen_models.PykeenKGE attribute), 83
relation_embeddings (dicee.models.PykeenKGE attribute), 135
relation_embeddings (dicee.models.quaternion.AConvQ attribute), 86
relation_embeddings (dicee.models.quaternion.ConvQ attribute), 85
relation_embeddings (dicee.PykeenKGE attribute), 186
relation_to_idx (dicee.knowledge_graph.KG attribute), 46
relations_str (dicee.knowledge_graph.KG property), 46
reload dataset() (in module dicee), 199
reload_dataset() (in module dicee.dataset_classes), 29
report (dicee.DICE_Trainer attribute), 194
report (dicee.evaluator.Evaluator attribute), 42
report (dicee.executer.Execute attribute), 43
report (dicee.trainer.DICE_Trainer attribute), 164
report (dicee.trainer.dice_trainer.DICE_Trainer attribute), 159
reports (dicee.callbacks.Eval attribute), 24
requires_grad_for_interactions (dicee.CKeci attribute), 169
requires_grad_for_interactions (dicee.Keci attribute), 170
requires_grad_for_interactions (dicee.models.CKeci attribute), 129
requires_grad_for_interactions (dicee.models.clifford.CKeci attribute), 68
```

```
requires_grad_for_interactions (dicee.models.clifford.Keci attribute), 65
requires_grad_for_interactions (dicee.models.Keci attribute), 126
resid_dropout (dicee.models.transformers.CausalSelf Attention attribute), 92
residual (dicee.literal_classes.LiteralEmbeddings attribute), 52
residual_convolution() (dicee.AConEx method), 178
residual_convolution() (dicee.AConvO method), 179
residual_convolution() (dicee.AConvQ method), 179
residual convolution() (dicee.ConEx method), 181
residual_convolution() (dicee.ConvO method), 181
residual_convolution() (dicee.ConvQ method), 180
residual_convolution() (dicee.models.AConEx method), 112
residual_convolution() (dicee.models.AConvO method), 125
residual_convolution() (dicee.models.AConvQ method), 119
residual_convolution() (dicee.models.complex.AConEx method), 73
residual_convolution() (dicee.models.complex.ConEx method), 72
residual_convolution() (dicee.models.ConEx method), 112
residual_convolution() (dicee.models.ConvO method), 125
residual_convolution() (dicee.models.ConvQ method), 119
residual_convolution() (dicee.models.octonion.AConvO method), 82
residual_convolution() (dicee.models.octonion.ConvO method), 81
residual_convolution() (dicee.models.quaternion.AConvQ method), 86
residual_convolution() (dicee.models.quaternion.ConvQ method), 86
retrieve_embedding() (dicee.scripts.index_serve.NeuralSearcher method), 152
retrieve_embeddings() (in module dicee.scripts.index_serve), 152
return_multi_hop_query_results() (dicee.KGE method), 197
return_multi_hop_query_results() (dicee.knowledge_graph_embeddings.KGE method), 49
root() (in module dicee.scripts.index_serve), 152
roots (dicee.models.FMult attribute), 138
roots (dicee.models.function_space.FMult attribute), 76
roots (dicee.models.function_space.GFMult attribute), 77
roots (dicee.models.GFMult attribute), 139
runtime (dicee.analyse_experiments.Experiment attribute), 19
sample_counter (dicee.abstracts.AbstractPPECallback attribute), 17
sample_entity() (dicee.abstracts.BaseInteractiveKGE method), 14
sample_relation() (dicee.abstracts.BaseInteractiveKGE method), 14
sample_triples_ratio (dicee.config.Namespace attribute), 28
sample_triples_ratio (dicee.knowledge_graph.KG attribute), 45
sampling_ratio (dicee.literal_classes.LiteralDataset attribute), 53, 54
sanity_checking_with_arguments() (in module dicee.sanity_checkers), 151
save() (dicee.abstracts.BaseInteractiveKGE method), 14
\verb|save()| (dicee.read\_preprocess\_save\_load\_kg.LoadSaveToDisk method), 150|
save() (dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk method), 146
save_checkpoint() (dicee.abstracts.AbstractTrainer static method), 13
save_checkpoint_model() (in module dicee), 192
save_checkpoint_model() (in module dicee.static_funcs), 156
save embeddings() (in module dicee), 193
save_embeddings() (in module dicee.static_funcs), 156
save_embeddings_as_csv (dicee.config.Namespace attribute), 26
save_experiment() (dicee.analyse_experiments.Experiment method), 19
save_model_at_every_epoch (dicee.config.Namespace attribute), 27
save_numpy_ndarray() (in module dicee), 192
save_numpy_ndarray() (in module dicee.read_preprocess_save_load_kg.util), 149
save_numpy_ndarray() (in module dicee.static_funcs), 156
save_pickle() (in module dicee), 192
save_pickle() (in module dicee.read_preprocess_save_load_kg.util), 149
save_pickle() (in module dicee.static_funcs), 156
save_queries() (dicee.query_generator.QueryGenerator method), 144
save_queries() (dicee.QueryGenerator method), 211
save_queries_and_answers() (dicee.query_generator.QueryGenerator static method), 144
save_queries_and_answers() (dicee.QueryGenerator static method), 212
save_trained_model() (dicee.executer.Execute method), 44
scalar_batch_NN() (dicee.LFMult method), 185
scalar_batch_NN() (dicee.models.function_space.LFMult method), 78
scalar_batch_NN() (dicee.models.LFMult method), 141
scaler (dicee.callbacks.Perturb attribute), 25
```

```
scaler (dicee.trainer.torch trainer ddp.NodeTrainer attribute), 164
score () (dicee.ComplEx static method), 177
score () (dicee.DistMult method), 169
score () (dicee. Keci method), 172
score () (dicee.models.clifford.Keci method), 68
score () (dicee.models.ComplEx static method), 113
score() (dicee.models.complex.ComplEx static method), 73
score () (dicee.models.DistMult method), 108
score () (dicee.models.Keci method), 128
score() (dicee.models.octonion.OMult method), 80
score () (dicee.models.OMult method), 124
score() (dicee.models.QMult method), 118
score () (dicee.models.quaternion.QMult method), 85
score() (dicee.models.real.DistMult method), 87
score() (dicee.models.real.TransE method), 87
score () (dicee.models.TransE method), 109
score () (dicee.OMult method), 184
score () (dicee.QMult method), 183
score () (dicee. TransE method), 172
score_func (dicee.models.FMult2 attribute), 139
score_func (dicee.models.function_space.FMult2 attribute), 77
scoring_technique (dicee.analyse_experiments.Experiment attribute), 19
scoring_technique (dicee.config.Namespace attribute), 27
search() (dicee.scripts.index_serve.NeuralSearcher method), 152
search_embeddings() (in module dicee.scripts.index_serve), 152
search_embeddings_batch() (in module dicee.scripts.index_serve), 154
seed (dicee.query_generator.QueryGenerator attribute), 143
seed (dicee.QueryGenerator attribute), 211
select_model() (in module dicee), 192
select_model() (in module dicee.static_funcs), 156
selected_optimizer (dicee.BaseKGE attribute), 190
selected_optimizer (dicee.models.base_model.BaseKGE attribute), 62
selected_optimizer (dicee.models.BaseKGE attribute), 103, 107, 110, 115, 121, 133, 137
separator (dicee.config.Namespace attribute), 27
separator (dicee.knowledge_graph.KG attribute), 46
sequential_vocabulary_construction() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 150
sequential_vocabulary_construction() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 145
serve() (in module dicee.scripts.index_serve), 154
set_global_seed() (dicee.query_generator.QueryGenerator method), 143
set_global_seed() (dicee.QueryGenerator method), 211
\verb|set_model_eval_mode()| \textit{ (dicee. abstracts. Base Interactive KGE method), } 14
set_model_train_mode() (dicee.abstracts.BaseInteractiveKGE method), 14
setup() (dicee.CVDataModule method), 208
setup() (dicee.dataset_classes.CVDataModule method), 38
setup_executor() (dicee.executer.Execute method), 44
Shallom (class in dicee), 184
Shallom (class in dicee.models), 109
Shallom (class in dicee.models.real), 87
shallom (dicee.models.real.Shallom attribute), 87
shallom (dicee.models.Shallom attribute), 109
shallom (dicee.Shallom attribute), 184
single_hop_query_answering() (dicee.KGE method), 197
single_hop_query_answering() (dicee.knowledge_graph_embeddings.KGE method), 49
spargl_endpoint (dicee.config.Namespace attribute), 26
sparql_endpoint (dicee.knowledge_graph.KG attribute), 45
start() (dicee.DICE_Trainer method), 194
start() (dicee.executer.Execute method), 44
start() (dicee.read_preprocess_save_load_kg.PreprocessKG method), 149
start() (dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method), 144
start() (dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk method), 145
start() (dicee.read_preprocess_save_load_kg.ReadFromDisk method), 150
start () (dicee.trainer.DICE_Trainer method), 165
\verb|start()| (\textit{dicee.trainer.dice\_trainer.DICE\_Trainer method}), 160
start_time (dicee.callbacks.PrintCallback attribute), 20
start_time (dicee.executer.Execute attribute), 43
step() (dicee.EnsembleKGE method), 192
step() (dicee.models.ADOPT method), 97
step() (dicee.models.adopt.ADOPT method), 55
```

```
step() (dicee.models.ensemble.EnsembleKGE method), 76
storage_path (dicee.config.Namespace attribute), 26
storage_path (dicee.DICE_Trainer attribute), 194
storage_path (dicee.trainer.DICE_Trainer attribute), 164
storage_path (dicee.trainer.dice_trainer.DICE_Trainer attribute), 160
store() (in module dicee), 192
store() (in module dicee.static_funcs), 156
store ensemble() (dicee.abstracts.AbstractPPECallback method), 18
strategy (dicee.abstracts.AbstractTrainer attribute), 12
StringListRequest (class in dicee.scripts.index_serve), 152
swa (dicee.config.Namespace attribute), 28
Т
T() (dicee.DualE method), 177
T() (dicee.models.DualE method), 142
T() (dicee.models.dualE.DualE method), 75
t_conorm() (dicee.abstracts.InteractiveQueryDecomposition method), 15
t_norm() (dicee.abstracts.InteractiveQueryDecomposition method), 15
target_dim (dicee.AllvsAll attribute), 203
target_dim (dicee.dataset_classes.AllvsAll attribute), 33
target_dim (dicee.dataset_classes.MultiLabelDataset attribute), 30
target_dim (dicee.dataset_classes.OnevsAllDataset attribute), 31
target_dim (dicee.knowledge_graph.KG attribute), 46
target_dim (dicee.MultiLabelDataset attribute), 200
target_dim (dicee.OnevsAllDataset attribute), 202
temperature (dicee.BytE attribute), 187
temperature (dicee.models.transformers.BytE attribute), 89
tensor\_t\_norm() (dicee.abstracts.InteractiveQueryDecomposition method), 15
TensorParallel (class in dicee.trainer.model_parallelism), 161
test_dataloader() (dicee.models.base_model.BaseKGELightning method), 58
test_dataloader() (dicee.models.BaseKGELightning method), 99
test_epoch_end() (dicee.models.base_model.BaseKGELightning method), 58
test_epoch_end() (dicee.models.BaseKGELightning method), 99
test_h1 (dicee.analyse_experiments.Experiment attribute), 19
test_h3 (dicee.analyse_experiments.Experiment attribute), 19
test_h10 (dicee.analyse_experiments.Experiment attribute), 19
test_mrr (dicee.analyse_experiments.Experiment attribute), 19
test_path (dicee.query_generator.QueryGenerator attribute), 143
test_path (dicee.QueryGenerator attribute), 211
timeit() (in module dicee), 192, 199
timeit() (in module dicee.read_preprocess_save_load_kg.util), 148
timeit() (in module dicee.static_funcs), 156
timeit() (in module dicee.static_preprocess_funcs), 158
to() (dicee.EnsembleKGE method), 192
to() (dicee.KGE method), 195
to() (dicee.knowledge_graph_embeddings.KGE method), 47
to() (dicee.models.ensemble.EnsembleKGE method), 75
to_df() (dicee.analyse_experiments.Experiment method), 19
topk (dicee.BytE attribute), 187
{\tt topk}~({\it dicee.models.transformers.BytE~attribute}),\,89
topk (dicee.scripts.index_serve.NeuralSearcher attribute), 152
torch_ordered_shaped_bpe_entities (dicee.dataset_classes.MultiLabelDataset attribute), 30
torch_ordered_shaped_bpe_entities (dicee.MultiLabelDataset attribute), 201
TorchDDPTrainer (class in dicee.trainer.torch_trainer_ddp), 163
TorchTrainer (class in dicee.trainer.torch_trainer), 162
train() (dicee.KGE method), 198
train() (dicee.knowledge_graph_embeddings.KGE method), 50
train() (dicee.trainer.torch_trainer_ddp.NodeTrainer method), 164
train_data (dicee.AllvsAll attribute), 203
train_data (dicee.dataset_classes.AllvsAll attribute), 33
train_data (dicee.dataset_classes.KvsAll attribute), 32
train_data (dicee.dataset_classes.KvsSampleDataset attribute), 35
train_data (dicee.dataset_classes.MultiClassClassificationDataset attribute), 31
train_data (dicee.dataset_classes.OnevsAllDataset attribute), 31
train_data (dicee.dataset_classes.OnevsSample attribute), 33, 34
train_data (dicee.KvsAll attribute), 202
train_data (dicee.KvsSampleDataset attribute), 205
```

```
train data (dicee. MultiClass Classification Dataset attribute), 201
train_data (dicee.OnevsAllDataset attribute), 201
train data (dicee. Onevs Sample attribute), 203, 204
train_dataloader() (dicee.CVDataModule method), 207
train_dataloader() (dicee.dataset_classes.CVDataModule method), 37
train_dataloader() (dicee.models.base_model.BaseKGELightning method), 59
train_dataloader() (dicee.models.BaseKGELightning method), 100
train dataloaders (dicee.trainer.torch trainer.TorchTrainer attribute), 162
train_dataset_loader (dicee.trainer.torch_trainer_ddp.NodeTrainer attribute), 164
\verb|train_file_path| (\textit{dicee.literal\_classes.LiteralDataset attribute}), 53, 54
train_h1 (dicee.analyse_experiments.Experiment attribute), 18
train_h3 (dicee.analyse_experiments.Experiment attribute), 19
train_h10 (dicee.analyse_experiments.Experiment attribute), 19
train_indices_target (dicee.dataset_classes.MultiLabelDataset attribute), 30
\verb|train_indices_target| \textit{(dicee.MultiLabelDataset attribute)}, 200
train_k_vs_all() (dicee.KGE method), 198
\verb|train_k_vs_all()| \textit{(dicee.knowledge\_graph\_embeddings.KGE method)}, 50
train_literals() (dicee.KGE method), 198
train_literals() (dicee.knowledge_graph_embeddings.KGE method), 50
train_mode (dicee.EnsembleKGE attribute), 191
train_mode (dicee.models.ensemble.EnsembleKGE attribute), 75
train_mrr (dicee.analyse_experiments.Experiment attribute), 18
train_path (dicee.query_generator.QueryGenerator attribute), 143
train_path (dicee.QueryGenerator attribute), 210
train_set (dicee.BPE_NegativeSamplingDataset attribute), 200
train_set (dicee.dataset_classes.BPE_NegativeSamplingDataset attribute), 30
train_set (dicee.dataset_classes.MultiLabelDataset attribute), 30
train_set (dicee.dataset_classes.NegSampleDataset attribute), 36
train_set (dicee.dataset_classes.TriplePredictionDataset attribute), 37
train_set (dicee.MultiLabelDataset attribute), 200
train_set (dicee.NegSampleDataset attribute), 206
train set (dicee. TriplePredictionDataset attribute), 207
train_set_idx (dicee.CVDataModule attribute), 207
\verb|train_set_idx| \textit{(dicee.dataset\_classes.CVDataModule attribute)}, 37
train_set_target (dicee.knowledge_graph.KG attribute), 46
train_target (dicee.AllvsAll attribute), 203
train target (dicee.dataset classes.AllvsAll attribute), 33
train_target (dicee.dataset_classes.KvsAll attribute), 32
train_target (dicee.dataset_classes.KvsSampleDataset attribute), 35
train_target (dicee.KvsAll attribute), 202
train_target (dicee.KvsSampleDataset attribute), 205
train_target_indices (dicee.knowledge_graph.KG attribute), 46
train_triples() (dicee.KGE method), 198
train_triples() (dicee.knowledge_graph_embeddings.KGE method), 50
trained_model (dicee.executer.Execute attribute), 43
trainer (dicee.config.Namespace attribute), 27
trainer (dicee.DICE_Trainer attribute), 194
trainer (dicee.executer.Execute attribute), 43
trainer (dicee.trainer.DICE_Trainer attribute), 164
trainer (dicee.trainer.dice_trainer.DICE_Trainer attribute), 159
\verb|trainer| (\textit{dicee.trainer.torch\_trainer\_ddp.NodeTrainer attribute}), 163
training_step (dicee.trainer.torch_trainer.TorchTrainer attribute), 162
training_step() (dicee.BytE method), 188
training_step() (dicee.models.base_model.BaseKGELightning method), 56
training_step() (dicee.models.BaseKGELightning method), 97
{\tt training\_step()} \ (\textit{dicee.models.transformers.BytE method}), 90
training_step_outputs (dicee.models.base_model.BaseKGELightning attribute), 56
training_step_outputs (dicee.models.BaseKGELightning attribute), 97
training_technique (dicee.knowledge_graph.KG attribute), 46
TransE (class in dicee), 172
TransE (class in dicee.models), 108
TransE (class in dicee.models.real), 87
{\tt transfer\_batch\_to\_device()} \ \textit{(dicee.CVDataModule method)}, 208
transfer_batch_to_device() (dicee.dataset_classes.CVDataModule method), 38
transformer (dicee. BytE attribute), 187
transformer (dicee.models.transformers.BytE attribute), 90
transformer (dicee.models.transformers.GPT attribute), 95
trapezoid() (dicee.models.FMult2 method), 140
```

```
trapezoid() (dicee.models.function_space.FMult2 method), 77
tri_score() (dicee.LFMult method), 185
tri_score() (dicee.models.function_space.LFMult method), 78
tri_score() (dicee.models.function_space.LFMult1 method), 78
tri_score() (dicee.models.LFMult method), 141
tri_score() (dicee.models.LFMult1 method), 140
triple_score() (dicee.KGE method), 197
triple_score() (dicee.knowledge_graph_embeddings.KGE method), 48
TriplePredictionDataset (class in dicee), 206
TriplePredictionDataset (class in dicee.dataset_classes), 36
tuple2list() (dicee.query_generator.QueryGenerator method), 143
tuple2list() (dicee.QueryGenerator method), 211
U
unlabelled_size (dicee.callbacks.PseudoLabellingCallback attribute), 22
unmap() (dicee.query_generator.QueryGenerator method), 143
unmap () (dicee. Query Generator method), 211
unmap_query() (dicee.query_generator.QueryGenerator method), 143
unmap_query() (dicee.QueryGenerator method), 211
V
val_aswa (dicee.callbacks.ASWA attribute), 23
val_dataloader() (dicee.models.base_model.BaseKGELightning method), 59
val_dataloader() (dicee.models.BaseKGELightning method), 100
val_h1 (dicee.analyse_experiments.Experiment attribute), 19
val_h3 (dicee.analyse_experiments.Experiment attribute), 19
val_h10 (dicee.analyse_experiments.Experiment attribute), 19
val_mrr (dicee.analyse_experiments.Experiment attribute), 19
val_path (dicee.query_generator.QueryGenerator attribute), 143
val_path (dicee.QueryGenerator attribute), 211
validate_knowledge_graph() (in module dicee.sanity_checkers), 151
vocab_preparation() (dicee.evaluator.Evaluator method), 42
vocab_size (dicee.models.transformers.GPTConfig attribute), 94
vocab_to_parquet() (in module dicee), 193
vocab_to_parquet() (in module dicee.static_funcs), 157
vtp_score() (dicee.LFMult method), 185
\verb|vtp_score|| (\textit{dicee.models.function\_space.LFMult method}), 79
vtp_score() (dicee.models.function_space.LFMult1 method), 78
vtp_score() (dicee.models.LFMult method), 141
vtp_score() (dicee.models.LFMult1 method), 140
W
weight (dicee.models.transformers.LayerNorm attribute), 91
weight_decay (dicee.BaseKGE attribute), 190
weight_decay (dicee.config.Namespace attribute), 27
weight_decay (dicee.models.base_model.BaseKGE attribute), 62
weight_decay (dicee.models.BaseKGE attribute), 103, 107, 110, 115, 121, 133, 137
weights (dicee.models.FMult attribute), 138
weights (dicee.models.function_space.FMult attribute), 76
weights (dicee.models.function_space.GFMult attribute), 77
weights (dicee.models.GFMult attribute), 139
write_csv_from_model_parallel() (in module dicee), 193
write_csv_from_model_parallel() (in module dicee.static_funcs), 157
write_links() (dicee.query_generator.QueryGenerator method), 143
write_links() (dicee.QueryGenerator method), 211
write_report() (dicee.executer.Execute method), 44
X
x_values (dicee.LFMult attribute), 185
x_values (dicee.models.function_space.LFMult attribute), 78
x_values (dicee.models.LFMult attribute), 140
```