
OWLAPY

Release 1.2.0

Ontolearn Team

Aug 28, 2024

Contents:

1	About owlapy	2
1.1	What is owlapy?	2
1.2	What does owlapy have to offer?	2
1.3	How to install?	3
2	Basic Usage	3
2.1	Atomic Classes	4
2.2	Object Property	4
2.3	Complex class expressions	4
2.4	Convert to SPARQL, DL or Manchester syntax	5
3	Ontologies	6
3.1	Loading an Ontology	6
3.2	Modifying an Ontology	6
3.3	Save an Ontology	8
3.4	Worlds	8
4	Reasoners	9
4.1	Usage of the Reasoner	10
4.2	Class Reasoning	10
4.3	Object Properties and Data Properties Reasoning	11
4.4	Find Instances	11
5	Owlapi Adaptor	12
5.1	Initialization	12
5.2	Notes	12
5.3	Examples	13
6	Further Resources	13
6.1	More Inside the Project	13
6.2	Contribution	13
6.3	Questions	13
6.4	Coverage Report	13
7	owlapy	15
7.1	Subpackages	15
7.2	Submodules	48

7.3	Attributes	147
7.4	Functions	147
7.5	Package Contents	147
Python Module Index		149
Index		150

OWLAPY¹: Representation of OWL objects in python.

1 About owlapy

Version: owlapy 1.2.0

GitHub repository: <https://github.com/dice-group/owlapy>

Publisher and maintainer: DICE² - data science research group of Paderborn University³.

Contact: onto-learn@lists.uni-paderborn.de

License: MIT License

1.1 What is owlapy?

Owlapy is an open-source software library in python that is used to represent entities in OWL 2 Web Ontology Language.

We identified the gap of having a library that will serve as a base structure for representing OWL entities and for manipulating OWL Ontologies in python, and like that, owlapy was created. Owlapy is loosely based on its java-counterpart, *owlapi*. Owlapy is currently utilized by powerful libraries such as [Ontolearn](#)⁴ and [OntoSample](#)⁵.

Owlapy is the perfect choice for machine learning projects that are built in python and focus on knowledge graphs and class expression learnings.

1.2 What does owlapy have to offer?

- Create, manipulate and save Ontologies.
- Retrieving information from the signature of the ontology.
- Reasoning over ontology.
- Represent every notation in [OWL 2 Structural Specification and Functional-Style Syntax](#)⁶ including:
 - Entities, Literals, and Anonymous Individuals

¹ <https://github.com/dice-group/owlapy>

² <https://dice-research.org/>

³ <https://www.uni-paderborn.de/en/university>

⁴ <https://github.com/dice-group/Ontolearn>

⁵ <https://github.com/alkidbaci/OntoSample>

⁶ <https://www.w3.org/TR/owl2-syntax/>

- Property Expressions
- Data Ranges
- Class Expressions
- Axioms
- Annotations
- Construct complex class expressions.
- Provide interfaces for OWL Ontology, Ontology manager and Reasoner.
- Convert owl expression to SPARQL queries.
- Render owl expression to Description Logics or Manchester syntax.
- Parse Description Logics or Manchester expression to owl expression.

1.3 How to install?

Installation from source:

```
git clone https://github.com/dice-group/owlapy
conda create -n temp_owlapy python=3.10.13 --no-default-packages && conda activate_
temp_owlapy && pip3 install -e .
```

or using PyPI:

```
pip3 install owlapy
```

2 Basic Usage

The main usage for owlapy is to use it for class expression construction. Class expression learning algorithms require such basic structure to work upon. Let's walk through an example of constructing some class expressions.

In this example we will be using the *family* ontology, a simple ontology with namespace: `http://example.com/family#`. Here is a hierarchical diagram that shows the classes and their relationship:

```

      Thing
      |
    person
    /   |
  male female

```

It contains only one object property which is `hasChild` and in total there are six persons (individuals), of which four are males and two are females.

2.1 Atomic Classes

To represent the classes `male`, `female`, and `person` we can simply use the class `OWLClass`⁷:

```
from owlapy.class_expression import OWLClass
from owlapy.iri import IRI

namespace = "http://example.com/family#"

male = OWLClass(IRI(namespace, "male"))
female = OWLClass(IRI(namespace, "female"))
person = OWLClass(IRI(namespace, "person"))
```

Notice that we created an `IRI` object for every class. `IRI`⁸ is used to represent an *IRI*. Every named entity requires an `IRI`, whereas Anonymous entities does not. However, in owlapy you can create an `OWLClass` by passing the *IRI* directly as a string, like so:

```
male = OWLClass("http://example.com/family#male")
```

2.2 Object Property

To represent the object property `hasChild` we can use the class `OWLObjectProperty`⁹:

```
from owlapy.owl_property import OWLObjectProperty

hasChild = OWLObjectProperty("http://example.com/family#hasChild")
```

Tip: In owlapy the naming of the classes is made in accordance with the notations from OWL 2 specification but with the word “OWL” in the beginning. Example: “*OWLObjectProperty*” represents the notation “*ObjectProperty*”.

2.3 Complex class expressions

Now that we have these atomic entities, we can construct more complex class expressions. Let’s say we want to represent all individuals which are `male` and have at least 1 child.

We already have the concept of `male`. We need to find the appropriate class for the second part: “*have at least 1 child*”. In OWL 2 specification that would be `ObjectMinCardinality`¹⁰. In owlapy, as we said, we simply add the word “OWL” upfront to find the correct class:

```
from owlapy.class_expression import OWLObjectMinCardinality

has_at_least_one_child = OWLObjectMinCardinality(
    cardinality = 1,
    property = hasChild,
    filler = person
)
```

⁷ https://dice-group.github.io/owlapy/autoapi/owlapy/class_expression/owl_class/index.html#owlapy.class_expression.owl_class.OWLClass

⁸ <https://dice-group.github.io/owlapy/autoapi/owlapy/iri/index.html#owlapy.iri.IRI>

⁹ https://dice-group.github.io/owlapy/autoapi/owlapy/owl_property/index.html#owlapy.owl_property.OWLObjectProperty

¹⁰ https://www.w3.org/TR/owl2-syntax/#Minimum_Cardinality

As you can see, to create an object of class `OWLObjectMinCardinality`¹¹ is as easy as that. You specify the cardinality which in this case is 1, the object property where we apply this cardinality restriction and the filler class in case you want to restrict the domain of the class expression. In this case we used `person`.

Now let's merge both class expressions together using `OWLObjectIntersectionOf`¹²:

```
from owlapy.class_expression import OWLObjectIntersectionOf

ce = OWLObjectIntersectionOf([male, has_at_least_one_child])
```

2.4 Convert to SPARQL, DL or Manchester syntax

Owlapy is not just a library to represent OWL entities, you can also use it to convert owl expressions into other formats:

```
from owlapy import owl_expression_to_sparql, owl_expression_to_dl, owl_expression_to_
    ↳manchester

print(owl_expression_to_dl(ce))
# Result: male ♂ (> 1 hasChild.person)

print(owl_expression_to_sparql(ce))
# Result: SELECT DISTINCT ?x WHERE { ?x a <http://example.com/family#male> . { SELECT_
    ↳?x WHERE { ?x <http://example.com/family#hasChild> ?s_1 . ?s_1 a <http://example.
    ↳com/family#person> . } GROUP BY ?x HAVING ( COUNT ( ?s_1 ) >= 1 ) } }

print(owl_expression_to_manchester(ce))
# Result: male and (hasChild min 1 person)
```

To parse a DL or Manchester expression to owl expression you can use the following convenient methods:

```
from owlapy import dl_to_owl_expression, manchester_to_owl_expression

print(dl_to_owl_expression("∃ hasChild.male", namespace))
# Result: OWLObjectSomeValuesFrom(property=OWLObjectProperty(IRI('http://example.com/
    ↳family#', 'hasChild')), filler=OWLObjectClass(IRI('http://example.com/family#', 'male')))

print(manchester_to_owl_expression("female and (hasChild max 2 person)", namespace))
# Result: OWLObjectIntersectionOf((OWLObjectClass(IRI('http://example.com/family#', 'female
    ↳')), OWLObjectMaxCardinality(property=OWLObjectProperty(IRI('http://example.com/
    ↳family#', 'hasChild')), 2, filler=OWLObjectClass(IRI('http://example.com/family#', 'person
    ↳')))))
```

In these examples we showed a fraction of **owlapy**. You can explore the *api documentation* to learn more about all classes in owlapy and check more examples in the `examples`¹³ directory.

¹¹ https://dice-group.github.io/owlapy/autoapi/owlapy/class_expression/restriction/index.html#owlapy.class_expression.restriction.OWLObjectMinCardinality

¹² https://dice-group.github.io/owlapy/autoapi/owlapy/class_expression/nary_boolean_expression/index.html#owlapy.class_expression.nary_boolean_expression.OWLObjectIntersectionOf

¹³ <https://github.com/dice-group/owlapy/tree/develop/examples>

3 Ontologies

To get started with Structured Machine Learning, the first thing required is an *Ontology*¹⁴ with *Named Individuals*¹⁵. In this guide we show the basics of working with ontologies in Owlapy. We will use the *father* ontology for the following examples.

3.1 Loading an Ontology

To load an ontology as well as to manage it, you will need an *OWL**OntologyManager*. An ontology can be loaded using the following Python code:

```
from owlapy.iri import IRI
from owlapy.owl_ontology_manager import OntologyManager

manager = OntologyManager()
onto = manager.load_ontology(IRI.create("file://KGs/Family/father.owl"))
```

First, we import the *IRI* class and a suitable *OWL**OntologyManager*. To load a file from our computer, we have to reference it with an *IRI*. Secondly, we need the *Ontology Manager*. Owlapy contains one such manager: The *Ontology-Manager*.

Now, we can already inspect the contents of the ontology. For example, to list all individuals:

```
for ind in onto.individuals_in_signature():
    print(ind)
```

You can get the object properties in the signature:

```
onto.object_properties_in_signature()
```

For more methods, see the abstract class *OWL**Ontology* or the concrete implementation *Ontology*.

3.2 Modifying an Ontology

Axioms in ontology serve as the basis for defining the vocabulary of a domain and for making statements about the relationships between individuals and concepts in that domain. They provide a formal and precise way to represent knowledge and allow for automated reasoning and inference. Axioms can be **added**, **modified**, or **removed** from an ontology, allowing the ontology to evolve and adapt as new knowledge is gained.

In owlapy we also have different axioms represented by different classes. You can check all the axioms classes *here*. Some frequently used axioms are:

- *OWLDeclarationAxiom*
- *OWLObjectPropertyAssertionAxiom*
- *OWLDataPropertyAssertionAxiom*
- *OWLClassAssertionAxiom*
- *OWLSubClassOfAxiom*
- *OWLEquivalentClassesAxiom*

¹⁴ <https://www.w3.org/TR/owl2-overview/>

¹⁵ https://www.w3.org/TR/owl-syntax/#Named_Individuals

Add a new Class

Let's suppose you want to add a new class in our example ontology `KGs/Family/father.owl`. It can be done as follows:

```
from owlapy.class_expression import OWLClass
from owlapy.owl_axiom import OWLDeclarationAxiom

iri = IRI('http://example.com/father#', 'child')
child_class = OWLClass(iri)
child_class_declaration_axiom = OWLDeclarationAxiom(child_class)

onto.add_axiom(child_class_declaration_axiom)
```

In this example, we added the class 'child' to the *father.owl* ontology. Firstly we create an instance of *OWLClass* to represent the concept of 'child' by using an *IRI*. On the other side, an instance of *IRI* is created by passing two arguments which are the namespace of the ontology and the remainder 'child'. To declare this new class we need an axiom of type *OWLDeclarationAxiom*. We simply pass the *child_class* to create an instance of this axiom. The final step is to add this axiom to the ontology. We use the *add_axiom* method to add into the ontology *onto* the axiom *child_class_declaration_axiom*.

Add a new Object Property / Data Property

The idea is the same as adding a new class. Instead of *OWLClass*, for object properties, you can use the class *OWLObjectProperty* and for data properties you can use the class *OWLDataProperty*.

```
from owlapy.owl_property import OWLObjectProperty, OWLDataProperty

# adding the object property 'hasParent'
hasParent_op = OWLObjectProperty(IRI('http://example.com/father#', 'hasParent'))
hasParent_op_declaration_axiom = OWLDeclarationAxiom(hasParent_op)
onto.add_axiom(hasParent_op_declaration_axiom)

# adding the data property 'hasAge'
hasAge_dp = OWLDataProperty(IRI('http://example.com/father#', 'hasAge'))
hasAge_dp_declaration_axiom = OWLDeclarationAxiom(hasAge_dp)
onto.add_axiom(hasAge_dp_declaration_axiom)
```

See the *owlapy* for more OWL entities that you can add as a declaration axiom.

Add an Assertion Axiom

To assign a class to a specific individual use the following code:

```
from owlapy.owl_axiom import OWLClassAssertionAxiom

individuals = list(onto.individuals_in_signature())
heinz = individuals[1] # get the 2nd individual in the list which is 'heinz'

class_assertion_axiom = OWLClassAssertionAxiom(heinz, child_class)

onto.add_axiom(class_assertion_axiom)
```

We have used the previous method *individuals_in_signature()* to get all the individuals and converted them to a list, so we can access them by using indexes. In this example, we want to assert a class axiom for the individual *heinz*.

We have used the class `OWLClassAssertionAxiom` where the first argument is the ‘individual’ `heinz` and the second argument is the ‘class_expression’. As the class expression, we used the previously defined class `child_Class`. Finally, add the axiom by using `add_axiom` method of the *OWLOntology*.

Let’s show one more example using a `OWLObjectPropertyAssertionAxiom` to assign the age of 17 to `heinz`.

```
from owlapy.owl_literal import OWLLiteral
from owlapy.owl_axiom import OWLObjectPropertyAssertionAxiom

literal_17 = OWLLiteral(17)
dp_assertion_axiom = OWLObjectPropertyAssertionAxiom(heinz, hasAge_dp, literal_17)

onto.add_axiom(dp_assertion_axiom)
```

OWLLiteral is a class that represents the literal values in Owlapy. We have stored the integer literal value of ‘17’ in the variable `literal_17`. Then we construct the `OWLObjectPropertyAssertionAxiom` by passing as the first argument, the individual `heinz`, as the second argument the data property `hasAge_dp`, and the third argument the literal value `literal_17`. Finally, add it to the ontology by using `add_axiom` method.

Check the *owlapy* to see all the OWL assertion axioms that you can use.

Remove an Axiom

To remove an axiom you can use the `remove_axiom` method as follows:

```
onto.remove_axiom(dp_assertion_axiom)
```

The required argument is the axiom/axioms you want to remove.

3.3 Save an Ontology

If you modified an ontology, you may want to save it as a new file. To do this you can use the `save` method of the *OWLOntology*. It requires one argument, the IRI of the new ontology.

```
onto.save(IRI.create('file://' + 'test' + '.owl'))
```

The above line of code will save the ontology `onto` in the file `test.owl` which will be created in the same directory as the file you are running this code.

3.4 Worlds

Owlready2 stores every triple in a ‘World’ object, and it can handle several Worlds in parallel. Owlready2 uses an optimized quadstore to store the world. Each world object is stored in a separate quadstore and by default the quadstore is stored in memory, but it can also be stored in an SQLite3 file. The method `save_world()` of the ontology manager does the latter. When an *OWLOntologyManager* object is created, a new world is also created as an attribute of the manager. By calling the method `load_ontology(iri)` the ontology is loaded to this world.

It possible to create several isolated “worlds”, sometimes called “universe of speech”. This makes it possible, in particular, to load the same ontology several times, independently, that is to say, without the modifications made on one copy affecting the other copy. Sometimes the need to isolate an ontology arise. What that means is that you can have multiple reference of the same ontology in different worlds.

It is important that an ontology is associated with a reasoner which is used to inferring knowledge from the ontology, i.e. to perform ontology reasoning. In the next guide we will see how to use a reasoner in Owlapy.

4 Reasoners

To validate facts about statements in the ontology, the help of a reasoner component is required.

For this guide we will also consider the ‘father’ ontology that we slightly described [here](#):

```
from owlapy.owl_ontology_manager import OntologyManager

manager = OntologyManager()
onto = manager.load_ontology(IRI.create("KGs/Family/father.owl"))
```

In our Owlapy library, we provide several **reasoners** to choose from:

- ***OntologyReasoner***

Or differently Structural Reasoner, is the base reasoner in Owlapy. The functionalities of this reasoner are limited. It does not provide full reasoning in *ALCH*. Furthermore, it has no support for instances of complex class expressions, which is covered by the other reasoners (SyncReasoner and FIC). This reasoner is used as a base reasoner for FIC which overwrites the `instances` method. We recommend using the other reasoners for any reasoning tasks.

Initialization:

```
from owlapy.owl_reasoner import OntologyReasoner

structural_reasoner = OntologyReasoner(onto)
```

The structural reasoner requires an ontology (*OWL*Ontology).

- ***SyncReasoner***

Can perform full reasoning in *ALCH* due to the use of reasoners from owlapi like HermiT, Pellet, etc. and provides support for complex class expression instances (when using the method `instances`). SyncReasoner is more useful when your main goal is reasoning over the ontology, and you are familiarized with the java reasoners (HermiT, Pellet, ...).

Initialization:

```
from owlapy.owl_reasoner import SyncReasoner

sync_reasoner = SyncReasoner(ontology_path="KGs/Mutagenesis/mutagenesis.owl",
                             ↪reasoner="HermiT")
```

Sync Reasoner is made available by *owlapi adaptor* and requires the ontology path together with a reasoner name from the possible set of reasoners: "Hermit", "Pellet", "JFact", "Openllet".

- ***FastInstanceCheckerReasoner* (FIC)**

FIC also provides support for complex class expression but the rest of the methods are the same as in the base reasoner. It has a cache storing system that allows for faster execution of some reasoning functionalities. Due to this feature, FIC is more appropriate to be used in concept learning.

Initialization:

```
from owlapy.owl_reasoner import FastInstanceCheckerReasoner

fic_reasoner = FastInstanceCheckerReasoner(onto, structural_reasoner, property_
    ↪cache = True,
                                           negation_default = True, sub_
    ↪properties = False)
```

Besides the ontology, FIC requires a base reasoner to delegate any reasoning tasks not covered by it. This base reasoner can be any other reasoner in Owlapy (usually it's *OntologyReasoner*). `property_cache` specifies whether to cache property values. This requires more memory, but it speeds up the reasoning processes. If `negation_default` argument is set to `True` the missing facts in the ontology means false. The argument `sub_properties` is another boolean argument to specify whether you want to take sub properties in consideration for `instances()` method.

4.1 Usage of the Reasoner

All the reasoners available in the Owlapy library inherit from the class: *OWLReasonerEx*. This class provides some extra convenient methods compared to its base abstract class *OWLReasoner*. Further on, in this guide, we use *FastInstanceCheckerReasoner* to show the capabilities of a reasoner in Owlapy.

As mentioned earlier we will use the *father* dataset to give examples.

4.2 Class Reasoning

Using an *OWLOntology* you can list all the classes in the signature, but a reasoner can give you more than that. You can get the subclasses, superclasses or the equivalent classes of a class in the ontology:

```
from owlapy.class_expression import OWLClass
from owlapy.iri import IRI

namespace = "http://example.com/father#"
male = OWLClass(IRI(namespace, "male"))

male_super_classes = fic_reasoner.super_classes(male)
male_sub_classes = fic_reasoner.sub_classes(male)
male_equivalent_classes = fic_reasoner.equivalent_classes(male)
```

We define the *male* class by creating an *OWLClass* object. The methods `super_classes` and `sub_classes` have 2 more boolean arguments: `direct` and `only_named`. If `direct=True` then only the direct classes in the hierarchy will be returned, else it will return every class in the hierarchy depending on the method (`sub_classes` or `super_classes`). By default, its value is *False*. The next argument `only_named` specifies whether you want to show only named classes or complex classes as well. By default, its value is *True* which means that it will return only the named classes.

NOTE: The extra arguments `direct` and `only_named` are also used in other methods that reason upon the class, object property, or data property hierarchy.

NOTE: *SyncReasoner* implements *OWLReasoner* where we can specify the `only_named` argument in some methods but in java reasoners there is no use for such argument and therefore this argument is trivial when used in *SyncReasoner*'s methods.

You can get all the types of a certain individual using `types` method:

```
anna = list(onto.individuals_in_signature()).pop()

anna_types = fic_reasoner.types(anna)
```

We retrieve *anna* as the first individual on the list of individuals of the 'Father' ontology. The `types` method only returns named classes.

4.3 Object Properties and Data Properties Reasoning

Owlapy reasoners offers some convenient methods for working with object properties and data properties. Below we show some of them, but you can always check all the methods in the *OWLReasoner* class documentation.

You can get all the object properties that an individual has by using the following method:

```
anna = individuals[0]
object_properties = fic_reasoner.ind_object_properties(anna)
```

In this example, `object_properties` contains all the object properties that *anna* has, which in our case would only be *hasChild*. Now we can get the individuals of this object property for *anna*.

```
for op in object_properties:
    object_properties_values = fic_reasoner.object_property_values(anna, op)
    for individual in object_properties_values:
        print(individual)
```

In this example we iterated over the `object_properties`, assuming that there are more than 1, and we use the reasoner to get the values for each object property `op` of the individual *anna*. The values are individuals which we store in the variable `object_properties_values` and are printed in the end. The method `object_property_values` requires as the first argument, an *OWLNamedIndividual* that is the subject of the object property values and the second argument an *OWLObjectProperty* whose values are to be retrieved for the specified individual.

NOTE: You can as well get all the data properties of an individual in the same way by using `ind_data_properties` instead of `ind_object_properties` and `data_property_values` instead of `object_property_values`. Keep in mind that `data_property_values` returns literal values (type of *OWLLiteral*).

In the same way as with classes, you can also get the sub object properties or equivalent object properties.

```
from owlapy.owl_property import OWLObjectProperty

hasChild = OWLObjectProperty(IRI(namespace, "hasChild"))

equivalent_to_hasChild = fic_reasoner.equivalent_object_properties(hasChild)
hasChild_sub_properties = fic_reasoner.sub_object_properties(hasChild)
```

In case you want to get the domains and ranges of an object property use the following:

```
hasChild_domains = fic_reasoner.object_property_domains(hasChild)
hasChild_ranges = fic_reasoner.object_property_ranges(hasChild)
```

NOTE: Again, you can do the same for data properties but instead of the word ‘object’ in the method name you should use ‘data’.

4.4 Find Instances

The method `instances` is a very convenient method. It takes only 1 argument that is basically a class expression and returns all the individuals belonging to that class expression. In Owlapy we have implemented a Python class for each type of class expression. The argument is of type *OWLClassExpression*.

Let us now show a simple example by finding the instances of the class *male* and printing them:

```
male_individuals = fic_reasoner.instances(male)
for ind in male_individuals:
    print(ind)
```

In this guide we covered the main functionalities of the reasoners in Owlapy. In the next one, we speak about owlapi adaptor and how can make use of owlapi in owlapy.

5 Owlapi Adaptor

As mentioned earlier, owlapy is loosely based in [owlapi](#)¹⁶, a library for ontology modification in java.

We have created *OWLAPIAdaptor*, an adaptor class that facilitates the conversion of owl class expressions from owlapy to owlapi and vice-versa. This adaptor is still considered experimental, and it's in the initial phase of development.

We are able to use owlapi via [Jpype](#)¹⁷, a python module that provides access to Java via python. To start executing Java code via jpype, one needs to start the java virtual machine (JVM). This is automatically done when initializing a *OWLAPIAdaptor* object.

5.1 Initialization

To use the adaptor you have to start the JVM via jpype, which is done automatically when you create an *OWLAPIAdaptor* object. After you are finished you can stop the JVM by either using `jpype.shutdownJVM()` or the static method from the adaptor `stopJVM()`. This will free the resources used by JPyPe and the java packages.

```
from owlapy.owlapi_adaptor import OWLAPIAdaptor

adaptor = OWLAPIAdaptor("KGs/Family/father.owl")
# Use the adaptor
print(f"Is the ontology consistent? {adaptor.has_consistent_ontology()}")

# Stop the JVM
adaptor.stopJVM()
```

In the above code snippet, we created an adaptor for the father ontology by passing the local path of that ontology. Then we print whether the ontology is consistent or not.

5.2 Notes

An important note is that when initialising the adaptor you are basically starting a JVM in the background, and therefore you are able to import and use java classes as you would do in python. That means that you can play around with owlapi code in python as long as your JVM is started. Isn't that awesome!

OWLAPIAdaptor uses *HermiT* reasoner by default. You can choose between: "HermiT", "Pellet", "JFact" and "Openllet".

You can use the reasoning method directly from the adaptor but for classes that require an *OWLReasoner* you can use [SyncReasoner](#)¹⁸.

owlapi version: 5.1.9

¹⁶ <https://github.com/owlcs/owlapi>

¹⁷ <https://jpype.readthedocs.io/en/latest/>

¹⁸ https://dice-group.github.io/owlapy/autoapi/owlapy/owl_reasoner/index.html#owlapy.owl_reasoner.SyncReasoner

5.3 Examples

You can check a usage example in the *examples*¹⁹ folder.

Test cases²⁰ for the adaptor can also serve as an example, so you can check that out as well.

6 Further Resources

Currently, we are working on our manuscript describing our framework. If you want to attribute our library, please use our [GitHub page](#)²¹ for reference.

6.1 More Inside the Project

Examples and test cases provide a good starting point to get to know the project better. Find them in the folders *examples*²² and *tests*²³.

6.2 Contribution

Feel free to create a pull request and we will take a look on it. Your commitment is well appreciated!

6.3 Questions

In case you have any question, please contact: caglardemir8@gmail.com or open an issue on our [GitHub issues page](#)²⁴.

6.4 Coverage Report

The coverage report is generated using *coverage.py*²⁵.

Name	Stmts	Miss	Cover	Missing
owlapy/ __init__ .py	4	0	100%	
owlapy/class_expression/ __init__ .py	8	0	100%	
owlapy/class_expression/class_expression.py	34	2	94%	58, 62
owlapy/class_expression/nary_boolean_expression.py	24	0	100%	
owlapy/class_expression/owl_class.py	33	1	97%	44
owlapy/class_expression/restriction.py	313	26	92%	41, 49, 68, ↪ 71, 89, 170, 245-246, 302, 305, 335, 340, 343, 426, 451, 499, 502, 579-580, 616, ↪ 659, 662, 700, 703, 751, 823
owlapy/converter.py	397	189	52%	52-68, 75-↪ 76, 79, 82, 152, 157, 169, 176, 184, 246-257, 264-282, 294, 304-307, 313-359, 366-↪ 387, 394-401, 417-420, 431, 451, 460-481, 489-491, 498-511, 515-521, 525-548, 552-↪ 555, 559-560, 564-576, 580-587, 591-592, 620, 624-628

(continues on next page)

¹⁹ <https://github.com/dice-group/owlapy/tree/develop/examples>

²⁰ <https://github.com/dice-group/owlapy/tree/develop/tests>

²¹ <https://github.com/dice-group/owlapy>

²² <https://github.com/dice-group/owlapy/tree/develop/examples>

²³ <https://github.com/dice-group/owlapy/tree/develop/tests>

²⁴ <https://github.com/dice-group/owlapy/issues>

²⁵ <https://coverage.readthedocs.io/en/7.6.1/>

(continued from previous page)

owlapy/iri.py	79	7	91%	54, 69, 82, → 97, 128, 133, 150
owlapy/meta_classes.py	11	0	100%	
owlapy/namespaces.py	27	3	89%	36, 40, 43
owlapy/owl_annotation.py	17	4	76%	17, 25, 43, → 51
owlapy/owl_axiom.py	518	157	70%	36, 39, 42, → 45, 59, 111-113, 116, 136-138, 141, 144, 147-150, 153, 182-184, 187, 190, 193, 196- → 200, 203, 253-256, 259-261, 264, 288, 291, 294, 332-335, 338-340, 343, 398-401, 404- → 406, 409, 533-536, 539, 561-563, 566, 569, 572, 575, 578-581, 584, 620-623, 626, → 645-648, 652, 656, 674-675, 683, 692, 695-697, 700, 711, 733-737, 745, 753, 761, → 764-766, 769, 786-788, 791, 794, 797-800, 803, 822-824, 827, 830, 833-836, 839, 858- → 860, 863, 866, 869-872, 875, 905-908, 911, 982-985, 988, 1018, 1044, 1071-1073, → 1076, 1091, 1103, 1116, 1129, 1142, 1157, 1172, 1185-1187, 1190, 1208, 1227-1230, → 1233, 1254-1257, 1260
owlapy/owl_data_ranges.py	40	1	98%	46
owlapy/owl_datatype.py	20	2	90%	33-34
owlapy/owl_individual.py	20	1	95%	37
owlapy/owl_literal.py	286	73	74%	49, 77, 86, → 90, 99, 103, 112, 116, 125, 129, 138, 142, 151, 155, 164, 169, 173, 203, 208, 217, → 221, 244, 247-249, 252, 258, 262, 288, 293, 302, 306, 311, 323, 329, 332-334, 337, → 340, 346, 350, 355, 373, 376-378, 381, 387, 391, 415, 418-420, 423, 429, 433, 454, → 459, 462-464, 467, 473, 477, 489-491, 494, 497-499, 502
owlapy/owl_object.py	27	4	85%	24, 79-81
owlapy/owl_ontology.py	391	40	90%	86, 97-100, → 103, 109-111, 249, 292-295, 304, 312, 329, 341, 345, 358, 371, 376, 379-381, 384, → 423, 433, 449-450, 473-474, 553-554, 595, 599, 603, 629, 736, 742, 750
owlapy/owl_ontology_manager.py	568	167	71%	48, 140, → 151, 155, 168-169, 177, 200, 208-211, 312-318, 341-350, 355-376, 396, 466, 469, 474- → 496, 501-511, 521-527, 539, 542-543, 583, 588-593, 603, 608, 625, 634-645, 650-665, → 676, 681, 691, 703, 707, 743, 749, 760, 766, 771-795, 800-807, 825-831, 850, 853, → 859-862, 888
owlapy/owl_property.py	69	11	84%	17, 24, 32, → 40, 67, 76, 126, 158, 162, 174, 193
owlapy/owl_reasoner.py	841	175	79%	452-455, → 572, 584-586, 591-597, 604, 653-659, 665-669, 727-734, 760, 795-799, 825-828, 856- → 858, 860-862, 871, 884-886, 888-890, 897, 902-904, 924, 928-929, 942-944, 965, 1010- → 1012, 1113, 1121, 1124, 1127, 1130, 1133, 1136, 1139, 1142, 1145, 1160-1162, 1168, → 1172, 1175, 1178, 1181, 1184, 1187, 1193, 1196, 1210, 1240-1243, 1251-1290, 1305, → 1318-1328, 1353-1356, 1372, 1386, 1456-1460, 1488, 1498-1502, 1510-1514, 1555-1561, → 1573, 1632, 1635, 1638, 1641, 1644, 1647, 1650, 1653, 1657, 1661, 1665, 1668, 1671, → 1674, 1677, 1680, 1683, 1687, 1691, 1694, 1697
owlapy/owlapi_adaptor.py	130	65	50%	18, 74-76, → 91-96, 110-115, 151-152, 164-165, 179-180, 195-196, 214, 232, 251, 271, 287, 305, → 320, 333, 346, 361, 376, 390, 404, 419, 434, 450, 454-483, 511
owlapy/owlapi_mapper.py	103	14	86%	35, 51, 72, → 76, 80, 84, 88, 133-136, 141, 145, 149
owlapy/parser.py	371	16	96%	316, 327, → 400-401, 416, 577, 618, 656, 667, 721, 723, 751-752, 763, 779-780
owlapy/providers.py	38	3	92%	41, 54, 56
owlapy/render.py	290	46	84%	79-114, → 143-158, 176, 180, 186, 206, 222, 231, 236, 241, 375, 379, 386, 405, 421, 430, 435, → 440
owlapy/utils.py	766	227	70%	164, 168, → 172, 178, 184-188, 192-196, 200, 204, 208, 214, 218, 222, 226, 230, 236, 242, 248, → 252, 256, 260, 264-267, 271-274, 278, 285, 300-302, 305-314, 317, 320, 323, 326, → 329, 333-339, 343, 354, 358, 362, 366, 370, 374-378, 382-386, 390-394, 398-402, 406,

(continues on next page)

(continued from previous page)

→ 410, 414-419, 423-428, 432-437, 441, 445, 449-453, 457-461, 465-469, 473-477, 481-485, 489, 493-497, 501, 505-510, 514-519, 523-528, 532, 536-540, 545, 554, 558, 562, 566, 570, 574, 578, 582-587, 591-597, 601, 605, 609, 614, 619, 624, 628, 632, 636, 640, 644-647, 651-654, 658, 662, 666, 671, 676, 681, 685, 736, 740, 746, 748, 751, 753, 796, 852, 866-868, 877, 919-920, 940, 1039, 1044, 1049, 1071, 1075, 1083, 1087, 1092, 1164-1182, 1195-1197, 1202-1206				
owlapy/vocab.py	92	4	96%	32, 35, 113-114

TOTAL	5517	1238	78%	

7 owlapy

7.1 Subpackages

owlapy.class_expression

OWL Class Expressions https://www.w3.org/TR/owl2-syntax/#Class_Expressions ClassExpression :=

owl_class.py: Class nary_boolean_expression.py: ObjectIntersectionOf, ObjectUnionOf
class_expression.py: ObjectComplementOf
restriction.py: ObjectOneOf, ObjectSomeValuesFrom, ObjectAllValuesFrom, ObjectHas-
Value, ObjectHasSelf, ObjectMinCardinality, ObjectMaxCardinality, ObjectExactCardinality, Data-
SomeValuesFrom, DataAllValuesFrom, DataHasValue, DataMinCardinality, DataMaxCardinality,
DataExactCardinality

Submodules

owlapy.class_expression.class_expression

OWL Base Classes Expressions

Classes

<i>OWLClassExpression</i>	OWL Class expressions represent sets of individuals by formally specifying conditions on the individuals' properties;
<i>OWLAnonymousClassExpression</i>	A Class Expression which is not a named Class.
<i>OWLBooleanClassExpression</i>	Represent an anonymous boolean class expression.
<i>OWLObjectComplementOf</i>	Represents an ObjectComplementOf class expression in the OWL 2 Specification.

Module Contents

class owlapy.class_expression.class_expression.OWLClassExpression

Bases: *owlapy.owl_data_ranges.OWLPropertyRange*

OWL Class expressions represent sets of individuals by formally specifying conditions on the individuals' properties; individuals satisfying these conditions are said to be instances of the respective class expressions. In the structural specification of OWL 2, class expressions are represented by ClassExpression. (https://www.w3.org/TR/owl2-syntax/#Class_Expressions)

__slots__ = ()

abstract is_owl_thing () → bool

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

abstract is_owl_nothing () → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

abstract get_object_complement_of () → *OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

abstract get_nnf () → *OWLClassExpression*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

class owlapy.class_expression.class_expression.OWLAnonymousClassExpression

Bases: *OWLClassExpression*

A Class Expression which is not a named Class.

is_owl_nothing () → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

is_owl_thing () → bool

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

get_object_complement_of () → *OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

get_nnf () → *OWLClassExpression*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

class owlapy.class_expression.class_expression.OWLBooleanClassExpression

Bases: *OWLAnonymousClassExpression*

Represent an anonymous boolean class expression.

__slots__ = ()

class owlapy.class_expression.class_expression.OWLObjectComplementOf (

op: OWLClassExpression)

Bases: *OWLBooleanClassExpression*, *owlapy.meta_classes.HasOperands[OWLClassExpression]*

Represents an ObjectComplementOf class expression in the OWL 2 Specification.

__slots__ = '_operand'

type_index: Final = 3003

get_operand () → *OWLClassExpression*

Returns

The wrapped expression.

operands () → Iterable[*OWLClassExpression*]

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

__repr__ ()

Return repr(self).

__eq__ (*other*)

Return self==value.

__hash__ ()

Return hash(self).

owlapy.class_expression.nary_boolean_expression

OWL nary boolean expressions

Classes

<i>OWLNaryBooleanClassExpression</i>	OWLNaryBooleanClassExpression.
<i>OWLObjectUnionOf</i>	A union class expression <code>ObjectUnionOf(CE1 ... CEn)</code> contains all individuals that are instances
<i>OWLObjectIntersectionOf</i>	An intersection class expression <code>ObjectIntersectionOf(CE1 ... CEn)</code> contains all individuals that are instances

Module Contents

```
class owlapy.class_expression.nary_boolean_expression.  
    OWLNaryBooleanClassExpression (  
        operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])  
Bases: owlapy.class_expression.class_expression.OWLBooleanClassExpression,  
        owlapy.meta_classes.HasOperands[owlapy.class_expression.class_expression.  
        OWLClassExpression]  
OWLNaryBooleanClassExpression.  
__slots__ = ()  
operands () → Iterable[owlapy.class_expression.class_expression.OWLClassExpression]  
    Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.  
    Returns  
        The operands.  
__repr__ ()  
    Return repr(self).  
__eq__ (other)  
    Return self==value.  
__hash__ ()  
    Return hash(self).  
class owlapy.class_expression.nary_boolean_expression.OWLObjectUnionOf (  
        operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])  
Bases: OWLNaryBooleanClassExpression  
A union class expression ObjectUnionOf( CE1 ... CEn ) contains all individuals that are instances of at least one  
class expression CEi for  $1 \leq i \leq n$ . (https://www.w3.org/TR/owl2-syntax/#Union\_of\_Class\_Expressions)  
__slots__ = '_operands'  
type_index: Final = 3002  
class owlapy.class_expression.nary_boolean_expression.  
    OWLObjectIntersectionOf (  
        operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])  
Bases: OWLNaryBooleanClassExpression  
An intersection class expression ObjectIntersectionOf( CE1 ... CEn ) contains all individuals that are instances of  
all class expressions CEi for  $1 \leq i \leq n$ . (https://www.w3.org/TR/owl2-syntax/#Intersection\_of\_Class\_Expressions)
```

```
__slots__ = '_operands'
type_index: Final = 3001
```

owlapy.class_expression.owl_class

OWL Class

Classes

<i>OWLClass</i>	An OWL 2 named Class. Classes can be understood as sets of individuals.
-----------------	---

Module Contents

```
class owlapy.class_expression.owl_class.OWLClass (iri: owlapy.iri.IRI | str)
```

Bases: *owlapy.class_expression.class_expression.OWLClassExpression*, *owlapy.owl_object.OWLEntity*

An OWL 2 named Class. Classes can be understood as sets of individuals. (<https://www.w3.org/TR/owl2-syntax/#Classes>)

```
__slots__ = ('_iri', '_is_nothing', '_is_thing')
```

```
type_index: Final = 1001
```

```
property iri: owlapy.iri.IRI
```

Gets the IRI of this object.

Returns

The IRI of this object.

```
property str
```

Gets the string representation of this object

Returns

The IRI as string

```
property reminder: str
```

The reminder of the IRI

```
is_owl_thing() → bool
```

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

is_owl_nothing() → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

get_object_complement_of()

→ *owlapy.class_expression.class_expression.OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

get_nnf() → *OWLClass*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

owlapy.class_expression.restriction

OWL Restrictions

Attributes

Literals

Classes

<i>OWLRestriction</i>	Represents an Object Property Restriction or Data Property Restriction in the OWL 2 specification.
<i>OWLHasValueRestriction</i>	Represent a HasValue restriction in the OWL 2
<i>OWLObjectRestriction</i>	Represents an Object Property Restriction in the OWL 2 specification.
<i>OWLQuantifiedRestriction</i>	Represents a quantified restriction.
<i>OWLCardinalityRestriction</i>	Base interface for owl min and max cardinality restriction.
<i>OWLQuantifiedObjectRestriction</i>	Represents a quantified object restriction.
<i>OWLObjectCardinalityRestriction</i>	Represents Object Property Cardinality Restrictions in the OWL 2 specification.
<i>OWLObjectMinCardinality</i>	A minimum cardinality expression <i>ObjectMinCardinality</i> (<i>n</i> OPE CE) consists of a nonnegative integer <i>n</i> , an object
<i>OWLObjectMaxCardinality</i>	A maximum cardinality expression <i>ObjectMaxCardinality</i> (<i>n</i> OPE CE) consists of a nonnegative integer <i>n</i> , an object
<i>OWLObjectExactCardinality</i>	An exact cardinality expression <i>ObjectExactCardinality</i> (<i>n</i> OPE CE) consists of a nonnegative integer <i>n</i> , an object
<i>OWLObjectSomeValuesFrom</i>	An existential class expression <i>ObjectSomeValuesFrom</i> (OPE CE) consists of an object property expression OPE and
<i>OWLObjectAllValuesFrom</i>	A universal class expression <i>ObjectAllValuesFrom</i> (OPE CE) consists of an object property expression OPE and a
<i>OWLObjectHasSelf</i>	A self-restriction <i>ObjectHasSelf</i> (OPE) consists of an object property expression OPE,
<i>OWLObjectHasValue</i>	A has-value class expression <i>ObjectHasValue</i> (OPE a) consists of an object property expression OPE and an
<i>OWLObjectOneOf</i>	An enumeration of individuals <i>ObjectOneOf</i> (<i>a</i> ₁ ... <i>a</i> _{<i>n</i>}) contains exactly the individuals <i>a</i> _{<i>i</i>} with 1 ≤ <i>i</i> ≤ <i>n</i> .
<i>OWLDataRestriction</i>	Represents a Data Property Restriction.
<i>OWLQuantifiedDataRestriction</i>	Represents a quantified data restriction.
<i>OWLDataCardinalityRestriction</i>	Represents Data Property Cardinality Restrictions.
<i>OWLDataMinCardinality</i>	A minimum cardinality expression <i>DataMinCardinality</i> (<i>n</i> DPE DR) consists of a nonnegative integer <i>n</i> , a data
<i>OWLDataMaxCardinality</i>	A maximum cardinality expression <i>ObjectMaxCardinality</i> (<i>n</i> OPE CE) consists of a nonnegative integer <i>n</i> , an object
<i>OWLDataExactCardinality</i>	An exact cardinality expression <i>ObjectExactCardinality</i> (<i>n</i> OPE CE) consists of a nonnegative integer <i>n</i> , an
<i>OWLDataSomeValuesFrom</i>	An existential class expression <i>DataSomeValuesFrom</i> (DPE ₁ ... DPE _{<i>n</i>} DR) consists of <i>n</i> data property expressions
<i>OWLDataAllValuesFrom</i>	A universal class expression <i>DataAllValuesFrom</i> (DPE ₁ ... DPE _{<i>n</i>} DR) consists of <i>n</i> data property expressions DPE _{<i>i</i>} ,
<i>OWLDataHasValue</i>	A has-value class expression <i>DataHasValue</i> (DPE <i>l</i> _{<i>t</i>}) consists of a data property expression DPE and a literal <i>l</i> _{<i>t</i>} ,
<i>OWLDataOneOf</i>	An enumeration of literals <i>DataOneOf</i> (<i>l</i> _{<i>t</i>} ₁ ... <i>l</i> _{<i>t</i>} _{<i>n</i>}) contains exactly the explicitly specified literals <i>l</i> _{<i>t</i>} _{<i>i</i>} with
<i>OWLDatatypeRestriction</i>	A datatype restriction <i>DatatypeRestriction</i> (DT F ₁ <i>l</i> _{<i>t</i>} ₁ ... F _{<i>n</i>} <i>l</i> _{<i>t</i>} _{<i>n</i>}) consists of a unary datatype DT and <i>n</i> pairs
<i>OWLFacetRestriction</i>	A facet restriction is used to restrict a particular datatype.

Module Contents

`owlapy.class_expression.restriction.Literals`

class `owlapy.class_expression.restriction.OWLRestriction`

Bases: `owlapy.class_expression.class_expression.OWLAnonymousClassExpression`

Represents an Object Property Restriction or Data Property Restriction in the OWL 2 specification.

__slots__ = ()

abstract `get_property()` → `owlapy.owl_property.OWLPropertyExpression`

Returns

Property being restricted.

is_data_restriction() → bool

Determines if this is a data restriction.

Returns

True if this is a data restriction.

is_object_restriction() → bool

Determines if this is an object restriction.

Returns

True if this is an object restriction.

class `owlapy.class_expression.restriction.OWLHasValueRestriction` (*value*: `_T`)

Bases: `Generic[_T]`, `OWLRestriction`, `owlapy.meta_classes.HasFiller[_T]`

Represent a HasValue restriction in the OWL 2

Parameters

`_T` – The value type.

__slots__ = ()

__eq__ (*other*)

Return self==value.

__hash__ ()

Return hash(self).

get_filler() → `_T`

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

class `owlapy.class_expression.restriction.OWLObjectRestriction`

Bases: `OWLRestriction`

Represents an Object Property Restriction in the OWL 2 specification.

__slots__ = ()

is_object_restriction() → bool

Determines if this is an object restriction.

Returns

True if this is an object restriction.

abstract get_property() → *owlapy.owl_property.OWLObjectPropertyExpression*

Returns

Property being restricted.

class owlapy.class_expression.restriction.**OWLQuantifiedRestriction**

Bases: *Generic[_T]*, *OWLRestriction*, *owlapy.meta_classes.HasFiller[_T]*

Represents a quantified restriction.

Parameters

_T – value type

__slots__ = ()

class owlapy.class_expression.restriction.**OWLCardinalityRestriction**(

cardinality: int, filler: _F)

Bases: *Generic[_F]*, *OWLQuantifiedRestriction[_F]*, *owlapy.meta_classes.HasCardinality*

Base interface for owl min and max cardinality restriction.

Parameters

_F – Type of filler.

__slots__ = ()

get_cardinality() → int

Gets the cardinality of a restriction.

Returns

The cardinality. A non-negative integer.

get_filler() → *_F*

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

class owlapy.class_expression.restriction.**OWLQuantifiedObjectRestriction**(

filler: owlapy.class_expression.class_expression.OWLClassExpression)

Bases: *OWLQuantifiedRestriction[owlapy.class_expression.class_expression.OWLClassExpression]*, *OWLObjectRestriction*

Represents a quantified object restriction.

__slots__ = ()

get_filler() → *owlapy.class_expression.class_expression.OWLClassExpression*

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

```
class owlapy.class_expression.restriction.OWLObjectCardinalityRestriction(  
    cardinality: int, property: owlapy.owl_property.OWLObjectPropertyExpression,  
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
```

Bases: *OWLCardinalityRestriction*[*owlapy.class_expression.class_expression.OWLClassExpression*], *OWLQuantifiedObjectRestriction*

Represents Object Property Cardinality Restrictions in the OWL 2 specification.

```
__slots__ = ()
```

```
get_property() → owlapy.owl_property.OWLObjectPropertyExpression
```

Returns

Property being restricted.

```
__repr__()
```

Return repr(self).

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
class owlapy.class_expression.restriction.OWLObjectMinCardinality(  
    cardinality: int, property: owlapy.owl_property.OWLObjectPropertyExpression,  
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
```

Bases: *OWLObjectCardinalityRestriction*

A minimum cardinality expression *ObjectMinCardinality*(*n* *OPE* *CE*) consists of a nonnegative integer *n*, an object property expression *OPE*, and a class expression *CE*, and it contains all those individuals that are connected by *OPE* to at least *n* different individuals that are instances of *CE*. (https://www.w3.org/TR/owl2-syntax/#Minimum_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3008
```

```
class owlapy.class_expression.restriction.OWLObjectMaxCardinality(  
    cardinality: int, property: owlapy.owl_property.OWLObjectPropertyExpression,  
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
```

Bases: *OWLObjectCardinalityRestriction*

A maximum cardinality expression *ObjectMaxCardinality*(*n* *OPE* *CE*) consists of a nonnegative integer *n*, an object property expression *OPE*, and a class expression *CE*, and it contains all those individuals that are connected by *OPE*

to at most *n* different individuals that are instances of *CE*. (https://www.w3.org/TR/owl2-syntax/#Maximum_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3010
```



```
class owlapy.class_expression.restriction.OwlObjectExactCardinality(
    cardinality: int, property: owlapy.owl_property.OwlObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OwlClassExpression)
```

Bases: *OwlObjectCardinalityRestriction*

An exact cardinality expression **ObjectExactCardinality**(*n* OPE CE) consists of a nonnegative integer *n*, an object

property expression OPE, and a class expression CE, and it contains all those individuals that are connected by to exactly *n* different individuals that are instances of CE.

(https://www.w3.org/TR/owl2-syntax/#Exact_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3009
```

```
as_intersection_of_min_max()
```

→ *owlapy.class_expression.nary_boolean_expression.OwlObjectIntersectionOf*

Obtains an equivalent form that is a conjunction of a min cardinality and max cardinality restriction.

Returns

The semantically equivalent but structurally simpler form $(= 1 \text{ R C}) = \geq 1 \text{ R C}$ and $\leq 1 \text{ R C}$.

```
class owlapy.class_expression.restriction.OwlObjectSomeValuesFrom(
    property: owlapy.owl_property.OwlObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OwlClassExpression)
```

Bases: *OwlQuantifiedObjectRestriction*

An existential class expression **ObjectSomeValuesFrom**(OPE CE) consists of an object property expression OPE and a class expression CE, and it contains all those individuals that are connected by OPE to an individual that is an instance of CE.

```
__slots__ = ('_property', '_filler')
```

```
type_index: Final = 3005
```

```
__repr__()
```

Return repr(self).

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
get_property() → owlapy.owl_property.OwlObjectPropertyExpression
```

Returns

Property being restricted.

```
class owlapy.class_expression.restriction.OwlObjectAllValuesFrom(
    property: owlapy.owl_property.OwlObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OwlClassExpression)
```

Bases: *OwlQuantifiedObjectRestriction*

A universal class expression **ObjectAllValuesFrom**(OPE CE) consists of an object property expression OPE and a class expression CE, and it contains all those individuals that are connected by OPE only to individuals that are instances of CE. (https://www.w3.org/TR/owl2-syntax/#Universal_Quantification)

```
__slots__ = ('_property', '_filler')
```

```

type_index: Final = 3006

__repr__()
    Return repr(self).

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

get_property() → owlapy.owl_property.OWLObjectPropertyExpression

    Returns
        Property being restricted.

```

class owlapy.class_expression.restriction.**OWLObjectHasSelf**(
property: owlapy.owl_property.OWLObjectPropertyExpression)
Bases: *OWLObjectRestriction*

A self-restriction ObjectHasSelf(OPE) consists of an object property expression OPE, and it contains all those individuals that are connected by OPE to themselves. (<https://www.w3.org/TR/owl2-syntax/#Self-Restriction>)

```

__slots__ = '_property'

type_index: Final = 3011

get_property() → owlapy.owl_property.OWLObjectPropertyExpression

    Returns
        Property being restricted.

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

```

class owlapy.class_expression.restriction.**OWLObjectHasValue**(
property: owlapy.owl_property.OWLObjectPropertyExpression,
individual: owlapy.owl_individual.OWLIndividual)
Bases: *OWLHasValueRestriction[owlapy.owl_individual.OWLIndividual], OWLObjectRestriction*

A has-value class expression ObjectHasValue(OPE a) consists of an object property expression OPE and an individual a, and it contains all those individuals that are connected by OPE to a. Each such class expression can be seen as a syntactic shortcut for the class expression ObjectSomeValuesFrom(OPE ObjectOneOf(a)). (https://www.w3.org/TR/owl2-syntax/#Individual_Value_Restriction)

```

__slots__ = ('_property', '_v')

type_index: Final = 3007

get_property() → owlapy.owl_property.OWLObjectPropertyExpression

    Returns
        Property being restricted.

```

as_some_values_from() → *owlapy.class_expression.class_expression.OWLClassExpression*

A convenience method that obtains this restriction as an existential restriction with a nominal filler.

Returns

The existential equivalent of this value restriction. $\text{simp}(\text{HasValue}(p\ a)) = \text{some}(p\ \{a\})$.

__repr__()

Return repr(self).

class owlapy.class_expression.restriction.OWLObjectOneOf (

values: owlapy.owl_individual.OWLIndividual | Iterable[owlapy.owl_individual.OWLIndividual])

Bases: *owlapy.class_expression.class_expression.OWLAnonymousClassExpression, owlapy.meta_classes.HasOperands[owlapy.owl_individual.OWLIndividual]*

An enumeration of individuals ObjectOneOf($a_1 \dots a_n$) contains exactly the individuals a_i with $1 \leq i \leq n$. (https://www.w3.org/TR/owl2-syntax/#Enumeration_of_Individuals)

__slots__ = **'_values'**

type_index: Final = 3004

individuals() → *Iterable[owlapy.owl_individual.OWLIndividual]*

Gets the individuals that are in the oneOf. These individuals represent the exact instances (extension) of this class expression.

Returns

The individuals that are the values of this {`@code` ObjectOneOf} class expression.

operands() → *Iterable[owlapy.owl_individual.OWLIndividual]*

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

as_object_union_of() → *owlapy.class_expression.class_expression.OWLClassExpression*

Simplifies this enumeration to a union of singleton nominals.

Returns

This enumeration in a more standard DL form. $\text{simp}(\{a\}) = \{a\}$ $\text{simp}(\{a_0, \dots, \{a_n\}\}) = \text{unionOf}(\{a_0\}, \dots, \{a_n\})$

__hash__()

Return hash(self).

__eq__(*other*)

Return self==value.

__repr__()

Return repr(self).

class owlapy.class_expression.restriction.OWLDataRestriction

Bases: *OWLRestriction*

Represents a Data Property Restriction.

__slots__ = **()**

is_data_restriction() → bool

Determines if this is a data restriction.

Returns

True if this is a data restriction.

```
class owlapy.class_expression.restriction.OWLQuantifiedDataRestriction(  
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLQuantifiedRestriction*[*owlapy.owl_data_ranges.OWLDataRange*], *OWLDataRestriction*

Represents a quantified data restriction.

```
__slots__ = ()
```

```
get_filler() → owlapy.owl_data_ranges.OWLDataRange
```

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

```
class owlapy.class_expression.restriction.OWLDataCardinalityRestriction(  
    cardinality: int, property: owlapy.owl_property.OWLDataPropertyExpression,  
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLCardinalityRestriction*[*owlapy.owl_data_ranges.OWLDataRange*], *OWLQuantifiedDataRestriction*, *OWLDataRestriction*

Represents Data Property Cardinality Restrictions.

```
__slots__ = ()
```

```
get_property() → owlapy.owl_property.OWLDataPropertyExpression
```

Returns

Property being restricted.

```
__repr__()
```

Return repr(self).

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
class owlapy.class_expression.restriction.OWLDataMinCardinality(cardinality: int,  
    property: owlapy.owl_property.OWLDataPropertyExpression,  
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLDataCardinalityRestriction*

A minimum cardinality expression *DataMinCardinality*(*n* DPE DR) consists of a nonnegative integer *n*, a data property expression DPE, and a unary data range DR, and it contains all those individuals that are connected by DPE to at least *n* different literals in DR. (https://www.w3.org/TR/owl2-syntax/#Minimum_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3015
```

```
class owlapy.class_expression.restriction.OWLDataMaxCardinality(cardinality: int,
    property: owlapy.owl_property.OWLDataPropertyExpression,
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLDataCardinalityRestriction*

A maximum cardinality expression `ObjectMaxCardinality(n OPE CE)` consists of a nonnegative integer `n`, an object property expression `OPE`, and a class expression `CE`, and it contains all those individuals that are connected by `OPE` to at most `n` different individuals that are instances of `CE`. (https://www.w3.org/TR/owl2-syntax/#Maximum_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3017
```

```
class owlapy.class_expression.restriction.OWLDataExactCardinality(cardinality: int, property: owlapy.owl_property.OWLDataPropertyExpression,
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLDataCardinalityRestriction*

An exact cardinality expression `ObjectExactCardinality(n OPE CE)` consists of a nonnegative integer `n`, an object property expression `OPE`, and a class expression `CE`, and it contains all those individuals that are connected

by `OPE` to exactly `n` different individuals that are instances of `CE` (https://www.w3.org/TR/owl2-syntax/#Exact_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3016
```

```
as_intersection_of_min_max()
```

→ *owlapy.class_expression.nary_boolean_expression.OWLObjectIntersectionOf*

Obtains an equivalent form that is a conjunction of a min cardinality and max cardinality restriction.

Returns

The semantically equivalent but structurally simpler form $(= 1 \text{ R D}) = \geq 1 \text{ R D}$ and $\leq 1 \text{ R D}$.

```
class owlapy.class_expression.restriction.OWLDataSomeValuesFrom(property: owlapy.owl_property.OWLDataPropertyExpression,
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLQuantifiedDataRestriction*

An existential class expression `DataSomeValuesFrom(DPE1 ... DPEn DR)` consists of `n` data property expressions `DPEi`, $1 \leq i \leq n$, and a data range `DR` whose arity must be `n`. Such a class expression contains all those individuals that are connected by `DPEi` to literals `lti`, $1 \leq i \leq n$, such that the tuple (lt_1, \dots, lt_n) is in `DR`. A class expression of the form `DataSomeValuesFrom(DPE DR)` can be seen as a syntactic shortcut for the class expression `DataMinCardinality(1 DPE DR)`. (https://www.w3.org/TR/owl2-syntax/#Existential_Quantification_2)

```
__slots__ = '_property'
```

```
type_index: Final = 3012
```

```
__repr__()
```

Return `repr(self)`.

```
__eq__(other)
```

Return `self==value`.

```
__hash__()
```

Return `hash(self)`.

get_property () → *owlapy.owl_property.OWLDataPropertyExpression*

Returns

Property being restricted.

```
class owlapy.class_expression.restriction.OWLDataAllValuesFrom(  
    property: owlapy.owl_property.OWLDataPropertyExpression,  
    filler: owlapy.owl_data_ranges.OWLDataRange)
```

Bases: *OWLQuantifiedDataRestriction*

A universal class expression `DataAllValuesFrom(DPE1 ... DPEn DR)` consists of *n* data property expressions `DPEi`, $1 \leq i \leq n$, and a data range `DR` whose arity must be *n*. Such a class expression contains all those individuals that

are connected by DPE_i only to literals *l_i*, $1 \leq i \leq n$, such that each tuple (*l₁* , ..., *l_n*) is in DR.

A class

expression of the form `DataAllValuesFrom(DPE DR)` can be seen as a syntactic shortcut for the class expression `DataMaxCardinality(0 DPE DataComplementOf(DR))`. (https://www.w3.org/TR/owl2-syntax/#Universal_Quantification_2)

```
__slots__ = '_property'
```

```
type_index: Final = 3013
```

```
__repr__ ()
```

Return repr(self).

```
__eq__ (other)
```

Return self==value.

```
__hash__ ()
```

Return hash(self).

get_property () → *owlapy.owl_property.OWLDataPropertyExpression*

Returns

Property being restricted.

```
class owlapy.class_expression.restriction.OWLDataHasValue(  
    property: owlapy.owl_property.OWLDataPropertyExpression,  
    value: owlapy.owl_literal.OWLLiteral)
```

Bases: *OWLHasValueRestriction*[*owlapy.owl_literal.OWLLiteral*], *OWLDataRestriction*

A has-value class expression `DataHasValue(DPE lt)` consists of a data property expression `DPE` and a literal `lt`, and it contains all those individuals that are connected by `DPE` to `lt`. Each such class expression can be seen as a syntactic shortcut for the class expression `DataSomeValuesFrom(DPE DataOneOf(lt))`. (https://www.w3.org/TR/owl2-syntax/#Literal_Value_Restriction)

```
__slots__ = '_property'
```

```
type_index: Final = 3014
```

```
__repr__ ()
```

Return repr(self).

```
__eq__ (other)
```

Return self==value.

```

__hash__()
    Return hash(self).

as_some_values_from() → owlapy.class_expression.class_expression.OWLClassExpression
    A convenience method that obtains this restriction as an existential restriction with a nominal filler.

    Returns
        The existential equivalent of this value restriction.  $\text{simp}(\text{HasValue}(p\ a)) = \text{some}(p\ \{a\})$ .

get_property() → owlapy.owl_property.OWLDataPropertyExpression

    Returns
        Property being restricted.

```

class owlapy.class_expression.restriction.OWLDataOneOf (
 values: owlapy.owl_literal.OWLLiteral | Iterable[owlapy.owl_literal.OWLLiteral])

Bases: owlapy.owl_data_ranges.OWLDataRange, owlapy.meta_classes.HasOperands[owlapy.owl_literal.OWLLiteral]

An enumeration of literals DataOneOf($l_{t1} \dots l_{tn}$) contains exactly the explicitly specified literals l_{ti} with $1 \leq i \leq n$. The resulting data range has arity one. (https://www.w3.org/TR/owl2-syntax/#Enumeration_of_Literals)

type_index: Final = 4003

values() → Iterable[owlapy.owl_literal.OWLLiteral]

Gets the values that are in the oneOf.

Returns

The values of this {`DataOneOf`} class expression.

operands() → Iterable[owlapy.owl_literal.OWLLiteral]

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

```

__hash__()
    Return hash(self).

__eq__(other)
    Return self==value.

__repr__()
    Return repr(self).

```

class owlapy.class_expression.restriction.OWLDatatypeRestriction (
 type_: owlapy.owl_datatype.OWLDatatype,
 facet_restrictions: OWLFacetRestriction | Iterable[OWLFacetRestriction])

Bases: owlapy.owl_data_ranges.OWLDataRange

A datatype restriction DatatypeRestriction(DT F1 $l_{t1} \dots F_n l_{tn}$) consists of a unary datatype DT and n pairs (F_i, l_{ti}). The resulting data range is unary and is obtained by restricting the value space of DT according to the semantics of all (F_i, v_i) (multiple pairs are interpreted conjunctively), where v_i are the data values of the literals l_{ti} . (https://www.w3.org/TR/owl2-syntax/#Datatype_Restrictions)

__slots__ = ('_type', '_facet_restrictions')

type_index: Final = 4006

get_datatype() → owlapy.owl_datatype.OWLDatatype

```

get_facet_restrictions () → Sequence[OWLFacetRestriction]

__eq__ (other)
    Return self==value.

__hash__ ()
    Return hash(self).

__repr__ ()
    Return repr(self).

class owlapy.class_expression.restriction.OWLFacetRestriction (
    facet: owlapy.vocab.OWLFacet, literal: Literals)
    Bases: owlapy.owl_object.OWLObject
    A facet restriction is used to restrict a particular datatype.
    __slots__ = ('_facet', '_literal')
    type_index: Final = 4007

    get_facet () → owlapy.vocab.OWLFacet
    get_facet_value () → owlapy.owl_literal.OWLLiteral

    __eq__ (other)
        Return self==value.

    __hash__ ()
        Return hash(self).

    __repr__ ()
        Return repr(self).

```

Classes

<i>OWLClassExpression</i>	OWL Class expressions represent sets of individuals by formally specifying conditions on the individuals' properties;
<i>OWLAnonymousClassExpression</i>	A Class Expression which is not a named Class.
<i>OWLBooleanClassExpression</i>	Represent an anonymous boolean class expression.
<i>OWLObjectComplementOf</i>	Represents an ObjectComplementOf class expression in the OWL 2 Specification.
<i>OWLClass</i>	An OWL 2 named Class. Classes can be understood as sets of individuals.
<i>OWLNaryBooleanClassExpression</i>	OWLNaryBooleanClassExpression.
<i>OWLObjectUnionOf</i>	A union class expression ObjectUnionOf(CE1 ... CEn) contains all individuals that are instances
<i>OWLObjectIntersectionOf</i>	An intersection class expression ObjectIntersectionOf(CE1 ... CEn) contains all individuals that are instances
<i>OWLRestriction</i>	Represents an Object Property Restriction or Data Property Restriction in the OWL 2 specification.
<i>OWLQuantifiedRestriction</i>	Represents a quantified restriction.
<i>OWLQuantifiedObjectRestriction</i>	Represents a quantified object restriction.

continues on next page

Table 1 – continued from previous page

<i>OWLObjectRestriction</i>	Represents an Object Property Restriction in the OWL 2 specification.
<i>OWLHasValueRestriction</i>	Represent a HasValue restriction in the OWL 2
<i>OWLDataRestriction</i>	Represents a Data Property Restriction.
<i>OWLCardinalityRestriction</i>	Base interface for owl min and max cardinality restriction.
<i>OWLObjectCardinalityRestriction</i>	Represents Object Property Cardinality Restrictions in the OWL 2 specification.
<i>OWLObjectHasSelf</i>	A self-restriction <i>ObjectHasSelf</i> (<i>OPE</i>) consists of an object property expression <i>OPE</i> ,
<i>OWLDataOneOf</i>	An enumeration of literals <i>DataOneOf</i> (<i>lt1</i> ... <i>ltn</i>) contains exactly the explicitly specified literals <i>lti</i> with
<i>OWLQuantifiedDataRestriction</i>	Represents a quantified data restriction.
<i>OWLDataCardinalityRestriction</i>	Represents Data Property Cardinality Restrictions.
<i>OWLObjectSomeValuesFrom</i>	An existential class expression <i>ObjectSomeValuesFrom</i> (<i>OPE CE</i>) consists of an object property expression <i>OPE</i> and
<i>OWLObjectAllValuesFrom</i>	A universal class expression <i>ObjectAllValuesFrom</i> (<i>OPE CE</i>) consists of an object property expression <i>OPE</i> and a
<i>OWLObjectHasValue</i>	A has-value class expression <i>ObjectHasValue</i> (<i>OPE a</i>) consists of an object property expression <i>OPE</i> and an
<i>OWLDatatypeRestriction</i>	A datatype restriction <i>DatatypeRestriction</i> (<i>DT F1 lt1</i> ... <i>Fn ltn</i>) consists of a unary datatype <i>DT</i> and <i>n</i> pairs
<i>OWLFacet</i>	Enumerations for OWL facets.
<i>OWLFacetRestriction</i>	A facet restriction is used to restrict a particular datatype.
<i>OWLObjectMinCardinality</i>	A minimum cardinality expression <i>ObjectMinCardinality</i> (<i>n OPE CE</i>) consists of a nonnegative integer <i>n</i> , an object
<i>OWLObjectMaxCardinality</i>	A maximum cardinality expression <i>ObjectMaxCardinality</i> (<i>n OPE CE</i>) consists of a nonnegative integer <i>n</i> , an object
<i>OWLObjectExactCardinality</i>	An exact cardinality expression <i>ObjectExactCardinality</i> (<i>n OPE CE</i>) consists of a nonnegative integer <i>n</i> , an object
<i>OWLDataSomeValuesFrom</i>	An existential class expression <i>DataSomeValuesFrom</i> (<i>DPE1</i> ... <i>DPEn DR</i>) consists of <i>n</i> data property expressions
<i>OWLDataAllValuesFrom</i>	A universal class expression <i>DataAllValuesFrom</i> (<i>DPE1</i> ... <i>DPEn DR</i>) consists of <i>n</i> data property expressions <i>DPEi</i> ,
<i>OWLDataHasValue</i>	A has-value class expression <i>DataHasValue</i> (<i>DPE lt</i>) consists of a data property expression <i>DPE</i> and a literal <i>lt</i> ,
<i>OWLDataMinCardinality</i>	A minimum cardinality expression <i>DataMinCardinality</i> (<i>n DPE DR</i>) consists of a nonnegative integer <i>n</i> , a data
<i>OWLDataMaxCardinality</i>	A maximum cardinality expression <i>ObjectMaxCardinality</i> (<i>n OPE CE</i>) consists of a nonnegative integer <i>n</i> , an object
<i>OWLDataExactCardinality</i>	An exact cardinality expression <i>ObjectExactCardinality</i> (<i>n OPE CE</i>) consists of a nonnegative integer <i>n</i> , an
<i>OWLObjectOneOf</i>	An enumeration of individuals <i>ObjectOneOf</i> (<i>a1</i> ... <i>an</i>) contains exactly the individuals <i>ai</i> with $1 \leq i \leq n$.

Package Contents

class owlapy.class_expression.OWLClassExpression

Bases: *owlapy.owl_data_ranges.OWLPropertyRange*

OWL Class expressions represent sets of individuals by formally specifying conditions on the individuals' properties; individuals satisfying these conditions are said to be instances of the respective class expressions. In the structural specification of OWL 2, class expressions are represented by ClassExpression. (https://www.w3.org/TR/owl2-syntax/#Class_Expressions)

__slots__ = ()

abstract is_owl_thing() → bool

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

abstract is_owl_nothing() → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

abstract get_object_complement_of() → *OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

abstract get_nnf() → *OWLClassExpression*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

class owlapy.class_expression.OWLAnonymousClassExpression

Bases: *OWLClassExpression*

A Class Expression which is not a named Class.

is_owl_nothing() → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

is_owl_thing() → bool

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

get_object_complement_of() → *OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

get_nnf () → *OWLClassExpression*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

class owlapy.class_expression.OWLBooleanClassExpression

Bases: *OWLAnonymousClassExpression*

Represent an anonymous boolean class expression.

__slots__ = ()

class owlapy.class_expression.OWLObjectComplementOf (op: *OWLClassExpression*)

Bases: *OWLBooleanClassExpression*, *owlapy.meta_classes.HasOperands[OWLClassExpression]*

Represents an ObjectComplementOf class expression in the OWL 2 Specification.

__slots__ = '_operand'

type_index: Final = 3003

get_operand () → *OWLClassExpression*

Returns

The wrapped expression.

operands () → Iterable[*OWLClassExpression*]

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

__repr__ ()

Return repr(self).

__eq__ (other)

Return self==value.

__hash__ ()

Return hash(self).

class owlapy.class_expression.OWLClass (iri: *owlapy.iri.IRI* | str)

Bases: *owlapy.class_expression.class_expression.OWLClassExpression*, *owlapy.owl_object.OWLEntity*

An OWL 2 named Class. Classes can be understood as sets of individuals. (<https://www.w3.org/TR/owl2-syntax/#Classes>)

__slots__ = ('_iri', '_is_nothing', '_is_thing')

type_index: Final = 1001

property iri: *owlapy.iri.IRI*

Gets the IRI of this object.

Returns

The IRI of this object.

property str

Gets the string representation of this object

Returns

The IRI as string

property reminder: str

The reminder of the IRI

is_owl_thing() → bool

Determines if this expression is the built in class owl:Thing. This method does not determine if the class is equivalent to owl:Thing.

Returns

Thing.

Return type

True if this expression is owl

is_owl_nothing() → bool

Determines if this expression is the built in class owl:Nothing. This method does not determine if the class is equivalent to owl:Nothing.

get_object_complement_of()

→ *owlapy.class_expression.class_expression.OWLObjectComplementOf*

Gets the object complement of this class expression.

Returns

A class expression that is the complement of this class expression.

get_nnf() → *OWLClass*

Gets the negation normal form of the complement of this expression.

Returns

A expression that represents the NNF of the complement of this expression.

class owlapy.class_expression.OWLNaryBooleanClassExpression (
 operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])

Bases: *owlapy.class_expression.class_expression.OWLBooleanClassExpression*,
owlapy.meta_classes.HasOperands[owlapy.class_expression.class_expression.OWLClassExpression]

OWLNaryBooleanClassExpression.

__slots__ = ()

operands() → *Iterable[owlapy.class_expression.class_expression.OWLClassExpression]*

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

__repr__()

Return repr(self).

__eq__(other)

Return self==value.

__hash__()

Return hash(self).

```

class owlapy.class_expression.OWLObjectUnionOf (
    operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])
    Bases: OWLNaryBooleanClassExpression

    A union class expression ObjectUnionOf( CE1 ... CEn ) contains all individuals that are instances of at least one
    class expression CEi for  $1 \leq i \leq n$ . (https://www.w3.org/TR/owl2-syntax/#Union\_of\_Class\_Expressions)

    __slots__ = '_operands'

    type_index: Final = 3002

class owlapy.class_expression.OWLObjectIntersectionOf (
    operands: Iterable[owlapy.class_expression.class_expression.OWLClassExpression])
    Bases: OWLNaryBooleanClassExpression

    An intersection class expression ObjectIntersectionOf( CE1 ... CEn ) contains all individuals that are instances of
    all class expressions CEi for  $1 \leq i \leq n$ . (https://www.w3.org/TR/owl2-syntax/#Intersection\_of\_Class\_Expressions)

    __slots__ = '_operands'

    type_index: Final = 3001

class owlapy.class_expression.OWLRestriction
    Bases: owlapy.class_expression.class_expression.OWLAnonymousClassExpression

    Represents an Object Property Restriction or Data Property Restriction in the OWL 2 specification.

    __slots__ = ()

    abstract get_property () → owlapy.owl_property.OWLPropertyExpression

        Returns
            Property being restricted.

    is_data_restriction () → bool
        Determines if this is a data restriction.

        Returns
            True if this is a data restriction.

    is_object_restriction () → bool
        Determines if this is an object restriction.

        Returns
            True if this is an object restriction.

class owlapy.class_expression.OWLQuantifiedRestriction
    Bases: Generic[_T], OWLRestriction, owlapy.meta_classes.HasFiller[_T]

    Represents a quantified restriction.

    Parameters
        _T – value type

    __slots__ = ()

```

```

class owlapy.class_expression.OWLQuantifiedObjectRestriction (
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
    Bases:      OWLQuantifiedRestriction[owlapy.class_expression.class_expression.
        OWLClassExpression], OWLObjectRestriction
    Represents a quantified object restriction.

    __slots__ = ()

    get_filler() → owlapy.class_expression.class_expression.OWLClassExpression
        Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of
        a data restriction this will be a constant (data value). For quantified restriction this will be a class expression
        or a data range.

        Returns
            the value

class owlapy.class_expression.OWLObjectRestriction
    Bases: OWLRestriction
    Represents an Object Property Restriction in the OWL 2 specification.

    __slots__ = ()

    is_object_restriction() → bool
        Determines if this is an object restriction.

        Returns
            True if this is an object restriction.

    abstract get_property() → owlapy.owl_property.OWLObjectPropertyExpression

        Returns
            Property being restricted.

class owlapy.class_expression.OWLHasValueRestriction (value: _T)
    Bases: Generic[_T], OWLRestriction, owlapy.meta_classes.HasFiller[_T]
    Represent a HasValue restriction in the OWL 2

        Parameters
            _T – The value type.

    __slots__ = ()

    __eq__ (other)
        Return self==value.

    __hash__ ()
        Return hash(self).

    get_filler() → _T
        Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of
        a data restriction this will be a constant (data value). For quantified restriction this will be a class expression
        or a data range.

        Returns
            the value

```

```

class owlapy.class_expression.OWLDataRestriction
    Bases: OWLRestriction

    Represents a Data Property Restriction.

    __slots__ = ()

    is_data_restriction() → bool
        Determines if this is a data restriction.

        Returns
            True if this is a data restriction.

class owlapy.class_expression.OWLCardinalityRestriction(cardinality: int, filler: _F)
    Bases: Generic[_F], OWLQuantifiedRestriction[_F], owlapy.meta_classes.HasCardinality

    Base interface for owl min and max cardinality restriction.

    Parameters
        _F – Type of filler.

    __slots__ = ()

    get_cardinality() → int
        Gets the cardinality of a restriction.

    Returns
        The cardinality. A non-negative integer.

    get_filler() → _F
        Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of
        a data restriction this will be a constant (data value). For quantified restriction this will be a class expression
        or a data range.

    Returns
        the value

class owlapy.class_expression.OWLObjectCardinalityRestriction(cardinality: int,
    property: owlapy.owl_property.OWLObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
    Bases: OWLCardinalityRestriction[owlapy.class_expression.class_expression.OWLClassExpression], OWLQuantifiedObjectRestriction

    Represents Object Property Cardinality Restrictions in the OWL 2 specification.

    __slots__ = ()

    get_property() → owlapy.owl_property.OWLObjectPropertyExpression

    Returns
        Property being restricted.

    __repr__()
        Return repr(self).

    __eq__(other)
        Return self==value.

    __hash__()
        Return hash(self).

```

```

class owlapy.class_expression.OLObjectHasSelf (
    property: owlapy.owl_property.OWLObjectPropertyExpression)
    Bases: OWLObjectRestriction

    A self-restriction ObjectHasSelf( OPE ) consists of an object property expression OPE, and it contains all those
    individuals that are connected by OPE to themselves. (https://www.w3.org/TR/owl2-syntax/#Self-Restriction)

    __slots__ = '_property'

    type_index: Final = 3011

    get_property () → owlapy.owl_property.OWLObjectPropertyExpression

        Returns
            Property being restricted.

    __eq__ (other)
        Return self==value.

    __hash__ ()
        Return hash(self).

    __repr__ ()
        Return repr(self).

class owlapy.class_expression.OWLDataOneOf (
    values: owlapy.owl_literal.OWLLiteral | Iterable[owlapy.owl_literal.OWLLiteral])
    Bases: owlapy.owl_data_ranges.OWLDataRange, owlapy.meta_classes.
    HasOperands[owlapy.owl_literal.OWLLiteral]

    An enumeration of literals DataOneOf( lt1 ... ltn ) contains exactly the explicitly specified literals lti with  $1 \leq i \leq n$ .
    The resulting data range has arity one. (https://www.w3.org/TR/owl2-syntax/#Enumeration\_of\_Literals)

    type_index: Final = 4003

    values () → Iterable[owlapy.owl_literal.OWLLiteral]
        Gets the values that are in the oneOf.

        Returns
            The values of this {@code DataOneOf} class expression.

    operands () → Iterable[owlapy.owl_literal.OWLLiteral]
        Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

        Returns
            The operands.

    __hash__ ()
        Return hash(self).

    __eq__ (other)
        Return self==value.

    __repr__ ()
        Return repr(self).

class owlapy.class_expression.OWLQuantifiedDataRestriction (
    filler: owlapy.owl_data_ranges.OWLDataRange)

```


Bases: `OWLQuantifiedRestriction[owlapy.owl_data_ranges.OWLDataRange]`, `OWLDataRestriction`

Represents a quantified data restriction.

__slots__ = ()

get_filler() → `owlapy.owl_data_ranges.OWLDataRange`

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

class `owlapy.class_expression.OWLDataCardinalityRestriction` (*cardinality: int*,
property: owlapy.owl_property.OWLDataPropertyExpression,
filler: owlapy.owl_data_ranges.OWLDataRange)

Bases: `OWLCardinalityRestriction[owlapy.owl_data_ranges.OWLDataRange]`,
`OWLQuantifiedDataRestriction`, `OWLDataRestriction`

Represents Data Property Cardinality Restrictions.

__slots__ = ()

get_property() → `owlapy.owl_property.OWLDataPropertyExpression`

Returns

Property being restricted.

__repr__()

Return repr(self).

__eq__(*other*)

Return self==value.

__hash__()

Return hash(self).

class `owlapy.class_expression.OWLObjectSomeValuesFrom` (
property: owlapy.owl_property.OWLObjectPropertyExpression,
filler: owlapy.class_expression.class_expression.OWLClassExpression)

Bases: `OWLQuantifiedObjectRestriction`

An existential class expression `ObjectSomeValuesFrom(OPE CE)` consists of an object property expression OPE and a class expression CE, and it contains all those individuals that are connected by OPE to an individual that is an instance of CE.

__slots__ = ('_property', '_filler')

type_index: `Final` = 3005

__repr__()

Return repr(self).

__eq__(*other*)

Return self==value.

__hash__ ()

Return hash(self).

get_property () → *owlapy.owl_property.OWLObjectPropertyExpression*

Returns

Property being restricted.

class owlapy.class_expression.OWLObjectAllValuesFrom (
 property: owlapy.owl_property.OWLObjectPropertyExpression,
 filler: owlapy.class_expression.class_expression.OWLClassExpression)

Bases: *OWLQuantifiedObjectRestriction*

A universal class expression ObjectAllValuesFrom(OPE CE) consists of an object property expression OPE and a class expression CE, and it contains all those individuals that are connected by OPE only to individuals that are instances of CE. (https://www.w3.org/TR/owl2-syntax/#Universal_Quantification)

__slots__ = ('_property', '_filler')

type_index: Final = 3006

__repr__ ()

Return repr(self).

__eq__ (other)

Return self==value.

__hash__ ()

Return hash(self).

get_property () → *owlapy.owl_property.OWLObjectPropertyExpression*

Returns

Property being restricted.

class owlapy.class_expression.OWLObjectHasValue (
 property: owlapy.owl_property.OWLObjectPropertyExpression,
 individual: owlapy.owl_individual.OWLIndividual)

Bases: *OWLHasValueRestriction[owlapy.owl_individual.OWLIndividual], OWLObjectRestriction*

A has-value class expression ObjectHasValue(OPE a) consists of an object property expression OPE and an individual a, and it contains all those individuals that are connected by OPE to a. Each such class expression can be seen as a syntactic shortcut for the class expression ObjectSomeValuesFrom(OPE ObjectOneOf(a)). (https://www.w3.org/TR/owl2-syntax/#Individual_Value_Restriction)

__slots__ = ('_property', '_v')

type_index: Final = 3007

get_property () → *owlapy.owl_property.OWLObjectPropertyExpression*

Returns

Property being restricted.

as_some_values_from () → *owlapy.class_expression.class_expression.OWLClassExpression*

A convenience method that obtains this restriction as an existential restriction with a nominal filler.

Returns

The existential equivalent of this value restriction. $\text{simp}(\text{HasValue}(p\ a)) = \text{some}(p\ \{a\})$.

```

__repr__ ()
    Return repr(self).

class owlapy.class_expression.OWLDatatypeRestriction (
    type_: owlapy.owl_datatype.OWLDatatype,
    facet_restrictions: OWLFacetRestriction | Iterable[OWLFacetRestriction])
    Bases: owlapy.owl_data_ranges.OWLDataRange

    A datatype restriction DatatypeRestriction( DT F1 lt1 ... Fn ltn ) consists of a unary datatype DT and n pairs (
    Fi , lti ). The resulting data range is unary and is obtained by restricting the value space of DT according to the
    semantics of all ( Fi , vi ) (multiple pairs are interpreted conjunctively), where vi are the data values of the literals
    lti. (https://www.w3.org/TR/owl2-syntax/#Datatype\_Restrictions)

    __slots__ = ('_type', '_facet_restrictions')

    type_index: Final = 4006

    get_datatype () → owlapy.owl_datatype.OWLDatatype

    get_facet_restrictions () → Sequence[OWLFacetRestriction]

    __eq__ (other)
        Return self==value.

    __hash__ ()
        Return hash(self).

    __repr__ ()
        Return repr(self).

class owlapy.class_expression.OWLFacet (remainder: str, symbolic_form: str,
    operator: Callable[[_X, _X], bool])
    Bases: _Vocabulary, enum.Enum

    Enumerations for OWL facets.

    property symbolic_form

    property operator

    static from_str (name: str) → OWLFacet

    MIN_INCLUSIVE: Final

    MIN_EXCLUSIVE: Final

    MAX_INCLUSIVE: Final

    MAX_EXCLUSIVE: Final

    LENGTH: Final

    MIN_LENGTH: Final

    MAX_LENGTH: Final

    PATTERN: Final

    TOTAL_DIGITS: Final

```

```

FRACTION_DIGITS: Final

class owlapy.class_expression.OWLFacetRestriction (facet: owlapy.vocab.OWLFacet,
    literal: Literals)
    Bases: owlapy.owl_object.OWLObject
    A facet restriction is used to restrict a particular datatype.
    __slots__ = ('_facet', '_literal')
    type_index: Final = 4007
    get_facet () → owlapy.vocab.OWLFacet
    get_facet_value () → owlapy.owl_literal.OWLLiteral
    __eq__ (other)
        Return self==value.
    __hash__ ()
        Return hash(self).
    __repr__ ()
        Return repr(self).

class owlapy.class_expression.OWLObjectMinCardinality (cardinality: int,
    property: owlapy.owl_property.OWLObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
    Bases: OWLObjectCardinalityRestriction
    A minimum cardinality expression ObjectMinCardinality( n OPE CE ) consists of a nonnegative integer n, an object
    property expression OPE, and a class expression CE, and it contains all those individuals that are connected by
    OPE to at least n different individuals that are instances of CE. (https://www.w3.org/TR/owl2-syntax/#Minimum\_Cardinality)
    __slots__ = ('_cardinality', '_filler', '_property')
    type_index: Final = 3008

class owlapy.class_expression.OWLObjectMaxCardinality (cardinality: int,
    property: owlapy.owl_property.OWLObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
    Bases: OWLObjectCardinalityRestriction
    A maximum cardinality expression ObjectMaxCardinality( n OPE CE ) consists of a nonnegative integer n, an
    object property expression OPE, and a class expression CE, and it contains all those individuals that are connected
    by OPE
        to at most n different individuals that are instances of CE. (https://www.w3.org/TR/owl2-syntax/#Maximum\_Cardinality)
    __slots__ = ('_cardinality', '_filler', '_property')
    type_index: Final = 3010

class owlapy.class_expression.OWLObjectExactCardinality (cardinality: int,
    property: owlapy.owl_property.OWLObjectPropertyExpression,
    filler: owlapy.class_expression.class_expression.OWLClassExpression)
    Bases: OWLObjectCardinalityRestriction

```

An exact cardinality expression **ObjectExactCardinality(n OPE CE)** consists of a nonnegative integer **n**, an object

property expression **OPE**, and a class expression **CE**, and it contains all those individuals that are connected by to exactly **n** different individuals that are instances of **CE**.

(https://www.w3.org/TR/owl2-syntax/#Exact_Cardinality)

```
__slots__ = ('_cardinality', '_filler', '_property')
```

```
type_index: Final = 3009
```

```
as_intersection_of_min_max()
```

→ *owlapy.class_expression.nary_boolean_expression.OwlObjectIntersectionOf*

Obtains an equivalent form that is a conjunction of a min cardinality and max cardinality restriction.

Returns

The semantically equivalent but structurally simpler form ($= 1 R C$) $=> 1 R C$ and $<= 1 R C$.

```
class owlapy.class_expression.OwlDataSomeValuesFrom(
```

```
    property: owlapy.owl_property.OwlDataPropertyExpression,
```

```
    filler: owlapy.owl_data_ranges.OwlDataRange)
```

Bases: *OwlQuantifiedDataRestriction*

An existential class expression **DataSomeValuesFrom(DPE₁ ... DPE_n DR)** consists of **n** data property expressions **DPE_i**, $1 \leq i \leq n$, and a data range **DR** whose arity must be **n**. Such a class expression contains all those individuals that are connected by **DPE_i** to literals **lt_i**, $1 \leq i \leq n$, such that the tuple (**lt₁** , ..., **lt_n**) is in **DR**. A class expression of the form **DataSomeValuesFrom(DPE DR)** can be seen as a syntactic shortcut for the class expression **DataMinCardinality(1 DPE DR)**. (https://www.w3.org/TR/owl2-syntax/#Existential_Quantification_2)

```
__slots__ = '_property'
```

```
type_index: Final = 3012
```

```
__repr__()
```

Return repr(self).

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
get_property() → owlapy.owl_property.OwlDataPropertyExpression
```

Returns

Property being restricted.

```
class owlapy.class_expression.OwlDataAllValuesFrom(
```

```
    property: owlapy.owl_property.OwlDataPropertyExpression,
```

```
    filler: owlapy.owl_data_ranges.OwlDataRange)
```

Bases: *OwlQuantifiedDataRestriction*

A universal class expression **DataAllValuesFrom(DPE₁ ... DPE_n DR)** consists of **n** data property expressions **DPE_i**, $1 \leq i \leq n$, and a data range **DR** whose arity must be **n**. Such a class expression contains all those individuals that

are connected by DPE_i only to literals lt_i, $1 \leq i \leq n$, such that each tuple (lt₁ , ..., lt_n) is in DR.

A class

expression of the form **DataAllValuesFrom(DPE DR)** can be seen as a syntactic shortcut for the class expression **DataMaxCardinality(0 DPE DataComplementOf(DR))**. (https://www.w3.org/TR/owl2-syntax/#Universal_Quantification_2)

```

__slots__ = '_property'

type_index: Final = 3013

__repr__ ()
    Return repr(self).

__eq__ (other)
    Return self==value.

__hash__ ()
    Return hash(self).

get_property () → owlapy.owl_property.OWLDataPropertyExpression

```

Returns

Property being restricted.

```

class owlapy.class_expression.OWLDataHasValue (
    property: owlapy.owl_property.OWLDataPropertyExpression,
    value: owlapy.owl_literal.OWLLiteral)

Bases: OWLHasValueRestriction[owlapy.owl_literal.OWLLiteral], OWLDataRestriction

```

A has-value class expression `DataHasValue(DPE It)` consists of a data property expression DPE and a literal It, and it contains all those individuals that are connected by DPE to It. Each such class expression can be seen as a syntactic shortcut for the class expression `DataSomeValuesFrom(DPE DataOneOf(It))`. (https://www.w3.org/TR/owl2-syntax/#Literal_Value_Restriction)

```

__slots__ = '_property'

type_index: Final = 3014

__repr__ ()
    Return repr(self).

__eq__ (other)
    Return self==value.

__hash__ ()
    Return hash(self).

```

```

as_some_values_from () → owlapy.class_expression.class_expression.OWLClassExpression

```

A convenience method that obtains this restriction as an existential restriction with a nominal filler.

Returns

The existential equivalent of this value restriction. $\text{simp}(\text{HasValue}(p\ a)) = \text{some}(p\ \{a\})$.

```

get_property () → owlapy.owl_property.OWLDataPropertyExpression

```

Returns

Property being restricted.

```

class owlapy.class_expression.OWLDataMinCardinality (cardinality: int,
    property: owlapy.owl_property.OWLDataPropertyExpression,
    filler: owlapy.owl_data_ranges.OWLDataRange)

Bases: OWLDataCardinalityRestriction

```

A minimum cardinality expression `DataMinCardinality(n DPE DR)` consists of a nonnegative integer n, a data property expression DPE, and a unary data range DR, and it contains all those individuals that are connected by DPE to at least n different literals in DR. (https://www.w3.org/TR/owl2-syntax/#Minimum_Cardinality)

```

__slots__ = ('_cardinality', '_filler', '_property')

type_index: Final = 3015

```

class owlapy.class_expression.OWLDataMaxCardinality (cardinality: int,
property: owlapy.owl_property.OWLDataPropertyExpression,
filler: owlapy.owl_data_ranges.OWLDataRange)

Bases: *OWLDataCardinalityRestriction*

A maximum cardinality expression ObjectMaxCardinality(n OPE CE) consists of a nonnegative integer n, an object property expression OPE, and a class expression CE, and it contains all those individuals that are connected by OPE to at most n different individuals that are instances of CE. (https://www.w3.org/TR/owl2-syntax/#Maximum_Cardinality)

```

__slots__ = ('_cardinality', '_filler', '_property')

type_index: Final = 3017

```

class owlapy.class_expression.OWLDataExactCardinality (cardinality: int,
property: owlapy.owl_property.OWLDataPropertyExpression,
filler: owlapy.owl_data_ranges.OWLDataRange)

Bases: *OWLDataCardinalityRestriction*

An exact cardinality expression ObjectExactCardinality(n OPE CE) consists of a nonnegative integer n, an object property expression OPE, and a class expression CE, and it contains all those individuals that are connected by OPE to exactly n different individuals that are instances of CE (https://www.w3.org/TR/owl2-syntax/#Exact_Cardinality)

```

__slots__ = ('_cardinality', '_filler', '_property')

type_index: Final = 3016

```

as_intersection_of_min_max()
→ owlapy.class_expression.nary_boolean_expression.OWLObjectIntersectionOf

Obtains an equivalent form that is a conjunction of a min cardinality and max cardinality restriction.

Returns
The semantically equivalent but structurally simpler form ($= 1 \text{ R D} \Rightarrow 1 \text{ R D}$ and $\leq 1 \text{ R D}$).

class owlapy.class_expression.OWLObjectOneOf (
values: owlapy.owl_individual.OWLIndividual | Iterable[owlapy.owl_individual.OWLIndividual])

Bases: *owlapy.class_expression.class_expression.OWLAnonymousClassExpression*,
owlapy.meta_classes.HasOperands[owlapy.owl_individual.OWLIndividual]

An enumeration of individuals ObjectOneOf(a1 ... an) contains exactly the individuals ai with $1 \leq i \leq n$. (https://www.w3.org/TR/owl2-syntax/#Enumeration_of_Individuals)

```

__slots__ = '_values'

type_index: Final = 3004

```

individuals() → Iterable[owlapy.owl_individual.OWLIndividual]

Gets the individuals that are in the oneOf. These individuals represent the exact instances (extension) of this class expression.

Returns
The individuals that are the values of this {`@code` ObjectOneOf} class expression.

operands () → Iterable[*owlapy.owl_individual.OWLIndividual*]

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

as_object_union_of () → *owlapy.class_expression.class_expression.OWLClassExpression*

Simplifies this enumeration to a union of singleton nominals.

Returns

This enumeration in a more standard DL form. $\text{simp}(\{a\}) = \{a\}$ $\text{simp}(\{a_0, \dots, \{a_n\}\}) = \text{unionOf}(\{a_0\}, \dots, \{a_n\})$

__hash__ ()

Return hash(self).

__eq__ (other)

Return self==value.

__repr__ ()

Return repr(self).

owlapy.entities

Entities are the fundamental building blocks of OWL 2 ontologies, and they define the vocabulary — the named terms — of an ontology. In logic, the set of entities is usually said to constitute the signature of an ontology.

Classes, datatypes, object properties, data properties, annotation properties, and named individuals are entities, and they are all uniquely identified by an IR.

7.2 Submodules

owlapy.converter

Format converter.

Attributes

<i>converter</i>

Classes

<i>VariablesMapping</i>	Helper class for owl-to-sparql conversion.
<i>Owl2SparqlConverter</i>	Convert owl (owlapy model class expressions) to SPARQL.

Functions

<code>peek(x)</code>	Peek the last element of an array.
<code>owl_expression_to_sparql(→ str)</code>	Convert an OWL Class Expression (https://www.w3.org/TR/owl2-syntax/#Class_Expressions) into a SPARQL query

Module Contents

`owlapy.converter.peek(x)`

Peek the last element of an array.

Returns

The last element `arr[-1]`.

class `owlapy.converter.VariablesMapping`

Helper class for owl-to-sparql conversion.

`__slots__ = ('class_cnt', 'prop_cnt', 'ind_cnt', 'dict')`

`class_cnt = 0`

`prop_cnt = 0`

`ind_cnt = 0`

`dict`

`get_variable(e: owlapy.owl_object.OWLEntity) → str`

`new_individual_variable() → str`

`new_property_variable() → str`

`__contains__(item: owlapy.owl_object.OWLEntity) → bool`

`__getitem__(item: owlapy.owl_object.OWLEntity) → str`

class `owlapy.converter.Owl2SparqlConverter`

Convert owl (owlapy model class expressions) to SPARQL.

`__slots__ = ('ce', 'sparql', 'variables', 'parent', 'parent_var', 'properties', 'variable_entities', 'cnt', ...)`

`ce: owlapy.class_expression.OWLClassExpression`

`sparql: List[str]`

`variables: List[str]`

`parent: List[owlapy.class_expression.OWLClassExpression]`

`parent_var: List[str]`

`variable_entities: Set[owlapy.owl_object.OWLEntity]`

```

properties: Dict[int, List[owlapy.owl_object.OWLEntity]]

mapping: VariablesMapping

grouping_vars: Dict[owlapy.class_expression.OWLClassExpression, Set[str]]

having_conditions: Dict[owlapy.class_expression.OWLClassExpression,
Set[str]]

cnt: int

for_all_de_morgan: bool

named_individuals: bool

convert (root_variable: str, ce: owlapy.class_expression.OWLClassExpression,
        for_all_de_morgan: bool = True, named_individuals: bool = False)
    Used to convert owl class expression to SPARQL syntax.

```

Parameters

- **root_variable** (*str*) – Root variable name that will be used in SPARQL query.
- **ce** (*OWLClassExpression*) – The owl class expression to convert.
- **named_individuals** (*bool*) – If ‘True’ return only entities that are instances of owl:NamedIndividual.

Returns

The SPARQL query.

Return type

list[str]

```

property modal_depth

abstract render (e)

stack_variable (var)

stack_parent (parent: owlapy.class_expression.OWLClassExpression)

property current_variable

abstract process (ce: owlapy.class_expression.OWLClassExpression)

forAll (ce: owlapy.class_expression.OWLObjectAllValuesFrom)

forAllDeMorgan (ce: owlapy.class_expression.OWLObjectAllValuesFrom)

new_count_var () → str

append_triple (subject, predicate, object_)

append (frag)

triple (subject, predicate, object_)

as_query (root_variable: str, ce: owlapy.class_expression.OWLClassExpression,
        for_all_de_morgan: bool = True, count: bool = False,
        values: Iterable[owlapy.owl_individual.OWLNamedIndividual] | None = None,
        named_individuals: bool = False) → str

```

`owlapy.converter.converter`

`owlapy.converter.owl_expression_to_sparql (`

expression: owlapy.class_expression.OWLClassExpression = None, root_variable: str = '?x',

values: Iterable[owlapy.owl_individual.OWLNamedIndividual] | None = None,

for_all_de_morgan: bool = True, named_individuals: bool = False) → str

Convert an OWL Class Expression (https://www.w3.org/TR/owl2-syntax/#Class_Expressions) into a SPARQL query root variable: the variable that will be projected expression: the class expression to be transformed to a SPARQL query

values: positive or negative examples from a class expression problem. Unclear for_all_de_morgan: if set to True, the SPARQL mapping will use the mapping containing the nested FILTER NOT EXISTS patterns for the universal quantifier ($\neg(\exists r. \neg C)$), instead of the counting query named_individuals: if set to True, the generated SPARQL query will return only entities that are instances of owl:NamedIndividual

owlapy.iri

OWL IRI

Classes

IRI

An IRI, consisting of a namespace and a remainder.

Module Contents

class `owlapy.iri.IRI (namespace: str | owlapy.namespaces.Namespaces, remainder: str)`

Bases: `owlapy.owl_annotation.OWLAnnotationSubject`, `owlapy.owl_annotation.OWLAnnotationValue`

An IRI, consisting of a namespace and a remainder.

__slots__ = ('_namespace', '_remainder', '__weakref__')

type_index: `Final` = 0

static create (*namespace: owlapy.namespaces.Namespaces, remainder: str*) → *IRI*

static create (*namespace: str, remainder: str*) → *IRI*

static create (*string: str*) → *IRI*

__repr__ ()

Return repr(self).

__eq__ (*other*)

Return self==value.

__hash__ ()

Return hash(self).

is_nothing ()

Determines if this IRI is equal to the IRI that owl:Nothing is named with.

Returns

True if this IRI is equal to <<http://www.w3.org/2002/07/owl#Nothing>> and otherwise False.

is_thing()

Determines if this IRI is equal to the IRI that owl:Thing is named with.

Returns

True if this IRI is equal to <<http://www.w3.org/2002/07/owl#Thing>> and otherwise False.

is_reserved_vocabulary() → bool

Determines if this IRI is in the reserved vocabulary. An IRI is in the reserved vocabulary if it starts with <<http://www.w3.org/1999/02/22-rdf-syntax-ns#>> or <<http://www.w3.org/2000/01/rdf-schema#>> or <<http://www.w3.org/2001/XMLSchema#>> or <<http://www.w3.org/2002/07/owl#>>.

Returns

True if the IRI is in the reserved vocabulary, otherwise False.

as_iri() → *IRI*

Returns

if the value is an IRI, return it. Return None otherwise.

as_str() → str

CD: Should be deprecated. :returns: The string that specifies the IRI.

property str: str

Returns: The string that specifies the IRI.

property reminder: str

Returns: The string corresponding to the reminder of the IRI.

get_namespace() → str

Returns

The namespace as string.

get_remainder() → str

Returns

The remainder (coincident with NCName usually) for this IRI.

owlapy.meta_classes

Meta classes for OWL objects.

Classes

<i>HasIRI</i>	Simple class to access the IRI.
<i>HasOperands</i>	An interface to objects that have a collection of operands.
<i>HasFiller</i>	An interface to objects that have a filler.
<i>HasCardinality</i>	An interface to objects that have a cardinality.

Module Contents

class owlapy.meta_classes.**HasIRI**

Simple class to access the IRI.

__slots__ = ()

abstract property **iri**

Gets the IRI of this object.

Returns

The IRI of this object.

property str: **str**

Abstractmethod

Gets the string representation of this object

Returns

The IRI as string

class owlapy.meta_classes.**HasOperands**

Bases: Generic[_T]

An interface to objects that have a collection of operands.

Parameters

_T – Operand type.

__slots__ = ()

abstract operands () → Iterable[_T]

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

class owlapy.meta_classes.**HasFiller**

Bases: Generic[_T]

An interface to objects that have a filler.

Parameters

_T – Filler type.

__slots__ = ()

abstract get_filler () → _T

Gets the filler for this restriction. In the case of an object restriction this will be an individual, in the case of a data restriction this will be a constant (data value). For quantified restriction this will be a class expression or a data range.

Returns

the value

class owlapy.meta_classes.**HasCardinality**

An interface to objects that have a cardinality.

__slots__ = ()

abstract `get_cardinality()` \rightarrow int

Gets the cardinality of a restriction.

Returns

The cardinality. A non-negative integer.

owlapy.namespaces

Namespaces.

Attributes

OWL

RDFS

RDF

XSD

Classes

Namespaces

Namespaces provide a simple method for qualifying element and attribute names used in Extensible Markup

Module Contents

class owlapy.namespaces.**Namespaces** (*prefix: str, ns: str*)

Namespaces provide a simple method for qualifying element and attribute names used in Extensible Markup Language documents by associating them with namespaces identified by URI references

__slots__ = ('_prefix', '_ns')

property ns: str

property prefix: str

__repr__()

Return repr(self).

__hash__()

Return hash(self).

__eq__(*other*)

Return self==value.

owlapy.namespaces.**OWL: Final**

`owlapy.namespaces.RDFS: Final`

`owlapy.namespaces.RDF: Final`

`owlapy.namespaces.XSD: Final`

owlapy.owl_annotation

OWL Annotations

Classes

<i>OWLAnnotationObject</i>	A marker interface for the values (objects) of annotations.
<i>OWLAnnotationSubject</i>	A marker interface for annotation subjects, which can either be IRIs or anonymous individuals
<i>OWLAnnotationValue</i>	A marker interface for annotation values, which can either be an IRI (URI), Literal or Anonymous Individual.

Module Contents

class `owlapy.owl_annotation.OWLAnnotationObject`

Bases: *owlapy.owl_object.OWLObject*

A marker interface for the values (objects) of annotations.

__slots__ = ()

as_iri()

Returns

if the value is an IRI, return it. Return None otherwise.

as_anonymous_individual()

Returns

if the value is an anonymous, return it. Return None otherwise.

class `owlapy.owl_annotation.OWLAnnotationSubject`

Bases: *OWLAnnotationObject*

A marker interface for annotation subjects, which can either be IRIs or anonymous individuals

__slots__ = ()

class `owlapy.owl_annotation.OWLAnnotationValue`

Bases: *OWLAnnotationObject*

A marker interface for annotation values, which can either be an IRI (URI), Literal or Anonymous Individual.

__slots__ = ()

is_literal() → bool

Returns

true if the annotation value is a literal

as_literal()

Returns

if the value is a literal, returns it. Return None otherwise

owlapy.owl_axiom

OWL Axioms

Classes

<i>OWLAxiom</i>	Represents Axioms in the OWL 2 Specification.
<i>OWLLogicalAxiom</i>	A base interface of all axioms that affect the logical meaning of an ontology. This excludes declaration
<i>OWLPropertyAxiom</i>	The base interface for property axioms.
<i>OWLObjectPropertyAxiom</i>	The base interface for object property axioms.
<i>OWLDatapropertyAxiom</i>	The base interface for data property axioms.
<i>OWLIndividualAxiom</i>	The base interface for individual axioms.
<i>OWLClassAxiom</i>	The base interface for class axioms.
<i>OWLDeclarationAxiom</i>	Represents a Declaration axiom in the OWL 2 Specification. A declaration axiom declares an entity in an ontology.
<i>OWLDatatypeDefinitionAxiom</i>	A datatype definition DatatypeDefinition(DT DR) defines a new datatype DT as being semantically
<i>OWLHasKeyAxiom</i>	A key axiom HasKey(CE (OPE1 ... OPEm) (DPE1 ... DPEn)) states that each
<i>OWLNaryAxiom</i>	Represents an axiom that contains two or more operands that could also be represented with multiple pairwise
<i>OWLNaryClassAxiom</i>	Represents an axiom that contains two or more operands that could also be represented with
<i>OWLEquivalentClassesAxiom</i>	An equivalent classes axiom EquivalentClasses(CE1 ... CEn) states that all of the class expressions CEi,
<i>OWLDisjointClassesAxiom</i>	A disjoint classes axiom DisjointClasses(CE1 ... CEn) states that all of the class expressions CEi, $1 \leq i \leq n$,
<i>OWLNaryIndividualAxiom</i>	Represents an axiom that contains two or more operands that could also be represented with
<i>OWLDifferentIndividualsAxiom</i>	An individual inequality axiom DifferentIndividuals(a1 ... an) states that all of the individuals ai,
<i>OWLSameIndividualAxiom</i>	An individual equality axiom SameIndividual(a1 ... an) states that all of the individuals ai, $1 \leq i \leq n$,
<i>OWLNaryPropertyAxiom</i>	Represents an axiom that contains two or more operands that could also be represented with
<i>OWLEquivalentObjectPropertiesAxiom</i>	An equivalent object properties axiom EquivalentObjectProperties(OPE1 ... OPEn) states that all of the object
<i>OWLDisjointObjectPropertiesAxiom</i>	A disjoint object properties axiom DisjointObjectProperties(OPE1 ... OPEn) states that all of the object
<i>OWLInverseObjectPropertiesAxiom</i>	An inverse object properties axiom InverseObjectProperties(OPE1 OPE2) states that the object property
<i>OWLEquivalentDataPropertiesAxiom</i>	An equivalent data properties axiom EquivalentDataProperties(DPE1 ... DPEn) states that all the data property

continues on next page

Table 2 – continued from previous page

<i>OWLDisjointDataPropertiesAxiom</i>	A disjoint data properties axiom <i>DisjointDataProperties</i> (DPE1 ... DPE _n) states that all of the data property
<i>OWLSubClassOfAxiom</i>	A subclass axiom <i>SubClassOf</i> (CE1 CE2) states that the class expression CE1 is a subclass of the class
<i>OWLDisjointUnionAxiom</i>	A disjoint union axiom <i>DisjointUnion</i> (C CE1 ... CE _n) states that a class C is a disjoint union of the class
<i>OWLClassAssertionAxiom</i>	A class assertion <i>ClassAssertion</i> (CE a) states that the individual a is an instance of the class expression CE.
<i>OWLAnnotationProperty</i>	Represents an <i>AnnotationProperty</i> in the OWL 2 specification.
<i>OWLAnnotation</i>	Annotations are used in the various types of annotation axioms, which bind annotations to their subjects
<i>OWLAnnotationAxiom</i>	A super interface for annotation axioms.
<i>OWLAnnotationAssertionAxiom</i>	An annotation assertion <i>AnnotationAssertion</i> (AP as av) states that the annotation subject as — an IRI or an
<i>OWLSubAnnotationPropertyOfAxiom</i>	An annotation subproperty axiom <i>SubAnnotationPropertyOf</i> (AP1 AP2) states that the annotation property AP1 is
<i>OWLAnnotationPropertyDomainAxiom</i>	An annotation property domain axiom <i>AnnotationPropertyDomain</i> (AP U) states that the domain of the annotation
<i>OWLAnnotationPropertyRangeAxiom</i>	An annotation property range axiom <i>AnnotationPropertyRange</i> (AP U)
<i>OWLSubPropertyAxiom</i>	Base interface for object and data sub-property axioms.
<i>OWLSubObjectPropertyOfAxiom</i>	Object subproperty axioms are analogous to subclass axioms, and they come in two forms.
<i>OWLSubDataPropertyOfAxiom</i>	A data subproperty axiom <i>SubDataPropertyOf</i> (DPE1 DPE2) states that the data property expression DPE1 is a
<i>OWLPropertyAssertionAxiom</i>	Base class for Property Assertion axioms.
<i>OWLObjectPropertyAssertionAxiom</i>	A positive object property assertion <i>ObjectPropertyAssertion</i> (OPE a1 a2) states that the individual a1 is
<i>OWLNegativeObjectPropertyAssertionAxiom</i>	A negative object property assertion <i>NegativeObjectPropertyAssertion</i> (OPE a1 a2) states that the individual a1
<i>OWLDataPropertyAssertionAxiom</i>	A positive data property assertion <i>DataPropertyAssertion</i> (DPE a lt) states that the individual a is connected
<i>OWLNegativeDataPropertyAssertionAxiom</i>	A negative data property assertion <i>NegativeDataPropertyAssertion</i> (DPE a lt) states that the individual a is not
<i>OWLUnaryPropertyAxiom</i>	Base class for Unary property axiom.
<i>OWLObjectPropertyCharacteristicAxiom</i>	Base interface for functional object property axiom.
<i>OWLFunctionalObjectPropertyAxiom</i>	An object property functionality axiom <i>FunctionalObjectProperty</i> (OPE) states that
<i>OWLAsymmetricObjectPropertyAxiom</i>	An object property asymmetry axiom <i>AsymmetricObjectProperty</i> (OPE) states that
<i>OWLInverseFunctionalObjectPropertyAxiom</i>	An object property inverse functionality axiom <i>InverseFunctionalObjectProperty</i> (OPE)
<i>OWLIrreflexiveObjectPropertyAxiom</i>	An object property irreflexivity axiom <i>IrreflexiveObjectProperty</i> (OPE) states that the

continues on next page

Table 2 – continued from previous page

<i>OWLReflexiveObjectPropertyAxiom</i>	An object property reflexivity axiom <i>ReflexiveObjectProperty</i> (OPE) states that the
<i>OWLSymmetricObjectPropertyAxiom</i>	An object property symmetry axiom <i>SymmetricObjectProperty</i> (OPE) states that
<i>OWLTransitiveObjectPropertyAxiom</i>	An object property transitivity axiom <i>TransitiveObjectProperty</i> (OPE) states that the
<i>OWLDataPropertyCharacteristicAxiom</i>	Base interface for Functional data property axiom.
<i>OWLFunctionalDataPropertyAxiom</i>	A data property functionality axiom <i>FunctionalDataProperty</i> (DPE) states that
<i>OWLPropertyDomainAxiom</i>	Base class for Property Domain axioms.
<i>OWLPropertyRangeAxiom</i>	Base class for Property Range axioms.
<i>OWLObjectPropertyDomainAxiom</i>	An object property domain axiom <i>ObjectPropertyDomain</i> (OPE CE) states that the domain of the
<i>OWLDataPropertyDomainAxiom</i>	A data property domain axiom <i>DataPropertyDomain</i> (DPE CE) states that the domain of the
<i>OWLObjectPropertyRangeAxiom</i>	An object property range axiom <i>ObjectPropertyRange</i> (OPE CE) states that the range of the object property
<i>OWLDataPropertyRangeAxiom</i>	A data property range axiom <i>DataPropertyRange</i> (DPE DR) states that the range of the data property

Module Contents

class owlapy.owl_axiom.**OWLAxiom** (*annotations: Iterable[OWLAxiom] | None = None*)

Bases: *owlapy.owl_object.OWLObject*

Represents Axioms in the OWL 2 Specification.

An OWL ontology contains a set of axioms. These axioms can be annotation axioms, declaration axioms, imports axioms or logical axioms.

__slots__ = **'_annotations'**

annotations () → List[OWLAxiom] | None

is_annotated () → bool

is_logical_axiom () → bool

is_annotation_axiom () → bool

class owlapy.owl_axiom.**OWLLogicalAxiom** (*annotations: Iterable[OWLAxiom] | None = None*)

Bases: *OWLAxiom*

A base interface of all axioms that affect the logical meaning of an ontology. This excludes declaration axioms (including imports declarations) and annotation axioms.

__slots__ = **()**

is_logical_axiom () → bool

class owlapy.owl_axiom.**OWLPropertyAxiom** (*annotations: Iterable[OWLAxiom] | None = None*)

Bases: *OWLLogicalAxiom*

The base interface for property axioms.

```

__slots__ = ()

class owlapy.owl_axiom.OWLObjectPropertyAxiom(
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLPropertyAxiom
    The base interface for object property axioms.

__slots__ = ()

class owlapy.owl_axiom.OWLDataPropertyAxiom(
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLPropertyAxiom
    The base interface for data property axioms.

__slots__ = ()

class owlapy.owl_axiom.OWLIndividualAxiom(
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLLogicalAxiom
    The base interface for individual axioms.

__slots__ = ()

class owlapy.owl_axiom.OWLClassAxiom(annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLLogicalAxiom
    The base interface for class axioms.

__slots__ = ()

class owlapy.owl_axiom.OWLDeclarationAxiom(entity: owlapy.owl_object.OWLEntity,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLAxiom
    Represents a Declaration axiom in the OWL 2 Specification. A declaration axiom declares an entity in an ontology.
    It doesn't affect the logical meaning of the ontology.

__slots__ = '_entity'

get_entity() → owlapy.owl_object.OWLEntity

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLDatatypeDefinitionAxiom(
    datatype: owlapy.owl_datatype.OWLDatatype, datarange: owlapy.owl_datatype.OWLDataRange,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLLogicalAxiom
    A datatype definition DatatypeDefinition( DT DR ) defines a new datatype DT as being semantically equivalent to
    the data range DR; the latter must be a unary data range. This axiom allows one to use the defined datatype DT as

```

a synonym for DR — that is, in any expression in the ontology containing such an axiom, DT can be replaced with DR without affecting the meaning of the ontology.

(https://www.w3.org/TR/owl2-syntax/#Datatype_Definitions)

```
__slots__ = ('_datatype', '_datarange')
```

```
get_datatype() → owlapy.owl_datatype.OWLDatatype
```

```
get_datarange() → owlapy.owl_datatype.OWLDataRange
```

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
__repr__()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLHasKeyAxiom(
    class_expression: owlapy.class_expression.OWLClassExpression,
    property_expressions: List[owlapy.owl_property.OWLPropertyExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLLogicalAxiom*, *owlapy.meta_classes.HasOperands[owlapy.owl_property.OWLPropertyExpression]*

A key axiom `HasKey(CE (OPE1 ... OPEm) (DPE1 ... DPEn))` states that each (named) instance of the class expression CE is uniquely identified by the object property expressions OPEi and/or the data property expressions DPEj — that is, no two distinct (named) instances of CE can coincide on the values of all object property expressions OPEi and all data property expressions DPEj. In each such axiom in an OWL ontology, m or n (or both) must be larger than zero. A key axiom of the form `HasKey(owl:Thing (OPE))` is similar to the axiom `InverseFunctionalObjectProperty(OPE)`, the main differences being that the former axiom is applicable only to individuals that are explicitly named in an ontology, while the latter axiom is also applicable to anonymous individuals and individuals whose existence is implied by existential quantification.

(<https://www.w3.org/TR/owl2-syntax/#Keys>)

```
__slots__ = ('_class_expression', '_property_expressions')
```

```
get_class_expression() → owlapy.class_expression.OWLClassExpression
```

```
get_property_expressions() → List[owlapy.owl_property.OWLPropertyExpression]
```

```
operands() → Iterable[owlapy.owl_property.OWLPropertyExpression]
```

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
__repr__()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLNaryAxiom (annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: Generic[_C], OWLAxiom

Represents an axiom that contains two or more operands that could also be represented with multiple pairwise axioms.

Parameters

_C – Class of contained objects.

```
__slots__ = ()
```

```
abstract as_pairwise_axioms () → Iterable[OWLNaryAxiom[_C]]
```

```
class owlapy.owl_axiom.OWLNaryClassAxiom (
    class_expressions: List[owlapy.class_expression.OWLClassExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: OWLClassAxiom, OWLNaryAxiom[owlapy.class_expression.OWLClassExpression]

Represents an axiom that contains two or more operands that could also be represented with multiple pairwise axioms.

```
__slots__ = '_class_expressions'
```

```
class_expressions () → Iterable[owlapy.class_expression.OWLClassExpression]
```

Gets all of the top level class expressions that appear in this axiom.

Returns

Sorted stream of class expressions that appear in the axiom.

```
as_pairwise_axioms () → Iterable[OWLNaryClassAxiom]
```

Gets this axiom as a set of pairwise axioms; if the axiom contains only two operands, the axiom itself is returned unchanged, including its annotations.

Returns

This axiom as a set of pairwise axioms.

```
__eq__ (other)
```

Return self==value.

```
__hash__ ()
```

Return hash(self).

```
__repr__ ()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLEquivalentClassesAxiom (
    class_expressions: List[owlapy.class_expression.OWLClassExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: OWLNaryClassAxiom

An equivalent classes axiom EquivalentClasses(CE1 ... CE_n) states that all of the class expressions CE_i, 1 ≤ i ≤ n, are semantically equivalent to each other. This axiom allows one to use each CE_i as a synonym for each CE_j — that is, in any expression in the ontology containing such an axiom, CE_i can be replaced with CE_j without affecting the meaning of the ontology.

(https://www.w3.org/TR/owl2-syntax/#Equivalent_Classes)

```
__slots__ = ()
```

```
contains_named_equivalent_class () → bool
```

```

contains_owl_nothing() → bool

contains_owl_thing() → bool

named_classes() → Iterable[owlapy.class_expression.OWLClass]

```

class owlapy.owl_axiom.OWLDisjointClassesAxiom(
class_expressions: List[owlapy.class_expression.OWLClassExpression],
annotations: Iterable[OWLAnnotation] | None = None)

Bases: *OWLNaryClassAxiom*

A disjoint classes axiom DisjointClasses(CE1 ... CE_n) states that all of the class expressions CE_i, 1 ≤ i ≤ n, are pairwise disjoint; that is, no individual can be at the same time an instance of both CE_i and CE_j for i ≠ j.

(https://www.w3.org/TR/owl2-syntax/#Disjoint_Classes)

```

__slots__ = ()

```

class owlapy.owl_axiom.OWLNaryIndividualAxiom(
individuals: List[owlapy.owl_individual.OWLIndividual],
annotations: Iterable[OWLAnnotation] | None = None)

Bases: *OWLIndividualAxiom, OWLNaryAxiom[owlapy.owl_individual.OWLIndividual]*

Represents an axiom that contains two or more operands that could also be represented with multiple pairwise individual axioms.

```

__slots__ = '_individuals'

```

individuals() → Iterable[owlapy.owl_individual.OWLIndividual]

Get the individuals.

Returns
Generator containing the individuals.

as_pairwise_axioms() → Iterable[OWLNaryIndividualAxiom]

__eq__(other)
Return self==value.

__hash__()
Return hash(self).

__repr__()
Return repr(self).

class owlapy.owl_axiom.OWLDifferentIndividualsAxiom(
individuals: List[owlapy.owl_individual.OWLIndividual],
annotations: Iterable[OWLAnnotation] | None = None)

Bases: *OWLNaryIndividualAxiom*

An individual inequality axiom DifferentIndividuals(a1 ... a_n) states that all of the individuals a_i, 1 ≤ i ≤ n, are different from each other; that is, no individuals a_i and a_j with i ≠ j can be derived to be equal. This axiom can be used to axiomatize the unique name assumption — the assumption that all different individual names denote different individuals. (https://www.w3.org/TR/owl2-syntax/#Individual_Inequality)

```

__slots__ = ()

```

```
class owlapy.owl_axiom.OWLSameIndividualAxiom(
    individuals: List[owlapy.owl_individual.OWLIndividual],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLNaryIndividualAxiom*

An individual equality axiom SameIndividual($a_1 \dots a_n$) states that all of the individuals a_i , $1 \leq i \leq n$, are equal to each other. This axiom allows one to use each a_i as a synonym for each a_j — that is, in any expression in the ontology containing such an axiom, a_i can be replaced with a_j without affecting the meaning of the ontology.

(https://www.w3.org/TR/owl2-syntax/#Individual_Equality)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLNaryPropertyAxiom(properties: List[_P],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *Generic[_P]*, *OWLPropertyAxiom*, *OWLNaryAxiom[_P]*

Represents an axiom that contains two or more operands that could also be represented with multiple pairwise property axioms.

```
__slots__ = '_properties'
```

```
properties() → Iterable[_P]
```

Get all the properties that appear in the axiom.

Returns

Generator containing the properties.

```
as_pairwise_axioms() → Iterable[OWLNaryPropertyAxiom]
```

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
__repr__()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLEquivalentObjectPropertiesAxiom(
    properties: List[owlapy.owl_property.OWLObjectPropertyExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLNaryPropertyAxiom[owlapy.owl_property.OWLObjectPropertyExpression]*, *OWLObjectPropertyAxiom*

An equivalent object properties axiom EquivalentObjectProperties($OPE_1 \dots OPE_n$) states that all of the object property expressions OPE_i , $1 \leq i \leq n$, are semantically equivalent to each other. This axiom allows one to use each OPE_i as a synonym for each OPE_j — that is, in any expression in the ontology containing such an axiom, OPE_i can be replaced with OPE_j without affecting the meaning of the ontology.

(https://www.w3.org/TR/owl2-syntax/#Equivalent_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLDisjointObjectPropertiesAxiom(
    properties: List[owlapy.owl_property.OWLObjectPropertyExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLNaryPropertyAxiom[owlapy.owl_property.OWLObjectPropertyExpression]*, *OWLObjectPropertyAxiom*

A disjoint object properties axiom `DisjointObjectProperties(OPE1 ... OPEn)` states that all of the object property expressions `OPEi`, $1 \leq i \leq n$, are pairwise disjoint; that is, no individual `x` can be connected to an individual `y` by both `OPEi` and `OPEj` for $i \neq j$.

(https://www.w3.org/TR/owl2-syntax/#Disjoint_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLInverseObjectPropertiesAxiom(
    first: owlapy.owl_property.OWLObjectPropertyExpression,
    second: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
Bases: OWLNaryPropertyAxiom[owlapy.owl_property.OWLObjectPropertyExpression],
        OWLObjectPropertyAxiom
```

An inverse object properties axiom `InverseObjectProperties(OPE1 OPE2)` states that the object property expression `OPE1` is an inverse of the object property expression `OPE2`. Thus, if an individual `x` is connected by `OPE1` to an individual `y`, then `y` is also connected by `OPE2` to `x`, and vice versa.

(https://www.w3.org/TR/owl2-syntax/#Inverse_Object_Properties_2)

```
__slots__ = ('_first', '_second')
```

```
get_first_property() → owlapy.owl_property.OWLObjectPropertyExpression
```

```
get_second_property() → owlapy.owl_property.OWLObjectPropertyExpression
```

```
__repr__()
```

Return `repr(self)`.

```
class owlapy.owl_axiom.OWLEquivalentDataPropertiesAxiom(
    properties: List[owlapy.owl_property.OWLDataPropertyExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
Bases: OWLNaryPropertyAxiom[owlapy.owl_property.OWLDataPropertyExpression],
        OWLDataPropertyAxiom
```

An equivalent data properties axiom `EquivalentDataProperties(DPE1 ... DPEn)` states that all the data property expressions `DPEi`, $1 \leq i \leq n$, are semantically equivalent to each other. This axiom allows one to use each `DPEi` as a synonym for each `DPEj` — that is, in any expression in the ontology containing such an axiom, `DPEi` can be replaced with `DPEj` without affecting the meaning of the ontology.

(https://www.w3.org/TR/owl2-syntax/#Equivalent_Data_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLDisjointDataPropertiesAxiom(
    properties: List[owlapy.owl_property.OWLDataPropertyExpression],
    annotations: Iterable[OWLAnnotation] | None = None)
Bases: OWLNaryPropertyAxiom[owlapy.owl_property.OWLDataPropertyExpression],
        OWLDataPropertyAxiom
```

A disjoint data properties axiom `DisjointDataProperties(DPE1 ... DPEn)` states that all of the data property expressions `DPEi`, $1 \leq i \leq n$, are pairwise disjoint; that is, no individual `x` can be connected to a literal `y` by both

`DPEi` and `DPEj` for $i \neq j$.

(https://www.w3.org/TR/owl2-syntax/#Disjoint_Data_Properties)

```
__slots__ = ()
```



```

class owlapy.owl_axiom.OWLSubClassOfAxiom (
    sub_class: owlapy.class_expression.OWLClassExpression,
    super_class: owlapy.class_expression.OWLClassExpression,
    annotations: Iterable[OWLAnnotation] | None = None)

```

Bases: *OWLClassAxiom*

A subclass axiom SubClassOf(CE1 CE2) states that the class expression CE1 is a subclass of the class expression CE2. Roughly speaking, this states that CE1 is more specific than CE2. Subclass axioms are a fundamental type of axioms in OWL 2 and can be used to construct a class hierarchy. Other kinds of class expression axiom can be seen as syntactic shortcuts for one or more subclass axioms.

(https://www.w3.org/TR/owl2-syntax/#Subclass_Axioms)

```

__slots__ = ('_sub_class', '_super_class')

```

```

get_sub_class () → owlapy.class_expression.OWLClassExpression

```

```

get_super_class () → owlapy.class_expression.OWLClassExpression

```

```

__eq__ (other)

```

Return self==value.

```

__hash__ ()

```

Return hash(self).

```

__repr__ ()

```

Return repr(self).

```

class owlapy.owl_axiom.OWLDisjointUnionAxiom (cls_: owlapy.class_expression.OWLClass,
    class_expressions: List[owlapy.class_expression.OWLClassExpression],
    annotations: Iterable[OWLAnnotation] | None = None)

```

Bases: *OWLClassAxiom*

A disjoint union axiom DisjointUnion(C CE1 ... CEn) states that a class C is a disjoint union of the class expressions CE_i, 1 ≤ i ≤ n, all of which are pairwise disjoint. Such axioms are sometimes referred to as covering axioms, as they state that the extensions of all CE_i exactly cover the extension of C. Thus, each instance of C is an instance of exactly one CE_i, and each instance of CE_i is an instance of C.

(https://www.w3.org/TR/owl2-syntax/#Disjoint_Union_of_Class_Expressions)

```

__slots__ = ('_cls', '_class_expressions')

```

```

get_owl_class () → owlapy.class_expression.OWLClass

```

```

get_class_expressions () → Iterable[owlapy.class_expression.OWLClassExpression]

```

```

get_owl_equivalent_classes_axiom () → OWLEquivalentClassesAxiom

```

```

get_owl_disjoint_classes_axiom () → OWLDisjointClassesAxiom

```

```

__eq__ (other)

```

Return self==value.

```

__hash__ ()

```

Return hash(self).

```

__repr__ ()

```

Return repr(self).

```

class owlapy.owl_axiom.OWLClassAssertionAxiom(
    individual: owlapy.owl_individual.OWLIndividual,
    class_expression: owlapy.class_expression.OWLClassExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
Bases: OWLIndividualAxiom

A class assertion ClassAssertion( CE a ) states that the individual a is an instance of the class expression CE.
(https://www.w3.org/TR/owl2-syntax/#Class\_Assertions)

__slots__ = ('_individual', '_class_expression')

get_individual() → owlapy.owl_individual.OWLIndividual

get_class_expression() → owlapy.class_expression.OWLClassExpression

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLAnnotationProperty(iri: owlapy.iri.IRI | str)
Bases: owlapy.owl_property.OWLProperty

Represents an AnnotationProperty in the OWL 2 specification.

__slots__ = '_iri'

property iri: owlapy.iri.IRI
    Gets the IRI of this object.

    Returns
        The IRI of this object.

property str: str
    Gets the string representation of this object

    Returns
        The IRI as string

class owlapy.owl_axiom.OWLAnnotation(property: OWLAnnotationProperty,
    value: owlapy.owl_annotation.OWLAnnotationValue)
Bases: owlapy.owl_object.OWLObject

Annotations are used in the various types of annotation axioms, which bind annotations to their subjects (i.e. axioms
or declarations).

__slots__ = ('_property', '_value')

get_property() → OWLAnnotationProperty
    Gets the property that this annotation acts along.

    Returns
        The annotation property.

```

get_value () → *owlapy.owl_annotation.OWLAnnotationValue*

Gets the annotation value. The type of value will depend upon the type of the annotation e.g. whether the annotation is an OWLLiteral, an IRI or an OWLAnonymousIndividual.

Returns

The annotation value.

__eq__ (other)

Return self==value.

__hash__ ()

Return hash(self).

__repr__ ()

Return repr(self).

class owlapy.owl_axiom.OWLAnnotationAxiom (
 annotations: Iterable[OWLAnnotation] | None = None)

Bases: *OWLAxiom*

A super interface for annotation axioms.

__slots__ = ()

is_annotation_axiom () → bool

class owlapy.owl_axiom.OWLAnnotationAssertionAxiom (
 subject: owlapy.owl_annotation.OWLAnnotationSubject, annotation: OWLAnnotation,
 annotations: Iterable[OWLAnnotation] | None = None)

Bases: *OWLAnnotationAxiom*

An annotation assertion AnnotationAssertion(AP as av) states that the annotation subject as — an IRI or an anonymous individual — is annotated with the annotation property AP and the annotation value av.

(https://www.w3.org/TR/owl2-syntax/#Annotation_Assertion)

__slots__ = ('_subject', '_annotation')

get_subject () → *owlapy.owl_annotation.OWLAnnotationSubject*

Gets the subject of this object.

Returns

The subject.

get_property () → *OWLAnnotationProperty*

Gets the property.

Returns

The property.

get_value () → *owlapy.owl_annotation.OWLAnnotationValue*

Gets the annotation value. This is either an IRI, an OWLAnonymousIndividual or an OWLLiteral.

Returns

The annotation value.

__eq__ (other)

Return self==value.

__hash__ ()

Return hash(self).

```

__repr__ ()
    Return repr(self).

```

class owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom (
 sub_property: *OWLAnnotationProperty*, super_property: *OWLAnnotationProperty*,
 annotations: *Iterable[OWLAnnotation]* | None = None)

Bases: *OWLAnnotationAxiom*

An annotation subproperty axiom SubAnnotationPropertyOf(AP1 AP2) states that the annotation property AP1 is a subproperty of the annotation property AP2.

(https://www.w3.org/TR/owl2-syntax/#Annotation_Subproperties)

```

__slots__ = ('_sub_property', '_super_property')

get_sub_property () → OWLAnnotationProperty

get_super_property () → OWLAnnotationProperty

__eq__ (other)
    Return self==value.

__hash__ ()
    Return hash(self).

__repr__ ()
    Return repr(self).

```

class owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom (
 property_: *OWLAnnotationProperty*, domain: owlapy.iri.IRI,
 annotations: *Iterable[OWLAnnotation]* | None = None)

Bases: *OWLAnnotationAxiom*

An annotation property domain axiom AnnotationPropertyDomain(AP U) states that the domain of the annotation property AP is the IRI U.

(https://www.w3.org/TR/owl2-syntax/#Annotation_Property_Domain)

```

__slots__ = ('_property', '_domain')

get_property () → OWLAnnotationProperty

get_domain () → owlapy.iri.IRI

__eq__ (other)
    Return self==value.

__hash__ ()
    Return hash(self).

__repr__ ()
    Return repr(self).

```

class owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom (
 property_: *OWLAnnotationProperty*, range_: owlapy.iri.IRI,
 annotations: *Iterable[OWLAnnotation]* | None = None)

Bases: *OWLAnnotationAxiom*

An annotation property range axiom AnnotationPropertyRange(AP U) states that the range of the annotation property AP is the IRI U.

(https://www.w3.org/TR/owl2-syntax/#Annotation_Property_Range)

```

__slots__ = ('_property', '_range')

get_property() → OWLAnnotationProperty

get_range() → owlapy.iri.IRI

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLSubPropertyAxiom(sub_property: _P, super_property: _P,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: Generic[_P], OWLPropertyAxiom
    Base interface for object and data sub-property axioms.

__slots__ = ('_sub_property', '_super_property')

get_sub_property() → _P

get_super_property() → _P

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLSubObjectPropertyOfAxiom(
    sub_property: owlapy.owl_property.OWLObjectPropertyExpression,
    super_property: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLSubPropertyAxiom[owlapy.owl_property.OWLObjectPropertyExpression],
    OWLObjectPropertyAxiom

    Object subproperty axioms are analogous to subclass axioms, and they come in two forms. The basic form is
    SubObjectPropertyOf( OPE1 OPE2 ). This axiom states that the object property expression OPE1 is a subproperty
    of the object property expression OPE2 — that is, if an individual x is connected by OPE1 to an individual y, then
    x is also connected by OPE2 to y. The more complex form is SubObjectPropertyOf( ObjectPropertyChain( OPE1
    ... OPEn ) OPE ) but ObjectPropertyChain is not represented in owlapy yet.

    (https://www.w3.org/TR/owl2-syntax/#Object\_Subproperties)

__slots__ = ()

class owlapy.owl_axiom.OWLSubDataPropertyOfAxiom(
    sub_property: owlapy.owl_property.OWLDataPropertyExpression,
    super_property: owlapy.owl_property.OWLDataPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLSubPropertyAxiom[owlapy.owl_property.OWLDataPropertyExpression],
    OWLDataPropertyAxiom

```

A data subproperty axiom `SubDataPropertyOf(DPE1 DPE2)` states that the data property expression DPE1 is a subproperty of the data property expression DPE2 — that is, if an individual x is connected by DPE1 to a literal y, then x is connected by DPE2 to y as well.

(https://www.w3.org/TR/owl2-syntax/#Data_Subproperties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLPropertyAssertionAxiom(  
    subject: owlapy.owl_individual.OWLIndividual, property_: _P, object_: _C,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: `Generic[_P, _C]`, `OWLIndividualAxiom`

Base class for Property Assertion axioms.

```
__slots__ = ('_subject', '_property', '_object')
```

```
get_subject() → owlapy.owl_individual.OWLIndividual
```

```
get_property() → _P
```

```
get_object() → _C
```

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
__repr__()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLObjectPropertyAssertionAxiom(  
    subject: owlapy.owl_individual.OWLIndividual,  
    property_: owlapy.owl_property.OWLObjectPropertyExpression,  
    object_: owlapy.owl_individual.OWLIndividual,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: `OWLPropertyAssertionAxiom[owlapy.owl_property.OWLObjectPropertyExpression, owlapy.owl_individual.OWLIndividual]`

A positive object property assertion `ObjectPropertyAssertion(OPE a1 a2)` states that the individual a1 is connected by the object property expression OPE to the individual a2.

(https://www.w3.org/TR/owl2-syntax/#Positive_Object_Property_Assertions)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLNegativeObjectPropertyAssertionAxiom(  
    subject: owlapy.owl_individual.OWLIndividual,  
    property_: owlapy.owl_property.OWLObjectPropertyExpression,  
    object_: owlapy.owl_individual.OWLIndividual,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: `OWLPropertyAssertionAxiom[owlapy.owl_property.OWLObjectPropertyExpression, owlapy.owl_individual.OWLIndividual]`

A negative object property assertion `NegativeObjectPropertyAssertion(OPE a1 a2)` states that the individual a1 is not connected by the object property expression OPE to the individual a2.

(https://www.w3.org/TR/owl2-syntax/#Negative_Object_Property_Assertions)

```

__slots__ = ()

class owlapy.owl_axiom.OWLDataPropertyAssertionAxiom (
    subject: owlapy.owl_individual.OWLIndividual,
    property_: owlapy.owl_property.OWLDataPropertyExpression,
    object_: owlapy.owl_literal.OWLLiteral, annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLPropertyAssertionAxiom[owlapy.owl_property.OWLDataPropertyExpression,
    owlapy.owl_literal.OWLLiteral]

    A positive data property assertion DataPropertyAssertion( DPE a lt ) states that the individual a is connected by
    the data property expression DPE to the literal lt.

    (https://www.w3.org/TR/owl2-syntax/#Positive\_Data\_Property\_Assertions)

__slots__ = ()

class owlapy.owl_axiom.OWLNegativeDataPropertyAssertionAxiom (
    subject: owlapy.owl_individual.OWLIndividual,
    property_: owlapy.owl_property.OWLDataPropertyExpression,
    object_: owlapy.owl_literal.OWLLiteral, annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLPropertyAssertionAxiom[owlapy.owl_property.OWLDataPropertyExpression,
    owlapy.owl_literal.OWLLiteral]

    A negative data property assertion NegativeDataPropertyAssertion( DPE a lt ) states that the individual a is not
    connected by the data property expression DPE to the literal lt.

    (https://www.w3.org/TR/owl2-syntax/#Negative\_Data\_Property\_Assertions)

__slots__ = ()

class owlapy.owl_axiom.OWLUnaryPropertyAxiom (property_: _P,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: Generic[_P], OWLPropertyAxiom

    Base class for Unary property axiom.

__slots__ = '_property'

get_property() → _P

class owlapy.owl_axiom.OWLObjectPropertyCharacteristicAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
    Bases: OWLUnaryPropertyAxiom[owlapy.owl_property.OWLObjectPropertyExpression],
    OWLObjectPropertyAxiom

    Base interface for functional object property axiom.

__slots__ = ()

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

```

```
class owlapy.owl_axiom.OWLFunctionalObjectPropertyAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property functionality axiom *FunctionalObjectProperty*(OPE) states that the object property expression OPE is functional — that is, for each individual x, there can be at most one distinct individual y such that x is connected by OPE to y.

(https://www.w3.org/TR/owl2-syntax/#Functional_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLAsymmetricObjectPropertyAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property asymmetry axiom *AsymmetricObjectProperty*(OPE) states that the object property expression OPE is asymmetric — that is, if an individual x is connected by OPE to an individual y, then y cannot be connected by OPE to x.

(https://www.w3.org/TR/owl2-syntax/#Symmetric_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLInverseFunctionalObjectPropertyAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property inverse functionality axiom *InverseFunctionalObjectProperty*(OPE) states that the object property expression OPE is inverse-functional — that is, for each individual x, there can be at most one individual y such that y is connected by OPE with x.

(https://www.w3.org/TR/owl2-syntax/#Inverse-Functional_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLIrreflexiveObjectPropertyAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property irreflexivity axiom *IrreflexiveObjectProperty*(OPE) states that the object property expression OPE is irreflexive — that is, no individual is connected by OPE to itself.

(https://www.w3.org/TR/owl2-syntax/#Irreflexive_Object_Properties)

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLReflexiveObjectPropertyAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property reflexivity axiom *ReflexiveObjectProperty*(OPE) states that the object property expression OPE is reflexive — that is, each individual is connected by OPE to itself. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubClassOf*(owl:Thing *ObjectHasSelf*(OPE))

(https://www.w3.org/TR/owl2-syntax/#Reflexive_Object_Properties)


```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLSymmetricObjectPropertyAxiom(  
    property_: owlapy.owl_property.OWLObjectPropertyExpression,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property symmetry axiom *SymmetricObjectProperty*(OPE) states that the object property expression OPE is symmetric — that is, if an individual x is connected by OPE to an individual y, then y is also connected by OPE to x. Each such axiom can be seen as a syntactic shortcut for the following axiom:

SubObjectPropertyOf(OPE *ObjectInverseOf*(OPE))

https://www.w3.org/TR/owl2-syntax/#Symmetric_Object_Properties

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLTransitiveObjectPropertyAxiom(  
    property_: owlapy.owl_property.OWLObjectPropertyExpression,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLObjectPropertyCharacteristicAxiom*

An object property transitivity axiom *TransitiveObjectProperty*(OPE) states that the object property expression OPE is transitive — that is, if an individual x is connected by OPE to an individual y that is connected by OPE to an individual z, then x is also connected by OPE to z. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubObjectPropertyOf*(*ObjectPropertyChain*(OPE OPE) OPE)

https://www.w3.org/TR/owl2-syntax/#Transitive_Object_Properties

```
__slots__ = ()
```

```
class owlapy.owl_axiom.OWLDataPropertyCharacteristicAxiom(  
    property_: owlapy.owl_property.OWLDataPropertyExpression,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLUnaryPropertyAxiom*[*owlapy.owl_property.OWLDataPropertyExpression*],
OWLDataPropertyAxiom

Base interface for Functional data property axiom.

```
__slots__ = ()
```

```
__eq__(other)
```

Return self==value.

```
__hash__()
```

Return hash(self).

```
__repr__()
```

Return repr(self).

```
class owlapy.owl_axiom.OWLFunctionalDataPropertyAxiom(  
    property_: owlapy.owl_property.OWLDataPropertyExpression,  
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLDataPropertyCharacteristicAxiom*

A data property functionality axiom *FunctionalDataProperty*(DPE) states that the data property expression DPE is functional — that is, for each individual x, there can be at most one distinct literal y such that x is connected by DPE with y. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubClassOf*(*owl:Thing* *DataMaxCardinality*(1 DPE))

https://www.w3.org/TR/owl2-syntax/#Transitive_Object_Properties

```

__slots__ = ()

class owlapy.owl_axiom.OWLPropertyDomainAxiom (property_: _P,
        domain: owlapy.class_expression.OWLClassExpression,
        annotations: Iterable[OWLAnnotation] | None = None)
Bases: Generic[_P], OWLUnaryPropertyAxiom[_P]
Base class for Property Domain axioms.

__slots__ = '_domain'

get_domain() → owlapy.class_expression.OWLClassExpression

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLPropertyRangeAxiom (property_: _P, range_: _R,
        annotations: Iterable[OWLAnnotation] | None = None)
Bases: Generic[_P, _R], OWLUnaryPropertyAxiom[_P]
Base class for Property Range axioms.

__slots__ = '_range'

get_range() → _R

__eq__(other)
    Return self==value.

__hash__()
    Return hash(self).

__repr__()
    Return repr(self).

class owlapy.owl_axiom.OWLObjectPropertyDomainAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    domain: owlapy.class_expression.OWLClassExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
Bases: OWLPropertyDomainAxiom[owlapy.owl_property.OWLObjectPropertyExpression]

An object property domain axiom ObjectPropertyDomain( OPE CE ) states that the domain of the object property
expression OPE is the class expression CE — that is, if an individual x is connected by OPE with some other
individual, then x is an instance of CE. Each such axiom can be seen as a syntactic shortcut for the following
axiom: SubClassOf( ObjectSomeValuesFrom( OPE owl:Thing ) CE )

(https://www.w3.org/TR/owl2-syntax/#Object\_Property\_Domain)

__slots__ = ()

class owlapy.owl_axiom.OWLDataPropertyDomainAxiom (
    property_: owlapy.owl_property.OWLDataPropertyExpression,
    domain: owlapy.class_expression.OWLClassExpression,
    annotations: Iterable[OWLAnnotation] | None = None)

```

Bases: *OWLPropertyDomainAxiom*[*owlapy.owl_property.OWLDataPropertyExpression*]

A data property domain axiom *DataPropertyDomain*(DPE CE) states that the domain of the data property expression DPE is the class expression CE — that is, if an individual x is connected by DPE with some literal, then x is an instance of CE. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubClassOf*(*DataSomeValuesFrom*(DPE *rdfs:Literal*) CE)

(https://www.w3.org/TR/owl2-syntax/#Data_Property_Domain)

__slots__ = ()

```
class owlapy.owl_axiom.OWLObjectPropertyRangeAxiom (
    property_: owlapy.owl_property.OWLObjectPropertyExpression,
    range_: owlapy.class_expression.OWLClassExpression,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLPropertyRangeAxiom*[*owlapy.owl_property.OWLObjectPropertyExpression*, *owlapy.class_expression.OWLClassExpression*]

An object property range axiom *ObjectPropertyRange*(OPE CE) states that the range of the object property expression OPE is the class expression CE — that is, if some individual is connected by OPE with an individual x, then x is an instance of CE. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubClassOf*(*owl:Thing* *ObjectAllValuesFrom*(OPE CE))

(https://www.w3.org/TR/owl2-syntax/#Object_Property_Range)

__slots__ = ()

```
class owlapy.owl_axiom.OWLDataPropertyRangeAxiom (
    property_: owlapy.owl_property.OWLDataPropertyExpression,
    range_: owlapy.owl_datatype.OWLDataRange,
    annotations: Iterable[OWLAnnotation] | None = None)
```

Bases: *OWLPropertyRangeAxiom*[*owlapy.owl_property.OWLDataPropertyExpression*, *owlapy.owl_datatype.OWLDataRange*]

A data property range axiom *DataPropertyRange*(DPE DR) states that the range of the data property expression DPE is the data range DR — that is, if some individual is connected by DPE with a literal x, then x is in DR. The arity of DR must be one. Each such axiom can be seen as a syntactic shortcut for the following axiom: *SubClassOf*(*owl:Thing* *DataAllValuesFrom*(DPE DR))

(https://www.w3.org/TR/owl2-syntax/#Data_Property_Range)

__slots__ = ()

owlapy.owl_data_ranges

OWL Data Ranges

https://www.w3.org/TR/owl2-syntax/#Data_Ranges

DataRange := *Datatype* | *DataIntersectionOf* | *DataUnionOf* | *DataComplementOf* | *DataOneOf* | *DatatypeRestriction*

Classes

<i>OWLPropertyRange</i>	OWL Objects that can be the ranges of properties.
<i>OWLDataRange</i>	Represents a DataRange in the OWL 2 Specification.
<i>OWLNaryDataRange</i>	OWLNaryDataRange.
<i>OWLDataIntersectionOf</i>	An intersection data range <code>DataIntersectionOf(DR1 ... DRn)</code> contains all tuples of literals that are contained
<i>OWLDataUnionOf</i>	A union data range <code>DataUnionOf(DR1 ... DRn)</code> contains all tuples of literals that are contained in the at least
<i>OWLDataComplementOf</i>	A complement data range <code>DataComplementOf(DR)</code> contains all tuples of literals that are not contained in the

Module Contents

class owlapy.owl_data_ranges.OWLPropertyRange

Bases: *owlapy.owl_object.OWLObject*

OWL Objects that can be the ranges of properties.

class owlapy.owl_data_ranges.OWLDataRange

Bases: *OWLPropertyRange*

Represents a DataRange in the OWL 2 Specification.

class owlapy.owl_data_ranges.OWLNaryDataRange (*operands: Iterable[OWLDataRange]*)

Bases: *OWLDataRange*, *owlapy.meta_classes.HasOperands[OWLDataRange]*

OWLNaryDataRange.

__slots__ = ()

operands () → *Iterable[OWLDataRange]*

Gets the operands - e.g., the individuals in a sameAs axiom, or the classes in an equivalent classes axiom.

Returns

The operands.

__repr__ ()

Return repr(self).

__eq__ (*other*)

Return self==value.

__hash__ ()

Return hash(self).

class owlapy.owl_data_ranges.OWLDataIntersectionOf (
 operands: Iterable[OWLDataRange])

Bases: *OWLNaryDataRange*

An intersection data range `DataIntersectionOf(DR1 ... DRn)` contains all tuples of literals that are contained in each data range `DRi` for $1 \leq i \leq n$. All data ranges `DRi` must be of the same arity, and the resulting data range is of that arity as well.

(https://www.w3.org/TR/owl2-syntax/#Intersection_of_Data_Ranges)

```
__slots__ = '_operands'
```

```
type_index: Final = 4004
```

```
class owlapy.owl_data_ranges.OWLDataUnionOf (operands: Iterable[OWLDataRange])
```

Bases: *OWLNaryDataRange*

A union data range *DataUnionOf*(DR1 ... DRn) contains all tuples of literals that are contained in the at least one data range DRi for $1 \leq i \leq n$. All data ranges DRi must be of the same arity, and the resulting data range is of that arity as well.

(https://www.w3.org/TR/owl2-syntax/#Union_of_Data_Ranges)

```
__slots__ = '_operands'
```

```
type_index: Final = 4005
```

```
class owlapy.owl_data_ranges.OWLDataComplementOf (data_range: OWLDataRange)
```

Bases: *OWLDataRange*

A complement data range *DataComplementOf*(DR) contains all tuples of literals that are not contained in the data range DR. The resulting data range has the arity equal to the arity of DR.

(https://www.w3.org/TR/owl2-syntax/#Complement_of_Data_Ranges)

```
type_index: Final = 4002
```

```
get_data_range () → OWLDataRange
```

Returns

The wrapped data range.

```
__repr__ ()
```

Return repr(self).

```
__eq__ (other)
```

Return self==value.

```
__hash__ ()
```

Return hash(self).

owlapy.owl_datatype

OWL Datatype

Classes

OWLDatatype

Datatypes are entities that refer to sets of data values. Thus, datatypes are analogous to classes,

Module Contents

class owlapy.owl_datatype.**OWLDatatype** (*iri: owlapy.iri.IRI | owlapy.meta_classes.HasIRI*)

Bases: *owlapy.owl_object.OWLEntity*, *owlapy.owl_data_ranges.OWLDataRange*

Datatypes are entities that refer to sets of data values. Thus, datatypes are analogous to classes, the main difference being that the former contain data values such as strings and numbers, rather than individuals. Datatypes are a kind of data range, which allows them to be used in restrictions. Each data range is associated with an arity; for datatypes, the arity is always one. The built-in datatype `rdfs:Literal` denotes any set of data values that contains the union of the value spaces of all datatypes.

(<https://www.w3.org/TR/owl2-syntax/#Datatypes>)

__slots__ = `'_iri'`

type_index: `Final = 4001`

property iri: *owlapy.iri.IRI*

Gets the IRI of this object.

Returns

The IRI of this object.

property str: `str`

Gets the string representation of this object

Returns

The IRI as string

owlapy.owl_hierarchy

Classes representing hierarchy in OWL.

Classes

<i>AbstractHierarchy</i>	Representation of an abstract hierarchy which can be used for classes or properties.
<i>ClassHierarchy</i>	Representation of a class hierarchy.
<i>ObjectPropertyHierarchy</i>	Representation of an object property hierarchy.
<i>DatatypePropertyHierarchy</i>	Representation of a data property hierarchy.

Module Contents

class owlapy.owl_hierarchy.**AbstractHierarchy** (*factory: Type[_S],
hierarchy_down: Iterable[Tuple[_S, Iterable[_S]]]*)

class owlapy.owl_hierarchy.**AbstractHierarchy** (*factory: Type[_S],
reasoner: owlapy.owl_reasoner.OWLReasoner*)

Bases: `Generic[_S]`

Representation of an abstract hierarchy which can be used for classes or properties.

Parameters

- **hierarchy_down** – A downwards hierarchy given as a mapping of Entities to sub-entities.
- **reasoner** – Alternatively, a reasoner whose root_ontology is queried for entities.

`__slots__ = ('_Type', '_ent_set', '_parents_map', '_parents_map_trans', '_children_map', ...)`

`classmethod get_top_entity() → _S`

Abstractmethod

The most general entity in this hierarchy, which contains all the entities.

`classmethod get_bottom_entity() → _S`

Abstractmethod

The most specific entity in this hierarchy, which contains none of the entities.

`static restrict (hierarchy: _U, *, remove: Iterable[_S] = None, allow: Iterable[_S] = None) → _U`

Restrict a given hierarchy to a set of allowed/removed entities.

Parameters

- **hierarchy** – An existing Entity hierarchy to restrict.
- **remove** – Set of entities which should be ignored.
- **allow** – Set of entities which should be used.

Returns

The restricted hierarchy.

`restrict_and_copy (*, remove: Iterable[_S] = None, allow: Iterable[_S] = None) → _U`

Restrict this hierarchy.

See restrict for more info.

`parents (entity: _S, direct: bool = True) → Iterable[_S]`

Parents of an entity.

Parameters

- **entity** – Entity for which to query parent entities.
- **direct** – False to return transitive parents.

Returns

Super-entities.

`is_parent_of (a: _S, b: _S) → bool`

if A is a parent of B.

Note

A is always a parent of A.

`is_child_of (a: _S, b: _S) → bool`

If A is a child of B.

Note

A is always a child of A.

children (*entity*: *_S*, *direct*: *bool = True*) → *Iterable[_S]*

Children of an entity.

Parameters

- **entity** – Entity for which to query child entities.
- **direct** – False to return transitive children.

Returns

Sub-entities.

siblings (*entity*: *_S*) → *Iterable[_S]*

items () → *Iterable[_S]*

roots (*of*: *_S | None = None*) → *Iterable[_S]*

leaves (*of*: *_S | None = None*) → *Iterable[_S]*

__contains__ (*item*: *_S*) → *bool*

__len__ ()

```
class owlapy.owl_hierarchy.ClassHierarchy (hierarchy_down: Iterable[Tuple[owlapy.class_expression.OWLClass, Iterable[owlapy.class_expression.OWLClass]]])
```

```
class owlapy.owl_hierarchy.ClassHierarchy (reasoner: owlapy.owl_reasoner.OWLReasoner)  
    Bases: AbstractHierarchy[owlapy.class_expression.OWLClass]
```

Representation of a class hierarchy.

Parameters

- **hierarchy_down** – A downwards hierarchy given as a mapping of Class to sub-classes.
- **reasoner** – Alternatively, a reasoner whose root_ontology is queried for classes and sub-classes.

```
classmethod get_top_entity () → owlapy.class_expression.OWLClass
```

The most general entity in this hierarchy, which contains all the entities.

```
classmethod get_bottom_entity () → owlapy.class_expression.OWLClass
```

The most specific entity in this hierarchy, which contains none of the entities.

```
sub_classes (entity: owlapy.class_expression.OWLClass, direct: bool = True)  
    → Iterable[owlapy.class_expression.OWLClass]
```

```
super_classes (entity: owlapy.class_expression.OWLClass, direct: bool = True)  
    → Iterable[owlapy.class_expression.OWLClass]
```

```
is_subclass_of (subclass: owlapy.class_expression.OWLClass,  
               superclass: owlapy.class_expression.OWLClass) → bool
```

```
class owlapy.owl_hierarchy.ObjectPropertyHierarchy (hierarchy_down: Iterable[Tuple[owlapy.owl_property.OWLObjectProperty, Iterable[owlapy.owl_property.OWLObjectProperty]]])
```



```

class owlapy.owl_hierarchy.ObjectPropertyHierarchy (
    reasoner: owlapy.owl_reasoner.OWLReasoner)
    Bases: AbstractHierarchy[owlapy.owl_property.OWLObjectProperty]
    Representation of an objet property hierarchy.

    classmethod get_top_entity () → owlapy.owl_property.OWLObjectProperty
        The most general entity in this hierarchy, which contains all the entities.

    classmethod get_bottom_entity () → owlapy.owl_property.OWLObjectProperty
        The most specific entity in this hierarchy, which contains none of the entities.

    sub_object_properties (entity: owlapy.owl_property.OWLObjectProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLObjectProperty]

    super_object_properties (entity: owlapy.owl_property.OWLObjectProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLObjectProperty]

    more_general_roles (role: owlapy.owl_property.OWLObjectProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLObjectProperty]

    more_special_roles (role: owlapy.owl_property.OWLObjectProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLObjectProperty]

    is_sub_property_of (sub_property: owlapy.owl_property.OWLObjectProperty,
        super_property: owlapy.owl_property.OWLObjectProperty) → bool

    most_general_roles () → Iterable[owlapy.owl_property.OWLObjectProperty]

    most_special_roles () → Iterable[owlapy.owl_property.OWLObjectProperty]

class owlapy.owl_hierarchy.DatatypePropertyHierarchy (
    hierarchy_down: Iterable[Tuple[owlapy.owl_property.OWLDataProperty, Iterable[owlapy.owl_property.OWLDataProperty]]])

class owlapy.owl_hierarchy.DatatypePropertyHierarchy (
    reasoner: owlapy.owl_reasoner.OWLReasoner)
    Bases: AbstractHierarchy[owlapy.owl_property.OWLDataProperty]
    Representation of a data property hierarchy.

    classmethod get_top_entity () → owlapy.owl_property.OWLDataProperty
        The most general entity in this hierarchy, which contains all the entities.

    classmethod get_bottom_entity () → owlapy.owl_property.OWLDataProperty
        The most specific entity in this hierarchy, which contains none of the entities.

    sub_data_properties (entity: owlapy.owl_property.OWLDataProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLDataProperty]

    super_data_properties (entity: owlapy.owl_property.OWLDataProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLDataProperty]

    more_general_roles (role: owlapy.owl_property.OWLDataProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLDataProperty]

    more_special_roles (role: owlapy.owl_property.OWLDataProperty, direct: bool = True)
        → Iterable[owlapy.owl_property.OWLDataProperty]

    is_sub_property_of (sub_property: owlapy.owl_property.OWLDataProperty,
        super_property: owlapy.owl_property.OWLDataProperty) → bool

```

`most_general_roles ()` → `Iterable[owlapy.owl_property.OWLDataProperty]`

`most_special_roles ()` → `Iterable[owlapy.owl_property.OWLDataProperty]`

owlapy.owl_individual

OWL Individuals

Classes

<i>OWLIndividual</i>	Represents a named or anonymous individual.
<i>OWLNamedIndividual</i>	Named individuals are identified using an IRI. Since they are given an IRI, named individuals are entities.

Module Contents

class `owlapy.owl_individual.OWLIndividual`

Bases: `owlapy.owl_object.OWLObject`

Represents a named or anonymous individual.

`__slots__ = ()`

class `owlapy.owl_individual.OWLNamedIndividual (iri: owlapy.iri.IRI | str)`

Bases: `OWLIndividual`, `owlapy.owl_object.OWLEntity`

Named individuals are identified using an IRI. Since they are given an IRI, named individuals are entities. IRIs from the reserved vocabulary must not be used to identify named individuals in an OWL 2 DL ontology.

(https://www.w3.org/TR/owl2-syntax/#Named_Individuals)

`__slots__ = '_iri'`

`type_index: Final = 1005`

property `iri: owlapy.iri.IRI`

Gets the IRI of this object.

Returns

The IRI of this object.

property `str`

Gets the string representation of this object

Returns

The IRI as string

owlapy.owl_literal

OWL Literals

Attributes

<i>Literals</i>
<i>OWLTopObjectProperty</i>
<i>OWLBottomObjectProperty</i>
<i>OWLTopDataProperty</i>
<i>OWLBottomDataProperty</i>
<i>DoubleOWLDatatype</i>
<i>IntegerOWLDatatype</i>
<i>BooleanOWLDatatype</i>
<i>StringOWLDatatype</i>
<i>DateOWLDatatype</i>
<i>DateTimeOWLDatatype</i>
<i>DurationOWLDatatype</i>
<i>TopOWLDatatype</i>
<i>NUMERIC_DATATYPES</i>
<i>TIME_DATATYPES</i>

Classes

<i>OWLLiteral</i>	Literals represent data values such as particular strings or integers. They are analogous to typed RDF
-------------------	--

Module Contents

`owlapy.owl_literal.Literals`

class `owlapy.owl_literal.OWLLiteral`

Bases: `owlapy.owl_annotation.OWLAnnotationValue`

Literals represent data values such as particular strings or integers. They are analogous to typed RDF literals and can also be understood as individuals denoting data values. Each literal consists of a lexical form, which is a string, and a datatype.

(<https://www.w3.org/TR/owl2-syntax/#Literals>)

__slots__ = ()

type_index: **Final** = 4008

get_literal() → str

Gets the lexical value of this literal. Note that the language tag is not included.

Returns

The lexical value of this literal.

is_boolean() → bool

Whether this literal is typed as boolean.

parse_boolean() → bool

Parses the lexical value of this literal into a bool. The lexical value of this literal should be in the lexical space of the boolean datatype ("<http://www.w3.org/2001/XMLSchema#boolean>").

Returns

A bool value that is represented by this literal.

is_double() → bool

Whether this literal is typed as double.

parse_double() → float

Parses the lexical value of this literal into a double. The lexical value of this literal should be in the lexical space of the double datatype ("<http://www.w3.org/2001/XMLSchema#double>").

Returns

A double value that is represented by this literal.

is_integer() → bool

Whether this literal is typed as integer.

parse_integer() → int

Parses the lexical value of this literal into an integer. The lexical value of this literal should be in the lexical space of the integer datatype ("<http://www.w3.org/2001/XMLSchema#integer>").

Returns

An integer value that is represented by this literal.

is_string() → bool

Whether this literal is typed as string.

parse_string() → str

Parses the lexical value of this literal into a string. The lexical value of this literal should be in the lexical space of the string datatype ("<http://www.w3.org/2001/XMLSchema#string>").

Returns

A string value that is represented by this literal.

is_date() → bool

Whether this literal is typed as date.

parse_date() → datetime.date

Parses the lexical value of this literal into a date. The lexical value of this literal should be in the lexical space of the date datatype ("<http://www.w3.org/2001/XMLSchema#date>").

Returns

A date value that is represented by this literal.

is_datetime() → bool

Whether this literal is typed as dateTime.

parse_datetime() → datetime.datetime

Parses the lexical value of this literal into a datetime. The lexical value of this literal should be in the lexical space of the dateTime datatype ("<http://www.w3.org/2001/XMLSchema#dateTime>").

Returns

A datetime value that is represented by this literal.

is_duration() → bool

Whether this literal is typed as duration.

parse_duration() → pandas.Timedelta

Parses the lexical value of this literal into a Timedelta. The lexical value of this literal should be in the lexical space of the duration datatype ("<http://www.w3.org/2001/XMLSchema#duration>").

Returns

A Timedelta value that is represented by this literal.

is_literal() → bool

Returns

true if the annotation value is a literal

as_literal() → *OWLLiteral*

Returns

if the value is a literal, returns it. Return None otherwise

to_python() → Literals

abstract get_datatype() → *owlapy.owl_datatype.OWLDatatype*

Gets the OWLDatatype which types this literal.

Returns

The OWLDatatype that types this literal.

`owlapy.owl_literal.OWLTopObjectProperty: Final`

```

owlapy.owl_literal.OWLBottomObjectProperty: Final
owlapy.owl_literal.OWLTopDataProperty: Final
owlapy.owl_literal.OWLBottomDataProperty: Final
owlapy.owl_literal.DoubleOWLDatatype: Final
owlapy.owl_literal.IntegerOWLDatatype: Final
owlapy.owl_literal.BooleanOWLDatatype: Final
owlapy.owl_literal.StringOWLDatatype: Final
owlapy.owl_literal.DateOWLDatatype: Final
owlapy.owl_literal.DateTimeOWLDatatype: Final
owlapy.owl_literal.DurationOWLDatatype: Final
owlapy.owl_literal.TopOWLDatatype: Final
owlapy.owl_literal.NUMERIC_DATATYPES:
Final[Set[owlapy.owl_datatype.OWLDatatype]]
owlapy.owl_literal.TIME_DATATYPES: Final[Set[owlapy.owl_datatype.OWLDatatype]]

```

owlapy.owl_object

OWL Base classes

Classes

<i>OWLObject</i>	Base interface for OWL objects
<i>OWLObjectRenderer</i>	Abstract class with a render method to render an OWL Object into a string.
<i>OWLObjectParser</i>	Abstract class with a parse method to parse a string to an OWL Object.
<i>OWLNamedObject</i>	Represents a named object for example, class, property, ontology etc. - i.e. anything that has an
<i>OWLEntity</i>	Represents Entities in the OWL 2 Specification.

Module Contents

```

class owlapy.owl_object.OWLObject
    Base interface for OWL objects
    __slots__ = ()
    abstract __eq__(other)
        Return self==value.

```

```

abstract __hash__()
    Return hash(self).

abstract __repr__()
    Return repr(self).

is_anonymous() → bool

class owlapy.owl_object.OWLObjectRenderer
    Abstract class with a render method to render an OWL Object into a string.

    abstract set_short_form_provider(short_form_provider) → None
        Configure a short form provider that shortens the OWL objects during rendering.

        Parameters
            short_form_provider – Short form provider.

    abstract render(o: OWLObject) → str
        Render OWL Object to string.

        Parameters
            o – OWL Object.

        Returns
            String rendition of OWL object.

class owlapy.owl_object.OWLObjectParser
    Abstract class with a parse method to parse a string to an OWL Object.

    abstract parse_expression(expression_str: str) → OWLObject
        Parse a string to an OWL Object.

        Parameters
            expression_str(str) – Expression string.

        Returns
            The OWL Object which is represented by the string.

class owlapy.owl_object.OWLNamedObject
    Bases: OWLObject, owlapy.meta_classes.HasIRI
    Represents a named object for example, class, property, ontology etc. - i.e. anything that has an IRI as its name.

    __slots__ = ()

    __eq__(other)
        Return self==value.

    __lt__(other)
        Return self<value.

    __hash__()
        Return hash(self).

    __repr__()
        Return repr(self).

class owlapy.owl_object.OWLEntity
    Bases: OWLNamedObject
    Represents Entities in the OWL 2 Specification.

```

```

__slots__ = ()

to_string_id() → str

is_anonymous() → bool

```

owlapy.owl_ontology

OWL Ontology

Attributes

<i>logger</i>
<i>OWLREADY2_FACET_KEYS</i>

Classes

<i>OWLOntologyID</i>	An object that identifies an ontology. Since OWL 2, ontologies do not have to have an ontology IRI, or if they
<i>OWLOntology</i>	Represents an OWL 2 Ontology in the OWL 2 specification.
<i>Ontology</i>	Represents an OWL 2 Ontology in the OWL 2 specification.
<i>SyncOntology</i>	Represents an OWL 2 Ontology in the OWL 2 specification.
<i>ToOwlready2</i>	
<i>FromOwlready2</i>	Map owlready2 classes to owlapy model classes.

Module Contents

owlapy.owl_ontology.logger

```

class owlapy.owl_ontology.OWLOntologyID(ontology_iri: owlapy.iri.IRI | None = None,
                                           version_iri: owlapy.iri.IRI | None = None)

```

An object that identifies an ontology. Since OWL 2, ontologies do not have to have an ontology IRI, or if they have an ontology IRI then they can optionally also have a version IRI. Instances of this OWLOntologyID class bundle identifying information of an ontology together. If an ontology doesn't have an ontology IRI then we say that it is "anonymous".

```

__slots__ = ('_ontology_iri', '_version_iri')

```

```

get_ontology_iri() → owlapy.iri.IRI | None

```

Gets the ontology IRI.

Returns

Ontology IRI. If the ontology is anonymous, it will return None.

get_version_iri () → *owlapy.iri.IRI* | None

Gets the version IRI.

Returns

Version IRI or None.

get_default_document_iri () → *owlapy.iri.IRI* | None

Gets the IRI which is used as a default for the document that contain a representation of an ontology with this ID. This will be the version IRI if there is an ontology IRI and version IRI, else it will be the ontology IRI if there is an ontology IRI but no version IRI, else it will be None if there is no ontology IRI. See Ontology Documents in the OWL 2 Structural Specification.

Returns

the IRI that can be used as a default for an ontology document, or None.

is_anonymous () → bool

__repr__ ()

Return repr(self).

__eq__ (other)

Return self==value.

class owlapy.owl_ontology.OWLOntology

Bases: *owlapy.owl_object.OWLObject*

Represents an OWL 2 Ontology in the OWL 2 specification.

An OWLOntology consists of a possibly empty set of OWLAxioms and a possibly empty set of OWLAnnotations. An ontology can have an ontology IRI which can be used to identify the ontology. If it has an ontology IRI then it may also have an ontology version IRI. Since OWL 2, an ontology need not have an ontology IRI. (See the OWL 2 Structural Specification).

An ontology cannot be modified directly. Changes must be applied via its OWLOntologyManager.

__slots__ = ()

type_index: Final = 1

abstract classes_in_signature () → Iterable[*owlapy.class_expression.OWLClass*]

Gets the classes in the signature of this object.

Returns

Classes in the signature of this object.

abstract data_properties_in_signature ()

→ Iterable[*owlapy.owl_property.OWLDataProperty*]

Get the data properties that are in the signature of this object.

Returns

Data properties that are in the signature of this object.

abstract object_properties_in_signature ()

→ Iterable[*owlapy.owl_property.OWLObjectProperty*]

A convenience method that obtains the object properties that are in the signature of this object.

Returns

Object properties that are in the signature of this object.

```
abstract individuals_in_signature ()  
    → Iterable[owlapy.owl_individual.OWLNamedIndividual]
```

A convenience method that obtains the individuals that are in the signature of this object.

Returns

Individuals that are in the signature of this object.

```
abstract equivalent_classes_axioms (c: owlapy.class_expression.OWLClass)  
    → Iterable[owlapy.owl_axiom.OWLEquivalentClassesAxiom]
```

Gets all of the equivalent axioms in this ontology that contain the specified class as an operand.

Parameters

c – The class for which the EquivalentClasses axioms should be retrieved.

Returns

EquivalentClasses axioms contained in this ontology.

```
abstract general_class_axioms () → Iterable[owlapy.owl_axiom.OWLClassAxiom]
```

Get the general class axioms of this ontology. This includes SubClass axioms with a complex class expression

as the sub class and EquivalentClass axioms and DisjointClass axioms with only complex class expressions.

Returns

General class axioms contained in this ontology.

```
abstract data_property_domain_axioms (property: owlapy.owl_property.OWLDataProperty)  
    → Iterable[owlapy.owl_axiom.OWLDataPropertyDomainAxiom]
```

Gets the OWLDataPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

```
abstract data_property_range_axioms (property: owlapy.owl_property.OWLDataProperty)  
    → Iterable[owlapy.owl_axiom.OWLDataPropertyRangeAxiom]
```

Gets the OWLDataPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

```
abstract object_property_domain_axioms (  
    property: owlapy.owl_property.OWLObjectProperty)  
    → Iterable[owlapy.owl_axiom.OWLObjectPropertyDomainAxiom]
```

Gets the OWLObjectPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

```
abstract object_property_range_axioms (
    property: owlapy.owl_property.OWLObjectProperty)
    → Iterable[owlapy.owl_axiom.OWLObjectPropertyRangeAxiom]
```

Gets the OWLObjectPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

```
abstract get_owl_ontology_manager () → _M
```

Gets the manager that manages this ontology.

```
abstract get_ontology_id () → OWLOntologyID
```

Gets the OWLOntologyID belonging to this object.

Returns

The OWLOntologyID.

```
is_anonymous () → bool
```

Check whether this ontology does contain an IRI or not.

```
add_axiom (axiom: owlapy.owl_axiom.OWLAxiom | Iterable[owlapy.owl_axiom.OWLAxiom])
```

Add the specified axiom/axioms to the ontology.

Parameters

axiom – Can be a single axiom or a collection of axioms.

Returns

Nothing.

```
remove_axiom (axiom: owlapy.owl_axiom.OWLAxiom | Iterable[owlapy.owl_axiom.OWLAxiom])
```

Removes the specified axiom/axioms to the ontology.

Parameters

axiom – Can be a single axiom or a collection of axioms.

Returns

Nothing.

```
save (document_iri: owlapy.iri.IRI | None = None)
```

Saves this ontology, using its IRI to determine where/how the ontology should be saved.

Parameters

document_iri – Whether you want to save in a different location.

```
class owlapy.owl_ontology.Ontology (manager: _OM, ontology_iri: owlapy.iri.IRI, load: bool)
```

Bases: *OWLOntology*

Represents an OWL 2 Ontology in the OWL 2 specification.

An OWLOntology consists of a possibly empty set of OWLAxioms and a possibly empty set of OWLAnnotations. An ontology can have an ontology IRI which can be used to identify the ontology. If it has an ontology IRI then it may also have an ontology version IRI. Since OWL 2, an ontology need not have an ontology IRI. (See the OWL 2 Structural Specification).

An ontology cannot be modified directly. Changes must be applied via its OWLOntologyManager.

```
__slots__ = ('_manager', '_iri', '_world', '_onto')
```

onto

classes_in_signature () → Iterable[*owlapy.class_expression.OWLClass*]

Gets the classes in the signature of this object.

Returns

Classes in the signature of this object.

data_properties_in_signature () → Iterable[*owlapy.owl_property.OWLDataProperty*]

Get the data properties that are in the signature of this object.

Returns

Data properties that are in the signature of this object.

object_properties_in_signature () → Iterable[*owlapy.owl_property.OWLObjectProperty*]

A convenience method that obtains the object properties that are in the signature of this object.

Returns

Object properties that are in the signature of this object.

individuals_in_signature () → Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

A convenience method that obtains the individuals that are in the signature of this object.

Returns

Individuals that are in the signature of this object.

equivalent_classes_axioms (c: *owlapy.class_expression.OWLClass*)

→ Iterable[*owlapy.owl_axiom.OWLEquivalentClassesAxiom*]

Gets all of the equivalent axioms in this ontology that contain the specified class as an operand.

Parameters

c – The class for which the EquivalentClasses axioms should be retrieved.

Returns

EquivalentClasses axioms contained in this ontology.

general_class_axioms () → Iterable[*owlapy.owl_axiom.OWLClassAxiom*]

Get the general class axioms of this ontology. This includes SubClass axioms with a complex class expression

as the sub class and EquivalentClass axioms and DisjointClass axioms with only complex class expressions.

Returns

General class axioms contained in this ontology.

get_owl_ontology_manager () → *_OM*

Gets the manager that manages this ontology.

get_ontology_id () → *OWLOntologyID*

Gets the OWLOntologyID belonging to this object.

Returns

The OWLOntologyID.

data_property_domain_axioms (pe: *owlapy.owl_property.OWLDataProperty*)

→ Iterable[*owlapy.owl_axiom.OWLDataPropertyDomainAxiom*]

Gets the OWLDataPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

data_property_range_axioms (*pe: owlapy.owl_property.OWLDataProperty*)

→ Iterable[*owlapy.owl_axiom.OWLDataPropertyRangeAxiom*]

Gets the OWLDataPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

object_property_domain_axioms (*pe: owlapy.owl_property.OWLObjectProperty*)

→ Iterable[*owlapy.owl_axiom.OWLObjectPropertyDomainAxiom*]

Gets the OWLObjectPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

object_property_range_axioms (*pe: owlapy.owl_property.OWLObjectProperty*)

→ Iterable[*owlapy.owl_axiom.OWLObjectPropertyRangeAxiom*]

Gets the OWLObjectPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

add_axiom (*axiom: owlapy.owl_axiom.OWLAxiom | Iterable[owlapy.owl_axiom.OWLAxiom]*)

Add the specified axiom/axioms to the ontology.

Parameters

axiom – Can be a single axiom or a collection of axioms.

Returns

Nothing.

remove_axiom (*axiom: owlapy.owl_axiom.OWLAxiom | Iterable[owlapy.owl_axiom.OWLAxiom]*)

Removes the specified axiom/axioms to the ontology.

Parameters

axiom – Can be a single axiom or a collection of axioms.

Returns

Nothing.

save (*document_iri: owlapy.iri.IRI | None = None*)

Saves this ontology, using its IRI to determine where/how the ontology should be saved.

Parameters

document_iri – Whether you want to save in a different location.

get_original_iri ()

Get the IRI argument that was used to create this ontology.

__eq__ (*other*)
Return self==value.

__hash__ ()
Return hash(self).

__repr__ ()
Return repr(self).

class owlapy.owl_ontology.**SyncOntology** (*manager: _SM, path: owlapy.iri.IRI | str,*
new: bool = False)

Bases: *OWLontology*

Represents an OWL 2 Ontology in the OWL 2 specification.

An OWLontology consists of a possibly empty set of OWLAxioms and a possibly empty set of OWLAnnotations. An ontology can have an ontology IRI which can be used to identify the ontology. If it has an ontology IRI then it may also have an ontology version IRI. Since OWL 2, an ontology need not have an ontology IRI. (See the OWL 2 Structural Specification).

An ontology cannot be modified directly. Changes must be applied via its OWLontologyManager.

manager

path

new

mapper

classes_in_signature () → Iterable[*owlapy.class_expression.OWLClass*]

Gets the classes in the signature of this object.

Returns

Classes in the signature of this object.

data_properties_in_signature () → Iterable[*owlapy.owl_property.OWLDataProperty*]

Get the data properties that are in the signature of this object.

Returns

Data properties that are in the signature of this object.

object_properties_in_signature () → Iterable[*owlapy.owl_property.OWLObjectProperty*]

A convenience method that obtains the object properties that are in the signature of this object.

Returns

Object properties that are in the signature of this object.

individuals_in_signature () → Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

A convenience method that obtains the individuals that are in the signature of this object.

Returns

Individuals that are in the signature of this object.

equivalent_classes_axioms (*c: owlapy.class_expression.OWLClass*)
→ Iterable[*owlapy.owl_axiom.OWLEquivalentClassesAxiom*]

Gets all of the equivalent axioms in this ontology that contain the specified class as an operand.

Parameters

c – The class for which the EquivalentClasses axioms should be retrieved.

Returns

EquivalentClasses axioms contained in this ontology.

general_class_axioms () → Iterable[*owlapy.owl_axiom.OWLClassAxiom*]

Get the general class axioms of this ontology. This includes SubClass axioms with a complex class expression

as the sub class and EquivalentClass axioms and DisjointClass axioms with only complex class expressions.

Returns

General class axioms contained in this ontology.

data_property_domain_axioms (*property: owlapy.owl_property.OWLDataProperty*)
→ Iterable[*owlapy.owl_axiom.OWLDataPropertyDomainAxiom*]

Gets the OWLDataPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

data_property_range_axioms (*property: owlapy.owl_property.OWLDataProperty*)
→ Iterable[*owlapy.owl_axiom.OWLDataPropertyRangeAxiom*]

Gets the OWLDataPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

object_property_domain_axioms (*property: owlapy.owl_property.OWLObjectProperty*)
→ Iterable[*owlapy.owl_axiom.OWLObjectPropertyDomainAxiom*]

Gets the OWLObjectPropertyDomainAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

object_property_range_axioms (*property: owlapy.owl_property.OWLObjectProperty*)
→ Iterable[*owlapy.owl_axiom.OWLObjectPropertyRangeAxiom*]

Gets the OWLObjectPropertyRangeAxiom objects where the property is equal to the specified property.

Parameters

property – The property which is equal to the property of the retrieved axioms.

Returns

The axioms matching the search.

get_owl_ontology_manager () → *_M*

Gets the manager that manages this ontology.

get_owlapi_ontology ()

get_ontology_id() → *OWLOntologyID*

Gets the OWLOntologyID belonging to this object.

Returns

The OWLOntologyID.

__eq__(*other*)

Return self==value.

__hash__()

Return hash(self).

__repr__()

Return repr(self).

`owlapy.owl_ontology.OWLREADY2_FACET_KEYS`

class `owlapy.owl_ontology.ToOwlready2`(*world*: *owlready2.World*)

__slots__ = `'_world'`

abstract map_object(*o*: *owlapy.owl_object.OWLObject*)

Map owlapy object classes.

abstract map_concept(*o*: *owlapy.class_expression.OWLClassExpression*)

→ *owlready2.ClassConstruct* | *owlready2.ThingClass*

Map owlapy concept classes.

abstract map_datarange(*p*: *owlapy.owl_data_ranges.OWLDataRange*)

→ *owlready2.ClassConstruct* | *type*

Map owlapy data range classes.

class `owlapy.owl_ontology.FromOwlready2`

Map owlready2 classes to owlapy model classes.

__slots__ = `()`

abstract map_concept(*c*: *owlready2.ClassConstruct* | *owlready2.ThingClass*)

→ *owlapy.class_expression.OWLClassExpression*

Map concept classes.

abstract map_datarange(*p*: *owlready2.ClassConstruct*)

→ *owlapy.owl_data_ranges.OWLDataRange*

Map data range classes.

owlapy.owl_ontology_manager

Classes

<i>OWLOntologyChange</i>	Represents an ontology change.
<i>OWLOntologyManager</i>	An OWLOntologyManager manages a set of ontologies. It is the main point for creating, loading and accessing
<i>OWLImportsDeclaration</i>	Represents an import statement in an ontology.
<i>AddImport</i>	Represents an ontology change where an import statement is added to an ontology.
<i>OntologyManager</i>	An OWLOntologyManager manages a set of ontologies. It is the main point for creating, loading and accessing
<i>SyncOntologyManager</i>	

Module Contents

```
class owlapy.owl_ontology_manager.OWLOntologyChange (  
    ontology: owlapy.owl_ontology.OWLOntology)
```

Represents an ontology change.

```
__slots__ = ()
```

```
get_ontology () → owlapy.owl_ontology.OWLOntology
```

Gets the ontology that the change is/was applied to.

Returns

The ontology that the change is applicable to.

```
class owlapy.owl_ontology_manager.OWLOntologyManager
```

An OWLOntologyManager manages a set of ontologies. It is the main point for creating, loading and accessing ontologies.

```
abstract create_ontology (iri: owlapy.iri.IRI) → owlapy.owl_ontology.OWLOntology
```

Creates a new (empty) ontology that has the specified ontology IRI (and no version IRI).

Parameters

iri – The IRI of the ontology to be created.

Returns

The newly created ontology, or if an ontology with the specified IRI already exists then this existing ontology will be returned.

```
abstract load_ontology (iri: owlapy.iri.IRI) → owlapy.owl_ontology.OWLOntology
```

Loads an ontology that is assumed to have the specified ontology IRI as its IRI or version IRI. The ontology IRI will be mapped to an ontology document IRI.

Parameters

iri – The IRI that identifies the ontology. It is expected that the ontology will also have this IRI (although the OWL API should tolerate situations where this is not the case).

Returns

The OWLOntology representation of the ontology that was loaded.

```
abstract apply_change (change: OWLOntologyChange)
```

A convenience method that applies just one change to an ontology. When this method is used through an

OWLontologyManager implementation, the instance used should be the one that the ontology returns through the `get_owl_ontology_manager()` call.

Parameters

change – The change to be applied.

Raises

ChangeApplied.UNSUCCESSFULLY – if the change was not applied successfully.

class owlapy.owl_ontology_manager.**OWLImportsDeclaration** (*import_iri: owlapy.iri.IRI*)

Bases: *owlapy.meta_classes.HasIRI*

Represents an import statement in an ontology.

__slots__ = **'_iri'**

property **iri**: *owlapy.iri.IRI*

Gets the import IRI.

Returns

The import IRI that points to the ontology to be imported. The imported ontology might have this IRI as its ontology IRI but this is not mandated. For example, an ontology with a non-resolvable ontology IRI can be deployed at a resolvable URL.

property **str**: **str**

Gets the string representation of this object

Returns

The IRI as string

class owlapy.owl_ontology_manager.**AddImport** (*ontology: owlapy.owl_ontology.OWLontology*,
import_declaration: OWLImportsDeclaration)

Bases: *OWLontologyChange*

Represents an ontology change where an import statement is added to an ontology.

__slots__ = (**'_ont'**, **'_declaration'**)

get_import_declaration () → *OWLImportsDeclaration*

Gets the import declaration that the change pertains to.

Returns

The import declaration.

class owlapy.owl_ontology_manager.**OntologyManager** (*world_store=None*)

Bases: *OWLontologyManager*

An OWLontologyManager manages a set of ontologies. It is the main point for creating, loading and accessing ontologies.

__slots__ = **'_world'**

create_ontology (*iri: str | owlapy.iri.IRI = None*) → *owlapy.owl_ontology.Ontology*

Creates a new (empty) ontology that that has the specified ontology IRI (and no version IRI).

Parameters

iri – The IRI of the ontology to be created.

Returns

The newly created ontology, or if an ontology with the specified IRI already exists then this existing ontology will be returned.

load_ontology (*iri*: *str* | *owlapy.iri.IRI* = *None*) → *owlapy.owl_ontology.Ontology*

Loads an ontology that is assumed to have the specified ontology IRI as its IRI or version IRI. The ontology IRI will be mapped to an ontology document IRI.

Parameters

iri – The IRI that identifies the ontology. It is expected that the ontology will also have this IRI (although the OWL API should tolerate situations where this is not the case).

Returns

The OWLOntology representation of the ontology that was loaded.

apply_change (*change*: *OWLOntologyChange*)

A convenience method that applies just one change to an ontology. When this method is used through an OWLOntologyManager implementation, the instance used should be the one that the ontology returns through the get_owl_ontology_manager() call.

Parameters

change – The change to be applied.

Raises

ChangeApplied.UNSUCCESSFULLY – if the change was not applied successfully.

save_world ()

Saves the actual state of the quadstore in the SQLite3 file.

class owlapy.owl_ontology_manager.**SyncOntologyManager**

owlapi_manager

create_ontology (*iri*: *owlapy.iri.IRI*) → *owlapy.owl_ontology.SyncOntology*

load_ontology (*path*: *owlapy.iri.IRI* | *str*) → *owlapy.owl_ontology.SyncOntology*

get_owlapi_manager ()

owlapy.owl_property

OWL Properties

Classes

<i>OWLPropertyExpression</i>	Represents a property or possibly the inverse of a property.
<i>OWLObjectPropertyExpression</i>	A high level interface to describe different types of object properties.
<i>OWLDataPropertyExpression</i>	A high level interface to describe different types of data properties.
<i>OWLProperty</i>	A base class for properties that aren't expression i.e. named properties. By definition, properties
<i>OWLObjectProperty</i>	Represents an Object Property in the OWL 2 Specification. Object properties connect pairs of individuals.
<i>OWLObjectInverseOf</i>	Represents the inverse of a property expression (ObjectInverseOf). An inverse object property expression
<i>OWLDataProperty</i>	Represents a Data Property in the OWL 2 Specification. Data properties connect individuals with literals.

Module Contents

class owlapy.owl_property.OWLPropertyExpression

Bases: *owlapy.owl_object.OWLObject*

Represents a property or possibly the inverse of a property.

__slots__ = ()

is_data_property_expression() → bool

Returns

True if this is a data property.

is_object_property_expression() → bool

Returns

True if this is an object property.

is_owl_top_object_property() → bool

Determines if this is the owl:topObjectProperty.

Returns

topObjectProperty.

Return type

True if this property is the owl

is_owl_top_data_property() → bool

Determines if this is the owl:topDataProperty.

Returns

topDataProperty.

Return type

True if this property is the owl

class owlapy.owl_property.OWLObjectPropertyExpression

Bases: *OWLPropertyExpression*

A high level interface to describe different types of object properties.

__slots__ = ()

abstract get_inverse_property() → *OWLObjectPropertyExpression*

Obtains the property that corresponds to the inverse of this property.

Returns

The inverse of this property. Note that this property will not necessarily be in the simplest form.

abstract get_named_property() → *OWLObjectProperty*

Get the named object property used in this property expression.

Returns

P if this expression is either inv(P) or P.

is_object_property_expression() → bool

Returns

True if this is an object property.

```

class owlapy.owl_property.OWLDataPropertyExpression
    Bases: OWLPropertyExpression
    A high level interface to describe different types of data properties.
    __slots__ = ()
    is_data_property_expression()

        Returns
            True if this is a data property.

class owlapy.owl_property.OWLProperty(iri: owlapy.iri.IRI | str)
    Bases: OWLPropertyExpression, owlapy.owl_object.OWLEntity
    A base class for properties that aren't expression i.e. named properties. By definition, properties are either data
    properties or object properties.
    __slots__ = '_iri'
    property str: str
        Gets the string representation of this object
        Returns
            The IRI as string
    property iri: owlapy.iri.IRI
        Gets the IRI of this object.
        Returns
            The IRI of this object.

class owlapy.owl_property.OWLObjectProperty(iri: owlapy.iri.IRI | str)
    Bases: OWLObjectPropertyExpression, OWLProperty
    Represents an Object Property in the OWL 2 Specification. Object properties connect pairs of individuals.
    (https://www.w3.org/TR/owl2-syntax/#Object\_Properties)
    __slots__ = '_iri'
    type_index: Final = 1002
    get_named_property() → OWLObjectProperty
        Get the named object property used in this property expression.
        Returns
            P if this expression is either inv(P) or P.
    get_inverse_property() → OWLObjectInverseOf
        Obtains the property that corresponds to the inverse of this property.
        Returns
            The inverse of this property. Note that this property will not necessarily be in the simplest form.
    is_owl_top_object_property() → bool
        Determines if this is the owl:topObjectProperty.
        Returns
            topObjectProperty.
        Return type
            True if this property is the owl

```

```
class owlapy.owl_property.OWLObjectInverseOf (property: OWLObjectProperty)
```

Bases: *OWLObjectPropertyExpression*

Represents the inverse of a property expression (ObjectInverseOf). An inverse object property expression ObjectInverseOf(P) connects an individual I1 with I2 if and only if the object property P connects I2 with I1. This can be used to refer to the inverse of a property, without actually naming the property. For example, consider the property hasPart, the inverse property of hasPart (isPartOf) can be referred to using this interface inverseOf(hasPart), which can be used in restrictions e.g. inverseOf(hasPart) some Car refers to the set of things that are part of at least one car.

(https://www.w3.org/TR/owl2-syntax/#Inverse_Object_Properties)

```
__slots__ = '_inverse_property'
```

```
type_index: Final = 1003
```

```
get_inverse () → OWLObjectProperty
```

Gets the property expression that this is the inverse of.

Returns

The object property expression such that this object property expression is an inverse of it.

```
get_inverse_property () → OWLObjectProperty
```

Obtains the property that corresponds to the inverse of this property.

Returns

The inverse of this property. Note that this property will not necessarily be in the simplest form.

```
get_named_property () → OWLObjectProperty
```

Get the named object property used in this property expression.

Returns

P if this expression is either inv(P) or P.

```
__repr__ ()
```

Return repr(self).

```
__eq__ (other)
```

Return self==value.

```
__hash__ ()
```

Return hash(self).

```
class owlapy.owl_property.OWLDataProperty (iri: owlapy.iri.IRI | str)
```

Bases: *OWLDataPropertyExpression*, *OWLProperty*

Represents a Data Property in the OWL 2 Specification. Data properties connect individuals with literals. In some knowledge representation systems, functional data properties are called attributes.

(https://www.w3.org/TR/owl2-syntax/#Data_Properties)

```
__slots__ = '_iri'
```

```
type_index: Final = 1004
```

```
is_owl_top_data_property () → bool
```

Determines if this is the owl:topDataProperty.

Returns

topDataProperty.

Return type

True if this property is the owl

owlapy.owl_reasoner

OWL Reasoner

Attributes

<i>logger</i>

Classes

<i>OWLReasoner</i>	An OWLReasoner reasons over a set of axioms (the set of reasoner axioms) that is based on the imports closure of
<i>OWLReasonerEx</i>	Extra convenience methods for OWL Reasoners
<i>OntologyReasoner</i>	Extra convenience methods for OWL Reasoners
<i>FastInstanceCheckerReasoner</i>	Tries to check instances fast (but maybe incomplete).
<i>SyncReasoner</i>	

Module Contents

owlapy.owl_reasoner.logger

class owlapy.owl_reasoner.OWLReasoner (ontology: owlapy.owl_ontology.OWLOntology)

An OWLReasoner reasons over a set of axioms (the set of reasoner axioms) that is based on the imports closure of a particular ontology - the “root” ontology.

__slots__ = ()

abstract data_property_domains (pe: owlapy.owl_property.OWLDataProperty, direct: bool = False) → Iterable[owlapy.class_expression.OWLClassExpression]

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let N = equivalent_classes(DataSomeValuesFrom(pe rdfs:Literal)). If direct is True: then if N is not empty then the return value is N, else the return value is the result of super_classes(DataSomeValuesFrom(pe rdfs:Literal), true). If direct is False: then the result of

super_classes(DataSomeValuesFrom(pe rdfs:Literal), false) together with N if N is non-empty.
(Note, rdfs:Literal is the top datatype).

abstract object_property_domains (*pe*: owlapy.owl_property.OWLObjectProperty,
direct: bool = False) → Iterable[owlapy.class_expression.OWLClassExpression]

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let N = equivalent_classes(ObjectSomeValuesFrom(pe owl:Thing)). If direct is True: then if N is not empty then the return value is N, else the return value is the result of super_classes(ObjectSomeValuesFrom(pe owl:Thing), true). If direct is False: then the result of super_classes(ObjectSomeValuesFrom(pe owl:Thing), false) together with N if N is non-empty.

abstract object_property_ranges (*pe*: owlapy.owl_property.OWLObjectProperty,
direct: bool = False) → Iterable[owlapy.class_expression.OWLClassExpression]

Gets the class expressions that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns

Let N = equivalent_classes(ObjectSomeValuesFrom(ObjectInverseOf(pe) owl:Thing)). If direct is True: then if N is not empty then the return value is N, else the return value is the result of super_classes(ObjectSomeValuesFrom(ObjectInverseOf(pe) owl:Thing), true). If direct is False: then the result of super_classes(ObjectSomeValuesFrom(ObjectInverseOf(pe) owl:Thing), false) together with N if N is non-empty.

abstract equivalent_classes (*ce*: owlapy.class_expression.OWLClassExpression,
only_named: bool = True) → Iterable[owlapy.class_expression.OWLClassExpression]

Gets the class expressions that are equivalent to the specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose equivalent classes are to be retrieved.
- **only_named** – Whether to only retrieve named equivalent classes or also complex class expressions.

Returns

All class expressions C where the root ontology imports closure entails EquivalentClasses(ce C). If ce is not a class name (i.e. it is an anonymous class expression) and there are no such

classes C then there will be no result. If ce is unsatisfiable with respect to the set of reasoner axioms then owl:Nothing, i.e. the bottom node, will be returned.

abstract disjoint_classes (ce: *owlapy.class_expression.OWLClassExpression*,
only_named: bool = True) → Iterable[*owlapy.class_expression.OWLClassExpression*]

Gets the class expressions that are disjoint with specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose disjoint classes are to be retrieved.
- **only_named** – Whether to only retrieve named disjoint classes or also complex class expressions.

Returns

All class expressions D where the set of reasoner axioms entails EquivalentClasses(D ObjectComplementOf(ce)) or StrictSubClassOf(D ObjectComplementOf(ce)).

abstract different_individuals (ind: *owlapy.owl_individual.OWLNamedIndividual*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the individuals that are different from the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose different individuals are to be retrieved.

Returns

All individuals x where the set of reasoner axioms entails DifferentIndividuals(ind x).

abstract same_individuals (ind: *owlapy.owl_individual.OWLNamedIndividual*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the individuals that are the same as the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose same individuals are to be retrieved.

Returns

All individuals x where the root ontology imports closure entails SameIndividual(ind x).

abstract equivalent_object_properties (
op: *owlapy.owl_property.OWLObjectPropertyExpression*)
→ Iterable[*owlapy.owl_property.OWLObjectPropertyExpression*]

Gets the simplified object properties that are equivalent to the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose equivalent object properties are to be retrieved.

Returns

All simplified object properties e where the root ontology imports closure entails EquivalentObjectProperties(op e). If op is unsatisfiable with respect to the set of reasoner axioms then owl:bottomDataProperty will be returned.

abstract equivalent_data_properties (dp: *owlapy.owl_property.OWLDataProperty*)
→ Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the data properties that are equivalent to the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose equivalent data properties are to be retrieved.

Returns

All data properties e where the root ontology imports closure entails `EquivalentDataProperties(dp e)`. If dp is unsatisfiable with respect to the set of reasoner axioms then `owl:bottomDataProperty` will be returned.

abstract data_property_values (e : *owlapy.owl_object.OWLEntity*,
 pe : *owlapy.owl_property.OWLDataProperty*, $direct$: *bool = True*)
→ *Iterable[owlapy.owl_literal.OWLLiteral]*

Gets the data property values for the specified entity and data property expression.

Parameters

- **e** – The owl entity (usually an individual) that is the subject of the data property values.
- **pe** – The data property expression whose values are to be retrieved for the specified entity.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Note: Can be used to get values, for example, of ‘label’ property of owl entities such as classes and properties too (not only individuals).

Returns

A set of OWLLiterals containing literals such that for each literal l in the set, the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)`.

abstract object_property_values (ind : *owlapy.owl_individual.OWLNamedIndividual*,
 pe : *owlapy.owl_property.OWLObjectPropertyExpression*, $direct$: *bool = True*)
→ *Iterable[owlapy.owl_individual.OWLNamedIndividual]*

Gets the object property values for the specified individual and object property expression.

Parameters

- **ind** – The individual that is the subject of the object property values.
- **pe** – The object property expression whose values are to be retrieved for the specified individual.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Returns

The named individuals such that for each individual j , the set of reasoner axioms entails `ObjectPropertyAssertion(pe ind j)`.

abstract instances (ce : *owlapy.class_expression.OWLClassExpression*, $direct$: *bool = False*)
→ *Iterable[owlapy.owl_individual.OWLNamedIndividual]*

Gets the individuals which are instances of the specified class expression.

Parameters

- **ce** – The class expression whose instances are to be retrieved.
- **direct** – Specifies if the direct instances should be retrieved (True), or if all instances should be retrieved (False).

Returns

If **direct** is True, each named individual j where the set of reasoner axioms entails `DirectClassAssertion(ce, j)`. If **direct** is False, each named individual j where the set of reasoner axioms entails `ClassAssertion(ce, j)`. If ce is unsatisfiable with respect to the set of reasoner axioms then nothing returned.

abstract sub_classes (*ce: owlapy.class_expression.OWLClassExpression, direct: bool = False, only_named: bool = True*) → Iterable[*owlapy.class_expression.OWLClassExpression*]

Gets the set of named classes that are the strict (potentially direct) subclasses of the specified class expression with respect to the reasoner axioms.

Parameters

- **ce** – The class expression whose strict (direct) subclasses are to be retrieved.
- **direct** – Specifies if the direct subclasses should be retrieved (True) or if the all subclasses (descendant) classes should be retrieved (False).
- **only_named** – Whether to only retrieve named sub-classes or also complex class expressions.

Returns

If direct is True, each class C where reasoner axioms entails DirectSubClassOf(C, ce). If direct is False, each class C where reasoner axioms entails StrictSubClassOf(C, ce). If ce is equivalent to owl:Nothing then nothing will be returned.

abstract disjoint_object_properties (*op: owlapy.owl_property.OWLObjectPropertyExpression*) → Iterable[*owlapy.owl_property.OWLObjectPropertyExpression*]

Gets the simplified object properties that are disjoint with the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose disjoint object properties are to be retrieved.

Returns

All simplified object properties e where the root ontology imports closure entails EquivalentObjectProperties(e ObjectPropertyComplementOf(op)) or StrictSubObjectPropertyOf(e ObjectPropertyComplementOf(op)).

abstract disjoint_data_properties (*dp: owlapy.owl_property.OWLDataProperty*) → Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the data properties that are disjoint with the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose disjoint data properties are to be retrieved.

Returns

All data properties e where the root ontology imports closure entails EquivalentDataProperties(e DataPropertyComplementOf(dp)) or StrictSubDataPropertyOf(e DataPropertyComplementOf(dp)).

abstract sub_data_properties (*dp: owlapy.owl_property.OWLDataProperty, direct: bool = False*) → Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the set of named data properties that are the strict (potentially direct) subproperties of the specified data property expression with respect to the imports closure of the root ontology.

Parameters

- **dp** – The data property whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If `direct` is `True`, each property `P` where the set of reasoner axioms entails `DirectSubDataPropertyOf(P, pe)`. If `direct` is `False`, each property `P` where the set of reasoner axioms entails `StrictSubDataPropertyOf(P, pe)`. If `pe` is equivalent to `owl:bottomDataProperty` then nothing will be returned.

abstract super_data_properties (*dp: owlapy.owl_property.OWLDataProperty*,
direct: bool = False) → `Iterable[owlapy.owl_property.OWLDataProperty]`

Gets the stream of data properties that are the strict (potentially direct) super properties of the specified data property with respect to the imports closure of the root ontology.

Parameters

- **dp** (`OWLDataProperty`) – The data property whose super properties are to be retrieved.
- **direct** (`bool`) – Specifies if the direct super properties should be retrieved (`True`) or if the all super properties (ancestors) should be retrieved (`False`).

Returns

Iterable of super properties.

abstract sub_object_properties (*op: owlapy.owl_property.OWLObjectPropertyExpression*,
direct: bool = False) → `Iterable[owlapy.owl_property.OWLObjectPropertyExpression]`

Gets the stream of simplified object property expressions that are the strict (potentially direct) subproperties of the specified object property expression with respect to the imports closure of the root ontology.

Parameters

- **op** – The object property expression whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (`True`) or if the all subproperties (descendants) should be retrieved (`False`).

Returns

If `direct` is `True`, simplified object property expressions, such that for each simplified object property expression, `P`, the set of reasoner axioms entails `DirectSubObjectPropertyOf(P, pe)`. If `direct` is `False`, simplified object property expressions, such that for each simplified object property expression, `P`, the set of reasoner axioms entails `StrictSubObjectPropertyOf(P, pe)`. If `pe` is equivalent to `owl:bottomObjectProperty` then nothing will be returned.

abstract super_object_properties (*op: owlapy.owl_property.OWLObjectPropertyExpression*,
direct: bool = False) → `Iterable[owlapy.owl_property.OWLObjectPropertyExpression]`

Gets the stream of object properties that are the strict (potentially direct) super properties of the specified object property with respect to the imports closure of the root ontology.

Parameters

- **op** (`OWLObjectPropertyExpression`) – The object property expression whose super properties are to be retrieved.
- **direct** (`bool`) – Specifies if the direct super properties should be retrieved (`True`) or if the all super properties (ancestors) should be retrieved (`False`).

Returns

Iterable of super properties.

abstract types (*ind: owlapy.owl_individual.OWLNamedIndividual*, *direct: bool = False*)
→ `Iterable[owlapy.class_expression.OWLClass]`

Gets the named classes which are (potentially direct) types of the specified named individual.

Parameters

- **ind** – The individual whose types are to be retrieved.
- **direct** – Specifies if the direct types should be retrieved (True), or if all types should be retrieved (False).

Returns

If **direct** is True, each named class C where the set of reasoner axioms entails `DirectClassAssertion(C, ind)`. If **direct** is False, each named class C where the set of reasoner axioms entails `ClassAssertion(C, ind)`.

abstract `get_root_ontology()` → *owlapy.owl_ontology.OWLontology*

Gets the “root” ontology that is loaded into this reasoner. The reasoner takes into account the axioms in this ontology and its import’s closure.

abstract `super_classes(ce: owlapy.class_expression.OWLClassExpression, direct: bool = False, only_named: bool = True)` → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the stream of named classes that are the strict (potentially direct) super classes of the specified class expression with respect to the imports closure of the root ontology.

Parameters

- **ce** – The class expression whose strict (direct) super classes are to be retrieved.
- **direct** – Specifies if the direct super classes should be retrieved (True) or if the all super classes (ancestors) classes should be retrieved (False).
- **only_named** – Whether to only retrieve named super classes or also complex class expressions.

Returns

If **direct** is True, each class C where the set of reasoner axioms entails `DirectSubClassOf(ce, C)`. If **direct** is False, each class C where set of reasoner axioms entails `StrictSubClassOf(ce, C)`. If **ce** is equivalent to `owl:Thing` then nothing will be returned.

class `owlapy.owl_reasoner.OWLReasonerEx(ontology: owlapy.owl_ontology.OWLontology)`

Bases: *OWLReasoner*

Extra convenience methods for OWL Reasoners

data_property_ranges (*pe: owlapy.owl_property.OWLDataProperty, direct: bool = False*)
→ *Iterable[owlapy.owl_data_ranges.OWLDataRange]*

Gets the data ranges that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns:

all_data_property_values (*pe: owlapy.owl_property.OWLDataProperty, direct: bool = True*)
→ *Iterable[owlapy.owl_literal.OWLLiteral]*

Gets all values for the given data property expression that appear in the knowledge base.

Parameters

- **pe** – The data property expression whose values are to be retrieved
- **direct** – Specifies if only the direct values of the data property **pe** should be retrieved (True), or if the values of sub properties of **pe** should be taken into account (False).

Returns

A set of OWLLiterals containing literals such that for each literal *l* in the set, the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)` for any *ind*.

ind_data_properties (*ind*: *owlapy.owl_individual.OWLNamedIndividual*, *direct*: *bool = True*)
→ `Iterable[owlapy.owl_property.OWLDataProperty]`

Gets all data properties for the given individual that appear in the knowledge base.

Parameters

- **ind** – The named individual whose data properties are to be retrieved
- **direct** – Specifies if the direct data properties should be retrieved (True), or if all data properties should be retrieved (False), so that sub properties are taken into account.

Returns

All data properties *pe* where the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)` for atleast one *l*.

ind_object_properties (*ind*: *owlapy.owl_individual.OWLNamedIndividual*, *direct*: *bool = True*)
→ `Iterable[owlapy.owl_property.OWLObjectProperty]`

Gets all object properties for the given individual that appear in the knowledge base.

Parameters

- **ind** – The named individual whose object properties are to be retrieved
- **direct** – Specifies if the direct object properties should be retrieved (True), or if all object properties should be retrieved (False), so that sub properties are taken into account.

Returns

All data properties *pe* where the set of reasoner axioms entails `ObjectPropertyAssertion(pe ind ind2)` for atleast one *ind2*.

class `owlapy.owl_reasoner.OntologyReasoner` (*ontology*: *owlapy.owl_ontology.Ontology*)

Bases: *OWLReasonerEx*

Extra convenience methods for OWL Reasoners

__slots__ = ('_ontology', '_world')

data_property_domains (*pe*: *owlapy.owl_property.OWLDataProperty*, *direct*: *bool = False*)
→ `Iterable[owlapy.class_expression.OWLClassExpression]`

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let *N* = `equivalent_classes(DataSomeValuesFrom(pe rdfs:Literal))`. If *direct* is True: then if *N* is not empty then the return value is *N*, else the return value is the result of `super_classes(DataSomeValuesFrom(pe rdfs:Literal), true)`. If *direct* is False: then the result of `super_classes(DataSomeValuesFrom(pe rdfs:Literal), false)` together with *N* if *N* is non-empty. (Note, `rdfs:Literal` is the top datatype).

object_property_domains (*pe*: *owlapy.owl_property.OWLObjectProperty*, *direct*: *bool = False*)
→ *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{ObjectSomeValuesFrom}(pe \text{ owl:Thing}))$. If *direct* is True: then if N is not empty then the return value is N , else the return value is the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(pe \text{ owl:Thing}), \text{true})$. If *direct* is False: then the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(pe \text{ owl:Thing}), \text{false})$ together with N if N is non-empty.

object_property_ranges (*pe*: *owlapy.owl_property.OWLObjectProperty*, *direct*: *bool = False*)
→ *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the class expressions that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}))$. If *direct* is True: then if N is not empty then the return value is N , else the return value is the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}), \text{true})$. If *direct* is False: then the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}), \text{false})$ together with N if N is non-empty.

equivalent_classes (*ce*: *owlapy.class_expression.OWLClassExpression*, *only_named*: *bool = True*)
→ *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the class expressions that are equivalent to the specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose equivalent classes are to be retrieved.
- **only_named** – Whether to only retrieve named equivalent classes or also complex class expressions.

Returns

All class expressions C where the root ontology imports closure entails $\text{EquivalentClasses}(ce \ C)$. If *ce* is not a class name (i.e. it is an anonymous class expression) and there are no such classes C then there will be no result. If *ce* is unsatisfiable with respect to the set of reasoner axioms then *owl:Nothing*, i.e. the bottom node, will be returned.

disjoint_classes (*ce: owlapy.class_expression.OWLClassExpression, only_named: bool = True*)
→ Iterable[*owlapy.class_expression.OWLClassExpression*]

Gets the class expressions that are disjoint with specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose disjoint classes are to be retrieved.
- **only_named** – Whether to only retrieve named disjoint classes or also complex class expressions.

Returns

All class expressions D where the set of reasoner axioms entails `EquivalentClasses(D ObjectComplementOf(ce))` or `StrictSubClassOf(D ObjectComplementOf(ce))`.

different_individuals (*ind: owlapy.owl_individual.OWLNamedIndividual*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the individuals that are different from the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose different individuals are to be retrieved.

Returns

All individuals x where the set of reasoner axioms entails `DifferentIndividuals(ind x)`.

same_individuals (*ind: owlapy.owl_individual.OWLNamedIndividual*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the individuals that are the same as the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose same individuals are to be retrieved.

Returns

All individuals x where the root ontology imports closure entails `SameIndividual(ind x)`.

data_property_values (*e: owlapy.owl_object.OWLEntity, pe: owlapy.owl_property.OWLDataProperty, direct: bool = True*)
→ Iterable[*owlapy.owl_literal.OWLLiteral*]

Gets the data property values for the specified entity and data property expression.

Parameters

- **e** – The owl entity (usually an individual) that is the subject of the data property values.
- **pe** – The data property expression whose values are to be retrieved for the specified entity.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Note: Can be used to get values, for example, of ‘label’ property of owl entities such as classes and properties too (not only individuals).

Returns

A set of OWLLiterals containing literals such that for each literal l in the set, the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)`.

all_data_property_values (*pe: owlapy.owl_property.OWLDataProperty, direct: bool = True*)
→ Iterable[*owlapy.owl_literal.OWLLiteral*]

Gets all values for the given data property expression that appear in the knowledge base.

Parameters

- **pe** – The data property expression whose values are to be retrieved
- **direct** – Specifies if only the direct values of the data property **pe** should be retrieved (True), or if the values of sub properties of **pe** should be taken into account (False).

Returns

A set of OWLLiterals containing literals such that for each literal *l* in the set, the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)` for any *ind*.

object_property_values (*ind*: *owlapy.owl_individual.OWLNamedIndividual*,
pe: *owlapy.owl_property.OWLObjectPropertyExpression*, *direct*: *bool = False*)
→ *Iterable[owlapy.owl_individual.OWLNamedIndividual]*

Gets the object property values for the specified individual and object property expression.

Parameters

- **ind** – The individual that is the subject of the object property values.
- **pe** – The object property expression whose values are to be retrieved for the specified individual.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Returns

The named individuals such that for each individual *j*, the set of reasoner axioms entails `ObjectPropertyAssertion(pe ind j)`.

instances (*ce*: *owlapy.class_expression.OWLClassExpression*, *direct*: *bool = False*)
→ *Iterable[owlapy.owl_individual.OWLNamedIndividual]*

Gets the individuals which are instances of the specified class expression.

Parameters

- **ce** – The class expression whose instances are to be retrieved.
- **direct** – Specifies if the direct instances should be retrieved (True), or if all instances should be retrieved (False).

Returns

If **direct** is True, each named individual *j* where the set of reasoner axioms entails `DirectClassAssertion(ce, j)`. If **direct** is False, each named individual *j* where the set of reasoner axioms entails `ClassAssertion(ce, j)`. If *ce* is unsatisfiable with respect to the set of reasoner axioms then nothing returned.

sub_classes (*ce*: *owlapy.class_expression.OWLClassExpression*, *direct*: *bool = False*,
only_named: *bool = True*) → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the set of named classes that are the strict (potentially direct) subclasses of the specified class expression with respect to the reasoner axioms.

Parameters

- **ce** – The class expression whose strict (direct) subclasses are to be retrieved.
- **direct** – Specifies if the direct subclasses should be retrieved (True) or if the all subclasses (descendant) classes should be retrieved (False).
- **only_named** – Whether to only retrieve named sub-classes or also complex class expressions.

Returns

If **direct** is True, each class *C* where reasoner axioms entails `DirectSubClassOf(C, ce)`. If **direct**

is False, each class C where reasoner axioms entails `StrictSubClassOf(C, ce)`. If ce is equivalent to `owl:Nothing` then nothing will be returned.

super_classes (*ce*: *owlapy.class_expression.OWLClassExpression*, *direct*: *bool = False*,
only_named: *bool = True*) → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the stream of named classes that are the strict (potentially direct) super classes of the specified class expression with respect to the imports closure of the root ontology.

Parameters

- **ce** – The class expression whose strict (direct) super classes are to be retrieved.
- **direct** – Specifies if the direct super classes should be retrieved (True) or if the all super classes (ancestors) classes should be retrieved (False).
- **only_named** – Whether to only retrieve named super classes or also complex class expressions.

Returns

If `direct` is True, each class C where the set of reasoner axioms entails `DirectSubClassOf(ce, C)`. If `direct` is False, each class C where set of reasoner axioms entails `StrictSubClassOf(ce, C)`. If ce is equivalent to `owl:Thing` then nothing will be returned.

equivalent_object_properties (*op*: *owlapy.owl_property.OWLObjectPropertyExpression*)
→ *Iterable[owlapy.owl_property.OWLObjectPropertyExpression]*

Gets the simplified object properties that are equivalent to the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose equivalent object properties are to be retrieved.

Returns

All simplified object properties e where the root ontology imports closure entails `EquivalentObjectProperties(op e)`. If op is unsatisfiable with respect to the set of reasoner axioms then `owl:bottomDataProperty` will be returned.

equivalent_data_properties (*dp*: *owlapy.owl_property.OWLDataProperty*)
→ *Iterable[owlapy.owl_property.OWLDataProperty]*

Gets the data properties that are equivalent to the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose equivalent data properties are to be retrieved.

Returns

All data properties e where the root ontology imports closure entails `EquivalentDataProperties(dp e)`. If dp is unsatisfiable with respect to the set of reasoner axioms then `owl:bottomDataProperty` will be returned.

disjoint_object_properties (*op*: *owlapy.owl_property.OWLObjectPropertyExpression*)
→ *Iterable[owlapy.owl_property.OWLObjectPropertyExpression]*

Gets the simplified object properties that are disjoint with the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose disjoint object properties are to be retrieved.

Returns

All simplified object properties e where the root ontology imports closure entails `EquivalentObjectProperties(e ObjectPropertyComplementOf(op))` or `StrictSubObjectPropertyOf(e ObjectPropertyComplementOf(op))`.

disjoint_data_properties (*dp*: *owlapy.owl_property.OWLDataProperty*)
→ *Iterable[owlapy.owl_property.OWLDataProperty]*

Gets the data properties that are disjoint with the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose disjoint data properties are to be retrieved.

Returns

All data properties *e* where the root ontology imports closure entails *EquivalentDataProperties(e DataPropertyComplementOf(dp))* or *StrictSubDataPropertyOf(e DataPropertyComplementOf(dp))*.

super_data_properties (*dp*: *owlapy.owl_property.OWLDataProperty*, *direct*: *bool = False*)
→ *Iterable[owlapy.owl_property.OWLDataProperty]*

Gets the stream of data properties that are the strict (potentially direct) super properties of the specified data property with respect to the imports closure of the root ontology.

Parameters

- **dp** (*OWLDataProperty*) – The data property whose super properties are to be retrieved.
- **direct** (*bool*) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

sub_data_properties (*dp*: *owlapy.owl_property.OWLDataProperty*, *direct*: *bool = False*)
→ *Iterable[owlapy.owl_property.OWLDataProperty]*

Gets the set of named data properties that are the strict (potentially direct) subproperties of the specified data property expression with respect to the imports closure of the root ontology.

Parameters

- **dp** – The data property whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If *direct* is True, each property *P* where the set of reasoner axioms entails *DirectSubDataPropertyOf(P, pe)*. If *direct* is False, each property *P* where the set of reasoner axioms entails *StrictSubDataPropertyOf(P, pe)*. If *pe* is equivalent to *owl:bottomDataProperty* then nothing will be returned.

super_object_properties (*op*: *owlapy.owl_property.OWLObjectPropertyExpression*,
direct: *bool = False*) → *Iterable[owlapy.owl_property.OWLObjectPropertyExpression]*

Gets the stream of object properties that are the strict (potentially direct) super properties of the specified object property with respect to the imports closure of the root ontology.

Parameters

- **op** (*OWLObjectPropertyExpression*) – The object property expression whose super properties are to be retrieved.
- **direct** (*bool*) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

sub_object_properties (*op*: *owlapy.owl_property.OWLObjectPropertyExpression*,
direct: *bool* = *False*) → *Iterable[owlapy.owl_property.OWLObjectPropertyExpression]*

Gets the stream of simplified object property expressions that are the strict (potentially direct) subproperties of the specified object property expression with respect to the imports closure of the root ontology.

Parameters

- **op** – The object property expression whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If *direct* is True, simplified object property expressions, such that for each simplified object property expression, P, the set of reasoner axioms entails *DirectSubObjectPropertyOf*(P, pe). If *direct* is False, simplified object property expressions, such that for each simplified object property expression, P, the set of reasoner axioms entails *StrictSubObjectPropertyOf*(P, pe). If pe is equivalent to owl:bottomObjectProperty then nothing will be returned.

types (*ind*: *owlapy.owl_individual.OWLNamedIndividual*, *direct*: *bool* = *False*)
→ *Iterable[owlapy.class_expression.OWLClass]*

Gets the named classes which are (potentially direct) types of the specified named individual.

Parameters

- **ind** – The individual whose types are to be retrieved.
- **direct** – Specifies if the direct types should be retrieved (True), or if all types should be retrieved (False).

Returns

If *direct* is True, each named class C where the set of reasoner axioms entails *DirectClassAssertion*(C, ind). If *direct* is False, each named class C where the set of reasoner axioms entails *ClassAssertion*(C, ind).

get_root_ontology () → *owlapy.owl_ontology.OWLOntology*

Gets the “root” ontology that is loaded into this reasoner. The reasoner takes into account the axioms in this ontology and its import’s closure.

```
class owlapy.owl_reasoner.FastInstanceCheckerReasoner (  
    ontology: owlapy.owl_ontology.OWLOntology, base_reasoner: OWLReasoner, *,  
    property_cache: bool = True, negation_default: bool = True, sub_properties: bool = False)
```

Bases: *OWLReasonerEx*

Tries to check instances fast (but maybe incomplete).

```
__slots__ = ('_ontology', '_base_reasoner', '_ind_set', '_cls_to_ind',  
            '_has_prop', ...)
```

```
reset ()
```

The reset method shall reset any cached state.

```
data_property_domains (pe: owlapy.owl_property.OWLDataProperty, direct: bool = False)  
→ Iterable[owlapy.class_expression.OWLClassExpression]
```

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.

- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{DataSomeValuesFrom}(\text{pe } \text{rdfs:Literal}))$. If **direct** is True: then if N is not empty then the return value is N , else the return value is the result of $\text{super_classes}(\text{DataSomeValuesFrom}(\text{pe } \text{rdfs:Literal}), \text{true})$. If **direct** is False: then the result of $\text{super_classes}(\text{DataSomeValuesFrom}(\text{pe } \text{rdfs:Literal}), \text{false})$ together with N if N is non-empty. (Note, rdfs:Literal is the top datatype).

data_property_ranges (*pe*: *owlapy.owl_property.OWLDataProperty*, *direct*: *bool = False*)
 → *Iterable[owlapy.owl_data_ranges.OWLDataRange]*

Gets the data ranges that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns:

object_property_domains (*pe*: *owlapy.owl_property.OWLObjectProperty*, *direct*: *bool = False*)
 → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{ObjectSomeValuesFrom}(\text{pe } \text{owl:Thing}))$. If **direct** is True: then if N is not empty then the return value is N , else the return value is the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{pe } \text{owl:Thing}), \text{true})$. If **direct** is False: then the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{pe } \text{owl:Thing}), \text{false})$ together with N if N is non-empty.

object_property_ranges (*pe*: *owlapy.owl_property.OWLObjectProperty*, *direct*: *bool = False*)
 → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the class expressions that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **pe** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(\text{pe } \text{owl:Thing})))$. If **direct** is True: then if N is not empty then the return value is N , else the return value is the

result of `super_classes(ObjectSomeValuesFrom(ObjectInverseOf(pe) owl:Thing), true)`. If `direct` is `False`: then the result of `super_classes(ObjectSomeValuesFrom(ObjectInverseOf(pe) owl:Thing), false)` together with `N` if `N` is non-empty.

equivalent_classes (*ce: owlapy.class_expression.OWLClassExpression, only_named: bool = True*)
→ `Iterable[owlapy.class_expression.OWLClassExpression]`

Gets the class expressions that are equivalent to the specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose equivalent classes are to be retrieved.
- **only_named** – Whether to only retrieve named equivalent classes or also complex class expressions.

Returns

All class expressions `C` where the root ontology imports closure entails `EquivalentClasses(ce C)`. If `ce` is not a class name (i.e. it is an anonymous class expression) and there are no such classes `C` then there will be no result. If `ce` is unsatisfiable with respect to the set of reasoner axioms then `owl:Nothing`, i.e. the bottom node, will be returned.

disjoint_classes (*ce: owlapy.class_expression.OWLClassExpression, only_named: bool = True*)
→ `Iterable[owlapy.class_expression.OWLClassExpression]`

Gets the class expressions that are disjoint with specified class expression with respect to the set of reasoner axioms.

Parameters

- **ce** – The class expression whose disjoint classes are to be retrieved.
- **only_named** – Whether to only retrieve named disjoint classes or also complex class expressions.

Returns

All class expressions `D` where the set of reasoner axioms entails `EquivalentClasses(D ObjectComplementOf(ce))` or `StrictSubClassOf(D ObjectComplementOf(ce))`.

different_individuals (*ce: owlapy.owl_individual.OWLNamedIndividual*)
→ `Iterable[owlapy.owl_individual.OWLNamedIndividual]`

Gets the individuals that are different from the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose different individuals are to be retrieved.

Returns

All individuals `x` where the set of reasoner axioms entails `DifferentIndividuals(ind x)`.

same_individuals (*ce: owlapy.owl_individual.OWLNamedIndividual*)
→ `Iterable[owlapy.owl_individual.OWLNamedIndividual]`

Gets the individuals that are the same as the specified individual with respect to the set of reasoner axioms.

Parameters

ind – The individual whose same individuals are to be retrieved.

Returns

All individuals `x` where the root ontology imports closure entails `SameIndividual(ind x)`.

data_property_values (*e: owlapy.owl_object.OWLEntity,*
pe: owlapy.owl_property.OWLDataProperty, direct: bool = True)
→ `Iterable[owlapy.owl_literal.OWLLiteral]`

Gets the data property values for the specified entity and data property expression.

Parameters

- **e** – The owl entity (usually an individual) that is the subject of the data property values.
- **pe** – The data property expression whose values are to be retrieved for the specified entity.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Note: Can be used to get values, for example, of 'label' property of owl entities such as classes and properties too (not only individuals).

Returns

A set of OWLLiterals containing literals such that for each literal l in the set, the set of reasoner axioms entails DataPropertyAssertion(pe ind l).

all_data_property_values (*pe: owlapy.owl_property.OWLDataProperty, direct: bool = True*)
→ Iterable[*owlapy.owl_literal.OWLLiteral*]

Gets all values for the given data property expression that appear in the knowledge base.

Parameters

- **pe** – The data property expression whose values are to be retrieved
- **direct** – Specifies if only the direct values of the data property pe should be retrieved (True), or if the values of sub properties of pe should be taken into account (False).

Returns

A set of OWLLiterals containing literals such that for each literal l in the set, the set of reasoner axioms entails DataPropertyAssertion(pe ind l) for any ind.

object_property_values (*ind: owlapy.owl_individual.OWLNamedIndividual, pe: owlapy.owl_property.OWLObjectPropertyExpression, direct: bool = True*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the object property values for the specified individual and object property expression.

Parameters

- **ind** – The individual that is the subject of the object property values.
- **pe** – The object property expression whose values are to be retrieved for the specified individual.
- **direct** – Specifies if the direct values should be retrieved (True), or if all values should be retrieved (False), so that sub properties are taken into account.

Returns

The named individuals such that for each individual j, the set of reasoner axioms entails ObjectPropertyAssertion(pe ind j).

instances (*ce: owlapy.class_expression.OWLClassExpression, direct: bool = False*)
→ Iterable[*owlapy.owl_individual.OWLNamedIndividual*]

Gets the individuals which are instances of the specified class expression.

Parameters

- **ce** – The class expression whose instances are to be retrieved.
- **direct** – Specifies if the direct instances should be retrieved (True), or if all instances should be retrieved (False).

Returns

If `direct` is `True`, each named individual `j` where the set of reasoner axioms entails `DirectClassAssertion(ce, j)`. If `direct` is `False`, each named individual `j` where the set of reasoner axioms entails `ClassAssertion(ce, j)`. If `ce` is unsatisfiable with respect to the set of reasoner axioms then nothing returned.

sub_classes (*ce*: *owlapy.class_expression.OWLClassExpression*, *direct*: *bool = False*,
only_named: *bool = True*) → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the set of named classes that are the strict (potentially direct) subclasses of the specified class expression with respect to the reasoner axioms.

Parameters

- **ce** – The class expression whose strict (direct) subclasses are to be retrieved.
- **direct** – Specifies if the direct subclasses should be retrieved (`True`) or if the all subclasses (descendant) classes should be retrieved (`False`).
- **only_named** – Whether to only retrieve named sub-classes or also complex class expressions.

Returns

If `direct` is `True`, each class `C` where reasoner axioms entails `DirectSubClassOf(C, ce)`. If `direct` is `False`, each class `C` where reasoner axioms entails `StrictSubClassOf(C, ce)`. If `ce` is equivalent to `owl:Nothing` then nothing will be returned.

super_classes (*ce*: *owlapy.class_expression.OWLClassExpression*, *direct*: *bool = False*,
only_named: *bool = True*) → *Iterable[owlapy.class_expression.OWLClassExpression]*

Gets the stream of named classes that are the strict (potentially direct) super classes of the specified class expression with respect to the imports closure of the root ontology.

Parameters

- **ce** – The class expression whose strict (direct) super classes are to be retrieved.
- **direct** – Specifies if the direct super classes should be retrieved (`True`) or if the all super classes (ancestors) classes should be retrieved (`False`).
- **only_named** – Whether to only retrieve named super classes or also complex class expressions.

Returns

If `direct` is `True`, each class `C` where the set of reasoner axioms entails `DirectSubClassOf(ce, C)`. If `direct` is `False`, each class `C` where set of reasoner axioms entails `StrictSubClassOf(ce, C)`. If `ce` is equivalent to `owl:Thing` then nothing will be returned.

types (*ind*: *owlapy.owl_individual.OWLNamedIndividual*, *direct*: *bool = False*)
→ *Iterable[owlapy.class_expression.OWLClass]*

Gets the named classes which are (potentially direct) types of the specified named individual.

Parameters

- **ind** – The individual whose types are to be retrieved.
- **direct** – Specifies if the direct types should be retrieved (`True`), or if all types should be retrieved (`False`).

Returns

If `direct` is `True`, each named class `C` where the set of reasoner axioms entails `DirectClassAssertion(C, ind)`. If `direct` is `False`, each named class `C` where the set of reasoner axioms entails `ClassAssertion(C, ind)`.

equivalent_object_properties (*dp: owlapy.owl_property.OWLObjectPropertyExpression*)
→ Iterable[*owlapy.owl_property.OWLObjectPropertyExpression*]

Gets the simplified object properties that are equivalent to the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose equivalent object properties are to be retrieved.

Returns

All simplified object properties *e* where the root ontology imports closure entails `EquivalentObjectProperties(op e)`. If *op* is unsatisfiable with respect to the set of reasoner axioms then `owl:bottomDataProperty` will be returned.

equivalent_data_properties (*dp: owlapy.owl_property.OWLDataProperty*)
→ Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the data properties that are equivalent to the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose equivalent data properties are to be retrieved.

Returns

All data properties *e* where the root ontology imports closure entails `EquivalentDataProperties(dp e)`. If *dp* is unsatisfiable with respect to the set of reasoner axioms then `owl:bottomDataProperty` will be returned.

disjoint_object_properties (*dp: owlapy.owl_property.OWLObjectPropertyExpression*)
→ Iterable[*owlapy.owl_property.OWLObjectPropertyExpression*]

Gets the simplified object properties that are disjoint with the specified object property with respect to the set of reasoner axioms.

Parameters

op – The object property whose disjoint object properties are to be retrieved.

Returns

All simplified object properties *e* where the root ontology imports closure entails `EquivalentObjectProperties(e ObjectPropertyComplementOf(op))` or `StrictSubObjectPropertyOf(e ObjectPropertyComplementOf(op))`.

disjoint_data_properties (*dp: owlapy.owl_property.OWLDataProperty*)
→ Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the data properties that are disjoint with the specified data property with respect to the set of reasoner axioms.

Parameters

dp – The data property whose disjoint data properties are to be retrieved.

Returns

All data properties *e* where the root ontology imports closure entails `EquivalentDataProperties(e DataPropertyComplementOf(dp))` or `StrictSubDataPropertyOf(e DataPropertyComplementOf(dp))`.

sub_data_properties (*dp: owlapy.owl_property.OWLDataProperty, direct: bool = False*)
→ Iterable[*owlapy.owl_property.OWLDataProperty*]

Gets the set of named data properties that are the strict (potentially direct) subproperties of the specified data property expression with respect to the imports closure of the root ontology.

Parameters

- **dp** – The data property whose strict (direct) subproperties are to be retrieved.

- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If **direct** is True, each property P where the set of reasoner axioms entails `DirectSubDataPropertyOf(P, pe)`. If **direct** is False, each property P where the set of reasoner axioms entails `StrictSubDataPropertyOf(P, pe)`. If **pe** is equivalent to `owl:bottomDataProperty` then nothing will be returned.

super_data_properties (*dp: owlapy.owl_property.OWLDataProperty, direct: bool = False*)
 → `Iterable[owlapy.owl_property.OWLDataProperty]`

Gets the stream of data properties that are the strict (potentially direct) super properties of the specified data property with respect to the imports closure of the root ontology.

Parameters

- **dp** (`OWLDataProperty`) – The data property whose super properties are to be retrieved.
- **direct** (`bool`) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

super_object_properties (*op: owlapy.owl_property.OWLObjectProperty, direct: bool = False*)
 → `Iterable[owlapy.owl_property.OWLDataProperty]`

Gets the stream of object properties that are the strict (potentially direct) super properties of the specified object property with respect to the imports closure of the root ontology.

Parameters

- **op** (`OWLObjectPropertyExpression`) – The object property expression whose super properties are to be retrieved.
- **direct** (`bool`) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

sub_object_properties (*op: owlapy.owl_property.OWLObjectPropertyExpression, direct: bool = False*) → `Iterable[owlapy.owl_property.OWLObjectPropertyExpression]`

Gets the stream of simplified object property expressions that are the strict (potentially direct) subproperties of the specified object property expression with respect to the imports closure of the root ontology.

Parameters

- **op** – The object property expression whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If **direct** is True, simplified object property expressions, such that for each simplified object property expression, P, the set of reasoner axioms entails `DirectSubObjectPropertyOf(P, pe)`. If **direct** is False, simplified object property expressions, such that for each simplified object property expression, P, the set of reasoner axioms entails `StrictSubObjectPropertyOf(P, pe)`. If **pe** is equivalent to `owl:bottomObjectProperty` then nothing will be returned.

get_root_ontology () → `owlapy.owl_ontology.OWLOntology`

Gets the “root” ontology that is loaded into this reasoner. The reasoner takes into account the axioms in this ontology and its import’s closure.

```
class owlapy.owl_reasoner.SyncReasoner (ontology: owlapy.owl_ontology.SyncOntology | str,  
    reasoner='HermiT')
```

mapper

inference_types_mapping

```
instances (ce: owlapy.class_expression.OWLClassExpression, direct=False)  
    → List[owlapy.owl_individual.OWLNamedIndividual]
```

Get the instances for a given class expression using HermiT.

Parameters

- **ce** (OWLClassExpression) – The class expression in OWLAPY format.
- **direct** (bool) – Whether to get direct instances or not. Defaults to False.

Returns

A list of individuals classified by the given class expression.

Return type

list

```
equivalent_classes (ce: owlapy.class_expression.OWLClassExpression)  
    → List[owlapy.class_expression.OWLClassExpression]
```

Gets the set of named classes that are equivalent to the specified class expression with respect to the set of reasoner axioms.

Parameters

ce (OWLClassExpression) – The class expression whose equivalent classes are to be retrieved.

Returns

Equivalent classes of the given class expression.

```
disjoint_classes (ce: owlapy.class_expression.OWLClassExpression)  
    → List[owlapy.class_expression.OWLClassExpression]
```

Gets the classes that are disjoint with the specified class expression.

Parameters

ce (OWLClassExpression) – The class expression whose disjoint classes are to be retrieved.

Returns

Disjoint classes of the given class expression.

```
sub_classes (ce: owlapy.class_expression.OWLClassExpression, direct=False)  
    → List[owlapy.class_expression.OWLClassExpression]
```

Gets the set of named classes that are the strict (potentially direct) subclasses of the specified class expression with respect to the reasoner axioms.

Args:

ce (OWLClassExpression): The class expression whose strict (direct) subclasses are to be retrieved. **direct** (bool, optional): Specifies if the direct subclasses should be retrieved (True) or if

all subclasses (descendant) classes should be retrieved (False). Defaults to False.

Returns

The subclasses of the given class expression depending on *direct* field.

super_classes (*ce: owlapy.class_expression.OWLClassExpression, direct=False*)
→ List[*owlapy.class_expression.OWLClassExpression*]

Gets the stream of named classes that are the strict (potentially direct) super classes of the specified class expression with respect to the imports closure of the root ontology.

Parameters

- **ce** (*OWLClassExpression*) – The class expression whose strict (direct) subclasses are to be retrieved.
- **direct** (*bool, optional*) – Specifies if the direct superclasses should be retrieved (True) or if all superclasses (descendant) classes should be retrieved (False). Defaults to False.

Returns

The subclasses of the given class expression depending on *direct* field.

data_property_domains (*p: owlapy.owl_property.OWLDataProperty, direct: bool = False*)

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **p** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let N = `equivalent_classes(DataSomeValuesFrom(pe rdfs:Literal))`. If *direct* is True: then if N is not empty then the return value is N, else the return value is the result of `super_classes(DataSomeValuesFrom(pe rdfs:Literal), true)`. If *direct* is False: then the result of `super_classes(DataSomeValuesFrom(pe rdfs:Literal), false)` together with N if N is non-empty. (Note, `rdfs:Literal` is the top datatype).

object_property_domains (*p: owlapy.owl_property.OWLObjectProperty, direct: bool = False*)

Gets the class expressions that are the direct or indirect domains of this property with respect to the imports closure of the root ontology.

Parameters

- **p** – The property expression whose domains are to be retrieved.
- **direct** – Specifies if the direct domains should be retrieved (True), or if all domains should be retrieved (False).

Returns

Let N = `equivalent_classes(ObjectSomeValuesFrom(pe owl:Thing))`. If *direct* is True: then if N is not empty then the return value is N, else the return value is the result of `super_classes(ObjectSomeValuesFrom(pe owl:Thing), true)`. If *direct* is False: then the result of `super_classes(ObjectSomeValuesFrom(pe owl:Thing), false)` together with N if N is non-empty.

object_property_ranges (*p: owlapy.owl_property.OWLObjectProperty, direct: bool = False*)

Gets the class expressions that are the direct or indirect ranges of this property with respect to the imports closure of the root ontology.

Parameters

- **p** – The property expression whose ranges are to be retrieved.
- **direct** – Specifies if the direct ranges should be retrieved (True), or if all ranges should be retrieved (False).

Returns

Let $N = \text{equivalent_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}))$. If **direct** is True: then if N is not empty then the return value is N , else the return value is the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}), \text{true})$. If **direct** is False: then the result of $\text{super_classes}(\text{ObjectSomeValuesFrom}(\text{ObjectInverseOf}(pe) \text{ owl:Thing}), \text{false})$ together with N if N is non-empty.

sub_object_properties (*p: owlapy.owl_property.OWLObjectProperty, direct: bool = False*)

Gets the stream of simplified object property expressions that are the strict (potentially direct) subproperties of the specified object property expression with respect to the imports closure of the root ontology.

Parameters

- **p** – The object property expression whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If **direct** is True, simplified object property expressions, such that for each simplified object property expression, P , the set of reasoner axioms entails $\text{DirectSubObjectPropertyOf}(P, pe)$. If **direct** is False, simplified object property expressions, such that for each simplified object property expression, P , the set of reasoner axioms entails $\text{StrictSubObjectPropertyOf}(P, pe)$. If pe is equivalent to $\text{owl:bottomObjectProperty}$ then nothing will be returned.

super_object_properties (*p: owlapy.owl_property.OWLObjectProperty, direct: bool = False*)

Gets the stream of object properties that are the strict (potentially direct) super properties of the specified object property with respect to the imports closure of the root ontology.

Parameters

- **p** (*OWLObjectPropertyExpression*) – The object property expression whose super properties are to be retrieved.
- **direct** (*bool*) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

sub_data_properties (*p: owlapy.owl_property.OWLDataProperty, direct: bool = False*)

Gets the set of named data properties that are the strict (potentially direct) subproperties of the specified data property expression with respect to the imports closure of the root ontology.

Parameters

- **p** – The data property whose strict (direct) subproperties are to be retrieved.
- **direct** – Specifies if the direct subproperties should be retrieved (True) or if the all subproperties (descendants) should be retrieved (False).

Returns

If **direct** is True, each property P where the set of reasoner axioms entails $\text{DirectSubDataPropertyOf}(P, pe)$. If **direct** is False, each property P where the set of reasoner axioms entails

StrictSubDataPropertyOf(P, pe). If pe is equivalent to owl:bottomDataProperty then nothing will be returned.

super_data_properties (*p: owlapy.owl_property.OWLDataProperty, direct: bool = False*)

Gets the stream of data properties that are the strict (potentially direct) super properties of the specified data property with respect to the imports closure of the root ontology.

Parameters

- **p** (*OWLDataProperty*) – The data property whose super properties are to be retrieved.
- **direct** (*bool*) – Specifies if the direct super properties should be retrieved (True) or if the all super properties (ancestors) should be retrieved (False).

Returns

Iterable of super properties.

different_individuals (*i: owlapy.owl_individual.OWLNamedIndividual*)

Gets the individuals that are different from the specified individual with respect to the set of reasoner axioms.

Parameters

i – The individual whose different individuals are to be retrieved.

Returns

All individuals x where the set of reasoner axioms entails DifferentIndividuals(ind x).

same_individuals (*i: owlapy.owl_individual.OWLNamedIndividual*)

Gets the individuals that are the same as the specified individual with respect to the set of reasoner axioms.

Parameters

i – The individual whose same individuals are to be retrieved.

Returns

All individuals x where the root ontology imports closure entails SameIndividual(ind x).

equivalent_object_properties (*p: owlapy.owl_property.OWLObjectProperty*)

Gets the simplified object properties that are equivalent to the specified object property with respect to the set of reasoner axioms.

Parameters

p – The object property whose equivalent object properties are to be retrieved.

Returns

All simplified object properties e where the root ontology imports closure entails EquivalentObjectProperties(op e). If op is unsatisfiable with respect to the set of reasoner axioms then owl:bottomDataProperty will be returned.

equivalent_data_properties (*p: owlapy.owl_property.OWLDataProperty*)

Gets the data properties that are equivalent to the specified data property with respect to the set of reasoner axioms.

Parameters

p – The data property whose equivalent data properties are to be retrieved.

Returns

All data properties e where the root ontology imports closure entails EquivalentDataProperties(dp e). If dp is unsatisfiable with respect to the set of reasoner axioms then owl:bottomDataProperty will be returned.

object_property_values (*i: owlapy.owl_individual.OWLNamedIndividual, p: owlapy.owl_property.OWLObjectProperty*)

Gets the object property values for the specified individual and object property expression.

Parameters

- **i** – The individual that is the subject of the object property values.
- **p** – The object property expression whose values are to be retrieved for the specified individual.

Returns

The named individuals such that for each individual *j*, the set of reasoner axioms entails `ObjectPropertyAssertion(pe ind j)`.

data_property_values (*e: owlapy.owl_object.OWLEntity*,
p: owlapy.owl_property.OWLDataProperty)

Gets the data property values for the specified entity and data property expression.

Parameters

- **e** – The entity (usually an individual) that is the subject of the data property values.
- **p** – The data property expression whose values are to be retrieved for the specified individual.

Returns

A set of OWLLiterals containing literals such that for each literal *l* in the set, the set of reasoner axioms entails `DataPropertyAssertion(pe ind l)`.

disjoint_object_properties (*p: owlapy.owl_property.OWLObjectProperty*)

Gets the simplified object properties that are disjoint with the specified object property with respect to the set of reasoner axioms.

Parameters

p – The object property whose disjoint object properties are to be retrieved.

Returns

All simplified object properties *e* where the root ontology imports closure entails `EquivalentObjectProperties(e ObjectPropertyComplementOf(op))` or `StrictSubObjectPropertyOf(e ObjectPropertyComplementOf(op))`.

disjoint_data_properties (*p: owlapy.owl_property.OWLDataProperty*)

Gets the data properties that are disjoint with the specified data property with respect to the set of reasoner axioms.

Parameters

p – The data property whose disjoint data properties are to be retrieved.

Returns

All data properties *e* where the root ontology imports closure entails `EquivalentDataProperties(e DataPropertyComplementOf(dp))` or `StrictSubDataPropertyOf(e DataPropertyComplementOf(dp))`.

types (*i: owlapy.owl_individual.OWLNamedIndividual*, *direct: bool = False*)

Gets the named classes which are (potentially direct) types of the specified named individual.

Parameters

- **i** – The individual whose types are to be retrieved.
- **direct** – Specifies if the direct types should be retrieved (True), or if all types should be retrieved (False).

Returns

If *direct* is True, each named class *C* where the set of reasoner axioms entails `DirectClassAssertion(C, ind)`. If *direct* is False, each named class *C* where the set of reasoner axioms entails `ClassAssertion(C, ind)`.

has_consistent_ontology () → bool

Check if the used ontology is consistent.

Returns

True if the ontology used by this reasoner is consistent, False otherwise.

Return type

bool

infer_axioms (*inference_types*: list[str]) → Iterable[owlapy.owl_axiom.OWLAXiom]

Infer the specified inference type of axioms for the ontology managed by this instance's reasoner and return them.

Parameters

inference_types – Axiom inference types: Available options (can set more than 1): ["InferredClassAssertionAxiomGenerator", "InferredSubClassAxiomGenerator", "InferredDisjointClassesAxiomGenerator", "InferredEquivalentClassAxiomGenerator", "InferredEquivalentDataPropertiesAxiomGenerator", "InferredEquivalentObjectPropertyAxiomGenerator", "InferredInverseObjectPropertiesAxiomGenerator", "InferredSubDataPropertyAxiomGenerator", "InferredSubObjectPropertyAxiomGenerator", "InferredDataPropertyCharacteristicAxiomGenerator", "InferredObjectPropertyCharacteristicAxiomGenerator"]

Returns

Iterable of inferred axioms.

infer_axioms_and_save (*output_path*: str = None, *output_format*: str = None, *inference_types*: list[str] = None)

Generates inferred axioms for the ontology managed by this instance's reasoner and saves them to a file. This function uses the OWL API to generate inferred class assertion axioms based on the ontology and reasoner associated with this instance. The inferred axioms are saved to the specified output file in the desired format.

Parameters

- **output_path** – The name of the file where the inferred axioms will be saved.
- **output_format** – The format in which to save the inferred axioms. Supported formats are: - "ttl" or "turtle" for Turtle format - "rdf/xml" for RDF/XML format - "owl/xml" for OWL/XML format If not specified, the format of the original ontology is used.
- **inference_types** – Axiom inference types: Available options (can set more than 1): ["InferredClassAssertionAxiomGenerator", "InferredSubClassAxiomGenerator", "InferredDisjointClassesAxiomGenerator", "InferredEquivalentClassAxiomGenerator", "InferredEquivalentDataPropertiesAxiomGenerator", "InferredEquivalentObjectPropertyAxiomGenerator", "InferredInverseObjectPropertiesAxiomGenerator", "InferredSubDataPropertyAxiomGenerator", "InferredSubObjectPropertyAxiomGenerator", "InferredDataPropertyCharacteristicAxiomGenerator", "InferredObjectPropertyCharacteristicAxiomGenerator"]

Returns

None (the file is saved to the specified directory)

generate_and_save_inferred_class_assertion_axioms (*output*='temp.ttl', *output_format*: str = None)

Generates inferred class assertion axioms for the ontology managed by this instance's reasoner and saves them to a file. This function uses the OWL API to generate inferred class assertion axioms based on the ontology and reasoner associated with this instance. The inferred axioms are saved to the specified output file in the desired format. Parameters: ——— output : str, optional

The name of the file where the inferred axioms will be saved. Default is "temp.ttl".

output_format

[str, optional] The format in which to save the inferred axioms. Supported formats are: - “ttl” or “turtle” for Turtle format - “rdf/xml” for RDF/XML format - “owl/xml” for OWL/XML format If not specified, the format of the original ontology is used.

Notes:

- The function supports saving in multiple formats: Turtle, RDF/XML, and OWL/XML.
- The inferred axioms are generated using the reasoner associated with this instance and the OWL API's InferredClassAssertionAxiomGenerator.
- The inferred axioms are added to a new ontology which is then saved in the specified format.

Example:

```
>>> instance.generate_and_save_inferred_class_assertion_axioms(output=  
↪ "inferred_axioms.ttl", format="ttl")  
This will save the inferred class assertion axioms to the file "inferred_  
↪ axioms.ttl" in Turtle format.
```

`get_root_ontology()` → *owlapy.owl_ontology.OWLontology*

owlapy.owlapi_mapper

Classes

OWLAPIMapper

Functions

init(the_class)

Module Contents

`owlapy.owlapi_mapper.init` (*the_class*)

class `owlapy.owlapi_mapper.OWLAPIMapper` (*ontology*: *_SO*)

manager

ontology

namespace

ontology_set
bidirectional_provider
entity_checker
parser
renderer
map_ (*e*)
 (owlapy <-> owlapi) entity mapping.
Parameters
e – OWL entity/expression.
static to_list (*stream_obj*)
 Converts Java Stream object to Python list

owlapy.parser

String to OWL parsers.

Attributes

<i>MANCHESTER_GRAMMAR</i>
<i>DL_GRAMMAR</i>
<i>DLparser</i>
<i>ManchesterParser</i>

Classes

<i>ManchesterOWLSyntaxParser</i>	Manchester Syntax parser to parse strings to OWLClass-Expressions.
<i>DLSyntaxParser</i>	Description Logic Syntax parser to parse strings to OWL-ClassExpressions.

Functions

```
dl_to_owl_expression(dl_expression, namespace)
manchester_to_owl_expression(manchester_ex
...)
```

Module Contents

`owlapy.parser.MANCHESTER_GRAMMAR`

```
class owlapy.parser.ManchesterOWLSyntaxParser (
    namespace: str | owlapy.namespaces.Namespaces | None = None, grammar=None)
    Bases: parsimonious.nodes.NodeVisitor, owlapy.owl_object.OWLObjectParser
    Manchester Syntax parser to parse strings to OWLClassExpressions. Following: https://www.w3.org/TR/owl2-manchester-syntax.
    slots = ('ns', 'grammar')
    ns: str | owlapy.namespaces.Namespaces | None
    grammar
    parse_expression (expression_str: str) → owlapy.class_expression.OWLClassExpression
        Parse a string to an OWL Object.
        Parameters
            expression_str (str) – Expression string.
        Returns
            The OWL Object which is represented by the string.
    visit_union (node, children) → owlapy.class_expression.OWLClassExpression
    visit_intersection (node, children) → owlapy.class_expression.OWLClassExpression
    visit_primary (node, children) → owlapy.class_expression.OWLClassExpression
    visit_some_only_res (node, children) → owlapy.class_expression.OWLQuantifiedObjectRestriction
    visit_cardinality_res (node, children)
        → owlapy.class_expression.OWLObjectCardinalityRestriction
    visit_value_res (node, children) → owlapy.class_expression.OWLObjectHasValue
    visit_has_self (node, children) → owlapy.class_expression.OWLObjectHasSelf
    visit_object_property (node, children) → owlapy.owl_property.OWLObjectPropertyExpression
    visit_class_expression (node, children) → owlapy.class_expression.OWLClassExpression
    visit_individual_list (node, children) → owlapy.class_expression.OWLObjectOneOf
    visit_data_primary (node, children) → owlapy.owl_data_ranges.OWLDataRange
```

visit_data_some_only_res (*node*, *children*)
 → *owlapy.class_expression.OWLQuantifiedDataRestriction*

visit_data_cardinality_res (*node*, *children*)
 → *owlapy.class_expression.OWLDataCardinalityRestriction*

visit_data_value_res (*node*, *children*) → *owlapy.class_expression.OWLDataHasValue*

visit_data_union (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*

visit_data_intersection (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*

visit_literal_list (*node*, *children*) → *owlapy.class_expression.OWLDataOneOf*

visit_data_parentheses (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*

visit_datatype_restriction (*node*, *children*)
 → *owlapy.class_expression.OWLDatatypeRestriction*

visit_facet_restrictions (*node*, *children*)
 → List[*owlapy.class_expression.OWLFacetRestriction*]

visit_facet_restriction (*node*, *children*) → *owlapy.class_expression.OWLFacetRestriction*

visit_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_typed_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

abstract visit_string_literal_language (*node*, *children*)

visit_string_literal_no_language (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_quoted_string (*node*, *children*) → str

visit_float_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_decimal_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_integer_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_boolean_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_datetime_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_duration_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_date_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*

visit_non_negative_integer (*node*, *children*) → int

visit_datatype_iri (*node*, *children*) → str

visit_datatype (*node*, *children*) → *owlapy.owl_datatype.OWLDatatype*

visit_facet (*node*, *children*) → *owlapy.vocab.OWLFacet*

visit_class_iri (*node*, *children*) → *owlapy.class_expression.OWLClass*

visit_individual_iri (*node*, *children*) → *owlapy.owl_individual.OWLNamedIndividual*

visit_object_property_iri (*node*, *children*) → *owlapy.owl_property.OWLObjectProperty*

visit_data_property_iri (*node*, *children*) → *owlapy.owl_property.OWLDataProperty*

visit_iri (*node*, *children*) → *owlapy.iri.IRI*

visit_full_iri (*node*, *children*) → *owlapy.iri.IRI*

abstract visit_abbreviated_iri (*node*, *children*)

visit_simple_iri (*node*, *children*) → *owlapy.iri.IRI*

visit_parentheses (*node*, *children*) → *owlapy.class_expression.OWLClassExpression*

generic_visit (*node*, *children*)

Default visitor method

Parameters

- **node** – The node we’re visiting
- **visited_children** – The results of visiting the children of that node, in a list

I’m not sure there’s an implementation of this that makes sense across all (or even most) use cases, so we leave it to subclasses to implement for now.

owlapy.parser.DL_GRAMMAR

```
class owlapy.parser.DLSyntaxParser (  
    namespace: str | owlapy.namespaces.Namespaces | None = None, grammar=None)
```

Bases: *parsimonious.nodes.NodeVisitor*, *owlapy.owl_object.OWLObjectParser*

Description Logic Syntax parser to parse strings to OWLClassExpressions.

slots = ('ns', 'grammar')

ns: str | *owlapy.namespaces.Namespaces* | None

grammar

parse_expression (*expression_str*: str) → *owlapy.class_expression.OWLClassExpression*

Parse a string to an OWL Object.

Parameters

expression_str (*str*) – Expression string.

Returns

The OWL Object which is represented by the string.

visit_union (*node*, *children*) → *owlapy.class_expression.OWLClassExpression*

visit_intersection (*node*, *children*) → *owlapy.class_expression.OWLClassExpression*

visit_primary (*node*, *children*) → *owlapy.class_expression.OWLClassExpression*

visit_some_only_res (*node*, *children*) → *owlapy.class_expression.OWLQuantifiedObjectRestriction*

visit_cardinality_res (*node*, *children*)
→ *owlapy.class_expression.OWLObjectCardinalityRestriction*

visit_value_res (*node*, *children*) → *owlapy.class_expression.OWLObjectHasValue*

visit_has_self (*node*, *children*) → *owlapy.class_expression.OWLObjectHasSelf*

visit_object_property (*node*, *children*) → *owlapy.owl_property.OWLObjectPropertyExpression*
visit_class_expression (*node*, *children*) → *owlapy.class_expression.OWLClassExpression*
visit_individual_list (*node*, *children*) → *owlapy.class_expression.OWLObjectOneOf*
visit_data_primary (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*
visit_data_some_only_res (*node*, *children*)
 → *owlapy.class_expression.OWLQuantifiedDataRestriction*
visit_data_cardinality_res (*node*, *children*)
 → *owlapy.class_expression.OWLDataCardinalityRestriction*
visit_data_value_res (*node*, *children*) → *owlapy.class_expression.OWLDataHasValue*
visit_data_union (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*
visit_data_intersection (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*
visit_literal_list (*node*, *children*) → *owlapy.class_expression.OWLDataOneOf*
visit_data_parentheses (*node*, *children*) → *owlapy.owl_data_ranges.OWLDataRange*
visit_datatype_restriction (*node*, *children*)
 → *owlapy.class_expression.OWLDatatypeRestriction*
visit_facet_restrictions (*node*, *children*)
 → List[*owlapy.class_expression.OWLFacetRestriction*]
visit_facet_restriction (*node*, *children*) → *owlapy.class_expression.OWLFacetRestriction*
visit_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_typed_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
abstract_visit_string_literal_language (*node*, *children*)
visit_string_literal_no_language (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_quoted_string (*node*, *children*) → str
visit_float_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_decimal_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_integer_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_boolean_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_datetime_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_duration_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_date_literal (*node*, *children*) → *owlapy.owl_literal.OWLLiteral*
visit_non_negative_integer (*node*, *children*) → int
visit_datatype_iri (*node*, *children*) → str
visit_datatype (*node*, *children*) → *owlapy.owl_datatype.OWLDatatype*

```

visit_facet (node, children) → owlapy.vocab.OWLFacet
visit_class_iri (node, children) → owlapy.class_expression.OWLClass
visit_individual_iri (node, children) → owlapy.owl_individual.OWLNamedIndividual
visit_object_property_iri (node, children) → owlapy.owl_property.OWLObjectProperty
visit_data_property_iri (node, children) → owlapy.owl_property.OWLDataProperty
visit_iri (node, children) → owlapy.iri.IRI
visit_full_iri (node, children) → owlapy.iri.IRI
abstract visit_abbreviated_iri (node, children)
visit_simple_iri (node, children) → owlapy.iri.IRI
visit_parentheses (node, children) → owlapy.class_expression.OWLClassExpression
generic_visit (node, children)

```

Default visitor method

Parameters

- **node** – The node we’re visiting
- **visited_children** – The results of visiting the children of that node, in a list

I’m not sure there’s an implementation of this that makes sense across all (or even most) use cases, so we leave it to subclasses to implement for now.

```
owlapy.parser.DLparser
```

```
owlapy.parser.ManchesterParser
```

```
owlapy.parser.dl_to_owl_expression (dl_expression: str, namespace: str)
```

```
owlapy.parser.manchester_to_owl_expression (manchester_expression: str, namespace: str)
```

owlapy.providers

OWL Datatype restriction constructors.

Attributes

Restriction_Literals

Functions

<code>owl_datatype_max_exclusive_restriction</code>	Create a max exclusive restriction.
<code>owl_datatype_min_exclusive_restriction</code>	Create a min exclusive restriction.
<code>owl_datatype_max_inclusive_restriction</code>	Create a max inclusive restriction.
<code>owl_datatype_min_inclusive_restriction</code>	Create a min inclusive restriction.
<code>owl_datatype_min_max_exclusive_restric</code>	Create a min-max exclusive restriction.
<code>owl_datatype_min_max_inclusive_restric</code>	Create a min-max inclusive restriction.

Module Contents

`owlapy.providers.Restriction_Literals`

`owlapy.providers.owl_datatype_max_exclusive_restriction` (*max_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a max exclusive restriction.

`owlapy.providers.owl_datatype_min_exclusive_restriction` (*min_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a min exclusive restriction.

`owlapy.providers.owl_datatype_max_inclusive_restriction` (*max_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a max inclusive restriction.

`owlapy.providers.owl_datatype_min_inclusive_restriction` (*min_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a min inclusive restriction.

`owlapy.providers.owl_datatype_min_max_exclusive_restriction` (*min_*: *Restriction_Literals*, *max_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a min-max exclusive restriction.

`owlapy.providers.owl_datatype_min_max_inclusive_restriction` (*min_*: *Restriction_Literals*, *max_*: *Restriction_Literals*)
→ *owlapy.class_expression.OWLDatatypeRestriction*

Create a min-max inclusive restriction.

`owlapy.render`

Renderers for different syntax.

Attributes

mapper

DLrenderer

ManchesterRenderer

Classes

DLSyntaxObjectRenderer

DL Syntax renderer for OWL Objects.

ManchesterOWLSyntaxOWLObjectRenderer

Manchester Syntax renderer for OWL Objects

Functions

translating_short_form_provider(\rightarrow str)

e: entity.

translating_short_form_endpoint(\rightarrow str)

Translates an OWLEntity to a short form string using provided rules and an endpoint.

owl_expression_to_dl(\rightarrow str)

owl_expression_to_manchester(\rightarrow str)

Module Contents

`owlapy.render.mapper`

`owlapy.render.translating_short_form_provider` (e: *owlapy.owl_object.OWLEntity*, *reasoner*,
rules: dict[str:str] = None) \rightarrow str

e: entity. reasoner: OWLReasoner or Triplestore(from Ontolearn) rules: A mapping from OWLEntity to predicates,

Keys in rules can be general or specific iris, e.g., IRI to IRI s.t. the second IRI must be a predicate leading to literal

`owlapy.render.translating_short_form_endpoint` (e: *owlapy.owl_object.OWLEntity*,
endpoint: str, *rules*: dict[abc.ABCMeta:str] = None) \rightarrow str

Translates an OWLEntity to a short form string using provided rules and an endpoint.

Parameters: e (OWLEntity): The OWL entity to be translated. endpoint (str): The endpoint of a triple store to query against. rules (dict[abc.ABCMeta:str], optional): A dictionary mapping OWL classes to string IRIs leading to a literal.

Returns: str: The translated short form of the OWL entity. If no matching rules are found, a simple short form is returned.

This function iterates over the provided rules to check if the given OWL entity is an instance of any specified class. If a match is found, it constructs a SPARQL query to retrieve the literal value associated with the entity and predicate. If a literal is found, it is returned as the short form. If no literals are found, the SPARQL query and entity information are printed for debugging purposes. If no matching rules are found, a warning is issued and a simple short form is returned.

Example: >>> e = OWLEntity("http://example.org/entity") >>> endpoint = "http://example.org/sparql" >>> rules = {SomeOWLClass: "http://example.org/predicate"} >>> translating_short_form_endpoint(e, endpoint, rules)

```
class owlapy.render.DLSyntaxObjectRenderer (
    short_form_provider: Callable[[owlapy.owl_object.OWLEntity], str] = _simple_short_form_provider)
```

Bases: *owlapy.owl_object.OWLObjectRenderer*

DL Syntax renderer for OWL Objects.

```
__slots__ = '_sfp'
```

```
set_short_form_provider (short_form_provider: Callable[[owlapy.owl_object.OWLEntity], str])
    → None
```

Configure a short form provider that shortens the OWL objects during rendering.

Parameters

short_form_provider – Short form provider.

```
render (o: owlapy.owl_object.OWLObject) → str
```

Render OWL Object to string.

Parameters

o – OWL Object.

Returns

String rendition of OWL object.

```
class owlapy.render.ManchesterOWLSyntaxOWLObjectRenderer (
    short_form_provider: Callable[[owlapy.owl_object.OWLEntity], str] = _simple_short_form_provider,
    no_render_thing=False)
```

Bases: *owlapy.owl_object.OWLObjectRenderer*

Manchester Syntax renderer for OWL Objects

```
__slots__ = ('_sfp', '_no_render_thing')
```

```
set_short_form_provider (short_form_provider: Callable[[owlapy.owl_object.OWLEntity], str])
    → None
```

Configure a short form provider that shortens the OWL objects during rendering.

Parameters

short_form_provider – Short form provider.

```
render (o: owlapy.owl_object.OWLObject) → str
```

Render OWL Object to string.

Parameters

o – OWL Object.

Returns

String rendition of OWL object.

```
owlapy.render.DLrenderer
```

`owlapy.render.ManchesterRenderer`

`owlapy.render.owl_expression_to_dl (o: owlapy.owl_object.OWLObject) → str`

`owlapy.render.owl_expression_to_manchester (o: owlapy.owl_object.OWLObject) → str`

owlapy.static_funcs

Static functions for general purposes.

Functions

<code>move(*args)</code>	"Move" an imported class to the current module by setting the classes <code>__module__</code> attribute.
<code>download_external_files(ftp_link)</code>	
<code>startJVM()</code>	Start the JVM with jar dependencies. This method is called automatically on object initialization, if the
<code>stopJVM(→ None)</code>	Detaches the thread from Java packages and shuts down the java virtual machine hosted by jpye.

Module Contents

`owlapy.static_funcs.move (*args)`

“Move” an imported class to the current module by setting the classes `__module__` attribute.

This is useful for documentation purposes to hide internal packages in sphinx.

Parameters

args – List of classes to move.

`owlapy.static_funcs.download_external_files (ftp_link: str)`

`owlapy.static_funcs.startJVM()`

Start the JVM with jar dependencies. This method is called automatically on object initialization, if the JVM is not started yet.

`owlapy.static_funcs.stopJVM() → None`

Detaches the thread from Java packages and shuts down the java virtual machine hosted by jpye.

owlapy.utils

Owlapy utils.

Attributes

<code>measurer</code>

Classes

<code>OWLClassExpressionLengthMetric</code>	Length calculation of OWLClassExpression
<code>EvaluatedDescriptionSet</code>	Abstract base class for generic types.
<code>ConceptOperandSorter</code>	
<code>OperandSetTransform</code>	
<code>HasIndex</code>	Interface for types with an index; this is used to group objects by type when sorting.
<code>OrderedOWLObject</code>	Holder of OWL Objects that can be used for Python sorted.
<code>NNF</code>	This class contains functions to transform a Class Expression into Negation Normal Form.
<code>TopLevelCNF</code>	This class contains functions to transform a class expression into Top-Level Conjunctive Normal Form.
<code>TopLevelDNF</code>	This class contains functions to transform a class expression into Top-Level Disjunctive Normal Form.
<code>LRUCache</code>	Constants shares by all lru cache instances.

Functions

<code>get_expression_length(→ int)</code>	
<code>combine_nary_expressions(...)</code>	Shortens an OWLClassExpression or OWLDataRange by combining all nested nary expressions of the same type.
<code>iter_count(→ int)</code>	Count the number of elements in an iterable.
<code>as_index(→ HasIndex)</code>	Cast OWL Object to HasIndex.

Module Contents

```
class owlapy.utils.OWLClassExpressionLengthMetric(*, class_length: int,
    object_intersection_length: int, object_union_length: int, object_complement_length: int,
    object_some_values_length: int, object_all_values_length: int, object_has_value_length: int,
    object_cardinality_length: int, object_has_self_length: int, object_one_of_length: int,
    data_some_values_length: int, data_all_values_length: int, data_has_value_length: int,
    data_cardinality_length: int, object_property_length: int, object_inverse_length: int,
    data_property_length: int, datatype_length: int, data_one_of_length: int,
    data_complement_length: int, data_intersection_length: int, data_union_length: int)
    Length calculation of OWLClassExpression
```

Parameters

- `class_length` – Class: “C”
- `object_intersection_length` – Intersection: $A \sqcap B$
- `object_union_length` – Union: $A \sqcup B$
- `object_complement_length` – Complement: $\neg C$
- `object_some_values_length` – Obj. Some Values: $\exists r.C$
- `object_all_values_length` – Obj. All Values: $\forall r.C$
- `object_has_value_length` – Obj. Has Value: $\exists r.\{I\}$
- `object_cardinality_length` – Obj. Cardinality restriction: $\leq n r.C$
- `object_has_self_length` – Obj. Self restriction: $\exists r.\text{Self}$
- `object_one_of_length` – Obj. One of: $\exists r.\{X,Y,Z\}$
- `data_some_values_length` – Data Some Values: $\exists p.t$
- `data_all_values_length` – Data All Values: $\forall p.t$
- `data_has_value_length` – Data Has Value: $\exists p.\{V\}$
- `data_cardinality_length` – Data Cardinality restriction: $\leq n r.t$
- `object_property_length` – Obj. Property: $\exists r.C$
- `object_inverse_length` – Inverse property: $\exists r^{-}.C$
- `data_property_length` – Data Property: $\exists p.t$
- `datatype_length` – Datatype: $^{\wedge}\text{datatype}$
- `data_one_of_length` – Data One of: $\exists p.\{U,V,W\}$
- `data_complement_length` – Data Complement: $\neg\text{datatype}$
- `data_intersection_length` – Data Intersection: $\text{datatype} \sqcap \text{datatype}$
- `data_union_length` – Data Union: $\text{datatype} \sqcup \text{datatype}$

```
__slots__ = ('class_length', 'object_intersection_length',  
'object_union_length', ...)
```

```
class_length: int
```

```
object_intersection_length: int
```

```
object_union_length: int
```

```
object_complement_length: int
```

```
object_some_values_length: int
```

```
object_all_values_length: int
```

```
object_has_value_length: int
```

```
object_cardinality_length: int
```

```
object_has_self_length: int
```

```

object_one_of_length: int
data_some_values_length: int
data_all_values_length: int
data_has_value_length: int
data_cardinality_length: int
object_property_length: int
object_inverse_length: int
data_property_length: int
datatype_length: int
data_one_of_length: int
data_complement_length: int
data_intersection_length: int
data_union_length: int

static get_default() → OWLClassExpressionLengthMetric

abstract length(o: owlpy.owl_object.OWLObject) → int

```

owlapy.utils.measurer

owlapy.utils.get_expression_length(ce: owlpy.class_expression.OWLClassExpression) → int

```

class owlpy.utils.EvaluatedDescriptionSet (ordering: Callable[[_N], _O],
      max_size: int = 10)
    Bases: Generic[_N, _O]

```

Abstract base class for generic types.

A generic type is typically declared by inheriting from this class parameterized with one or more type variables. For example, a generic mapping type might be defined as:

```

class Mapping(Generic[KT, VT]):
    def __getitem__(self, key: KT) -> VT:
        ...
    # Etc.

```

This class can then be used as follows:

```

def lookup_name(mapping: Mapping[KT, VT], key: KT, default: VT) -> VT:
    try:
        return mapping[key]
    except KeyError:
        return default

```

```
__slots__ = ('items', '_max_size', '_Ordering')
```

```
items: SortedSet[_N]
```

```

maybe_add (node: _N)

clean ()

worst ()

best ()

best_quality_value () → float

__iter__ () → Iterable[_N]

class owlapy.utils.ConceptOperandSorter

    abstract sort (o: _O) → _O

class owlapy.utils.OperandSetTransform

    simplify (o: owlapy.class_expression.OWLClassExpression)
        → owlapy.class_expression.OWLClassExpression

class owlapy.utils.HasIndex
    Bases: Protocol

    Interface for types with an index; this is used to group objects by type when sorting.

    type_index: ClassVar[int]

    __eq__ (other)
        Return self==value.

class owlapy.utils.OrderedOWLObject (o: _HasIndex)
    Holder of OWL Objects that can be used for Python sorted.

    The Ordering is dependent on the type_index of the impl. classes recursively followed by all components of the
    OWL Object.

    o
        OWL object.

    __slots__ = ('o', '_chain')

    o: _HasIndex

    __lt__ (other)
        Return self<value.

    __eq__ (other)
        Return self==value.

class owlapy.utils.NNF
    This class contains functions to transform a Class Expression into Negation Normal Form.

    abstract get_class_nnf (ce: owlapy.class_expression.OWLClassExpression,
        negated: bool = False) → owlapy.class_expression.OWLClassExpression

    Convert a Class Expression to Negation Normal Form. Operands will be sorted.

    Parameters

    • ce – Class Expression.

    • negated – Whether the result should be negated.

```

Returns

Class Expression in Negation Normal Form.

class owlapy.utils.**TopLevelCNF**

This class contains functions to transform a class expression into Top-Level Conjunctive Normal Form.

get_top_level_cnf (*ce: owlapy.class_expression.OWLClassExpression*)
→ *owlapy.class_expression.OWLClassExpression*

Convert a class expression into Top-Level Conjunctive Normal Form. Operands will be sorted.

Parameters

ce – Class Expression.

Returns

Class Expression in Top-Level Conjunctive Normal Form.

class owlapy.utils.**TopLevelDNF**

This class contains functions to transform a class expression into Top-Level Disjunctive Normal Form.

get_top_level_dnf (*ce: owlapy.class_expression.OWLClassExpression*)
→ *owlapy.class_expression.OWLClassExpression*

Convert a class expression into Top-Level Disjunctive Normal Form. Operands will be sorted.

Parameters

ce – Class Expression.

Returns

Class Expression in Top-Level Disjunctive Normal Form.

owlapy.utils.**combine_nary_expressions** (*ce: owlapy.class_expression.OWLClassExpression*)
→ *owlapy.class_expression.OWLClassExpression*

owlapy.utils.**combine_nary_expressions** (*ce: owlapy.owl_data_ranges.OWLDataRange*)
→ *owlapy.owl_data_ranges.OWLDataRange*

Shortens an OWLClassExpression or OWLDataRange by combining all nested nary expressions of the same type. Operands will be sorted.

E.g. OWLObjectUnionOf(A, OWLObjectUnionOf(C, B)) -> OWLObjectUnionOf(A, B, C).

owlapy.utils.**iter_count** (*i: Iterable*) → int

Count the number of elements in an iterable.

owlapy.utils.**as_index** (*o: owlapy.owl_object.OWLObject*) → *HasIndex*

Cast OWL Object to HasIndex.

class owlapy.utils.**LRUCache** (*maxsize: int | None = None*)

Bases: *Generic[_K, _V]*

Constants shares by all lru cache instances.

Adapted from functools.lru_cache.

sentinel

Unique object used to signal cache misses.

PREV

Name for the link field 0.

NEXT

Name for the link field 1.

KEY

Name for the link field 2.

RESULT

Name for the link field 3.

sentinel

cache

full = False

cache_get

cache_len

lock

root = []

maxsize

__contains__ (*item: _K*) → bool

__getitem__ (*item: _K*) → _V

__setitem__ (*key: _K, value: _V*)

cache_info()

Report cache statistics.

cache_clear()

Clear the cache and cache statistics.

owlapy.vocab

Enumerations.

Classes

<i>OWLRFDFVocabulary</i>	Enumerations for OWL/RDF vocabulary.
<i>XSDVocabulary</i>	Enumerations for XSD vocabulary.
<i>OWLFacet</i>	Enumerations for OWL facets.

Module Contents

class owlapy.vocab.OWLRFDFVocabulary (*namespace: owlapy.namespaces.Namespaces,*
remainder: str)

Bases: _Vocabulary, enum.Enum

Enumerations for OWL/RDF vocabulary.

OWL_THING

```

OWL_NOTHING

OWL_CLASS

OWL_NAMED_INDIVIDUAL

OWL_TOP_OBJECT_PROPERTY

OWL_BOTTOM_OBJECT_PROPERTY

OWL_TOP_DATA_PROPERTY

OWL_BOTTOM_DATA_PROPERTY

RDFS_LITERAL

class owlapy.vocab.XSDVocabulary(remainder: str)
    Bases: _Vocabulary, enum.Enum
    Enumerations for XSD vocabulary.
    DECIMAL: Final = 'decimal'
    INTEGER: Final = 'integer'
    LONG: Final = 'long'
    DOUBLE: Final = 'double'
    FLOAT: Final = 'float'
    BOOLEAN: Final = 'boolean'
    STRING: Final = 'string'
    DATE: Final = 'date'
    DATE_TIME: Final = 'dateTime'
    DATE_TIME_STAMP: Final = 'dateTimeStamp'
    DURATION: Final = 'duration'

class owlapy.vocab.OWLFacet(remainder: str, symbolic_form: str,
                             operator: Callable[[_X, _X], bool])
    Bases: _Vocabulary, enum.Enum
    Enumerations for OWL facets.
    property symbolic_form
    property operator
    static from_str(name: str) → OWLFacet
    MIN_INCLUSIVE: Final
    MIN_EXCLUSIVE: Final
    MAX_INCLUSIVE: Final

```

```

MAX_EXCLUSIVE: Final

LENGTH: Final

MIN_LENGTH: Final

MAX_LENGTH: Final

PATTERN: Final

TOTAL_DIGITS: Final

FRACTION_DIGITS: Final

```

7.3 Attributes

```
__version__
```

7.4 Functions

<code>owl_expression_to_dl(→ str)</code>	
<code>owl_expression_to_manchester(→ str)</code>	
<code>dl_to_owl_expression(dl_expression, namespace)</code>	
<code>manchester_to_owl_expression(manchester_ex ...)</code>	
<code>owl_expression_to_sparql(→ str)</code>	Convert an OWL Class Expression (https://www.w3.org/TR/owl2-syntax/#Class_Expressions) into a SPARQL query

7.5 Package Contents

```

owlapy.owl_expression_to_dl(o: owlapy.owl_object.OWLObject) → str

owlapy.owl_expression_to_manchester(o: owlapy.owl_object.OWLObject) → str

owlapy.dl_to_owl_expression(dl_expression: str, namespace: str)

owlapy.manchester_to_owl_expression(manchester_expression: str, namespace: str)

owlapy.owl_expression_to_sparql(
    expression: owlapy.class_expression.OWLClassExpression = None, root_variable: str = '?x',
    values: Iterable[owlapy.owl_individual.OWLNamedIndividual] | None = None,
    for_all_de_morgan: bool = True, named_individuals: bool = False) → str

Convert an OWL Class Expression (https://www.w3.org/TR/owl2-syntax/#Class\_Expressions) into a SPARQL
query root variable: the variable that will be projected expression: the class expression to be transformed to a
SPARQL query

```

values: positive or negative examples from a class expression problem. Unclear for_all_de_morgan: if set to True, the SPARQL mapping will use the mapping containing the nested FILTER NOT EXISTS patterns for the universal quantifier ($\neg(\exists r. \neg C)$), instead of the counting query named_individuals: if set to True, the generated SPARQL query will return only entities that are instances of owl:NamedIndividual

```
owlapy.__version__ = '1.2.1'
```

Python Module Index

O

- `owlapy`, 15
- `owlapy.class_expression`, 15
- `owlapy.class_expression.class_expression`, 15
- `owlapy.class_expression.nary_boolean_expression`, 17
- `owlapy.class_expression.owl_class`, 19
- `owlapy.class_expression.restriction`, 20
- `owlapy.converter`, 48
- `owlapy.entities`, 48
- `owlapy.iri`, 51
- `owlapy.meta_classes`, 52
- `owlapy.namespaces`, 54
- `owlapy.owl_annotation`, 55
- `owlapy.owl_axiom`, 56
- `owlapy.owl_data_ranges`, 75
- `owlapy.owl_datatype`, 77
- `owlapy.owl_hierarchy`, 78
- `owlapy.owl_individual`, 82
- `owlapy.owl_literal`, 83
- `owlapy.owl_object`, 86
- `owlapy.owl_ontology`, 88
- `owlapy.owl_ontology_manager`, 96
- `owlapy.owl_property`, 99
- `owlapy.owl_reasoner`, 103
- `owlapy.owlapi_mapper`, 129
- `owlapy.parser`, 130
- `owlapy.providers`, 135
- `owlapy.render`, 136
- `owlapy.static_funcs`, 139
- `owlapy.utils`, 139
- `owlapy.vocab`, 145

Index

Non-alphabetical

`__contains__` () (owlapy.converter.VariablesMapping method), 49
`__contains__` () (owlapy.owl_hierarchy.AbstractHierarchy method), 80
`__contains__` () (owlapy.utils.LRUCache method), 145
`__eq__` () (owlapy.class_expression.class_expression.OwlObjectComplementOf method), 17
`__eq__` () (owlapy.class_expression.nary_boolean_expression.OwlNaryBooleanClassExpression method), 18
`__eq__` () (owlapy.class_expression.OwlDataAllValuesFrom method), 46
`__eq__` () (owlapy.class_expression.OwlDataCardinalityRestriction method), 41
`__eq__` () (owlapy.class_expression.OwlDataHasValue method), 46
`__eq__` () (owlapy.class_expression.OwlDataOneOf method), 40
`__eq__` () (owlapy.class_expression.OwlDataSomeValuesFrom method), 45
`__eq__` () (owlapy.class_expression.OwlDatatypeRestriction method), 43
`__eq__` () (owlapy.class_expression.OwlFacetRestriction method), 44
`__eq__` () (owlapy.class_expression.OwlHasValueRestriction method), 38
`__eq__` () (owlapy.class_expression.OwlNaryBooleanClassExpression method), 36
`__eq__` () (owlapy.class_expression.OwlObjectAllValuesFrom method), 42
`__eq__` () (owlapy.class_expression.OwlObjectCardinalityRestriction method), 39
`__eq__` () (owlapy.class_expression.OwlObjectComplementOf method), 35
`__eq__` () (owlapy.class_expression.OwlObjectHasSelf method), 40
`__eq__` () (owlapy.class_expression.OwlObjectOneOf method), 48
`__eq__` () (owlapy.class_expression.OwlObjectSomeValuesFrom method), 41
`__eq__` () (owlapy.class_expression.restriction.OwlDataAllValuesFrom method), 30
`__eq__` () (owlapy.class_expression.restriction.OwlDataCardinalityRestriction method), 28
`__eq__` () (owlapy.class_expression.restriction.OwlDataHasValue method), 30
`__eq__` () (owlapy.class_expression.restriction.OwlDataOneOf method), 31
`__eq__` () (owlapy.class_expression.restriction.OwlDataSomeValuesFrom method), 29
`__eq__` () (owlapy.class_expression.restriction.OwlDatatypeRestriction method), 32
`__eq__` () (owlapy.class_expression.restriction.OwlFacetRestriction method), 32
`__eq__` () (owlapy.class_expression.restriction.OwlHasValueRestriction method), 22
`__eq__` () (owlapy.class_expression.restriction.OwlObjectAllValuesFrom method), 26
`__eq__` () (owlapy.class_expression.restriction.OwlObjectCardinalityRestriction method), 24
`__eq__` () (owlapy.class_expression.restriction.OwlObjectHasSelf method), 26
`__eq__` () (owlapy.class_expression.restriction.OwlObjectOneOf method), 27
`__eq__` () (owlapy.class_expression.restriction.OwlObjectSomeValuesFrom method), 25
`__eq__` () (owlapy.iri.IRI method), 51
`__eq__` () (owlapy.namespaces.Namespaces method), 54
`__eq__` () (owlapy.owl_axiom.OwlAnnotation method), 67
`__eq__` () (owlapy.owl_axiom.OwlAnnotationAssertionAxiom method), 67
`__eq__` () (owlapy.owl_axiom.OwlAnnotationPropertyDomainAxiom method), 68
`__eq__` () (owlapy.owl_axiom.OwlAnnotationPropertyRangeAxiom method), 69
`__eq__` () (owlapy.owl_axiom.OwlClassAssertionAxiom method), 66
`__eq__` () (owlapy.owl_axiom.OwlDataPropertyCharacteristicAxiom method), 73
`__eq__` () (owlapy.owl_axiom.OwlDatatypeDefinitionAxiom method), 60
`__eq__` () (owlapy.owl_axiom.OwlDeclarationAxiom method), 59
`__eq__` () (owlapy.owl_axiom.OwlDisjointUnionAxiom method), 65
`__eq__` () (owlapy.owl_axiom.OwlHasKeyAxiom method), 60
`__eq__` () (owlapy.owl_axiom.OwlNaryClassAxiom method), 61
`__eq__` () (owlapy.owl_axiom.OwlNaryIndividualAxiom method), 62
`__eq__` () (owlapy.owl_axiom.OwlNaryPropertyAxiom method), 63
`__eq__` () (owlapy.owl_axiom.OwlObjectPropertyCharacteristicAxiom method), 71
`__eq__` () (owlapy.owl_axiom.OwlPropertyAssertionAxiom method), 70
`__eq__` () (owlapy.owl_axiom.OwlPropertyDomainAxiom method), 74
`__eq__` () (owlapy.owl_axiom.OwlPropertyRangeAxiom method), 74
`__eq__` () (owlapy.owl_axiom.OwlSubAnnotationPropertyOfAxiom method), 68
`__eq__` () (owlapy.owl_axiom.OwlSubClassOfAxiom method), 65
`__eq__` () (owlapy.owl_axiom.OwlSubPropertyAxiom method), 69
`__eq__` () (owlapy.owl_data_ranges.OwlDataComplementOf method), 77
`__eq__` () (owlapy.owl_data_ranges.OwlNaryDataRange method), 76
`__eq__` () (owlapy.owl_object.OwlNamedObject method), 87
`__eq__` () (owlapy.owl_object.OwlObject method), 86
`__eq__` () (owlapy.owl_ontology.Ontology method), 93
`__eq__` () (owlapy.owl_ontology.OwlOntologyID method), 89
`__eq__` () (owlapy.owl_ontology.SyncOntology method), 96
`__eq__` () (owlapy.owl_property.OwlObjectInverseOf method), 102

__eq__() (owlapy.utils.HasIndex method), 143
 __eq__() (owlapy.utils.OrderedOWLObject method), 143
 __getitem__() (owlapy.converter.VariablesMapping method), 49
 __getitem__() (owlapy.utils.LRUCache method), 145
 __hash__() (owlapy.class_expression.class_expression.OWLObjectComplementOf method), 17
 __hash__() (owlapy.class_expression.nary_boolean_expression.OWLNaryBooleanClassExpression method), 18
 __hash__() (owlapy.class_expression.OWLDataAllValuesFrom method), 46
 __hash__() (owlapy.class_expression.OWLDataCardinalityRestriction method), 41
 __hash__() (owlapy.class_expression.OWLDataHasValue method), 46
 __hash__() (owlapy.class_expression.OWLDataOneOf method), 40
 __hash__() (owlapy.class_expression.OWLDataSomeValuesFrom method), 45
 __hash__() (owlapy.class_expression.OWLDatatypeRestriction method), 43
 __hash__() (owlapy.class_expression.OWLFacetRestriction method), 44
 __hash__() (owlapy.class_expression.OWLHasValueRestriction method), 38
 __hash__() (owlapy.class_expression.OWLNaryBooleanClassExpression method), 36
 __hash__() (owlapy.class_expression.OWLObjectAllValuesFrom method), 42
 __hash__() (owlapy.class_expression.OWLObjectCardinalityRestriction method), 39
 __hash__() (owlapy.class_expression.OWLObjectComplementOf method), 35
 __hash__() (owlapy.class_expression.OWLObjectHasSelf method), 40
 __hash__() (owlapy.class_expression.OWLObjectOneOf method), 48
 __hash__() (owlapy.class_expression.OWLObjectSomeValuesFrom method), 41
 __hash__() (owlapy.class_expression.restriction.OWLDataAllValuesFrom method), 30
 __hash__() (owlapy.class_expression.restriction.OWLDataCardinalityRestriction method), 28
 __hash__() (owlapy.class_expression.restriction.OWLDataHasValue method), 30
 __hash__() (owlapy.class_expression.restriction.OWLDataOneOf method), 31
 __hash__() (owlapy.class_expression.restriction.OWLDataSomeValuesFrom method), 29
 __hash__() (owlapy.class_expression.restriction.OWLDatatypeRestriction method), 32
 __hash__() (owlapy.class_expression.restriction.OWLFacetRestriction method), 32
 __hash__() (owlapy.class_expression.restriction.OWLHasValueRestriction method), 22
 __hash__() (owlapy.class_expression.restriction.OWLObjectAllValuesFrom method), 26
 __hash__() (owlapy.class_expression.restriction.OWLObjectCardinalityRestriction method), 24
 __hash__() (owlapy.class_expression.restriction.OWLObjectHasSelf method), 26
 __hash__() (owlapy.class_expression.restriction.OWLObjectOneOf method), 27
 __hash__() (owlapy.class_expression.restriction.OWLObjectSomeValuesFrom method), 25
 __hash__() (owlapy.iri.IRI method), 51
 __hash__() (owlapy.namespaces.Namespaces method), 54
 __hash__() (owlapy.owl_axiom.OWLAnnotation method), 67
 __hash__() (owlapy.owl_axiom.OWLAnnotationAssertionAxiom method), 67
 __hash__() (owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom method), 68
 __hash__() (owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom method), 69
 __hash__() (owlapy.owl_axiom.OWLClassAssertionAxiom method), 66
 __hash__() (owlapy.owl_axiom.OWLDataPropertyCharacteristicAxiom method), 73
 __hash__() (owlapy.owl_axiom.OWLDatatypeDefinitionAxiom method), 60
 __hash__() (owlapy.owl_axiom.OWLDeclarationAxiom method), 59
 __hash__() (owlapy.owl_axiom.OWLDisjointUnionAxiom method), 65
 __hash__() (owlapy.owl_axiom.OWLHasKeyAxiom method), 60
 __hash__() (owlapy.owl_axiom.OWLNaryClassAxiom method), 61
 __hash__() (owlapy.owl_axiom.OWLNaryIndividualAxiom method), 62
 __hash__() (owlapy.owl_axiom.OWLNaryPropertyAxiom method), 63
 __hash__() (owlapy.owl_axiom.OWLObjectPropertyCharacteristicAxiom method), 71
 __hash__() (owlapy.owl_axiom.OWLPropertyAssertionAxiom method), 70
 __hash__() (owlapy.owl_axiom.OWLPropertyDomainAxiom method), 74
 __hash__() (owlapy.owl_axiom.OWLPropertyRangeAxiom method), 74
 __hash__() (owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom method), 68
 __hash__() (owlapy.owl_axiom.OWLSubClassOfAxiom method), 65
 __hash__() (owlapy.owl_axiom.OWLSubPropertyAxiom method), 69
 __hash__() (owlapy.owl_data_ranges.OWLDataComplementOf method), 77
 __hash__() (owlapy.owl_data_ranges.OWLNaryDataRange method), 76
 __hash__() (owlapy.owl_object.OWLNamedObject method), 87
 __hash__() (owlapy.owl_object.OWLObject method), 86
 __hash__() (owlapy.owl_ontology.Ontology method), 94
 __hash__() (owlapy.owl_ontology.SyncOntology method), 96
 __hash__() (owlapy.owl_property.OWLObjectInverseOf method), 102
 __iter__() (owlapy.utils.EvaluatedDescriptionSet method), 143
 __len__() (owlapy.owl_hierarchy.AbstractHierarchy method), 80
 __lt__() (owlapy.owl_object.OWLNamedObject method), 87
 __lt__() (owlapy.utils.OrderedOWLObject method), 143
 __repr__() (owlapy.class_expression.class_expression.OWLObjectComplementOf method), 17

`__repr__()` (`owlapy.class_expression.nary_boolean_expression.OWLNaryBooleanClassExpression` method), 18
`__repr__()` (`owlapy.class_expression.OWLDataAllValuesFrom` method), 46
`__repr__()` (`owlapy.class_expression.OWLDataCardinalityRestriction` method), 41
`__repr__()` (`owlapy.class_expression.OWLDataHasValue` method), 46
`__repr__()` (`owlapy.class_expression.OWLDataOneOf` method), 40
`__repr__()` (`owlapy.class_expression.OWLDataSomeValuesFrom` method), 45
`__repr__()` (`owlapy.class_expression.OWLDatatypeRestriction` method), 43
`__repr__()` (`owlapy.class_expression.OWLFacetRestriction` method), 44
`__repr__()` (`owlapy.class_expression.OWLNaryBooleanClassExpression` method), 36
`__repr__()` (`owlapy.class_expression.OWLObjectAllValuesFrom` method), 42
`__repr__()` (`owlapy.class_expression.OWLObjectCardinalityRestriction` method), 39
`__repr__()` (`owlapy.class_expression.OWLObjectComplementOf` method), 35
`__repr__()` (`owlapy.class_expression.OWLObjectHasSelf` method), 40
`__repr__()` (`owlapy.class_expression.OWLObjectHasValue` method), 42
`__repr__()` (`owlapy.class_expression.OWLObjectOneOf` method), 48
`__repr__()` (`owlapy.class_expression.OWLObjectSomeValuesFrom` method), 41
`__repr__()` (`owlapy.class_expression.restriction.OWLDataAllValuesFrom` method), 30
`__repr__()` (`owlapy.class_expression.restriction.OWLDataCardinalityRestriction` method), 28
`__repr__()` (`owlapy.class_expression.restriction.OWLDataHasValue` method), 30
`__repr__()` (`owlapy.class_expression.restriction.OWLDataOneOf` method), 31
`__repr__()` (`owlapy.class_expression.restriction.OWLDataSomeValuesFrom` method), 29
`__repr__()` (`owlapy.class_expression.restriction.OWLDatatypeRestriction` method), 32
`__repr__()` (`owlapy.class_expression.restriction.OWLFacetRestriction` method), 32
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectAllValuesFrom` method), 26
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectCardinalityRestriction` method), 24
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectHasSelf` method), 26
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectHasValue` method), 27
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectOneOf` method), 27
`__repr__()` (`owlapy.class_expression.restriction.OWLObjectSomeValuesFrom` method), 25
`__repr__()` (`owlapy.iri.IRI` method), 51
`__repr__()` (`owlapy.namespaces.Namespaces` method), 54
`__repr__()` (`owlapy.owl_axiom.OWLAnnotation` method), 67
`__repr__()` (`owlapy.owl_axiom.OWLAnnotationAssertionAxiom` method), 67
`__repr__()` (`owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom` method), 68
`__repr__()` (`owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom` method), 69
`__repr__()` (`owlapy.owl_axiom.OWLClassAssertionAxiom` method), 66
`__repr__()` (`owlapy.owl_axiom.OWLDataPropertyCharacteristicAxiom` method), 73
`__repr__()` (`owlapy.owl_axiom.OWLDatatypeDefinitionAxiom` method), 60
`__repr__()` (`owlapy.owl_axiom.OWLDeclarationAxiom` method), 59
`__repr__()` (`owlapy.owl_axiom.OWLDisjointUnionAxiom` method), 65
`__repr__()` (`owlapy.owl_axiom.OWLHasKeyAxiom` method), 60
`__repr__()` (`owlapy.owl_axiom.OWLInverseObjectPropertiesAxiom` method), 64
`__repr__()` (`owlapy.owl_axiom.OWLNaryClassAxiom` method), 61
`__repr__()` (`owlapy.owl_axiom.OWLNaryIndividualAxiom` method), 62
`__repr__()` (`owlapy.owl_axiom.OWLNaryPropertyAxiom` method), 63
`__repr__()` (`owlapy.owl_axiom.OWLObjectPropertyCharacteristicAxiom` method), 71
`__repr__()` (`owlapy.owl_axiom.OWLPropertyAssertionAxiom` method), 70
`__repr__()` (`owlapy.owl_axiom.OWLPropertyDomainAxiom` method), 74
`__repr__()` (`owlapy.owl_axiom.OWLPropertyRangeAxiom` method), 74
`__repr__()` (`owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom` method), 68
`__repr__()` (`owlapy.owl_axiom.OWLSubClassOfAxiom` method), 65
`__repr__()` (`owlapy.owl_axiom.OWLSubPropertyAxiom` method), 69
`__repr__()` (`owlapy.owl_data_ranges.OWLDataComplementOf` method), 77
`__repr__()` (`owlapy.owl_data_ranges.OWLNaryDataRange` method), 76
`__repr__()` (`owlapy.owl_object.OWLNamedObject` method), 87
`__repr__()` (`owlapy.owl_object.OWLObject` method), 87
`__repr__()` (`owlapy.owl_ontology.Ontology` method), 94
`__repr__()` (`owlapy.owl_ontology.OWLOntologyID` method), 89
`__repr__()` (`owlapy.owl_ontology.SyncOntology` method), 96
`__repr__()` (`owlapy.owl_property.OWLObjectInverseOf` method), 102
`__setitem__()` (`owlapy.utils.LRUCache` method), 145
`__slots__` (`owlapy.class_expression.class_expression.OWLBooleanClassExpression` attribute), 17
`__slots__` (`owlapy.class_expression.class_expression.OWLClassExpression` attribute), 16
`__slots__` (`owlapy.class_expression.class_expression.OWLObjectComplementOf` attribute), 17
`__slots__` (`owlapy.class_expression.nary_boolean_expression.OWLNaryBooleanClassExpression` attribute), 18
`__slots__` (`owlapy.class_expression.nary_boolean_expression.OWLObjectIntersectionOf` attribute), 18
`__slots__` (`owlapy.class_expression.nary_boolean_expression.OWLObjectUnionOf` attribute), 18
`__slots__` (`owlapy.class_expression.owl_class.OWLClass` attribute), 19

- __slots__ (owlapy.class_expression.OWLBooleanClassExpression attribute), 35
- __slots__ (owlapy.class_expression.OWLCardinalityRestriction attribute), 39
- __slots__ (owlapy.class_expression.OWLClass attribute), 35
- __slots__ (owlapy.class_expression.OWLClassExpression attribute), 34
- __slots__ (owlapy.class_expression.OWLDataAllValuesFrom attribute), 46
- __slots__ (owlapy.class_expression.OWLDataCardinalityRestriction attribute), 41
- __slots__ (owlapy.class_expression.OWLDataExactCardinality attribute), 47
- __slots__ (owlapy.class_expression.OWLDataHasValue attribute), 46
- __slots__ (owlapy.class_expression.OWLDataMaxCardinality attribute), 47
- __slots__ (owlapy.class_expression.OWLDataMinCardinality attribute), 46
- __slots__ (owlapy.class_expression.OWLDataRestriction attribute), 39
- __slots__ (owlapy.class_expression.OWLDataSomeValuesFrom attribute), 45
- __slots__ (owlapy.class_expression.OWLDatatypeRestriction attribute), 43
- __slots__ (owlapy.class_expression.OWLFacetRestriction attribute), 44
- __slots__ (owlapy.class_expression.OWLHasValueRestriction attribute), 38
- __slots__ (owlapy.class_expression.OWLNaryBooleanClassExpression attribute), 36
- __slots__ (owlapy.class_expression.OWLObjectAllValuesFrom attribute), 42
- __slots__ (owlapy.class_expression.OWLObjectCardinalityRestriction attribute), 39
- __slots__ (owlapy.class_expression.OWLObjectComplementOf attribute), 35
- __slots__ (owlapy.class_expression.OWLObjectExactCardinality attribute), 45
- __slots__ (owlapy.class_expression.OWLObjectHasSelf attribute), 40
- __slots__ (owlapy.class_expression.OWLObjectHasValue attribute), 42
- __slots__ (owlapy.class_expression.OWLObjectIntersectionOf attribute), 37
- __slots__ (owlapy.class_expression.OWLObjectMaxCardinality attribute), 44
- __slots__ (owlapy.class_expression.OWLObjectMinCardinality attribute), 44
- __slots__ (owlapy.class_expression.OWLObjectOneOf attribute), 47
- __slots__ (owlapy.class_expression.OWLObjectRestriction attribute), 38
- __slots__ (owlapy.class_expression.OWLObjectSomeValuesFrom attribute), 41
- __slots__ (owlapy.class_expression.OWLObjectUnionOf attribute), 37
- __slots__ (owlapy.class_expression.OWLQuantifiedDataRestriction attribute), 41
- __slots__ (owlapy.class_expression.OWLQuantifiedObjectRestriction attribute), 38
- __slots__ (owlapy.class_expression.OWLQuantifiedRestriction attribute), 37
- __slots__ (owlapy.class_expression.OWLRestriction attribute), 37
- __slots__ (owlapy.class_expression.restriction.OWLCardinalityRestriction attribute), 23
- __slots__ (owlapy.class_expression.restriction.OWLDataAllValuesFrom attribute), 30
- __slots__ (owlapy.class_expression.restriction.OWLDataCardinalityRestriction attribute), 28
- __slots__ (owlapy.class_expression.restriction.OWLDataExactCardinality attribute), 29
- __slots__ (owlapy.class_expression.restriction.OWLDataHasValue attribute), 30
- __slots__ (owlapy.class_expression.restriction.OWLDataMaxCardinality attribute), 29
- __slots__ (owlapy.class_expression.restriction.OWLDataMinCardinality attribute), 28
- __slots__ (owlapy.class_expression.restriction.OWLDataRestriction attribute), 27
- __slots__ (owlapy.class_expression.restriction.OWLDataSomeValuesFrom attribute), 29
- __slots__ (owlapy.class_expression.restriction.OWLDatatypeRestriction attribute), 31
- __slots__ (owlapy.class_expression.restriction.OWLFacetRestriction attribute), 32
- __slots__ (owlapy.class_expression.restriction.OWLHasValueRestriction attribute), 22
- __slots__ (owlapy.class_expression.restriction.OWLObjectAllValuesFrom attribute), 25
- __slots__ (owlapy.class_expression.restriction.OWLObjectCardinalityRestriction attribute), 24
- __slots__ (owlapy.class_expression.restriction.OWLObjectExactCardinality attribute), 25
- __slots__ (owlapy.class_expression.restriction.OWLObjectHasSelf attribute), 26
- __slots__ (owlapy.class_expression.restriction.OWLObjectHasValue attribute), 26
- __slots__ (owlapy.class_expression.restriction.OWLObjectMaxCardinality attribute), 24
- __slots__ (owlapy.class_expression.restriction.OWLObjectMinCardinality attribute), 24
- __slots__ (owlapy.class_expression.restriction.OWLObjectOneOf attribute), 27
- __slots__ (owlapy.class_expression.restriction.OWLObjectRestriction attribute), 22
- __slots__ (owlapy.class_expression.restriction.OWLObjectSomeValuesFrom attribute), 25
- __slots__ (owlapy.class_expression.restriction.OWLQuantifiedDataRestriction attribute), 28
- __slots__ (owlapy.class_expression.restriction.OWLQuantifiedObjectRestriction attribute), 23
- __slots__ (owlapy.class_expression.restriction.OWLQuantifiedRestriction attribute), 23
- __slots__ (owlapy.class_expression.restriction.OWLRestriction attribute), 22
- __slots__ (owlapy.converter.Owl2SparqlConverter attribute), 49
- __slots__ (owlapy.converter.VariablesMapping attribute), 49
- __slots__ (owlapy.iri.IRI attribute), 51
- __slots__ (owlapy.meta_classes.HasCardinality attribute), 53
- __slots__ (owlapy.meta_classes.HasFiller attribute), 53
- __slots__ (owlapy.meta_classes.HasIRI attribute), 53
- __slots__ (owlapy.meta_classes.HasOperands attribute), 53
- __slots__ (owlapy.namespaces.Namespaces attribute), 54
- __slots__ (owlapy.owl_annotation.OWLAnnotationObject attribute), 55

__slots__ (owlapy.owl_annotation.OWLAnnotationSubject attribute), 55
 __slots__ (owlapy.owl_annotation.OWLAnnotationValue attribute), 55
 __slots__ (owlapy.owl_axiom.OWLAnnotation attribute), 66
 __slots__ (owlapy.owl_axiom.OWLAnnotationAssertionAxiom attribute), 67
 __slots__ (owlapy.owl_axiom.OWLAnnotationAxiom attribute), 67
 __slots__ (owlapy.owl_axiom.OWLAnnotationProperty attribute), 66
 __slots__ (owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom attribute), 68
 __slots__ (owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom attribute), 68
 __slots__ (owlapy.owl_axiom.OWLAsymmetricObjectPropertyAxiom attribute), 72
 __slots__ (owlapy.owl_axiom.OWLAxiom attribute), 58
 __slots__ (owlapy.owl_axiom.OWLClassAssertionAxiom attribute), 66
 __slots__ (owlapy.owl_axiom.OWLClassAxiom attribute), 59
 __slots__ (owlapy.owl_axiom.OWLDataPropertyAssertionAxiom attribute), 71
 __slots__ (owlapy.owl_axiom.OWLDataPropertyAxiom attribute), 59
 __slots__ (owlapy.owl_axiom.OWLDataPropertyCharacteristicAxiom attribute), 73
 __slots__ (owlapy.owl_axiom.OWLDataPropertyDomainAxiom attribute), 75
 __slots__ (owlapy.owl_axiom.OWLDataPropertyRangeAxiom attribute), 75
 __slots__ (owlapy.owl_axiom.OWLDatatypeDefinitionAxiom attribute), 60
 __slots__ (owlapy.owl_axiom.OWLDeclarationAxiom attribute), 59
 __slots__ (owlapy.owl_axiom.OWLDifferentIndividualsAxiom attribute), 62
 __slots__ (owlapy.owl_axiom.OWLDisjointClassesAxiom attribute), 62
 __slots__ (owlapy.owl_axiom.OWLDisjointDataPropertiesAxiom attribute), 64
 __slots__ (owlapy.owl_axiom.OWLDisjointObjectPropertiesAxiom attribute), 64
 __slots__ (owlapy.owl_axiom.OWLDisjointUnionAxiom attribute), 65
 __slots__ (owlapy.owl_axiom.OWLEquivalentClassesAxiom attribute), 61
 __slots__ (owlapy.owl_axiom.OWLEquivalentDataPropertiesAxiom attribute), 64
 __slots__ (owlapy.owl_axiom.OWLEquivalentObjectPropertiesAxiom attribute), 63
 __slots__ (owlapy.owl_axiom.OWLFunctionalDataPropertyAxiom attribute), 73
 __slots__ (owlapy.owl_axiom.OWLFunctionalObjectPropertyAxiom attribute), 72
 __slots__ (owlapy.owl_axiom.OWLHasKeyAxiom attribute), 60
 __slots__ (owlapy.owl_axiom.OWLIndividualAxiom attribute), 59
 __slots__ (owlapy.owl_axiom.OWLInverseFunctionalObjectPropertyAxiom attribute), 72
 __slots__ (owlapy.owl_axiom.OWLInverseObjectPropertiesAxiom attribute), 64
 __slots__ (owlapy.owl_axiom.OWLIrreflexiveObjectPropertyAxiom attribute), 72
 __slots__ (owlapy.owl_axiom.OWLLogicalAxiom attribute), 58
 __slots__ (owlapy.owl_axiom.OWLNaryAxiom attribute), 61
 __slots__ (owlapy.owl_axiom.OWLNaryClassAxiom attribute), 61
 __slots__ (owlapy.owl_axiom.OWLNaryIndividualAxiom attribute), 62
 __slots__ (owlapy.owl_axiom.OWLNaryPropertyAxiom attribute), 63
 __slots__ (owlapy.owl_axiom.OWLNegativeDataPropertyAssertionAxiom attribute), 71
 __slots__ (owlapy.owl_axiom.OWLNegativeObjectPropertyAssertionAxiom attribute), 70
 __slots__ (owlapy.owl_axiom.OWLObjectPropertyAssertionAxiom attribute), 70
 __slots__ (owlapy.owl_axiom.OWLObjectPropertyAxiom attribute), 59
 __slots__ (owlapy.owl_axiom.OWLObjectPropertyCharacteristicAxiom attribute), 71
 __slots__ (owlapy.owl_axiom.OWLObjectPropertyDomainAxiom attribute), 74
 __slots__ (owlapy.owl_axiom.OWLObjectPropertyRangeAxiom attribute), 75
 __slots__ (owlapy.owl_axiom.OWLPropertyAssertionAxiom attribute), 70
 __slots__ (owlapy.owl_axiom.OWLPropertyAxiom attribute), 58
 __slots__ (owlapy.owl_axiom.OWLPropertyDomainAxiom attribute), 74
 __slots__ (owlapy.owl_axiom.OWLPropertyRangeAxiom attribute), 74
 __slots__ (owlapy.owl_axiom.OWLReflexiveObjectPropertyAxiom attribute), 72
 __slots__ (owlapy.owl_axiom.OWLSameIndividualAxiom attribute), 63
 __slots__ (owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom attribute), 68
 __slots__ (owlapy.owl_axiom.OWLSubClassOfAxiom attribute), 65
 __slots__ (owlapy.owl_axiom.OWLSubDataPropertyOfAxiom attribute), 70
 __slots__ (owlapy.owl_axiom.OWLSubObjectPropertyOfAxiom attribute), 69
 __slots__ (owlapy.owl_axiom.OWLSubPropertyAxiom attribute), 69
 __slots__ (owlapy.owl_axiom.OWLSymmetricObjectPropertyAxiom attribute), 73
 __slots__ (owlapy.owl_axiom.OWLTransitiveObjectPropertyAxiom attribute), 73
 __slots__ (owlapy.owl_axiom.OWLUnaryPropertyAxiom attribute), 71
 __slots__ (owlapy.owl_data_ranges.OWLDataIntersectionOf attribute), 76
 __slots__ (owlapy.owl_data_ranges.OWLDataUnionOf attribute), 77
 __slots__ (owlapy.owl_data_ranges.OWLNaryDataRange attribute), 76
 __slots__ (owlapy.owl_datatype.OWLDatatype attribute), 78
 __slots__ (owlapy.owl_hierarchy.AbstractHierarchy attribute), 79
 __slots__ (owlapy.owl_individual.OWLIndividual attribute), 82
 __slots__ (owlapy.owl_individual.OWLNamedIndividual attribute), 82
 __slots__ (owlapy.owl_literal.OWLLiteral attribute), 84

- `__slots__` (*owlapy.owl_object.OWLEntity attribute*), 87
- `__slots__` (*owlapy.owl_object.OWLNamedObject attribute*), 87
- `__slots__` (*owlapy.owl_object.OWLObject attribute*), 86
- `__slots__` (*owlapy.owl_ontology_manager.AddImport attribute*), 98
- `__slots__` (*owlapy.owl_ontology_manager.OntologyManager attribute*), 98
- `__slots__` (*owlapy.owl_ontology_manager.OWLImportsDeclaration attribute*), 98
- `__slots__` (*owlapy.owl_ontology_manager.OWLOntologyChange attribute*), 97
- `__slots__` (*owlapy.owl_ontology.FromOwlready2 attribute*), 96
- `__slots__` (*owlapy.owl_ontology.Ontology attribute*), 91
- `__slots__` (*owlapy.owl_ontology.OWLOntology attribute*), 89
- `__slots__` (*owlapy.owl_ontology.OWLOntologyID attribute*), 88
- `__slots__` (*owlapy.owl_ontology.ToOwlready2 attribute*), 96
- `__slots__` (*owlapy.owl_property.OWLDataProperty attribute*), 102
- `__slots__` (*owlapy.owl_property.OWLDataPropertyExpression attribute*), 101
- `__slots__` (*owlapy.owl_property.OWLObjectInverseOf attribute*), 102
- `__slots__` (*owlapy.owl_property.OWLObjectProperty attribute*), 101
- `__slots__` (*owlapy.owl_property.OWLObjectPropertyExpression attribute*), 100
- `__slots__` (*owlapy.owl_property.OWLProperty attribute*), 101
- `__slots__` (*owlapy.owl_property.OWLPropertyExpression attribute*), 100
- `__slots__` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner attribute*), 116
- `__slots__` (*owlapy.owl_reasoner.OntologyReasoner attribute*), 110
- `__slots__` (*owlapy.owl_reasoner.OWLReasoner attribute*), 103
- `__slots__` (*owlapy.render.DLSyntaxObjectRenderer attribute*), 138
- `__slots__` (*owlapy.render.ManchesterOWLSyntaxOWLObjectRenderer attribute*), 138
- `__slots__` (*owlapy.utils.EvaluatedDescriptionSet attribute*), 142
- `__slots__` (*owlapy.utils.OrderedOWLObject attribute*), 143
- `__slots__` (*owlapy.utils.OWLClassExpressionLengthMetric attribute*), 141
- `__version__` (*in module owlapy*), 148

A

- `AbstractHierarchy` (*class in owlapy.owl_hierarchy*), 78
- `add_axiom()` (*owlapy.owl_ontology.Ontology method*), 93
- `add_axiom()` (*owlapy.owl_ontology.OWLOntology method*), 91
- `AddImport` (*class in owlapy.owl_ontology_manager*), 98
- `all_data_property_values()` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 119
- `all_data_property_values()` (*owlapy.owl_reasoner.OntologyReasoner method*), 112
- `all_data_property_values()` (*owlapy.owl_reasoner.OWLReasonerEx method*), 109
- `annotations()` (*owlapy.owl_axiom.OWLAxiom method*), 58
- `append()` (*owlapy.converter.Owl2SparqlConverter method*), 50
- `append_triple()` (*owlapy.converter.Owl2SparqlConverter method*), 50
- `apply_change()` (*owlapy.owl_ontology_manager.OntologyManager method*), 99
- `apply_change()` (*owlapy.owl_ontology_manager.OWLOntologyManager method*), 97
- `as_anonymous_individual()` (*owlapy.owl_annotation.OWLAnnotationObject method*), 55
- `as_index()` (*in module owlapy.utils*), 144
- `as_intersection_of_min_max()` (*owlapy.class_expression.OWLDataExactCardinality method*), 47
- `as_intersection_of_min_max()` (*owlapy.class_expression.OWLObjectExactCardinality method*), 45
- `as_intersection_of_min_max()` (*owlapy.class_expression.restriction.OWLDataExactCardinality method*), 29
- `as_intersection_of_min_max()` (*owlapy.class_expression.restriction.OWLObjectExactCardinality method*), 25
- `as_iri()` (*owlapy.iri.IRI method*), 52
- `as_iri()` (*owlapy.owl_annotation.OWLAnnotationObject method*), 55
- `as_literal()` (*owlapy.owl_annotation.OWLAnnotationValue method*), 55
- `as_literal()` (*owlapy.owl_literal.OWLLiteral method*), 85
- `as_object_union_of()` (*owlapy.class_expression.OWLObjectOneOf method*), 48
- `as_object_union_of()` (*owlapy.class_expression.restriction.OWLObjectOneOf method*), 27
- `as_pairwise_axioms()` (*owlapy.owl_axiom.OWLNaryAxiom method*), 61
- `as_pairwise_axioms()` (*owlapy.owl_axiom.OWLNaryClassAxiom method*), 61
- `as_pairwise_axioms()` (*owlapy.owl_axiom.OWLNaryIndividualAxiom method*), 62
- `as_pairwise_axioms()` (*owlapy.owl_axiom.OWLNaryPropertyAxiom method*), 63
- `as_query()` (*owlapy.converter.Owl2SparqlConverter method*), 50
- `as_some_values_from()` (*owlapy.class_expression.OWLDataHasValue method*), 46
- `as_some_values_from()` (*owlapy.class_expression.OWLObjectHasValue method*), 42
- `as_some_values_from()` (*owlapy.class_expression.restriction.OWLDataHasValue method*), 31
- `as_some_values_from()` (*owlapy.class_expression.restriction.OWLObjectHasValue method*), 26
- `as_str()` (*owlapy.iri.IRI method*), 52

B

- `best()` (*owlapy.utils.EvaluatedDescriptionSet method*), 143

best_quality_value() (owlapy.utils.EvaluatedDescriptionSet method), 143
 bidi_provider (owlapy.owlapi_mapper.OWLAPIMapper attribute), 130
 BOOLEAN (owlapy.vocab.XSDVocabulary attribute), 146
 BooleanOWLDatatype (in module owlapy.owl_literal), 86

C

cache (owlapy.utils.LRUCache attribute), 145
 cache_clear() (owlapy.utils.LRUCache method), 145
 cache_get (owlapy.utils.LRUCache attribute), 145
 cache_info() (owlapy.utils.LRUCache method), 145
 cache_len (owlapy.utils.LRUCache attribute), 145
 ce (owlapy.converter.Owl2SparqlConverter attribute), 49
 children() (owlapy.owl_hierarchy.AbstractHierarchy method), 80
 class_cnt (owlapy.converter.VariablesMapping attribute), 49
 class_expressions() (owlapy.owl_axiom.OWLNaryClassAxiom method), 61
 class_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 classes_in_signature() (owlapy.owl_ontology.Ontology method), 92
 classes_in_signature() (owlapy.owl_ontology.OWLOntology method), 89
 classes_in_signature() (owlapy.owl_ontology.SyncOntology method), 94
 ClassHierarchy (class in owlapy.owl_hierarchy), 80
 clean() (owlapy.utils.EvaluatedDescriptionSet method), 143
 cnt (owlapy.converter.Owl2SparqlConverter attribute), 50
 combine_nary_expressions() (in module owlapy.utils), 144
 ConceptOperandSorter (class in owlapy.utils), 143
 contains_named_equivalent_class() (owlapy.owl_axiom.OWLEquivalentClassesAxiom method), 61
 contains_owl_nothing() (owlapy.owl_axiom.OWLEquivalentClassesAxiom method), 61
 contains_owl_thing() (owlapy.owl_axiom.OWLEquivalentClassesAxiom method), 62
 convert() (owlapy.converter.Owl2SparqlConverter method), 50
 converter (in module owlapy.converter), 50
 create() (owlapy.iri.IRI static method), 51
 create_ontology() (owlapy.owl_ontology_manager.OntologyManager method), 98
 create_ontology() (owlapy.owl_ontology_manager.OWLOntologyManager method), 97
 create_ontology() (owlapy.owl_ontology_manager.SyncOntologyManager method), 99
 current_variable (owlapy.converter.Owl2SparqlConverter property), 50

D

data_all_values_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_cardinality_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_complement_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_has_value_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_intersection_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_one_of_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_properties_in_signature() (owlapy.owl_ontology.Ontology method), 92
 data_properties_in_signature() (owlapy.owl_ontology.OWLOntology method), 89
 data_properties_in_signature() (owlapy.owl_ontology.SyncOntology method), 94
 data_property_domain_axioms() (owlapy.owl_ontology.Ontology method), 92
 data_property_domain_axioms() (owlapy.owl_ontology.OWLOntology method), 90
 data_property_domain_axioms() (owlapy.owl_ontology.SyncOntology method), 95
 data_property_domains() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 116
 data_property_domains() (owlapy.owl_reasoner.OntologyReasoner method), 110
 data_property_domains() (owlapy.owl_reasoner.OWLReasoner method), 103
 data_property_domains() (owlapy.owl_reasoner.SyncReasoner method), 124
 data_property_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_property_range_axioms() (owlapy.owl_ontology.Ontology method), 93
 data_property_range_axioms() (owlapy.owl_ontology.OWLOntology method), 90
 data_property_range_axioms() (owlapy.owl_ontology.SyncOntology method), 95
 data_property_ranges() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 117
 data_property_ranges() (owlapy.owl_reasoner.OWLReasonerEx method), 109
 data_property_values() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 118
 data_property_values() (owlapy.owl_reasoner.OntologyReasoner method), 112
 data_property_values() (owlapy.owl_reasoner.OWLReasoner method), 106
 data_property_values() (owlapy.owl_reasoner.SyncReasoner method), 127
 data_some_values_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 data_union_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 DatatypeLength (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 DatatypePropertyHierarchy (class in owlapy.owl_hierarchy), 81
 DATE (owlapy.vocab.XSDVocabulary attribute), 146

DATE_TIME (*owlapy.vocab.XSDVocabulary attribute*), 146
 DATE_TIME_STAMP (*owlapy.vocab.XSDVocabulary attribute*), 146
 DateOWLDatatype (*in module owlapy.owl_literal*), 86
 DateTimeOWLDatatype (*in module owlapy.owl_literal*), 86
 DECIMAL (*owlapy.vocab.XSDVocabulary attribute*), 146
 dict (*owlapy.converter.VariablesMapping attribute*), 49
 different_individuals() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 118
 different_individuals() (*owlapy.owl_reasoner.OntologyReasoner method*), 112
 different_individuals() (*owlapy.owl_reasoner.OWLReasoner method*), 105
 different_individuals() (*owlapy.owl_reasoner.SyncReasoner method*), 126
 disjoint_classes() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 118
 disjoint_classes() (*owlapy.owl_reasoner.OntologyReasoner method*), 111
 disjoint_classes() (*owlapy.owl_reasoner.OWLReasoner method*), 105
 disjoint_classes() (*owlapy.owl_reasoner.SyncReasoner method*), 123
 disjoint_data_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 121
 disjoint_data_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 115
 disjoint_data_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 107
 disjoint_data_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 127
 disjoint_object_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 121
 disjoint_object_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 114
 disjoint_object_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 107
 disjoint_object_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 127
 DL_GRAMMAR (*in module owlapy.parser*), 133
 dl_to_owl_expression() (*in module owlapy*), 147
 dl_to_owl_expression() (*in module owlapy.parser*), 135
 DLparser (*in module owlapy.parser*), 135
 DLrenderer (*in module owlapy.render*), 138
 DLSyntaxObjectRenderer (*class in owlapy.render*), 138
 DLSyntaxParser (*class in owlapy.parser*), 133
 DOUBLE (*owlapy.vocab.XSDVocabulary attribute*), 146
 DoubleOWLDatatype (*in module owlapy.owl_literal*), 86
 download_external_files() (*in module owlapy.static_funcs*), 139
 DURATION (*owlapy.vocab.XSDVocabulary attribute*), 146
 DurationOWLDatatype (*in module owlapy.owl_literal*), 86

E

entity_checker (*owlapy.owlapi_mapper.OWLAPIMapper attribute*), 130
 equivalent_classes() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 118
 equivalent_classes() (*owlapy.owl_reasoner.OntologyReasoner method*), 111
 equivalent_classes() (*owlapy.owl_reasoner.OWLReasoner method*), 104
 equivalent_classes() (*owlapy.owl_reasoner.SyncReasoner method*), 123
 equivalent_classes_axioms() (*owlapy.owl_ontology.Ontology method*), 92
 equivalent_classes_axioms() (*owlapy.owl_ontology.OWLOntology method*), 90
 equivalent_classes_axioms() (*owlapy.owl_ontology.SyncOntology method*), 94
 equivalent_data_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 121
 equivalent_data_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 114
 equivalent_data_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 105
 equivalent_data_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 126
 equivalent_object_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 120
 equivalent_object_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 114
 equivalent_object_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 105
 equivalent_object_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 126
 EvaluatedDescriptionSet (*class in owlapy.utils*), 142

F

FastInstanceCheckerReasoner (*class in owlapy.owl_reasoner*), 116
 FLOAT (*owlapy.vocab.XSDVocabulary attribute*), 146
 for_all_de_morgan (*owlapy.converter.Owl2SparqlConverter attribute*), 50
 forAll() (*owlapy.converter.Owl2SparqlConverter method*), 50
 forAllDeMorgan() (*owlapy.converter.Owl2SparqlConverter method*), 50
 FRACTION_DIGITS (*owlapy.class_expression.OWLFacet attribute*), 43
 FRACTION_DIGITS (*owlapy.vocab.OWLFacet attribute*), 147
 from_str() (*owlapy.class_expression.OWLFacet static method*), 43
 from_str() (*owlapy.vocab.OWLFacet static method*), 146
 FromOwlready2 (*class in owlapy.owl_ontology*), 96
 full (*owlapy.utils.LRUCache attribute*), 145

G

`general_class_axioms()` (*owlapy.owl_ontology.Ontology method*), 92
`general_class_axioms()` (*owlapy.owl_ontology.OWLOntology method*), 90
`general_class_axioms()` (*owlapy.owl_ontology.SyncOntology method*), 95
`generate_and_save_inferred_class_assertion_axioms()` (*owlapy.owl_reasoner.SyncReasoner method*), 128
`generic_visit()` (*owlapy.parser.DLSyntaxParser method*), 135
`generic_visit()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 133
`get_bottom_entity()` (*owlapy.owl_hierarchy.AbstractHierarchy class method*), 79
`get_bottom_entity()` (*owlapy.owl_hierarchy.ClassHierarchy class method*), 80
`get_bottom_entity()` (*owlapy.owl_hierarchy.DatatypePropertyHierarchy class method*), 81
`get_bottom_entity()` (*owlapy.owl_hierarchy.ObjectPropertyHierarchy class method*), 81
`get_cardinality()` (*owlapy.class_expression.OWLCardinalityRestriction method*), 39
`get_cardinality()` (*owlapy.class_expression.restriction.OWLCardinalityRestriction method*), 23
`get_cardinality()` (*owlapy.meta_classes.HasCardinality method*), 53
`get_class_expression()` (*owlapy.owl_axiom.OWLClassAssertionAxiom method*), 66
`get_class_expression()` (*owlapy.owl_axiom.OWLHasKeyAxiom method*), 60
`get_class_expressions()` (*owlapy.owl_axiom.OWLDisjointUnionAxiom method*), 65
`get_class_nnf()` (*owlapy.utils.NNF method*), 143
`get_data_range()` (*owlapy.owl_data_ranges.OWLDataComplementOf method*), 77
`get_datarange()` (*owlapy.owl_axiom.OWLDatatypeDefinitionAxiom method*), 60
`get_datatype()` (*owlapy.class_expression.OWLDatatypeRestriction method*), 43
`get_datatype()` (*owlapy.class_expression.restriction.OWLDatatypeRestriction method*), 31
`get_datatype()` (*owlapy.owl_axiom.OWLDatatypeDefinitionAxiom method*), 60
`get_datatype()` (*owlapy.owl_literal.OWLLiteral method*), 85
`get_default()` (*owlapy.utils.OWLClassExpressionLengthMetric static method*), 142
`get_default_document_iri()` (*owlapy.owl_ontology.OWLOntologyID method*), 89
`get_domain()` (*owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom method*), 68
`get_domain()` (*owlapy.owl_axiom.OWLPropertyDomainAxiom method*), 74
`get_entity()` (*owlapy.owl_axiom.OWLDeclarationAxiom method*), 59
`get_expression_length()` (*in module owlapy.utils*), 142
`get_facet()` (*owlapy.class_expression.OWLFacetRestriction method*), 44
`get_facet()` (*owlapy.class_expression.restriction.OWLFacetRestriction method*), 32
`get_facet_restrictions()` (*owlapy.class_expression.OWLDatatypeRestriction method*), 43
`get_facet_restrictions()` (*owlapy.class_expression.restriction.OWLDatatypeRestriction method*), 31
`get_facet_value()` (*owlapy.class_expression.OWLFacetRestriction method*), 44
`get_facet_value()` (*owlapy.class_expression.restriction.OWLFacetRestriction method*), 32
`get_filler()` (*owlapy.class_expression.OWLCardinalityRestriction method*), 39
`get_filler()` (*owlapy.class_expression.OWLHasValueRestriction method*), 38
`get_filler()` (*owlapy.class_expression.OWLQuantifiedDataRestriction method*), 41
`get_filler()` (*owlapy.class_expression.OWLQuantifiedObjectRestriction method*), 38
`get_filler()` (*owlapy.class_expression.restriction.OWLCardinalityRestriction method*), 23
`get_filler()` (*owlapy.class_expression.restriction.OWLHasValueRestriction method*), 22
`get_filler()` (*owlapy.class_expression.restriction.OWLQuantifiedDataRestriction method*), 28
`get_filler()` (*owlapy.class_expression.restriction.OWLQuantifiedObjectRestriction method*), 23
`get_filler()` (*owlapy.meta_classes.HasFiller method*), 53
`get_first_property()` (*owlapy.owl_axiom.OWLInverseObjectPropertiesAxiom method*), 64
`get_import_declaration()` (*owlapy.owl_ontology_manager.AddImport method*), 98
`get_individual()` (*owlapy.owl_axiom.OWLClassAssertionAxiom method*), 66
`get_inverse()` (*owlapy.owl_property.OWLObjectInverseOf method*), 102
`get_inverse_property()` (*owlapy.owl_property.OWLObjectInverseOf method*), 102
`get_inverse_property()` (*owlapy.owl_property.OWLObjectProperty method*), 101
`get_inverse_property()` (*owlapy.owl_property.OWLObjectPropertyExpression method*), 100
`get_literal()` (*owlapy.owl_literal.OWLLiteral method*), 84
`get_named_property()` (*owlapy.owl_property.OWLObjectInverseOf method*), 102
`get_named_property()` (*owlapy.owl_property.OWLObjectProperty method*), 101
`get_named_property()` (*owlapy.owl_property.OWLObjectPropertyExpression method*), 100
`get_namespace()` (*owlapy.iri.IRI method*), 52
`get_nnf()` (*owlapy.class_expression.class_expression.OWLAnonymousClassExpression method*), 17
`get_nnf()` (*owlapy.class_expression.class_expression.OWLClassExpression method*), 16
`get_nnf()` (*owlapy.class_expression.owl_class.OWLClass method*), 20
`get_nnf()` (*owlapy.class_expression.OWLAnonymousClassExpression method*), 35
`get_nnf()` (*owlapy.class_expression.OWLClass method*), 36
`get_nnf()` (*owlapy.class_expression.OWLClassExpression method*), 34
`get_object()` (*owlapy.owl_axiom.OWLPropertyAssertionAxiom method*), 70
`get_object_complement_of()` (*owlapy.class_expression.class_expression.OWLAnonymousClassExpression method*), 16
`get_object_complement_of()` (*owlapy.class_expression.class_expression.OWLClassExpression method*), 16
`get_object_complement_of()` (*owlapy.class_expression.owl_class.OWLClass method*), 20
`get_object_complement_of()` (*owlapy.class_expression.OWLAnonymousClassExpression method*), 34

`get_object_complement_of()` (*owlapy.class_expression.OWLClass method*), 36
`get_object_complement_of()` (*owlapy.class_expression.OWLClassExpression method*), 34
`get_ontology()` (*owlapy.owl_ontology_manager.OWL ontology Change method*), 97
`get_ontology_id()` (*owlapy.owl_ontology.Ontology method*), 92
`get_ontology_id()` (*owlapy.owl_ontology.OWL ontology method*), 91
`get_ontology_id()` (*owlapy.owl_ontology.SyncOntology method*), 95
`get_ontology_iri()` (*owlapy.owl_ontology.OWL ontology ID method*), 88
`get_operand()` (*owlapy.class_expression.class_expression.OWLObjectComplementOf method*), 17
`get_operand()` (*owlapy.class_expression.OWLObjectComplementOf method*), 35
`get_original_iri()` (*owlapy.owl_ontology.Ontology method*), 93
`get_owl_class()` (*owlapy.owl_axiom.OWLDisjointUnionAxiom method*), 65
`get_owl_disjoint_classes_axiom()` (*owlapy.owl_axiom.OWLDisjointUnionAxiom method*), 65
`get_owl_equivalent_classes_axiom()` (*owlapy.owl_axiom.OWLDisjointUnionAxiom method*), 65
`get_owl_ontology_manager()` (*owlapy.owl_ontology.Ontology method*), 92
`get_owl_ontology_manager()` (*owlapy.owl_ontology.OWL ontology method*), 91
`get_owl_ontology_manager()` (*owlapy.owl_ontology.SyncOntology method*), 95
`get_owlapi_manager()` (*owlapy.owl_ontology_manager.SyncOntologyManager method*), 99
`get_owlapi_ontology()` (*owlapy.owl_ontology.SyncOntology method*), 95
`get_property()` (*owlapy.class_expression.OWLDataAllValuesFrom method*), 46
`get_property()` (*owlapy.class_expression.OWLDataCardinalityRestriction method*), 41
`get_property()` (*owlapy.class_expression.OWLDataHasValue method*), 46
`get_property()` (*owlapy.class_expression.OWLDataSomeValuesFrom method*), 45
`get_property()` (*owlapy.class_expression.OWLObjectAllValuesFrom method*), 42
`get_property()` (*owlapy.class_expression.OWLObjectCardinalityRestriction method*), 39
`get_property()` (*owlapy.class_expression.OWLObjectHasSelf method*), 40
`get_property()` (*owlapy.class_expression.OWLObjectHasValue method*), 42
`get_property()` (*owlapy.class_expression.OWLObjectRestriction method*), 38
`get_property()` (*owlapy.class_expression.OWLObjectSomeValuesFrom method*), 42
`get_property()` (*owlapy.class_expression.OWLRestriction method*), 37
`get_property()` (*owlapy.class_expression.restriction.OWLDataAllValuesFrom method*), 30
`get_property()` (*owlapy.class_expression.restriction.OWLDataCardinalityRestriction method*), 28
`get_property()` (*owlapy.class_expression.restriction.OWLDataHasValue method*), 31
`get_property()` (*owlapy.class_expression.restriction.OWLDataSomeValuesFrom method*), 29
`get_property()` (*owlapy.class_expression.restriction.OWLObjectAllValuesFrom method*), 26
`get_property()` (*owlapy.class_expression.restriction.OWLObjectCardinalityRestriction method*), 24
`get_property()` (*owlapy.class_expression.restriction.OWLObjectHasSelf method*), 26
`get_property()` (*owlapy.class_expression.restriction.OWLObjectHasValue method*), 26
`get_property()` (*owlapy.class_expression.restriction.OWLObjectRestriction method*), 23
`get_property()` (*owlapy.class_expression.restriction.OWLObjectSomeValuesFrom method*), 25
`get_property()` (*owlapy.class_expression.restriction.OWLRestriction method*), 22
`get_property()` (*owlapy.owl_axiom.OWLAnnotation method*), 66
`get_property()` (*owlapy.owl_axiom.OWLAnnotationAssertionAxiom method*), 67
`get_property()` (*owlapy.owl_axiom.OWLAnnotationPropertyDomainAxiom method*), 68
`get_property()` (*owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom method*), 69
`get_property()` (*owlapy.owl_axiom.OWLPropertyAssertionAxiom method*), 70
`get_property()` (*owlapy.owl_axiom.OWLUnaryPropertyAxiom method*), 71
`get_property_expressions()` (*owlapy.owl_axiom.OWLHasKeyAxiom method*), 60
`get_range()` (*owlapy.owl_axiom.OWLAnnotationPropertyRangeAxiom method*), 69
`get_range()` (*owlapy.owl_axiom.OWLPropertyRangeAxiom method*), 74
`get_remainder()` (*owlapy.iri.IRI method*), 52
`get_root_ontology()` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 122
`get_root_ontology()` (*owlapy.owl_reasoner.OntologyReasoner method*), 116
`get_root_ontology()` (*owlapy.owl_reasoner.OWLReasoner method*), 109
`get_root_ontology()` (*owlapy.owl_reasoner.SyncReasoner method*), 129
`get_second_property()` (*owlapy.owl_axiom.OWLInverseObjectPropertiesAxiom method*), 64
`get_sub_class()` (*owlapy.owl_axiom.OWLSubClassOfAxiom method*), 65
`get_sub_property()` (*owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom method*), 68
`get_sub_property()` (*owlapy.owl_axiom.OWLSubPropertyAxiom method*), 69
`get_subject()` (*owlapy.owl_axiom.OWLAnnotationAssertionAxiom method*), 67
`get_subject()` (*owlapy.owl_axiom.OWLPropertyAssertionAxiom method*), 70
`get_super_class()` (*owlapy.owl_axiom.OWLSubClassOfAxiom method*), 65
`get_super_property()` (*owlapy.owl_axiom.OWLSubAnnotationPropertyOfAxiom method*), 68
`get_super_property()` (*owlapy.owl_axiom.OWLSubPropertyAxiom method*), 69
`get_top_entity()` (*owlapy.owl_hierarchy.AbstractHierarchy class method*), 79
`get_top_entity()` (*owlapy.owl_hierarchy.ClassHierarchy class method*), 80
`get_top_entity()` (*owlapy.owl_hierarchy.DatatypePropertyHierarchy class method*), 81
`get_top_entity()` (*owlapy.owl_hierarchy.ObjectPropertyHierarchy class method*), 81
`get_top_level_cnf()` (*owlapy.utils.TopLevelCNF method*), 144

`get_top_level_dnf()` (*owlapy.utils.TopLevelDNF method*), 144
`get_value()` (*owlapy.owl_axiom.OWLAnnotation method*), 66
`get_value()` (*owlapy.owl_axiom.OWLAnnotationAssertionAxiom method*), 67
`get_variable()` (*owlapy.converter.VariablesMapping method*), 49
`get_version_iri()` (*owlapy.owl_ontology.OWLOntologyID method*), 89
`grammar` (*owlapy.parser.DLSyntaxParser attribute*), 133
`grammar` (*owlapy.parser.ManchesterOWLSyntaxParser attribute*), 131
`grouping_vars` (*owlapy.converter.Owl2SparqlConverter attribute*), 50

H

`has_consistent_ontology()` (*owlapy.owl_reasoner.SyncReasoner method*), 128
`HasCardinality` (*class in owlapy.meta_classes*), 53
`HasFiller` (*class in owlapy.meta_classes*), 53
`HasIndex` (*class in owlapy.utils*), 143
`HasIRI` (*class in owlapy.meta_classes*), 53
`HasOperands` (*class in owlapy.meta_classes*), 53
`having_conditions` (*owlapy.converter.Owl2SparqlConverter attribute*), 50

I

`ind_cnt` (*owlapy.converter.VariablesMapping attribute*), 49
`ind_data_properties()` (*owlapy.owl_reasoner.OWLReasonerEx method*), 110
`ind_object_properties()` (*owlapy.owl_reasoner.OWLReasonerEx method*), 110
`individuals()` (*owlapy.class_expression.OWLObjectOneOf method*), 47
`individuals()` (*owlapy.class_expression.restriction.OWLObjectOneOf method*), 27
`individuals()` (*owlapy.owl_axiom.OWLNaryIndividualAxiom method*), 62
`individuals_in_signature()` (*owlapy.owl_ontology.Ontology method*), 92
`individuals_in_signature()` (*owlapy.owl_ontology.OWLOntology method*), 89
`individuals_in_signature()` (*owlapy.owl_ontology.SyncOntology method*), 94
`infer_axioms()` (*owlapy.owl_reasoner.SyncReasoner method*), 128
`infer_axioms_and_save()` (*owlapy.owl_reasoner.SyncReasoner method*), 128
`inference_types_mapping` (*owlapy.owl_reasoner.SyncReasoner attribute*), 123
`init()` (*in module owlapy.owlapi_mapper*), 129
`instances()` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 119
`instances()` (*owlapy.owl_reasoner.OntologyReasoner method*), 113
`instances()` (*owlapy.owl_reasoner.OWLReasoner method*), 106
`instances()` (*owlapy.owl_reasoner.SyncReasoner method*), 123
`INTEGER` (*owlapy.vocab.XSDVocabulary attribute*), 146
`IntegerOWLDatatype` (*in module owlapy.owl_literal*), 86
`IRI` (*class in owlapy.iri*), 51
`iri` (*owlapy.class_expression.owl_class.OWLClass property*), 19
`iri` (*owlapy.class_expression.OWLClass property*), 35
`iri` (*owlapy.meta_classes.HasIRI property*), 53
`iri` (*owlapy.owl_axiom.OWLAnnotationProperty property*), 66
`iri` (*owlapy.owl_datatype.OWLDatatype property*), 78
`iri` (*owlapy.owl_individual.OWLNamedIndividual property*), 82
`iri` (*owlapy.owl_ontology_manager.OWLImportsDeclaration property*), 98
`iri` (*owlapy.owl_property.OWLProperty property*), 101
`is_annotated()` (*owlapy.owl_axiom.OWLAxiom method*), 58
`is_annotation_axiom()` (*owlapy.owl_axiom.OWLAnnotationAxiom method*), 67
`is_annotation_axiom()` (*owlapy.owl_axiom.OWLAxiom method*), 58
`is_anonymous()` (*owlapy.owl_object.OWLEntity method*), 88
`is_anonymous()` (*owlapy.owl_object.OWLObject method*), 87
`is_anonymous()` (*owlapy.owl_ontology.OWLOntology method*), 91
`is_anonymous()` (*owlapy.owl_ontology.OWLOntologyID method*), 89
`is_boolean()` (*owlapy.owl_literal.OWLLiteral method*), 84
`is_child_of()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 79
`is_data_property_expression()` (*owlapy.owl_property.OWLDataPropertyExpression method*), 101
`is_data_property_expression()` (*owlapy.owl_property.OWLPropertyExpression method*), 100
`is_data_restriction()` (*owlapy.class_expression.OWLDataRestriction method*), 39
`is_data_restriction()` (*owlapy.class_expression.OWLRestriction method*), 37
`is_data_restriction()` (*owlapy.class_expression.restriction.OWLDataRestriction method*), 27
`is_data_restriction()` (*owlapy.class_expression.restriction.OWLRestriction method*), 22
`is_date()` (*owlapy.owl_literal.OWLLiteral method*), 85
`is_datetime()` (*owlapy.owl_literal.OWLLiteral method*), 85
`is_double()` (*owlapy.owl_literal.OWLLiteral method*), 84
`is_duration()` (*owlapy.owl_literal.OWLLiteral method*), 85
`is_integer()` (*owlapy.owl_literal.OWLLiteral method*), 84

- `is_literal()` (*owlapy.owl_annotation.OWLAnnotationValue method*), 55
- `is_literal()` (*owlapy.owl_literal.OWLLiteral method*), 85
- `is_logical_axiom()` (*owlapy.owl_axiom.OWLXiom method*), 58
- `is_logical_axiom()` (*owlapy.owl_axiom.OWLLogicalXiom method*), 58
- `is_nothing()` (*owlapy.iri.IRI method*), 51
- `is_object_property_expression()` (*owlapy.owl_property.OWLObjectPropertyExpression method*), 100
- `is_object_property_expression()` (*owlapy.owl_property.OWLPropertyExpression method*), 100
- `is_object_restriction()` (*owlapy.class_expression.OWLObjectRestriction method*), 38
- `is_object_restriction()` (*owlapy.class_expression.OWLRestriction method*), 37
- `is_object_restriction()` (*owlapy.class_expression.restriction.OWLObjectRestriction method*), 22
- `is_object_restriction()` (*owlapy.class_expression.restriction.OWLRestriction method*), 22
- `is_owl_nothing()` (*owlapy.class_expression.class_expression.OWLAnonymousClassExpression method*), 16
- `is_owl_nothing()` (*owlapy.class_expression.class_expression.OWLClassExpression method*), 16
- `is_owl_nothing()` (*owlapy.class_expression.owl_class.OWLClass method*), 19
- `is_owl_nothing()` (*owlapy.class_expression.OWLAnonymousClassExpression method*), 34
- `is_owl_nothing()` (*owlapy.class_expression.OWLClass method*), 36
- `is_owl_nothing()` (*owlapy.class_expression.OWLClassExpression method*), 34
- `is_owl_thing()` (*owlapy.class_expression.class_expression.OWLAnonymousClassExpression method*), 16
- `is_owl_thing()` (*owlapy.class_expression.class_expression.OWLClassExpression method*), 16
- `is_owl_thing()` (*owlapy.class_expression.owl_class.OWLClass method*), 19
- `is_owl_thing()` (*owlapy.class_expression.OWLAnonymousClassExpression method*), 34
- `is_owl_thing()` (*owlapy.class_expression.OWLClass method*), 36
- `is_owl_thing()` (*owlapy.class_expression.OWLClassExpression method*), 34
- `is_owl_top_data_property()` (*owlapy.owl_property.OWLDataProperty method*), 102
- `is_owl_top_data_property()` (*owlapy.owl_property.OWLPropertyExpression method*), 100
- `is_owl_top_object_property()` (*owlapy.owl_property.OWLObjectProperty method*), 101
- `is_owl_top_object_property()` (*owlapy.owl_property.OWLPropertyExpression method*), 100
- `is_parent_of()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 79
- `is_reserved_vocabulary()` (*owlapy.iri.IRI method*), 52
- `is_string()` (*owlapy.owl_literal.OWLLiteral method*), 85
- `is_sub_property_of()` (*owlapy.owl_hierarchy.DatatypePropertyHierarchy method*), 81
- `is_sub_property_of()` (*owlapy.owl_hierarchy.ObjectPropertyHierarchy method*), 81
- `is_subclass_of()` (*owlapy.owl_hierarchy.ClassHierarchy method*), 80
- `is_thing()` (*owlapy.iri.IRI method*), 52
- `items` (*owlapy.utils.EvaluatedDescriptionSet attribute*), 142
- `items()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 80
- `iter_count()` (*in module owlapy.utils*), 144

K

- `KEY` (*owlapy.utils.LRUCache attribute*), 144

L

- `leaves()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 80
- `LENGTH` (*owlapy.class_expression.OWLFacet attribute*), 43
- `LENGTH` (*owlapy.vocab.OWLFacet attribute*), 147
- `length()` (*owlapy.utils.OWLClassExpressionLengthMetric method*), 142
- `Literals` (*in module owlapy.class_expression.restriction*), 22
- `Literals` (*in module owlapy.owl_literal*), 84
- `load_ontology()` (*owlapy.owl_ontology_manager.OntologyManager method*), 98
- `load_ontology()` (*owlapy.owl_ontology_manager.OWLOntologyManager method*), 97
- `load_ontology()` (*owlapy.owl_ontology_manager.SyncOntologyManager method*), 99
- `lock` (*owlapy.utils.LRUCache attribute*), 145
- `logger` (*in module owlapy.owl_ontology*), 88
- `logger` (*in module owlapy.owl_reasoner*), 103
- `LONG` (*owlapy.vocab.XSDVocabulary attribute*), 146
- `LRUCache` (*class in owlapy.utils*), 144

M

- `manager` (*owlapy.owl_ontology.SyncOntology attribute*), 94
- `manager` (*owlapy.owlapi_mapper.OWLAPIMapper attribute*), 129
- `MANCHESTER_GRAMMAR` (*in module owlapy.parser*), 131
- `manchester_to_owl_expression()` (*in module owlapy*), 147
- `manchester_to_owl_expression()` (*in module owlapy.parser*), 135
- `ManchesterOWLSyntaxOWLObjectRenderer` (*class in owlapy.render*), 138
- `ManchesterOWLSyntaxParser` (*class in owlapy.parser*), 131
- `ManchesterParser` (*in module owlapy.parser*), 135

ManchesterRenderer (in module owlapy.render), 138
 map_() (owlapy.owlapi_mapper.OWLAPIMapper method), 130
 map_concept() (owlapy.owl_ontology.FromOwlready2 method), 96
 map_concept() (owlapy.owl_ontology.ToOwlready2 method), 96
 map_datarange() (owlapy.owl_ontology.FromOwlready2 method), 96
 map_datarange() (owlapy.owl_ontology.ToOwlready2 method), 96
 map_object() (owlapy.owl_ontology.ToOwlready2 method), 96
 mapper (in module owlapy.render), 137
 mapper (owlapy.owl_ontology.SyncOntology attribute), 94
 mapper (owlapy.owl_reasoner.SyncReasoner attribute), 123
 mapping (owlapy.converter.Owl2SparqlConverter attribute), 50
 MAX_EXCLUSIVE (owlapy.class_expression.OWLFacet attribute), 43
 MAX_EXCLUSIVE (owlapy.vocab.OWLFacet attribute), 146
 MAX_INCLUSIVE (owlapy.class_expression.OWLFacet attribute), 43
 MAX_INCLUSIVE (owlapy.vocab.OWLFacet attribute), 146
 MAX_LENGTH (owlapy.class_expression.OWLFacet attribute), 43
 MAX_LENGTH (owlapy.vocab.OWLFacet attribute), 147
 maxsize (owlapy.utils.LRUCache attribute), 145
 maybe_add() (owlapy.utils.EvaluatedDescriptionSet method), 142
 measurer (in module owlapy.utils), 142
 MIN_EXCLUSIVE (owlapy.class_expression.OWLFacet attribute), 43
 MIN_EXCLUSIVE (owlapy.vocab.OWLFacet attribute), 146
 MIN_INCLUSIVE (owlapy.class_expression.OWLFacet attribute), 43
 MIN_INCLUSIVE (owlapy.vocab.OWLFacet attribute), 146
 MIN_LENGTH (owlapy.class_expression.OWLFacet attribute), 43
 MIN_LENGTH (owlapy.vocab.OWLFacet attribute), 147
 modal_depth (owlapy.converter.Owl2SparqlConverter property), 50
 module
 owlapy, 15
 owlapy.class_expression, 15
 owlapy.class_expression.class_expression, 15
 owlapy.class_expression.nary_boolean_expression, 17
 owlapy.class_expression.owl_class, 19
 owlapy.class_expression.restriction, 20
 owlapy.converter, 48
 owlapy.entities, 48
 owlapy.iri, 51
 owlapy.meta_classes, 52
 owlapy.namespaces, 54
 owlapy.owl_annotation, 55
 owlapy.owl_axiom, 56
 owlapy.owl_data_ranges, 75
 owlapy.owl_datatype, 77
 owlapy.owl_hierarchy, 78
 owlapy.owl_individual, 82
 owlapy.owl_literal, 83
 owlapy.owl_object, 86
 owlapy.owl_ontology, 88
 owlapy.owl_ontology_manager, 96
 owlapy.owl_property, 99
 owlapy.owl_reasoner, 103
 owlapy.owlapi_mapper, 129
 owlapy.parser, 130
 owlapy.providers, 135
 owlapy.render, 136
 owlapy.static_funcs, 139
 owlapy.utils, 139
 owlapy.vocab, 145
 more_general_roles() (owlapy.owl_hierarchy.DatatypePropertyHierarchy method), 81
 more_general_roles() (owlapy.owl_hierarchy.ObjectPropertyHierarchy method), 81
 more_special_roles() (owlapy.owl_hierarchy.DatatypePropertyHierarchy method), 81
 more_special_roles() (owlapy.owl_hierarchy.ObjectPropertyHierarchy method), 81
 most_general_roles() (owlapy.owl_hierarchy.DatatypePropertyHierarchy method), 81
 most_general_roles() (owlapy.owl_hierarchy.ObjectPropertyHierarchy method), 81
 most_special_roles() (owlapy.owl_hierarchy.DatatypePropertyHierarchy method), 82
 most_special_roles() (owlapy.owl_hierarchy.ObjectPropertyHierarchy method), 81
 move() (in module owlapy.static_funcs), 139

N

named_classes() (owlapy.owl_axiom.OWLEquivalentClassesAxiom method), 62
 named_individuals (owlapy.converter.Owl2SparqlConverter attribute), 50
 namespace (owlapy.owlapi_mapper.OWLAPIMapper attribute), 129
 Namespaces (class in owlapy.namespaces), 54
 new (owlapy.owl_ontology.SyncOntology attribute), 94
 new_count_var() (owlapy.converter.Owl2SparqlConverter method), 50
 new_individual_variable() (owlapy.converter.VariablesMapping method), 49
 new_property_variable() (owlapy.converter.VariablesMapping method), 49
 NEXT (owlapy.utils.LRUCache attribute), 144
 NNF (class in owlapy.utils), 143
 ns (owlapy.namespaces.Namespaces property), 54
 ns (owlapy.parser.DLSyntaxParser attribute), 133
 ns (owlapy.parser.ManchesterOWLSyntaxParser attribute), 131
 NUMERIC_DATATYPES (in module owlapy.owl_literal), 86

O

o (owlapy.utils.OrderedOWLObject attribute), 143
 object_all_values_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_cardinality_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_complement_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_has_self_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_has_value_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_intersection_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_inverse_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 object_one_of_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_properties_in_signature() (owlapy.owl_ontology.Ontology method), 92
 object_properties_in_signature() (owlapy.owl_ontology.OWLOntology method), 89
 object_properties_in_signature() (owlapy.owl_ontology.SyncOntology method), 94
 object_property_domain_axioms() (owlapy.owl_ontology.Ontology method), 93
 object_property_domain_axioms() (owlapy.owl_ontology.OWLOntology method), 90
 object_property_domain_axioms() (owlapy.owl_ontology.SyncOntology method), 95
 object_property_domains() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 117
 object_property_domains() (owlapy.owl_reasoner.OntologyReasoner method), 110
 object_property_domains() (owlapy.owl_reasoner.OWLReasoner method), 104
 object_property_domains() (owlapy.owl_reasoner.SyncReasoner method), 124
 object_property_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 142
 object_property_range_axioms() (owlapy.owl_ontology.Ontology method), 93
 object_property_range_axioms() (owlapy.owl_ontology.OWLOntology method), 90
 object_property_range_axioms() (owlapy.owl_ontology.SyncOntology method), 95
 object_property_ranges() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 117
 object_property_ranges() (owlapy.owl_reasoner.OntologyReasoner method), 111
 object_property_ranges() (owlapy.owl_reasoner.OWLReasoner method), 104
 object_property_ranges() (owlapy.owl_reasoner.SyncReasoner method), 124
 object_property_values() (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 119
 object_property_values() (owlapy.owl_reasoner.OntologyReasoner method), 113
 object_property_values() (owlapy.owl_reasoner.OWLReasoner method), 106
 object_property_values() (owlapy.owl_reasoner.SyncReasoner method), 126
 object_some_values_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 object_union_length (owlapy.utils.OWLClassExpressionLengthMetric attribute), 141
 ObjectPropertyHierarchy (class in owlapy.owl_hierarchy), 80
 onto (owlapy.owl_ontology.Ontology attribute), 91
 Ontology (class in owlapy.owl_ontology), 91
 ontology (owlapy.owlapi_mapper.OWLAPIMapper attribute), 129
 ontology_set (owlapy.owlapi_mapper.OWLAPIMapper attribute), 129
 OntologyManager (class in owlapy.owl_ontology_manager), 98
 OntologyReasoner (class in owlapy.owl_reasoner), 110
 operands() (owlapy.class_expression.class_expression.OWLObjectComplementOf method), 17
 operands() (owlapy.class_expression.nary_boolean_expression.OWLNaryBooleanClassExpression method), 18
 operands() (owlapy.class_expression.OWLDataOneOf method), 40
 operands() (owlapy.class_expression.OWLNaryBooleanClassExpression method), 36
 operands() (owlapy.class_expression.OWLObjectComplementOf method), 35
 operands() (owlapy.class_expression.OWLObjectOneOf method), 47
 operands() (owlapy.class_expression.restriction.OWLDataOneOf method), 31
 operands() (owlapy.class_expression.restriction.OWLObjectOneOf method), 27
 operands() (owlapy.meta_classes.HasOperands method), 53
 operands() (owlapy.owl_axiom.OWLHasKeyAxiom method), 60

- `operands()` (*owlapy.owl_data_ranges.OWLNaryDataRange method*), 76
- `OperandSetTransform` (*class in owlapy.utils*), 143
- `operator` (*owlapy.class_expression.OWLFacet property*), 43
- `operator` (*owlapy.vocab.OWLFacet property*), 146
- `OrderedOWLObject` (*class in owlapy.utils*), 143
- `OWL` (*in module owlapy.namespaces*), 54
- `Owl2SparqlConverter` (*class in owlapy.converter*), 49
- `OWL_BOTTOM_DATA_PROPERTY` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `OWL_BOTTOM_OBJECT_PROPERTY` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `OWL_CLASS` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `owl_datatype_max_exclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_datatype_max_inclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_datatype_min_exclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_datatype_min_inclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_datatype_min_max_exclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_datatype_min_max_inclusive_restriction()` (*in module owlapy.providers*), 136
- `owl_expression_to_dl()` (*in module owlapy*), 147
- `owl_expression_to_dl()` (*in module owlapy.render*), 139
- `owl_expression_to_manchester()` (*in module owlapy*), 147
- `owl_expression_to_manchester()` (*in module owlapy.render*), 139
- `owl_expression_to_sparql()` (*in module owlapy*), 147
- `owl_expression_to_sparql()` (*in module owlapy.converter*), 51
- `OWL_NAMED_INDIVIDUAL` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `OWL_NOTHING` (*owlapy.vocab.OWLRDFVocabulary attribute*), 145
- `OWL_THING` (*owlapy.vocab.OWLRDFVocabulary attribute*), 145
- `OWL_TOP_DATA_PROPERTY` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `OWL_TOP_OBJECT_PROPERTY` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
- `OWLAnnotation` (*class in owlapy.owl_axiom*), 66
- `OWLAnnotationAssertionAxiom` (*class in owlapy.owl_axiom*), 67
- `OWLAnnotationAxiom` (*class in owlapy.owl_axiom*), 67
- `OWLAnnotationObject` (*class in owlapy.owl_annotation*), 55
- `OWLAnnotationProperty` (*class in owlapy.owl_axiom*), 66
- `OWLAnnotationPropertyDomainAxiom` (*class in owlapy.owl_axiom*), 68
- `OWLAnnotationPropertyRangeAxiom` (*class in owlapy.owl_axiom*), 68
- `OWLAnnotationSubject` (*class in owlapy.owl_annotation*), 55
- `OWLAnnotationValue` (*class in owlapy.owl_annotation*), 55
- `OWLAnonymousClassExpression` (*class in owlapy.class_expression*), 34
- `OWLAnonymousClassExpression` (*class in owlapy.class_expression.class_expression*), 16
- `owlapi_manager` (*owlapy.owl_ontology_manager.SyncOntologyManager attribute*), 99
- `OWLAPIMapper` (*class in owlapy.owlapi_mapper*), 129
- `owlapy`
 - module, 15
- `owlapy.class_expression`
 - module, 15
- `owlapy.class_expression.class_expression`
 - module, 15
- `owlapy.class_expression.nary_boolean_expression`
 - module, 17
- `owlapy.class_expression.owl_class`
 - module, 19
- `owlapy.class_expression.restriction`
 - module, 20
- `owlapy.converter`
 - module, 48
- `owlapy.entities`
 - module, 48
- `owlapy.iri`
 - module, 51
- `owlapy.meta_classes`
 - module, 52
- `owlapy.namespaces`
 - module, 54
- `owlapy.owl_annotation`
 - module, 55
- `owlapy.owl_axiom`
 - module, 56
- `owlapy.owl_data_ranges`
 - module, 75

- owlapy.owl_datatype
 module, 77
- owlapy.owl_hierarchy
 module, 78
- owlapy.owl_individual
 module, 82
- owlapy.owl_literal
 module, 83
- owlapy.owl_object
 module, 86
- owlapy.owl_ontology
 module, 88
- owlapy.owl_ontology_manager
 module, 96
- owlapy.owl_property
 module, 99
- owlapy.owl_reasoner
 module, 103
- owlapy.owlapi_mapper
 module, 129
- owlapy.parser
 module, 130
- owlapy.providers
 module, 135
- owlapy.render
 module, 136
- owlapy.static_funcs
 module, 139
- owlapy.utils
 module, 139
- owlapy.vocab
 module, 145
- OWLASymmetricObjectPropertyAxiom (*class in owlapy.owl_axiom*), 72
- OWLAxiom (*class in owlapy.owl_axiom*), 58
- OWLBooleanClassExpression (*class in owlapy.class_expression*), 35
- OWLBooleanClassExpression (*class in owlapy.class_expression.class_expression*), 17
- OWLBottomDataProperty (*in module owlapy.owl_literal*), 86
- OWLBottomObjectProperty (*in module owlapy.owl_literal*), 85
- OWLCardinalityRestriction (*class in owlapy.class_expression*), 39
- OWLCardinalityRestriction (*class in owlapy.class_expression.restriction*), 23
- OWLClass (*class in owlapy.class_expression*), 35
- OWLClass (*class in owlapy.class_expression.owl_class*), 19
- OWLClassAssertionAxiom (*class in owlapy.owl_axiom*), 65
- OWLClassAxiom (*class in owlapy.owl_axiom*), 59
- OWLClassExpression (*class in owlapy.class_expression*), 34
- OWLClassExpression (*class in owlapy.class_expression.class_expression*), 16
- OWLClassExpressionLengthMetric (*class in owlapy.utils*), 140
- OWLDataAllValuesFrom (*class in owlapy.class_expression*), 45
- OWLDataAllValuesFrom (*class in owlapy.class_expression.restriction*), 30
- OWLDataCardinalityRestriction (*class in owlapy.class_expression*), 41
- OWLDataCardinalityRestriction (*class in owlapy.class_expression.restriction*), 28
- OWLDataComplementOf (*class in owlapy.owl_data_ranges*), 77
- OWLDataExactCardinality (*class in owlapy.class_expression*), 47
- OWLDataExactCardinality (*class in owlapy.class_expression.restriction*), 29
- OWLDataHasValue (*class in owlapy.class_expression*), 46
- OWLDataHasValue (*class in owlapy.class_expression.restriction*), 30
- OWLDataIntersectionOf (*class in owlapy.owl_data_ranges*), 76
- OWLDataMaxCardinality (*class in owlapy.class_expression*), 47
- OWLDataMaxCardinality (*class in owlapy.class_expression.restriction*), 28
- OWLDataMinCardinality (*class in owlapy.class_expression*), 46
- OWLDataMinCardinality (*class in owlapy.class_expression.restriction*), 28
- OWLDataOneOf (*class in owlapy.class_expression*), 40
- OWLDataOneOf (*class in owlapy.class_expression.restriction*), 31
- OWLDataProperty (*class in owlapy.owl_property*), 102
- OWLDataPropertyAssertionAxiom (*class in owlapy.owl_axiom*), 71
- OWLDataPropertyAxiom (*class in owlapy.owl_axiom*), 59
- OWLDataPropertyCharacteristicAxiom (*class in owlapy.owl_axiom*), 73
- OWLDataPropertyDomainAxiom (*class in owlapy.owl_axiom*), 74

OWLDataPropertyExpression (class in owlapy.owl_property), 100
 OWLDataPropertyRangeAxiom (class in owlapy.owl_axiom), 75
 OWLDataRange (class in owlapy.owl_data_ranges), 76
 OWLDataRestriction (class in owlapy.class_expression), 38
 OWLDataRestriction (class in owlapy.class_expression.restriction), 27
 OWLDataSomeValuesFrom (class in owlapy.class_expression), 45
 OWLDataSomeValuesFrom (class in owlapy.class_expression.restriction), 29
 OWLDatatype (class in owlapy.owl_datatype), 78
 OWLDatatypeDefinitionAxiom (class in owlapy.owl_axiom), 59
 OWLDatatypeRestriction (class in owlapy.class_expression), 43
 OWLDatatypeRestriction (class in owlapy.class_expression.restriction), 31
 OWLDataUnionOf (class in owlapy.owl_data_ranges), 77
 OWLDeclarationAxiom (class in owlapy.owl_axiom), 59
 OWLDifferentIndividualsAxiom (class in owlapy.owl_axiom), 62
 OWLDisjointClassesAxiom (class in owlapy.owl_axiom), 62
 OWLDisjointDataPropertiesAxiom (class in owlapy.owl_axiom), 64
 OWLDisjointObjectPropertiesAxiom (class in owlapy.owl_axiom), 63
 OWLDisjointUnionAxiom (class in owlapy.owl_axiom), 65
 OWLEntity (class in owlapy.owl_object), 87
 OWLEquivalentClassesAxiom (class in owlapy.owl_axiom), 61
 OWLEquivalentDataPropertiesAxiom (class in owlapy.owl_axiom), 64
 OWLEquivalentObjectPropertiesAxiom (class in owlapy.owl_axiom), 63
 OWLFacet (class in owlapy.class_expression), 43
 OWLFacet (class in owlapy.vocab), 146
 OWLFacetRestriction (class in owlapy.class_expression), 44
 OWLFacetRestriction (class in owlapy.class_expression.restriction), 32
 OWLFunctionalDataPropertyAxiom (class in owlapy.owl_axiom), 73
 OWLFunctionalObjectPropertyAxiom (class in owlapy.owl_axiom), 71
 OWLHasKeyAxiom (class in owlapy.owl_axiom), 60
 OWLHasValueRestriction (class in owlapy.class_expression), 38
 OWLHasValueRestriction (class in owlapy.class_expression.restriction), 22
 OWLImportsDeclaration (class in owlapy.owl_ontology_manager), 98
 OWLIndividual (class in owlapy.owl_individual), 82
 OWLIndividualAxiom (class in owlapy.owl_axiom), 59
 OWLInverseFunctionalObjectPropertyAxiom (class in owlapy.owl_axiom), 72
 OWLInverseObjectPropertiesAxiom (class in owlapy.owl_axiom), 64
 OWLIrreflexiveObjectPropertyAxiom (class in owlapy.owl_axiom), 72
 OWLLiteral (class in owlapy.owl_literal), 84
 OWLLogicalAxiom (class in owlapy.owl_axiom), 58
 OWLNamedIndividual (class in owlapy.owl_individual), 82
 OWLNamedObject (class in owlapy.owl_object), 87
 OWLNaryAxiom (class in owlapy.owl_axiom), 60
 OWLNaryBooleanClassExpression (class in owlapy.class_expression), 36
 OWLNaryBooleanClassExpression (class in owlapy.class_expression.nary_boolean_expression), 18
 OWLNaryClassAxiom (class in owlapy.owl_axiom), 61
 OWLNaryDataRange (class in owlapy.owl_data_ranges), 76
 OWLNaryIndividualAxiom (class in owlapy.owl_axiom), 62
 OWLNaryPropertyAxiom (class in owlapy.owl_axiom), 63
 OWLNegativeDataPropertyAssertionAxiom (class in owlapy.owl_axiom), 71
 OWLNegativeObjectPropertyAssertionAxiom (class in owlapy.owl_axiom), 70
 OWLObject (class in owlapy.owl_object), 86
 OWLObjectAllValuesFrom (class in owlapy.class_expression), 42
 OWLObjectAllValuesFrom (class in owlapy.class_expression.restriction), 25
 OWLObjectCardinalityRestriction (class in owlapy.class_expression), 39
 OWLObjectCardinalityRestriction (class in owlapy.class_expression.restriction), 24
 OWLObjectComplementOf (class in owlapy.class_expression), 35
 OWLObjectComplementOf (class in owlapy.class_expression.class_expression), 17
 OWLObjectExactCardinality (class in owlapy.class_expression), 44
 OWLObjectExactCardinality (class in owlapy.class_expression.restriction), 24
 OWLObjectHasSelf (class in owlapy.class_expression), 39
 OWLObjectHasSelf (class in owlapy.class_expression.restriction), 26
 OWLObjectHasValue (class in owlapy.class_expression), 42
 OWLObjectHasValue (class in owlapy.class_expression.restriction), 26
 OWLObjectIntersectionOf (class in owlapy.class_expression), 37
 OWLObjectIntersectionOf (class in owlapy.class_expression.nary_boolean_expression), 18
 OWLObjectInverseOf (class in owlapy.owl_property), 102
 OWLObjectMaxCardinality (class in owlapy.class_expression), 44
 OWLObjectMaxCardinality (class in owlapy.class_expression.restriction), 24

OWLObjectMinCardinality (class in owlapy.class_expression), 44
 OWLObjectMinCardinality (class in owlapy.class_expression.restriction), 24
 OWLObjectOneOf (class in owlapy.class_expression), 47
 OWLObjectOneOf (class in owlapy.class_expression.restriction), 27
 OWLObjectParser (class in owlapy.owl_object), 87
 OWLObjectProperty (class in owlapy.owl_property), 101
 OWLObjectPropertyAssertionAxiom (class in owlapy.owl_axiom), 70
 OWLObjectPropertyAxiom (class in owlapy.owl_axiom), 59
 OWLObjectPropertyCharacteristicAxiom (class in owlapy.owl_axiom), 71
 OWLObjectPropertyDomainAxiom (class in owlapy.owl_axiom), 74
 OWLObjectPropertyExpression (class in owlapy.owl_property), 100
 OWLObjectPropertyRangeAxiom (class in owlapy.owl_axiom), 75
 OWLObjectRenderer (class in owlapy.owl_object), 87
 OWLObjectRestriction (class in owlapy.class_expression), 38
 OWLObjectRestriction (class in owlapy.class_expression.restriction), 22
 OWLObjectSomeValuesFrom (class in owlapy.class_expression), 41
 OWLObjectSomeValuesFrom (class in owlapy.class_expression.restriction), 25
 OWLObjectUnionOf (class in owlapy.class_expression), 36
 OWLObjectUnionOf (class in owlapy.class_expression.nary_boolean_expression), 18
 OWLOntology (class in owlapy.owl_ontology), 89
 OWLOntologyChange (class in owlapy.owl_ontology_manager), 97
 OWLOntologyID (class in owlapy.owl_ontology), 88
 OWLOntologyManager (class in owlapy.owl_ontology_manager), 97
 OWLProperty (class in owlapy.owl_property), 101
 OWLPropertyAssertionAxiom (class in owlapy.owl_axiom), 70
 OWLPropertyAxiom (class in owlapy.owl_axiom), 58
 OWLPropertyDomainAxiom (class in owlapy.owl_axiom), 74
 OWLPropertyExpression (class in owlapy.owl_property), 100
 OWLPropertyRange (class in owlapy.owl_data_ranges), 76
 OWLPropertyRangeAxiom (class in owlapy.owl_axiom), 74
 OWLQuantifiedDataRestriction (class in owlapy.class_expression), 40
 OWLQuantifiedDataRestriction (class in owlapy.class_expression.restriction), 28
 OWLQuantifiedObjectRestriction (class in owlapy.class_expression), 37
 OWLQuantifiedObjectRestriction (class in owlapy.class_expression.restriction), 23
 OWLQuantifiedRestriction (class in owlapy.class_expression), 37
 OWLQuantifiedRestriction (class in owlapy.class_expression.restriction), 23
 OWLRDFVocabulary (class in owlapy.vocab), 145
 OWLREADY2_FACET_KEYS (in module owlapy.owl_ontology), 96
 OWLReasoner (class in owlapy.owl_reasoner), 103
 OWLReasonerEx (class in owlapy.owl_reasoner), 109
 OWLReflexiveObjectPropertyAxiom (class in owlapy.owl_axiom), 72
 OWLRestriction (class in owlapy.class_expression), 37
 OWLRestriction (class in owlapy.class_expression.restriction), 22
 OWLSameIndividualAxiom (class in owlapy.owl_axiom), 62
 OWLSubAnnotationPropertyOfAxiom (class in owlapy.owl_axiom), 68
 OWLSubClassOfAxiom (class in owlapy.owl_axiom), 64
 OWLSubDataPropertyOfAxiom (class in owlapy.owl_axiom), 69
 OWLSubObjectPropertyOfAxiom (class in owlapy.owl_axiom), 69
 OWLSubPropertyAxiom (class in owlapy.owl_axiom), 69
 OWLSymmetricObjectPropertyAxiom (class in owlapy.owl_axiom), 73
 OWLTopDataProperty (in module owlapy.owl_literal), 86
 OWLTopObjectProperty (in module owlapy.owl_literal), 85
 OWLTransitiveObjectPropertyAxiom (class in owlapy.owl_axiom), 73
 OWLUnaryPropertyAxiom (class in owlapy.owl_axiom), 71

P

parent (owlapy.converter.Owl2SparqlConverter attribute), 49
 parent_var (owlapy.converter.Owl2SparqlConverter attribute), 49
 parents () (owlapy.owl_hierarchy.AbstractHierarchy method), 79
 parse_boolean () (owlapy.owl_literal.OwLLiteral method), 84
 parse_date () (owlapy.owl_literal.OwLLiteral method), 85
 parse_datetime () (owlapy.owl_literal.OwLLiteral method), 85
 parse_double () (owlapy.owl_literal.OwLLiteral method), 84
 parse_duration () (owlapy.owl_literal.OwLLiteral method), 85
 parse_expression () (owlapy.owl_object.OwLObjectParser method), 87
 parse_expression () (owlapy.parser.DLSyntaxParser method), 133
 parse_expression () (owlapy.parser.ManchesterOWLSyntaxParser method), 131

`parse_integer()` (*owlapy.owl_literal.OWLLiteral method*), 84
`parse_string()` (*owlapy.owl_literal.OWLLiteral method*), 85
`parser` (*owlapy.owlapi_mapper.OWLAPIMapper attribute*), 130
`path` (*owlapy.owl_ontology.SyncOntology attribute*), 94
`PATTERN` (*owlapy.class_expression.OWLFacet attribute*), 43
`PATTERN` (*owlapy.vocab.OWLFacet attribute*), 147
`peek()` (*in module owlapy.converter*), 49
`prefix` (*owlapy.namespaces.Namespaces property*), 54
`PREV` (*owlapy.utils.LRUCache attribute*), 144
`process()` (*owlapy.converter.Owl2SparqlConverter method*), 50
`prop_cnt` (*owlapy.converter.VariablesMapping attribute*), 49
`properties` (*owlapy.converter.Owl2SparqlConverter attribute*), 49
`properties()` (*owlapy.owl_axiom.OWLNaryPropertyAxiom method*), 63

R

`RDF` (*in module owlapy.namespaces*), 55
`RDFS` (*in module owlapy.namespaces*), 54
`RDFS_LITERAL` (*owlapy.vocab.OWLRDFVocabulary attribute*), 146
`reminder` (*owlapy.class_expression.owl_class.OWLClass property*), 19
`reminder` (*owlapy.class_expression.OWLClass property*), 36
`reminder` (*owlapy.iri.IRI property*), 52
`remove_axiom()` (*owlapy.owl_ontology.Ontology method*), 93
`remove_axiom()` (*owlapy.owl_ontology.OWLOntology method*), 91
`render()` (*owlapy.converter.Owl2SparqlConverter method*), 50
`render()` (*owlapy.owl_object.OWLObjectRenderer method*), 87
`render()` (*owlapy.render.DLSyntaxObjectRenderer method*), 138
`render()` (*owlapy.render.ManchesterOWLSyntaxOWLObjectRenderer method*), 138
`renderer` (*owlapy.owlapi_mapper.OWLAPIMapper attribute*), 130
`reset()` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 116
`restrict()` (*owlapy.owl_hierarchy.AbstractHierarchy static method*), 79
`restrict_and_copy()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 79
`Restriction_Literals` (*in module owlapy.providers*), 136
`RESULT` (*owlapy.utils.LRUCache attribute*), 145
`root` (*owlapy.utils.LRUCache attribute*), 145
`roots()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 80

S

`same_individuals()` (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 118
`same_individuals()` (*owlapy.owl_reasoner.OntologyReasoner method*), 112
`same_individuals()` (*owlapy.owl_reasoner.OWLReasoner method*), 105
`same_individuals()` (*owlapy.owl_reasoner.SyncReasoner method*), 126
`save()` (*owlapy.owl_ontology.Ontology method*), 93
`save()` (*owlapy.owl_ontology.OWLOntology method*), 91
`save_world()` (*owlapy.owl_ontology_manager.OntologyManager method*), 99
`sentinel` (*owlapy.utils.LRUCache attribute*), 144, 145
`set_short_form_provider()` (*owlapy.owl_object.OWLObjectRenderer method*), 87
`set_short_form_provider()` (*owlapy.render.DLSyntaxObjectRenderer method*), 138
`set_short_form_provider()` (*owlapy.render.ManchesterOWLSyntaxOWLObjectRenderer method*), 138
`siblings()` (*owlapy.owl_hierarchy.AbstractHierarchy method*), 80
`simplify()` (*owlapy.utils.OperandSetTransform method*), 143
`slots` (*owlapy.parser.DLSyntaxParser attribute*), 133
`slots` (*owlapy.parser.ManchesterOWLSyntaxParser attribute*), 131
`sort()` (*owlapy.utils.ConceptOperandSorter method*), 143
`sparql` (*owlapy.converter.Owl2SparqlConverter attribute*), 49
`stack_parent()` (*owlapy.converter.Owl2SparqlConverter method*), 50
`stack_variable()` (*owlapy.converter.Owl2SparqlConverter method*), 50
`startJVM()` (*in module owlapy.static_funcs*), 139
`stopJVM()` (*in module owlapy.static_funcs*), 139
`str` (*owlapy.class_expression.owl_class.OWLClass property*), 19
`str` (*owlapy.class_expression.OWLClass property*), 36
`str` (*owlapy.iri.IRI property*), 52
`str` (*owlapy.meta_classes.HasIRI property*), 53
`str` (*owlapy.owl_axiom.OWLAnnotationProperty property*), 66
`str` (*owlapy.owl_datatype.OWLDatatype property*), 78
`str` (*owlapy.owl_individual.OWLNamedIndividual property*), 82
`str` (*owlapy.owl_ontology_manager.OWLImportsDeclaration property*), 98
`str` (*owlapy.owl_property.OWLProperty property*), 101

STRING (*owlapy.vocab.XSDVocabulary attribute*), 146
 StringOWLDatatype (*in module owlapy.owl_literal*), 86
 sub_classes() (*owlapy.owl_hierarchy.ClassHierarchy method*), 80
 sub_classes() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 120
 sub_classes() (*owlapy.owl_reasoner.OntologyReasoner method*), 113
 sub_classes() (*owlapy.owl_reasoner.OWLReasoner method*), 106
 sub_classes() (*owlapy.owl_reasoner.SyncReasoner method*), 123
 sub_data_properties() (*owlapy.owl_hierarchy.DatatypePropertyHierarchy method*), 81
 sub_data_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 121
 sub_data_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 115
 sub_data_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 107
 sub_data_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 125
 sub_object_properties() (*owlapy.owl_hierarchy.ObjectPropertyHierarchy method*), 81
 sub_object_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 122
 sub_object_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 115
 sub_object_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 108
 sub_object_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 125
 super_classes() (*owlapy.owl_hierarchy.ClassHierarchy method*), 80
 super_classes() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 120
 super_classes() (*owlapy.owl_reasoner.OntologyReasoner method*), 114
 super_classes() (*owlapy.owl_reasoner.OWLReasoner method*), 109
 super_classes() (*owlapy.owl_reasoner.SyncReasoner method*), 123
 super_data_properties() (*owlapy.owl_hierarchy.DatatypePropertyHierarchy method*), 81
 super_data_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 122
 super_data_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 115
 super_data_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 108
 super_data_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 126
 super_object_properties() (*owlapy.owl_hierarchy.ObjectPropertyHierarchy method*), 81
 super_object_properties() (*owlapy.owl_reasoner.FastInstanceCheckerReasoner method*), 122
 super_object_properties() (*owlapy.owl_reasoner.OntologyReasoner method*), 115
 super_object_properties() (*owlapy.owl_reasoner.OWLReasoner method*), 108
 super_object_properties() (*owlapy.owl_reasoner.SyncReasoner method*), 125
 symbolic_form (*owlapy.class_expression.OWLFacet property*), 43
 symbolic_form (*owlapy.vocab.OWLFacet property*), 146
 SyncOntology (*class in owlapy.owl_ontology*), 94
 SyncOntologyManager (*class in owlapy.owl_ontology_manager*), 99
 SyncReasoner (*class in owlapy.owl_reasoner*), 123

T

TIME_DATATYPES (*in module owlapy.owl_literal*), 86
 to_list() (*owlapy.owlapi_mapper.OWLAPIMapper static method*), 130
 to_python() (*owlapy.owl_literal.OWLLiteral method*), 85
 to_string_id() (*owlapy.owl_object.OWLEntity method*), 88
 ToOwlready2 (*class in owlapy.owl_ontology*), 96
 TopLevelCNF (*class in owlapy.utils*), 144
 TopLevelDNF (*class in owlapy.utils*), 144
 TopOWLDatatype (*in module owlapy.owl_literal*), 86
 TOTAL_DIGITS (*owlapy.class_expression.OWLFacet attribute*), 43
 TOTAL_DIGITS (*owlapy.vocab.OWLFacet attribute*), 147
 translating_short_form_endpoint() (*in module owlapy.render*), 137
 translating_short_form_provider() (*in module owlapy.render*), 137
 triple() (*owlapy.converter.Owl2SparqlConverter method*), 50
 type_index (*owlapy.class_expression.class_expression.OWLObjectComplementOf attribute*), 17
 type_index (*owlapy.class_expression.nary_boolean_expression.OWLObjectIntersectionOf attribute*), 19
 type_index (*owlapy.class_expression.nary_boolean_expression.OWLObjectUnionOf attribute*), 18
 type_index (*owlapy.class_expression.owl_class.OWLClass attribute*), 19
 type_index (*owlapy.class_expression.OWLClass attribute*), 35
 type_index (*owlapy.class_expression.OWLDataAllValuesFrom attribute*), 46
 type_index (*owlapy.class_expression.OWLDataExactCardinality attribute*), 47
 type_index (*owlapy.class_expression.OWLDataHasValue attribute*), 46
 type_index (*owlapy.class_expression.OWLDataMaxCardinality attribute*), 47
 type_index (*owlapy.class_expression.OWLDataMinCardinality attribute*), 47
 type_index (*owlapy.class_expression.OWLDataOneOf attribute*), 40
 type_index (*owlapy.class_expression.OWLDataSomeValuesFrom attribute*), 45
 type_index (*owlapy.class_expression.OWLDatatypeRestriction attribute*), 43
 type_index (*owlapy.class_expression.OWLFacetRestriction attribute*), 44
 type_index (*owlapy.class_expression.OWLObjectAllValuesFrom attribute*), 42

type_index (owlapy.class_expression.OwlObjectComplementOf attribute), 35
 type_index (owlapy.class_expression.OwlObjectExactCardinality attribute), 45
 type_index (owlapy.class_expression.OwlObjectHasSelf attribute), 40
 type_index (owlapy.class_expression.OwlObjectHasValue attribute), 42
 type_index (owlapy.class_expression.OwlObjectIntersectionOf attribute), 37
 type_index (owlapy.class_expression.OwlObjectMaxCardinality attribute), 44
 type_index (owlapy.class_expression.OwlObjectMinCardinality attribute), 44
 type_index (owlapy.class_expression.OwlObjectOneOf attribute), 47
 type_index (owlapy.class_expression.OwlObjectSomeValuesFrom attribute), 41
 type_index (owlapy.class_expression.OwlObjectUnionOf attribute), 37
 type_index (owlapy.class_expression.restriction.OwlDataAllValuesFrom attribute), 30
 type_index (owlapy.class_expression.restriction.OwlDataExactCardinality attribute), 29
 type_index (owlapy.class_expression.restriction.OwlDataHasValue attribute), 30
 type_index (owlapy.class_expression.restriction.OwlDataMaxCardinality attribute), 29
 type_index (owlapy.class_expression.restriction.OwlDataMinCardinality attribute), 28
 type_index (owlapy.class_expression.restriction.OwlDataOneOf attribute), 31
 type_index (owlapy.class_expression.restriction.OwlDataSomeValuesFrom attribute), 29
 type_index (owlapy.class_expression.restriction.OwlDatatypeRestriction attribute), 31
 type_index (owlapy.class_expression.restriction.OwlFacetRestriction attribute), 32
 type_index (owlapy.class_expression.restriction.OwlObjectAllValuesFrom attribute), 25
 type_index (owlapy.class_expression.restriction.OwlObjectExactCardinality attribute), 25
 type_index (owlapy.class_expression.restriction.OwlObjectHasSelf attribute), 26
 type_index (owlapy.class_expression.restriction.OwlObjectHasValue attribute), 26
 type_index (owlapy.class_expression.restriction.OwlObjectMaxCardinality attribute), 24
 type_index (owlapy.class_expression.restriction.OwlObjectMinCardinality attribute), 24
 type_index (owlapy.class_expression.restriction.OwlObjectOneOf attribute), 27
 type_index (owlapy.class_expression.restriction.OwlObjectSomeValuesFrom attribute), 25
 type_index (owlapy.iri.IRI attribute), 51
 type_index (owlapy.owl_data_ranges.OwlDataComplementOf attribute), 77
 type_index (owlapy.owl_data_ranges.OwlDataIntersectionOf attribute), 77
 type_index (owlapy.owl_data_ranges.OwlDataUnionOf attribute), 77
 type_index (owlapy.owl_datatype.OwlDatatype attribute), 78
 type_index (owlapy.owl_individual.OwlNamedIndividual attribute), 82
 type_index (owlapy.owl_literal.OwlLiteral attribute), 84
 type_index (owlapy.owl_ontology.OwlOntology attribute), 89
 type_index (owlapy.owl_property.OwlDataProperty attribute), 102
 type_index (owlapy.owl_property.OwlObjectInverseOf attribute), 102
 type_index (owlapy.owl_property.OwlObjectProperty attribute), 101
 type_index (owlapy.utils.HasIndex attribute), 143
 types () (owlapy.owl_reasoner.FastInstanceCheckerReasoner method), 120
 types () (owlapy.owl_reasoner.OntologyReasoner method), 116
 types () (owlapy.owl_reasoner.OwlReasoner method), 108
 types () (owlapy.owl_reasoner.SyncReasoner method), 127

V

values () (owlapy.class_expression.OwlDataOneOf method), 40
 values () (owlapy.class_expression.restriction.OwlDataOneOf method), 31
 variable_entities (owlapy.converter.Owl2SparqlConverter attribute), 49
 variables (owlapy.converter.Owl2SparqlConverter attribute), 49
 VariablesMapping (class in owlapy.converter), 49
 visit_abbreviated_iri () (owlapy.parser.DLSyntaxParser method), 135
 visit_abbreviated_iri () (owlapy.parser.ManchesterOWLSyntaxParser method), 133
 visit_boolean_literal () (owlapy.parser.DLSyntaxParser method), 134
 visit_boolean_literal () (owlapy.parser.ManchesterOWLSyntaxParser method), 132
 visit_cardinality_res () (owlapy.parser.DLSyntaxParser method), 133
 visit_cardinality_res () (owlapy.parser.ManchesterOWLSyntaxParser method), 131
 visit_class_expression () (owlapy.parser.DLSyntaxParser method), 134
 visit_class_expression () (owlapy.parser.ManchesterOWLSyntaxParser method), 131
 visit_class_iri () (owlapy.parser.DLSyntaxParser method), 135
 visit_class_iri () (owlapy.parser.ManchesterOWLSyntaxParser method), 132
 visit_data_cardinality_res () (owlapy.parser.DLSyntaxParser method), 134
 visit_data_cardinality_res () (owlapy.parser.ManchesterOWLSyntaxParser method), 132
 visit_data_intersection () (owlapy.parser.DLSyntaxParser method), 134
 visit_data_intersection () (owlapy.parser.ManchesterOWLSyntaxParser method), 132
 visit_data_parentheses () (owlapy.parser.DLSyntaxParser method), 134
 visit_data_parentheses () (owlapy.parser.ManchesterOWLSyntaxParser method), 132
 visit_data_primary () (owlapy.parser.DLSyntaxParser method), 134

`visit_data_primary()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_data_property_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_data_property_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_data_some_only_res()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_data_some_only_res()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_data_union()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_data_union()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_data_value_res()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_data_value_res()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_datatype()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_datatype()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_datatype_iri()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_datatype_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_datatype_restriction()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_datatype_restriction()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_date_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_date_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_datetime_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_datetime_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_decimal_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_decimal_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_duration_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_duration_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_facet()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_facet()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_facet_restriction()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_facet_restriction()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_facet_restrictions()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_facet_restrictions()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_float_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_float_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_full_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_full_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 133
`visit_has_self()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_has_self()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_individual_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_individual_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_individual_list()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_individual_list()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_integer_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_integer_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_intersection()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_intersection()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 133
`visit_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_literal_list()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_literal_list()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_non_negative_integer()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_non_negative_integer()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_object_property()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_object_property()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_object_property_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_object_property_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_parentheses()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_parentheses()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 133
`visit_primary()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_primary()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_quoted_string()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_quoted_string()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_simple_iri()` (*owlapy.parser.DLSyntaxParser method*), 135
`visit_simple_iri()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 133
`visit_some_only_res()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_some_only_res()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_string_literal_language()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_string_literal_language()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_string_literal_no_language()` (*owlapy.parser.DLSyntaxParser method*), 134

`visit_string_literal_no_language()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_typed_literal()` (*owlapy.parser.DLSyntaxParser method*), 134
`visit_typed_literal()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 132
`visit_union()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_union()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131
`visit_value_res()` (*owlapy.parser.DLSyntaxParser method*), 133
`visit_value_res()` (*owlapy.parser.ManchesterOWLSyntaxParser method*), 131

W

`worst()` (*owlapy.utils.EvaluatedDescriptionSet method*), 143

X

XSD (*in module owlapy.namespaces*), 55
XSDVocabulary (*class in owlapy.vocab*), 146