Contents

1 Introduction **1**
- 1.1 Overcoming the Disparate Data Space . . . 1
- 1.2 Motivation . . . 1
- 1.3 Contributions . . . 1

2 The Ontology Matching Problem **2**
- 2.1 Definition . . . 2
- 2.2 State-of-the Art . . . 2
- 2.3 Challenges . . . 2

3 Ontology Matching Approaches (Related Work) **3**
- 3.1 Classification of Approaches . . . 3
- 3.2 Base Matcher . . . 4
  - 3.2.1 Label Based . . . 4
  - 3.2.2 Instance Based . . . 4
  - 3.2.3 Structure Based . . . 4
- 3.3 Hybrid Matching Approaches . . . 4
- 3.4 Analysis of Hybrid Matching Approaches . . . 4

4 Hybrid Ontology Matching using Outlier Analysis **5**
- 4.1 Definition Outlier Analysis . . . 5
- 4.2 Motivation for using Outlier Analysis for Ontology Matching . . . 5
- 4.3 Ontology Matching as an Outlier Detection Problem . . . 5
  - 4.3.1 Creating the Feature Vector . . . 5
  - 4.3.2 Significance of Outliers for Ontology Matching . . . 5
  - 4.3.3 Transforming the Outlier Analysis Result to a Matching . . . 5

5 A Matching Pipeline using Outlier Detection **6**
- 5.1 Overview . . . 6
- 5.2 Base Matcher used . . . 6

5.3 Methods used to combine Matcher 6
5.4 Feature Selection 6
5.5 Outlier Analysis 6

6 Evaluation **7**
6.1 Datasets 7
6.2 Experimental Setup 7
6.3 Used Baselines 7
6.4 Results 7

7 Discussion **8**
7.1 Flexibility towards changing Data Domains 8
7.2 Runtime Considerations 8
7.3 Comparison with current OAEI Participants 8

8 Conclusion **9**