

**DEPARTMENT OF COMPUTER SCIENCE AND
ENGINEERING**

CSP81: PROJECT WORK
TERM: Feb-June 2025

Project Mid Term Report

Guide
Dr. Mallegowda M.

TEAM MEMBERS

Sl. No	USN	Name
1.	1MS22CS011	Aditri B Ray
2.	1MS22CS028	Anisha Ajit
3.	1MS22CS051	Diya D Shah

Guide Signature:_____

Table of Contents

Chapter No	Content	Page No
1	Introduction	3
2	Literature Survey	5
	2.1 Introduction to the Literature Survey	5
	2.2 Related Works	6
	2.3 Research Gaps Identified	13
3	Software Requirement Specification	15
	3.1 Scope	15
	3.2 Overall Description	15
	3.2.1 Product Functions	15
	3.2.2 User Characteristics	16
	3.2.3 Constraints	16
	3.3 Assumptions and Dependencies	16
	3.4 Specific Requirements	17
	3.4.1 Functional Requirements	17
	3.4.2 Non-Functional Requirements	17
	3.4.3 External Interface Requirements	18
4	System Design	19
	4.1 Architectural Design	19
	4.2 Data Flow Database Design	23
	4.3 User Interface Design	30
	4.3.1 Component Design	32
	4.4 Class diagram and classes	35
	4.5 Sequence diagram	42

	4.6 Security & Performance Considerations	44
	4.7 Technology Stack Selection	46
	4.8 Scalability Reliability Planning	47
	4.9 Conclusion	49
5	Implementation	50
	5.1 Overview of the implementation process	50
	5.2 Development Tools and Technologies	50
	5.3 Implementation Process	52
	5.4 Module-wise Implementation	54
	5.5 Challenges and solutions	56
	5.6 Security and Performance considerations	58
	5.7 Conclusion	60
6	Conclusion	61
7	Future Work	62
	References	63

1. Introduction

Floods are among the most destructive natural disasters affecting urban environments, often resulting in significant loss of life, infrastructure damage, and economic disruption. Rapid urbanization combined with climate variability has increased the frequency and severity of flood events, making effective evacuation planning a critical requirement for city authorities and disaster management agencies. Traditional evacuation planning methods are often static and fail to account for real-time environmental changes such as rainfall intensity, water spread, and traffic congestion.

To address these challenges, the Digital Twin–Driven Flood Evacuation System provides a dynamic simulation platform that models urban environments and evaluates evacuation strategies under different flood scenarios. The system is designed as a client–server web application, where a high-performance backend built with Python and FastAPI performs flood simulations, traffic analysis, and AI-based route optimization, while a React.js and MapLibre-powered frontend provides interactive visualization of flood propagation and evacuation routes. Communication between the frontend and backend occurs through REST APIs for configuration and data retrieval, and Server-Sent Events (SSE) for streaming real-time simulation updates. This architecture enables efficient computation while maintaining a responsive and intuitive user interface for decision-makers.

1.1 Purpose

The purpose of the Digital Twin–Driven Flood Evacuation System is to provide urban planners and disaster response authorities with a sophisticated, data-driven platform for managing flood emergencies. This document outlines the software requirements for a system that integrates real-time environmental data, physics-based flood simulations, and advanced AI optimization algorithms to generate dynamic, life-saving evacuation strategies.

1.2 Scope

The scope of this project encompasses the design, development, and deployment of a web-based simulation platform. The system capabilities include:

- High-Fidelity Digital Twin: Automatic generation of urban road networks and elevation models for specific administrative regions (Hoblis) using OpenStreetMap (OSM) and SRTM data.
- Dynamic Simulation Engine: Modeling of flood propagation based on variable rainfall intensity (mm) and terrain topology.
- Multi-Algorithm AI Engine: Implementation of three distinct metaheuristic algorithms—Genetic Algorithm (GA), Ant Colony Optimization (ACO), and Particle Swarm Optimization (PSO)—to compute optimal evacuation routes.
- Real-Time Traffic Integration: Utilization of the TomTom Traffic API to fetch live congestion data, ensuring routes are realistic and avoid gridlocked areas.
- Interactive Visualization: A dashboard interface for real-time monitoring of flood risks, shelter capacities, and evolving evacuation paths.

Current Limitation: The system utilizes software-based simulation and third-party APIs; it does not currently interface with physical IoT water-level sensors or autonomous vehicle hardware.

2. Literature Survey

2.1 Introduction

2.1.1 Purpose of Literature Survey

Disaster management has emerged as a critical domain of research due to escalating urban flood risks driven by climate change, population density, and infrastructure limitations. Digital Twin (DT) technology offers transformative potential by creating dynamic virtual replicas of urban environments for flood simulation, evacuation route optimization, and real-time decision support. This literature survey examines recent advancements (2023-2025) to establish theoretical foundations for our Digital Twin-Driven Flood Evacuation System with AI Optimization.

The purpose of this survey is to systematically analyze peer-reviewed contributions from IEEE, Springer, Elsevier, ACM, MDPI, and ScienceDirect, identifying established methodologies while highlighting gaps our project addresses. Recent works demonstrate progress in AI-enhanced flood prediction, graph-based routing, and city-scale digital twins, yet few integrate multi-algorithm pathfinding with generative AI strategy generation within lightweight, simulation-only frameworks.

2.1.2 Scope of Survey

2.1.2.1 Digital Twin Applications in Flood Management

Recent scholarly work showcases DT evolution from conceptual frameworks to operational platforms. Zhang et al. apply deep reinforcement learning for rescue path optimization under pluvial flooding, while Li et al. integrate hydrodynamic models with multi-objective evacuation planning. Gupta et al. synthesize AI advancements showing superior prediction speed over physics-based hydrology. Zhou et al. develop rainfall-responsive digital twins, and Mandal et al. demonstrate city-scale infrastructure impact analysis.

2.1.2.2 Evacuation Routing and Optimization Advances

Routing optimization remains central to effective response. Chen et al. validate large-scale agent simulations for 50k evacuees, while Yin et al. review metaheuristic dominance in complex scenarios. Alizadeh et al. fuse crowdsourced data for hyper-local routing, and Behrooz/Ilbeigi achieve 74% flow improvements through adaptive road reversal. Basheer et al. balance multi-criteria via fuzzy AHP, demonstrating 22% time savings.

2.1.2.3 Smart City Resilience Integration

DT synergy with smart infrastructure is increasingly vital. Riaz et al. combine 3D models with early warning systems, while Prihatmanto et al. show 18% evacuation efficiency gains through city-scale twins. Anik et al. trace ML prediction evolution, and Wang et al. quantify dynamic congestion evolution. These works establish resilience foundations but reveal gaps in algorithm comparison and AI decision support.

This survey categorizes contributions across three themes: (i) predictive digital twins and flood modeling, (ii) multi-algorithm evacuation routing, and (iii) AI-enhanced decision frameworks. By synthesizing these advancements, we identify opportunities for integrated systems combining OSMnx-based twins, classical graph algorithms (Dijkstra/A*/Quanta), and generative AI strategy synthesis—precisely addressing limitations in current literature.

2.2 Related Works

Title	Author(s)	Year	Model / Technique / Algorithm / Methodology Used	Parameters / Features	Result Discussion	Shortcomings / Advantages & Disadvantages
Deep reinforcement learning for optimal rescue path planning	X. Zhang et al.	2023	Deep Reinforcement Learning (DRL) with risk-probability grids	Water depth, congestion, uncertainty modeling	Outperformed Dijkstra by 20% in safety under uncertainty	High training time; black-box decisions
A novel emergency evacuation route optimization model	J. Li et al.	2024	Hydrodynamic modeling + multi-objective optimization	Flood depth, traffic capacity, shelter proximity	Reduced evacuation time by 25%	Computationally intensive
Artificial intelligence for flood risk management	A. Gupta et al.	2025	Review of AI models (MLPs, CNNs, Transformers)	Data fusion, forecasting horizons 1–72 hours	AI outperforms physics models in speed	Lacks unified evacuation framework

A framework for incorporating rainfall data	Y. Zhou et al.	2025	Rainfall integration in hydrological digital twin	Real-time rainfall, 2D inundation maps	Improved prediction responsiveness	No evacuation routing integration
Large-scale real-time evacuation modeling	Y. Chen et al.	2025	Agent-based modeling with GIS integration	50k evacuees, shelter distribution	Feasibility for city-scale simulation	High memory requirements
City-scale digital twin framework	D. Mandal et al.	2025	Digital twin with hydrological models	Sensor data, GIS, 3D flood simulations	Holistic impact assessment	No multi-algorithm routing
An overview of flood evacuation planning	H. Yin et al.	2025	Systematic review of evacuation models	Hazard mapping, shelter optimization	Comprehensive modeling paradigms	No specific DT implementation
Human-centered flood mapping and routing	S. Alizadeh et al.	2023	Gauge data + crowdsourced photo fusion	Depth estimation, routing cost updates	Accurate local depth estimates	Variable crowdsourced data quality
Management of climate resilience	K. Riaz et al.	2023	Digital twin + 3D city models	Climate inputs, sensor triggers	Proactive smart city response	High infrastructure costs
The Digital Twin City in evacuation	A. Prihatman et al.	2025	City-scale digital twin simulation	Inundation, evacuation flows	18% evacuation time savings	Prototype stage

Adaptive emergency evacuation routing	H. Behrooz, M. Ilbeigi	2024	DFS-based direction-aware reversal	Adaptive traffic flow modeling	74% more efficient than static DFS	Assumes traffic control availability
Priority search simulation model	A. Basheer et al.	2023	Fuzzy AHP + priority queue in GIS	Road status, water depth, distance	22% time reduction	Weight tuning sensitivity
Evolution from physical to ML models	M. S. B. M. A. Anik et al.	2025	Review of flood prediction evolution	GIS, LiDAR, ML/DL models	ML > physics models in speed	Limited evacuation discussion
Urban flooding digital twin framework	Y. Zhou et al.	2024	Conceptual DT lifecycle framework	What-if scenarios, XR planning	Comprehensive preparedness framework	Conceptual only
Dynamic congestion risk assessment	J. Wang et al.	2024	Time-variant topological analysis	Network topology, traffic demand	Identifies critical congestion windows	Risk assessment only
Development of an Urban Flood Model for Bengaluru City, Karnataka, India	P. P. Mujumdar et al.	2021	SWMM-based hydrological modeling + sensor-based forecasting	Rainfall sensors, runoff modeling, early warning dissemination	Enables near real-time flood prediction for urban areas	Does not address evacuation routing
Ant Colony Optimization	W. Xu & K. Zhang	2024	Multi-agent simulation + Ant Colony	Waterlogging effects, vehicle	Efficient multi-center rescue route planning under	Limited real-time

for Urban Flood Rescue Routing			Optimization (ACO)	routing constraints	flood conditions	integration; no digital twin
Optimising Urban Flood Evacuation Routes with Metaheuristic Algorithms	C. Li et al.	2025	Improved ACO, PSO, GA, SSA metaheuristics	Hazard ratings, travel time, route simplicity	IACO safest; IPSO fastest; IGA simplest routes	Case-study specific; lacks dynamic flood propagation
An Intelligent Optimization Method for Evacuation Routes	H. Nirwana et al.	2024	BFS, DFS, Greedy-Backtracking, Genetic Algorithm	Route distance, disaster impact zones	Comparative evaluation identifies most efficient algorithm	Static modeling; no real-time hazard updates
Integrated urban flood management in India—technology driven solutions	Mujumdar P et al.	2020	Hydrological & hydraulic flood modeling framework	DEM data, SWMM modeling, risk assessment	Structured methodology for urban flood risk analysis	Focuses on modeling, not evacuation optimization

2.1 Tabular Summary of Related Papers (2020–2025)

In [1], the authors propose a deep reinforcement learning framework for optimal rescue path planning under uncertain and complex urban pluvial flood conditions. The model represents the road network as a grid enriched with probabilistic flood risk, water depth, and congestion information, enabling the agent to learn safe and adaptive rescue paths. Compared to classical shortest-path approaches, the method improves safety metrics and adaptability under uncertainty. However, the training process requires significant computational resources and the learned policy lacks interpretability, making it difficult for emergency planners to validate or justify decisions.

A multi-objective emergency evacuation route optimization model for flood disasters is presented in [2], integrating hydrodynamic flood modeling with network-based optimization. The framework considers flood depth, road capacity, travel time, and

shelter allocation to generate safer evacuation paths across different flood scenarios. The results demonstrate reduced total evacuation time and improved network-level safety compared to static routing strategies. Nevertheless, the approach is computationally intensive and depends heavily on accurate hydrodynamic simulations and static population assumptions.

A comprehensive review of artificial intelligence applications in flood risk management is provided in [3], covering machine learning, deep learning, and hybrid physical–data-driven approaches. The study highlights the increasing shift from traditional hydrological models toward AI-based systems that leverage multi-source data such as gauges, radar, and satellite imagery. While AI models often outperform classical techniques in prediction accuracy and computational speed, the review emphasizes that most systems focus solely on forecasting and lack integration with evacuation routing or digital twin decision-support systems.

In [4], a digital twin framework is proposed for incorporating real-time rainfall data into flood simulations. By embedding hydrological and hydraulic models within a digital twin architecture, the framework improves the responsiveness and realism of flood inundation mapping. Although this enhances hydraulic accuracy, the study focuses primarily on flood monitoring and prediction rather than evacuation routing or algorithmic optimization, leaving the routing and planning layer largely unexplored.

A large-scale real-time evacuation modeling approach for urban floods is introduced in [5], combining agent-based modeling with dynamic network simulations. The system simulates thousands of evacuees interacting within a flooded transportation network, capturing congestion, bottlenecks, and shelter capacity constraints. The results show that city-scale evacuation simulations are feasible and valuable for policy evaluation. However, the approach requires substantial computational power and does not compare multiple routing algorithms or incorporate AI-based strategy synthesis.

The integration of flood forecasting, transportation networks, and infrastructure systems within a city-scale digital twin is explored in [6]. This framework provides a holistic view of flood impacts on urban mobility and infrastructure, enabling resilience planning through scenario-based analysis. While effective for impact assessment and visualization, the study does not implement detailed evacuation routing algorithms or provide algorithmic benchmarking under varying flood intensities.

A systematic overview of flood evacuation planning models is presented in [7], categorizing approaches into hazard mapping, optimization-based routing, and agent-based simulations. The review highlights the role of metaheuristic algorithms and simulation–optimization frameworks in evacuation planning. Despite the wide range of

models discussed, the authors note that integrated systems combining digital twins, routing algorithms, and intelligent decision-support mechanisms remain limited.

In [8], a human-centered flood mapping approach is developed by augmenting gauge data with crowdsourced street photographs to improve local water depth estimation. The refined flood maps are then used to update routing costs, resulting in improved safety decisions. While this data fusion enhances situational awareness, the study focuses more on mapping accuracy and localized routing adjustments rather than on comprehensive digital twin design or multi-algorithm comparison.

The potential of digital twin technology and 3D city modeling for climate resilience is investigated in [9]. The framework integrates real-time climate inputs, 3D visualization, and early warning mechanisms to support proactive flood management. Although it demonstrates strong architectural potential, the application to evacuation routing and algorithmic evaluation remains conceptual and lacks detailed optimization implementation.

A digital twin city concept for enhancing flood evacuation systems is described in [10], emphasizing real-time simulation of inundation and evacuation flows. The study demonstrates that digital twin-based simulations can improve evacuation efficiency by enabling scenario testing before real-world deployment. However, the work remains largely prototype-level and does not provide detailed routing algorithm analysis or AI-assisted planning components.

Adaptive emergency evacuation routing with directional road control is examined in [11], where dynamic lane reversal strategies are used to maximize network flow during emergencies. Applied to a real-world urban network, the method achieves significant improvements in evacuation efficiency compared to static strategies. Nevertheless, the approach assumes strong centralized traffic control capabilities and focuses on a specific routing mechanism without broader algorithmic comparison.

A GIS-based flood evacuation model incorporating fuzzy Analytic Hierarchy Process (AHP) and priority search is presented in [12]. The model evaluates multiple criteria, including water depth, road status, distance, and evacuation time, to compute optimal routes. While the integration of fuzzy weights improves route selection compared to simple shortest-path methods, the approach is sensitive to parameter tuning and lacks integration with a digital twin architecture or AI-driven optimization layers.

The evolution from physical process-based flood prediction models to machine learning approaches is reviewed in [13]. The study highlights how GIS, LiDAR, and deep learning models are increasingly used to improve urban flood forecasting. Despite improvements in predictive performance, the review points out that most models terminate at the

prediction stage and do not extend into evacuation routing or digital twin-based decision systems.

A conceptual framework for an urban flooding digital twin system is proposed in [14], focusing on scenario generation, preparedness simulation, and stakeholder collaboration. The framework emphasizes lifecycle management of flooding events across preparedness, response, and recovery phases. However, it remains largely conceptual and does not detail routing algorithm integration or AI-driven evacuation strategy generation.

Dynamic congestion risks in flood-disrupted transportation networks are analyzed in [15] using time-variant topological measures and traffic demand modeling. The study quantifies evolving congestion vulnerabilities and identifies critical network links under flood conditions. While valuable for risk assessment, the approach does not compute optimized evacuation routes nor incorporate digital twin platforms or generative AI for decision support.

Ant Colony Optimization for multi-center urban flood rescue routing is presented in [16]. The study models flood-affected regions as weighted graphs with edge costs based on inundation severity and road accessibility. ACO improves convergence speed and reduces evacuation time compared to traditional shortest-path methods. However, it assumes static flood conditions, lacks real-time hydrodynamic integration, and depends heavily on parameter tuning.

An integrated urban flood modeling framework for Bengaluru city is discussed in [17], combining hydrological simulations with GIS-based mapping for improved flood forecasting. The study enhances hazard identification and drainage analysis but focuses mainly on prediction rather than evacuation optimization. It does not incorporate AI-based routing or real-time decision-support mechanisms.

A structured urban flood risk assessment framework is presented in [18], emphasizing watershed modeling, drainage evaluation, and GIS-based vulnerability mapping. While it strengthens preparedness and infrastructure planning, it does not include adaptive evacuation routing or digital twin integration for dynamic response management.

Comparative metaheuristic evacuation routing techniques are evaluated in [19], including ACO, PSO, GA, and SSA. The study integrates hazard and safety parameters into route optimization, showing strong convergence performance. However, it assumes static flood scenarios and lacks real-time simulation or digital twin synchronization.

An intelligent evacuation routing approach is analyzed in [20], comparing classical graph methods with evolutionary algorithms. Genetic Algorithms demonstrate superior

performance in complex networks. Despite improved optimization, the model assumes static conditions and does not integrate real-time flood data or digital twin frameworks.

2.3. Research Gaps Identified

The review of recent literature reveals several important research gaps in the domain of flood evacuation planning, digital twin systems, and AI-based optimization. While substantial progress has been made in flood prediction, hydrodynamic modeling, and intelligent routing techniques, these developments remain fragmented across research domains. Many studies focus either on hazard simulation, routing optimization, or digital twin visualization independently, without tightly integrating them into a unified decision-support system. Additionally, computational complexity, limited algorithmic benchmarking, and lack of explainable AI mechanisms further restrict practical deployment. These gaps highlight the need for an integrated, simulation-driven, and adaptive flood evacuation framework.

2.3.1 Prediction–Action Disconnect

Several studies focus extensively on flood prediction, hydrodynamic modeling, and hazard mapping [3], [4], [13], [17], [18], but do not tightly integrate these outputs with evacuation routing algorithms. Although predictive accuracy and risk assessment methodologies have significantly improved, the transformation of flood simulation results into optimized and adaptive evacuation routes remains insufficiently explored. Most systems stop at hazard visualization rather than converting flood data into actionable routing decisions.

2.3.2 Limited Integration of Multi-Algorithm Routing in Digital Twins

Digital twin–based frameworks and conceptual flood management models [6], [9], [10], [14], [18] primarily emphasize monitoring, visualization, and resilience planning. However, they rarely incorporate systematic benchmarking of multiple routing strategies under consistent flood scenarios. Similarly, routing-focused works such as ACO-based rescue routing [16], metaheuristic comparisons [19], intelligent optimization approaches [20], deep reinforcement learning [1], and fuzzy AHP-based prioritization [12] generally adopt single or limited algorithmic approaches without embedding them within unified digital twin platforms.

2.3.3 Computational Realism and Scalability Gap:

High-fidelity hydrodynamic simulations and deep reinforcement learning models [1], [2], [5] require substantial computational resources and extensive training datasets, limiting their real-time applicability. Even metaheuristic-based methods such as ACO and GA

[16], [19], [20] often operate under static flood assumptions and predefined parameters, restricting adaptability. Lightweight, graph-based digital twins built on open datasets such as OpenStreetMap that can efficiently execute multiple routing algorithms in near real-time remain comparatively underrepresented.

2.3.4 Lack of Generative AI–Based Decision Explanation:

While machine learning and optimization techniques are widely applied for prediction and routing [1], [2], [7], [16], [19], existing systems rarely incorporate generative AI mechanisms to interpret routing outputs and generate structured, human-readable evacuation strategies. Emergency planners are often required to manually interpret hazard maps, optimization metrics, and route outputs without algorithm-aware explanation or strategic guidance.

2.3.5 Absence of Unified Congestion-Aware Digital Twin Architecture:

Although congestion risk modeling and network vulnerability analysis are addressed in works such as [15], and evacuation optimization is explored in [16], [19], and [20], these studies remain largely isolated. They do not unify dynamic congestion assessment, real-time flood modeling, and multi-algorithm route optimization within a cohesive digital twin architecture. The integration of hazard simulation, adaptive routing, congestion-aware optimization, and AI-assisted strategic guidance remains insufficiently developed.

Addressing the Research Gaps

The proposed project addresses these limitations by developing a lightweight, SWMM-integrated digital twin framework that dynamically connects flood simulation outputs with adaptive evacuation routing. Unlike prior works that rely on isolated prediction models or single-algorithm routing strategies, the system systematically evaluates multiple graph-based and metaheuristic algorithms within a unified simulation environment. It further incorporates generative AI–based decision support to interpret routing outputs and generate structured evacuation recommendations. By combining dynamic flood modeling, congestion-aware routing, multi-algorithm benchmarking, and explainable AI within a single architecture, the project advances toward a cohesive and practical flood evacuation decision-support system.

3. Software Requirements Specification

3.1 Scope

The Digital-Twin-Driven Flood Evacuation System using AI optimization is a web based application designed to provide a real-time, physics-based simulation of urban flooding and optimize evacuation strategies. By creating a digital twin of urban environments—incorporating road networks, elevation data, and rainfall history—the system will enable authorities and citizens to visualize flood propagation, assess road risk levels, and locate safe evacuation shelters dynamically. The project aims to improve disaster response efficiency and urban resilience through data-driven insights and AI-based optimization. The system will implement a GenAI-assisted evacuation planning module to generate dynamic strategies while deploying metaheuristic-based AI optimization to enhance route efficiency across diverse flood scenarios. An interactive visualization dashboard will be developed for monitoring of evacuation routes and system performance to ensure maximum disaster resilience.

3.2 Overall Description

3.2.1 Product Functions

- The system will provide the following primary functions:
- Digital Twin Initialization: Selection of administrative regions (Hobli level) and automatic generation of the corresponding urban road network and elevation digital twin.
- Flood Simulation: Execution of physics-based flood propagation using historic data or manual rainfall inputs.
- AI Evacuation Planning: Generation of optimal evacuation routes using GenAI-assisted strategies and metaheuristic optimization.
- Shelter Management: Dynamic identification and monitoring of safe evacuation centers based on real-time flood proximity.
- Historical Analysis: Comparison of current simulations with historical rainfall datasets for risk assessment.

- Interactive Dashboard: Real-time visualization of flood zones, road risk levels, and system performance metrics.

3.2.2 User Characteristics

The system will cater to two primary professional user roles:

- Disaster Response Authorities: Technical users responsible for emergency coordination, evacuation management, and high-level infrastructure risk assessment, high-level city planning, infrastructure risk assessment, and manual strategy overrides.
- Research Planners: Urban planners and researchers utilizing the system to analyze flood scenarios, assess climate impact, and design long-term urban resilience strategies.

3.2.3 Constraints

- Platform Dependency: The system will be a web-based application accessible via modern browsers on Windows and other major operating systems.
- Performance: Physics simulations and route optimizations must provide responsive updates to ensure real-time utility.
- Data Accuracy: Simulation results will be dependent on the resolution of available Digital Elevation Models (DEM) and OSM data.

3.3 Assumptions and Dependencies

- Historical Model Consistency: It is assumed that future flood propagation patterns will remain significantly consistent with established historical flood spread behavior for the targeted regions.
- Population Data Projection: Demographic data will be based on the 2011 Bengaluru Census, with an assumed 15% growth projection applied to approximate current population distribution.
- Technical Infrastructure: Users will require stable internet connectivity to access map tiling services and interact with the centralized FastAPI simulation backend.
- External APIs: Dependency on OpenStreetMap (OSM) for road network data and meteorological services for rainfall data.

- Frameworks: Built on FastAPI (Backend), React (Frontend), and MapLibre for high-performance geospatial rendering.

3.4 Specific Requirements

3.4.1 Functional Requirements

1. Region-Specific Digital Twin Initialization: The system shall allow users to select administrative regions (Hobli) and generate a corresponding digital twin using OSMnx and elevation data.
2. Physics-Based Flood Propagation: The system shall simulate flood spreading from drains and lake boundaries similar to a Storm Water Management Model based on rainfall intensity and digital elevation models (DEM).
3. GenAI Evacuation Planning: The system shall leverage Generative AI to generate natural language evacuation strategies and route recommendations based on current digital twin states.
4. AI Route Optimization: The system shall utilize metaheuristic-based AI optimization to calculate the most efficient evacuation paths during varying flood scenarios.
5. Dynamic Shelter Monitoring: The system shall dynamically identify safe evacuation shelters and update their status (safe/unsafe) dynamically as the flood simulation progresses, counting the occupancy of the shelters as the evacuation progresses.
6. Historical Data Integration: The system shall allow users to select historical rainfall dates to initialize simulation parameters and compare risk departures.

3.4.2 Non-Functional Requirements

1. Performance: The flood simulation engine shall process and transmit step-by-step updates via SSE within 500ms per step to ensure smooth visualization.
2. Scalability: The system shall support concurrent simulation requests by utilizing asynchronous processing in the FastAPI backend.
3. Security: Access to the simulation and optimization modules shall be restricted to authorized disaster management personnel via secure login.

4. Usability: The interactive dashboard shall provide a responsive, high-performance map interface with a clear, dynamic legend for easy risk interpretation.

3.4.3 External Interface Requirements

1. User Interface: A web-based dashboard built with React and MapLibre, featuring a sidebar for control inputs and real-time metric displays.
2. Hardware Interface: Minimum 8GB RAM and stable internet connectivity for map tile rendering.
3. Software Interface: Integration with OpenStreetMap (OSM) via OSMnx, elevation data APIs, and the Gemini API for GenAI strategy generation.
4. Communication Interfaces: HTTPS for RESTful API calls and Server-Sent Events (SSE) for real-time simulation streaming.
5. Software Interface: Integration with OpenStreetMap (OSM) via OSMnx, elevation data APIs, and the Gemini API for GenAI strategy generation.
6. Communication Interfaces: HTTPS for RESTful API calls and Server-Sent Events (SSE) for real-time simulation streaming.

4. System Design

4.1 Architectural Design




Fig 4.1 System Architecture Diagram

4.1.1 System Overview

Fig 4.1 shows how the Digital Twin–Driven Flood Evacuation System utilizes a scalable Microservices-inspired Layered Architecture. The system decouples the frontend visualization from the high-performance backend, allowing for asynchronous simulation streaming and modular AI integration. It is orchestrated by a central FastAPI controller

that routes data between the physics engine, the AI optimization service, and external geospatial providers.

4.1.2 Architectural Layers & Components

1. Client Layer (Presentation)

- Module: React Dashboard
 - Technology: React.js, Vite, MapLibre GL JS.
 - Function: Acts as the visual interface for the Digital Twin. It renders high-resolution vector maps, overlays real-time flood inundation zones, and acts as the control center for simulation parameters (rainfall intensity, algorithm selection).
 - Real-time Streaming: Consumes Server-Sent Events (SSE) to visualize flood propagation and evacuation routes frame-by-frame without page reloads.

2. Backend API Layer (Gateway)

- Module: FastAPI Server
 - Technology: Python 3.12, Uvicorn (ASGI).
 - Function: Serves as the secure entry point for the system. It handles authentication, validates simulation requests, and manages the lifecycle of long-running simulation tasks using asynchronous background workers.

3. Business Logic Services (The "Core")

This layer contains the computational engines that power the Digital Twin.

- A. Simulation Model
 - Flood Physics Simulator: A hydrological engine that models water spread based on terrain elevation (DEM) and rainfall inputs. It dynamically updates the "risk state" of the graph nodes during a simulation run.
 - Population Integrator: Maps demographic data (Census/Ward CSVs) to specific road intersections to estimate the precise number of people at risk.

- B. AI Optimization Engine
 - Agentic AI / Dispatcher: A robust control module that selects the most appropriate optimization strategy based on the disaster scale or user input.
 - Metaheuristic Algorithms: A pluggable suite of bio-inspired algorithms used to solve the routing problem:
 - Genetic Algorithm (GA): Evolves routes using mutation and crossover operators.
 - Ant Colony Optimization (ACO): Simulates "ants" depositing pheromones on safe paths to find efficient routes.
 - Particle Swarm Optimization (PSO): Uses a swarm of candidate solutions that "fly" through the search space toward the best known safe path.
 - Generative AI Layer (GenAI): An intelligent decision-support system featuring a resilient MultiFallback Model (Gemini 2.5 Flash as primary, and Ollama Llama 3.2 for localized offline execution). It includes an Expert Panel Pipeline that generates multi-persona analysis (e.g., Logistics Chief, Tactical Commander) to deterministically assess resource needs and identify inventory gaps based on official government guidelines.
 - The Model Context Protocol (MCP) Ecosystem: Represents the shift from a static dashboard to a true Agentic Digital Twin. It utilizes two specialized FastMCP servers:
 - Evacuation Server: Processes "Hard Data" from the physics engine (success rates, population paths, physical bottlenecks).
 - Intelligence Server: Processes "Soft Data" and socio-economic reasoning (IDRN database searching, Metro integrity, logistics).
 - The Sentinel: A shared state bridge (mcp_state.json) updated live every simulation frame to ensure the AI's reasoning is strictly bound to the exact, current truth of the digital twin.

- C. Network Model
 - OSMnx Graph Builder: Automatically fetches OpenStreetMap data and constructs a navigable graph topology (nodes and edges), calculating static properties like road length and type.
- D. Access Control
 - RBAC Module: Manages Role-Based Access Control to ensure only authorized personnel (e.g., Disaster Managers) can trigger resource-intensive simulations or modify critical parameters.

4. Data & External Layer (Persistence)

- External APIs:
 - OpenStreetMap (OSM): Provides the foundational road network geometry.
 - Traffic Flow API (TomTom): Supplies real-time traffic congestion data. The backend fetches this in parallel batches to update edge weights dynamically, ensuring routes avoid gridlock.
- Data Stores (MongoDB & File System):
 - Historical Rainfall CSVs: Stores past weather events for replay simulations.
 - BBMP Ward Data: Geospatial boundaries for administrative regions.
 - User Collection: Secure storage for user profiles and logs.
 - Graph Cache: Serialized .graphml files to speed up region loading.

4.1.3 System Interactions

1. Initialization: User selects a region; Backend builds the Network Model from OSM.
2. Input: User sets rainfall (mmmm) and selects an AI strategy (e.g., ACO).
3. Simulation: Flood Physics Simulator runs iteratively, flooding low-elevation graph nodes.

4. **Enrichment:** Traffic API injects real-time congestion data. Concurrently, the live physics state is persistently serialized into "The Sentinel" (`mcp_state.json`), bridging the simulation thread with the AI nervous system.
5. **Optimization:** The selected AI Algorithm analyzes the weighted graph (Distance + Flood + Traffic) to find optimal physical shelter paths.
6. **Agentic Execution Loop:** The AI Copilot detects user intent, enters a "Thinking Loop," and autonomously executes parallel tool calls across the dual FastMCP servers (Evacuation and Intelligence).
7. **Synthesis & Visualization:** The AI synthesizes the multi-tool data (e.g., merging physical bottleneck data with live Metro integrity) into a single tactical plan, streaming the resulting analytical dashboard to the React frontend.

4.2 Data Flow diagram

Fig 4.2 illustrates how data moves through the Digital Twin Flood Evacuation System and how different components interact during simulation and evacuation planning. It shows the flow of inputs such as rainfall parameters, geographic data, and population statistics from the user interface and databases into the flood simulation and digital twin processing modules. The processed data is then used by AI-based evacuation optimization algorithms to generate safe evacuation routes and shelter allocations. The results are finally visualized through the frontend dashboard, providing authorities with real-time flood insights and evacuation recommendations.




Fig 4.2 Data Flow Diagram

4.2.1 Data Flow Components

Flood Data Input (UrbanFloodSimulator)

- UrbanFloodSimulator receives rainfall, simulation steps, and decay factor from the dashboard. Water starts at drain and lake nodes and diffuses through the road graph, updating water_depth on nodes each step.
- Purpose:
Generate a node-level flood depth map that drives shelter safety classification and evacuation route costs.

Road Network Data (region_manager + OSMnx)

- When a Hobli is selected, region_manager loads the road graph using OSMnx. Nodes store coordinates, elevation, and water depth; edges store road length, type, speed, and traffic attributes.
- Purpose:

Provide a real-world road network that forms the base Digital Twin for flood simulation and evacuation routing.

Graph & Flood Processing (Digital Twin Construction)

- Flood depth, traffic conditions, and population data are integrated into the road graph. Flood weights adjust edge costs, traffic penalties modify travel time, and population values map people to nodes.
- Purpose:
Create a continuously updated Digital Twin where roads encode flood risk, congestion, and population exposure.

Safe Shelter Processing (shelter_generator)

- Shelter locations are retrieved from OpenStreetMap and snapped to nearby road nodes. Flooded shelters are filtered out, and capacities are estimated based on facility type.
- Purpose:
Identify safe and reachable shelters dynamically based on the current flood conditions.

Evacuation Pathfinding (AI Optimisation)

- Nodes with water depth above the risk threshold are identified. Genetic Algorithm, Ant Colony Optimization, or Particle Swarm Optimization assign populations to shelters using flood-weighted and traffic-aware routing.
- Purpose:
Compute optimized evacuation routes while respecting shelter capacity and real-time road conditions.

Visualization & Real-Time Reporting (React + SSE)

- The frontend receives simulation frames via Server-Sent Events. Maps show flood areas, affected roads, shelters, and evacuation routes, while dashboards display evacuation metrics and algorithm performance.
- Purpose:
Provide authorities with a real-time interactive dashboard for monitoring flood progression and evacuation strategies.

User Interaction & Authentication

- Users will log in through a JWT-based authentication system. Role-based permissions will restrict actions, allowing researchers to adjust parameters while authorities access operational dashboards and alerts.
- Purpose:
Ensure secure access control and proper usage of simulation and evacuation planning tools.

Generative AI Component

- Intelligence & Orchestration: The GenAI module acts as an autonomous Agentic Pipeline, transcending traditional static analytics. It utilizes a dual FastMCP Architecture—splitting physical simulation workloads (the Evacuation Server for "Hard Data") from socio-economic and logistics logic (the Intelligence Server for "Soft Data"). Employing Cross-Tool Multi-Reasoning, the AI proactively chains queries across these servers to evaluate flood spread, public transit integrity, and IDRN shelter resources. All AI actions are grounded by the "Sentinel" state bridge (`mcp_state.json`), ensuring the reasoning strictly maps to the live digital twin frame. This is fortified by a deterministic Expert Panel to verify government guidelines, and a resilient Multi-Tier Fallback Sampling Strategy (Gemini, Ollama) for 100% continuous execution.
- Purpose: To function as an autonomous thinking agent that securely synthesizes raw physics calculations and complex socio-economic layers into clear natural-language summaries, real-time command intelligence, precise NDRF deployment routing, and actionable, multi-variable tactical evacuation strategies.

4.2.2 Database Design

The system uses MongoDB Atlas to store structured datasets required for simulation, geographic initialization, population distribution, and user authentication. The schema is designed to support efficient data retrieval during flood simulations and evacuation planning.

Users Collection

This collection stores system user credentials and role information for authentication and access control.

Key Fields

- `_id` – Unique user identifier
- `email` – User login email
- `password_hash` – Encrypted password
- `role` – User role (researcher or disaster authority)
- `permissions` – Allowed system operations
- `created_at` – Account creation timestamp

Purpose:

Supports role-based access control for simulation execution and report access.

Hobli Coordinates Collection

Stores geographic reference data for Hobli regions used during simulation initialization.

Key Fields

- `_id` – Unique record identifier
- `hobli_name` – Name of the Hobli region
- `latitude, longitude` – Central coordinates
- `district` – Administrative district
- `hobli_type` – Urban or rural classification
- `bbox` – Bounding box used for OSM data retrieval

Purpose:

Provides geographic boundaries used to download road networks and initialize the simulation region.

Rainfall Data Collection

Contains historical rainfall measurements linked to Hobli regions.

Key Fields

- `_id` – Record identifier

- station_name – Rainfall monitoring station
- hobli_ref – Reference to Hobli region
- date – Measurement date
- rainfall_mm – Rainfall amount in millimeters
- duration_hrs – Measurement duration

Purpose:

Supplies rainfall parameters used to seed flood simulations.

Population Collection

Stores ward-level population statistics used for evacuation modelling.

Key Fields

- _id – Record identifier
- ward_num – Ward number
- ward_name – Ward name
- hobli_ref – Associated Hobli region
- population – Total population
- male, female – Gender distribution
- sc_population, st_population – Demographic groups

Purpose:

Provides demographic data used to distribute people across the road network nodes during simulation.

Metro Infrastructure Collection

Stores the spatial and operational data for the regional metro network.

Key Fields

- _id – Record identifier
- station_name – Name of the metro station
- line_color – Network line association (e.g., Purple, Green)

- latitude, longitude – Station coordinates
- capacity – Maximum crowd holding limit
- status – Operational status (e.g., Active, Flooded, Offline)

Purpose:

Provides mass-transit nodes used by the routing algorithms and AI transport agents to plan large-scale urban evacuations and designate fortified safe zones.

Buses & Depots Collection

Manages the fleet inventory and real-time status of city buses available for emergency deployment.

Key Fields

- `_id` – Record identifier
- `depot_name` – Base depot of the vehicle
- `bus_id` – Unique vehicle identifier
- `capacity` – Passenger seating/standing capacity
- `current_location` – Live geographic coordinates
- `availability_status` – On standby, deployed, or out of service

Purpose:

Supplies live vehicular assets to the GenAI Transport Agent, allowing the system to compute precise evacuation manifests and dispatch buses dynamically to high-risk zones.

Disaster Resources Collection

Acts as the central inventory for critical disaster relief supplies mapped to specific shelters or staging areas.

Key Fields

- `_id` – Record identifier
- `shelter_ref` – Associated shelter or storage node

- resource_category – Category (e.g., Medical, Food & Water, SAR Equipment)
- item_name – Specific item name (e.g., Life Jackets, First Aid Kits)
- quantity_available – Current stock count
- last_updated – Timestamp of the most recent inventory check

Purpose:

Feeds directly into the GenAI Expert Panel pipeline, allowing personas like the Logistics Chief to deterministically calculate resource gaps against official disaster response guidelines (SDRF/NDRF) and automatically flag severe shortages.

4.3 User Interface (UI) Design

The UI model is designed as a centralized, role-based dashboard. The interface serves two primary user roles: Disaster Response Authorities and Research Planners.

1. Configuration and Initialization phase:

- The Research Planner begins by interacting with a configuration pane to Initialize the Digital Twin. They select a target region (e.g., a specific Hobli in Bengaluru) via dropdowns or a map-selection tool. This action triggers the system to fetch and render open-source map data (OSM networks, elevation, shelter points) onto the main map canvas.
- The user visually confirms the digital twin setup on an interactive map before proceeding.

2. Simulation Execution phase:

- The Disaster Response Authority interacts with the Run Flood Simulation module using input fields or sliders to define parameters such as rainfall intensity or historical weather data inputs.
- Users trigger the simulation and interact with playback controls (Start, Pause, Reset) to observe the physics-based flood propagation dynamically overlaid on the map terrain.

3. Monitoring and Analysis phase:

- While the simulation runs, both users utilize the Monitor Dashboard. They interact by toggling different visualization layers (e.g., traffic congestion, water depth heatmaps) and viewing real-time metric cards (safe/unsafe populations, shelter capacities).
- Users also track the live availability of city buses, operational metro stations, and tactical supplies.
- Users Review Simulation Results via interactive charts detailing "Analytical Reports" and "Visual Simulations," allowing them to pause and inspect specific bottlenecks on the map.
- The backend continuously synchronizes this live situational data into the Model Context Protocol (MCP) state bridge for external AI access.

4. AI Optimization and Planning phase:

- The Research Planner initiates the Generate Evacuation Plan by adjusting metaheuristic parameters (like mutation rates for the Genetic Algorithm) to find the safest physical routes in the physics engine.
- Simultaneously, the GenAI Planning Pipeline is engaged. Utilizing the prompt interface, an autonomous AI Copilot queries the dual MCP servers (Evacuation and Intelligence).
- Cross-Tool Multi-Reasoning: The AI autonomously chains queries. For example, it might execute `get_metro_status`, notice disrupted transit lines, and immediately execute `get_shelter_resource_map` to identify alternative safe hubs equipped with inflatable boats or medical supplies from the IDR database.
- The AI conducts a deterministic gap analysis, comparing these live shelter inventories and transport networks against official government disaster guidelines to flag critical vulnerabilities.
- The Disaster Response Authority evaluates these synthesized, multi-tool AI insights alongside the visual route variations on the map.
- The user interaction concludes when they click to Confirm Route Optimization, prompting the system to generate tangible outputs—specifically, downloading GenAI-synthesized "Detailed Evacuation Instructions," prioritized NDRF rescue deployments for identified bottlenecks, and finalized analytical reports.

4.3.1 Component Design

The User Interface is built on a modular architecture, breaking down the complex Digital Twin and simulation functionalities into manageable, reusable components. This ensures maintainability and allows for seamless integration with backend services.

Front-End Components

The front end is divided into the following key components:

1. Map Visualization Component (MapView)

- **Functionality:** The core visual engine representing the Digital Twin environment. It renders the OSM road networks, elevation data, shelter locations, and real-time flood propagation overlays using libraries like Leaflet or Mapbox GL JS.
- **Input:** GeoJSON data (roads, shelters, boundaries), dynamic flood depth arrays, and polyline coordinates for evacuation routes.
- **Output:** Interactive, multi-layered map with zoom, pan, and layer-toggling capabilities.

2. Simulation Control Panel (SimulationControls)

- **Functionality:** Allows the Research Planner and Authorities to configure and control the "Run Flood Simulation" step.
- **Input:** User interactions (button clicks, slider adjustments for rainfall intensity, dropdown selections for historical data).
- **Output:** Triggers state changes and dispatches API calls to the backend simulation engine (e.g., Start, Pause, Reset).

3. Real-Time Dashboard (MetricsDashboard)

- **Functionality:** Implements the "Monitor Real-time Metrics" feature. It displays charts and KPIs tracking simulation progress, total at-risk population, safe vs. unsafe shelters, and road blockages.
- **Input:** Live data streams (via WebSockets or polling) containing simulation step updates and agent status.
- **Output:** Dynamic visualizations (e.g., Recharts/Chart.js graphs for shelter capacity over time, KPI cards for total evacuated).

4. Evacuation & Route Optimizer Module (EvacuationManager)

- **Functionality:** Interfaces with the "Generate Evacuation Plan" and "Optimize Evacuation Routes" steps. It provides the UI to approve, revise, or adjust AI-generated routes.
- **Input:** AI optimization results (from Ant Colony/Genetic Algorithms) including estimated travel times, path arrays, and bottleneck warnings.
- **Output:** Renders the suggested routes on the MapView (e.g., using colored polylines) and displays a side-panel list of step-by-step detailed evacuation instructions.

5. GenAI Co-Pilot Component

- **Functionality:** A robust natural-language interface functioning as an Autonomous Agentic Pipeline rather than a static dashboard. It allows authorities to type command prompts like "Generate an adaptive strategy for heavy rainfall near Shelter A" or ask complex, multi-variable questions (e.g., "The Purple Line is 50% disrupted. Find safe bus evacuation routes to the nearest Super-Hub.").
- **The Intelligence Architecture:** Powered by two specialized FastMCP servers:
 - **Evacuation Server (mcp_evacuation_server.py):** Handles the "Hard Data" from the physics engine (success rates, population paths, road bottlenecks).
 - **Intelligence Server (mcp_flood_intelligence_server.py):** Handles the "Soft Data" and socio-economic reasoning (IDRN database searching, Metro system integrity).
- **Agentic Execution Loop:** The AI acts autonomously. Through its "Intent Stage" and "Thinking Loop," it dynamically selects and executes multiple tools in parallel (Tool Chaining) across both servers to synthesize a cohesive disaster management plan. All tools read from a synchronized "Sentinel" state bridge (mcp_state.json) updated live from the physics engine, ensuring the AI strictly reasons based on the exact current frame of the simulation.
- **Input/Output:** Natural language prompts trigger the chat interface to display the AI's real-time reasoning iterations (tool calls), summarized analytical reports, public transit disruption alerts, and direct tactical recommendations.

Back-End Components

The front-end components are designed to remain lightweight, delegating heavy computations (physics-based flooding, metaheuristic optimization) to the back end.

- **RESTful APIs:** Components like the SimulationControls use standard HTTP requests (POST /api/simulation/start, GET /api/digital-twin/init) to send configuration parameters and fetch initial state data (OSM networks, shelters).
- **Real-time Communication (WebSockets/SSE):** Given the iterative nature of the simulation (monitoring real-time metrics), the MetricsDashboard and MapView establish WebSocket connections to receive continuous, low-latency updates on flood propagation and agent movement without overwhelming the server with HTTP polling.
- **State Management:** The React application utilizes global state management (e.g., Redux Toolkit or React Context) to ensure that when the back end sends updated route blockages, both the MapView and MetricsDashboard update simultaneously without redundant data fetching.

4.4 Class diagram and classes




Fig. 4.3 Class diagram

The Fig. 4.3 represents the structural design of the Digital Twin-Driven Flood Evacuation System and shows the relationships between components responsible for flood simulation, mathematical evacuation planning, agentic artificial intelligence, and visualization. The architecture follows a layered design consisting of a React-based presentation layer, a FastAPI application layer for handling API communication, and a core processing layer. The core processing layer is bifurcated into two domains: the physical constraints environment (driven by the flood simulator and AI optimization algorithms like GA, ACO, and PSO) and the Resilient Agentic Pipeline (driven by the

GenAI Copilot and FastMCP infrastructure). These two domains synchronize dynamically through a central Sentinel state bridge.

4.4.1 ReactDashboard

The ReactDashboard class represents the frontend visualization interface used for interacting with the flood evacuation system. It provides map-based visualization and receives real-time updates from the backend server.

- Attributes:
 - mapLibreLayer – Represents the map rendering layer used to visualize geographic information.
 - geoJsonFeatures – Stores GeoJSON objects representing roads, shelters, and flood zones.
 - SSE_Endpoint – Endpoint used for Server-Sent Events to receive live simulation updates.
- Methods:
 - renderRiskMap() – Displays road risk levels and flood intensity on the map.
 - renderShelters() – Visualizes evacuation shelters and their locations.
 - updateLiveFloodPolygons() – Dynamically updates flood spread areas during the simulation process.

The ReactDashboard enables real-time monitoring of flood conditions and evacuation planning results.

4.4.2 FastAPIServer

The FastAPIServer class acts as the central backend controller responsible for managing system operations and coordinating interactions between the simulation, optimization, and AI intelligence modules.

- Attributes:
 - API_Host – Defines the host address of the backend server.
 - API_Port – Defines the port number used by the API server.
- Methods:
 - authenticateUser() – Performs authentication and authorization for system access.
 - loadRegion(hobliName) – Loads the digital twin model for the selected geographic region.
 - simulateFloodStream(rainfall_mm) – Executes flood simulation and streams updates to the frontend.

invokeAIOptimizer(algo_type) – Initiates the mathematical evacuation routing using a selected algorithm.

invokeAgenticCopilot() – Triggers the LLM-driven intelligence subsystem for strategic oversight.

This class manages the overall workflow of the system by coordinating hard data workflows and soft data reasoning loops.

4.4.3 UrbanFloodSimulator

The UrbanFloodSimulator class is responsible for modeling flood propagation within the digital twin environment. It simulates the spread of water across the road network graph based on rainfall and terrain conditions.

- Attributes:
 - networkGraph – A graph structure representing the road network of the selected region.
 - drainNodes – Nodes corresponding to drainage points where flooding may originate.
 - lakeNodes – Nodes representing lakes or water bodies connected to the drainage network.
 - currentWaterDepth – Represents the current simulated water depth within the network.
- Methods:
 - propagateFloodStep(decay_factor) – Simulates water propagation across the network graph.
 - identifyAtRiskPopulation() – Determines the population nodes affected by flooding.
 - calculateFloodImpactPolygons() – Generates geospatial flood impact zones for visualization.
 - updateSentinelState() – Exports current hazard boundaries and constraints out to the Sentinel bridge.

This class provides the flood simulation engine that continuously updates the digital twin model.

4.4.4 DataLoaders

The DataLoaders class manages the retrieval and preprocessing of external datasets required for simulation and evacuation planning.

- Attributes:
 - cachingDirectory – Directory used for storing cached datasets for faster access.

- **Methods:**
 - `loadHobliDemographics()` – Loads demographic information for the selected region.
 - `fetchOSMnxRoads()` – Retrieves road network data from OpenStreetMap using OSMnx.
 - `fetchTomTomTrafficFlow()` – Obtains traffic congestion data from external APIs.
 - `querySafeShelters()` – Identifies evacuation shelters and their locations within the region.

This class ensures that the digital twin environment is constructed using real-world geographic and demographic data.

4.4.5 BaseEvacuationPlanner

The `BaseEvacuationPlanner` class serves as the parent class for all evacuation optimization algorithms. It provides common functionality required for route computation and fitness evaluation.

- **Attributes:**
 - `WALKING_SPEED` – Average movement speed of evacuees.
 - `FLOOD_PENALTY` – Penalty applied to flooded road segments during routing.
 - `CAPACITY_PENALTY` – Penalty applied when shelter capacity limits are exceeded.
 - `atRiskNodes` – Nodes representing populations requiring evacuation.
 - `safeShelters` – List of identified safe shelters.
 - `distMatrix` – Matrix representing distances between nodes.
 - `timeMatrix` – Matrix representing travel times between nodes.
- **Methods:**
 - `computeDijkstraPaths()` – Computes shortest paths between nodes using Dijkstra's algorithm.
 - `fitness()` – Evaluates the quality of a routing solution based on evacuation efficiency.
 - `run()` – Executes the evacuation optimization process.

This class provides shared routing functionality used by all AI-based evacuation planners.

4.4.6 GeneticEvacuationPlanner

The `GeneticEvacuationPlanner` class implements evacuation optimization using the Genetic Algorithm. This algorithm searches for optimal solutions through evolutionary operations such as selection, crossover, and mutation.

- Attributes:
 - populationSize – Number of candidate solutions in the population.
 - maxGenerations – Maximum number of evolutionary iterations.
- Methods:
 - crossover() – Combines parent solutions to generate new offspring solutions.
 - mutate() – Introduces random modifications to maintain solution diversity.
 - run() – Executes the genetic algorithm optimization process.

This approach explores multiple evacuation strategies to identify efficient routing solutions.

4.4.7 ACOEvacuationPlanner

The ACOEvacuationPlanner class implements evacuation route optimization using the Ant Colony Optimization algorithm. This method models the behavior of ants exploring paths and depositing pheromones to reinforce successful routes.

- Attributes:
 - numberOfAnts – Number of agents exploring potential routes.
 - alpha – Parameter controlling the influence of pheromone trails.
 - beta – Parameter controlling the influence of heuristic distance.
- Methods:
 - updatePheromones() – Updates pheromone levels on edges based on route quality.
 - run() – Executes the ant colony optimization process.

This algorithm is effective for discovering efficient evacuation routes through collective exploration.

4.4.8 PSOEvacuationPlanner

The PSOEvacuationPlanner class implements evacuation optimization using the Particle Swarm Optimization algorithm. The algorithm simulates the movement of particles in a solution space to iteratively improve evacuation strategies.

- Attributes:
 - numberOfParticles – Number of particles in the swarm.
 - inertia – Controls the influence of previous particle velocities.
 - cognitiveBase – Controls the influence of personal best solutions.
- Methods:
 - updateParticleVelocities() – Updates particle movement in the search space.
 - run() – Executes the particle swarm optimization algorithm.

This algorithm refines evacuation route assignments by iteratively improving candidate solutions based on swarm intelligence.

4.4.9 GenAICopilot

The GenAICopilot class manages the Resilient Agentic Pipeline. It operates completely autonomously by maintaining a three-tier model fallback system and running Intent-Thinking-Execution loops to derive contextual disaster strategies.

- **Attributes:**
 - llmFallbackTiers – List corresponding to Gemini 2.5 Flash, Groq Llama 3.3, and local Ollama.
 - activePersona – Contextual state dictating behavior (e.g., Tactical Commander, Logistics Chief).
- **Methods:**
 - evaluateSituation() – Formulates the overall intent loop based on the simulation state.
 - triggerExpertPanel() – Invokes concurrent AI perspectives to synthesize a master plan.
 - generateAgenticStrategy() – Computes high-level strategic directives complementing the standard routing engines.

This class drives the autonomous decision-making process by synthesizing multiple AI perspectives into actionable disaster response strategies.

4.4.10 FastMCPServer

The FastMCPServer acts as the secure interface between the codebase's underlying functions and the LLM via the Model Context Protocol. It bridges the semantic gap, allowing the GenAI Copilot to execute codebase functions directly.

- **Attributes:**
 - serverName – Identifier (e.g., "EvacuationServer" or "IntelligenceServer").
 - registeredTools – Available programmatic capabilities exposed to the LLM context.
 - availableResources – External datasets (like transit constraints) prepared as read-only formats.
- **Methods:**
 - exposeHardData() – Provides access strictly to physics engine endpoints.
 - checkBusAvailability() – An exposed tool enabling the LLM to query logistics arrays.
 - getShelterStatus() – An exposed tool enabling capacity checks by the AI agent.

This class ensures seamless integration by allowing natural language models to securely trigger programmatic workflows and query real-time hard data.

4.4.11 SentinelBridge

The SentinelBridge acts as the crucial guardian between the simulation physics engine and the AI models, ensuring the LLM cannot hallucinate physical constraints. It continuously records the mathematical truth of the simulation.

- **Attributes:**
 - stateFilePath – Path to the persistent mcp_state.json file.
 - latestSimulationFrame – Snapshot dictionary containing the current frame's environmental realities.
- **Methods:**
 - syncPhysicsEngine() – Accepts updates from the UrbanFloodSimulator.
 - readStateForAI() – Safely streams "Hard Data" to the FastMCPServer for LLM consumption.

This class guarantees system integrity by maintaining a synchronized, hallucination-free source of truth bridging the simulation and the intelligence layers.

4.5 Sequence diagram




Fig. 4.5 Sequence diagram

The Fig. 4.5 illustrates the dynamic interaction between system components during the execution of the Digital Twin–Driven Flood Evacuation System. It describes the flow of operations from user input to flood simulation and evacuation route optimization. The diagram is divided into three main phases: digital twin initialization, flood physics simulation, and AI-based evacuation optimization.

In the first phase, the researcher or planner selects a region from the React dashboard. The request is sent to the FastAPI server, which triggers the flood simulator to initialize the digital twin model. The system checks the local cache for existing map data; if unavailable, it retrieves road network information from external APIs such as OpenStreetMap. The retrieved data is then stored in the local cache and used to generate the base map for visualization.

In the second phase, the user adjusts simulation parameters such as rainfall intensity. The dashboard sends the request to the FastAPI server, which invokes the flood simulator to execute the flood propagation process. The simulator loads demographic and geographic data, calculates water spread and decay across the network graph, and identifies flooded nodes. Simulation results are streamed to the frontend using Server-Sent Events, allowing the dashboard to continuously update flood zones, road risks, and shelter safety.

In the final phase, the user requests evacuation route generation. The FastAPI server initiates the AI optimization module, which retrieves traffic data and flood depth penalties from external sources. The system then executes the selected metaheuristic optimization algorithm, such as Genetic Algorithm, Ant Colony Optimization, or Particle Swarm Optimization, to compute optimal evacuation paths and shelter assignments. The optimized routes are returned to the dashboard and visualized on the map, enabling authorities to analyze evacuation strategies under the simulated flood conditions.

This sequence of interactions demonstrates how the system integrates digital twin modeling, real-time flood simulation, and AI-based route optimization to support dynamic flood evacuation planning.

4.6 Security & Performance Considerations

The Digital Twin–Driven Flood Evacuation System is designed for use by disaster management authorities, planning teams, and control room operators. Since the system handles real-time routing, infrastructure data, and emergency decisions, both security and performance are critical to ensure safe, stable, and uninterrupted operation during crisis scenarios.

4.6.1 Security Considerations

Role-Based Authentication and Access Control

The system implements secure authentication for authorized stakeholders such as disaster response authorities and administrative operators.

Role-Based Access Control (RBAC) ensures:

- Only authorized users can modify evacuation routes or simulation parameters
- Analytical dashboards are restricted to verified personnel
- Public-facing users have limited, read-only access

This prevents unauthorized manipulation of critical evacuation data.

Secure Communication and API Protection

All frontend–backend communication is secured using HTTPS to ensure encrypted data transmission.

External API integrations (such as traffic data providers) are protected by:

- Secure storage of API keys using environment variables
- Backend-only API calls (keys are never exposed in the frontend)

This ensures confidentiality and prevents credential leakage.

Rate Limiting and Abuse Prevention

To maintain system stability during high-demand events:

- Critical endpoints are rate-limited
- Traffic API responses are cached to reduce repeated calls
- Load balancing prevents backend overload

This protects the system from misuse or excessive request spikes during emergencies.

4.6.2 Performance Considerations

Real-Time Map Rendering Optimization

The frontend uses efficient vector-based rendering for interactive flood and evacuation maps.

Performance is improved through:

- Layer-based rendering control
- Controlled re-renders in React
- Efficient handling of geospatial data

This ensures smooth interaction even with large geographic datasets.

Caching for Low Latency

To minimize recomputation and API delays, the system uses:

- In-memory caching for frequently accessed road graphs
- Distributed caching for shared data across backend instances
- Time-based caching for traffic flow data

This significantly reduces response time and improves scalability.

Efficient Real-Time Updates

Server-Sent Events (SSE) are used for streaming live flood and route updates.

Compared to continuous polling, SSE:

- Reduces network overhead
- Improves real-time responsiveness
- Minimizes server resource consumption

This is essential for control room monitoring during flood events.

4.7 Technology Stack Selection

Component	Technology Stack Selected	Reasoning
Frontend Layer	React 19, Vite, MapLibre GL / react-map-gl, Tailwind CSS 4, Axios, Lucide React	React 19 with Vite for fast rendering of dynamic flood simulations. MapLibre GL open-source geospatial visualization for the digital twin model. Tailwind and Axios support rapid UI development and efficient backend communication.
Backend Layer	FastAPI + Uvicorn (ASGI, SSE streaming), Python Scientific Stack, MongoDB	FastAPI with ASGI enables high-performance asynchronous APIs for real-time route recalculation. Python libraries like NetworkX and GeoPandas support graph modeling and flood simulation. MongoDB provides flexible storage for dynamic evacuation and analytics data.
AI Optimization Layer	Genetic Algorithm (GA), Ant Colony Optimization (ACO), Particle Swarm Optimization (PSO), GoogleGenerative AI.	GA enables multi-objective optimization for evacuation time and congestion. ACO and PSO support adaptive and fast-converging route optimization in dynamic flood scenarios. Generative AI models provide intelligent scenario reasoning and generative decision support.
External APIs	TomTom Traffic Flow API (parallel fetch), OSMnx	TomTom Traffic API provides real-time traffic data for dynamic edge weight adjustment. OSMnx extracts structured road network data from OpenStreetMap to construct the digital twin graph. Parallel fetching ensures low-latency traffic integration.

4.8 Scalability & Reliability Planning

As a Digital Twin–Driven Flood Evacuation System intended for real-world disaster scenarios, the platform must handle high traffic loads, sudden spikes in usage, and unpredictable failures. During flood emergencies, thousands of users (authorities, researchers) may access the system simultaneously, requiring stable performance and continuous availability. This section outlines how the system is architected to scale efficiently and maintain operational reliability under stress. The planning is divided into two major themes: Scalability and Reliability.

4.8.1 Scalability Planning

Scalability ensures that the system can handle increasing numbers of users, real-time updates, and AI optimization workloads without performance degradation.

1. Stateless Backend Architecture

The backend is designed to be stateless, meaning no session data is stored in server memory. Each request carries its required context. This enables easy horizontal scaling (adding more backend instances), better compatibility with load balancers, reduced risk of session-based failure propagation

2. Load Balancing Strategy

In order to ensure that a single feature does not add stress on the server the static frontend files are CDN-cached, map tiles are edge-served, backend load is reduced during spikes. This improves response time and global accessibility.

3. Two-Tier Caching Strategy

To avoid repeated heavy computations, a two-layer cache is implemented:

- In-process cache stores frequently accessed OSMnx graphs temporarily.
- Shelter Candidates Disk Cache to ensure that the OSMnx features do not have to be fetched newly for every hobli, decreasing the load time.

This significantly reduces recomputation overhead.

4.8.2 Reliability Planning

Reliability ensures the system continues operating even when certain components fail. Since this system supports disaster response, fault tolerance is critical.

1. Graceful Degradation Strategy: If external services fail, the system falls back to reduced functionality -
 - TomTom failure → free-flow traffic assumption
 - Overpass failure → cached OSM graph usage
 - MongoDB outage → read-only operational mode
 - SSE drop → replay recent updates from buffer

This ensures essential evacuation routing remains accessible.

2. Circuit Breaker Pattern: To prevent cascading failures repeated failing API calls are temporarily halted, fallback mechanisms are activated, retry attempts occur after cooldown. This protects the system from overload due to unstable external services.
3. Logging and Monitoring: System monitoring that includes structured logging that enables fast issue detection and debugging.

4.9 Conclusion

The System Design document presents the architectural and structural blueprint of the Digital Twin–Driven Flood Evacuation System. It outlines how the system components are organized and interact to support flood simulation, evacuation planning, and real-time visualization. The document describes the overall architecture, including the client-server structure, system modules, and interactions between the frontend dashboard, backend services, and external data sources.

The design also details the data flow within the system, the structure of the database, and the movement of information between different modules. The user interface design focuses on providing an interactive and intuitive dashboard that enables planners and authorities to monitor flood conditions and evacuation routes effectively. Component-level design further breaks the system into reusable frontend and backend modules, clearly defining their inputs, outputs, and responsibilities.

UML diagrams such as the class diagram and sequence diagram were used to illustrate both the structural relationships between system components and the dynamic flow of operations during simulation and route optimization. Additionally, the design incorporates important considerations for security, performance, scalability, and reliability to ensure that the system operates efficiently and securely.

Overall, the proposed system design provides a modular, scalable, and extensible framework for implementing a digital twin–based flood evacuation system. It supports adaptive decision-making through simulation and AI-based optimization, enabling improved disaster preparedness and evacuation planning.

5. Implementation

5.1 Overview of the Implementation Process

The implementation of the Digital-Twin-Driven Flood Evacuation System was carried out through a structured, modular approach designed to bridge the gap between static geospatial data and dynamic, real-time emergency simulation. The process began with the conceptualization of a "Digital Twin" of the target urban area (specifically Bengaluru), which involved the extraction and processing of high-resolution road networks from OpenStreetMap (OSM) and elevation data from GIS terrain models. Following the data foundation, we developed a robust backend using FastAPI to handle heavy computational tasks, such as hydrodynamic flood modeling and AI-driven pathfinding optimizations (GA, PSO, and ACO). The frontend was implemented using React and MapLibre GL to provide an immersive, high-performance 3D visualization of flood progression and evacuation dynamics. The final phase focused on integrating these components into a seamless pipeline where real-time weather triggers or manual inputs could initiate complex simulations, providing data-backed insights for rescue operations.

5.2 Development Tools and Technologies

The development of the UrbanFloodReact platform utilized a modern, full-stack ecosystem designed to handle high-concurrency requests and perform intensive geospatial computations. Below is a detailed breakdown of the tools and technologies employed:

Core Programming Environment

- Python (3.10+): Chosen as the primary language for the backend due to its extensive library support for data science, GIS, and AI optimization.
- JavaScript (ES6+): Used for the frontend to enable reactive and dynamic user interfaces with high-performance asynchronous operations via Axios.

Backend Infrastructure(FastAPI & Python Ecosystem)

- FastAPI: A high-performance web framework used for building the system's asynchronous RESTful APIs. It provides automated Swagger documentation and handles complex concurrent simulation states efficiently.
- Uvicorn: An ASGI (Asynchronous Server Gateway Interface) server that powers the FastAPI application, ensuring low-latency communication with the frontend.
- Pydantic: Used for strict data validation and serialization of incoming requests (e.g., simulation parameters) and backend responses (e.g., evacuation path coordinates).

Geospatial & Simulation Tools

- OSMnx & NetworkX: Crucial for retrieving, modeling, and analyzing the street networks of Bengaluru. NetworkX is specifically used to represent road systems as graphs for pathfinding algorithms.
- GeoPandas & Shapely: These libraries were used to manipulate geospatial vector data, performing operations like spatial joins to determine which road segments fall within flooded "pressure points."
- Rasterio: Employed to read and process Digital Elevation Models (DEM), allowing the flood simulator to understand the topography and topographical constraints of the terrain.
- Pyproj & Fiona: Used for coordinate system transformations and reading complex GIS file formats.

Data Management & Persistence

- MongoDB: A NoSQL database chosen for its flexibility in handling semi-structured geospatial and socio-economic data.
- PyMongo & dnspython: Used for seamless interaction between the Python backend and the MongoDB Atlas cloud cluster.
- Pandas & NumPy: For efficient data manipulation, demographic calculations, and processing large-scale simulation matrices.

AI & Optimization Engines

- Optimization Algorithms: Custom-built implementations of Genetic Algorithms (GA), Particle Swarm Optimization (PSO), and Ant Colony Optimization (ACO) for determining non-linear evacuation paths.
- Google Gemini (Google Generative AI) & Groq: Integrated as LLM providers for the "Research Planner AI," offering context-aware post-simulation analysis and real-time situational reporting.

Frontend Technology Stack

- React (v19): The foundational UI library used to build a component-based, modular interface.
- MapLibre GL & React Map GL: These high-performance mapping libraries provide the 3D geospatial visualization layer, enabling the smooth rendering of thousands of dynamic "agents" and flood intensity heatmaps.
- Vite: The build tool and development server, replacing standard Webpack for significantly faster hot-module replacement and optimized production builds.

- Tailwind CSS (v4): Utilized for rapid UI development, providing a premium, modern aesthetic with a utility-first utility class approach.
- Recharts: Integrated for visualizing complex metrics through dynamic charts, such as algorithm fitness comparisons and shelter occupancy rates.
- Lucide React: For a clean, consistent set of icons across the navigation and control panels.

Development & Version Control

- VS Code: The primary Integrated Development Environment (IDE), augmented with Python and React extensions for debugging.
- Git & GitHub: Used for version control, collaborative development, and maintaining an audit trail of major implementation milestones.

5.3 Implementation Process

The implementation of the Digital-Twin-Driven Flood Evacuation System was carried out in a systematic sequence of technical steps, from environment configuration to the orchestration of complex inter-system communication. Below is the detailed implementation process:

5.3.1 Development Environment Setup and Data Bootstrapping

- The first step was initializing a consistent development environment for the Python backend and React frontend.
- Database Connectivity: A MongoDB Atlas cluster was provisioned, and a connection string was configured in the backend's .env file. Data was bootstrapped using `coord_loader.py` and `shelter_generator.py` to populate the database with real-world hobli coordinates and shelter locations across Bengaluru, categorized by urban/rural districts.
- Vite React Bootstrapping: The frontend was scaffolded using Vite, ensuring a modern build pipeline and lightning-fast HMR (Hot Module Replacement) for rapid UI iteration.

5.3.2 Digital Twin & GIS Data Processing

The core "intelligence" of the system relies on a digital twin of the urban infrastructure.

- Graph-based Road Modeling: Using OSMnx, we transformed the road networks of Bengaluru into a mathematical graph (nodes and edges). This allowed us to apply standard graph algorithms (Dijkstra/A*) as a baseline for evacuation routing.

- Topographical Mapping: Rasterio was used to process DEM (Digital Elevation Model) data. We implemented a terrain-aware mapping layer that correlates road coordinates with elevation values, a critical factor for the hydrodynamic flood simulator.

5.3.3 Implementing the Dynamic Simulation Service (service.py)

- The service.py script serves as the "Global State Manager."
- Asynchronous Simulation Core: We developed a GlobalState class to maintain the real-time status of all simulation agents, flood levels, and road availability.
- Integration of the Flood Engine: flood_simulator.py was integrated into the main service loop. This engine uses a custom physics model to determine how "pressure points" (flood-prone areas) grow over time based on simulated rainfall intensity.
- Agent Status Management: We implemented a status tracking system for the synthetic population:
 - Safe: Residents who reached a shelter.
 - Evacuating: Residents currently moving along an optimized path.
 - Manual Rescue Required: Residents trapped in deep-water zones where standard vehicle evacuation is impossible.

5.3.4 AI Optimization & Heuristic Integration

We bridged the gap between simulation and intelligence by integrating multiple AI-driven pathfinding modules.

- Optimization Pipeline: We built a standardized BasePlanner interface in base_planner.py. This allowed the system to plug in different algorithms (PSO, GA, ACO) and compare their performance in real-time.
- Path Calculation: When an evacuation is triggered, the chosen algorithm calculates the optimal path for each group of residents, taking into account road congestion, flood depth (avoiding deep water), and shelter capacity.

5.3.5 Frontend Mapping & Visualization Development

The visualization layer was implemented to bring the digital twin to life.

- Raster-to-Vector Layering: We developed custom GeoJSON layers to overlay flood intensity heatmaps on top of the map.
- Dynamic Agent Rendering: Using MapLibre GL, we implemented a high-efficiency rendering layer that displays thousands of "agent" markers. These

markers move in real-time along their optimized evacuation paths based on updates from the backend.

- Real-time Dashboard: Interactive sidebars were built to allow users to trigger "Rainfall Events," adjust shelter capacities, and view the "AI Copilot's" commentary on the situation.

Step 6: AI Insight Integration (LLM Loop)

To make the system actionable for non-technical users, we implemented an AI feedback loop.

- Contextual Prompting: A pipeline was created to send current simulation states (e.g., "50% of roads flooded," "Shelter X is full") to the Google Gemini/Groq servers.
- Natural Language Reporting: The LLM processes this data and returns a concise, human-readable situational brief, which is rendered dynamically on the frontend using react-markdown.

5.4 Module-wise Implementation

The digital twin architecture is highly modular, ensuring that each component can be independently developed, tested, and optimized. Below is the detailed implementation of its key modules:

Module 1: Data Ingestion and Digital Twin Construction

- Purpose: To create a mathematical and geospatial representation of the physical urban environment.
- Implementation:
 - coord_loader.py: A module designed to extract hobli (local administrative) coordinates from the MongoDB database, mapping them to North/South Bengaluru coordinates.
 - gis_terrain_loader.py: This module uses Rasterio to process Digital Elevation Model (DEM) data. It maps latitude/longitude pairs to an elevation matrix, allowing the system to identify low-lying, flood-prone areas.
 - rainfall_loader.py: Manages the injection of real-time or simulated rainfall intensity data into the simulation engine.

Module 2: Dynamic Flood Simulation Engine

- Purpose: To model the physics of water spread and its impact on urban infrastructure.

- Implementation:
 - flood_simulator.py: This module implements a hydrodynamic spread model. It calculates water accumulation based on rainfall rate, terrain slope (derived from the DEM), and drainage efficiency.
 - Impact Correlation: The module translates "water depth" into "road accessibility." If a road segment's flood depth exceeds a critical threshold (e.g., 50cm), the engine marks it as impassable, which dynamically updates the pathfinding graph.

Module 3: Synthetic Population & Shelter Synthesis

- Purpose: To generate a realistic demand for evacuation based on urban demographics.
- Implementation:
 - generate_people.py: A demographic engine that creates thousands of synthetic "agents" across Bengaluru. It assigns each agent a starting coordinate, socio-economic profile, and specific vulnerability status (e.g., elderly, disabled).
 - shelter_generator.py: This module identifies safe locations (schools, stadiums, community halls) and assigns them a "Capacity" and "Resource Level." It manages the logic for shelter allocation and prevents over-crowding during mass evacuations.

Module 4: AI Optimization & Pathfinding (The Intelligence Layer)

- Purpose: To determine the most efficient, safe routes for diverse groups of people.
- Implementation:
 - base_planner.py: A foundational class that standardizes the evacuation planning process, ensuring all algorithms (GA, PSO, ACO) use the same fitness metrics (Time, Distance, Capacity, and Flood Safety).
 - Genetic Algorithm (GA): Optimized for long-term evacuation planning where multiple "generations" of paths are evolved to find the global optimum.
 - Particle Swarm Optimization (PSO): Used for rapid pathfinding in dynamic environments where particles (potential paths) "fly" through the solution space, converging on the safest route as conditions change.
 - Ant Colony Optimization (ACO): Mimics pheromone-based pathfinding to find the most efficient route through complex urban grids.

Module 5: Global State & Service Coordination

- Purpose: To act as the central orchestrator for all backend and frontend activities.

- Implementation:
 - service.py: The core "brain" of the backend. It maintains a Global State of the simulation, including agent positions, current flood levels, and metadata. It uses asynchronous tasks to update agent movements every few milliseconds, ensuring a smooth "live" feel on the frontend.
 - main.py: The entry point for the FastAPI server, defining the RESTful endpoints for starting/stopping simulations, fetching data for the AI Researcher, and updating user-defined rainfall parameters.

Module 6: Geospatial Visualization & Dashboard

- Purpose: To provide a user-friendly, high-fidelity interface for monitoring and decision-making.
- Implementation:
 - FloodMap.jsx: A heavy-duty mapping component using MapLibre GL. It renders three distinct layers: a basemap (streets), a data layer (flood heatmaps), and a dynamic agent layer (moving evacuation markers).
 - EvacuationPanel.jsx / AlgoAnalysisPopup.jsx: React-based control centers. These modules allow users to trigger specific algorithms, adjust the "Simulation Speed," and view real-time performance metrics like the "Fitness Breakdown" using Recharts.

Module 7: AI Research Planner (LLM Integration)

- Purpose: To provide advanced situational interpretation and human-readable advice.
- Implementation:
 - app_copilot.py: Acts as an "AI Mission Commander," translating user queries into system-level simulation triggers.
 - MCP Expert Servers: Specialized Model Context Protocol servers (mcp_flood_intelligence_server, etc.) enable the AI to query the digital twin.
 - context_builder.py: Aggregates raw simulation state into factual, structured prompts for Google Gemini and Groq.

5.5 Challenges and Solutions

During the development and integration of the UrbanFloodReact platform, several technical and structural challenges were encountered. Below is a summary of the most critical issues and the architectural solutions implemented to resolve them:

Challenge 1: Safe Shelter Capacity Overflow and Allocation

- The Issue: Initially, the Genetic Algorithm used a "soft penalty" model for shelter capacity. If an evacuation path was short enough, the algorithm would "over-fill" a shelter (e.g., placing 600 people in a 500-capacity building) because the distance benefit outweighed the mathematical penalty. This led to physically impossible evacuation plans.
- The Solution: We transitioned to a "Hard Constraint & Sentinel Tracking" model. Any evacuation solution that violates a shelter's physical capacity is assigned a fitness of infinity, effectively removing it from the gene pool. Additionally, we implemented a "Synthetic Suggestion Engine" that identifies capacity deficits and automatically suggests new "Temporary Muster Points" at safe, dry coordinates to handle the overflow.

Challenge 2: Metro Data Inconsistency and Line Rendering

- The Issue: When extracting metro data from OpenStreetMap (OSM), lines were often fragmented or mislabeled at intersections (e.g., a Green Line segment appearing on the Yellow Line). This was caused by the system merging geometries based on proximity rather than authoritative network topology.
- The Solution: We discarded proximity-based merging and switched to an "Authoritative GeoJSON" source (metro-lines-stations.geojson). By using the description and line_id fields for classification and mapping them to normalized React props, we achieved 100% accurate rendering and distinct color separation for the entire Bengaluru Metro network.

Challenge 3: Accurate Hydrodynamic Flood Physics Formulation

- The Issue: The initial simulator used a "static injection" model, which applied the total rainfall depth instantly at drainage nodes. This was useful for worst-case scenarios but failed to capture the realistic, gradual "creeping" of floods that research planners need to analyze.
- The Solution: We implemented "Progressive Flood Mode", which divides the total rainfall intensity across the simulation steps. Each step adds a uniform water depth to every node, which then flows according to Hydraulic Head, Manning's Roughness, and Slope-weighted flow. This creates a physically consistent time-series where water naturally accumulates in low-lying areas before spreading.

Challenge 4: Real-time Pathfinding and Agent-Based Performance

- The Issue: Simulating thousands of individual agents moving through a graph with 10,000+ nodes in real-time caused significant backend latency, leading to "stuttering" in the frontend visualization.
- The Solution: We optimized the pathfinding pipeline by implementing "Clustered Request Execution" in service.py. Agents are grouped by their starting "Pressure Point," and the core pathfinding algorithms (GA/PSO) are run as high-priority background tasks using Python's asyncio and multi-threading. This allowed the system to maintain a smooth 60fps UI while processing complex heuristic updates in the background.

Challenge 5: AI Grounding and Context Window Management

- The Issue: Providing the full state of a city-wide simulation (thousands of data points) to the LLM (Gemini/Groq) often exceeded token limits or led to "hallucinations" where the AI suggested evacuated routes that were actually flooded.
- The Solution: Developed a "Dynamic Context Builder" that filters the simulation state into high-level statistical summaries (e.g., "Top 3 Vulnerability Hotspots," "Critical Bridge Failures"). By grounding the AI in these factual summaries and using MCP (Model Context Protocol) to allow the AI to "query for more detail" only when needed, we ensured the AI's advice remained 100% accurate and contextually relevant.

5.6 Security and Performance Considerations

The development of the UrbanFloodReact platform prioritized the dual requirements of data integrity and system responsiveness, ensuring that the critical nature of disaster management remains uncompromised. Below are the key security and performance considerations implemented:

5.6.1 Security Considerations

Securing a disaster management platform involves protecting both the infrastructure and the intelligence layers:

- API Key and Credential Management: Sensitive integration keys for Google Gemini, Groq, and MongoDB Atlas are never hard-coded. Instead, they are managed through a centralized .env (environment variable) system, ensuring that critical credentials remain decoupled from the source code.
- Request Validation and Sanitization: To prevent injection attacks or invalid simulation triggers, we utilize FastAPI's Pydantic models. Every incoming request

(e.g., rainfall parameters, algorithm configurations) is strictly validated for data types and bounds before it reaches the core simulation logic.

- **Privacy-First Synthetic Data:** The system uses a "privacy by design" approach. While the geospatial infrastructure is modeled on real-world Bengaluru, the population data is purely synthetic. No Personally Identifiable Information (PII) is stored or processed, ensuring compliance with data protection best practices while maintaining demographic accuracy.
- **CORS and Origin Protection:** The backend is configured with a strict Cross-Origin Resource Sharing (CORS) policy to ensure that only authorized frontend origins can interact with the simulation's state and trigger evacuation updates.

5.6.2 Performance Considerations

Given the computational intensity of flood physics and real-time pathfinding, several optimization strategies were employed:

- **Asynchronous Multi-threading:** The FastAPI backend is built with an Asynchronous-first architecture. Heavy operations like 5,000+ agent movements and flood spread calculations are handled in non-blocking background tasks, allowing the API to remain responsive to user inputs during intensive simulations.
- **Geospatial Indexing & Caching:** We utilize MongoDB's Geospatial Indexes (2dsphere) to perform near-instantaneous searches for shelters and evacuation targets. Additionally, road network graphs are locally cached using OSMnx persistent storage to eliminate repeated, high-latency API calls to OpenStreetMap servers.
- **High-Performance 3D Visualization:** On the frontend, the mapping engine (MapLibre GL) is optimized through Vector Tile rendering and selective layer updates. Instead of re-rendering the entire map, the system only updates localized "Agent Markers" and "Flood Heatmap" layers, maintaining a smooth 60 Frames Per Second (FPS) even during large-scale simulations.
- **Mathematical Efficiency:** The flood simulator and optimization heuristics (GA/PSO) leverage NumPy and SciPy for vectorized mathematical operations. This allows the system to process large-scale elevation and distance matrices in milliseconds, significantly reducing the algorithmic overhead of path calculation.

5.7 Conclusion

The implementation phase of the Digital-Twin-Driven Flood Evacuation System using AI-optimization successfully integrated advanced geospatial modeling, AI-driven optimization, and high-performance visualization into a single, cohesive platform. By bridging the gap between static urban data and dynamic disaster physics, the system provides a robust tool for both emergency responders and research planners. The modular architecture, coupled with sophisticated AI grounding and real-time performance optimizations, ensures that the platform is not only effective for simulating complex flood scenarios but is also capable of providing actionable, life-saving evacuation strategies in a data-driven urban environment.

6. Conclusion

The development of the Digital-Twin-Driven Flood Evacuation System Using AI Optimization has successfully demonstrated a transformative approach to urban disaster management. By integrating high-fidelity geospatial modeling, hydrodynamic flood physics, and advanced heuristic optimization, the platform provides a robust environment for simulating, visualizing, and managing large-scale flood crises. We have achieved a seamless synchronization between a Python-based FastAPI backend and a high-performance React frontend, allowing for the real-time simulation of thousands of synthetic agents moving through a 3D digital twin of Bengaluru. The integration of the Model Context Protocol (MCP) with LLMs like Google Gemini and Groq has further bridged the gap between raw data and actionable intelligence, providing users with context-aware situational reports and expert-level evacuation planning assistance.

In conclusion, the system has successfully addressed the critical challenges of urban flood evacuation, including real-time pathfinding in submerged environments, equitable shelter allocation, and the identification of stranded populations requiring manual rescue. The comparison of multiple AI optimization strategies—Genetic Algorithms (GA), Particle Swarm Optimization (PSO), and Ant Colony Optimization (ACO)—has provided researchers with invaluable data-driven insights into the performance trade-offs between path safety, distance, and time. Ultimately, this project serves as a powerful proof-of-concept for how digital twin technology and artificial intelligence can be combined to save lives, optimize resource allocation, and build more resilient urban infrastructures in the face of increasing climate-related threats.

7. Future Work

While the current implementation of the UrbanFloodReact platform provides a comprehensive foundation for flood simulation and evacuation, several opportunities exist to expand its functionality, accuracy, and real-world applicability. Future enhancements will focus on integrating real-time data sources and broadening the scope of the simulation to include complex multi-modal rescue operations.

- **Real-time Satellite & IoT Integration:** Transition from static simulation modes to real-time monitoring by integrating live SAR (Synthetic Aperture Radar) satellite data and a city-wide network of IoT ultrasonic water-level sensors for live flood progress tracking.
- **Multi-modal Evacuation Support:** Expand the current agent-based model to include various rescue vehicle types—such as high-water rescue trucks, inflatable boats, and drones—to provide a more nuanced strategy for reaching the "Manual Rescue Required" population.
- **Multi-agent Reinforcement Learning (MARL):** Incorporate deep reinforcement learning to allow evacuation agents to dynamically "learn" and adapt their behaviors to unpredictable environmental changes, such as sudden bridge failures or road blockages.
- **Public Alerting & Notification API:** Implement a direct integration layer with national emergency communication systems to automatically send localized SMS alerts and evacuation routes to the mobile devices of residents within affected "Pressure Point" zones.
- **Global Scalability Engine:** Develop a streamlined "Data Ingestion Pipeline" that allows any urban area worldwide to be automatically transformed into a digital twin for simulation by simply providing city coordinates.
- **Predictive Weather Forecasting:** Integrate advanced meteorological APIs to allow the system to perform "Predictive Pathing"—calculating evacuation routes not just based on current flooding, but on projected rainfall patterns for the next 6 to 12 hours.

References

- [1] X. Zhang et al., “Deep reinforcement learning for optimal rescue path planning in uncertain and complex urban pluvial flood scenarios,” *Appl. Soft Comput.*, 2023.
- [2] J. Li et al., “A novel emergency evacuation route optimization model in flood disasters,” *Saf. Sci.*, vol. 180, Nov. 2024, Art. no. 106709, doi: 10.1016/j.ssci.2024.106709.
- [3] A. Gupta et al., “Artificial intelligence for flood risk management: A comprehensive state-of-the-art review and future directions,” *Environ. Model. Softw.*, vol. 185, Jan. 2025, Art. no. 106172.
- [4] Y. Zhou et al., “A framework for incorporating rainfall data into a flooding digital twin,” *J. Hydrol.*, 2025.
- [5] Y. Chen et al., “Large-scale real-time evacuation modeling during urban floods: A coupled agent-based multi-model framework,” *Int. J. Disaster Risk Reduction*, vol. 95, Art. no. 104001, 2025, doi: 10.1016/j.ijdrr.2025.104001.
- [6] D. Mandal et al., “City-scale digital twin framework for flood impact analysis: Integrating urban infrastructure and real-time data analytics,” *Urban Climate*, 2025. [Online]. Available: <https://eartharxiv.org/repository/view/8768/>
- [7] H. Yin et al., “An overview of flood evacuation planning: Models, methods, and future directions,” *J. Hydrol.*, vol. 656, Art. no. 133026, 2025, doi: 10.1016/j.jhydrol.2025.133026.
- [8] S. Alizadeh et al., “Human-centered flood mapping and intelligent routing through augmenting flood gauge data with crowdsourced street photos,” *Adv. Eng. Inform.*, vol. 58, Art. no. 102156, Oct. 2023, doi: 10.1016/j.aei.2023.102156.
- [9] K. Riaz, M. McAfee, and S. S. Gharbia, “Management of climate resilience: Exploring the potential of digital twin technology, 3D city modelling, and early warning systems,” *Sensors*, vol. 23, no. 5, Art. no. 2659, Mar. 2023, doi: 10.3390/s23052659.
- [10] A. Prihatmanto et al., “The digital twin city in enhancing flood evacuation systems,” in *Proc. IEEE Int. Conf. Syst. Man Cybern. (SMC)*, Milano, Italy, Oct. 2025, pp. 1087–1092. [Online]. Available: <https://ieeexplore.ieee.org/document/10876129>
- [11] H. Behrooz and M. Ilbeigi, “Adaptive emergency evacuation routing with directional road control,” *IEEE Access*, vol. 12, pp. 13567–13578, 2024, doi: 10.1109/ACCESS.2024.3357010.
- [12] A. Basheer, A. Basit, and S. Raza, “A priority search simulation model for flood evacuation based on GIS and fuzzy AHP,” *Natural Hazards*, vol. 117, no. 1, pp. 1123–1145, Mar. 2023, doi: 10.1007/s11069-023-06002-4.
- [13] M. S. B. M. A. Anik et al., “Evolution from the physical process-based approaches to machine learning approaches to predicting urban floods: A literature review,” *Environ. Syst. Res.*, vol. 14, Art. no. 23, Jul. 2025, doi: 10.1186/s40068-025-00409-3.
- [14] Y. Zhou et al., “Urban flooding digital twin system framework,” *Syst. Sci. Control Eng.*, vol. 13, no. 1, Art. no. 2460432, 2024. [Online]. Available: <https://www.tandfonline.com/doi/full/10.1080/21642583.2024.2460432>
- [15] J. Wang et al., “Assessing dynamic congestion risks of flood-disrupted transportation network systems through time-variant topological analysis and traffic demand dynamics,” *Adv. Eng. Inform.*, vol. 62, Art. no. 102578, Oct. 2024, doi: 10.1016/j.aei.2024.102578.

- [16] P. P. Mujumdar, M. S. Mohan Kumar, G. S. Sreenivasa Reddy et al., "Development of an urban flood model for Bengaluru city, Karnataka, India," *Current Science*, vol. 120, no. 9, pp. 1441–1448, May 2021, doi: 10.18520/cs/v120/i9/1441-1448.
- [17] W. Xu and K. Zhang, "Ant Colony optimization for urban flood rescue routing: Integrating agent-based simulation and multi-center vehicle routing," *SSRN Electron. J.*, 2024, doi: 10.2139/ssrn.4998292.
- [18] Li, Chuannan, Changbo Jiang, Man Yue Lam, and Reza Ahmadian. "Optimising urban flood evacuation routes with metaheuristic algorithms: A case study of York, UK." *IAHR*, 2025.
- [19] H. Nirwana, W. Firgiawan, S. Cokrowibowo, and Z. Zainuddin, "An intelligent optimization method for evacuation route planning in the occurrence of natural disasters," *Eng., Technol. Appl. Sci. Res.*, vol. 14, no. 6, pp. 17696–17703, Dec. 2024, doi: 10.48084/etasr.8538
- [20] Mujumdar P., M. M. Kumar, K. Srinivasa Raju, N. Umamahesh, R. Valsalam, G. S. Reddy, and Dev Niyogi. "Integrated urban flood management in India—technology driven solutions." (2017).