

Connecting R with D3 for dynamic graphics, to explore multivariate data with tours

by Michael Kipp, Dianne Cook, Ursula Laa

Abstract The `tourr` package in R has several algorithms and displays for showing multivariate data as a sequence of low-dimensional projections. It can display as a movie but has no capacity for interaction, such as stop/go, change tour type, drop/add variables. The `tourrGui` package provides these sorts of controls, but the interface is programmed with the dated `RGtk2` package. This work explores using custom messages to pass data from R to D3 for viewing, using the Shiny framework.

Introduction

The tour algorithm (Cook et al. 1995; Cook et al. 2007) is a way of systematically generating and displaying projections of high-dimensional spaces in order for the viewer to examine the multivariate distribution of data. It can do this either randomly, or by picking projections judged interesting according to some criterion or index function. The `tourr` package (Wickham et al. 2011) provides the computing and display in R (R Core Team 2018; Ihaka and Gentleman 1996) to make several types of tours: grand, guided, little and local. The projection dimension can be chosen between one and the number of variables in the data. The display, though, has no capacity for interaction. The viewer can watch the tour like a movie, but not pause it and restart, or change tour type, or number of variables.

These interactive controls were provided with the `tourrGui` package (Huang, Cook, and Wickham 2012), which was programmed with the `RGtk2` package (Lawrence and Temple Lang 2010). This is not the toolkit of choice today, and has been superseded with primarily web-capable tools, like Shiny (Chang et al. 2017). To display dynamic graphics though, is not straight-forward. This paper explains how to use D3 (Bostock, Ogievetsky, and Heer 2011) as the display engine in a Shiny GUI, using custom message passing between server and client.

Creating a tour, with the `tourr` package

The `tourr` package (Wickham et al. 2011) is an R implementation of the tour algorithms discussed in Cook et al. (2007). It includes methods for geodesic interpolation and basis generation, as well as an implementation of the simulated annealing algorithm to optimise projection pursuit indices for the guided tour. The tour can be displayed directly in the R graphics device, for example:

```
# quartz() # to display on a Mac
# X11() # For windows
# The Rstudio graphics device cannot be used
animate_dist(flea[, 1:6], center = FALSE)
```

generating the animation in Figure ??.

EMBED MOVIE HERE

A tour path is a smooth sequence of projection matrices, $p \times d$, that when combined with a matrix of n data points, $n \times p$, and a rendering method, produces a steady stream of d -dimensional views of the data. Each tour is initialised with the `new_tour()` method, which instantiates a tour object and takes as arguments the data X , the tour method, e.g. `guided_tour()`, and the starting basis. Once initialised, a new target plane is chosen, and a series of steps along a geodesic path from starting to target plane are generated by interpolation.

This requires a series of calls to the tour object producing the series of projections. The steps are discrete, of size given by ω / Δ , where ω denotes the angular velocity of the geodesic interpolation, and Δ is a parameter denoting frames per second, reflecting the rendering speed of the device in use. The Δ parameter can be thought of as the frames per second, while ω affects the speed at which the tour moves through the projection space. For our purposes, Δ , `fps` in the code, is set at 25, while the ω can be adjusted by the user.

Connecting the tour projections to D3 display using `sendCustomMessage`

D3.js (Data-Driven Documents) (Bostock, Ogievetsky, and Heer 2011) is a JavaScript library for manipulating documents based on data. The advantages of D3 are similar to those provided by Shiny: namely, an industry standard with rich array of powerful, easy to use methods and widgets that can be displayed on a wide variety of devices, with a large user base. D3 works on data objects in the JavaScript Object Notation (JSON) format, which are then parsed and used to display customisable data visualisations.

The new implementation of the tour interface uses D3 to render each projection step returned by R, focusing on 2D projections as a test case. It does this by drawing and re-drawing a scatterplot with dots (or circles in D3 language) and providing SVG objects for the web browser to render.

There are two functions provided by the Shiny framework to transport data between R and JavaScript: `session$sendCustomMessage()` in R, and the corresponding `Shiny.addCustomMessageHandler()` in JavaScript. Whenever the former is executed in R, the latter function will execute a code block in JS. There are many examples of such functions being used to pass arbitrary data from an R app to a JS front-end, few examples exist of this basic functionality to update a D3 animation in real-time.

The data format expected by D3 is in JSON format, which combines two basic programming paradigms: a collection of name/value pairs, and an ordered list of values. R's preferred data formats include data frames, vectors and matrices. Every time a new projection has been calculated with the tour path, the resulting matrix needs to be converted to JSON and sent to D3. The code to send the D3 data looks like this:

```
session$sendCustomMessage(type = "data", message = toJSON(j))
```

This code is from the observe environment from the server.R file. It converts the matrix of projected data points to JSON format, and sends it to JavaScript with the id data. When parsed in D3 by its `data()` method, it is converted back into a logical 2D array where the columns are queried first, then the rows. If column names are included in the JSON, the column indices are strings; otherwise they are integers starting from 1. All of the code required to render the scatterplots and legends, along with colours, is JavaScript code in the file `d3anim.js`. In particular, the data from R is handled with the following code:

```
Shiny.addCustomMessageHandler("data",
  function(message) {
    /* D3 scatterplot is drawn and re-drawn using the
       data sent from the server. */
  })
```

Every time the message is sent (25 times per second), the code-block is run.

Getting projections

The `observeEvent` Shiny method defines a code block to be run whenever some input value changes. The following code snippet restarts a tour using a random basis:

```
observeEvent(input$restart_random,
{
  p <- length(input$variables)
  b <- matrix(runif(2*p), p, 2)
  rv$tour <-
    new_tour(as.matrix(rv$d[input$variables]),
             choose_tour(input$type,
                         input$guidedIndex,
                         c(rv$class[[1]]),
                         input$scagType), b)
})
```

The projections are calculated using the tour object in an `observe()` environment, which repeatedly runs the code until a reactive variable is changed, at which point it is "invalidated" and then re-started. The projections are calculated using the following code block:

```
observe({
```

```

tour <- rv$tour
aps <- rv$aps
step <- tour(aps / fps)
if (!is.null(step)) {
  invalidateLater(1000 / fps)
  j <- center(rv$mat %*% step$proj)
  j <- cbind(j, class = rv$class)
  colnames(j) <- NULL
  session$sendCustomMessage(type = "data",
    message = toJSON(j))
}
else {
  if (length(rv$mat[1, ]) < 3) {
    session$sendCustomMessage(type = "debug",
      message = "Error: Need > 2 variables.")
  } else {
    session$sendCustomMessage(type = "debug",
      message = "Guided tour finished: no better bases found.")
  }
}
})

```

Pros and cons

The D3 canvas makes for smooth drawing and re-drawing of the data projections. Adding a graphical user interface (GUI) around the display is straightforward with the Shiny package, e.g. control elements such as stop/go, increase/decrease speed, change tour type, add/remove variables from the mix.

The main disadvantage is that the speed is inconsistent, as server and client play tag to keep up with each other, and the display cannot handle many observations. Noticeable slow down was observed with 2000 points, the main reason being the rendering time required for the large number of SVG circle elements. The situation can be improved when using a single HTML5 canvas element to draw the scatter points, significantly reducing the rendering time.

Code

The code is available at [<https://github.com/makipp/TourrGuiD3>], and the source material for this paper is available at [<https://github.com/dicook/paper-tourrd3>].

Summary

The `sendCustomMessage` function provides a way to share a tour path with the D3 renderer, and embed it in a Shiny GUI providing controls such as stop/go, increase/decrease speed, change tour type, add/remove variables. However, the approach can result in inconsistent speed which appears as jerkiness in the motion, and it isn't suitable for large numbers of observations.

References

- Bostock, Michael, Vadim Ogievetsky, and Jeffrey Heer. 2011. "D3: Data-Driven Documents." *IEEE Transactions on Visualization and Computer Graphics* 17 (12): 2301–9. <http://vis.stanford.edu/papers/d3>.
- Chang, Winston, Joe Cheng, JJ Allaire, Yihui Xie, and Jonathan McPherson. 2017. *Shiny: Web Application Framework for R*. <https://CRAN.R-project.org/package=shiny>.
- Cook, Dianne, Andreas Buja, Javier Cabrera, and Catherine Hurley. 1995. "Grand Tour and Projection Pursuit." *Journal of Computational and Graphical Statistics* 4 (4): 155–72.
- Cook, Dianne, Andreas Buja, Eun-Kyung Lee, and Hadley Wickham. 2007. "Grand Tours, Projection Pursuit Guided Tours and Manual Controls."
- Huang, Bei, Dianne Cook, and Hadley Wickham. 2012. "TourrGui: A GWidgets GUI for the Tour to Explore High-Dimensional Data Using Low-Dimensional Projections." *Journal of Statistical Software* 49 (6): 1–12.
- Ihaka, Ross, and Robert Gentleman. 1996. "R: A Language for Data Analysis and Graphics." *Journal of Computational and Graphical Statistics* 5 (3): 299–314.

Lawrence, Michael, and Duncan Temple Lang. 2010. "RGtk2: A Graphical User Interface Toolkit for R." *Journal of Statistical Software* 37 (8): 1–52. <http://www.jstatsoft.org/v37/i08/>.

R Core Team. 2018. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. <http://www.R-project.org/>.

Wickham, Hadley, Dianne Cook, Heike Hofmann, and Andreas Buja. 2011. "Tourr: An R Package for Exploring Multivariate Data with Projections." *Journal of Statistical Software* 40 (2): 1–18.

Michael Kipp
Monash University
Department of Econometrics and Business Statistics
mkip271@gmail.com

Dianne Cook
Monash University
Department of Econometrics and Business Statistics
dicook@monash.edu

Ursula Laa
Monash University
School of Physics and Astronomy
ursula.laa@monash.edu