

1. Laravel(update version) Project Creation

composer create-project laravel/laravel laravel-inertia "11.*"

Env:

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=laravel_inertia
DB_USERNAME=root
DB_PASSWORD=
```

CMD:

Php artisan migrate

- a. cd project_name
- b. project_name>npm i vue@latest

Inertia - Server Side Install

(a) Inertia composer installation

composer require inertiajs/inertia-laravel

(a) Configure Blade Template Engine - Prepare Master Blade Layout /views/app.blade.php

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0,
maximum-scale=1.0" />
    @vite('resources/js/app.js')
    @inertiaHead
  </head>
  <body>
    @inertia
  </body>
</html>
```

(c) Create Inertia Middleware

```
php artisan inertia:middleware
```

(d) Add Inertia Middleware With Your Route Middleware

bootstrap/app.php

```
use App\Http\Middleware\HandleInertiaRequests;
```

```
->withMiddleware(function (Middleware $middleware) {  
    $middleware->web(append: [  
        HandleInertiaRequests::class,  
    ]);  
});
```

e) web:

```
Route::get('/', function () {  
    return Inertia::render('Home');  
});
```

Inertia - Client Side Install

(a) Install Vue JS

```
npm install @inertiajs/vue3
```

Import resources/js/app.js

```
import { router } from '@inertiajs/vue3'
```

(b) configure app.js

```
npm i vue
```

```
resources/js/app.js
```

```
import { createApp, h } from 'vue'  
import { createInertiaApp } from '@inertiajs/vue3'  
  
createInertiaApp({  
  resolve: name => {  
    const pages = import.meta.glob('./Pages/**/*.vue', { eager: true })  
    return pages[`./Pages/${name}.vue`]  
  },  
  setup({ el, App, props, plugin }) {
```

```

    createApp({ render: () => h(App, props) })
      .use(plugin)
      .mount(el)
  },
})

```

(c) configure vite
cmd: npm i @vitejs/plugin-vue

vite.config.js

```

import { defineConfig } from "vite";
import vue from "@vitejs/plugin-vue";
import laravel from "laravel-vite-plugin";
// import tailwindcss from "@tailwindcss/vite";
export default defineConfig({
  plugins: [
    laravel({
      input: ["resources/css/app.css", "resources/js/app.js"],
      refresh: true,
    }),
    vue(),
    // tailwindcss(),
  ],
  build: {
    manifest: true,
    outDir: "public/build",
  },
});

```

resources/js/Pages/Home.vue

```

<template>
  <h2>home page</h2>
</template>
<script>
</script>

```

Final

Php artisan serve

Npm run dev

`validateCsrfTokens` method in your application's `bootstrap/app.php` file:

```
->withMiddleware(function (Middleware $middleware) {  
    $middleware->validateCsrfTokens(except: [  
        '*', // all  
        'http://example.com/foo/bar',  
        'http://example.com/foo/*',  
    ]);  
})
```