

10-600: **Machine Learning Primer**

Matt Gormley

2022

© 2022 Matt Gormley

All rights reserved. This book or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the copyright holders (authors) except for the use of brief quotations in a book review.

Contents

1	Big-O	5
1	Overview	5
2	Definition and Mathematical Properties	5
2.1	An aside on verbiage	6
2.2	Standard Complexity Classes	6
2.3	Big-O properties	6
3	Code Examples	7

Chapter 1

Big-O

1 Overview

We can measure the run time, spatial complexity, or general resource consumption of a given function through Big-O notation. Informally, if the function `my_fn(x)` runs in $O(f(n))$, this means that when the input `x` is of size n , the worst-case scenario run time of `my_fn(x)` is asymptotically a constant multiple of $f(n)$.

Note that run time here refers to the number of algorithmic steps that the function takes rather than wall-clock time.

2 Definition and Mathematical Properties

For the purposes of this course, (and *most* future MLD courses you may or may not take), it's best to think of big-O for comparing two arbitrary functions, which we will call f and g respectively. For simplicity, we'll assume that both f and g are defined over \mathbb{R}_+ (that is, f and g only take positive real numbers as inputs) only, which is enough for this course. Formally, Big-O is defined as:

Definition 1.1 (Big-O Notation). If $f(n) \in O(g(n))$, then there exists some $c, n_0 \in \mathbb{R}_+$ such that:

$$\forall n \geq n_0, \quad f(n) \leq cg(n)$$

(Note: if you've seen Big-O before, you may be more familiar with the notation $f(n) = O(g(n))$. We avoid using this alternative as the equality operator implies a certain degree of symmetry that is not present.)

In words, this means that if $f(n) \in O(g(n))$, then at some point as the inputs increase, $f(n)$ will *always* be less than or equal to a constant multiple of $g(n)$.

2.1 An aside on verbiage

It can sometimes be confusing to talk about big-O in the context of computer science and the math behind it, as functions like $n!$ are simultaneously described as “fast-growing” and “slow”. This is not incorrect: calling $n!$ “fast-growing” refers to the fact that as n increases $n!$ quickly explodes (1, 1, 2, 6, 24, 120, 720, 5040, ...), while calling $n!$ “slow” refers to the fact that an algorithm that runs in $O(n!)$ time takes a constant multiple of $n!$ steps to run, which can take a long time! Normally, “fast-growing” is used more when talking about big-O in the pure mathematical sense (e.g. comparing arbitrary functions), while “slow” is used more in computer science when talking about run-time complexity, so we expect you to be comfortable with both!

2.2 Standard Complexity Classes

While the big-O bound for any function f can be defined by any other valid function g , in computer science we generally only talk about the following complexity classes (shown in increasing order of complexity):

1. $O(1)$: Constant time
2. $O(\log(n))$: logarithmic time
3. $O(n)$: linear time
4. $O(n \log(n))$: log-linear time
5. $O(n^2)$: quadratic time
6. $O(n^p)$: polynomial time, for some $p > 2$
7. $O(p^n)$: exponential time
8. $O(n!)$: factorial time

2.3 Big-O properties

Based on this definition, we get a few interesting properties as consequence:

Definition 1.2 (Transitivity). For three functions f, g, h all on \mathbb{R}_+ , if $f(n) \in O(g(n))$ and $g(n) \in O(h(n))$, then $f(n) \in O(h(n))$.

A result of the transitivity property is that a function f does not have a unique big-O bound, as we can always come up with faster growing functions than f . However, in computer science we normally want the *tightest* Big-O bound in order to formalize what realistically happens “in the worst case.”

Definition 1.3 (Lower-Order Ambivalence). If $f(n) = f_1(n) + f_2(n)$ for some functions f_1, f_2 such that $f_2(n) \in O(f_1(n))$, then $f(n) \in O(f_1(n))$.

In words, this means that we only care about the *fastest* growing part of a function to determine its Big-O complexity. So if $f(n) = 5n^3 + 2n$, then $f(n) \in O(n^3)$ (i.e. we can disregard the $2n$ term, as asymptotically $5n^3$ becomes much larger than $2n$).

Definition 1.4 (Log Equivalence). If $f(n) = \log_p(n)$ and $g(n) = \log_q(n)$ for two bases $p, q \in \mathbb{N}$, then $f(n) \in O(g(n))$ and $g(n) \in O(f(n))$.

To show that this is true, recall the log rule that $\log_a(b) = \frac{\log(b)}{\log(a)}$ where \log is the natural log. Given this, $f(n) = \frac{1}{\log(p)} \log(n)$ and $g(n) = \frac{1}{\log(q)} \log(n)$, and thus $f(n)$ and $g(n)$ are equivalent up to a constant.

3 Code Examples

Algorithm 1.5 (H). Linear Search

```

1: procedure LINEARSEARCH(list  $A$ , size of list  $n$ , value  $v$ )
2:   for  $i = 0$  to  $n - 1$  do
3:     if  $A[i] == v$  then return  $i$ 
4:
```

—