



My4S – A program-builder for creating web applications such as ERP, CRM, and others.

Avtor: Sergiy Chakhanyuk aka didSergiy4s.

Table of contents

What is My4S.....	4
Core Principles:	4
Technologies:	5
Briefly about My4S.....	5
On the server side:.....	5
ODBC driver	5
Features of My4S.	7
Here is what we have:.....	7
Introduction to browser forms	8
Database optimization	8
Capabilities of My4S	8
The Future of My4S	8
Database Recovery Mechanism.....	9
Recovery Process:	9
Security Note	9
AUTHORIZATION	9
Access rights management in the Enterprise	11

Password change	11
User linkage	11
Initial base (do not confuse with demo)	11
Entering the Configurator.....	11
METADATA table and menu structure.....	12
Adding new objects	12
Let us start by examining ID_DB.	12
Main metadata identifiers	12
Reserved constants.	13
BALANSE (Balance registers):.....	14
Balances in My4S and their support in Firebird.....	14
Database Truncation Mechanism as of a Specific Date	15
Security Features in Firebird.....	15
Form BALANSE	16
Why accounts and accounts#1.	16
Working with the metadata configuration form.....	18
Using the example of directories (CATS), let us examine how to work with forms.	18
Sets (Complects).	20
Subordinate directory (CATS1).....	21
Information registers (REGS).....	22
Documents (DOCS).	22
Editing the textarea field.....	24
New (Excel)!	25
Description of register movements	26
🔧 Operation of the mechanism for creating a document based on another in the Enterprise system	28
📄 Document check on opening	29
About 4SON	30
📁 Description of the Project File Structure in Node.js	32
📄 *Automatically Generated .js Files.....	33

 Internal Database Folders	33
 cf folder – .htm templates and other files for working in the Configurator.....	33
Report in My4s.....	35
Turnover Balance Sheet	35
Register Selection	36
🔍 Bottom Table: Filters	36
Examples of Working with Filters.....	37
📄 How Settings Are Saved	39
📦 Universality of Settings	39
Report Created in the Configurator	39
Creating a New Report.....	39
General Principles of Report Configuration	41
Working with the AS Column	41
Parameters Name, VV, and TAB	41
Let us now look at the next tab — MaketPrint:.....	43
Next Report — Assistant for Creating Additional Reports	44
Starting Work with a New Report	44
Important Rules When Creating a Report.....	44
Selecting a Table for the Report.....	45
Working with Dropdown Lists.....	45
Query_fast Reports (Quick Reports)	51
Processing	51
Let’s summarize reports and processing.	51
Firebird Select Report	52
Working with Multiple Time Zones.....	52
Let’s sum up briefly what was written above.	53
Installation guide for My4s on your computer or laptop with Windows	53
Steps for setting up the database (from scratch).....	55
Verification of operation.....	55

Working with My4s on Windows 7.....	56
Contact with the author:	56
License and usage	56
Copyright.....	56
Disclaimer of warranties	57

What is My4S.

My4S is a freely distributed web application with open-source code. The server-side runs on Node.js (currently only on Windows).

My4S can become an excellent tool for small and medium-sized businesses, especially if you need a flexible and free ERP/CRM system. Here are several ways it can be used:

1. Financial and accounting management.

You can configure accounting registers to track income, expenses, taxes, and other financial operations. Built-in balance sheets help analyze the state of the budget.

2. Inventory management.

Thanks to the ability to work with different registers and directories, you can easily manage goods, monitor stock levels, automate purchases, and analyze sales.

3. Customer and sales management.

Use directories of contractors and document flow to maintain a client database, manage orders, automate invoicing, and analyze sales.

4. Business process automation.

My4S allows you to create documents and registers, enabling automation of key processes — from payroll calculations to scheduling meetings and tasks.

5. Customization for any tasks.

Since the system is flexible and open-source, you can adapt it to your needs: add new features, expand reporting, and integrate with other services.

I express my deep gratitude to the developers of Node.js, Firebird databases, Firebird Editor Pro, Visual Studio Code!

Core Principles:

- Use exclusively free software (except Windows).
- In Node.js, only one exe file is currently used, and this is a fundamental position! It is important that any third-party code used in the program is trustworthy or can be modified without the author's involvement.

- Ability to connect any amount of external code, both in Node.js and in everything that supports JavaScript. However, responsibility for its use lies with you!

Technologies:

- Database: Firebird 3.0 and above. For administration, you can use Firebird Editor Pro.

Editor: If you don't yet have a favorite JavaScript editor, try Visual Studio Code — it offers good support for Node.js. Node.exe can be restarted directly from the editor, which is very convenient for making changes and testing. Debug mode is also available!

- Client and server: Both are written in the same language — JavaScript.

Briefly about My4S

On the client side:

No need to install any programs! We use only a browser (tested on Google Chrome, Microsoft Edge, Opera, CCleaner Browser).

It is launched with a browser string “path:port/path_mydb/cf” — entry to the Configurator, or “path:port/path_mydb/db” — entry for working with the program (Enterprise).

Where:

path — the path to the My4S server (if on a local computer “127.0.0.1”, if in a corporate network then “servername with Node”. On a local computer and corporate network everything works without the internet! Otherwise, the standard path to the site or VPN).

port — a free port that the server will listen to (specified in “Start4s.js”). By default, mine is “1637”.

path_mydb — the name of the folder with a specific database (there may be several databases on the server).

Example: “127.0.0.1:1637/mydb/cf”.

On the server side:

Install Firebird 3.x (you can also use Firebird 4.x (5.x) — but the developers rushed ahead too quickly!!). I tested under 3.x, but I think it should work with others (4.x tested quickly — works, 5.x still raw!). For ERP program development, 3.x is quite sufficient for now, and later you can decide yourself!

Step-by-step instructions on how to set up a demo database and the main database are at the end of the description.

ODBC driver

For working with Firebird, I use the ODBC driver. Why not “node-firebird-driver-native”?

There are several reasons:

I try not to use code that I am not sure will work with Firebird x (I had experience with Firebird 2.5 and used a driver from the internet — then Firebird 2.8 was released and the driver stopped working!). So slow and steady wins the race!

Node.js (single-threaded) uses one CPU core when running! Therefore, I use my own method of working with the Firebird database — instead of the node-firebird-driver-native driver, I use DSN ODBC for Firebird and call 'child_process' asynchronously each time, then run a function written and invoked with "cscript.exe". Windows automatically distributes processes across available CPU cores.

I have written two files for "cscript.exe". One for writing "MyComand.js", the other for retrieving data "MySelect.js". These files are written in Jscript for Windows, and they are included in the distribution in the root folder "My4S".

Example code:

Js:

```
let child_process = require('child_process');
let MyWscrComm, MyWscrSel;
bason = require(require('MyBasePath').idx(BasonPath));
MyWscrComm = "cscript.exe MyComand.js " + bason.DSN + ' ' + process;
MyWscrSel = "cscript.exe MySelect.js " + bason.DSN + ' ' + process;

let strExec = MyWscrComm + ' ' + CountLogs[mydbxx]++ + ' ' + mydbxx;
child_process.exec(strExec, () => { ... });
```

Optimization

Over time, I found that the child_process based architecture consumes a lot of server resources. Since the 8th release, I have refined the code and added new files:

MyCommand3.js and **MySelect3.js**

I left the old ones for compatibility. **They cannot be deleted!**

How the new scheme works:

When Node.exe starts, several MyComand3.js and MySelect3.js processes are created once (Each such process has its own unique number).

They remain active while Node.exe is running. Old processes, if they are still hanging, are automatically deleted.

At startup, each process connects to Firebird once. Then, at a certain interval (`WScript.Sleep`), it checks whether a special file has appeared in the `../qq/`. Each process has its own unique number, and Node passes files specifically to that process.

The number is determined by the global constant `CountProcessorCore` and the global counters `PrProcessorCore_s` (for **MySelect3**) and `PrProcessorCore_u` (for **MyCommand3**). The counter values always increase by one after use, within the range of `CountProcessorCore`.

Example for the file number in **MySelect3**:

NodeJs:

```
const slot = PrProcessorCore_s;
PrProcessorCore_s = (PrProcessorCore_s + 1) % CountProcessorCore;
const filePath = folder + "s" + slot;
```

where `folder` = `../qq/`. This way, the program sequentially loads all **MyComand3.js** and **MySelect3.js** processes with work.

CountProcessorCore constant

This constant determines how many MyComand3.js and MySelect3.js processes to create on Windows. The more processes, the faster the program works with Firebird.

But too much can be a problem.

Therefore, the value of the constant should be determined by system administrators, based on the capabilities of the server.

Recommendations:

For the My4S demo, first set the constant equal to the number of CPU cores.

Then you can experiment.

The program allows you to change the constant without restrictions, and it will take care of the stability of the work itself.

The minimum value is 2.

Constant EnterLocs_qq

May have two values: true – output files with logs of **MyComand3.js** and **MySelect3.js**, false – do not output log files to the folder “../qq/”.

Output of log files takes some time, therefore it is better to use this feature only at the beginning of system configuration.

Features of My4S.

After the release of Firebird 3.0 and above, the limits on database size (up to 128 TB) and tables (up to 64 TB) were significantly increased. Essentially, everything now depends only on the server’s capabilities.

Because of this, I decided to create only one table for documents, directories, information registers, and possibly others.

For clarity, let’s consider just one table — directories (CATS). But how can dozens or even hundreds of different directories such as nomenclature, contractors, etc. be placed into a single table? Each table has standard columns (id, id_n, name, actual, cod ...), and for all other columns we will use a blob (memo) field. All additional fields (columns) unique to each directory will be stored in a JSON string. I believe experienced programmers already understand my idea. NoSQL concepts have been around for a long time, and it is no coincidence that respected databases have begun to implement JSON.

To keep things consistent, all fields, names, and identifiers are written in English and limited to 31 characters.

Here is what we have:

id – a unique identifier of the table. Knowing the id, we can immediately access an element of any directory.

id_n – the name of the directory as defined in the Configurator (example: “contr”, “nomencil”, etc.).

name – the string of the directory element (“Gasoline A-95”, “Some Beer”, etc.), length defined in the Configurator.

cod – the string of the directory element (may contain barcode, office code, and other parameters separated by a delimiter such as a space or another symbol, length defined in the Configurator).

id_n + name and id_n + cod are paired indexes.

Almost the same applies to the information register (**REGS**), except instead of **cod** a date field is added for selecting periodic data.

With documents, everything is much more complex. We will use two linked tables: one for the header (**DOCS**) and another for the document rows (**ROWS_DOCS**).

Introduction to browser forms

Each table (directories, documents, information registers, etc.) will have a unified HTML template with fixed standard data, as well as a prepared HTML table (table) with a single row. For documents, two tables are provided: one for the document header (with a single row), and another for the tabular part (multi-row). This design eliminates the need for a form editor (IDE); it is sufficient to use a good HTML code editor (for example, Visual Studio Code).

Before opening a form, the template will be dynamically supplemented for each specific metadata object, using data recorded in blob fields or in JS files.

Database optimization

The program is designed to minimize database queries. Everything created in the Configurator is described by the properties of each metadata object and recorded into blob fields of the table. At the same time, this data is saved into a special JS file associated with the specific metadata. When opening a metadata form, the data is not loaded from the database but instead connected via SRC to this JS file. This file is updated each time the metadata is modified in the Configurator.

Such prepared JS files significantly reduce database queries, since the program works with preloaded data.

Capabilities of My4S

The My4S program is already prepared for creating ERP systems. For developing small applications such as family budget management or small warehouse accounting, deep knowledge of HTML (DOM) or programming languages is not even required — it is enough to study the My4S description.

The program supports:

- balance registers (simple and accounting, including the chart of accounts);
- cost write-off using the average method (FIFO and LIFO are not yet described — can be added independently);
- ready-made trial balance reports, both for balance registers and for accounting registers (with filters and saved settings);
- up to seven multi-row tables in a single document.

The Future of My4S

I've spent over 20 years as a programmer working with the Russian 1C7.7 and 1C8.x systems at companies across Ukraine. I'm trying to match what 1C8 can do — and to bring a fresh vision for building ERP systems that fits today's world. I hope this project will catch the interest of a community of programmer-dreamers who can help turn an "ugly duckling" into a "beautiful swan."

For now, I'm not trying to create finished products like Accounting, Trade Management (UTP), Manufacturing Enterprise Management (UPP), and the like. My goal is to build a convenient tool for creating that kind of software.

My4S is a flexible system that allows you to easily:

- refine existing modules and create new ones,
- create new objects and describe their properties,

- add new tables and functions to the database,
- modify old and develop new HTML templates.

Overall, My4S is a ready-made startup that lacks only one thing: for someone to believe in the program.

Database Recovery Mechanism

I have developed and successfully tested a mechanism for recovering the database after a critical failure. Its core purpose is to restore the database precisely to the point right before the crash.

Recovery Process:

1. **Transaction Logging:** Once a backup archive of the database is created, logging of all `UPDATE` and `INSERT` operations begins.
2. **Log File Storage:** All `UPDATE` and `INSERT` SQL blocks sent to the Firebird driver are written to files inside the `logs` folder (separately for each database if you run multiple databases on your machine).
3. **Restoration from Backup:** In the event of a failure, the database is first restored from the latest backup archive.
4. **Log Replay:** All stored files in the `logs` folder are then processed in a loop and sent to Firebird for execution, thereby restoring even the changes made within the Designer!

Attention: For now, I have not integrated this mechanism directly into the My4s interface. However, inside the `logs` folder, there is a `bec_res` directory containing the necessary files to restore the database. In these files, you need to properly configure the server file paths and set the correct password. Currently, this can only be done by experienced developers. Later, I will design a user-friendly solution (or perhaps you can suggest one!) to allow one-click database recovery directly within My4s.

Security Note

I am not a cybersecurity specialist, so I haven't specifically prioritized data protection at this stage. If the project proves successful, I hope experts will step in—either to build robust security solutions or to advise on how to implement them.

Currently, the only protection method I am familiar with is using **OpenVPN** with custom generated certificates. However, it is too early to worry about that now: for initial evaluation, you will be running the software locally on your own machine, which doesn't even require an internet connection.

AUTHORIZATION.

The image shows two side-by-side screenshots of a web browser displaying the My4S authorization interface. The browser's address bar shows the URL `127.0.0.1:1637/mydb/cf` on the left and `127.0.0.1:1637/mydb/db` on the right. The interface has a green background with the word "AUTHORIZATION:" in red. On the left, the "User:" field is a dropdown menu showing "Ворон А.", and the "Password:" field is a text input with masked characters. On the right, the "User:" field is a dropdown menu showing "demo", and the "Password:" field is a text input with masked characters. Both screenshots have a "Next >>" button at the bottom right.

Scr1


For entering the Configurator and the Enterprise, two different authorization approaches are used. To enter the configurator, data is taken from a JSON file for each database, if you do not have one “..\My4S\mydb\cf\Progv.us”:

```
"Prog1": [  
  "Voron A.",  
  "767a06140f52c4cd3f81c9124be765ba038f895644e6d08bb0157c8467b2317b",  
  ""  
],  
"Prog2": [  
  "Denis",  
  "a73317a3d07ff37fa0837338a29e0c9bd6f488b788be6e98bfcd30af9edaf43c",  
  ""  
]  
}
```

- **Prog1**—the main username displayed in the Enterprise.
- **"Voron A."** —representation, used exclusively for authorization.
- **The third element — a password encrypted using the Node.js 'crypto' module.**
- **The fourth element — not used yet, but may be useful in the future for configuring access rights.**

To change the password:

- Replace the encrypted string in the JSON file with a temporary password (no longer than five characters).
- Log in to the Configurator.
- Enter the new password in the window that appears and confirm it.



Scr2

The new password will be encrypted and written into the JSON file.

If everything went well, a tab with information will appear (otherwise ERROR):


The new password has been accepted. Close the tab and enter the program with the new password!

In the demo version, I have temporarily removed the six-character limit!

By default, the password for "Voron A." = "11", and for "Denis" = "22".

To enter the Enterprise, data is taken from the Firebird table “USERS”.

By default, the password for the user "demo" = "22". When entering the Enterprise database for the first time, the user field will be empty. You need to add a user with "ADD USERS". The user must know their name and type the suggested string, in this case "demo", then enter the password — and you are in the database! If you clear the browser history, you will need to add the user again. This is because user data will be stored not only in the "USERS" table, but also in the browser, so you don't have to go to the database every time!



ID	ACTUAL	NAME	ROL	PAS	REF	SETTINGS
847	✓	demo	(BLOB)	a73317a3d07ff37fa0837338a29e0c9bd6f488b788be6e98bfcd30af9edaf43c	(null)	(blob)
848	✓	user1	(BLOB)	767a06140f52c4cd3f81c9124be765ba038f895644e6d08bb0157c8467b2317b	(null)	(blob)

Scr3

For editing and adding new users in the Enterprise, there is an HTML form that is called from the “EditUsers” menu, both in the Configurator and in the Enterprise:

USER: Prog1

EDIT USERS:

User: user1 AddNew

848 ☒ ACTUAL NAME: user1 ROLES: zakupki

REF:

PASSW:

Save USERS

Scr4

Access rights management in the Enterprise

- Users with full rights ("all") can modify data but cannot modify other users with full rights.
- Programmers in the Configurator are the only ones who have the right to modify users with full rights.
- The chief accountant and their deputy can be granted full rights so as not to distract programmers when a new user needs to be added to the database.

Password change

1. Double-click in the "PASSW" field.
2. Enter a temporary password (no longer than five characters).
3. Save the changes by clicking "Save USERS".
4. To enter a new password, click "AddNew" and fill in all parameters.
5. Inform the user of the new password.
6. The user must log in with the temporary password, then enter and confirm the new one.
7. The new password will be known only to the user.

User linkage

In the REF field, it is planned to store the ID from the "Individuals" directory to link the user to a specific person.

Initial base (do not confuse with demo)

The initial database (my4sNull) is a database where there is still no metadata in the Enterprise in the CATS, CATS1, DOCS, REGS tables. In the Designer, I have already entered some data in the METADATA table, which I hope is necessary for proper work, especially for accounting. And then you yourself should know what to do - this is your program!

Attention! When entering the Configurator of the initial database for the first time, the password is "11". Then you must set your new password with at least six characters. In the Enterprise, at the beginning there will be no users (Users). You need to enter yourself and your password in the Configurator first!

Entering the Configurator.

After logging into the Configurator, the initial form will appear with the main menu on the left.

METADATA:

Configurator My4S(ver.4S=1.0.0) for the base mydb_en(ver.cf=1.0.8)

- METADATA
- Balance (Residual Registers)
- Cats (Directory)
- CATS1 (subordinate directories)
- DOCS (Documents)
- ID_DB: Base IDs//
- Processing
- Registers of information
- Rights (Roles)
- Reports
- MENU DB
- Assistant for writing additional reports
- EditUsers
- Firebird select

METADATA: ID_DB USER: Prog1

ADD NEW >>

Select ALL

NONE

NAME	PRESENTATION	ACTUAL
sumdoc	Amount of the document//number	✓
sumwithoutvat	Amount without VAT (sale)//number	✓
coef	Coefficient//number	✓
sumcost	Cost//number	✓
D_date	Date of the period//date	✓
contr_contract	Mandatory constant! Specifies the names of the directory of counterparties and their contracts//const	✓
name1	Other name//text	✓
price	Price//text	✓
prices_vat	Prices include VAT//checkbox	✓
kount	Quantity//number	✓
signcontr	Sign of the counterparty//select	✓

Scr5

METADATA table and menu structure

The METADATA table almost completely corresponds to the menu on the left, except for the last two items. It is precisely based on this table that the menu you see is formed.

Adding new objects

If you add a new metadata object, it will automatically appear in the menu on the left. However, for it to work fully, you will need to:

- Describe its properties and modules.
- If necessary, create new tables in Firebird.

For creating ERP programs almost everything necessary is already available. If additional functionality is required, it can be further developed!

Let us start by examining ID_DB.

METADATA: ID_DB USER: Prog1

ADD NEW >>

Select ALL

NONE

NAME	PRESENTATION	ACTUAL
sumdoc	Amount of //number	✓
sumwithoutvat	Amount wi //text	✓
coef	Coefficient//date	✓
sumcost	Cost//checkbox	✓
D_date	Date of the //select	✓
contr_contract	Mandatory //balans	✓
name1	Other name//const	✓
price	Price//const	✓
prices_vat	Prices include VAT//checkbox	✓
kount	Quantity//number	✓
signcontr	Sign of the counterparty//select	✓

Scr6

Main metadata identifiers

The program already provides predefined main identifiers (CATS, CATS1, DOCS, REGS, etc.), and it is better not to change them.

When creating a program, programmers can invent their own unique identifier names ("Name").

Restrictions on creating identifiers

- In large projects, different programmers may accidentally invent different identifiers for the same elements with identical properties.
- To avoid this, the use of new identifiers is only possible through the ID_DB table.
- If the required identifier is not there yet, it must be added.
- One may argue about the feasibility of such a solution, but I consider it the most practical.
- In the PRESENTATION column, after the description with //, the type of identifier is specified.
- Before each entry, you must select the type from the dropdown list.
- When saving, this type is automatically added to the line in PRESENTATION.

Additional properties of types date and select

A new property will appear: parameter. If necessary, new types can be added.

For date everything is obvious.

For select:

- You need to describe the dropdown HTML list as text (a replacement for enumeration).
- Each list element is separated by a vertical bar (|).
- Each element includes two parameters separated by a slash (/):
 1. The first — the parameter itself.
 2. The second — its representation.

You may notice that some types work like constants. Therefore, I do not have such metadata types as constants and enumerations!

Scr7

In Enterprise, when selecting from the drop-down list, it will look like this:

TABLES : Products										
ADD ROW (Alt+)			DELETE ROW (Alt-)							
#	Nomenclature	Quantity	Coefficient	Price	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan	✓
1	Gasoline-92	500	1	60	30000	2100	32100	7%	203 Fuel	
2	Gasoline-95	600	1	70	42000	2940	44940	20%	203 Fuel	
3	Oil M10G2K	210	1	35	7350	1470	8820	0%	203 Fuel	
4	Cognac "Napoleon"	1	1	200.0000	200	40	240	7%	281 Products in stock	
					79550	6550	86100	withoutVAT		

Scr8

Reserved constants.

contr_contract - Mandatory constant! Indicates the names of the directory of counterparties and their contracts are used in this database. In the parameter, use a comma to indicate how the directories are named counterparties and contracts. For example: contr,contract. This helps the program in some cases how to behave with these directories.

D_date - Closing date of the period. Documents cannot be corrected before this date!

BALANSE (Balance registers):

Balances in My4S and their support in Firebird

Balances can only be changed by documents. The Configurator provides mechanisms for creating movements of balance registers.

In Firebird, balance registers are supported by three tables:

BALANSOPT — stores unique combinations of dimensions for each balance register, each having a unique ID.

Example with nomenclature:

In all documents that modify a certain nomenclature, the same combinations of dimensions for each balance register are repeatedly used.

- To avoid storing these combinations in the database each time, they are replaced with unique IDs.
- This saves disk space and speeds up the system.



ID	ID_N	W1	W2	W3	W4	W5
795	contr_p_m	806	816			
797	contr_p_m	810	823			
804	account	828	790	777		
805	account	841				
836	corr_account	839				
837	corr_account	839	843			


Scr9

ID – unique identifier.

ID_N – the name of the balance register.

W1...W5 – IDs of directory elements (we have already agreed that IDs are unique for any directory). For example: W1 is the ID of the nomenclature, W2 is the ID of the warehouse, etc., depending on how you configure it in the Configurator!

BALANSDOC — this table stores all movements of balance registers across all documents. Each document may contain any number of rows. One row equals one movement, as configured in the Configurator. Using this table, we can obtain turnovers for any balance register.



ID_B	ID_DOCS	DAT	ACTUAL	DAT_BALANS	P_M	VV	V1	V2	V3	V4	V5	NUMROW	NUMTAB
797	929	1736642969961		202502		(BLOB)	-85860	0	0	0	0	0	0
811	929	1736642969961		202502		(BLOB)	6510	0	0	0	0	0	0
812	929	1736642969961		202502		(BLOB)	30000	500	0	0	0	1	1
841	929	1736642969961		202502		(BLOB)	30000	0	0	0	0	1	1
840	929	1736642969961		202502		(BLOB)	2100	0	0	0	0	1	1
832	929	1736642969961		202502		(BLOB)	7350	210	0	0	0	3	1
841	929	1736642969961		202502		(BLOB)	7350	0	0	0	0	3	1

Scr10

ID_B – stores the ID of a unique combination of dimensions from the BALANSOPT table.

ID_DOCS – ID of the related document.

DAT – document date. In My4S, the built-in Firebird DATE type is rarely used; instead, the date is stored as a large number (BIGINT) generated in JavaScript. All queries are formed in JavaScript modules, so there is no need to waste machine time converting dates between JavaScript and Firebird! However, in two tables, DOCS and REGS, the DATE type is still used in the DATEFB column (without time). This is needed for filtering by date periods (day, week, month, quarter ...). Firebird already has built-in functions for working with dates!

ACTUAL – flag indicating whether the movement is valid. If the document is marked invalid when saved, all movements linked to it also become invalid, and balances are reversed.

DAT_BALANS – 6 characters (year+month). Links the movement to a specific month and year.

P_M – indicates whether it is an inflow (true) or outflow (false).


VV – stores textual data used later, e.g., “act=Receipt of goods”.

V1...V5 – store resources, only NUMERIC type. Example: V1 is the movement amount, V2 is the quantity. Configured in the Configurator.

NUMROW – row number of the tabular section. If 0 – the document header.

NUMTAB – unique number of the tabular section for all movements of one document (up to 7 tabular sections).

BALANSE – this table stores balances at the beginning of each month, represented in the DAT_BALANS column.



DAT_BALANS	ID_B	P_M	V1	V2	V3	V4	V5	DOC
202503	847		403,36		0	0	0	0 (BLOB)
202503	823		-256	-3,2		0	0	0 (BLOB)
202503	824		-3,36	-0,028		0	0	0 (BLOB)
202504	793		-60225,6		0	0	0	0 (BLOB)
202504	795		-60225,6		0	0	0	0 (BLOB)

Scr11

Column types have already been described above, so I will not repeat them.

The beginning of the current month and the end of the previous month are essentially the same row in the table. If in the trial balance you set the period as the beginning and end of the month, the data will be quickly retrieved from this table row. However, if the start or end date (or both) fall between months, then to obtain balances for that date, the system will use the opening balance of the month plus the turnover from the BALANS-DOC table from the beginning of the month up to that date.

Important for accounting movements! The program does not support a direct link between debit and credit movements. Each movement exists independently, and the correctness and synchronization of movements are ensured by the programmer when describing movements in documents. When describing postings, simply record them in pairs — first debit, then credit (amounts with a minus sign) — and later reports will be able to calculate turnovers correctly! But these issues must be solved by programmers who will write the "Accounting for the country," while My4S allows you to build almost anything you want.

Database Truncation Mechanism as of a Specific Date

If a database has been in operation for years and has grown significantly, a need arises to reduce its size. In **My4s**, this is fairly easy to do.

The balance tracking mechanism is organized in such a way that deleting documents up to a month-aligned (discrete monthly) date does not affect final balances.

Note: There is no built-in document deletion mechanism in the My4s user interface. A document can only be set to **active** (actual) or **inactive**, which affects register postings during its write operation.

However, you can delete documents directly in the **Firebird** DBMS:

- Balances generated by documents will remain unchanged because they are stored in a separate table named `BALANSE`.
- You can also delete related documents in the `BALANSDOC` table up to the same date.

Security Features in Firebird

The Firebird database includes protection against accidental document deletion:

SQL:

```
ELSE IF (DELETING) THEN
BEGIN
    IF (OLD.actual) THEN
        UPDATE OR INSERT INTO DOCS(id, actual) VALUES (NULL, NULL); -- ERROR
END
```

Important when preparing for truncation: Keep this in mind: before deleting documents, you must **comment out** this check in the trigger, and once the database truncation is successfully completed — **restore it to its original state**.

And then do the standard becap/restore - check the remains and if everything is fine, then the database is truncated!

Form BALANSE

Now let us return to the menu and examine the work in the Configurator with the BALANSE (Balances) form.

METADATA: BALANSE **USER:** Prog1

© ADD NEW >> © Update ↺

NAME	PRESENTATION	ACTUAL
account	Bookkeeping Accounts	✓
contr_p_m	Ruins of pennies of counterparties	✓
corr_account	Correspondent accounts	✓

Scr12

Pay special attention to the first row: account – this is a reserved name for accounting balances. If you plan to keep track of balances by accounting accounts, this row must be present exactly as in the demo version (PRESENTATION – at your discretion).

Edit Metadata:> **USER:** Prog1 **SAVE BALANCE >>** **COPY NEW >>**

METADATA: BALANSE **NAME:** account **PRESENTATION:** Bookkeeping Accounts **ACTUAL:** ✓

ADD NEW ROW (+) **DELETE ROW (-)** **↓** **↑**

#	Type	Name	W_V	PRESENTATION	✓
1	CATS	accounts	w1	Account plan	■
2	number	sumdoc	v1	Amount of the document	■

Scr13

All other parameters will be automatically taken from the chart of accounts (Plan of accounts) — accounts (also a reserved identifier!).

I want to emphasize that in My4S there is no separate register for accounting and other balance registers. Everything works as a single system of three tables, as described above. Accounting balances differ only in that the first dimension (W1) is always a reference to the chart of accounts (Plan of accounts). In combination with the reserved identifiers account and accounts, the code itself determines how to handle accounting totals.

After that, you can create any number of simple balance registers, assigning them your own invented identifiers and describing all dimensions and resources according to the logic of your program.

Edit Metadata:> **USER:** Prog1 **SAVE BALANCE >>** **COPY NEW >>**

METADATA: BALANSE **NAME:** contr_p_m **PRESENTATION:** Ruins of pennies of counterparties **ACTUAL:** ✓

ADD NEW ROW (+) **DELETE ROW (-)** **↓** **↑**

#	Type	Name	W_V	PRESENTATION	✓
1	CATS	contr	w1	Counterparties	■
2	CATS1	contract	w2	Counterparty agreement	■
3	number	sumdoc	v1	Amount of the document	■

Scr14

Edit Metadata:> **USER:** Prog1 **SAVE BALANCE >>** **COPY NEW >>**

METADATA: BALANSE **NAME:** corr_account **PRESENTATION:** Correspondent accounts **ACTUAL:** ✓


ADD NEW ROW (+) **DELETE ROW (-)** **↓** **↑**

#	Type	Name	W_V	PRESENTATION	✓
1	CATS	accounts	w1	Account plan	■
2	CATS	accounts#1	w2	Account plan	■
3	number	sum1	v1	amount v1	■

Scr15

Why accounts and accounts#1.

You may wonder why accounts and accounts#1. This is another feature of mine. When in the Configurator you select a certain Type, you will see a ready-made list of identifiers for that type, and you will never see an identifier with the ending (#n). The reason is that this suffix (#n) is generated by the program itself. Before creating a new row, the program checks the Name of all rows for matches with the new identifier (ignoring the (#n) ending), and at the same time counts all matches. If necessary, the program will automatically append a new suffix to the identifier. Before doing so, it will issue a notification:



Scr16

This feature is used for searching in the Enterprise among different elements of directories (CATS) and more. Each cell of an HTML table has a text parameter called "title".

If you assign a value to it, when hovering the cursor over that cell, the "title" text will appear below it.

This parameter is filled by the program at the moment the table is populated on the fly, based on the data recorded in the Configurator.

The parameter will be written into cells where there is the possibility of selecting from a directory.


The string will look like: METADATA\id_n.

In the following example, "title" = "CATS\accounts#1".

w	vat	sumrow	✓
240	20% ▾	281 Products in stock ▾	☐
240		CATS\accounts#1	

Scr17

And now, when searching for an element in the directory, the program knows in which directory to look for this element. To do this, the program discards the suffix (#1) when searching in the database (Select ...) and in the filter you specify (WHERE).



Scr18

It returns a list of selected elements (no more than 50!) from which you choose the desired one, and if there is only one element, it will immediately be placed into the selection cell!

In the search line, you can enter several parameters separated by spaces.

Parameters are strings, and the elements selected will be those in which all occurrences of the search string are found.


The search is performed by the element name or by its code.

There is a special rule: if the first character is a digit, the search is performed by the "cod" parameter; otherwise, by "name"!

Example: "Beer Dark 0.5" — in the search line you can type "beer dar 5" and you will get the correct result.

For barcode search, simply scan it into the search line, and the search will then be performed by the "cod" parameter.

An approximate example of a selection string when filtering from the Nomenclature:



Working with the metadata configuration form.

Using the example of directories (CATS), let us examine how to work with forms.

METADATA: CATS **USER:** Prog1

© ADD NEW >> © Update ◁

NAME	PRESENTATION	ACTUAL
accounts	Account plan	✓
contr	Counterparties	✓
nomenc1	Nomenclature	✓
nomenc1group	Nomenclature groups	✓
store	Warehouses (Storage places)	✓

Scr20

Для начала редактирования какого-либо справочника – сделайте двойной щелчок на нем.

Покажем на номенклатуре:

Edit Metadata:> **USER:** Prog1 **ROLES:** zakupki,buh **SAVE METADATA >>** **COPY NEW >>**

METADATA: CATS **NAME:** nomenc1 **PRESENTATION:** Nomenclature **ACTUAL:** ✓

Select Form:

☒ TITLE ☐ CODE ☐ DESCRIPTION

ADD NEW ROW () **DELETE ROW ()** **u** **d**

#	In journal	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☐	select	vat	5	VAT(%)	☐	☐			☐
2	☒	select	typesnomenc1	8	Types of nomenclature	☐	☐			☐
3	☐	select	unit	8	Unit of measurement	☐	☐			☐
4	☐	text	name1	12	Other name	☐	☐			☐
5	☒	CATS	accounts	8	Account plan	☐	☐			☐

Scr21

Everything displayed in pink is closed for editing! Therefore, think carefully before creating any new objects.

Let me explain the “COPY NEW” button. When pressed, this form will be copied and created as a new form of metadata not yet saved in the database. In the “NAME” field, there will be a hint string “NEW METADATA!?”. You should replace it with the name of the metadata you have invented.

Everything marked in pink remains locked. However, you can delete a row and create a new one; with the new form you can experiment without consequences until you save it (SAVE). To delete rows, there is the “DELETE ROW()” button. By itself, pressing the button does nothing. You must indicate which rows to delete using the last column “checkbox,” where you mark the row(s) to be deleted, and then you can remove them. The checkbox is also used to move rows up or down with the corresponding buttons. But if you set two or more checkboxes, the move will not work!

Movement does not wrap around.

This is how it works in all forms of the Configurator and the Enterprise where there is a “checkbox” and the “COPY NEW” button!

Let us consider the Select Form: it contains radio buttons TITLE, CODE, DESCRIPTION. When I started, I thought of using all of them, but so far I have only needed TITLE. The others can be used to store some textual information in blob fields WW (CODE) and DESCRIPTION in the METADATA table.

TITLE, as you may have noticed, is an HTML table (table). Each row describes one column in the tabular part of the table, showing how it will appear in the Enterprise when you open the Nomenclature directory. The number of rows in the table equals the number of columns in the Enterprise. In my demo version it looks like this:

<< EDIT ELEMENT(CATS) >> **SAVE ELEMENT >>** **COPY NEW >>**

METADATA(NAME): Nomenclature* **USER:** demo* **ID:** 798* **GROUP:** (780)Fuel, lubricants and materials*

ELEMENT(name): Gasoline-92 **COD:** 92 **ACTUAL:** ✓

INFO:

Values (VV):

VAT(%)	Types of nomenclature	Unit of measurement	Other name	Account plan
7%	Fuel	kilograms	Gasoline-92	203 Fuel

Scr22

As I described earlier, what you see is an HTML template (ELEMENT.htm). The upper part is suitable for any directory, while the lower table will be defined in the Configurator to show how it looks for a specific directory. In this case, for the Nomenclature.

Let us return to the Configurator. Let us examine each column:


1. Sequential number
2. In journal – indicates whether to display information about the row in the journal. In the Enterprise, it will look like this:

#	ELEMENT (name)	COD	ACTUAL		Types of nomenclature Account plan
1	Gasoline-92	92	✓	☐	Fuel 203 Fuel
2	Gasoline-95	95	✓	☐	Fuel 203 Fuel
3	Gasoline-98	98	✓	☐	Fuel 203 Fuel
4	Oil M10G2K	10G	✓	☐	Fuel 203 Fuel

Scr23


3. Type – can only be changed when adding a new row using ADD NEW ROW ().

When you double-click (ondblclick) on the new row, a menu will appear in the center:



Scr24

3. Name – depending on the choice made in the first menu, another menu will appear. For example, if you select CATS, then a list of all directories will be displayed. cats0 – this is the transferred selection of the directory already in the Enterprise before starting the value selection.



Scr25

If you select CATS1 – this is a subordinate directory. It must always be paired with the main directory CATS.

First comes CATS and immediately after it CATS1, otherwise it will not work (e.g., Contractors, Contracts)!

If you select DOCS, then a list of all documents will appear.

Everything that comes after DOCS: text and further down the list – these are identifiers selected by type from the ID_DB table described earlier.

4. **Width %** – sets the width of the cell.

5. **Title** – the text of the table column header; if it does not fit, it will wrap inside the cell, expanding it vertically.

6. **Read only** – prohibits editing the cell content.

7. **Hidden** – determines whether the cell is visible.

8. **ADD Attributes** – you can additionally describe any attribute, except those listed above, according to HTML rules!

The full power of HTML is in your hands and knowledge. But as you can see, I have not yet needed to use this column's capabilities.

Quite a lot of what you can see in the demo version is recorded in the TabFix.css file, which you can also improve to your taste and style!

9. **Layers** – by default, all table forms stretch across the full width of the screen.

If there are few columns, this option is not needed.

When there are many columns, the browser will automatically adjust proportionally to the width you set (Width) so that all columns fit within the screen width.

In the Layers column, you write the name of the layer (just a string in any language).

If we want some columns to always be visible in every layer, we simply leave Layers empty.

The remaining columns are divided into layers, each with its own unique name (there can be several layers).

When the form is displayed in the Enterprise, a dropdown list of all layers will appear above the table on the left.

10. **Checkbox** – I have already explained earlier what it is used for.

Sets (Complects).

In My4S, a special subtype of directory called “Sets” is supported.

The indicator of a set in the Enterprise is the presence of opening and closing brackets “()” at the end of the directory element's name.

In the Configurator, a subordinate directory (CATS1) must be created and its columns defined.

#	In journal	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☒	CATS	nomenc	12	Nomenclature	☐	☐			☐
2	☒	number	kount	12	Quantity	☐	☐			☐

Scr26

And in the Enterprise:

#	ELEMENT (name)	COD	ACTUAL	✓	Types of nomenclature/Account plan
1	Cappuccino()	4	☒	☐	Set[2821 Products in separate trade (in ATT for sales)]
2	Mocaccino()	44	☒	☐	Set[2821 Products in separate trade (in ATT for sales)]

Scr27

VAT(%)	Types of nomenclature	Unit of measurement	Other name	Account plan
20%	Set	items	Cappuccino_Set	2821 Products in separate trade (ir...

And open the subordinate directory “OPEN Subordinate”:

#	ID_Name	ELEMENT (name)	ACTUAL	Nomenclature Quantity
1	kit	Milk substitute#	✓	Milk substitute 0.8
2	kit	Totti Supremo coffee#	✓	Totti Supremo coffee 0.007

Scr28

And then edit or create a new element:

Scr29

At the end of the name of each element of a set in the subordinate directory, you must place the “#” symbol.

Let us clarify for all ROLES elements in the Configurator – if it is empty, this means full access for all users in the Enterprise to this form!

Remember, everything marked in pink cannot be changed (Read only). But there is an exception for some form elements. Consider the ROLES element. Formally, it is indeed Read only and therefore marked in pink.

However, we still need the ability to assign user rights to the object, allowing certain users to modify it

(and let us not forget: a user with the “all” right has full access to all metadata objects without restrictions, so there is no need to specify this right again!).

To assign rights to an object, click on the ROLES element. A list of all rights entered in the “Rights (Роли)” menu will

open:

Scr30

If you need to correct or delete the list of already selected rights, click on Empty, and then click outside this small form – the list will be deleted!

Then click again on the ROLES element and, while holding down the Shift key, you can select several rights at once. After finishing the selection, click outside this small form – the ROLES field will display the list of selected rights separated by commas.

Almost everything described for directories (CATS) regarding working with forms will also apply to other forms in the Configurator.

Subordinate directory (CATS1).

It is the same as CATS, except for one special feature – the OWNER, which is the name of the directory to which it is subordinate.

#	In journal	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☒	CATS	accounts	12	Account plan	☒	☒			☒

Scr31

Information registers (REGS).

They are the same as CATS. For now, REGS differ from directories only in that, in the Enterprise, when creating an element you can set a date, and this automatically makes the information registers periodic!

In the Configurator:

Edit Metadata:> USER: Prog1 ROLES: zakupki SAVE METADATA >> COPY NEW >>

METADATA: REGS NAME: prices_regs PRESENTATION: Prices for goods (periodic) ACTUAL: ☒

Select Form:

☒ TITLE ☐ CODE ☐ DESCRIPTION

TITLE:

ADD NEW ROW (+) DELETE ROW (-) U D

#	In journal	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☒	CATS	nomenci	50	Nomenclature	☐	☐			☐
2	☒	text	price	12	Price	☐	☐			☐

Scr32

In the Enterprise:

<< EDIT ELEMENT(REGS) >> SAVE ELEMENT >>

METADATA(NAME): Prices for goods (periodic)* *USER: demo* *ID: 565*

DATE: 07.08.2026 T 21:41:46.000 ACTUAL: ☒

INFO:

Values (VV):

Nomenclature	Price
Visci Bells Original 0.2 l	124.4

Scr33

In the firebird:

REGS X							
Columns Constraints Indices Triggers Data Dependencies Source Grants							
+	Filter by SQL expression... Filter by						
-	ID	ACTUAL	ID_N	DAT	VV	WW	DATEFB
	565	☒	prices_regs	1733042222000	(BLOB)	(blob)	01.12.2024
	566	☒	prices_regs	1748540186000	(BLOB)	(blob)	29.05.2025

Scr34

Information registers are a separate object for storing data.
It is not possible to create a reference to them in metadata.
As you may have noticed, there is no such type in the Type selection!
Data can only be retrieved from Firebird by executing a (Select ...) query!

Documents (DOCS).

This is the most complex of the metadata objects. In addition to the header, it also has tabular sections (up to 7).

Documents describe all register movements.

It is possible to specify on the basis of which documents the current document is entered (IS THE BASIS FOR).

Edit Metadata:> USER: Prog1 ROLES: zakupki,buh SAVE METADATA >> COPY NEW >>

METADATA: DOCS NAME: receipt PRESENTATION: Receipt invoice ACTUAL: ☒ Debet_Credit: ☒

Select Form:

☒ TITLE ☐ TABLES ☐ MaketPrint ☐ DESCRIPTION

BALANCE: NONE

contr_p_m/true/w1=contr/w2=contract/v1=sumdoc/;

ADD NEW ROW () DELETE ROW () U D

#	In journal	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☒	CATS	contr	50	Counterparties	☐	☐			☐
2	☐	CATS1	contract	12	Counterparty agreement	☐	☐	data-r="accounts"		☐
3	☒	CATS	store	12	Warehouses (Storage pl	☐	☐			☐
4	☐	CATS	accounts	12	Account plan	☐	☐			☐
5	☐	number	sumvatdoc	7	The VAT amount of the t	☒	☐	value=0		☐
6	☒	number	sumdoc	8	Amount of the document	☒	☐	value=0		☐
7	☐	checkbox	prices_vat	4	Prices include VAT	☐	☐			☐

Scr35

Initial filling of tables, both in the header and in the tabular sections, is fully consistent with what was described above in CATS.

The only difference is that when filling tabular sections (TABLES), instead of the “In journal” column, a “tfoot” column appears.

This column specifies which columns in the Enterprise should be summed, and the total will be displayed in the bottom summary row.

Edit Metadata:> USER: Prog1 ROLES: zakupki,buh **SAVE METADATA >>** **COPY NEW >>**

METADATA: DOCS: NAME: receipt PRESENTATION: Receipt invoice ACTUAL: ☒ Debet_Credit: ☒

Select Form:
☐ TITLE ☒ TABLES ☐ MakePrint ☐ DESCRIPTION 1 2 **ADD TABLE >>**
 BALANCE: NONE account/true/w1=accounts#1/w2=nomenci/w3=store/v1=sumcost/v2=kount/vv=act=CMV+//;account/false/w1=accounts/w2=contr/w3=contrac

Name TABLE: Products **COPY** **PASTE**

ADD NEW ROW (+) **DELETE ROW (-)** **u** **n**

#	tfoot	Type	Name	Width %	Title	Read only	Hidden	ADD Attributes	Layers	✓
1	☐	CATS	nomenci	12	Nomenclature	☐	☐	data-r="vat,accounts"		☐
2	☐	number	kount	6	Quantity	☐	☐	value=1		☐
3	☐	number	coef	4	Coefficient	☐	☐	value=1		☐
4	☐	text	price	5	Price	☐	☐	value=0 style="text-align: center;"		☐
5	☒	number	sumcost	6	Cost	☐	☐	value=0		☐
6	☒	number	sumvat	7	VAT amount	☒	☐	value=0		☐
7	☒	number	sumrow	8	Total amount with taxes line	☒	☐	value=0		☐
8	☐	select	vat	5	VAT(%)	☐	☐			☐
9	☐	CATS	accounts#1	12	Account plan	☐	☐			☐

IS THE BASIS FOR: ☐

Scr36

In the Enterprise it will look like this:

<< EDIT DOCUMENT >> **SAVE DOC >>** **COPY NEW DOC >>**

Receipt invoice • USER: demo • ID: 853 •
 NumDoc: 000000000001 DateDOC: 03.09.2026 18:47:11.000 ACTUAL: ☒ PRINT >>

INFO:

Counterparties	Counterparty agreement	Warehouses (Storage places)	Account plan	The VAT amount of the document	Amount of the document	Prices include VAT
Serhly Rabko	Contr. #21 from 20.02	Head warehouse	631 Settlements with	6550,0000	86100,0000	☐

TABLES: Products **ADD ROW (Alt+)** **DELETE ROW (Alt-)** **u** **n**

#	Nomenclature	Quantity	Coefficient	Price	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan	✓
1	Gasoline-92	500	1	60	30000	2100	32100	7%	203 Fuel	☐
2	Gasoline-95	600	1	70	42000	2940	44940	7%	203 Fuel	☐
3	Oil M10G2K	210	1	35	7350	1470	8820	20%	203 Fuel	☐
4	Cognac "Napoleon"	1	1	200.0000	200	40	240	20%	281 Products in stock	☐
					79550	6550	86100			☐

Scr37

Back to the Configurator:

Debet_Credit: indicates whether the document is primarily incoming (Debet) or outgoing (Credit).

If the checkbox is selected – it is incoming; otherwise, it is outgoing.

Select Form: a switch between the parts of the document we are currently working with.

Each document has a header (TITLE) and tabular sections (TABLES).

The header is a mandatory element, while tabular tables may or may not exist!

MakePrint: this is a simple text area field. When creating a new document, it is empty.

It is recommended to fill it at the very end of editing the document, preferably after testing the document in the Enterprise.

When opening this form, you will see two buttons: “Generate print” and “View print”.

The first button generates a text-based print form of the document in pure HTML code.

The second button shows how this form will look in the browser (only the structure).

In our case, since there are two tabular sections, two templates will be shown.

..tbl..									
Counterparties: ..contr.. Counterparty agreement: ..contract.. Warehouses (Storage places): ..store.. Account plan: ..accounts..									
#	Nomenclature	Quantity	Coefficient	Price	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan
..#..	..nomencl..	..kount..	..coef..	..price..	..sumcost..	..sumvat..	..sumrow..	..vat..	..accounts#1..
						Cost: ..5..			
						VAT amount: ..6..			
						Total amount with taxes line: ..7..			
//TAB									
..txtt..									
Counterparties: ..contr.. Counterparty agreement: ..contract.. Warehouses (Storage places): ..store.. Account plan: ..accounts..									
#	Nomenclature	Quantity	Coefficient	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan	
..#..	..nomencl..	..kount..	..coef..	..sumcost..	..sumvat..	..sumrow..	..vat..	..accounts#1..	
						Cost: ..4..			
						VAT amount: ..5..			
						Total amount with taxes line: ..6..			

Scr38

In the Enterprise, based on this template, the print form will be generated, already filled with the document's data.

If the document has several tabular sections, the print form will be generated only for the table whose tab is currently selected!

Receipt invoice #0000000000001 * 2026-09-03 18:47:11.000(Products)									
Counterparties: Serhiy Rabko Counterparty agreement: Contr. #21 from 20.02.2022 Warehouses (Storage places): Head warehouse Account plan: 631 Settlements with domestic suppliers									
#	Nomenclature	Quantity	Coefficient	Price	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan
1	Gasoline-92	500	1.60		30000	2100	32100	7%	203 Fuel
2	Gasoline-95	600	1.70		42000	2940	44940	7%	203 Fuel
3	Oil M10G2K	210	1.35		7350	1470	8820	20%	203 Fuel
4	Cognac "Napoleon"	1	1.200.0000		200	40	240	20%	281 Products in stock
						Cost: 79550.00			
						VAT amount: 6550.00			
						Total amount with taxes line: 86100.00			

Scr39

Editing the textarea field

You can freely edit the text in the textarea field as you wish.

When saving the document in the Configurator, your changes will be recorded.

If the editing result does not satisfy you, you can cancel the changes by deleting all the text in the field (Ctrl+A → Delete),

then click the "Generate print" button – a new (initial) text will be automatically generated.

To return to editing the document, simply click on its title.

In the Configurator this will be "..txtt..", in the Enterprise system – "Incoming invoice ...".

Column "ADD Attributes"

Next to the parameter "Price" it says: value=0 style="text-align: center;".

For those familiar with HTML, this is obvious. For others: value — the default value set when opening the form.

style="text-align: center;" — defines alignment of the value in the center of the cell. This is part of the HTML standard, not a custom development.

Attribute data-r="vat,accounts"

This is my own enhancement – data-r is a reserved identifier.

In the Enterprise, when selecting a nomenclature in a row, the program checks if such an identifier (data-r) exists.

If it does, the program checks whether the nomenclature has identifiers (vat,accounts).

If found, the program remembers these values.

And if it finds the same identifiers in the document row, they will be automatically filled in!

They can, of course, be changed later. If this is not clear right away, you will understand in the demo version.

Tab "DESCRIPTION"

This is simply a textarea field where you can enter arbitrary text: Help, comments, hints, etc.

This text is not used anywhere except in this tab.

New (Excel)!

A new option has appeared to prepare templates (Layouts) using Excel.xlsx. Of course, a layout could also be prepared with HTML (by default in My4s, a simple report by tabular parts is created almost automatically, but that isn't always enough). However, the time required to prepare such a layout would be many times less than preparing such a report in Excel (for example, layouts like Tax Invoice, Goods and Transportation Invoices, and others)!


Now, let's understand how this works, at least for now, in the Designer. First, you must have Excel.xlsx installed. Start by creating a layout of how it should look when printed.

If a tabular part must be present, create the header and one row (already in the Enterprise; if there will be multiple rows in the tabular part, they will be written automatically as needed if the layout is prepared correctly). The layout will likely contain many cells that will be filled with data from the document at the moment of generating the print form. In these cells you should enter the names of the data identifiers from the document in the Designer and enclose them in double dots.

Example: `..contr..` (Name of the counterpart in the header "TITLE"). In the tabular part `..nomencl..` (Name of the nomenclature from "TABLES").

You set the cell styles yourself in the layout (color, font, left/right alignment, number/string, word wrap if it doesn't fit in the cell, and many others).

And one more very important thing. In the Excel template you must specify the row number where the tabular part begins (not the header!). To do this, place the cursor on the first column of the tabular part, in our case this is `..nomencl..`, and press Ctrl+F3. The Names Manager window will appear, and you click Create. The Create Name window will appear:



Scr39a

We must create the name as firstRow. It is very important to select the range (the correct range should already be set if you placed the cursor in the right place) or choose a new one by clicking the button on the right of the Range row. This range selection will allow, in the future, if you modify the template and add another row above the tabular part, the range will automatically shift by the required number of rows! As you can see from the screenshot, you can write anything in the cells, but only the part enclosed in double dots will be substituted.

If everything is filled correctly, the Enterprise program will generate the print form you need.

But that's not all! We must tell the program that we still have Excel templates. For this, go to MaketPrint and append at the end a line like: `//excel Print_EXCEL1//excel` If you should have two document templates: `//excel Print_EXCEL1//excel Print_EXCEL2//excel` If more than two, you can figure out the rest yourself! Instead of `Print_EXCEL1` you can write whatever you come up with; it will appear in the document print menu in the Enterprise:

Receipt invoice* • USER: demo* • ID: 853*
 NumDoc: 000000000001 DateDOC: 03.09.2026 T 18:47:11.000 ACTUAL: ☒ PRINT >>
 INFO:

Counterparties Counterparty agreement Storage Account plan The VAT amount of the document Amount of the document Prices include VAT
 Serhiy Rabko Contr. #21 from 20.02 631 Settlements with 6550,0000 86100,0000

TABLES: Products
 ADD ROW (Alt+) DELETE ROW (Alt-)


#	Nomenclature	Quantity	Coefficient	Price	Cost	VAT amount	Total amount with taxes line	VAT(%)	Account plan	✓
1	Gasoline-92	500	1	60	30000	2100	32100	7%	203 Fuel	☐
2	Gasoline-95	600	1	70	42000	2940	44940	7%	203 Fuel	☐
3	Oil M10G2K	210	1	35	7350	1470	8820	20%	203 Fuel	☐
4	Cognac "Napoleon"	1	1	200,0000	200	40	240	20%	281 Products in stock	☐
					79550	6550	86100			

Scr39b

Always, Excel templates should be named excel1.xlsx, excel2.xlsx, and so on. They will differ only by the number, in the order used for the menu:

//excel Print_EXCEL1//excel Print_EXCEL2//excel

Now, let's determine where to put the Excel template(s). These files must be copied to the folder that contains the document metadata, in our case the receipt folder, which at minimum must contain the file myXX.js.



Scr39c

Details about these folders are described later in the section **Internal database folders**.

Therefore, I won't repeat it here.

Because My4S is a web application, the browser currently cannot read Excel files. Therefore, the application on the fly saves the file as a PDF file with the same name but with the .pdf extension, and the browser can already read PDFs.

Description of register movements.

This stage is crucial in working with documents.

You should proceed to describing movements only after the document has been created in the Configurator.

In the header and tabular sections of the document, there is a BALANSE field with a dropdown list.

Next to it is a text field where lines describing register movements are automatically recorded (separated by ;;).

This field is visually highlighted and is not intended for direct editing.

However, by double-clicking on it, an additional textarea field will open, where all movements are displayed line by line.

This field can be edited manually — provided the rules for recording movements are followed.

Select Form:
 • TITLE • TABLES • MaketPrint • DESCRIPTION 1 2 ADD TABLE >>
 BALANSE: NONE account/true/w1=accounts#1/w2=nomencl/w3=store/v1=sumcost/v2=kount/vv=act=CMV+/,account/false/w1=accounts/w2=contr/w3=contract
 account/true/w1=accounts#1/w2=nomencl/w3=store/v1=sumcost/v2=kount/vv=act=CMV+;;
 account/false/w1=accounts/w2=contr/w3=contract/v1=sumcost/vv=act=Contr-;;
 account/true/w1=164321/w2=contr/w3=contract/v1=sumvat/vv=act=VAT+;;
 account/false/w1=accounts/w2=contr/w3=contract/v1=sumvat/vv=act=Contr-;;
 corr_account/true/w1=accounts#1/w2=accounts/v1=sumcost;;
 corr_account/true/w1=164321/w2=accounts/v1=sumvat;;


Scr40

To save the edited field, click on the non-editable field and a form will appear:

Повідомлення з 127.0.0.1:1637
 SAVE textarea?
 OK Скасувати

Scr41

If you click OK, the edited data will appear in the non-editable field as a single line separated by “;;”.




Now let’s see how this works:

Scr42


In the BALANCE dropdown list, a menu of all actions for forming movements is presented. If you click Empty, the non-edited line will be cleared, and it cannot be easily restored — you will have to fill in the register movements from scratch! Next, a full list of balance registers will be presented, as described in Metadata BALANCE.

Let’s start with the balance registers. Suppose you select contr p m. A window for entering values will appear:




Scr43

Here we must specify a single symbol +(Incoming) or –(Outgoing). If you enter any other symbol – it is an error! Then press Enter or OK, or if you want to cancel the action – press Esc or Cancel. If everything is correct, a new line will appear in the non-editable field (contr_p_m/false/w1=contr/w2=contract/v1=sumdoc;;) automatically generated by the program based on the Metadata BALANCE of the selected register:



Scr44


Based on this line, the program will automatically generate register movements when saving the document in the Enterprise. The number of such lines separated by “;;” determines how many register movements will be created for the given tab (TITLE or selected TABLES). Now let’s look at the movements for the register “account:BuhRakhunky (Accounting Accounts)”. Here there is a small



difference.

Scr45

First we also write “+” or “-”, but immediately after the symbol we write (without a space!) the score, along which the movement is expected to form. Data will be taken from the directory of accounts (In the Enterprise) to automatically generate a line, describing the movement account. Something like this:



Scr46

Уже выше я описывал, что значит accounts и accounts#1, повторяться не буду.

Но что касается движений регистров, уточню.

Когда программа при записи документа построчно читает строки в табличных частях, то одновременно она видит всю шапку документа,

но другие табличные части (если они есть) не видит.

Поэтому, если в шапке документа есть какой-то идентификатор, в данном случае accounts,

то accounts#1 (любой #n) может быть в каждой табличной части, и они никак не будут конкурировать.

В момент создания документа в Конструкторе программа сама позаботится, чтобы правильно расставить префиксы #n.

А вот при описании движений регистров программа может иногда неправильно расставить идентификаторы с #n.

Потому доверяй, но проверяй (штучный интеллект тоже ошибается!)

Вот для чего у вас есть возможность подкорректировать то, что создала программа.

А теперь разберём, что значит «!6432!».

Иногда мы можем наверняка знать бухгалтерский счёт для данного движения.

И тогда зачем забивать документ лишней колонкой со ссылкой на счёт?

Просто мы можем этот счёт прописать непосредственно в описании движений, обравив этот счёт восклицательными знаками.

Строка «act=ТМЦ+/-», здесь ТМЦ+(Приход) — краткое описание операции.

Я такое придумал, вы можете написать своё.

В Предприятии эта строка будет использована в печатной форме BALANSE, которая есть в каждом документе, и показывает все движения регистров остатков документа.

Receipt invoice #000000000001 * 2026-09-03 18:47:11.000

Bookkeeping Accounts(account)

w1/w2/w3/w4/w5	v1/v2/v3/v4/v5	ACT
203 Fuel / Gasoline-92 / Head warehouse	30000/500/0/0/0	CMV+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-30000/0/0/0/0	Contr-
6432 Tax liabilities are not confirmed / Serhiy Rabko / 301 Cash in national currency	2100/0/0/0/0	VAT+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-2100/0/0/0/0	Contr-
203 Fuel / Gasoline-95 / Head warehouse	42000/600/0/0/0	CMV+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-42000/0/0/0/0	Contr-
6432 Tax liabilities are not confirmed / Serhiy Rabko / 301 Cash in national currency	2940/0/0/0/0	VAT+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-2940/0/0/0/0	Contr-
203 Fuel / Oil M10G2K / Head warehouse	7350/210/0/0/0	CMV+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-7350/0/0/0/0	Contr-
6432 Tax liabilities are not confirmed / Serhiy Rabko / 301 Cash in national currency	1470/0/0/0/0	VAT+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-1470/0/0/0/0	Contr-
281 Products in stock / Cognac "Napoleon" / Head warehouse	200/1/0/0/0	CMV+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-200/0/0/0/0	Contr-
6432 Tax liabilities are not confirmed / Serhiy Rabko / 301 Cash in national currency	40/0/0/0/0	VAT+
631 Settlements with domestic suppliers / Serhiy Rabko / 301 Cash in national currency	-40/0/0/0/0	Contr-

Scr47

Correspondent accounts(contr_account)

w1/w2/w3/w4/w5	v1/v2/v3/v4/v5	ACT
203 Fuel / 631 Settlements with domestic suppliers	30000/0/0/0/0	
6432 Tax liabilities are not confirmed / 631 Settlements with domestic suppliers	2100/0/0/0/0	
203 Fuel / 631 Settlements with domestic suppliers	42000/0/0/0/0	
6432 Tax liabilities are not confirmed / 631 Settlements with domestic suppliers	2940/0/0/0/0	
203 Fuel / 631 Settlements with domestic suppliers	7350/0/0/0/0	
6432 Tax liabilities are not confirmed / 631 Settlements with domestic suppliers	1470/0/0/0/0	
281 Products in stock / 631 Settlements with domestic suppliers	200/0/0/0/0	
6432 Tax liabilities are not confirmed / 631 Settlements with domestic suppliers	40/0/0/0/0	

Ruins of pennies of counterparties(contr_p_m)

w1/w2/w3/w4/w5	v1/v2/v3/v4/v5	ACT
Serhiy Rabko / 301 Cash in national currency	86100/0/0/0/0	

Scr48

For now, AST works only for accounting.

Expenses are always marked with a minus sign, not only in the report but also in Firebird tables!

When collapsing (aggregating) the data, there is no need to manipulate or adjust.

🔧 Operation of the mechanism for creating a document based on another in the Enterprise system

Now let's describe how the "IS THE BASIS FOR" mechanism works.

I tried to automate this process as much as possible.

If we decide that another document should be created based on the one being edited,

we check the box after IS THE BASIS FOR: and a window will open with a list of all documents in the database.

Select one or several documents (using Shift), then close the checkbox,

and your selected document(s) will be placed into the text field:

IS THE BASIS FOR: ☒ receipt:Прибуткова накладна, spending:Видаткова накладна

Scr49

If you need to correct the data, click the checkbox and select the documents again.
At this point, your task in the Configurator will be finished.

Let me briefly explain how this is implemented and what role the programmer plays here.
If the structures of the source and new documents are similar (including matching identifiers), the system will automatically generate the document correctly.
You may only need to manually fill in one or two elements.
However, if the structures differ (for example, when creating a tax invoice), programmer intervention is required.
All necessary conditions are provided to ensure your work is efficient.

Document check on opening

When opening a document, the system checks whether it is created based on another document.
In `window.onload = function()`, the following code is used:

```
if (myForm.e_title.value === "BASIS") {  
    if (typeof MyFuncтBASIS == "function") {  
        MyFuncтBASIS();  
    } else doLoadDoc();  
}
```

The program checks whether such a function (MyFuncтBASIS) exists in the document's context.
By default, this function does not exist, and the program will attempt to create the document based on another as best as it can.

MyFuncтBASIS is a reserved function name.

Each object form has the ability to attach one or more modules, which will be included in the context of this object using SRC:

```
<script src="Myjsjs/DOCS/id_n_/my.js"></script>
```

my.js is entirely your function, and you are responsible for its correct operation.

Returning to the "based on" document: if your module contains the MyFuncтBASIS function, it will be executed,

and with its help you will manipulate the document at the moment of its loading

(for a proper understanding of how to handle this, look at how it works in the doLoadDoc function in the All_db.js module regarding "BASIS").

There will be more than one basic function like MyFuncтBASIS, which will allow you to manipulate the object both at the beginning of opening or saving, and at the end. I will describe this later.

If you get to know My4s better, you will be able to create such functions yourself and describe their processing (this is not a program where the main part is locked away in closed files like dll, exe, and others!).

About 4SON

Now it is time for me to confess that at the beginning I told you a small untruth about JSON in blob fields. If I had based the system on PostgreSQL, most likely it would have been true, but I used Firebird as the foundation, where built-in JSON support only appeared in version 5, while I started with version 3.

Therefore, I came up with my own method of storing data in blob fields and extracting it from there. It is a delimiter-based string. The thing is, putting JSON into a blob field is no problem (JSON.stringify), but retrieving data from it in a Select turned out to be quite problematic. I had to write a function similar to JSON.parse..

I even tried to do this after everything was already working with the delimiter string (me vs JSON!), and my function (Get_Blob) was already operational. But when I started writing my function (Get_JSON), I realized that the speed of retrieving data from JSON would be many times faster than from a delimiter string. And this function is used in all Select statements, and more than once!

So I decided to leave everything as it was, even though I understood that JSON would have been immediately clear to anyone reading this text, and I wouldn't have needed to explain anything, as I am trying to do now.

Here is a small example from the module text:

```
let strselect_ = "Select GET_BLOB(vv,'t_name') as acc, GET_BLOB(vv,'t_name_') as acc1 From MDMD WHERE id = " + select_one;

strselect_ = strselect_.replace("MDMD", t.title.split("|")[0]);

strselect_ = strselect_.replace("t_name", t_name).replace("t_name'", t_name');
```

If things are not yet fully clear (the example is taken out of context), the main point is to know that there is such a function in Firebird as **GET_BLOB(vv, 't_name')**. Here, vv is the blob field, and 't_name' is the name of the parameter in the string vv that we are searching for.

There can also be a third parameter – *separator*. If it is not provided, the default separator is used. In my case, the separator can consist of one to three arbitrary characters. For now, I have only needed three levels and, naturally, three separators.

```
const spr1 = "1~@", spr2 = "2~@", spr3 = "3~@";
```

The first "1~@" always goes by default!

Now let us move on to the description of the delimiter string – let us call it **4SON**. In the string, there can be multiple nested levels, each with its own delimiters. Here is the structure of **4SON** with two levels:

«name1=param1[=name11=param11spr2name12=param12spr2...|spr1name2=param2[=name21=param21spr2name22=param22spr2...|spr1...»

Do not be alarmed, everything will turn out to be much simpler! The main thing to understand is that there are **no spaces** at all. Parameters can contain any text, but the text cannot include a delimiter, and the text is not enclosed in quotes unless required by the content itself.

The type of the string (**string or number**) must already be known when writing a **Select**, or determined programmatically. If it is a number, then in the **Select** you will need to use the function **GET_BLOB4**, which returns a number.

I designed these delimiters so that the chance of them appearing naturally in the text would be minimal. In addition, the program in **Enterprise** strictly controls the text entered by operators to prevent the appearance of these delimiters!

To begin, let us look at a simple string with one level from the program:

«*nomencl=8001~@nomencl_3амінник молока1~@store#1=7771~@store#1_Головний склад1~@*»

Let me digress a little from the topic and explain what “**nomencl**” and “**nomencl_**” mean. The identifier without the final underscore (as named in the Configurator) is the **id of the directory** (remember – the id is unique for any directory, e.g. *nomencl=800*). The same identifier with an underscore at the end represents the **ready-made name of that directory element**. In some reports, this can significantly speed up the execution of a query (Select...).

Now let us return to **4SON** and continue. For example, let us take a string with simple single-character delimiters, which is located in the **blob field vv** with three levels:

*a=000aa=b1=111/b2=222/bb=c1=444&c2=555&/a1=333****

- The delimiter of the **first level** is “*”.
- In the **second level**, the delimiter is “/”.
- In the **third level**, the delimiter is “&”.

To obtain the string of the first level, it is simple: `GET_BLOB(vv, 'a', '*') = 000`

And in the same way we can get the string: `GET_BLOB(vv, 'a1', '*') = 333`

To obtain the second level, first we get the string in which the second level is located:

`GET_BLOB(vv, 'aa', '*') = b1=111/b2=222/bb=c1=444&c2=555&/`

Here we can get the string: `GET_BLOB(GET_BLOB(vv, 'aa', '*'), 'b2', '/') = 222`

And to obtain **c1** and **c2** (this is already the third level with the delimiter “&”), we first get the string “bb” in which the third level is located:

`GET_BLOB(GET_BLOB(GET_BLOB(vv, 'aa', '*'), 'bb', '/')) = c1=444&c2=555&/`

`GET_BLOB(GET_BLOB(GET_BLOB(GET_BLOB(vv, 'aa', '*'), 'bb', '/'), 'c1', '&')) = 444`
`GET_BLOB(GET_BLOB(GET_BLOB(GET_BLOB(vv, 'aa', '*'), 'bb', '/'), 'c2', '&')) = 555`

The same **GET_BLOB** function that exists in Firebird is also present in the main program written in **JavaScript**. Here is an example that clearly demonstrates everything I tried to explain a little earlier:

```
let vv = "a=000*aa=b1=111/b2=222/bb=c1=444&c2=555&/a1=333*";

let a = GET_BLOB(vv, 'a', '*'); //000

let a1 = GET_BLOB(vv, 'a1', '*'); //333

let aa = GET_BLOB(vv, 'aa', '*'); //b1=111/b2=222/bb=c1=444&c2=555&/

let b1 = GET_BLOB(aa, 'b1', '/'); //111

let b2 = GET_BLOB(aa, 'b2', '/'); //222

let bb = GET_BLOB(aa, 'bb', '/'); //c1=444&c2=555&

let c1 = GET_BLOB(bb, 'c1', '&'); //444

let c2 = GET_BLOB(bb, 'c2', '&'); //555

//А можно c2 получить одной строкой:
```

```
c2 = GET_BLOB(GET_BLOB(GET_BLOB(vv, 'aa', '*'), 'bb', '/'), 'c2', '&'); //555

//И даже так можно, если вы уверены, что 'bb=' один в строке

c2 = GET_BLOB(vv.split("bb=")[1], 'c2', '&'); //555
```

In fact, you do not need to know how **4SON** works, and the program will function correctly on its own. But I believe that programmers who wish to improve the program should understand it.

I fully realize that my program is still far from perfect. That is why I will be glad if someone helps me improve it, or at least enhances it for their own use.

Description of the Project File Structure in Node.js

Let us move on to the description of the files on which Node.js operates. All of them are located on the server (in the demo version – most likely on your computer) in the My4s folder. The location of this folder is chosen by you.

For now, we will skip the description of the files located in the root – some of them have already been mentioned, others will be considered later. Let us start with the folders:

 **.vscode** This folder contains the **launch.json** file, which specifies the path to **node.exe** when running the application through **Run** in **VSCode**. If Node.js is already installed on the server, everything will work correctly. If you are using only the **node.exe** file (for example, from the root of **My4s**), you need to uncomment the line:

```
"runtimeExecutable": "c:/My/My4s/node.exe",
```

and specify the full path to **node.exe**.

Example content of **launch.json**:

```
{

    // Используйте IntelliSense, чтобы узнать о возможных атрибутах.

    // Наведите указатель мыши, чтобы просмотреть описания существующих атрибутов.

    // Для получения дополнительной информации посетите:
    https://go.microsoft.com/fwlink/?linkid=830387

    "version": "0.2.0",

    "configurations": [

        {

            "type": "node",

            "request": "launch",

            "name": "Launch Program",

            // "runtimeExecutable": "c:/My/My4s/node.exe",

            "program": "${workspaceFolder}\\Start4s.js",

        }

    ]

}
```

```
}
```

📁 **MySnipp.code-snippets** – A very useful file that allows you to configure your own dropdown hints (**IntelliSense**) in **VSCode**.

📁 **cf** – Contains **.htm** file templates for working in the **Configurator**. 📁 **db** – **.htm** templates for working in **Enterprise**.

📁 **css** – **.css** styles. For now, only one file is used – **TabFix.css**. 📁 **js** – **.js** scripts connected in HTML files via **src**. Used only on the client side. 📁 **node_modules** – Contains **.js** modules used for routing. Used only on the server side.

📁 **qq** – An empty folder, but it is used for exchanging information between **Firebird** and **Node.js**.

All the folders and files listed above are **static**. They work with any database, and there can be several databases on the server.

Example of a connection string in the browser: **127.0.0.1:1637/mydb/cf**

Here, **mydb** is the name of the database being connected to. It must match the name of the folder inside **My4s**. In my case, it is **mydb**, but you can set your own name.

📁 Database Folder Structure

📄 **MyBase.json** – Located in the root of the database folder. It contains the main settings.

```
{
  "version_cf": "1.0.8",
  "name": "mydb_en",
  "DSN": "mydb_en",
  "FDB": "C:/fb/db4s_en/MYDB_EN.FDB",
  "FBK": "C:/fb/db4s_en/MYDB_EN.FBK",
  "FB": "'c:/Program Files/Firebird/Firebird_3_0/'"
}
```

At the moment, only **"version_cf"** and **"DSN"** are used. The other parameters are reserved for the future.

📄 *Automatically Generated .js Files

When metadata is saved in the **Configurator**, the program automatically creates or overwrites **.js** files. These files contain ready-made **SELECT... (Ajax)** queries and are connected to HTML forms using **src**.

These files are stored on the **client side**, which significantly speeds up working with the database.

```
<script src="Mydbdb/BalansXX.js"></script>

<script src="Mydbdb/AccountXX.js"></script>

<script src="Mydbdb/ID_DBXX.js"></script>
```

📁 Internal Database Folders

📁 **cf folder** – **.htm** templates and other files for working in the **Configurator**.


📄 **Progv.us** – A **JSON** file with user settings for the **Configurator**. Already described above. 📄 **Pass.htm** and **Pass2.htm** – Templates for entering and confirming a password. Universal for any database, but can be adapted if desired.

■ **index.js** – The routing file. Suitable for any database. ■ **Conf4S.htm** – The main form opened in the browser. A universal form for all databases.

■ **db folder** – **.htm** templates and other files for working in **Enterprise**. All files in the root of this folder are suitable for working with any database.


Now let us examine the

■ **Myjsjs** folder. All data in this folder is generated automatically when working with metadata in the **Configurator**. The folder is multi-level. First come all the main metadata:



Scr50

And inside each folder there are subfolders named after all the metadata identifiers subordinate to the main folder. For now, let us look at one example: **DOCS**.



Scr51

The folder names correspond to my demo version of the database (**mydb**). In your database, they may be different! In each such folder, there will always be one file with the same name **myXX.js**. This file always contains a single line: **xml_trXX**=[77,68,61,68,79,67,83,47...] It is generated automatically, and you should not attempt to modify it!

If you accidentally change this file and the metadata stops loading correctly, you need to go into the **Configurator**, open the form where the metadata is described, toggle the **ACTUAL** checkbox on and off, and then save (**Save**) again. The file will be restored.

The variable **xml_trXX** stores ready-made data as if obtained from the database via **SELECT... (Ajax)**. The numbers separated by commas are character codes in the **Firebird** database encoding (in my demo it is *windows-1251*). After that, there is a function for re-encoding into **UTF-8** – **loadXMLString(xml_trXX)**.

Using this data, when the form is opened, the **.htm template** will be dynamically appended, and only then can the template be filled with data. This works the same way as I described for the **.js files** in the root of the database folder. The difference is that this file is strictly tied to the metadata.

In the same folder, you can also place **js modules** in which you add the required functionality for working with this metadata without breaking the initial settings. These file(s) will be connected to the metadata template using **src**.

How src Works for Me It is time to explain how **src** works in my setup. I will show this using the example of the template file **DOCS_db.htm**:

```
<script src="Blob.js"></script>
<script src="All_db.js"></script>
<script src="Find4s.js"></script>
<script src="Formuls.js"></script>
<script src="print.js"></script>
<script src="Myjsjs/DOCS/id_n_/myXX.js"></script>
<script src="Mydbdb/BalansXX.js"></script>
```

```
<script src="Mydbdb/AccountXX.js"></script>
<script src="Mydbdb/ID_DBXX.js"></script>
<script src="Myjsjs/DOCS/id_n__/my.js"></script>
```

The program is configured to correctly recognize routes to **src** files. I use three types of **src connections**:

1. **Direct reference to a .js file name.** The program always searches in the  **js** folder.
2. **Searching for a file in the folder of a specific metadata.** Example:
src="Myjsjs/DOCS/id_n__/myXX.js". Since the template is used for multiple metadata, it is necessary to specify where to look for the **.js** file. Therefore, the **id_n__** **marker** is used. When preparing to send the form from the server to the client, the name of the required metadata identifier will be substituted here. In this way, you can connect not only the **myXX.js** file but also any other file located in this folder (possibly written by you). Example: <script src="Myjsjs/DOCS/id_n__/my.js"></script>.
3. **Connecting files located in the root folder of the database you are currently working with.** Example: <script src="Mydbdb/BalansXX.js"></script>. Here, **Mydbdb** is also a marker, which will be replaced with the name of the database.

As you can see, for each type of connection, you can place your own files in these folders and then use them when working with the given form.

□ Very important information! When connecting these files, identical function names may be repeated. When such a function is called in the program code, the one that is located **lower in the src connection order** will be executed!

Experienced programmers already understand the idea. For beginners, let me explain: suppose you already have a program written by someone else, but you want to tweak something in it without breaking your code during updates. You write your own function in the **My.js** module, or copy a function from another module that you want to modify, and then connect your module in **src** last!

Summary:

- In the  **js** folder, I recommend placing your modules that will be used in multiple HTML forms.
- For modules tied to a single metadata, place them in the folder of that metadata, where the **myXX.js** file already exists.

Report in My4s

Turnover Balance Sheet

The **Turnover Balance Sheet** is a universal report for all balance registers. It does not require configuration in the **Configurator**, as it is already built into the **Enterprise** system and automatically adapts to the parameters of each register.

 Update METADATA: BALANCE USER: demo			
#	NAME	PRESENTATION	ACTUAL
1	account	Bookkeeping Accounts	✓
2	contr_p_m	Ruins of pennies of counterparties	✓
3	corr_account	Correspondent accounts	✓

Register Selection

The list displays all balance registers available in the database. For example, let us open the report for the **contr_p_m** register with a double-click.

RUN BALANCE >>

BALANCE NAME: Ruins of pennies of counterparties

DATE BETWEEN: 01.08.2026 30.09.2026

Settings:

NONE AddNew Save Delete OpenSetting

↓ ↑

#	Choice	Dimension:Name	Wn	✓
1	☒	Counterparties	w1	☐
2	☒	Counterparty agreement	w2	☐

Amount of the document :v1 ☒ 0.0000

ADD NEW ROW (Alt+) DELETE ROW (Alt-)

Choice	Wn_Vn	Comparison operators	VALUE	✓
--------	-------	----------------------	-------	---

Scr53

Main Parameters

- **DATE BETWEEN** — specifies the start and end dates of the period.
- **Settings** — manages saving and loading of report settings (to be discussed below).

Top Table: Dimensions

- Displays all dimensions configured in the **Configurator**.
- The **Choice checkbox** — includes the dimension in the report.
- The last checkbox — allows changing the order of dimensions, affecting the hierarchy of the report (upper ones are primary, lower ones are subordinate).

Resources and Formatting

- Below is a list of resources with checkboxes.
- You can set the number of decimal places (rounding if necessary).

Amount of the document : v1 ☒ 0.0000 ☐

Choice

0.0000

0.00

0.000

0.000000

0.00000

Scr54

Bottom Table: Filters

- Contains condition rows. The report will include only those records that meet all rows (**AND logic**).
- **Choice** — enables the row in the filter plan.
- **Wn_Vn** — a dropdown list of all dimensions and resources.

- **Subordinate directories** (for example, *Contracts*) are not yet supported in filters.

Choice	Wn_Vn	Comparison operators
☐	NONE	=
	NONE	
	Counterparties	
	Amount of the document	

Scr55

Examples of Working with Filters

✦ **Filter by Dimensions** (for example, *Counterparties*):

- **Comparison operators:**
 - = — one counterparty.
 - <> — exclude one.
 - **In(** — select a list of counterparties.
 - <>**In(** — exclude a list.
- **VALUE** — cannot be edited directly. A double-click opens the **FIND** window for selection.

ADD NEW ROW (Alt+)		DELETE ROW (Alt-)	
Choice	Wn_Vn	Comparison operators	VALUE
☒	Counterparties	In(	BestTrade,Serhly Rabko,Tolokin Mykola PP

Scr56

To clarify, in the **VALUE** column the names of counterparties will be displayed (separated by commas), but only their unique **IDs**, stored in the **TITLE** of the cell, will be included in the query. You can see them (although it is not necessary to know this) by hovering the cursor over the cell — for example: **806, 810, 808**. This works the same way with any directory! In this example, we have only one resource, but in other registers there may be more (up to five), and for each one you can create a filter by adding a new row (**ADD NEW ROW (Alt+)**).

Now let us look at how to work with **filters by resources**. Suppose we select the resource “*Document Amount*”, then in the **Comparison operators** column we will get a different list.

=
<>
>
<
>=
<=
In(
<>In(

Scr57

To remind you, in **My4s** resources are numbers. **VALUE** is a string that can be edited, which in the simplest case means entering a number.

- If you want to cut out a numeric range, enter in one row ">" **number**, and then add another filter row with "<" **number**.
- If you use **In(** — write several numbers separated by commas (the decimal separator is always a dot).

If this is unclear, you will understand once you have at least my demo version.

But that is not all: for resource filters there is also the option to filter by **turnover** — simply enter a number, and the filter will apply only to the **end-begin** turnover column.

- If you want to filter by the **beginning of the period**, put the Latin letter **b** before the number — for example: **b250.75**.
- If you want to filter by the **end of the period**, put the Latin letter **e** before the number — for example: **e-28550.968** (a number less than zero!).

□ Always use the minus sign if the number is negative.

Here is an example of a report with filters: (*example remains in original form*)

And here is an example of the printed report form with filters:

Ruins of pennies of counterparties			
DATE BETWEEN: 2026-08-01 00:00:00 2026-09-30 23:59:59.999 Counterparties In(BestTrade.Serhiy Rabko,Tolokin Mykola PP			
Counterparties / Counterparty agreement	Amount of the document		
	begin	end begin	end
BestTrade	0	524945.6000	524945.6000
902 Compliance with products sold	0	100480.0000	100480.0000
Contr. #259 from 20.10.2020	0	324465.6000	324465.6000
Mocaccino()	0	100000.0000	100000.0000
Serhiy Rabko	0	771960.0000	771960.0000
301 Cash in national currency	0	686100.0000	686100.0000
64 Calculations for taxes and payments	0	85860.0000	85860.0000
Tolokin Mykola PP	0	884432.0000	884432.0000
Contr. #124 from 24.03.2022	0	884432.0000	884432.0000
TOTAL	0	2181337.6000	2181337.6000

Scr58

Take note of the dark row: **0 / 83760.0000** — the point is that in the **end-begin turnover column** not only the turnover is stored, but also hidden values (not printed, but viewable on the computer). Again, by using **TITLE** when hovering the cursor over the desired number, you will see two values separated by a slash.

- The first number is the **incoming (DEBIT)** for this row during the selected period.
- The second number is the **outgoing (CREDIT)**.

The key point is that you can also create filters based on these numbers!

- Simply put the Latin letter **d** before the number if you need the incoming (**DEBIT**, e.g. *d0*).
- Use **c** before the number for the outgoing (**CREDIT**, e.g. *c83760*).

All reports in **My4s** support **turnover breakdowns**. If you double-click on a turnover (**end-begin**), a list of all documents that contributed to this figure during the selected period will open.

METADATA: DOCS USER:demo DOCUMENT: AllDOCS			
#	DOCUMENT	ACT.	INFORMATION
1	Receipt invoice #0000000000006 * 2026-09-28 14:40:43.000	✓	BestTrade Head warehouse 480.0000
2	Operation #0000000000001 * 2026-08-31 08:24:09.000	✓	

Scr59

After that, there is the option to **double-click on a document** to open it, and you can even edit it, save it, and then re-run the report.

Now let us describe how **Settings** works.

Settings:

NONE ▾

AddNew

Save

Delete

OpenSetting

Scr60

When you create a filter and want to save it for future use, this is where **Settings** comes in handy. Click **AddNew** — a window will open.

Enter a name for the setting!
Введіть назву налаштування!

AddNewNameSetting1

OK Скасувати

Scr61

Enter the name of your setting. It will appear in the dropdown list. Next, click **Save**. The data will be written into the Firebird table **SETTING_ALL**.

MD	ID_N	USERS	NAME	ACTUAL	WV
QUERY	account	demo	281	✓	(BLOB)
QUERY	account	demo	631	✓	(BLOB)
QUERY	account	demo	2821	✓	(BLOB)
Reports	tovar	demo	rr	✓	(BLOB)
Reports	tovar	demo	ww	✓	(BLOB)
Reports	cats_nomencl	demo	kount	✓	(BLOB)
Reports	cats_nomencl	demo	count	✓	(BLOB)
Reports	cats_nomencl	demo	Контрагент	✓	(BLOB)
query	prov1	demo	contr	✓	(BLOB)
QUERY	contr_p_m	demo	contr	✓	(BLOB)
query_fast	prov3	demo	contr	✓	(BLOB)
query_fast	prov5	demo	formul-	✓	(BLOB)
QUERY	contr_p_m	demo	ПримерКонтр	✓	(BLOB)

Scr62

When you open the **Turnover Balance Sheet** report again, you can select your saved setting from the dropdown list by name. All configurations you have saved will be displayed. If you need to make changes, simply click **Save** again, and the updated setting will be stored.

📁 How Settings Are Saved

It is important to understand: when you click **Save**, the settings are stored not only in the **Firebird** database but also locally in the browser (via **localStorage**). The report primarily works with data from the browser. You may have already noticed that I try to minimize database queries — all to ensure the system can comfortably serve not just dozens but thousands of clients simultaneously (and ideally even more!).

❑ Browser Cleanup and Restoring Settings


Sometimes the browser needs to be cleaned, and then your local **Settings** disappear. But we save them in the database for a reason! To restore them, there is the **OpenSetting** button — after clicking it, all your settings will be loaded from the database and written back into the browser cache. The **OpenSetting** button will be hidden if the settings are already present in the browser.

📁 Universality of Settings

Settings are available in all reports created in **My4s** and work almost identically. Therefore, I will not describe them further.

Report Created in the Configurator

In the **Configurator**, open the menu — **Reports** :



METADATA: Reports USER: Prog1

© ADD NEW >> © Update U

NAME	PRESENTATION	ACTUAL
cats_nomencl	Nomenclature//Handbooks	✓
tovar	Products	✓

Scr63

Here you can see the reports created through the **Reports** menu. To create a new one, click **ADDNEW**. All reports are generated based on the combination of several tables using **UNION**. The use of **JOIN** is also possible, but in that case the SQL query (**SELECT...**) must be manually refined. At the core lies the **DOCS.htm** document creation form, adapted for reports. At present, up to **seven table parts** are supported. The number of table parts corresponds to the number of **UNION** operations in the query plus one.

Ось переклад цього блоку англійською у «чистому» форматі з виділенням ключових термінів:

Creating a New Report

When creating a new report, you need to specify:

- **NAME** — a unique name for the report (note: after saving, changing it will be difficult).
- **PRESENTATION** — the display name.

Next, in the **TITLE** field, select the required **Firebird tables** from the **TABLES** list — as many times as needed to form the **UNION** query. After each selection, a line of the following type is automatically added to the **textarea**:

```
SELECT * FROM DOCS2 WHERE ID_N='idd__' AND DAT BETWEEN dat8_ AND dat9_ AND 1=1;;
```

After choosing a table, an additional dropdown list with possible **ID_N** values will appear — this is needed to specify which document to work with (relevant for the **DOCS** and **DOCS2** tables).

In words, this may sound complicated, but when running the demo version everything becomes clear and visual. The system works automatically — the main thing is to correctly select the parameters.

Let us consider creating a report using the example of the already prepared report “**товар**”.

If you are not familiar with the principle of **UNION** in SQL, I recommend first reviewing the documentation — preferably for **Firebird**, although in other DBMS the mechanism works in a similar way.

The report is generated only for the following documents:


- **Incoming Invoice**
- **Transfer**
- **Retail Trade**

Special note: the **Transfer** document is used twice, since it contains two warehouses — the source and the recipient.

With each document selection, initial **SELECT queries** are added to the **textarea**, separated by the symbols “**;;**”. At the same time, table templates are automatically created — still empty, but ready to be filled.



Scr64



Scr64a

As I mentioned earlier, **DOCS2** is a **VIEW** that combines two Firebird tables into one (**DOCS** and **ROWS_DOCS**).

Now, when you switch to the **TABLES** tab, you will see table **No. 1 out of 4** already filled. But this is actually a ready-made query — fully prepared for saving. In reality, the table will initially be empty.

Edit Metadata:>

USER: Prog1

ROLES: zakupki.buh

SAVE METADATA >>

COPY NEW >>

METADATA: Reports
NAME: tovar
PRESENTATION: Products
ACTUAL: ☒

Select Form:

TITLE

TABLES

MarketPrint

DESCRIPTION

1

2

3

4

ADD TABLE >>

Name TABLE: DOCS2__receipt

COPY

PASTE

ADD NEW ROW (+)

DELETE ROW (-)

13	Numb.	Name	VV_TAB	Width %	Title	Same	Hidden	ADD Attributes	AS	✓
1	☐	VV	store	4	Ширина комірки	☐	☐		store	☐
2	☐	TAB	nomenci	40	номенклатура	☐	☐		nomenci	☐
3	☐	TAB	price	10	price	☐	☐	Inumber!	price	☐
4	☒	TAB	kount	10	Count(+)	☐	☐		kount	☐
5	☒			10	Count(-)	☒	☐		kount1	☐
6	☒	Formul	formul1	10	Count(+)	☐	☐		(kount-kount1)	☐
7	☒	TAB	sumrow	10	Sum(+)	☐	☐		sumrow	☐
8	☒			10	Sum(-)	☒	☐		sumrow1	☐
9	☒	Formul	formul2	10	Sum(+)	☐	☐		(sumrow-sumrow1)	☐
10	☒	TAB	sumvat	10	VAT(+)	☐	☐		sumvat	☐
11	☒			10	VAT(-)	☒	☐		sumvat1	☐

Scr65

General Principles of Report Configuration

- **DOCS2__receipt** — this is the table name automatically generated by the program. You can change it, but it will not affect the operation of the report.
- Before filling the tables, it is important to plan the structure of the query in advance.

• **Table No. 1** is considered the main one — all others are adjusted to it. • The number of rows in all tables is always the same. • **Dimensions** go first, and the **Width** parameter is taken from the first row. Other dimensions (not resources) do not affect Width. • In the **Numb** column, you must check the box for all resources.

Working with the AS Column

The **AS** column is used similarly to the SQL query **SELECT ... AS ...**. It is filled automatically, but you can change it if necessary — in some cases this is even required.

Adding a New Row When adding a new row, always start with the **Name** field. In the dropdown list, the first two parameters are standard:

- **Empty** — means that the parameter is absent in the current table but exists in at least one of the others. All other fields (except **Name** and **VV_TAB**) must still be filled in.
- **Formul** — indicates that a formula will be used in the column. In the window that appears, you must specify the formula name. All formulas are defined in **Table No. 1**.

For formulas, the **AS** column has special significance — it is the formula itself. Inside the parentheses, use identifiers from other **AS** rows.

Parameters Name, VV, and TAB

- All other parameters in **Name** are taken from the structure of the corresponding Firebird table.
- Special attention should be paid to the parameters **VV** and **TAB** (at least one is always present). These are **BLOB fields** containing information in the **4SON format** (described earlier).
- When such a parameter is selected, the **VV_TAB** column becomes active, allowing you to choose specific parameters from the BLOB field.

Language and Formatting

- All fields must be filled in using Latin characters, except for the **Title** column — here you can use arbitrary text.
- The **ADD Attributes** column is not used, as described earlier. It is simply a string intended for additional settings when executing the report.

Example of Use

- If a dimension contains not a reference to a directory but a regular number (for example, *price*), you must tell the program that this is a number.
- To do this, in the **ADD Attributes** column write: "**!number!**".
- Without this string, the report will work, but filtering by price will not be possible.

Other Notes

- A checkmark in the **Same** column means that the parameter will be placed in the same cell as the previous one (above) — i.e., in two levels (layers).
- For other tables, the main task is to configure and link rows with **Table No. 1** in the **Name** and **VV_TAB** columns. If there is no link, select **Empty**.
- The remaining columns do not play a role, regardless of what is written in them.

Select Form:

☐ TITLE ☒ TABLES ☐ MaketPrint ☐ DESCRIPTION

1 2 3 4 ADD TABLE >>>

Name TABLE: DOCS2_moves COPY PASTE DELETE TABLE

ADD NEW ROW (+) DELETE ROW (-)

13	Numb.	Name	VV_TAB	Width %	Title	Same	Hidden	ADD Attributes	AS	✓
1	☐	TAB	store#1	50		☐	☐		store	☐
2	☐	TAB	nomenci	50		☐	☐		nomenci	☐
3	☐			10		☐	☐			☐
4	☐	TAB	kount	10		☐	☐		kount	☐
5	☐			10		☐	☐			☐
6	☐			10		☐	☐			☐
7	☐			10		☐	☐			☐
8	☐			10		☐	☐			☐
9	☐			10		☐	☐			☐
10	☐			10		☐	☐			☐
11	☐			10		☐	☐			☐

Scr66

Select Form:

☐ TITLE ☒ TABLES ☐ MaketPrint ☐ DESCRIPTION

1 2 3 4 ADD TABLE >>>

Name TABLE: DOCS2_moves COPY PASTE DELETE TABLE

ADD NEW ROW (+) DELETE ROW (-)

13	Numb.	Name	VV_TAB	Width %	Title	Same	Hidden	ADD Attributes	AS	✓
1	☐	VV	store			☐	☐		store	☐
2	☐	TAB	nomenci			☐	☐		nomenci	☐
3	☐					☐	☐			☐
4	☐	TAB	kount			☐	☐		kount	☐
5	☐					☐	☐			☐
6	☐					☐	☐			☐
7	☐					☐	☐			☐
8	☐					☐	☐			☐
9	☐					☐	☐			☐
10	☐					☐	☐			☐
11	☐					☐	☐			☐

Scr67

Select Form:

☐ TITLE ☒ TABLES ☐ MaketPrint ☐ DESCRIPTION

1 2 3 4 ADD TABLE >>>

Name TABLE: DOCS2_retail COPY PASTE DELETE TABLE

ADD NEW ROW (+) DELETE ROW (-)

13	Numb.	Name	VV_TAB	Width %	Title	Same	Hidden	ADD Attributes	AS	✓
1	☐	VV	store	50		☐	☐		store	☐
2	☐	TAB	nomenci	50		☐	☐		nomenci	☐
3	☐	TAB	price	10		☐	☐		price	☐
4	☐			10		☐	☐			☐
5	☐	TAB	kount	10		☐	☐		kount	☐
6	☐			10		☐	☐			☐
7	☐			10		☐	☐			☐
8	☐	TAB	sumrow	10		☐	☐		sumrow	☐
9	☐			10		☐	☐			☐
10	☐			10		☐	☐			☐
11	☐	TAB	sumvat	10		☐	☐		sumvat	☐

Scr68

This is how the report will look in the Enterprise:

Products						
DATE BETWEEN: 2026-09-01 / 2026-09-06 ID_N='receipt' and ID_N='moves' and ID_N='moves' and ID_N='retail'						
store / nomenclature / price	Count(+) Count(-)	Count(+)	Sum(+) Sum(-)	Sum(+)	VAT(+) VAT(-)	VAT(+)
Head warehouse	1311.0000 0.0000	1311.0000	86100.0000 0.0000	86100.0000	6550.0000 0.0000	6550.0000
Cognac "Napoleon"	1.0000 0.0000	1.0000	240.0000 0.0000	240.0000	40.0000 0.0000	40.0000
200.0000	1.0000 0.0000	1.0000	240.0000 0.0000	240.0000	40.0000 0.0000	40.0000
Gasoline-92	500.0000 0.0000	500.0000	32100.0000 0.0000	32100.0000	2100.0000 0.0000	2100.0000
60	500.0000 0.0000	500.0000	32100.0000 0.0000	32100.0000	2100.0000 0.0000	2100.0000
Gasoline-95	600.0000 0.0000	600.0000	44940.0000 0.0000	44940.0000	2940.0000 0.0000	2940.0000
70	600.0000 0.0000	600.0000	44940.0000 0.0000	44940.0000	2940.0000 0.0000	2940.0000
Oil M10G2K	210.0000 0.0000	210.0000	8820.0000 0.0000	8820.0000	1470.0000 0.0000	1470.0000
35	210.0000 0.0000	210.0000	8820.0000 0.0000	8820.0000	1470.0000 0.0000	1470.0000
TOTAL:	1311.0000 0.0000	1311.0000	86100.0000 0.0000	86100.0000	6550.0000 0.0000	6550.0000

Scr69

As you may have noticed, in all my printed forms the **dimensions** are always displayed in a single column — the first one.

The reason is that the **SELECT... query** returns data as a single row, collapsed into the structure “*Warehouse / Item / Price*”. In the printed form, they are shown as separate rows with visual indentation (a long space).

Initially, I implemented the query so that it immediately returned the data in a ready-made form — exactly as you see on the screen. The query itself became significantly larger, but that was not critical. The problem arose elsewhere: the **Firebird server** began spending considerably more time executing such a query.

Therefore, I abandoned this idea and moved the logic of splitting into subordinate dimensions and calculating sums for each dimension to the **client side**. Yes, it required a lot of effort, but I wrote the code once, and now I apply it in all similar queries.

The report also supports **document breakdowns** (if it is a document-based report). For this, a hidden column **id_docs** is added. However, the breakdown works only for the **last dimension** — in this example, *Price* (via double-click).

Let us now look at the next tab — MaketPrint:

Select Form:

TITLE

TABLES

MaketPrint

DESCRIPTION

MaketPrint:Generate Select and MaketView print

WITH MyW AS (
SELECT Get_blob_A(vv,'store') AS store,Get_blob_A(tab,'nomenc1') AS nomenc1,Get_blob_A(tab,'price') AS price,SUM(Get_blob_4(tab,'kount')) AS kount,0 AS kount1,SUM(Get_blob_4(tab,'sumrow')) AS sumrow,0 AS sumrow1,SUM(Get_blob_4(tab,'sumvat')) AS sumvat,0 AS sumvat1,LIST(ID) AS id_docs
FROM DOCS2
WHERE ID_N='receipt' and DAT BETWEEN dat8_ and dat9_ and 1=1 GROUP BY 1,2,3
UNION ALL
SELECT Get_blob_A(tab,'store#1'),Get_blob_A(tab,'nomenc1'),0,SUM(Get_blob_4(tab,'kount')),0,0,0,0,0,LIST(ID)
FROM DOCS2
WHERE ID_N='moves' and DAT BETWEEN dat8_ and dat9_ and 1=1 GROUP BY 1,2,3
UNION ALL
SELECT Get_blob_A(vv,'store'),Get_blob_A(tab,'nomenc1'),0,SUM(Get_blob_4(tab,'kount')),0,0,0,0,0,LIST(ID)
FROM DOCS2
WHERE ID_N='moves' and DAT BETWEEN dat8_ and dat9_ and 1=1 GROUP BY 1,2,3
UNION ALL
SELECT
Get_blob_A(vv,'store'),Get_blob_A(tab,'nomenc1'),Get_blob_A(tab,'price'),0,SUM(Get_blob_4(tab,'kount')),0,SUM(Get_blob_4(tab,'sumrow')),0,SUM(Get_blob_4(tab,'sumvat')),LIST(ID)
FROM DOCS2
WHERE ID_N='retail' and DAT BETWEEN dat8_ and dat9_ and 1=1 GROUP BY 1,2,3
)
SELECT store,nomenc1,price,SUM(kount) AS kount,SUM(kount1) AS kount1,SUM(kount-kount1) AS formul1,SUM(sumrow) AS sumrow,SUM(sumrow1) AS sumrow1,SUM(sumrow-sumrow1) AS formul2,SUM(sumvat) AS sumvat,SUM(sumvat1) AS sumvat1,SUM(sumvat-sumvat1) AS formul3,LIST(id_docs) AS docs_id

Scr70

Initially, the **textarea** field remains empty. Only after fully completing the setup of all tables can you click the **Generate Select and Maket** button — the program will automatically generate the SQL query and HTML code. If the tables are filled correctly, the report should successfully run in the **Enterprise** system.

If the report works, the text can be edited — provided you clearly understand what you are doing. Of course, experimentation is allowed: refine the text, save it, and run it again in **Enterprise**. If the result turns out unsuccessful — no problem. Simply delete all the text and click **Generate Select and Maket** again. Note: if even a single character remains in the **textarea**, the button will not work.

When the text is ready, you can view the report structure by clicking the **View print** button.

..txtt..						
..titl1..						
store / nomenclature / price	Count(+) Count(-)	Count(+)	Sum(+) Sum(-)	Sum(+)	VAT(+) VAT(-)	VAT(+)
..store.. / ..nomencl.. / ..price..	..kount.. ..kount1..	..formul1..	..sumrow.. ..sumrow1..	..formul2..	..sumvat.. ..sumvat1..	..formul3..

Scr71

As I mentioned earlier — in **Enterprise**, by clicking on the header of the printed form (in our case, “*Goods*”), you can return to the report settings. You can change the dates or filters and generate the report again.

You can also return to the report settings by pressing **Esc**, but there is a small difference — in addition to the report settings, the printed form will remain visible just below the settings! This works in almost all reports.

The next tab is **DESCRIPTION**. This is simply a **textarea field**. It does not affect the operation of the report. You can write something like *Help* there, or anything else you consider useful!

Next Report — Assistant for Creating Additional Reports

In the **Configurator**, open the menu — **Assistant for Creating Additional Reports**.

This Configurator allows you to create almost the same reports as the previous one, but the time spent on building the report, I hope, will be significantly less. The reason is that the previous report requires a solid understanding of how **UNION** works in queries (**SELECT**).

In this report, however, you do not need to strictly understand or follow the rules of building a report using **UNION**. You simply need to make data selections from different tables (or even from just one!), and the program will automatically combine the table data according to the rules of **UNION**.

Let us now proceed to the description of creating a new report.

Edit Metadata:> USER: ROLES:

METADATA: NAME:

PRESENTATION: ACTUAL: ☐

Query (Free report)

[Online html editor](#)


Scr72

Starting Work with a New Report

- **Document Header:** its completion was described earlier, so it is not considered here.
- **Help:** if you check this option, a simple **textarea field** will open where you can add comments or a description of the report at your discretion.
- **Left/Right Arrows:** mainly used to test the query at the end of report creation, with the **RUN>>** button.

Important Rules When Creating a Report

1. At the beginning, the **textarea field** must always be empty. It cannot be edited until all required data has been filled in.
2. Work begins by pressing the **ADD_NEW** button. After this, the field will display service text: *Firebird: Construct a request for such parameters! Build a query for such parameters: //MySelect* Next, you must proceed to selecting the tables and data that will be used in the report.



Scr73

Selecting a Table for the Report


In the **FROM** dropdown list, you need to choose the desired table from **Firebird**.

All tables were described earlier, but it is worth explaining separately the **BALANS_DOC** view.

- **BALANS_DOC** is a **VIEW** that provides access to all document movements.
- You can study its structure in more detail using the **Firebird editor**.

For example, let us select the **DOCS2** view. After this, additional dropdown lists will appear:

- **FromName**
- **VV_TAB**



Scr74

Working with Dropdown Lists

- In the **FromName** list, all documents available in the database are displayed.
- For example, select the document **receipt** (*Incoming Invoice*).
- After selecting the document, the **VV_TAB** dropdown list is automatically filled.
- It will contain all parameters of the selected table, including those located in the document's **Blob** fields.

Thus, the sequence of actions is as follows:

1. Select a document in the **FromName** list.


- 2. Wait for the automatic filling of the **VV_TAB** list.
- 3. Use the parameters from **VV_TAB** for further report configuration.



Scr75

Here is where the real programmer’s work begins. You should already know which parameters you will need from this document. Then, select these parameters one by one from the dropdown list.

After each selection, the chosen parameters will be removed from the dropdown list and will appear in a special control field.



Scr76

Completing Parameter Selection At this stage, it is important to be careful:

- If a mistake is made, you will have to start over.
- To do this, you can clear the **textarea field** (Ctrl+A → Delete) or simply reload the page.

If everything is done correctly:


- At the end of all selections, you must choose the **END** item from the list (highlighted in red).
- This signals to the program that the selection stage is complete.
- After this, a new line will appear in the **textarea** above the `//MySelect` string, containing a preliminary set of data you selected earlier:

```
FROM:DOCS2:WHERE : id_n='receipt' and dat BETWEEN dat8_ and dat9_ and 2=2:SELECT
:Get_blob_A(vv,'contr') AS contr,Get_blob_A(vv,'store') AS
store,SUM(Get_blob_4(tab,'kount')) AS kount,
```

Do not be alarmed — this line will ultimately allow the program to correctly form the final **SELECT**.

If your query uses multiple tables, then again go to the **FROM** list, select a new table, and repeat the process just as with the first table. But now there is an important nuance: we are preparing a query using **UNION**.


With each parameter selection, the program analyzes the parameter name for matches with names from previous tables. If a match is found, a window will appear.



Scr77

If you click **OK**, the program will remember that these parameters must be combined when creating the final **SELECT** using **UNION**.

If you click **Cancel**, a new parameter will be created and a window will appear.



Scr78

Finalizing Parameter Selection

- A new parameter receives a name created from the new name and the table name, joined with an underscore. This ensures the program correctly builds **SELECT** statements with **UNION**.
- Important: if documents are involved in the report and a breakdown in the printed form is required, you must specify the **document id** as the last parameter when selecting document fields.

Return_VV_TAB List After selecting from the tables, proceed to the final step — open the **Return_VV_TAB** list. In addition to the standard items (**END**, **formul_**, **ALL**), it will display all selected parameters in the order they were added.

- If the parameters are already arranged correctly (dimensions first, then resources) and formulas are not needed, you can select **ALL** — then all parameters will automatically be included in the **Return** line.
- If the order is different or formulas are required, parameters must be selected manually, one by one, in the order they should appear in the printed form (dimensions first, then resources).
- To insert a formula into a column, select the **formul_** parameter. □ Note: if a parameter is used only inside a formula and is not needed in the printed form, it should not be selected.

Example After completing parameter selection, choose **END**. A new line will appear in the **textarea** above the `//MySelect` string with a preliminary set of data:

```
Return: Select : contr,store,nomenc1,price,SUM(kount) AS kount,SUM(sumvat) AS
sumvat,SUM(sumrow) AS sumrow,SUM(kount_spending) AS kount_spending,SUM(sumvat_spending)
AS sumvat_spending,SUM(sumrow_spending) AS sumrow_spending,SUM(formul_1) AS formul_1
```

After `//MySelect`, the program will generate the full **SELECT**, for example:

```
WITH q_all AS (
    SELECT Get_blob_A(vv,'contr') AS contr,Get_blob_A(vv,'store') AS
store,Get_blob_A(tab,'nomenc1') AS nomenc1,Get_blob_T(tab,'price') AS price,
        SUM(Get_blob_4(tab,'kount')) AS kount,SUM(Get_blob_4(tab,'sumvat')) AS
sumvat,SUM(Get_blob_4(tab,'sumrow')) AS sumrow,
```

```

        NULL AS price_spending, NULL AS kount_spending, NULL AS sumvat_spending, NULL AS
sumrow_spending
    FROM DOCS2 WHERE id_n='receipt' AND dat BETWEEN dat8_ AND dat9_ AND 2=2
    GROUP BY contr, store, nomenc1, price, price_spending
    UNION ALL
    SELECT Get_blob_A(vv, 'contr') AS contr, Get_blob_A(vv, 'store') AS
store, Get_blob_A(tab, 'nomenc1') AS nomenc1,
        NULL AS price, NULL AS kount, NULL AS sumvat, NULL AS sumrow,
        Get_blob_T(tab, 'price') AS price_spending,
        SUM(Get_blob_4(tab, 'kount')) AS kount_spending, SUM(Get_blob_4(tab, 'sumvat')) AS
sumvat_spending, SUM(Get_blob_4(tab, 'sumrow')) AS sumrow_spending
    FROM DOCS2 WHERE id_n='spending' AND dat BETWEEN dat8_ AND dat9_ AND 2=2
    GROUP BY contr, store, nomenc1, price, price_spending
)
SELECT contr, store, nomenc1, price, price_spending,
        SUM(kount) AS kount, SUM(sumvat) AS sumvat, SUM(sumrow) AS sumrow,
        SUM(kount_spending) AS kount_spending, SUM(sumvat_spending) AS
sumvat_spending, SUM(sumrow_spending) AS sumrow_spending,
        SUM(formul_1) AS formul_1
FROM q_all
GROUP BY contr, store, nomenc1, price, price_spending;

```

Editing Formulas At the formula refinement stage, edit the line `SUM(formul_1) AS formul_1` to reflect the required calculation. For example:

```
SUM(kount - kount_spending) AS formul_1
```

- The number of formulas can be unlimited.
- The program automatically creates them using a counter: **formul_1**, **formul_2**, **formul_3**, etc.

Once all parameters are correctly filled in, the **SELECT** block can be finalized. The query will then execute properly and return the expected result.

Generating HTML Code Next, generate the HTML code for the printed form output:

- Click the **SampleTable** button, and the program will automatically create the HTML code.
- To view the structure of the printed form, click the **TABLES** button — the structure of the printed form will appear at the bottom of the screen.

The screenshot shows a web application interface. At the top, there is a yellow header bar with the text `..titl1..`. Below the header, there is a table with 7 columns: `Контрагент / Склад / Номенклатура / Цена / Цена`, `Кількість`, `Сума ПДВ`, `Вся сума`, `Кількість1`, `Сума ПДВ1`, and `Вся сума1`. The table contains one row of data with values: `..contr.. / ..store.. / ..nomenc1.. / ..price.. / ..price_spending..`, `..kount..`, `..sumvat..`, `..sumrow..`, `..kount_spending..`, `..sumvat_spending..`, and `..sumrow_spending..`. Below the table, there is a green footer bar with the text `..txtf..`. On the left side of the interface, there is a sidebar with buttons: `RUN >>`, `Online htm editor`, `Delete Tables`, and `TABLES >>`. The `TABLES >>` button is highlighted. The main area of the interface displays the SQL query and its results.

Scr79

The **table header** will look the same as in **Enterprise**. If you need to change something, open the line with the tag and edit it (for example, you can adjust the column width using `width=?`). After that, click the **TABLES** button again, and the changes will appear in the structure.

The **Delete_Tables** button hides the table structure.

You can also make changes in the lines with tags, but for this you need a good understanding of how **HTML** works. □ The main rule: do not change parameter names between two dots (for example, `..kount..`), otherwise the report will stop working.

Any column can have an event attached. However, you must write the event handler yourself in a connected module, using:

Html:
`<script src="Myjsjs/METADATA___/id_n___/my.js"></script>`

If you add a new event but the program cannot find the corresponding function, it will result in an error. In this way, you can connect your own event handling for the required column.

I already have an example: on the first dimension column there is an event:

Html:
`ondblclick="Dblclick_DOC(this) "`

By default, it opens the breakdown of documents linked to the row. If you do not need this breakdown, the event can be deleted or replaced with your own.

Now about the **RUN>>** button. It allows you to test the operation of the **SELECT query** directly in the report Configurator.

- If the query uses date filtering (`dat BETWEEN dat8_ and dat9_`), you must first fill in these values, otherwise an error will occur.
- To do this, click the **DATE** button and in the window that appears specify the start and end dates.
- After that, highlight the plain text of the query.

Scr80

Only then can you click the **RUN>>** button.

If “**undefined**” appears, it means something is wrong with the query.

- Otherwise, the **textarea field** will display the query result, approximately in the following form:

Scr81

Do not worry: when outputting the printed form in **Enterprise**, the program will process all data correctly. This means only one thing — your query works.

If you press the **left arrow** button several times, you can return the **textarea field** to its initial state, until the date values reappear in the query (dat BETWEEN dat8_ and dat9_).

☐ Checking with the **RUN>>** button is not mandatory. Experienced **My4s** users will recognize when the query is correct. If it turns out to be incorrect, in **Enterprise** it simply will not work — then you return to the Configurator and fix it.

Now about the **Same** button (in the same column). When a report has many columns, the browser tries to fit them all on the screen, and the result is not always convenient.

After pressing the **Same** button, a window will open where you need to specify the tag number that you want to merge with the previous column.

Scr82

Automation will merge not only in <th> but also in <td>. You can press **Same** as many times as you want to merge columns — even across multiple levels! The merged column will be highlighted.

It is important that in the **Return** setup the columns are arranged in the correct order so they can be merged properly.

At the end, you can save everything you have done using the **SAVE METADATA** button. Then you can go to **Enterprise**, select **Additional reports** in the main menu, find your report, and test it. If something is wrong, return to the Configurator, edit the report, save it again, and check it in **Enterprise**.

Query_fast Reports (Quick Reports)

These reports largely coincide with the previous report “Assistant for Writing Additional Reports.” To create and edit these reports, the Configurator is not required — they are generated directly within the “Enterprise” system. This feature allows each user (for example, an accountant) to independently create their own reports. Naturally, programmers must first train them to do so. Therefore, a repeated description is not necessary. The only difference is that two items are missing from the table list: BALANS_DOC and METADATA (I believe work with these tables should be left to programmers). In “Enterprise,” from the main menu, select query_fast — a form will open with a list of all quick reports.

© Update **METADATA:** query_fast **USER:** demo

© ADD NEW Query fast >> © EDIT Query fast >>

#	NAME	PRESENTATION	ACTUAL
1	CATS_CATS1	CATS_CATS1	✓
2	prov4	prov4	✓
3	prov5	prov5	✓
4	prov3	prov3	✓

Scr83

If the list contains a large number of rows, you can use the standard Ctrl+F combination to find the desired one. To run a report, double-click the corresponding row. Ready-made reports have no access restrictions. To create a new report, click the ADD NEW ... button — a form will open, similar to the previous report. A detailed description can be found there as well. To edit an existing report, select its row and click the EDIT ... button. All users can use these reports. However, only the following can edit them: • users (user) who created the report; • users with full rights (all). Important: if a report is edited by a user with full rights (all), the primary owner still remains the user who originally created it.

Processing

Again, I used “Assistant for Writing Additional Reports” as the basis.

Edit Metadata:> **USER:** Программист1 **ROLES:** **SAVE METADATA >>** **COPY NEW >>**

METADATA: Processing **NAME:** demo1 **PRESENTATION:** demo1 **ACTUAL:** ✓

Processing (Обработка) Help

ADD_NEW FROM Return_VV_TAB SampleTable Same DATE

Firebird:Construct a request for such parameters!Побудуємо запит по таким параметрам:

Scr84

Almost always, a report is required for processing. This is convenient because it allows you to immediately verify the correctness of its execution. If, in the final version, displaying the print form on the screen turns out to be unnecessary, simply delete all the contents from the textarea starting with “//TAB” and below. Another scenario is also possible: a report may not be needed at all when preparing the processing. In this case, you describe all processing procedures independently in the module my.js (or another module connected via src). Then, information in the textarea is not required — it can be completely deleted or not filled in at all. In the connected module `<script src="Myjsjs/DOCS/id_n_/my.js"></script>` there must be a function **MyProcessing** (zr), and it will depend on you how the processing will work.

Let's summarize reports and processing.

In the “Enterprise” system, the operation of reports and processing is managed by a single HTML template **MyReport.htm** and connected modules (in addition to the standard ones):

Html:

```
<script src="Report_db.js"></script>
<script src="Myjsjs/METADATA_/id_n_/myXX.js"></script>
<script src="Mydbdb/query_fast.js"></script>
<script src="Myjsjs/METADATA_/id_n_/my.js"></script>
```

I will not provide a detailed description of their operation — the code is fully open. Experienced programmers can easily understand the logic and adapt it to their tasks if necessary.

By default, the program is configured to work in a single time zone. In the Blob.js module, at the very beginning, there is a variable: `"let timezoneOffset = 0;"`. If you assign this variable a value of 1, then the program will work with multiple time zones!

Caution! This constant cannot be changed during operation. It must be configured at the very beginning of the My4s implementation!

Let's sum up briefly what was written above.

I realize that what is written may not be immediately clear in some places. However, this description is quite sufficient for you to decide whether you want to continue familiarizing yourself with My4s. If you do want to continue, then you should first install the demo version and go through the description using specific examples. That way, many things will become clearer.

Installation guide for My4s on your computer or laptop with Windows

You should already have the `Distrib_My4s.zip` distribution archive on your computer, transferred from GitHub.

Note: On my setup, the demo database (ua) uses WIN1251 encoding.

The demo database (es) and the empty database (my4sNull) use UTF-8.

As specialists like to say, an extra gigabyte hardly matters anymore. So UTF-8 may pay off later — for example, if you want to roll out your finished program in another country.

I created My4s primarily for my country — Ukraine.

This does not mean that the system will not work with other coding, but it will take some effort to configure it (artificial intelligence will help you!).

But in a zero base it will be easier - I tried to write everything there in English. You can simply translate it into your language wherever you need it!

If you have Windows 10 or higher installed (it should also work on Windows 8.1, but this has not been tested), the following steps can be performed without problems.

1. Creating folders and the database

- Create a folder on your computer to store Firebird databases (for example, *FB*).
- Inside it, create a folder for the demo database (for example, *demoFB*).
- Move the files *MYDB9.FDB* and *MYDB3.fbk* from the distribution into this folder.
- Copy the file *fbclient.dll* from the Firebird folder into the demo database folder.

2. Copying additional files

- Copy the *My4s* folder from the distribution to a convenient location on your computer.

3. Installing Firebird

- Install a stable version of Firebird 3.x (this is sufficient for learning; it is lighter in size).
- Versions 4.x or 5.x can also be used, but for initial study, 3.x is recommended.

4. Installing the ODBC driver

- Download the driver *Firebird_ODBC_2.0.5.156_x64.exe* (or a newer version if available).
- Install the driver.

5. Connecting the driver in Windows

- Type “odbc” in the Windows search bar.
- Open *ODBC Data Source*.
- Add a new DSN (*Add...*).
- Open the *Setup* window to configure the connection.

Data Source Name (DSN)
mydb9

Description

Database
C:\My\fb\db4s\MYDB9.FDB Browse

Client
C:\My\fb\db4s\fbclient.dll Browse

Database Account
SYSDBA

Password
●●●●●●●●

Role

Character Set
WIN1251

Services Test connection

Options

Transaction
☐ read (default write)
☐ nowait (default wait)
☐ Lock Timeout
☒ safe thread

Extended identifier properties
☒ quoted identifiers
☐ sensitive identifier
☐ autoquoted identifier
 Set null field SCHEMA

Dialect
☒ 3 ☐ 1

OK Cancel Help

Scr86

Fill it out as shown in the screenshot. For working with the demo database, the DSN must be **mydb9** and the Character Set must be **WIN1251** (I already have this specified in the settings). Next, correctly fill in **database** and **client**. The password is **masterkey**, and everything else should be entered as in the screenshot. Then click **Test connection** – if there is no error, click **OK**.

Install **Firebird Editor Pro**. If you already have another editor, then you are probably an experienced Firebird user and will figure it out yourself! Open **Firebird Editor Pro**. Click the plus sign (**New connection**) and fill out the form.

Connections

Filter by string...

My4s3

My4s

Connection Options SSL

Profile
My4s Color

Group
+

Server
Show in title

Protocol
TCP

Port
3050

Database
C:\My\fb\db4s\MYDB9.FDB

Client library
C:\My\fb\db4s\fbclient.dll

Charset
WIN1251

SQL dialect
3

Username
SYSDBA


Password
●●●●●●●● Save password ☒

OK Cancel

Scr87

For me, it is **My4s**, but you can name it as you like, for example **demo4s**. In **Database**, select the file with the demo database, and in **Client library**, select the file *fbclient.dll*. For the demo database, the standard password is **masterkey**. Everything else should be filled in as shown in the screenshot. Click **OK**. If you have entered everything correctly, the demo

database will appear (for me it is **My4s**, and for you it will be whatever name you chose).



Scr88

Next, install Node.js — the latest stable version (LTS). If you don't care about the options, you can choose the default installation. After that (if not already installed), set up the stable version of Visual Studio Code. Launch the editor and open the folder (it should already have been copied from the distribution) **My4s** via the menu *File* → *Open Folder*. On the left, a navigation column will appear with all the contents of the **My4s** folder. You will be able to open any files, view their contents, and make changes if necessary. With a single click, you can update the files and immediately see the results in the browser (without having to start My4s from scratch again — just reload the page related to your changes!).

Visual Studio Code is a powerful text editor. In our case, its main advantage lies in strong support for **Node.js** and the ability to debug modules. In addition, the editor supports various interface languages, which makes working with it more convenient. You can find a detailed description on the internet. Debug mode is also available!

Steps for setting up the database (from scratch)

1. For getting acquainted with My4s, the demo version is sufficient.
2. If you want to create your own database from scratch:
 - In the distribution, there is a folder *my4sNull* containing:
 - the initial database *mydb3.FDB*
 - the backup copy *mydb3.fbk*
 - In the *FB* folder on your computer (or another folder with a different name), create a new folder *MyFb*.
 - Move the files from the *my4sNull* distribution into this folder.
3. In the *My4s* folder, there is already a template for the initial database in the *mydb3* folder.
4. In Windows settings, add a new DSN *mydb3* for the ODBC driver.
5. In Firebird Editor Pro, create a new connection (for example, *My4s3*, as described above).
6. The database already has some initial settings required for work. And then it depends entirely on you, what you will get in the end.

Verification of operation

- If everything has been done correctly, you will be able to work with two databases in the browser at once:
 - Demo database: **127.0.0.1:1637/mydb/cf** or **127.0.0.1:1637/mydb/db**
 - Your database: **127.0.0.1:1637/mydb3/cf** or **127.0.0.1:1637/mydb/db**
- The default password is **masterkey**. You can change it to any other.

💡 If it doesn't work the first time, don't be upset. That's normal—I didn't get it right immediately either! Just reread the description carefully.

For programming “from scratch” or working with the demo database on a local computer, it is quite sufficient to use VS Code — since you can directly run **Node.exe** through the *Run* menu.

But what should you do once you have already created your program, debugged it, and placed the **My4s** folder on the server so that many users can work with the database via the internet or a local network?

For this purpose, on the server where **Node.exe** is installed (remember: in *My4s* the server is just a single file, **Node.exe**, which must be located in the *My4s* folder), a special batch file **Start_Node.bat** is provided.

Its contents consist of just one line: **node.exe Start4s.js**

When launched, **Node.exe** receives the file **Start4s.js**, which:

- listens to the port (in this case, **1637**),
- contains the main routing,
- connects other files from the *My4s* folder as needed.

It is enough to run this batch file — and you will be able to connect to the database directly from the browser!

Important: on the server, it is not necessary to install the entire Node.js package. The key requirement is to have the correct **Node.exe** file of the release needed for operation.

Attention! You cannot run Node simultaneously from VS Code and from the batch file if you are working on the same computer!

Working with My4s on Windows 7

If your computer is running Windows 7 — don't worry. In the *Windows7* distribution you will find:

- **Node.js version 12** (compatible with Windows 7)
- A folder with a ready-to-use **VS Code**, which will also work on Windows 7

Contact with the author:

Email address for contact: sergey2429@i.ua

I will be glad if you find any inaccuracies, bugs, or—God forbid—errors. Be sure to describe under what conditions this occurs! If you improve any part of the program yourself, describe in detail what you did. And if I consider that it truly improves the program, I will gladly update it and credit you as the author of that part!

License and usage

My4S can be used free of charge in any environment, including but not limited to: personal, academic, commercial, governmental, corporate, non-profit, and commercial applications. “Free of charge” means there is no fee for installing and using My4S. Anyone who obtains a copy of this software has the right to use it without restrictions, including: use, copying, modification, publication, distribution, and granting access to other users with the same rights.

Copyright

All programs created with My4S must indicate that they were developed using this software.

Disclaimer of warranties

The software is provided “AS IS”, without any warranties, express or implied, including but not limited to: warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. The authors and copyright holders are not liable for any claims, damages, or other obligations arising from the use of this software.

Would you like me to format the entire license section (usage, copyright, disclaimer) into a clean Markdown block so it can be directly inserted into your documentation?