

Waypoint Group OMS – Project Structure & Routing Guide

Waypoint Group OMS – Full Project Structure & Routing Guide

This page documents the agreed **monorepo structure**, **who works where**, and the **role-based routes** used to test each persona in the React app.

Repository structure (monorepo)

```
TeamName_WaypointOMS/      # Main GitHub repository root
|
|— README.md                # Setup instructions, Tech Stack, and Team info
|— docker-compose.yml       # Runs Frontend, Backend, and DB in containers
|— .gitignore               # Ignores node_modules, target/, and .env files
|
|— frontend/                # React + Tailwind (Vite)
|   |— package.json
|   |— vite.config.js
|   |— src/
|       |— assets/          # Logos, SVGs, global icons
|       |— components/      # Shared UI (Buttons, Layouts, Maps)
|       |— context/         # Global state (Auth, Theme)
|       |— pages/           # Role-based pages
|           |— auth/        # Login / MFA
|           |— dispatcher/  # Dispatcher dashboard
|           |— store-manager/ # Store manager portal
|           |— loader/      # Loader mobile view
|           |— driver/      # Driver mobile view
|       |— routes/          # Route guards (auth/role)
```

```

|       |— services/           # Axios API calls to Spring
Boot
|       |— App.jsx             # React root component + routes
|
|       |— backend/           # Java Spring Boot
|       |   |— pom.xml         # Maven dependencies
|       |   |— src/
|       |       |— main/java/com/waypoint/oms/
|       |       |   |— config/   # CORS, Web, DB configurations
|       |       |   |— controller/ # REST API endpoints (e.g., OrderController)
|       |       |   |— model/     # Domain entities (User, Order, Vehicle)
|       |       |   |— repository/ # Spring Data repositories
|       |       |   |— security/   # JWT auth + RBAC filters
|       |       |   |— service/    # Business logic (allocation, routing)
|       |       |— main/resources/
|       |           |— application.yml # Server port, DB URI, JWT secrets (use env vars locally)

```

Who works where?

- **Frontend developers:** work only in `frontend/` (keep code inside your assigned persona folder in `src/pages/`).
- **Backend developers:** work only in `backend/` (models, services, controllers, security).
- **DevOps / QA:** manage repo root (especially `docker-compose.yml`) and integration.

Running & testing different user roles (dev workflow)

Frontend එක React වලින් හඳුනා නිසා apps 4ක් වෙනම run කරන්නේ නැහැ. ඒ වෙනුවට **React Router (URL paths)** use කරලා views වෙන් කරනවා. හැමෝටම තමන්ගේ role එක independent test කරන්න පුළුවන්.

1) Test by changing the URL path

Run the frontend:

```
npm run dev
```

Then test your role by visiting:

- Dispatcher → <http://localhost:5173/dispatcher>
- Driver → <http://localhost:5173/driver>
- Store Manager → <http://localhost:5173/store-manager>
- Loader → <http://localhost:5173/loader>

2) Example `App.jsx` routes

```
import { BrowserRouter as Router, Routes, Route } from "react-router-dom";

import DispatcherDashboard from "../pages/dispatcher/DispatcherDashboard";
import DriverView from "../pages/driver/DriverView";
import StoreManagerView from "../pages/store-manager/StoreManagerView";
import LoaderView from "../pages/loader/LoaderView";
import Login from "../pages/auth/Login";

function App() {
  return (
    <Router>
      <Routes>
        <Route path="/" element={<Login />} />
        <Route path="/dispatcher" element={<DispatcherDashboard />} />
        <Route path="/driver" element={<DriverView />} />
        <Route path="/store-manager" element={<StoreManagerView />} />
        <Route path="/loader" element={<LoaderView />} />
      </Routes>
    </Router>
  );
}
```

```
);  
}  
  
export default App;
```

Notes / reminders (recommended)

- **Routes ≠ security**: URL paths only separate views. Add **auth + role-based route guards** (and enforce RBAC on backend APIs).
- For a clean `docker compose up` experience, ensure the repo also includes the needed **Dockerfiles** and uses **environment variables** for secrets (don't commit real JWT secrets).