

CS 4602

Introduction to Machine Learning

Deep learning

Instructor: Po-Chih Kuo

Roadmap


- Introduction and Basic Concepts
- Regression
- Bayesian Classifiers
- Decision Trees
- Linear Classifier
- Neural Networks
- Deep learning
- Convolutional Neural Networks
- Reinforcement Learning
- KNN
- Model Selection and Evaluation
- Clustering
- Data Exploration & Dimensionality reduction

Outline

- Why deep?
- Optimization
- Regularization (Overfitting problem)

Tricks!

Why Deep Learning?



Deep learning:


- Has won numerous pattern recognition competitions
- Does so with minimal feature engineering

This wasn't always the case!

Since 1980s: Form of models hasn't changed much, but lots of new tricks...



- More hidden units
- Better (online) optimization
- New nonlinear functions (ReLUs)
- Faster computers (CPUs and GPUs)

Performance vs Sample Size



Parameters vs Accuracy on ImageNet

(Canziani 2016)



- ResNet50 and ResNet100 are used routinely in production.
- Each of the few billions photos uploaded on Facebook every day goes through a handful of ConvNets within 2 seconds.

Machine Learning = Learning Representations

- **The traditional model of pattern recognition (since the late 50's)**
 - Fixed/engineered features (or fixed kernel) + trainable classifier



Hand-crafted
Feature Extractor

"Simple" Trainable
Classifier


- **End-to-end learning / Feature learning / Deep learning**
 - Trainable features (or kernel) + trainable classifier



Trainable Feature
Extractor

Trainable Classifier


Deep Learning = Learning Hierarchical Representations



Feature visualization of convolutional net trained on ImageNet from [Zeiler & Fergus 2013]

Hierarchical representation

- Hierarchy of representations with increasing level of abstraction
- Each stage is a kind of trainable feature transform
- Image recognition
 - Pixel → edge → texton → motif → part → object
- Text
 - Character → word → word group → clause → sentence → story
- Speech
 - Sample → spectral band → sound → ... → phone → phoneme → word




CS4602

Which Models are Deep?

MLP, SVM, or DT

- 2-layer perceptrons are not deep
 - Because there is no feature hierarchy
- SVMs and Kernel methods are not deep
 - Layer1: kernels; layer2: linear
 - The first layer is “trained” using the samples as templates for the kernel functions.
- Decision trees are not deep
 - No hierarchy of features. All decisions are made in the input space



Outline


- Why deep?
- Optimization
- Regularization (Overfitting problem)

Optimization


- Vanishing Gradient Problem
- Stochastic Gradient Descent (SGD)
- Momentum Method
- Adaptive Learning Methods (AdaGrad, RMSProp, Adam)

Vanishing Gradient Problem

- Back propagation uses chain rule.
 - Chain rule multiplies derivatives
- If these derivatives are between 0 and 1 the product vanishes as the chain gets longer.
 - or the product explodes if the derivatives are greater than 1.
- Sigmoid activation function leads to this problem.
- Saturating: After some epochs that learning happens relatively fast, the value saturates, and it takes much time to update the weights, because the value of gradient is small.




Sigmoid



Relu (Rectified Linear Units) function

- Avoids Vanishing Gradient Problem
 - Fast to compute
 - Biological reason
- The formula is simple: $\max(0, z)$.

$$\frac{d}{dx} \text{ReLU}(x) = \begin{cases} 0, & \text{if } x < 0, \\ 1, & \text{otherwise.} \end{cases}$$




Batch Gradient Descent

Algorithm 1 Batch Gradient Descent at Iteration k

Require: Learning rate ϵ_k

Require: Initial Parameter θ

- 1: **while** stopping criteria not met **do**
 - 2: Compute gradient estimate over N examples:
 - 3: $\hat{\mathbf{g}} \leftarrow +\frac{1}{N} \nabla_{\theta} \sum_i L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$
 - 4: Apply Update: $\theta \leftarrow \theta - \epsilon \hat{\mathbf{g}}$
 - 5: **end while**
-



- Positive: Gradient estimates are stable
- Negative: Need to compute gradients over the entire training for one update


Stochastic Gradient Descent

Algorithm 2 Stochastic Gradient Descent at Iteration k

Require: Learning rate ϵ_k

Require: Initial Parameter θ

- 1: **while** stopping criteria not met **do**
 - 2: Sample example $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$ from training set
 - 3: Compute gradient estimate:
 - 4: $\hat{\mathbf{g}} \leftarrow +\nabla_{\theta} L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$
 - 5: Apply Update: $\theta \leftarrow \theta - \epsilon_k \hat{\mathbf{g}}$
 - 6: **end while**
-



ϵ_k is learning rate at step k

In practice the learning rate is decayed linearly till iteration τ


$$\epsilon_k = (1 - \alpha)\epsilon_0 + \alpha\epsilon_{\tau} \text{ with } \alpha = \frac{k}{\tau}$$

Minibatching

- Potential Problem: Gradient estimates can be very noisy
- Obvious Solution: Use larger mini-batches
- Advantage: Computation time per update does not depend on number of training examples N
- This allows convergence on extremely large datasets

Momentum

- The Momentum method is a method to accelerate learning using SGD
- In particular SGD suffers in the following scenarios:
 - Loss surface has high curvature
 - We get small but consistent gradients
 - The gradients are very noisy




→ Gradient step


Momentum

- How do we try and solve this problem?
- Introduce a new variable \mathbf{v} , the velocity
- We think of \mathbf{v} as the direction and speed by which the parameters move as the learning dynamics progresses
- The velocity is an exponentially decaying moving average of the negative gradients

$$\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \nabla_{\theta} \left(L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)}) \right)$$



- Update rule: $\theta \leftarrow \theta + \mathbf{v}$
- Usually values for α are set high $\approx 0.8, 0.9$



SGD with Momentum

Algorithm 2 Stochastic Gradient Descent with Momentum


Require: Learning rate ϵ_k

Require: Momentum Parameter α

Require: Initial Parameter θ

Require: Initial Velocity \mathbf{v}

- 1: **while** stopping criteria not met **do**
 - 2: Sample example $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$ from training set
 - 3: Compute gradient estimate:
 - 4: $\hat{\mathbf{g}} \leftarrow +\nabla_{\theta} L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$
 - 5: Compute the velocity update:
 - 6: $\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \hat{\mathbf{g}}$
 - 7: Apply Update: $\theta \leftarrow \theta + \mathbf{v}$
 - 8: **end while**
-



Nesterov Momentum

- The velocity term in the Momentum method:


$$\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \nabla_{\theta} \left(L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)}) \right)$$

- Nesterov Momentum:


$$\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \nabla_{\theta} \left(L(f(\mathbf{x}^{(i)}; \theta + \alpha \mathbf{v}), \mathbf{y}^{(i)}) \right)$$

- Update: $\theta \leftarrow \theta + \mathbf{v}$

Momentum



Nesterov Momentum



- Gradient step
- Momentum step
- Actual step

SGD with Nesterov Momentum =Nesterov Accelerated Gradient (NAG)

Algorithm 3 SGD with Nesterov Momentum

Require: Learning rate ϵ


Require: Momentum Parameter α

Require: Initial Parameter θ


Require: Initial Velocity \mathbf{v}

- 1: **while** stopping criteria not met **do**
 - 2: Sample example $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$ from training set
 - 3: Update parameters: $\tilde{\theta} \leftarrow \theta + \alpha \mathbf{v}$
 - 4: Compute gradient estimate:
 - 5: $\hat{\mathbf{g}} \leftarrow +\nabla_{\tilde{\theta}} L(f(\mathbf{x}^{(i)}; \tilde{\theta}), \mathbf{y}^{(i)})$
 - 6: Compute the velocity update: $\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \hat{\mathbf{g}}$
 - 7: Apply Update: $\theta \leftarrow \theta + \mathbf{v}$
 - 8: **end while**
-

Momentum SGD vs. NAG



(a) Momentum-Based Gradient Descent



(b) Nesterov Accelerated Gradient Descent


$$\text{Green Circle} \Rightarrow \frac{\partial L}{\partial w_0} = \frac{\text{Negative}(-)}{\text{Positive}(+)}$$

$$\text{Red Circle} \Rightarrow \frac{\partial L}{\partial w_0} = \frac{\text{Negative}(-)}{\text{Negative}(-)}$$

Ref: <https://mc.ai/learning-parameters-part-2-momentum-based-and-nesterov-accelerated-gradient-descent/>

Adaptive Learning Rate Methods

- Motivation
 - Till now we assign the same learning rate to all features
 - If the features vary in importance and frequency, why is this a good idea? It's probably not!



AdaGrad

- Idea: Downscale a model parameter by square-root of sum of squares of all its historical values
- Parameters that have large partial derivative of the loss
→ learning rates for them are rapidly declined

Algorithm 4 AdaGrad

Require: Global Learning rate ϵ , Initial Parameter θ , δ

Initialize $\mathbf{r} = 0$

- 1: **while** stopping criteria not met **do**
 - 2: Sample example $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$ from training set
 - 3: Compute gradient estimate: $\hat{\mathbf{g}} \leftarrow +\nabla_{\theta} L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$
 - 4: Accumulate: $\mathbf{r} \leftarrow \mathbf{r} + \hat{\mathbf{g}} \odot \hat{\mathbf{g}}$
 - 5: Compute update: $\Delta\theta \leftarrow -\frac{\epsilon}{\delta + \sqrt{\mathbf{r}}} \odot \hat{\mathbf{g}}$
 - 6: Apply Update: $\theta \leftarrow \theta + \Delta\theta$
 - 7: **end while**
-

RMSProp

Root **Mean** Squared Propagation

- AdaGrad is good when the objective is convex.
- AdaGrad might shrink the learning rate too aggressively, we want to keep the history in mind
- We can adapt it to perform better in non-convex settings by accumulating an exponentially decaying **average** of the gradient
- It was proposed in a slide in Geoffrey Hinton's coursera course

Algorithm 5 RMSProp

Require: Global Learning rate ϵ , decay parameter ρ , δ , Initial Parameter θ
Initialize $\mathbf{r} = 0$

- 1: **while** stopping criteria not met **do**
 - 2: Sample example $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$ from training set
 - 3: Compute gradient estimate: $\hat{\mathbf{g}} \leftarrow +\nabla_{\theta} L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$
 - 4: Accumulate: $\mathbf{r} \leftarrow \rho \mathbf{r} + (1 - \rho) \hat{\mathbf{g}} \odot \hat{\mathbf{g}}$
 - 5: Compute update: $\Delta \theta \leftarrow -\frac{\epsilon}{\delta + \sqrt{\mathbf{r}}} \odot \hat{\mathbf{g}}$
 - 6: Apply Update: $\theta \leftarrow \theta + \Delta \theta$
 - 7: **end while**
-

Adam: ADAdaptive Moments

- We could have used RMSProp with momentum
- Use of Momentum with rescaling is not well motivated
- Adam is like RMSProp with Momentum but with bias correction terms for the first and second moments


Algorithm 7 RMSProp with Nesterov

Require: ϵ (set to 0.0001), decay rates ρ_1 (set to 0.9), ρ_2 (set to 0.9), θ , δ


Initialize moments variables $\mathbf{s} = \mathbf{0}$ and $\mathbf{r} = \mathbf{0}$, time step $t = 0$

```
1: while stopping criteria not met do
2:   Sample example  $(\mathbf{x}^{(i)}, \mathbf{y}^{(i)})$  from training set
3:   Compute gradient estimate:  $\hat{\mathbf{g}} \leftarrow +\nabla_{\theta} L(f(\mathbf{x}^{(i)}; \theta), \mathbf{y}^{(i)})$ 
4:    $t \leftarrow t + 1$ 
5:   Update:  $\mathbf{s} \leftarrow \rho_1 \mathbf{s} + (1 - \rho_1) \hat{\mathbf{g}}$ 
6:   Update:  $\mathbf{r} \leftarrow \rho_2 \mathbf{r} + (1 - \rho_2) \hat{\mathbf{g}} \odot \hat{\mathbf{g}}$ 
7:   Correct Biases:  $\hat{\mathbf{s}} \leftarrow \frac{\mathbf{s}}{1 - \rho_1^t}, \hat{\mathbf{r}} \leftarrow \frac{\mathbf{r}}{1 - \rho_2^t}$ 
8:   Compute Update:  $\Delta\theta = -\epsilon \frac{\hat{\mathbf{s}}}{\sqrt{\hat{\mathbf{r}} + \delta}}$ 
9:   Apply Update:  $\theta \leftarrow \theta + \Delta\theta$ 
10: end while
```

Method	Explanation	Update of w	Update of b
Momentum	<ul style="list-style-type: none"> Dampens oscillations Improvement to SGD 2 parameters to tune 	$w - \alpha v_{dw}$	$b - \alpha v_{db}$
RMSprop	<ul style="list-style-type: none"> Root Mean Square propagation Speeds up learning algorithm by controlling oscillations 	$w - \alpha \frac{dw}{\sqrt{s_{dw}}}$	$b \leftarrow b - \alpha \frac{db}{\sqrt{s_{db}}}$
Adam	<ul style="list-style-type: none"> Adaptive Moment estimation Most popular method 4 parameters to tune 	$w - \alpha \frac{v_{dw}}{\sqrt{s_{dw}} + \epsilon}$	$b \leftarrow b - \alpha \frac{v_{db}}{\sqrt{s_{db}} + \epsilon}$




Ref: Alec Radford



Regularization

- In general: any method to **prevent overfitting** or help the optimization
- Specifically: additional **terms** in the **training** optimization objective to prevent overfitting or help the optimization




Classical regularization

- L2 regularization
 - **L2 = weight decay**
 - Regularization term that penalizes big weights, added to the objective

$$\min_{\theta} \hat{L}_R(\theta) = \boxed{\hat{L}(\theta)} + \boxed{\frac{\alpha}{2} \|\theta\|_2^2}$$

- L1 regularization

$$\min_{\theta} \hat{L}_R(\theta) = \hat{L}(\theta) + \alpha \|\theta\|_1$$




Other types of regularizations

- Data augmentation
- Early stopping
- Dropout
- Batch Normalization

Data augmentation

- Adding noise to the input: a special kind of augmentation
- Be careful about the transformation applied:
 - Example: classifying 'b' and 'd' or classifying '6' and '9'




Original	Flip	Rotation	Random crop
<ul style="list-style-type: none"> • Image without any modification 	<ul style="list-style-type: none"> • Flipped with respect to an axis for which the meaning of the image is preserved 	<ul style="list-style-type: none"> • Rotation with a slight angle • Simulates incorrect horizon calibration 	<ul style="list-style-type: none"> • Random focus on one part of the image • Several random crops can be done in a row
Color shift	Noise addition	Information loss	Contrast change
<ul style="list-style-type: none"> • Nuances of RGB is slightly changed • Captures noise that can occur with light exposure 	<ul style="list-style-type: none"> • Addition of noise • More tolerance to quality variation of inputs 	<ul style="list-style-type: none"> • Parts of image ignored • Mimics potential loss of parts of image 	<ul style="list-style-type: none"> • Luminosity changes • Controls difference in exposition due to time of day


Q: What does data augmentation for structured data?

Early stopping

- Idea: don't train the network to too small training error
- Recall overfitting: Larger the hypothesis class, easier to find a hypothesis that fits the difference between the two
- Prevent overfitting: do not push the hypothesis too much; use validation error to decide when to stop





Early stopping as a regularizer



Dropout

- Dropout refers to dropping out units
- Temporarily remove a node and all its incoming/outgoing connections resulting in a thinned network
- Each node is retained with a fixed probability (typically $p = 0.5$) for hidden nodes and $p = 0.8$ for visible nodes



Batch Normalization (BN)


- To normalize the layers' inputs by re-centering and re-scaling.
- It was proposed by Sergey Ioffe and Christian Szegedy in 2015
- B to denote a mini-batch of size m

$$\mu_B = \frac{1}{m} \sum_{i=1}^m x_i, \text{ and } \sigma_B^2 = \frac{1}{m} \sum_{i=1}^m (x_i - \mu_B)^2.$$

$$\hat{x}_i^{(k)} = \frac{x_i^{(k)} - \mu_B^{(k)}}{\sqrt{\sigma_B^{(k)^2} + \epsilon}}, \text{ where } k \in [1, d] \text{ and } i \in [1, m]$$

$\mu_B^{(k)}$ and $\sigma_B^{(k)^2}$ are the per-dimension mean and variance, respectively.

Why BN?





- BN reduces *Covariate Shift*.
 - The change in distribution of activation of a component. By using BN, each neuron's activation becomes (more or less) a Gaussian distribution.
- Covariate Shift is undesirable, because the later layers have to keep adapting to the change of the type of distribution.
- BN reduces effects of exploding and vanishing gradients, because every becomes roughly normal distributed.


BN: Other benefits in practice

- BN reduces training times.
 - Because of less Covariate Shift, less exploding/vanishing gradients.
- BN reduces demand for regularization, e.g. dropout or L2 norm.
 - Because the means and variances are calculated over batches and therefore every normalized value depends on the current batch. I.e. the network can no longer just memorize values and their correct answers.
- BN allows higher learning rates.
 - Because of less danger of exploding/vanishing gradients.
- BN enables training with saturating nonlinearities in deep networks, e.g. sigmoid.
 - Because the normalization prevents them from getting stuck in saturating ranges, e.g. very high/low values for sigmoid.

Possible Hierarchical Features



But...we got something like this



Let's get back to this in the next lecture !

Questions?

**learn DL
in one lesson**

