

FIRST FLOOR SUSPENDED SLAB SHORING PLAN: SCALE 1/8"=1'-0"

8" DEEP SLAB TYPICAL U.N.O. (150 P.S.F.)
20" DEEP SLAB BAND TYPICAL U.N.O. (300 P.S.F.)

ALL FRAMES TO BE 6' HIGH X 4' WIDE UNDER SLAB AND 5' HIGH UNDER SLAB BAND

HEAVY DUTY(10K/LEG) AS SHOWN ON PLAN WITH 7'-0" BRACING TYP. U.N.O.

NO SHORE IS REQUIRED UNDER SLAB NOR SLAB BAND TYP. UNLESS SHOWN OR

MARKED AS "X" FOR #2 POST SHORE TYP. (SEE PLAN FOR LOCATION).

PLYWOOD TO BE MIN. 3/4" D. FIR #1 OR BETTER.

4X6 WOOD JOISTS SUPPLIED BY TTF SCAFFOLDING SHALL NOT BE USED FOR PACKING

OR CUT SHORT FOR OTHER PURPOSES.

FOR GENERAL NOTES AND TYPICAL DETAILS SEE DRAWING F-1.

INSPECTION IS REQUIRED BY UNDERSIGNED P. ENG. PRIOR TO POURING CONCRETE.

(24 HOURS NOTICE PLEASE).



NOTES:

-THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ARCHITECTURAL AND STRUCTURAL DRAWINGS.

CONTRACTOR TO CHECK AND CONFIRM ALL DIMENSIONS & ELEVATIONS PRIOR TO SHIPMENT OF EQUIPMENT.

-ALL SHORING SET UP UNDER STAIRS SLOPE TO BE AT LOWEST ELEVATION AND BUILD UP UNDER SLOPS TYP.

-"--" DENOTES AS 2-2X6 WOOD JOISTS SHORTER THAN 6'-0" LONG TYP.

REVISIONS BY

Jo. Ltd.

SCAFFOLDING CO

10860 124th STREET, SURREY, BC, V3
TEL. 778 898 5301
Email: info@ttfscaffolding.com

Ltd.

JOB:

EDWARDS STREET CONDOS

9194 EDWARDS STREET, CHILLIWACK, B.C.

CONTR:

KARVIN DEVELOPMENTS LTD.

TITLE:

FIRST FLOOR SUSPENDED SLAB SHORING PLAN & DETAILS

Date: APR.10.2021
Scales: AS SHOWN

Drawn by: F.T.

Job: A - 3156

Job: A - 3156 Sheet: F-2