

2ND FLOOR SUSPENDED SLAB SHORING PLAN: SCALE 1/8"=1'-0"

8" DEEP SLAB TYPICAL U.N.O.

20" DEEP SLAB BAND TYPICAL U.N.O.

(300 P.S.F.) ALL FRAMES TO BE 6'+6' HIGH X 4' WIDE HEAVY DUTY(10 K/LEG) WITH 7'-0'' BRACING TYP.

NO SHORE IS REQUIRED UNDER SLAB TYP. UNLESS SHOWN OR MARKED AS "X" FOR #2 AND "X" FOR #4 POST SHORE TYP.

(150 P.S.F.)

PLYWOOD TO BE MIN. 3/4" D. FIR #1 OR BETTER.

4X6 WOOD JOISTS SUPPLIED BY TTF SCAFFOLDING SHALL NOT BE USED FOR PACKING

OR CUT SHORT FOR OTHER PURPOSES.

FOR GENERAL NOTES AND TYPICAL DETAILS SEE DRAWING F-1.

INSPECTION IS REQUIRED BY UNDERSIGNED P. ENG. PRIOR TO POURING CONCRETE.

NOTES:

THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ARCHITECTURAL AND STRUCTURAL DRAWINGS. CONTRACTOR TO CHECK AND CONFIRM ALL DIMENSIONS & ELEVATIONS PRIOR TO SHIPMENT OF EQUIPMENT.

PLACE CONT. 2-2X10 WOOD MUDSILL ON COMPACTED FILL WHERE FRAME LEGS WILL BE SET OUTSIDE THE BUILDING TYP.

(SEE DRAWING F-1 FOR GENERAL NOTES).

Ltd.

TTF SCAFFOLDING

ANDERSON

COMMERCIAL

5560 ANDERSON WAY, VERNON, B.C.

CONTR:

VALOROUS CONSTRUCTION LTD.

TITLE:

2ND FLOOR SUSPENDED SLAB SHORING PLAN & DETAILS

Date: AUG.23.2024 Scales: AS SHOWN

Drawn by: F.T.

Sheet: F-2