



GROUND LEVEL SUSPENDED SLAB SHORING PLAN: SCALE 1/8"=1'-0"

8" DEEP SLAB TYPICAL U.N.O. (150 P.S.F.)  
20" DEEP SLAB BAND TYPICAL U.N.O. (300 P.S.F.)  
ALL FRAMES TO BE 4' WIDE HEAVY DUTY(10 K/LEG) WITH 7'-0" BRACING TYP.(SEE PLAN FOR THE HEIGHT)  
NO SHORE IS REQUIRED UNDER SLAB TYP. UNLESS SHOWN OR MARKED AS "X" FOR #2 POST SHORE  
PLYWOOD TO BE MIN. 3/4" D. FIR #1 OR BETTER.  
4X6 WOOD JOISTS SUPPLIED BY TTF SCAFFOLDING SHALL NOT BE USED FOR PACKING  
OR CUT SHORT FOR OTHER PURPOSES.  
FOR GENERAL NOTES AND TYPICAL DETAILS SEE DRAWING F-1.  
INSPECTION IS REQUIRED BY UNDERSIGNED P. ENG. PRIOR TO POURING CONCRETE.  
(48 HOURS NOTICE PLEASE).

NOTES :

THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ARCHITECTURAL AND STRUCTURAL DRAWINGS.  
CONTRACTOR TO CHECK AND CONFIRM ALL DIMENSIONS & ELEVATIONS PRIOR TO SHIPMENT OF EQUIPMENT.