

Package ‘INEbaseR’

July 1, 2019

Type Package

Title R package for obtaining and analyzing open data from INE
(Instituto Nacional de Estadística) API

Version 0.1.0

Date 2018-01-01

Maintainer Andres Nacimiento <andresnacimiento@gmail.com>

Description R package for obtaining and analyzing open data from INE (Instituto Nacional de Estadística) API.

License GPL (>= 3)

Encoding UTF-8

LazyData false

BuildResaveData false

Imports jsonlite, highcharter

RoxygenNote 6.1.1

NeedsCompilation no

Author Andres Nacimiento [aut, prg, cre],
Mariano Sanz [ctg],
Carlos J. Perez [aut, drt, pdr]

Depends R (>= 3.5.0)

R topics documented:

get_cache_rds	2
get_geographical	2
get_metadata_crossing	3
get_operations	4
get_publications	4
get_series	5
get_tables	6
get_values	7
get_variables	8
represent_series	8
update_cache	9

Index	11
--------------	-----------

get_cache_rds	<i>Get rds content (cache)</i>
---------------	--------------------------------

Description

This function returns the content of a RDS file in cache

Usage

```
get_cache_rds(object, type = "SERIEOPERATION")
```

Arguments

object	(string) an object of the "type" option
type	(string) type of content do you want to read, type = "/POLYGONS-" by default

Examples

```
get_cache_rds("provincias", type = "POLYGONS")
get_cache_rds("comunidades_autonomas", type = "POLYGONS")
get_cache_rds("municipios", type = "POLYGONS")
get_cache_rds("natcodes", type = "DATATABLE")
get_cache_rds(4, type = "SERIEOPERATION")
```

get_geographical	<i>Get geographical</i>
------------------	-------------------------

Description

This function returns geographical information

Usage

```
get_geographical(code = NULL, resource = "variable", all = FALSE,
  verbose = FALSE, natcode = NULL, geocode = NULL,
  exponential_notation = FALSE, help = FALSE)
```

Arguments

code	(string) serie id
resource	(string) resource to access, by default resource = "variable" to get serie meta-data. Possible values are variable, natcode or natcode_to_geocode
all	(boolean) if all = TRUE you will get all natcodes
verbose	(boolean) show more information during the process
natcode	(int) geographical code from INE
geocode	(string) geographical code from Eurostat
exponential_notation	(boolean) to show or not exponential notation. e.g. e+10
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.

Examples

```
get_geographical("IPC251522")
get_geographical(resource = "variable", help = TRUE)
get_geographical("IPC251522", resource = "natcode")
get_geographical(natcode = 34050000000, resource = "natcode_to_geocode")
```

get_metadata_crossing *Get metadata crossing*

Description

This function returns data or metadata by metadata crossing

Usage

```
get_metadata_crossing(code = NULL, resource = "series", help = FALSE,
  query = NULL, p = 1, det = 0, tip = NULL, nlast = 1,
  lang = "ES")
```

Arguments

code	(string) operation identificator
resource	(string) resource to access, by default resource = "metadata" to get serie meta-data. Possible values are series or data
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
query	(string) string separated by AND with syntax variable = value using natural language
p	(int) periodicity, p = 1 by default
det	(int) det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
tip	(string) tip = M to obtain the metadata (crossing variables-values) of the series
nlast	last n values
lang	(string) language used to obtain information

Examples

```
get_metadata_crossing(resource = "series", help = TRUE)
get_metadata_crossing("IPC", resource = "series", query = "Provincias = Madrid AND Tipo de dato = Variacion mensual")
get_metadata_crossing("IPC", resource = "data", query = "Provincias = Madrid AND Tipo de dato = Variacion mensual")
```

get_operations	<i>Get operations</i>
----------------	-----------------------

Description

This function returns information about operations

Usage

```
get_operations(code = NULL, resource = "all", help = FALSE,
  ioe = FALSE, geographical_granularity = NULL,
  temporal_granularity = NULL, verbose = TRUE, lang = "ES")
```

Arguments

code	(string) operation identifier
resource	(string) resource to access, by default resource = "metadata" to get serie meta-data. Possible values are all, metadata, variables_values or by_granularity
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
ioe	(boolean) TRUE if code is in format I030138, and FALSE by default
geographical_granularity	(string) geographical granularity
temporal_granularity	(string) temporal granularity
verbose	(boolean) show more information during the process
lang	(string) language used to obtain information

Examples

```
get_operations()
get_operations(resource = "all")
get_operations(resource = "all", help = TRUE)
get_operations("IPC", resource = "metadata")
get_operations("IPC", resource = "variables_values")
get_operations(resource = "by_granularity", geographical_granularity = "PROV")
```

get_publications	<i>Get publications</i>
------------------	-------------------------

Description

This function returns all available publications from an operation or a date

Usage

```
get_publications(code = NULL, resource = "all", help = FALSE,
  det = 0, ioe = FALSE, lang = "ES")
```

Arguments

code	(string) operation or publication indentificator
resource	(string) resource to access, by default resource = "all" to get serie metadata. Possible values are all, operation or date
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
det	(int) det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
ioe	(boolean) TRUE if code is in format I030138, and FALSE by default
lang	(string) language used to obtain information

Examples

```
get_publications()
get_publications(resource = "all", help = TRUE)
get_publications("IPC", resource = "operation")
get_publications(8, resource = "date")
```

get_series	<i>Get series</i>
------------	-------------------

Description

This function returns data or metadata from an operation, table or a serie

Usage

```
get_series(code = NULL, resource = "metadata", help = FALSE,
  ioe = FALSE, det = 0, tip = NULL, lang = "ES",
  date_start = NULL, date_end = NULL, nlast = NULL,
  classification = NULL, verbose = FALSE, benchmark = FALSE,
  geographical_granularity = NULL, temporal_granularity = NULL)
```

Arguments

code	(string) serie, operation or table indentificator
resource	(string) resource to access, by default resource = "metadata" to get serie meta-data. Possible values are metadata, operation, values, table, metadataoperation, data, by_gra or nlast
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
ioe	(boolean) TRUE if code is in format I030138, and FALSE by default
det	(int) det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
tip	(string) tip = M to obtain the metadata (crossing variables-values) of the series
lang	(string) language used to obtain information
date_start	(string) start date in format YYYY-MM-DD

date_end	(string) end date in format YYYY-MM-DD
nlast	(int) last n serie values
classification	(string) serie classification, if classification = NULL this value will be auto-detected
verbose	(boolean) to show more information about this process, verbose = FALSE by default
benchmark	(boolean) used to measure the performance of the system, benchmark = FALSE by default.
geographical_granularity	(string) geographical granularity
temporal_granularity	(string) temporal granularity

Examples

```

get_series("IPC206449")
get_series(resource = "metadata", help = TRUE)
get_series("IPC", resource = "operation")
get_series("IPC206449", resource = "values")
get_series(22350, resource = "table")
get_series("IPC251541", resource = "nlast")
get_series("IPC206449", resource = "data", nlast = 5)
get_series("IPC", resource = "by_granularity", geographical_granularity = "CCAA", verbose = TRUE)
get_series("IPC251539", resource = "by_common_parameters", verbose = TRUE)

```

get_tables	<i>Get tables</i>
------------	-------------------

Description

This function returns data / metadata from tables

Usage

```

get_tables(code = NULL, resource = "operation", help = FALSE,
  grp = NULL, geo = 0, nlast = 0, det = 0, tip = NULL,
  ioe = FALSE, lang = "ES")

```

Arguments

code	operation (string/int) or table (int) identifier
resource	(string) resource to access, by default resource = "operation" to get tables of an operation. Possible values are operation,group,group_values or data
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource
grp	(int) group identification
geo	(int) use geo = 1 to access only tables with geographic content, geo = 0 by default
nlast	last n values

det	(int) use det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
tip	(string) use tip = "A" to view as friendly, specifically the view the field ultima_modificacion or use tip = "AM" to obtain the metadata (crossing variables-values) of the series and a friendly output.
ioe	(boolean) use ioe = TRUE if code is in format I030138, and FALSE by default
lang	(string) language used to obtain information

Examples

```
get_tables("IPC")
get_tables(resource = "operation", help = TRUE)
get_tables(25, resource = "operation")
get_tables(22350, resource = "group")
get_tables(22350, grp = 81497, resource = "group_values")
get_tables(22350, nlast = 5, resource = "data")
```

get_values	<i>Get values</i>
------------	-------------------

Description

This function returns values from a variable or variable operation

Usage

```
get_values(code = NULL, resource = "all", operation = NULL,
  help = FALSE, det = 0, ioe = FALSE, lang = "ES")
```

Arguments

code	(int) variable indentificator
resource	(string) resource to access, by default resource = "all" to get serie metadata. Possible values are all or variable_operation
operation	(string) operation indentificator
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
det	(int) det = 1 to see the detail of the variable to which it belongs, det = 0 by default
ioe	(boolean) TRUE if code is in format I030138, and FALSE by default
lang	(string) language used to obtain information

Examples

```
get_values(115)
get_values(resource = "all", help = TRUE)
get_values(762, operation = "IPC", resource = "variable_operation")
```

get_variables	<i>Get variables</i>
---------------	----------------------

Description

This function returns all or operations variables

Usage

```
get_variables(code = NULL, resource = "all", help = FALSE,
             ioe = FALSE, lang = "ES")
```

Arguments

code	(string) operation identifier
resource	(string) resource to access, by default resource = "metadata" to get serie meta-data. Possible values are all or operation
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
ioe	(boolean) TRUE if code is in format IO30138, and FALSE by default
lang	(string) language used to obtain information

Examples

```
get_variables()
get_variables(resource = "all", help = TRUE)
get_variables("IPC", resource = "operation")
```

represent_series	<i>Represent series</i>
------------------	-------------------------

Description

This function allows representing series data in maps or charts

Usage

```
represent_series(code = NULL, resource = "maps", help = FALSE,
                nlast = 0, date_start = NA, date_end = NA, classification = NULL,
                map_scale = 60, verbose = FALSE, benchmark = FALSE, det = 0,
                type = NA, lang = "ES")
```


Arguments

code	(string) serie identificator
resource	(string) resource to access, by default resource = "all" to get serie metadata. Possible values are maps, plot or highcharts
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
nlast	(int) last n serie data, if nlast = 0 this value will be auto-calculated
date_start	(date) start date in format (string) YYYY-MM-DD
date_end	(date) end date in format (string) YYYY-MM-DD
classification	(string) serie classification, if classification = NULL this value will be auto-detected
map_scale	(int) refers to the relationship or ratio between distance on a map and the corresponding distance on the ground. For example, on a 1:1000000 scale map, 1cm on the map equals 1km on the ground. Possible values are: 1, 3, 10, 20 or 60, and it's only for PROV or CCAA geographical granularity, map_scale = 60 by default and map_scale = NULL for high detailed map.
verbose	(boolean) show more information during the process
benchmark	(boolean) used to measure the performance of the system, benchmark = FALSE by default.
det	(int) det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
type	(string) what type of plot should be drawn, type = "p" (for points) by default. See type in plot
lang	(string) language used to obtain information

Examples

```

represent_series("IPC251521", resource = "maps")
represent_series(resource = "maps", help = TRUE)
represent_series("IPC251521", resource = "maps", map_scale = NULL)
represent_series("IPC206449", resource = "plot", nlast = 5)
represent_series("IPC206449", resource = "highcharts", nlast = 5)

```

update_cache

*Update cache***Description**

This function allows to update cache data

Usage

```

update_cache(code = NULL, resource = "series", help = FALSE, n = 0,
  page = 1, pagination = TRUE, page_start = NA, page_end = NA,
  benchmark = FALSE, force = FALSE, ignore_series = NULL,
  tip = "M", det = 2, lang = "ES")

```

Arguments

code	(string) operation identificator
resource	(string) resource to access, by default resource = "all" to get serie metadata. Possible values are all or series
help	(boolean) type any value for resource param and type help = TRUE to see params available for this resource.
n	(int) number of operation to update starting from first operation getted from get_operations_all() function.
page	(int) page = 1 to obtain data of an specific page (to use this, pagination = FALSE).
pagination	(boolean) TRUE to obtain data page by page and FALSE by default.
page_start	(int) page_start = 1 start page range to obtain data (to use this, pagination = TRUE).
page_end	(int) page_end = 2 end page range to obtain data (to use this, pagination = TRUE).
benchmark	(boolean) used to measure the performance of the system, benchmark = FALSE by default.
force	(boolean) to force to update all cache data, force = FALSE by default.
ignore_series	(list) list of operation identificators to ignore. More slow series to cache are: 16, 49, 330 and 334
tip	(string) tip = M to obtain the metadata (crossing variables-values) of the series.
det	(int) det = 2 to see two levels of depth, specifically to access the PubFechaAct object, det = 0 by default
lang	(string) language used to obtain information

Examples

```
update_cache(resource = "series")
update_cache(resource = "series", help = TRUE)
```

Index

`get_cache_rds`, [2](#)
`get_geographical`, [2](#)
`get_metadata_crossing`, [3](#)
`get_operations`, [4](#)
`get_publications`, [4](#)
`get_series`, [5](#)
`get_tables`, [6](#)
`get_values`, [7](#)
`get_variables`, [8](#)

`plot`, [9](#)

`represent_series`, [8](#)

`update_cache`, [9](#)