

Package ‘giscoR’

October 5, 2020

Type Package

Title Download Geospatial Data from GISCO API - Eurostat

Version 0.1.0

Description Tools to download data from the GISCO
(Geographic Information System of the COMmission) Eurostat database
<<https://ec.europa.eu/eurostat/web/gisco>>.
This package is in no way officially related to or endorsed by Eurostat.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

BugReports <https://github.com/dieghernan/giscoR/issues>

URL <https://dieghernan.github.io/giscoR/>, <https://github.com/dieghernan/giscoR>

Depends R (>= 3.3.0)

Imports sf (>= 0.9),
countrycode (>= 1.2.0),
geojsonsf (>= 2.0)

Suggests cartography (>= 2.0.0),
colorspace,
eurostat,
lwgeom,
tinytest,
knitr,
rmarkdown

Date 2020-10-05

VignetteBuilder knitr

R topics documented:

giscoR-package 2

gisco_attributions	3
gisco_coastallines	4
gisco_countries	5
gisco_countrycode	6
gisco_get_coastallines	7
gisco_get_communes	8
gisco_get_countries	10
gisco_get_lau	12
gisco_get_nuts	14
gisco_get_urban_audit	16
gisco_nuts	18

Index	20
--------------	-----------

giscoR-package	<i>Download geospatial data from GISCO API - Eurostat</i>
----------------	-----------------------------------------------------------

Description

giscoR is a API package that helps to retrieve data from Eurostat - GISCO (the Geographic Information System of the COMmission)

Details

giscoR package

Package:	giscoR
Type:	Package
Version:	See sessionInfo() or DESCRIPTION file
Date:	2020
License:	GPL-3
LazyLoad:	yes

Note

COPYRIGHT NOTICE

When data downloaded from [this page](#) is used in any printed or electronic publication, in addition to any other provisions applicable to the whole Eurostat website, data source will have to be acknowledged in the legend of the map and in the introductory page of the publication with the following copyright notice:

- EN: (C) EuroGeographics for the administrative boundaries
- FR: (C) EuroGeographics pour les limites administratives
- DE: (C) EuroGeographics bezüglich der Verwaltungsgrenzen

For publications in languages other than English, French or German, the translation of the copyright notice in the language of the publication shall be used.

If you intend to use the data commercially, please contact EuroGeographics for information regarding their licence agreements.

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

[GISCO webpage](#)

References

See citation("giscoR")

See Also

Useful links:

- <https://dieghernan.github.io/giscoR/>
- <https://github.com/dieghernan/giscoR>
- Report bugs at <https://github.com/dieghernan/giscoR/issues>

gisco_attributions	<i>Attribution when publishing GISCO data</i>
--------------------	-----------------------------------------------

Description

Get the legal text to be used along with the data downloaded with this package

Usage

```
gisco_attributions(lang = "en", copyright = TRUE)
```

Arguments

lang	Language (two-letter ISO_639-1 code). See details.
copyright	Boolean. Whether to display the copyright notice or not on the console.

Details

Current languages supported are "en" (English), "da" (Danish), "de" (German), "es" (Spanish), "fi" (Finnish), "fr" (French), "no" (Norwegian) and "sv" (Swedish).

Consider contributing if you spot any mistake or want to add a new language.

Value

A string with the attribution to be used.

Note**COPYRIGHT NOTICE**

When data downloaded from [this page](#) is used in any printed or electronic publication, in addition to any other provisions applicable to the whole Eurostat website, data source will have to be acknowledged in the legend of the map and in the introductory page of the publication with the following copyright notice:

- EN: (C) EuroGeographics for the administrative boundaries
- FR: (C) EuroGeographics pour les limites administratives
- DE: (C) EuroGeographics bezüglich der Verwaltungsgrenzen

For publications in languages other than English, French or German, the translation of the copyright notice in the language of the publication shall be used.

If you intend to use the data commercially, please contact EuroGeographics for information regarding their licence agreements.

Examples

```
en <- gisco_attributions()
gisco_attributions(lang = "es", copyright = FALSE )
gisco_attributions(lang = "XXX")
```

gisco_coastallines	<i>World coastal lines</i> LINESTRING object
--------------------	----------------------------------------------

Description

A sf object including the coast lines as provided by GISCO (2016 version).

Format

A LINESTRING data frame (resolution: 1:20million, EPSG:4326) object with 8 variables:

EFTA_FLAG Coast belonging to EFTA countries

OTHR_FLAG Coast belonging to other countries

EU_FLAG Coast belonging to EU countries

COAS_FLAG Coast flag

CNTR_BN_ID CNTR_BN_ID

CC_FLAG Coast belonging to EU candidate countries

FID FID

geometry geometry field

Source

[GISCO .geojson source](#)

See Also[gisco_get_countries](#)**Examples**

```
library(sf)

coasts <- gisco_coastallines

plot(
  st_geometry(coasts),
  xlim = c(100, 120),
  ylim = c(-24, 24),
  col = "deepskyblue4",
  lwd = 2
)
box()
title(
  main = "Coasts on Southeastern Asia",
  sub = gisco_attributions(copyright = FALSE),
  cex.sub = 0.7,
  line = 1
)
```

gisco_countries	<i>World countries POLYGON object</i>
-----------------	---------------------------------------

Description

A sf object including all countries as provided by GISCO (2016 version).

Format

A MULTIPOLYGON data frame (resolution: 1:20million, EPSG:4326) object with 257 rows and 7 variables:

id row ID

CNTR_NAME Official country name on local language

ISO3_CODE **ISO 3166-1 alpha-3 code** of each country, as provided by GISCO

CNTR_ID Country ID

NAME_ENGL Country name in English

FID FID

geometry geometry field

Source

GISCO **.geojson source**

See Also

[gisco_get_countries](#)

Examples

```
library(sf)

cntry <- gisco_countries
GBR <- subset(cntry, ISO3_CODE == "GBR")

plot(st_geometry(GBR), col = "red3", border = "blue4")
title(sub = gisco_attributions(), line = 1)
```

gisco_countrycode	<i>Dataframe including Eurostat and ISO2 and ISO3 codes for countries and world regions</i>
-------------------	---------------------------------------------------------------------------------------------

Description

A dataframe containing conversions between different country codification systems (Eurostat/ISO2 and 3) as well as geographic regions as provided by the World Bank and the UN (M49).

Format

A data frame object with 249 rows and 12 variables:

CNTR_CODE Eurostat code of each country
iso2c ISO 3166-1 alpha-2 code of each country
ISO3_CODE ISO 3166-1 alpha-3 code of each country
iso.name.en ISO English short name
cldr.short.en English short name as provided by the [Unicode Common Locale Data Repository](#)
continent As provided by the World Bank
un.region.code Numeric region code UN (M49)
un.region.name Region name UN (M49)
un.regionintermediate.code Numeric intermediate Region code UN (M49)
un.regionintermediate.name Intermediate Region name UN (M49)
un.regionsub.code Numeric sub-region code UN (M49)
un.regionsub.name Sub-Region name UN (M49)

Source

codelist dataset from the countrycode v1.2.0 package.

See Also[codelist](#)**Examples**

```
# Head
head(gisco_countrycode)
```

```
gisco_get_coastallines
```

Download Coastal Lines from GISCO

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_coastallines(
  resolution = "60",
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL
)
```

Arguments

resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60" (1:60million), • "20" (1:20million) • "10" (1:10million) • "03" (1:3million) or • "01" (1:1million).
year	Release year. One of "2006", "2010", "2013" or "2016"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
cache	a logical whether to do caching. Default is TRUE.
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).

Value

a POLYGON object on sf format.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Coastal Lines

Examples

```
library(sf)

coastlines <- gisco_get_coastallines()
plot(st_geometry(coastlines), col = "palegreen", border = "lightblue3")
title(main = "Coastal Lines",
      sub = gisco_attributions(copyright = FALSE),
      line = 1)
```

gisco_get_communes

Download Geospatial Communes Data from GISCO

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_communes(
  year = "2016",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL
)
```


Arguments

year	Release year. One of "2001", "2004", "2006", "2008", "2010", "2013" or 2016
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from <code>tempdir</code> . The directory can also be set with <code>options(gisco_cache_dir = <path>)</code> .
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines • COASTL: coastlines - Multilines • INLAND: inland boundaries - Multilines
country	Optional. A character vector of country codes. See Details.

Details

country only available on specific datasets. Some spatial type datasets (as Multilines data-types) may not have country-level identifies.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

If you experience any problem on download, try to download the file by any other method and set `cache_dir = <folder>`.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Communes

See Also

[gisco_get_lau](#)

Examples

```
library(sf)

communes <- gisco_get_communes(country = c("BEL", "NLD", "LUX"))

plot(
  communes[, "CNTR_ID"],
  pal = c("black", "deepskyblue2", "orange"),
  border = "grey90",
  main = "Communes on Benelux (2016)",
  key.pos = NULL
)
title(sub = gisco_attributions(copyright = FALSE),
      line = 1.2,
      cex.sub = 0.8)
```

gisco_get_countries	<i>Download Geospatial Country Data from GISCO</i>
---------------------	----------------------------------------------------

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_countries(
  resolution = "60",
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL,
  region = NULL
)
```

Arguments

resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none">"60" (1:60million),"20" (1:20million)"10" (1:10million)"03" (1:3million) or"01" (1:1million).
------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

year	Release year. One of "2001", "2006", "2010", "2013", "2016" or "2020"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
cache	a logical whether to do caching. Default is TRUE.
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines • COASTL: coastlines - Multilines • INLAND: inland boundaries - Multilines
country	Optional. A character vector of countries. See Details
region	Optional. A character vector of UN M49 region codes. Possible values are "Africa", "Americas", "Asia", "Europe", "Oceania". See Details and gisco_countrycode

Details

country and region only available when applicable.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Countries

See Also

[gisco_countrycode](#)

Examples

```
library(sf)

sf_world <- gisco_get_countries()
plot(st_geometry(sf_world), col = "seagreen2")
title(sub = gisco_attributions(), line = 1)

sf_africa <- gisco_get_countries(region = 'Africa')
plot(st_geometry(sf_africa),
     col = c("springgreen4", "darkgoldenrod1", "red2"))
title(sub = gisco_attributions(), line = 1)

sf_benelux <-
  gisco_get_countries(resolution = "20",
                      country = c('Belgium', 'Netherlands', 'Luxembourg'))
plot(st_geometry(sf_benelux),
     col = c("grey10", "orange", "deepskyblue2"))
title(sub = gisco_attributions(), line = 1)
```

gisco_get_lau

Download Geospatial Local Administrative Units Data from GISCO

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_lau(
  year = "2016",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  country = NULL,
  gisco_id = NULL
)
```

Arguments

year	Release year. One of "2016", "2017", "2018" or "2019"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> "4326" - WGS84 "3035" - ETRS89 / ETRS-LAEA "3857" - Pseudo-Mercator

update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from <code>tempdir</code> . The directory can also be set with <code>options(gisco_cache_dir = <path>)</code> .
country	Optional. A character vector of country codes. See details
gisco_id	Optional. A character vector of GISCO_ID LAU values.

Details

See <https://ec.europa.eu/eurostat/web/nuts/local-administrative-units> for more detail about LAUs.

If you experience any problem on download, try to download the file by any other method and set `cache_dir = <folder>`.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a POLYGON object on sf format.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Local Administrative Units

See Also

[gisco_get_communes](#)

Examples

```
library(sf)

lau_esp <- gisco_get_lau(country = "España")

plot(
  st_geometry(lau_esp),
  xlim = c(0, 4),
  ylim = c(39, 42),
  col = "wheat",
  border = "grey50"
```

```
)

box()

title(
  main = "Spain LAU",
  sub = gisco_attributions(copyright = FALSE),
  line = 1,
  cex.sub = 0.8,
  font.sub = 3
)
```

gisco_get_nuts	<i>Download Geospatial NUTS Data from GISCO</i>
----------------	-------------------------------------------------

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_nuts(
  resolution = "60",
  year = "2016",
  epsg = "4326",
  nuts_level = "all",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL,
  nuts_id = NULL
)
```

Arguments

resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none">"60" (1:60million),"20" (1:20million)"10" (1:10million)"03" (1:3million) or"01" (1:1million).
year	Release year. One of "2003", "2006", "2010", "2013", "2016" or "2021".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">"4326" - WGS84

	<ul style="list-style-type: none"> • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
nuts_level	NUTS level. One of "0" (Country-level), "1", "2" or "3". See https://ec.europa.eu/eurostat/web/nuts/background .
cache	a logical whether to do caching. Default is TRUE.
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines
country	Optional. A character vector of country codes. See Details
nuts_id	Optional. A character vector of NUTS IDs.

Details

country only available when applicable. Some spatialtype datasets (as Multilines data-types) may not have country-level identifies.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO NUTS

See Also

[gisco_countrycode](#), [gisco_nuts](#)

Examples

```
library(sf)

nuts0 <- gisco_get_nuts(nuts_level = "0", epsg = "3035")
nuts3 <- gisco_get_nuts(nuts_level = "3", epsg = "3035")

plot(
  st_geometry(nuts3),
  xlim = c(2200000, 7150000),
  ylim = c(1380000, 5500000),
  lwd = 0.05,
  border = "grey40"
)
plot(st_geometry(nuts0),
  lwd = 2,
  add = TRUE)
title(
  main = "NUTS3 Levels on Europe",
  sub = gisco_attributions(copyright = FALSE),
  cex.sub = 0.7,
  line = 1
)
```

gisco_get_urban_audit *Download Geospatial Urban Audit Data from GISCO*

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_urban_audit(
  year = "2018",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  level = NULL,
  country = NULL
)
```

Arguments

year	Release year. One of "2014", "2018" or "2020"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA

	<ul style="list-style-type: none"> • "3857" - Pseudo-Mercator
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point
level	Level of Urban Audit. Possible values are 'CITIES', 'FUA', 'GREATER_CITIES' or NULL. See Details.
country	Optional. A character vector of country codes. See details.

Details

level = NULL would download the whole dataset including all levels

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Urban Audit

Examples

```
library(sf)

FUA <-
  gisco_get_urban_audit(
    year = "2020",
    epsg = "3035",
    level = "FUA",
    country = "Deutschland"
  )

countries <- gisco_get_countries(
  resolution = "20",
```

```

    year = "2020",
    epsg = "3035",
    country = "Deutschland"
  )

  plot(st_geometry(countries) ,
        col = "grey10", )
  plot(st_geometry(FUA),
        add = TRUE,
        col = "darkgoldenrod3")
  title(
    main = "FUA (Functional Urban Areas) \non Germany (2020)",
    sub = gisco_attributions(copyright = FALSE),
    cex.main = 0.8,
    cex.sub = 0.7,
    line = 1
  )
)

```

gisco_nuts

All NUTS POLYGON object

Description

A sf object including all NUTS levels as provided by GISCO (2016 version).

Format

A POLYGON data frame (resolution: 1:20million, EPSG:4326) object with 11 variables:

id row ID
COAST_TYPE COAST_TYPE
MOUNT_TYPE MOUNT_TYPE
NAME_LATN Name on Latin characters
CNTR_CODE Eurostat Country code
FID FID
NUTS_ID NUTS identifier
NUTS_NAME NUTS name on local alphabet
LEVL_CODE NUTS level code (0,1,2,3)
URBN_TYPE URBN_TYPE
geometry geometry field

Source

[GISCO .geojson source](#)

See Also[gisco_get_nuts](#)**Examples**

```
library(sf)

nuts <- gisco_nuts

italy <- subset(nuts, CNTR_CODE == "IT" & LEVL_CODE == 3)

plot(st_geometry(italy), col = c("springgreen4", "ivory", "red2"))
title(
  sub = gisco_attributions(copyright = FALSE),
  cex.sub = 0.7,
  font.sub = 3
)
```

Index

* package

giscoR-package, [2](#)

codelist, [7](#)

gisco_attributions, [3](#), [8](#), [9](#), [11](#), [13](#), [15](#), [17](#)

gisco_coastallines, [4](#)

gisco_countries, [5](#)

gisco_countrycode, [6](#), [11](#), [15](#)

gisco_get_coastallines, [7](#)

gisco_get_communes, [8](#), [13](#)

gisco_get_countries, [5](#), [6](#), [10](#)

gisco_get_lau, [9](#), [12](#)

gisco_get_nuts, [14](#), [19](#)

gisco_get_urban_audit, [16](#)

gisco_nuts, [15](#), [18](#)

giscoR (giscoR-package), [2](#)

giscoR-package, [2](#)

tempdir, [7](#), [9](#), [11](#), [13](#), [15](#), [17](#)