## Run | Debug

| | |
|---|---|
| shift+F10 | Run current file |
| alt+shift+F10 | Open Run dialog box |
| shift+F9 | Debug current file |
| alt+shift+F9 | Open Debug dialog box |
| ctrl+F8 | toggle line breakpoint |
| ctrl+F5 | rerun |
| F9 | resume |
| F8 | Step Over |
| F7 | Step Into |
| Shift + F8 | Step Out |
| Alt+F9 | Run to Curser |
| alf+F10 | Show Execution Point |
| ctrl+F2 | Stop |

## File Navigation

| | |
|---|---|
| ctrl+e | toggle between previous files |
| alt+shift+e | toggle between previous files with code |
| alt+home | navigate files from current dir |

## Code Navigation

| | |
|---|---|
| ctrl+F12 | Floating structure window |
| ctrl+G | navigate to line |

## Source Control

| | |
|---|---|
| ctrl+~ | git branches overview |

## Code Editing

| | |
|---|---|
| ctrl+I | Implement methods of an interface or abstract class |
| alt+enter | new line after current position |
| ctrl+y | delete line |
| ctrl+delete | delete to word end |
| ctrl+back-space | delete to word start |
| alt+j | select next under curser |
| alt_shift+j | select previous under curser |
| ctrl+alt+shift+j | select all under curser |

## Code Completion

| | |
|---|---|
| ctrl+space | code completion |
| ctrl+space+space | smart code compeltion |
| ctrl+p | Shows method's inputs |
| ctrl+i | implement methods |
| ctrl+o | overide methods |