

Assignment #1

Diego Oniarti

October 20, 2024

1 Big step - call by name

Write the operational semantics rules for a big-step, call-by-name reduction for ULC. Write the semantically correct ones only, but write them all

$\frac{}{v \Downarrow v}$	val
$\frac{t \Downarrow n' \quad t' \Downarrow n'' \quad n' \oplus n'' = n}{t \oplus t' \Downarrow n}$	bs-bop
$\frac{t \Downarrow \lambda x.t'' \quad t''[t'/x] \Downarrow v}{t \ t' \Downarrow v}$	bs-app
$\frac{t_1 \Downarrow v_1 \quad t_2 \Downarrow v_2}{\langle t_1, t_2 \rangle \Downarrow \langle v_1, v_2 \rangle}$	pair
$\frac{t \Downarrow \langle v, v' \rangle}{t.1 \Downarrow v}$	first-projection
$\frac{t \Downarrow \langle v', v \rangle}{t.2 \Downarrow v}$	first-projection
$\frac{t \Downarrow v}{inL \ t \Downarrow inL \ v}$	inLeft
$\frac{t \Downarrow v}{inR \ t \Downarrow inR \ v}$	inRight
$\frac{t \Downarrow inL \ v' \quad t_1[v'/x_1] \Downarrow v}{\text{case } t \text{ of } \left \begin{array}{l} inL \ x_1 \mapsto t_1 \\ inR \ x_2 \mapsto t_2 \end{array} \right. \Downarrow v}$	pattern matching L
$\frac{t \Downarrow inR \ v' \quad t_2[v'/x_2] \Downarrow v}{\text{case } t \text{ of } \left \begin{array}{l} inL \ x_1 \mapsto t_1 \\ inR \ x_2 \mapsto t_2 \end{array} \right. \Downarrow v}$	pattern matching R

2 Equivalence of SOS and COS

3 Distinguish terms

$$t \stackrel{def}{=} \lambda d : (\mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}) \rightarrow (\mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N} \\ .d \ (\lambda a : \mathbb{N}. \lambda b : \mathbb{N}. b) \ (\lambda i : \mathbb{N}. \lambda j : \mathbb{N}. i)$$

Reduction 1

$$\begin{array}{ll}
(\lambda d.d (\lambda a.\lambda b.b) (\lambda i.\lambda j.i)) (\lambda x.\lambda y.x \ 0 \ (y \ 0 \ 0)) & \rightsquigarrow \\
(\lambda x.\lambda y.x \ 0 \ (y \ 0 \ 0)) (\lambda a.\lambda b.b) (\lambda i.\lambda j.i) & \rightsquigarrow \\
(\lambda y.(\lambda a.\lambda b.b) \ 0 \ (y \ 0 \ 0)) (\lambda i.\lambda j.i) & \rightsquigarrow \\
(\lambda a.\lambda b.b) \ 0 \ ((\lambda i.\lambda j.i) \ 0 \ 0) & \rightsquigarrow \\
(\lambda b.b) ((\lambda i.\lambda j.i) \ 0 \ 0) & \rightsquigarrow \\
(\lambda b.b) ((\lambda j.0) \ 0) & \rightsquigarrow \\
(\lambda b.b) \ 0 & \rightsquigarrow \\
0 &
\end{array}$$

Reduction 2

$$\begin{array}{ll}
(\lambda d.d (\lambda a.\lambda b.b) (\lambda i.\lambda j.i)) (\lambda x.\lambda y.x \ 0 \ (y \ 1 \ 0)) & \rightsquigarrow \\
(\lambda x.\lambda y.x \ 0 \ (y \ 1 \ 0)) (\lambda a.\lambda b.b) (\lambda i.\lambda j.i) & \rightsquigarrow \\
(\lambda y.(\lambda a.\lambda b.b) \ 0 \ (y \ 1 \ 0)) (\lambda i.\lambda j.i) & \rightsquigarrow \\
(\lambda a.\lambda b.b) \ 0 \ ((\lambda i.\lambda j.i) \ 1 \ 0) & \rightsquigarrow \\
(\lambda b.b) ((\lambda i.\lambda j.i) \ 1 \ 0) & \rightsquigarrow \\
(\lambda b.b) ((\lambda j.1) \ 0) & \rightsquigarrow \\
(\lambda b.b) \ 1 & \rightsquigarrow \\
1 &
\end{array}$$

4 Safe untypable term

$$(\lambda x : \mathbb{N} \rightarrow \mathbb{N}.x) \ 1$$

typing derivation

$$\frac{\frac{x : \mathbb{N} \rightarrow \mathbb{N} \in \Gamma}{x : \mathbb{N} \rightarrow \mathbb{N} \vdash x : \mathbb{N} \rightarrow \mathbb{N}}^{\text{var}} \quad \frac{}{\emptyset \vdash \lambda x : \mathbb{N} \rightarrow \mathbb{N}.x : (\mathbb{N} \rightarrow \mathbb{N}) \rightarrow (\mathbb{N} \rightarrow \mathbb{N})}^{\text{lam}} \quad \frac{}{\emptyset \vdash 1 : \mathbb{N}}^{\text{nat}}}{\emptyset \vdash (\lambda x : \mathbb{N} \rightarrow \mathbb{N}.x) \ 1 : }^{\text{app}}$$

COS-SM-CBV

$$(\lambda x : \mathbb{N} \rightarrow \mathbb{N}.x) \ 1 \rightsquigarrow 1$$

5 Typing derivation

$$\frac{\frac{f : \mathbb{N} \rightarrow \mathbb{N} \in \Gamma}{\Gamma \vdash f : \mathbb{N} \rightarrow \mathbb{N}}^{\text{var}} \quad \frac{\frac{x : \mathbb{N} \in \Gamma'}{\Gamma' \vdash x : \mathbb{N}}^{\text{var}} \quad \frac{}{\Gamma' \vdash 2 : \mathbb{N}}^{\text{nat}}}{\Gamma' \vdash \lambda x.x + 2 : \mathbb{N} \rightarrow \mathbb{N}}^{\text{op}} \quad \frac{}{\Gamma \vdash 4 : \mathbb{N}}^{\text{nat}}}{\Gamma \vdash (\lambda x.x + 2) \ 4 : \mathbb{N}}^{\text{lam}} \quad \frac{}{\Gamma \vdash f : \mathbb{N} \rightarrow \mathbb{N} \vdash f ((\lambda x.x + 2) \ 4) : \mathbb{N}}^{\text{app}}$$

$$\begin{array}{c}
\frac{x : \mathbb{N} \rightarrow \mathbb{N} \in \Gamma' \quad y : \mathbb{N} \in \Gamma'}{\Gamma' \vdash x : \mathbb{N} \rightarrow \mathbb{N} \text{ var} \quad \Gamma' \vdash y : \mathbb{N} \text{ var}} \text{ app} \\
\frac{\Gamma' \left\{ \begin{array}{l} \Gamma, \\ x : \mathbb{N} \rightarrow \mathbb{N}, \vdash x \ y : \mathbb{N} \\ y : \mathbb{N} \end{array} \right.}{\Gamma, \frac{x : \mathbb{N} \rightarrow \mathbb{N}}{x : \mathbb{N} \rightarrow \mathbb{N}} \vdash \lambda y. x \ y : \mathbb{N} \rightarrow \mathbb{N}} \text{ lam} \\
\frac{\Gamma \vdash \lambda x. \lambda y. x \ y : (\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \mathbb{N} \rightarrow \mathbb{N}}{\Gamma \vdash (\lambda x. \lambda y. x \ y) \ f : \mathbb{N} \rightarrow \mathbb{N}} \text{ app} \quad \frac{f : \mathbb{N} \rightarrow \mathbb{N} \in \Gamma \text{ var}}{\Gamma \vdash f : \mathbb{N} \rightarrow \mathbb{N} \text{ var}} \text{ app} \\
\frac{\Gamma \vdash (\lambda x. \lambda y. x \ y) \ f : \mathbb{N} \rightarrow \mathbb{N} \quad \overline{\Gamma \vdash 3 : \mathbb{N}}^{\text{nat}}}{\Gamma \{ f : \mathbb{N} \rightarrow \mathbb{N} \vdash ((\lambda x. \lambda y. x \ y) \ f) \ 3 : \mathbb{N}} \text{ app}
\end{array}$$

6 Encoding

Sequencing

$$\begin{array}{l}
t ::= \dots | t; t' \\
(\lambda x. t') \ t
\end{array}$$

(Assuming x is a free variable not used in x)

Let-in

$$\begin{array}{l}
t ::= \dots | \text{let } x = t \text{ in } t' \\
(\lambda x. t') \ t
\end{array}$$

Arrays of Length 4

$$\begin{array}{l}
t ::= \dots | [t, t, t, t] \\
v ::= \dots | [v, v, v, v] \\
[a, b, c, d] \equiv \langle \langle a, b \rangle, \langle c, d \rangle \rangle
\end{array}$$

Array field access

$$\begin{array}{l}
t ::= \dots | t.i \ (i \in 0..3) \\
t.0 \equiv t.0.0 \\
t.1 \equiv t.0.1 \\
t.2 \equiv t.1.0 \\
t.3 \equiv t.1.1
\end{array}$$

Array update

$$\begin{array}{l}
t ::= \dots | t.i = t \ (i \in 0..3) \\
t.0 = t' \equiv \langle \langle t', t.0.1 \rangle, \langle t.1.0, t.1.1 \rangle \rangle
\end{array}$$