

# Bootstrap Classes Reference

 w3schools.com/bootstrap/bootstrap\_ref\_all\_classes.asp

Class	Description	Example	Category
<code>.active</code>	Adds a grey background color to the <b>table</b> row ( <code>&lt;tr&gt;</code> or table cell ( <code>&lt;td&gt;</code> ) (same color used on hover)	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.active</code>	Adds a gray background color to the active link in a default <b>navbar</b> . Adds a black background and a white color to the current link inside an inverted navbar.	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.active</code>	Adds a blue background color to the active <b>list item</b> in a list group	<a href="#">Try it</a>	<a href="#">List Groups</a>
<code>.active</code>	Adds a blue background color to simulate a "pressed" <b>button</b>	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.active</code>	Animates a striped <b>progress bar</b>	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.active</code>	Adds a blue background color to the active <b>dropdown item</b> in a dropdown	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.active</code>	Adds a blue background color to the active <b>pagination</b> link (to highlight the current page)	<a href="#">Try it</a>	<a href="#">Pagination</a>
<code>.affix</code>	The Affix plugin allows an element to become affixed (locked/sticky) to an area on the page. It toggles <code>position:fixed</code> on and off	<a href="#">Try it</a>	<a href="#">Affix</a>
<code>.alert</code>	Creates an alert message box	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.alert-danger</code>	Red alert box. Indicates a dangerous or potentially negative action	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.alert-dismissible</code>	Together with the <code>.close</code> class, this class is used to close the alert	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.alert-info</code>	Light-blue alert box. Indicates some information	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.alert-link</code>	Used on links inside alerts to add matching colored links	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.alert-success</code>	Green alert box. Indicates a successful or positive action	<a href="#">Try it</a>	<a href="#">Alerts</a>

Class	Description	Example	Category
<code>.alert-warning</code>	Yellow alert box. Indicates caution should be taken with this action	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.badge</code>	Creates a circular badge (grey circle - often used as a numerical indicator)	<a href="#">Try it</a>	<a href="#">Badges</a>
<code>.bg-danger</code>	Adds a red background color to an element. Represents danger or a negative action	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.bg-info</code>	Adds a light-blue background color to an element. Represents some information	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.bg-primary</code>	Adds a blue background color to an element. Represents something important	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.bg-success</code>	Adds a green background color to an element. Indicates success or a positive action	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.bg-warning</code>	Adds a yellow background color to an element. Represents a warning or a negative action	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.breadcrumb</code>	A pagination. Indicates the current page's location within a navigational hierarchy	<a href="#">Try it</a>	<a href="#">Pagination</a>
<code>.btn</code>	Creates a basic button (gray background and rounded corners)	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-block</code>	Creates a block level button that spans the entire width of the parent element	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-danger</code>	Red button. Indicates danger or a negative action	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-default</code>	Default button. White background and grey border	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-group</code>	Groups buttons together on a single line	<a href="#">Try it</a>	<a href="#">Button Groups</a>
<code>.btn-group-justified</code>	Makes a group of buttons span the entire width of the screen	<a href="#">Try it</a>	<a href="#">Button Groups</a>
<code>.btn-group-lg</code>	Large button group (makes all buttons in a button group larger - increased font-size and padding)	<a href="#">Try it</a>	<a href="#">Button Groups</a>
<code>.btn-group-sm</code>	Small button group (makes all buttons in a button group smaller)	<a href="#">Try it</a>	<a href="#">Button Groups</a>
<code>.btn-group-xs</code>	Extra small button group (makes all buttons in a button group extra small)	<a href="#">Try it</a>	<a href="#">Button Groups</a>

Class	Description	Example	Category
<code>.btn-group-vertical</code>	Makes a button group appear vertically stacked	<a href="#">Try it</a>	<a href="#">Button Groups</a>
<code>.btn-info</code>	Light-blue button. Represents information	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-link</code>	Makes a button look like a link (get button behavior)	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-lg</code>	Large button	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-primary</code>	Blue button.	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-sm</code>	Small button	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-success</code>	Green button. Indicates success or a positive action	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-warning</code>	Yellow button. Represents warning or a negative action	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.btn-xs</code>	Extra small button	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.caption</code>	Adds a caption text inside a <code>.thumbnail</code>	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.caret</code>	Creates a caret arrow icon , which indicates that the button is a dropdown	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.carousel</code>	Creates a carousel (slideshow)	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.carousel-caption</code>	Creates a caption text for each slide in the carousel	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.carousel-control</code>	Container for next and previous links	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.carousel-indicators</code>	Adds little dots/indicators at the bottom of each slide (which indicates how many slides there is in the carousel, and which slide the user are currently viewing)	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.carousel-inner</code>	Container for slide items	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.center-block</code>	Centers any element (Sets an element to <code>display:block</code> with <code>margin-right:auto</code> and <code>margin-left:auto</code> )	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.checkbox</code>	Container for checkboxes	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.checkbox-inline</code>	Makes multiple checkboxes appear on the same line	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.clearfix</code>	Clears floats	<a href="#">Try it</a>	<a href="#">Helpers</a>

Class	Description	Example	Category
<code>.close</code>	Indicates a close icon	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.col-**-*</code>	Responsive grid (span 1-12 column). Extra small devices Phones (< 768px), Small devices Tablets (≥768px), Medium devices Desktops (≥992px), Large devices Desktops (≥1200px). Column values can be 1-12.	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.col-**-offset-*</code>	Move columns to the right. These classes increase the left margin of a column by * columns	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.col-**-pull-*</code>	Changes the order of the grid columns	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.col-**-push-*</code>	Changes the order of the grid columns	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.collapse</code>	Indicates collapsible content - which can be hidden or shown on demand	<a href="#">Try it</a>	<a href="#">Collapse</a>
<code>.collapse in</code>	Show the collapsible content by default	<a href="#">Try it</a>	<a href="#">Collapse</a>
<code>.container</code>	Fixed width container with widths determined by screen sites. Equal margin on the left and right.	<a href="#">Try it</a>	<a href="#">Containers</a>
<code>.container-fluid</code>	A container that spans the full width of the screen	<a href="#">Try it</a>	<a href="#">Containers</a>
<code>.control-label</code>	Allows a label to be used for form validation	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.danger</code>	Adds a red background to the table row ( <code>&lt;tr&gt;</code> ) or table cell ( <code>&lt;td&gt;</code> ). Indicates a dangerous or potentially negative action	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.disabled</code>	Disables a <b>button</b> (adds opacity and a "no-parking-sign" icon on hover)	<a href="#">Try it</a>	<a href="#">Buttons</a>
<code>.disabled</code>	Disables a <b>dropdown</b> item (adds a grey text color and a "no-parking-sign" icon on hover)	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.disabled</code>	Disables a <b>pagination</b> link (cannot be clicked - adds a grey text color and a "no-parking-sign" icon on hover)	<a href="#">Try it</a>	<a href="#">Pagination</a>
<code>.disabled</code>	Disables a <b>list</b> item in a list group (cannot be clicked - adds a grey background color and a "no-parking-sign" icon on hover)	<a href="#">Try it</a>	<a href="#">List Groups</a>

Class	Description	Example	Category
<code>.divider</code>	Used to separate links in the dropdown menu with a thin horizontal border	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dl-horizontal</code>	Lines up the terms <code>&lt;dt&gt;</code> and descriptions <code>&lt;dd&gt;</code> in <code>&lt;dl&gt;</code> elements side-by-side. Starts off like default <code>&lt;dl&gt;</code> s, but when the browser window expands, it will line up side-by-side	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.dropdown</code>	Creates a toggleable menu that allows the user to choose one value from a predefined list	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dropdown-header</code>	Used to add headers inside the dropdown menu	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dropdown-menu</code>	Adds the default styles for the dropdown menu container	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dropdown-menu-right</code>	Right-aligns a dropdown menu	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dropdown-toggle</code>	Used on the button that should hide and show (toggle) the dropdown menu	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.dropup</code>	Indicates a dropup menu (upwards instead of downwards)	<a href="#">Try it</a>	<a href="#">Dropdowns</a>
<code>.embed-responsive</code>	Container for embedded content. Makes videos or slideshows scale properly on any device	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.embed-responsive-16by9</code>	Container for embedded content. Creates an 16:9 aspect ratio embedded content	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.embed-responsive-4by3</code>	Container for embedded content. Creates an 4:3 aspect ratio embedded content	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.embed-responsive-item</code>	Used inside <code>.embed-responsive</code> . Scales the video nicely to the parent element	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.fade</code>	Adds a fading effect when closing an alert box	<a href="#">Try it</a>	<a href="#">Alerts</a>
<code>.form-control</code>	Used on input, textarea, and select elements to span the entire width of the page and make them responsive	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.form-control-feedback</code>	Form validation class	<a href="#">Try it</a>	<a href="#">Inputs 2</a>

Class	Description	Example	Category
<code>.form-control-static</code>	Adds plain text next to a form label within a horizontal form	<a href="#">Try it</a>	<a href="#">Inputs 2</a>
<code>.form-group</code>	Container for form input and label	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.form-inline</code>	Makes a <code>&lt;form&gt;</code> left-aligned with inline-block controls (This only applies to forms within viewports that are at least 768px wide)	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.form-horizontal</code>	Aligns labels and groups of form controls in a horizontal layout	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.glyphicon</code>	Creates an icon. Bootstrap provides 260 free glyphs from the <a href="#">Glyphicons</a> Halflings set	<a href="#">Try it</a>	<a href="#">Glyphicons</a>
<code>.has-danger</code>	Adds a red color to the label and a red border to the input, as well as an error icon inside the input (used together with <code>.has-feedback</code> )	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.has-feedback</code>	Adds feedback icons for inputs (checkmark, warning and error signs)	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.has-success</code>	Adds a green color to the label and a green border to the input, as well as a checkmark icon inside the input (used together with <code>.has-feedback</code> )	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.has-warning</code>	Adds a yellow/orange color to the label and a yellow/orange border to the input, as well as a checkmark icon inside the input (used together with <code>.has-feedback</code> )	<a href="#">Try it</a>	<a href="#">Forms</a>
<code>.help-block</code>	A block of help text that breaks onto a new line and may extend beyond one line.	<a href="#">Try it</a>	<a href="#">Input Sizing</a>
<code>.hidden</code>	Forces an element to be hidden ( <code>display:none</code> )	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.hidden-*</code>	Hides content depending on screen size	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.hide</code>	Deprecated. Use <code>.hidden</code> instead	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.h1 - .h6</code>	Makes an element look like a heading of the chosen class (h1-h6)	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.icon-bar</code>	Used in the navbar to create a hamburger menu (three horizontal bars)	<a href="#">Try it</a>	<a href="#">Navbar</a>

Class	Description	Example	Category
<code>.icon-next</code>	Unicode icon (arrow pointing right), used in carousels. This is often replaced with a glyphicon	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.icon-prev</code>	Unicode icon (arrow pointing left), used in carousels. This is often replaced with a glyphicon	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.img-circle</code>	Shapes an image to a circle (not supported in IE8 and earlier)	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.img-responsive</code>	Makes an image responsive	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.img-rounded</code>	Adds rounded corners to an image	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.img-thumbnail</code>	Shapes an image to a thumbnail (borders)	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.in</code>	Fades in tabs	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.info</code>	Adds a light-blue background to the table row ( <code>&lt;tr&gt;</code> ) or table cell ( <code>&lt;td&gt;</code> ). Indicates a neutral informative change or action	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.initialism</code>	Displays the text inside an <code>&lt;abbr&gt;</code> element in a slightly smaller font size	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.input-group</code>	Container to enhance an input by adding an icon, text or a button in front or behind it as a "help text"	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.input-group-lg</code>	Large input group	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.input-group-sm</code>	Small input group	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.input-group-addon</code>	Together with the <code>.input-group</code> class, this class makes it possible to add an icon or help text next to the input field	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.input-group-btn</code>	Together with the <code>.input-group</code> class, this class attaches a button next to an input. Often used as a search bar	<a href="#">Try it</a>	<a href="#">Inputs</a>
<code>.input-lg</code>	Large input field	<a href="#">Try it</a>	<a href="#">Input Sizing</a>
<code>.input-sm</code>	Small input field	<a href="#">Try it</a>	<a href="#">Input Sizing</a>
<code>.invisible</code>	Makes an element invisible ( <code>visibility:hidden</code> ). <b>Note:</b> Even though the element is invisible, it will take up space on the page	<a href="#">Try it</a>	<a href="#">Helpers</a>

Class	Description	Example	Category
<code>.item</code>	Class added to each carousel item. May be text or images	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.jumbotron</code>	Creates a padded grey box with rounded corners that enlarges the font sizes of the text inside it. Creates a big box for calling extra attention to some special content or information	<a href="#">Try it</a>	<a href="#">Jumbotron</a>
<code>.label</code>	Adds a grey rounded box to an element. Provides additional information about something (e.g. "New")	<a href="#">Try it</a>	<a href="#">Labels</a>
<code>.label-danger</code>	Red label	<a href="#">Try it</a>	<a href="#">Labels</a>
<code>.label-info</code>	Light-blue label	<a href="#">Try it</a>	<a href="#">Labels</a>
<code>.label-success</code>	Green label	<a href="#">Try it</a>	<a href="#">Labels</a>
<code>.label-warning</code>	Yellow label	<a href="#">Try it</a>	<a href="#">Labels</a>
<code>.lead</code>	Increase the font size and line height of a paragraph	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.left</code>	Used to identify the left carousel control	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.list-group</code>	Creates a bordered list group for <code>&lt;li&gt;</code> elements	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item</code>	Added to each <code>&lt;li&gt;</code> element in the list group	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-heading</code>	Creates a list group heading (used on other elements besides <code>&lt;li&gt;</code> )	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-text</code>	Used for item text inside the list group (used on other elements besides <code>&lt;li&gt;</code> )	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-danger</code>	Red background color for a list item in a list group	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-info</code>	Light-blue background color for a list item in a list group	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-success</code>	Green background color for a list item in a list group	<a href="#">Try it</a>	<a href="#">List Group</a>
<code>.list-group-item-warning</code>	Yellow background color for a list item in a list group	<a href="#">Try it</a>	<a href="#">List Group</a>



Class	Description	Example	Category
<code>.list-inline</code>	Places all list items on a single line (horizontal menu)	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.list-unstyled</code>	Removes all default list-style (bullets, left margin, etc.) styling from a <code>&lt;ul&gt;</code> or <code>&lt;ol&gt;</code> list	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.mark</code>	Highlights text: Highlighted text	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.media</code>	Aligns media objects (like images or videos - often used for comments in a blog post etc)	<a href="#">Try it</a>	<a href="#">Media Objects</a>
<code>.media-body</code>	Text that should appear next to a media object	<a href="#">Try it</a>	<a href="#">Media Objects</a>
<code>.media-heading</code>	Creates a heading inside the media object	<a href="#">Try it</a>	<a href="#">Media Objects</a>
<code>.media-list</code>	Nested media lists	<a href="#">Try it</a>	<a href="#">Media Objects</a>
<code>.media-object</code>	Indicates a media object (image or video)	<a href="#">Try it</a>	<a href="#">Media Objects</a>
<code>.modal</code>	Identifies the content as a modal and brings focus to it	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-body</code>	Defines the style for the body of the modal. Add any HTML markup here (p, img, etc)	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-content</code>	Styles the modal (border, background-color, etc). Inside this, add the modal's header, body and footer, if needed	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-dialog</code>	Sets the proper width and margin of the modal	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-footer</code>	The footer of the modal (often contains an action button and a close button)	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-header</code>	The header of the modal (often contains a title and a close button)	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-lg</code>	Large modal (wider than default)	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-open</code>	Used on the <code>&lt;body&gt;</code> element to prevent page scrolling ( <code>overflow:hidden</code> )	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-sm</code>	Small modal (less width)	<a href="#">Try it</a>	<a href="#">Modals</a>
<code>.modal-title</code>	The title of the modal	<a href="#">Try it</a>	<a href="#">Modals</a>

Class	Description	Example	Category
<code>.nav nav-tabs</code>	Indicates a tabbed menu	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.nav nav-pills</code>	Indicates a pill menu	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.nav .navbar-nav</code>	Used on a <code>&lt;ul&gt;</code> container that contains the list items with links inside a navigation bar	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.nav-justified</code>	Centers tabs/pills. Note that on screens smaller than 768px the items are stacked (content will remain centered)	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.nav-stacked</code>	Vertically stack tabs or pills	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.nav-tabs</code>	Creates a tabbed menu	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.navbar</code>	Creates a navigation bar	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-brand</code>	Added to a link or a header element inside the navbar to represent a logo or a header	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-btn</code>	Vertically aligns a button inside a navbar	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-collapse</code>	Collapses the navbar (hidden and replaced with a menu/hamburger icon on mobile phones and small tablets)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-default</code>	Creates a default navigation bar (light-grey background color)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-fixed-bottom</code>	Makes the navbar stay at the bottom of the screen (sticky/fixed)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-fixed-top</code>	Makes the navbar stay at the top of the screen (sticky/fixed)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-form</code>	Added to form elements inside the navbar to vertically center them (proper padding)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-header</code>	Added to a container element that contains the link/element that represent a logo or a header	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-inverse</code>	Creates a black navigation bar (instead of light-grey)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-left</code>	Aligns nav links, forms, buttons, or text, in the navbar to the left	<a href="#">Try it</a>	<a href="#">Navbar</a>

Class	Description	Example	Category
<code>.navbar-link</code>	Styles an element to look like a link inside the navbar (anchors get proper padding and an underline on hover, while other elements like p or span gets a default hover effect - white color in an inversed navbar and a black color in a default navbar)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-nav</code>	Used on a <code>&lt;ul&gt;</code> container that contains the list items with links inside a navigation bar	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-right</code>	Aligns nav links, forms, buttons, or text in the navbar to the right.	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-static-top</code>	Removes left, top and right borders (rounded corners) from the navbar (default navbar has a gray border and a 4px border-radius by default)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-text</code>	Vertical align any elements inside the navbar that are not links (ensures proper padding)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.navbar-toggle</code>	Styles the button that should open the navbar on small screens. Often used together with three <code>.icon-bar</code> classes to indicate a toggleable menu icon (hamburger/bars)	<a href="#">Try it</a>	<a href="#">Navbar</a>
<code>.next</code>	Used in the carousel control to identity the next control	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.next</code>	Used to align pager buttons to the right side of the page (next button)	<a href="#">Try it</a>	<a href="#">Pager</a>
<code>.page-header</code>	Adds a horizontal line under the heading (+ adds some extra space around the element)	<a href="#">Try it</a>	<a href="#">Page Header</a>
<code>.pager</code>	Creates previous/next buttons (used on <code>&lt;ul&gt;</code> elements)	<a href="#">Try it</a>	<a href="#">Pager</a>
<code>.pagination</code>	Creates a pagination (Useful when you have a web site with lots of pages. Used on <code>&lt;ul&gt;</code> elements)	<a href="#">Try it</a>	<a href="#">Pagination</a>
<code>.pagination-lg</code>	Large pagination (each pagination link gets a font-size of 18px. Default is 14px)	<a href="#">Try it</a>	<a href="#">Pagination</a>
<code>.pagination-sm</code>	Small pagination (each pagination link gets a font-size of 12px. Default is 14px)	<a href="#">Try it</a>	<a href="#">Pagination</a>

Class	Description	Example	Category
<code>.panel</code>	Creates a bordered box with some padding around its content	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-body</code>	Container for content inside the panel	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-collapse</code>	Collapsible panel (toggle between hiding and showing panel(s))	<a href="#">Try it</a>	<a href="#">Collapse</a>
<code>.panel-danger</code>	Red panel. Indicates danger	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-info</code>	Light-blue panel. Indicates information	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-success</code>	Green panel. Indicates success	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-warning</code>	Yellow panel. Indicates warning	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-footer</code>	Creates a panel footer (light background color)	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-group</code>	Used to group many panels together. This removes the bottom margin below each panel	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-heading</code>	Creates a panel header (light background color)	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.panel-title</code>	Used inside a <code>.panel-heading</code> to adjust the styling of the text (removes margins and adds a font-size of 16px)	<a href="#">Try it</a>	<a href="#">Panels</a>
<code>.popover</code>	Popup-box that appears when the user clicks on an element	<a href="#">Try it</a>	<a href="#">Popover</a>
<code>.pre-scrollable</code>	Makes a <code>&lt;pre&gt;</code> element scrollable ( <code>max-height</code> of 350px and provide a y-axis scrollbar)	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.prev</code>	Used in carousels to indicate a "previous" link	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.previous</code>	Used to align pager buttons to the left side of the page (previous button)	<a href="#">Try it</a>	<a href="#">Pager</a>
<code>.progress</code>	Container for progress bars	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.progress-bar</code>	Creates a progress bar	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.progress-bar-danger</code>	Red progress bar. Indicates danger	<a href="#">Try it</a>	<a href="#">Progress Bars</a>

Class	Description	Example	Category
<code>.progress-bar-info</code>	Light-blue progress bar. Indicates information	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.progress-bar-striped</code>	Creates a striped progress bar	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.progress-bar-success</code>	Green progress bar. Indicates success	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.progress-bar-warning</code>	Yellow progress bar. Indicates warning	<a href="#">Try it</a>	<a href="#">Progress Bars</a>
<code>.pull-left</code>	Float an element to the left	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.pull-right</code>	Float an element to the right	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.right</code>	Used to identify the right carousel control	<a href="#">Try it</a>	<a href="#">Carousel</a>
<code>.row</code>	Container for responsive columns	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.row-no-gutters</code>	Removes the gutters from a row and its columns	<a href="#">Try it</a>	<a href="#">Grid</a>
<code>.show</code>	Shows an element ( <code>display:block</code> )	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.small</code>	Creates a lighter, secondary text in any heading	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.sr-only</code>	Hides an element on all devices except for screen readers	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.sr-only-focusable</code>	Hides an element on all devices except for screen readers	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.success</code>	Adds a green background color to a table row ( <code>&lt;tr&gt;</code> ) or table cell ( <code>&lt;td&gt;</code> ). Indicates success or a positive action	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.tab-content</code>	Used together with <code>.tab-pane</code> to creates toggleable/dynamic tabs/pills	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.tab-pane</code>	Used together with <code>.tab-content</code> to creates toggleable/dynamic tabs/pills	<a href="#">Try it</a>	<a href="#">Tabs</a>
<code>.table</code>	Adds basic styling to a table (padding, bottom borders, etc)	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.table-bordered</code>	Adds borders on all sides of the table and cells	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.table-condensed</code>	Makes a table more compact by cutting cell padding in half	<a href="#">Try it</a>	<a href="#">Tables</a>

Class	Description	Example	Category
<code>.table-hover</code>	Creates a hoverable table (adds a grey background color on table rows on hover)	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.table-responsive</code>	Makes a table responsive (adds a horizontal scrollbar when needed)	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.text-capitalize</code>	Indicates capitalized text	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-center</code>	Center-aligns text	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-danger</code>	Red text color. Indicates danger	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-hide</code>	Hides text (helps replace an element's text content with a background image)	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-info</code>	Light-blue text color. Indicates information	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-justify</code>	Indicates justified text	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-left</code>	Aligns the text to the left	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-lowercase</code>	Changes text to lowercase	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-muted</code>	Grey text color	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-nowrap</code>	Prevents the text from wrapping	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-primary</code>	Blue text color	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-right</code>	Aligns text to the right	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-success</code>	Green text color. Indicates success	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-uppercase</code>	Makes text uppercase	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.text-warning</code>	Yellow/orange text color. Indicates warning	<a href="#">Try it</a>	<a href="#">Typography</a>
<code>.thumbnail</code>	Adds a border around an element (often images or videos) to make it look like a thumbnail	<a href="#">Try it</a>	<a href="#">Images</a>
<code>.tooltip</code>	Popup-box that appears when the user moves the mouse pointer over an element	<a href="#">Try it</a>	<a href="#">Tooltip</a>

Class	Description	Example	Category
<code>.visible-*</code>	Deprecated as of v3.2.0. Used to show and/or hide content by device. <b>Note:</b> Use <code>.hidden-*</code> instead	<a href="#">Try it</a>	<a href="#">Helpers</a>
<code>.visible-print-block</code>	Displays the element ( <code>display:block</code> ) in print (pre)view		<a href="#">Helpers</a>
<code>.visible-print-inline</code>	Displays the element ( <code>display:inline</code> ) in print (pre)view		<a href="#">Helpers</a>
<code>.visible-print-inline-block</code>	Displays the element ( <code>display:inline-block</code> ) in print (pre)view		<a href="#">Helpers</a>
<code>.hidden-print</code>	Hides the element ( <code>display:none</code> ) in print (pre)view		<a href="#">Helpers</a>
<code>.warning</code>	Adds a yellow background color to the table row ( <code>&lt;tr&gt;</code> ) or table cell ( <code>&lt;td&gt;</code> ). Indicates a warning	<a href="#">Try it</a>	<a href="#">Tables</a>
<code>.well</code>	Adds a rounded border around an element with a gray background color and some padding	<a href="#">Try it</a>	<a href="#">Wells</a>
<code>.well-lg</code>	Large well (more padding)	<a href="#">Try it</a>	<a href="#">Wells</a>
<code>.well-sm</code>	Small well (less padding)	<a href="#">Try it</a>	<a href="#">Wells</a>