

Instructions for Authors of SBC Conferences

Papers and Abstracts

Diego Dimer Rodrigues¹, Mariana R Mendoza¹

¹Instituto de Informática – Universidade Federal do Rio Grande do Sul (UFRGS)
Caixa Postal 15.064 – 91.501-970 – Porto Alegre – RS – Brazil

{ddrodrigues, mrmendoza}@inf.ufrgs.br

Abstract. *This meta-paper describes the style to be used in articles and short papers for SBC conferences. For papers in English, you should add just an abstract while for the papers in Portuguese, we also ask for an abstract in Portuguese (“resumo”). In both cases, abstracts should not have more than 10 lines and must be in the first page of the paper.*

1. Introduction

Machine learning (ML) is increasingly used in various domains, including Health, where it assists in diagnosis, prognosis, and treatment [Chen et al. 2021]. However, ML algorithms can potentially introduce biases, leading to unfair and potentially harmful outcomes [Obermeyer et al. 2019, Juhn et al. 2022].

This work aims to measure the risk of bias in Health datasets using pre-training bias metrics and assesses their impact on the performance of supervised ML algorithms, correlating the bias metrics to the overall models’ performance. We analyze four pre-training bias metrics [Hardt et al. 2021]: Class Imbalance (CI), Kullback-Leibler (KL) Divergence, Kolmogorov-Smirnov (KS), and Conditional Demographic Disparity in Labels (CDDL).

1.1. Class Imbalance (CI)

CI measures the representation of different classes within a dataset. It ranges from -1 to 1, with values near zero indicating balanced representation. Positive values indicate overrepresentation of the advantaged group, while negative values indicate overrepresentation of the disadvantaged group.

1.2. Kullback-Leibler (KL) Divergence

KL Divergence measures the divergence between the label distributions of two facets. It ranges from 0 to $+\infty$, with values near zero indicating similar distributions and higher values indicating greater divergence.

1.3. Kolmogorov-Smirnov (KS)

KS measures the maximum divergence between labels in the distribution for different facets. It ranges from 0 to 1, with values near zero indicating evenly distributed labels and values near one indicating unbalanced labels.

1.4. Conditional Demographic Disparity in Labels (CDDL)

CDDL measures the proportion of negative outcomes in a specific facet of a dataset. It ranges from -1 to 1, with positive values indicating demographic disparity favoring the advantaged group and negative values indicating disparity favoring the disadvantaged group.

2. References

References

- Chen, I. Y., Pierson, E., Rose, S., Joshi, S., Ferryman, K., and Ghassemi, M. (2021). Ethical machine learning in healthcare. *Annual Review of Biomedical Data Science Annu. Rev. Biomed. Data Sci*, 2021:123–144.
- Hardt, M., Chen, X., Cheng, X., Donini, M., Gelman, J., Gollaprolu, S., He, J., Larroy, P., Liu, X., McCarthy, N., Rathi, A., Rees, S., Siva, A., Tsai, E., Vasist, K., Yilmaz, P., Zafar, M. B., Das, S., Haas, K., Hill, T., and Kenthapadi, K. (2021). Amazon sagemaker clarify: Machine learning bias detection and explainability in the cloud. *ArXiv*.
- Juhn, Y. J., Ryu, E., Wi, C.-I., King, K. S., Malik, M., Romero-Brufau, S., Weng, C., Sohn, S., Sharp, R. R., and Halamka, J. D. (2022). Assessing socioeconomic bias in machine learning algorithms in health care: a case study of the houses index. *Journal of the American Medical Informatics Association*, 29(7):1142–1151.
- Obermeyer, Z., Powers, B., Vogeli, C., and Mullainathan, S. (2019). Dissecting racial bias in an algorithm used to manage the health of populations. *Science*, 366(6464):447–453.