SSCHA input file cheatsheet

&inputsscha

t: The temperature used to generate the ensemble (in Kelvin). [REQUIRED]

tg: The temperature that will be used in the minimization (in Kelvin).

lambda_a : ***[...]***

 $lambda_w:$

minim_struc :

 $precond_wyck:$

preconditioning:

root_representation:

 $neglect_symmetries:$

 $n_random_eff:$

n_random: The dimension of the ensemble

 $meaningful_factor:$ The stopping criteria. The code will end the

minimization after the gradient is lower than meaningful-factor times its stochastic error.

eq_energy : Set the equilibrium energy. It should be the en-

ergy of the structure without fluctuations, it is used to separate the electronic and the vibrational energy, since they are usually of different order of magnitude. It is measured in Ry.

fildyn_prefix : [REQUIRED]

 $\mbox{nqirr}: \mbox{[REQUIRED]} \ \ \mbox{The} \ \ \mbox{number} \ \ \mbox{of} \ \ \mbox{irriducible} \ \ \mbox{q}$

points (just look how many dynamical-matrixes

files are there).

data_dir: The position of the ensemble (where the data

are stored). Unit of measurements must be in bohr for displacements and Ry/bohr for forces and $Ry/bohr^3$ for stress tensors. Energy is in

Ry.

load_bin:

supercell_size: "The supercell size.

max_ka:

 $stress_offset:$

&inputsscha

gradi_op: Which gradient is used to trigger the stopping condition. By default, both of them should satisfy the meaningufl criteria. Options are "all", "gc", and "gw".

- 1. "all" both the gradient should satisfy the meaningulf (default)
- 2. "gw" only the wyckoff (i.e. structure) gradient.
- 3. "gc" only the force-constant matrix gradient

population: The population id. This is an integer that distinguish different ensembles and allows for use the same data_dir for several minimizations.

print_stress:

use_spglib:

&relax

type: [REQUIRED]

- "sscha"

- "relax"

- "vc-relax"

n_configs : [REQUIRED]

 \max_pop_id :

 $start_pop:$

 $ensemble_datadir:$

 $generate_ensemble:$

 $target_pressure:$

 $fix_volume:$

bulk_modulus:

 $sobol_sampling:$

sobol_scatter:

&calculator

 $k_{-}points: [REQUIRED]$

 $k_{-}offset:$

 $disable_check:$

program : [REQUIRED]

binary:

 $pseudo_{-}:$

1. "quantum-espresso"

• "ecutrho", "ecutwfc", "smearing", "degauss", "occupations", "conv_thr", "tstress", "tprnfor", "verbosity", "disk_io", "input_dft", "use_all_frac"

&utils

utils: "save_freq_filename" "save_rho_filename"

"mu_lock_start" "mu_free_end" "project_dyn"

"project_structure"

&cluster

template: "SSCHA_CLUSTERS_DIR" "hostname" "pwd"
 "account" "binary_path" "mpicmd" "reconnect_attempts" "port"

"shell" "submit_cmd" "queue_directive"
 "v_nodes" "n_nodes" "use_nodes" "v_cpu"
 "n_cpu" "use_cpu" "v_time" "n_time"
 "n_pools" "use_time" "v_memory" "max_ram"
 "use_memory" "v_partition" "partition_name"
 "use_partition" "init_script" "max_recalc"
 "batch_size" "local_workdir" "v_account"
 "use_account" "sshcmd" "scpcmd" "timeout"
 "job_numbers" "n_together"
 "workdir"

```
The input file perform the minimization.
   To run the SSCHA code with the input file use:
>>> sscha -i simple_input.in --save-data simple_input.out
The file can have any name (often *.in).
   An example of an input file:
!
! * * * * * * * * * * * * * * *
! *
       VC - RELAX EXAMPLE
! * * * * * * * * * * * * * *
! This is the input to perform the sscha minimization, followed
! by the change of the unit cell given by the stress step.
! This is not the recommended way to do it (you can do everything automatically)
! But usefull if you want to control manually each submission
&relax
type = "vc-relax"
start_pop = 2
max_pop_id = 2
generate_ensemble = .false.
fix_volume = .false.
target_pressure = 0 ! [GPa]
bulk_modulus = 15 ! [GPa]
n_{configs} = 1000
&end
&inputscha
n_random = 1000
data_dir = "../ensemble_data_test"
population = 2
fildyn_prefix = "../ensemble_data_test/dyn"
nqirr = 1
supercell_size = 1 1 1
Tg = 0
T = 0
meaningful_factor = 1e-4
gradi_op = "all"
n_random_eff = 500
print_stress = .true.
eq_energy = -144.40680397
lambda_a = 1
lambda_w = 1
root_representation = "normal"
preconditioning = .true.
max_ka= 20
```