

R documentation

of ‘blandAltmanLehPlot.Rd’

September 3, 2020

`blandAltmanLehPlot` *Generate Bland-Altman agreement plot between predicted and expected cell type proportions from test samples.*

Description

Generate Bland-Altman agreement plot between predicted and expected cell type proportions from test samples. The Bland-Altman agreement plots can be displayed all mixed or split based on cell type (`CellType`) or the number of cell types present in the sample (`nMix`). See `facet.by` argument and examples for more information.

Usage

```
blandAltmanLehPlot(  
  object,  
  colors,  
  color.by,  
  facet.by = NULL,  
  log.2 = FALSE,  
  filter.sc = TRUE,  
  density = TRUE,  
  color.density = "darkblue",  
  size.point = 0.05,  
  alpha.point = 1,  
  ncol = NULL,  
  nrow = NULL,  
  title = NULL,  
  theme = theme_grey(),  
  ...  
)
```

Arguments

<code>object</code>	DigitalDLSorter object with <code>trained.model</code> slot containing metrics in <code>eval.stats.samples</code> slot.
---------------------	---

<code>colors</code>	Vector of colors to use. Only vectors with a number of colors equal to or greater than the levels of <code>color.by</code> will be accepted. By default it is used a list of custom colors provided by the package.
<code>color.by</code>	Variable used to color data. The options are <code>nMix</code> and <code>CellType</code> .
<code>facet.by</code>	Variable used to display data in different panels. If it is <code>NULL</code> , the plot is not separated into different panels. The options are <code>nMix</code> (by number of different cell types) and <code>CellType</code> (by cell type).
<code>filter.sc</code>	Boolean indicating if filter single-cell profiles and only display correlations of results associated with bulk samples (<code>TRUE</code> by default).
<code>density</code>	Boolean indicating if show density lines (<code>TRUE</code> by default).
<code>color.density</code>	Color of density lines if <code>density</code> argument is equal to <code>TRUE</code> .
<code>size.point</code>	Size of points (0.1 by default).
<code>alpha.point</code>	Alpha of points (0.1 by default).
<code>ncol</code>	Number of columns if <code>facet.by</code> is different than <code>NULL</code> .
<code>nrow</code>	Number of rows if <code>facet.by</code> is different than <code>NULL</code> .
<code>title</code>	Title of the plot.
<code>theme</code>	ggplot theme.
<code>...</code>	Additional argument for <code>facet_wrap</code> ggplot function if <code>facet.by</code> is not equal to <code>NULL</code> .
<code>log2</code>	If show Bland-Altman agreement plot in log2 space (<code>FALSE</code> by default).

See Also

[calculateEvalMetrics](#) [corrExpPredPlot](#) [distErrorPlot](#) [barErrorPlot](#)

Examples

```
## Bland-Altman plot by cell type
blandAltmanLehPlot(
  object = DDLSchung,
  facet.by = "CellType",
  color.by = "CellType",
  corr = "both"
)
## Bland-Altman plot of all samples mixed
blandAltmanLehPlot(
  object = DDLSchung,
  facet.by = NULL,
  color.by = "CellType",
  alpha.point = 0.3
)
```

Index

barErrorPlot, [2](#)
blandAltmanLehPlot, [1](#)

calculateEvalMetrics, [2](#)
corrExpPredPlot, [2](#)

distErrorPlot, [2](#)