



R news and tutorials contributed by (573) R bloggers

- [Home](#)
- [About](#)
- [RSS](#)
- [add your blog!](#)
- [R jobs](#) ♦♦♦♦
- [Contact us](#)

Welcome!

Follow @rbloggers 25K f

Here you will find daily **news and tutorials about R**, contributed by over 573 bloggers. There are many ways to **follow us** -
[By e-mail:](#)

Your e-mail here

 21406 readers

BY FEEDBURNER

[On Facebook:](#)

R blog...

 28k likes

 Be the first of your friends to like this

If you are an R blogger yourself you are invited to [add your own R content feed to this site](#) (Non-English R bloggers should add themselves-[here](#))

[Jobs for R-users](#)

- [Looking for a Freelance R-Developer with Shiny experience](#)
- [Data Analyst @ New York](#)
- [R/Shiny App with d3 \(small job, quick turnaround, \\$250 < 4hrs\)](#)
- [Postdoctoral position \(Duke's River center\) in data visualization and ecosystem science @ Durham, North Carolina, United States](#)
- [Software Engineer for The Computational Biology Program at Oregon Health and Science University @ Portland, Oregon, United States](#)

Popular Searches

- [heatmap](#)
- [web scraping](#)
- [maps](#)
- [hadoop](#)
- [twitter](#)
- [alt=](#)
- [boxplot](#)
- [shiny](#)
- [time series](#)
- [animation](#)
- [ggplot2](#)
- [ggplot](#)
- [how to import image file to R](#)
- [latex](#)
- [trading](#)
- [finance](#)
- [PCA](#)
- [excel](#)
- [googlevis](#)
- [eclipse](#)
- [quantmod](#)
- [rstudio](#)
- [market research](#)
- [rattle](#)
- [Tutorial](#)
- [coplot](#)
- [rcmdr](#)
- [knitr](#)
- [title=](#)
- [rbloggers](#)

Recent Posts

- [Partoos, Recommender Systems and More](#)
- [Using htmlwidgets with knitr and Jekyll](#)
- [Wind in Netherlands](#)
- [Bioenergetics in R Workshop](#)
- [Correlation and Linear Regression](#)
- [Linear model with time series random component](#)
- [James Bond movies](#)
- [What it means to be a US Veteran Today](#)
- [Blog Post at Pluralsight](#)
- [The Lady Loves Statistics](#)
- [Annotables: R data package for annotating/converting Gene IDs](#)
- [Szkolenie z analizy sieciowej](#)
- [Applied Statistical Theory: Quantile Regression](#)
- [Let's meet on SatRdays: the link between RUGs and conferences](#)
- [importance sampling with infinite variance](#)

Other sites

- [SAS blogs](#)
- [Statistics of Israel](#)
- [Jobs for R-users](#)

Veterinary Epidemiologic Research: GLM – Evaluating Logistic Regression Models (part 3)

March 19, 2013

By [denishaine](#)

Like Share { 5 } Tweet { 2 }

(This article was first published on [denis haine » R](#), and kindly contributed to [R-bloggers](#))

Third part on logistic regression (first [here](#), second [here](#)).

Two steps in assessing the fit of the model: first is to determine if the model fits using summary measures of goodness of fit or by assessing the predictive ability of the model; second is to determine if there's any observations that do not fit the model or that have an influence on the model.

Covariate pattern

A covariate pattern is a unique combination of values of predictor variables.

```

1  mod3 <- glm(casecont ~ dcpct + dneo + dclo
2  +          family = binomial("logit")
3  summary(mod3)
4
5  Call:
6  glm(formula = casecont ~ dcpct + dneo +
7      family = binomial("logit"), data = i
8
9  Deviance Residuals:
10      Min       1Q   Median       3Q      Max
11  -1.9191  -0.7682   0.1874   0.5876   2.0
12
13  Coefficients:
14              Estimate Std. Error z
15  (Intercept)    -3.776896   0.993251
16  dcpct           0.022618   0.007723
17  dneoYes        3.184002   0.837199
18  dcloYes        0.445705   1.026026
19  dneoYes:dcloYes -2.551997   1.205075
20  ---
21  Signif. codes:  0 '***' 0.001 '**' 0.01
22
23  (Dispersion parameter for binomial fami
24
25      Null deviance: 149.72  on 107  degr
26  Residual deviance: 103.42  on 103  degr
27  AIC: 113.42
28
29  Number of Fisher Scoring iterations: 5
30
31  library(epiR)
32  Package epiR 0.9-45 is loaded
33  Type help(epi.about) for summary inform
34
35  mod3.mf <- model.frame(mod3)
36  (mod3.cp <- epi.cp(mod3.mf[-1]))
37  $cov.pattern
38      id  n dcpct dneo dclo
39  1    1  7     0   No   No
40  2    2 38    100  Yes   No
41  3    3  1    25   No   No
42  4    4  1     1   No   No
43  5    5 11    100   No  Yes
44  6    6  1    25  Yes  Yes
45  7   10  1    14  Yes   No
46  8   12  4    75  Yes   No
47  9   13  1    90  Yes  Yes
48 10   14  1    30   No   No
49 11   15  3     5  Yes   No
50 12   17  9   100  Yes  Yes
51 13   22  2    20  Yes   No
52 14   23  8   100   No   No
53 15   25  2    50  Yes  Yes
54 16   26  1     7   No   No
55 17   27  4    50  Yes   No
56 18   28  1    50   No   No

```

```

57 31 19 1 30 Yes No
58 34 20 1 99 No No
59 35 21 1 99 Yes Yes
60 40 22 1 80 Yes Yes
61 48 23 1 3 Yes No
62 59 24 1 1 Yes No
63 77 25 1 10 No No
64 84 26 1 83 No Yes
65 85 27 1 95 Yes No
66 88 28 1 99 Yes No
67 89 29 1 25 Yes No
68 105 30 1 40 Yes No
69
70 $id
71 [1] 1 2 3 4 5 1 1 6 5 7 5
72 [26] 16 17 18 1 2 19 2 14 20 21 12 :
73 [51] 14 12 11 5 15 2 8 2 24 2 2 :
74 [76] 2 25 2 17 2 2 2 2 26 27 13 :
75 [101] 2 2 2 2 30 2 2 5

```

There are 30 covariate patterns in the dataset. The pattern dcpct=100, dneo=Yes, dclox=No appears 38 times.

Pearson and deviance residuals

Residuals represent the difference between the data and the model. The Pearson residuals are comparable to standardized residuals used for linear regression models. Deviance residuals represent the contribution of each observation to the overall deviance.

```

1 residuals(mod3) # deviance residuals
2 residuals(mod3, "pearson") # pearson res:

```

Goodness-of-fit test

All goodness-of-fit tests are based on the premise that the data will be divided into subsets and within each subset the predicted number of outcomes will be computed and compared to the observed number of outcomes. The Pearson χ^2 and the deviance χ^2 are based on dividing the data up into the natural covariate patterns. The Hosmer-Lemeshow test is based on a more arbitrary division of the data.

The Pearson χ^2 is similar to the residual sum of squares used in linear models. It will be close in size to the deviance, but the model is fit to minimize the deviance and not the Pearson χ^2 . It is thus possible even if unlikely that the χ^2 could increase as a predictor is added to the model.

```

1 sum(residuals(mod3, type = "pearson")^2)
2 [1] 123.9656
3 deviance(mod3)
4 [1] 103.4168
5 1 - pchisq(deviance(mod3), df.residual(mod3))
6 [1] 0.4699251

```

The p-value is large indicating no evidence of lack of fit. However, when using the deviance statistic to assess the goodness-of-fit for a nonsaturated logistic model, the χ^2 approximation for the likelihood ratio test is questionable. When the covariate pattern is almost as large as N, the deviance cannot be assumed to have a χ^2 distribution.

Now the Hosmer-Lemeshow test, usually dividing by 10 the data:

```

1 hosmerlem <- function (y, yhat, g = 10)
2 +   cutyhat <- cut(yhat, breaks = quantiles(yhat, g, include.lowest = TRUE))
3 +   obs <- xtabs(cbind(1 - y, y) ~ cutyhat)
4 +   expect <- xtabs(cbind(1 - yhat, yhat) ~ cutyhat)
5 +   chisq <- sum((obs - expect)^2 / expect)
6 +   P <- 1 - pchisq(chisq, g - 2)
7 +   c("X^2" = chisq, Df = g - 2, "P(>Chisq)" = P)
8 + }
9
10 hosmerlem(y = nocardia$casecont, yhat = nocardia$predprob, g = 10)
11 Erreur dans cut.default(yhat, breaks = g) :
12 'breaks' are not unique

```

The model used has many ties in its predicted probabilities (too few covariate values?) resulting in an error when running the Hosmer-Lemeshow test. Using fewer cut-points (g = 5 or 7) does not solve the problem. This is a typical example when not to use this test. A better goodness-of-fit test than Hosmer-Lemeshow and Pearson / deviance χ^2 tests is the [le Cessie – van Houwelingen – Copas – Hosmer unweighted sum of squares test for global goodness of fit](#) (also [here](#)) implemented in the rms package (but you have to implement your model with the lrm function of this package):

```

1 mod3b <- lrm(casecont ~ dcpct + dneo + dclox)

```

```

2 + method = "lrm.fit", model
3 + linear.predictors = TRUE,
4 residuals(mod3b, type = "gof")
5 Sum of squared errors Expected value
6 16.4288056 16.82350
7 Z
8 -1.4219860 0.1550

```

The p-value is 0.16 so there's no evidence the model is incorrect. Even better than these tests would be to check for linearity of the predictors.

Overdispersion


Sometimes we can get a deviance that is much larger than expected if the model was correct. It can be due to the presence of outliers, sparse data or clustering of data. The approach to deal with overdispersion is to add a

dispersion parameter σ^2 . It can be estimated with: $\hat{\sigma}^2 = \frac{\chi^2}{n-p}$ (p = probability of success). A half-normal plot of the residuals can help checking for outliers:

```

1 library(faraway)
2 halfnorm(residuals(mod1))

```



Half-normal plot of the residuals

The dispersion parameter of model 1 can be found as:

```

1 (sigma2 <- sum(residuals(mod1, type = "lrm"))
2 [1] 1.128778
3 drop1(mod1, scale = sigma2, test = "F")
4 Single term deletions
5
6 Model:
7 casecont ~ dcpct + dneo + dclox
8
9 scale: 1.128778
10
11 Df Deviance AIC F value Pr(>F)
12 <none> 107.99 115.99
13 dcpct 1 119.34 124.05 10.9350 0.001
14 dneo 1 125.86 129.82 17.2166 6.834e-05
15 dclox 1 114.73 119.96 6.4931 0.011
16 ---
17 Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
18 Message d'avis :
19 In drop1.glm(mod1, scale = sigma2, test = "F"):
20 le test F implique une famille 'quasibinomial'

```

The dispersion parameter is not very different than one (no dispersion). If dispersion was present, you could use it in the F-tests for the predictors, adding scale to drop1.

Predictive ability of the model


A ROC curve can be drawn:

```

1 predicted <- predict(mod3)
2 library(ROCR)
3 prob <- prediction(predicted, nocardia$casecont)
4 + label.ordering = c("neg", "pos")
5 tprfpr <- performance(prob, "tpr", "fpr")
6 tpr <- unlist(slot(tprfpr, "y.values"))
7 fpr <- unlist(slot(tprfpr, "x.values"))
8 roc <- data.frame(tpr, fpr)
9 ggplot(roc) + geom_line(aes(x = fpr, y = tpr))
10 + geom_abline(intercept = 0, slope = 1)

```

```
11 + ylab("Sensitivity") +
12 + xlab("1 - Specificity")
```




ROC curve

Identifying important observations

Like for linear regression, large positive or negative standardized residuals allow to identify points which are not well fit by the model. A plot of Pearson residuals as a function of the logit for model 1 is drawn here, with bubbles relative to size of the covariate pattern. The plot should be an horizontal band with observations between -3 and +3. Covariate patterns 25 and 26 are problematic.

```
1 nocardia$casecont.num <- as.numeric(nocardi
2 mod1 <- glm(casecont.num ~ dcpct + dneo
3 + data = nocardia) # "logit"
4 mod1.mf <- model.frame(mod1)
5 mod1.cp <- epi.cp(mod1.mf[-1])
6 nocardia.cp <- as.data.frame(cbind(cpid
7 + nocardia.cp, dcpct, dneo)
8 + fi)
9 ### Residuals and delta betas based on c
10 mod1.obs <- as.vector(by(as.numeric(nocardi
11 + as.factor(nocardia.cp$fi)
12 mod1.fit <- as.vector(by(nocardia.cp$fi
13 + FUN = min))
14 mod1.res <- epi.cpresids(obs = mod1.obs,
15 + covpattern =
16
17 mod1.lodds <- as.vector(by(predict(mod1
18 + FUN = min))
19
20 plot(mod1.lodds, mod1.res$spearson,
21 + type = "n", ylab = "Pearson Resid
22 text(mod1.lodds, mod1.res$spearson, lab
23 symbols(mod1.lodds, mod1.res$spearson, c
```



Bubble plot of standardized residuals

The hat matrix is used to calculate leverage values and other diagnostic parameters. Leverage measures the potential impact of an observation. Points with high leverage have a potential impact. Covariate patterns 2, 14, 12 and 5 have the largest leverage values.

```
1 | mod1.res[sort.list(mod1.res$leverage, dec
2 | cpid leverage
3 | 2 0.74708052
4 | 14 0.54693851
5 | 12 0.54017700
6 | 5 0.42682684
7 | 11 0.21749664
8 | 1 0.19129427
9 | ...
```

Delta-betas provides an overall estimate of the effect of the j^{th} covariate pattern on the regression coefficients. It is analogous to Cook's distance in linear regression. Covariate pattern 2 has the largest delta-beta (and represents 38 observations).

```
1 | mod1.res[sort.list(mod1.res$sdeltabeta, c
2 | cpid sdeltabeta
3 | 2 7.890878470
4 | 14 3.983840529
5 | ...
```

Like

Share

5

Tweet

2

Related

$(75 - 50) \times 0.022 = 0.55$
Veterinary
Epidemiologic
Research: GLM –
Logistic Regression
(part 2)
In "R bloggers"



Logistic Regression
with R
In "R bloggers"



Veterinary
Epidemiologic
Research: GLM –
Logistic Regression
In "R bloggers"

5

2

Like

Tweet

Share

To leave a comment for the author, please follow the link and comment on their blog:
[denis haine » R](#).

R-bloggers.com offers [daily e-mail updates](#) about [R](#) news and [tutorials](#) on topics such as: [Data science](#), [Big Data](#), [R jobs](#), visualization ([ggplot2](#), [Boxplots](#), [maps](#), [animation](#)), programming ([RStudio](#), [Sweave](#), [LaTeX](#), [SQL](#), [Eclipse](#), [git](#), [hadoop](#), [Web Scraping](#)) statistics ([regression](#), [PCA](#), [time series](#), [trading](#)) and more...

If you got this far, why not **subscribe for updates** from the site?
Choose your flavor: [e-mail](#), [twitter](#), [RSS](#), or [facebook](#)...

Like

Share

5

Tweet

2

Comments are closed.

Top 3 Posts from the past 2 days

- James Bond movies
- Correlation and Linear Regression
- Linear model with time series random component

Search & Hit Enter

Top 9 articles of the week

- Installing R packages

2. [The Data Science Industry: Who Does What \(Infographic\)](#)
3. [In-depth introduction to machine learning in 15 hours of expert videos](#)
4. [magrittr: The best thing to have ever happened to R?](#)
5. [Using apply, sapply, lapply in R](#)
6. [How to Make a Histogram with Basic R](#)
7. [Introducing Distributed Data-structures in R](#)
8. [James Bond movies](#)
9. [Adding a legend to a plot](#)

Sponsors



R Consulting, Training, Support and
Application Development

Highland Statistics Ltd

Zero Inflated Models & GLMM

Beginner's Guide to GAM

Beginner's Guide to GLM & GLMM

Beginner's Guide to GAMM



Werden Sie zum Expe[R]ten mit der
R-Akademie von



Beratung | Software
Training | Lösungen




plotly online R graphing

[Plotly: collaborative, publication-quality graphing.](#)



STATISTICS
VIEWS

Bringing Statistics Together



January 11 - April 1, 2016 | Full Time Program

12 - WEEK DATA SCIENCE BOOTCAMP

Hands-on R, Python & Hadoop Training
Bootstrap your data science career
Receive personal and team support in job search
Become part of an engaged Data Science community

Early Application Deadline: Nov 16, 2015
Final Application Deadline: Dec 7, 2015




DataCamp
Learn R Interactively



ODSC 50 Talks
14 Workshops

6 Pre-conference Workshops

SAN FRANCISCO | NOV. 14TH - 15TH



Download a FREE Chapter Today!

SAVE 25%
on All R Books

Promo Code **CZP40**

CRC CRC Press
Taylor & Francis Group
www.crcpress.com



STATWORK

Consulting
Schulung
Data Mining


Mehr erfahren



Try the FASTEST ML
for **R**

Click for a Free Trial

YOTTAMINE
ANALYTICS



Become a
Certified Data Scientist

ENROLL NOW

simplilearn



[Contact us](#) if you wish to help support R-bloggers, and place your banner here.

[Jobs for R users](#)

- [Looking for a Freelance R-Developer with Shiny experience](#)
- [Data Analyst @ New York](#)
- [R/Shiny App with d3 \(small job, quick turnaround, \\$250 < 4hrs\)](#)
- [Postdoctoral position \(Duke's River center\) in data visualization and ecosystem science @ Durham, North Carolina, United States](#)
- [Software Engineer for The Computational Biology Program at Oregon Health and Science University @ Portland, Oregon, United States](#)
- [Data Scientist @ Israel](#)
- [Jr Financial Engineer](#)

Search & Hit Enter

[Full list of contributing R-bloggers](#)

[R-bloggers](#) was founded by [Tal Galili](#), with gratitude to the [R](#) community.

Is powered by [WordPress](#) using a [bavotasan.com](#) design.

Copyright © 2015 **R-bloggers**. All Rights Reserved. [Terms and Conditions](#) for this website