

CMPS 2200 Assignment 1

Name: _____

In this assignment, you will learn more about asymptotic notation, parallelism, functional languages, and algorithmic cost models. As in the recitation, some of your answer will go here and some will go in `main.py`. You are welcome to edit this `assignment-01.md` file directly, or print and fill in by hand. If you do the latter, please scan to a file `assignment-01.pdf` and push to your github repository.

1. (2 pts ea) Asymptotic notation

- 1a. Is $2^{n+1} \in O(2^n)$? Why or why not? .

.
. .
.

- 1b. Is $2^{2^n} \in O(2^n)$? Why or why not?

.
. .
.

- 1c. Is $n^{1.01} \in O(\log^2 n)$?

.
. .
.

- 1d. Is $n^{1.01} \in \Omega(\log^2 n)$?

.
. .
.

- 1e. Is $\sqrt{n} \in O((\log n)^3)$?

.
. .
.

- 1f. Is $\sqrt{n} \in \Omega((\log n)^3)$?

.
. .
.

- 1g. Consider the definition of “Little o” notation:

$g(n) \in o(f(n))$ means that for **every** positive constant c , there exists a constant n_0 such that $g(n) \leq c \cdot f(n)$ for all $n \geq n_0$. There is an analogous definition for “little omega” $\omega(f(n))$. The distinction between $o(f(n))$ and $O(f(n))$ is that the former requires the condition to be met for **every** c , not just for some c . For example, $10x \in o(x^2)$, but $10x^2 \notin o(x^2)$.

.

-
-
-
-
-
-
-
-
-
-

Recall the `sum_list_recursive_parallel` function from lecture 2. Specify our implementation in SPARC here.

[illegible]

Consider the following SPARC code:

- 3a. (4 pts) Translate this to Python code – fill in the `def foo` method in `main.py`
- 3b. (2 pts) What does this function do, in your own words?

•
•
•
•
•
•

Consider the following function:

```
"""
Input:
    `myarray`: a list of ints
    `key`: an int
Return:
    the longest continuous sequence of `key` in `myarray`
"""
```

- 4a. (8 pts) First, implement an iterative, sequential version of `longest_run` in `main.py`.
- 4b. (4 pts) What is the Work and Span of this implementation?

•
•
•
•
•
•
•
•
•
•

-
-
-
-
-
-
-
-
-
-

-
-
-
-
-
-
-