2020.05.29

Project
OBDH system

Juan A. de la Puente
<jpuente@dit.upm.es>

Overview

- The aim of this project is to build a simple mockup of a satellite OBDH system performing basic housekeeping telemetry
  - periodic sensor sampling
  - periodic basic telemetry
  - on-request housekeeping telemetry with recent data

- The target platform is an STM32F407 discovery board
- The host platform is a PC workstation
  - WIndows, MacOS, GNU Linux

Fight and ground segments



Functional requirements

- A set of sensors are periodically sampled with period T_S
- A basic TM message is sent periodically with period T_B. The message contains the last measured values from all sensors
- The system can receive a TC messages from the ground station, and replies with an appropriate TM message
- TM messages are stamped with the mission time when the message is sent
- Sensor measurements are stamped with mission time at which the measurements have been taken
- Time stamp values are given in seconds from the system start time, with a resolution of at least 1 ms

Temporal requirements

- Sensors must be sampled every T_S = 1 s
  - reading to be completed before D_S = 0.1 s
- Basic telemetry must be sent every T_B = 10 s
  - message must be sent before D_B = 0.5 s
- Telecommands are separated by at least T_C = 2 s
  - processing must be completed before D_C = 0.05 s
- Housekeeping telemetry messages are sent after reception of a TC
  - message must be sent before D_H = 0.2 s

Operating modes

- Idle
  - The ground station has no visibility of the satellite
  - Only basic TM is transmitted
  - Only *open link* TC is accepted
- Coverage
  - The ground station has visibility of the satellite
  - Started upon reception of an *open link* TC from ground
  - TC can be sent to the satellite replied by TM
  - Switch back to idle mode upon reception of a *close link* TC
    - or automatically after a maximum visibility window time

Telecommands

- OPEN : Open link
  - start coverage mode
- REQUEST
  - request housekeeping log
  - only in coverage mode
- CLOSE : Close link
  - end coverage mode

Telemetry messages

- HELLO : basic telemetry
  - last measured values from all the sensors.
  - periodically transmitted in idle mode
- HK : housekeeping
  - record with the last N measurements
  - transmitted in response to a telecommand in coverage mode
- MODE
  - current operating mode of the system
  - transmitted after a mode change in idle or coverage mode
- ERROR
  - abnormal conditions or erroneous TC received

Context diagram



System architecture



Architectural design (AADL)



Hardware connections

Connector pin	Board pin
1 (black)	GND
4 (orange)	PB7
5 (yellow)	PB6



Ground station



Ground station test arrangement



Ground station output

jpuente — screen /dev/cu.usbserial-FTA5I24G 115200 — screen — screen /dev...

```
0000000026 | HELLO 0000000026:1063:2073
0000000036 | HELLO 0000000036:1063:2078
0000000039 | MODE  COVERAGE
0000000045 | HK LOG
                   0000000040:1064:2080
                   0000000041:1066:2080
                   0000000042:1070:2077
                   0000000043:1063:2080
0000000049 | MODE  IDLE
0000000056 | HELLO 0000000056:1068:2080
0000000066 | HELLO 0000000066:1066:2079
```

Implementation

- **obdh**: compile on development platform
  - download code from the STR-UPM OBDH_LABS GitHub repository
  - compile and build with the arm-elf compiler
  - upload to the board through usb connection

- **gs**: run on linux/Mac/Windows workstation
  - requires python3 and pyserial.py

RT Analysis

i	Task		P	T	C	B	R	D
1	HK	P	4	1,0	$13 \cdot 10^{-6}$	$4 \cdot 10^{-6}$	$17 \cdot 10^{-6}$	0,100
2	Timer	S	3	60,0	$5 \cdot 10^{-6}$	$2 \cdot 10^{-6}$	$20 \cdot 10^{-6}$	0,200
3	Basic_TM	P	2	10,0	$26 \cdot 10^{-6}$	$4 \cdot 10^{-6}$	$48 \cdot 10^{-6}$	0,500
4	TC	S	1	2,0	$20 \cdot 10^{-6}$	—	$64 \cdot 10^{-6}$	1,0
	PO							
	Storage		4		$4 \cdot 10^{-6}$			
	Mode		3		$2 \cdot 10^{-6}$			

Response time analysis

- The response time equation is

$$R_i = C_i + B_i + \sum_{j \in \mathrm{hp}(i)} \left\lceil \frac{R_i}{T_j} \right\rceil C_j$$

  - not continuous nor linear
  - cannot be solved analytically

Linear iteration

- The response time equation can be solved by the following recurrence relationship:

$$w_i^{n+1} = C_i + B_i \sum_{j \in hp(i)} \left\lceil \frac{w_i^n}{T_j} \right\rceil \cdot C_k$$

- the succession $w_i{}^0,\ w_i{}^1,\ w_i{}^2,\ \ldots$ es non-decreasing monotonic
- an acceptable initial value is $w_i{}^0 = C_i + B_i$
- the iteration ends when
  - a) $w_i{}^{n+1} = w_i{}^n$ (and then $R_i = w_i{}^n$), or
  - b) $w_i{}^{n+1} > T_i$ (deadline missed)

Example

In the previous example

$$R_1 = C_1 + B_1 = 17 \cdot 10^{-6}$$

$$w_2^0 = C_2 + B_2 = 7 \cdot 10^{-6}$$

$$w_2^1 = C_2 + B_2 + \left\lceil \frac{w_2^0}{T_1} \right\rceil \cdot C_1 = 20 \cdot 10^{-6}$$

$$w_2^2 = C_2 + B_2 + \left\lceil \frac{w_2^1}{T_1} \right\rceil \cdot C_1 = 20 \cdot 10^{-6}$$

$$R_2 = 20 \cdot 10^{-6}$$

etc.