


2021.03.18

UPMSat-2 on-board software


Juan Antonio de la Puente <juan.de.la.puente@upm.es>

Top-level architecture



- Data links
 - ▶ UHF U band(AMSAT): 435.00–438.00MHz
 - AUL: Uplink (telecommands): max 1200 bps
 - ADL: Downlink (housekeeping data): max 1200 bps
 - ▶ UHF space research band: 400.15 – 401.0MHz
 - RDL: Downlink (experiment data): max 9600 bps


OBC context




Experiment payload

- MTS Micro Thermal Switch (*IBERESPACIO*)
- RW Reaction Wheel (*Satellite Services Ltd.*)


GS context




GS: Architecture




OBC operating modes



OBSW architectural design



Architecture of a subsystem



© 2018 Jorge Garrido

Sample code

```
with BasicTypes.TTC.TC;
with Ada.Streams;

-- @summary
-- High-level interface of the manager subsystem.
--
-- @description
-- This package provides the external interface of the Manager component.
-- It manages the overall satellite operation. It manages the satellite state
-- and handles events, errors and TCs
--
package Manager.HLInterface is

    -- Start the execution of the on-board software
    procedure Start;

    -- Notify an event to the manager
    -- @param the event to be handled
    procedure Notify_Event (Event : in BasicTypes.Event);

    -- Notify a TC to the manager
    -- @param CommandID Identifier of the command in the TC
    -- @param PacketDataField Contents of the TC
    -- @param PacketDataFieldLength Length of the contents of the TC
    procedure Process_TC
        (CommandID          : in BasicTypes.TTC.TC.TC_Command_ID;
         PacketDataField    : in Ada.Streams.Stream_Element_Array;
         PacketDataFieldLength : in Ada.Streams.Stream_Element_Offset);


    -- Get the current operating mode of the OBSW
    -- @return the operating mode
    function Current_Mode return BasicTypes.Operating_Mode;

end Manager.HLInterface;
```


Development tools

- Ada 2005 language
 - ▶ a few modules in C
 - automatically generated from Simulink
- Graphical programming environment
 - ▶ GPS: GNAT Programming System
- GNAT compilation chain
 - ▶ GNU Ada New York University Translator
 - ▶ Native compilers for development and high-level testing
 - ▶ Cross-compiler (GNU/Linux - LEON3) for production


GNAT Programming System



Cross-compilation process




Debugging tools



Testing (1)

Built with project `obsw_test.gpr`




GS runs on the development workstation
or on a different machine

OBSW runs on the development workstation
executable file: `obsw_test`

Testing (2)

Built with project `obsw_test_target.gpr`



Testing (3)

