	Cover Panels_Aluminum Panels	MiSUMi
	Part Number **PAAL4H-330-128-1-F315-G115-N3**	20210329135454

Surface Treatment, Finish, Coating	Clear Anodize	**Material**	EN AW-5052 Equiv.
Type	Panel	**Number of Holes**	4H (Four Holes)
Countersink Hole Nominal Dia. [P]	-	**External Dimension A(mm)**	330
External Dimension B(mm)	128	**F(mm)**	315
G(mm)	115	**Plate Thickness t(mm)**	1
Through Hole Nominal Dia. [N]	3	**-**	-





Hole Machining Details

N (Through) P (Countersink)



Screw Nominal Dia.	3	4	5	6	8
d	3.5	4.5	5.5	6.5	8.5
d1	7.5	-	11.5	-	18.5
h	2	-	3	-	5

Alterations

Part Number	-	A	-	B	-	T	-	F	-	G	-	Screw Nominal Dia.	-	(XC・YC…etc.)
PAAL4H	-	100	-	80	-	3.0	-	F50	-	G60	-	N4	-	XC10

	Hole Position from Left	Hole Position from Bottom	Relief at Four Corners	One Side Folded	Left and Right Sides Folded	Four Sides Folded
Alterations						
Code	XC	YC	CN	ZM	XM	XYM
Spec.	XC=1mm Increment (P) 5≤XC≤1186 (P) (2H, 4H Type) d(d1)/2+2.5≤XC≤ A-F-d(d1)/2-2.5 (P) (6H, 8H Type) d(d1)/2+2.5≤XC≤ A-2F-d(d1)/2-2.5	YC=1mm Increment (P) 5≤YC≤986 (P) (4H, 6H Type) d(d1)/2+2.5≤YC≤ B-G- d(d1)/2-2.5 (P) (8H Type) d(d1)/2+2.5≤YC≤ B-2G- d(d1)/2-2.5 (X) Not applicable to 2H Type	CN=1mm Increment Machines relief at 4 corners. (P) 5≤CN≤50 Ordering Code CN=25 ⇒ CN25 (X) Combination use with ZM, XM, XYM is not possible.	<Fabrication Conditions> ZM=1mm Increment T: 2.0 — 15≤ZM≤100 T: 3.0 — 17≤ZM≤100 T: 3.2 — 19≤ZM≤100 (P) PAALC has protrusions on external side. (X) Not applicable to T=5.0 (P) ZM+A≤1200 (X) Not compatible with CN.	<Fabrication Conditions> XM=1mm Increment T: 2.0 — 15≤XM≤100 T: 3.0 — 17≤XM≤100 T: 3.2 — 19≤XM≤100 (P) PAALC has protrusions on external side. (X) Not applicable to T=5.0 (P) XMx2+A≤1200 (X) Not compatible with CN.	<Fabrication Conditions> XYM=1mm Increment T: 2.0 — 15≤XYM≤100 T: 3.0 — 17≤XYM≤100 T: 3.2 — 19≤XYM≤100 (P) PAALC has protrusions on external side. (X) Not applicable to T=5.0 (P) XYMx2+A≤1200 (P) XYMx2+B≤1000 (X) Not compatible with CN.