

# Circuit Signals

Diego Trapero

## Table of contents

<b>1</b>	<b>Circuit Signals</b>	<b>2</b>
1.1	Periodic signals . . . . .	2
1.1.1	Average value of a periodic signal . . . . .	2
1.1.2	Root Mean Square of a periodic signal . . . . .	2
1.1.3	Signal Examples . . . . .	3
1.1.3.1	Sinusoidal signal . . . . .	3
1.1.4	Average and RMS values table . . . . .	4
1.1.5	Periodic signal decomposition in Fourier Series . . . . .	4

# 1 Circuit Signals

**Circuit signal** A circuit signal,  $s(t)$ , is a function of time that represents the variation of an electrical magnitude in a circuit.

## 1 Periodic signals

**Periodic signal** A periodic signal is a signal  $s(t)$  that satisfies  $s(t) = s(t+T)$  for all  $t$

- *Note* Constant signals are periodic signals because they fulfill the condition.

### Periodic signal parameters

- The period is the smallest value of  $T$  satisfying  $u(t+T) = u(t)$  for all  $t$
- Frequency,  $f = 1/T$  [Hz] [ $s^{-1}$ ]
- Angular frequency,  $\omega = 2\pi f$  [rad]
- Amplitudes
  - Peak-to-peak amplitude
  - Peak amplitude, commonly referred as just amplitude

## 1 Average value of a periodic signal

The average value  $S_{avg}$  or  $\bar{s}(t)$  of a periodic signal  $S(t)$  is

$$S_{avg} = \bar{s}(t) = \frac{1}{T} \int_t^{t+T} s(t) dt$$

- $S_{avg}$  can be negative, positive or zero

**Average power** Average power in a component is a case of the average value of a periodic signal. The average power  $P$  or  $p(t)$  dissipated in a component is

$$P = \bar{p}(t) = \frac{1}{T} \int_{t_0}^{t_0+T} p(t) dt = \frac{1}{T} \int_{t_0}^{t_0+T} v(t)i(t) dt$$

## 1 Root Mean Square of a periodic signal

The Root Mean Square  $S_{RMS}$  of a periodic signal  $s(t)$  is

$$S_{RMS} = \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} s(t)^2 dt}$$

**Motivation for RMS value** RMS value of a voltage or current signal (constant or non-constant) has the property that is the value of an equivalent DC voltage or current signal that would dissipate the same power through a resistance.

Average power has the expression  $P = \bar{p}(t) = \frac{1}{T} \int_{t_0}^{t_0+T} v(t)i(t) dt$  and using the RMS value of the signals we want to express it in a similar way to DC, where power is the product of two constants:  $P = VI$ .

### a) RMS value of current

- 1) Using Ohm Law derivate the power expression in DC:  $P = VI = RI^2$ .
- 2) Calculate the expression for  $I_{RMS}$ , that satisfies  $P = RI_{RMS}^2$ .

$$P = RI_{RMS}^2 = \frac{1}{T} \int_{t_0}^{t_0+T} v(t)i(t) dt$$

$$RI_{RMS}^2 = \frac{1}{T} \int_{t_0}^{t_0+T} Ri^2(t) dt$$

$$\cancel{R}I_{RMS}^2 = \cancel{R}\frac{1}{T} \int_{t_0}^{t_0+T} i^2(t) dt$$

$$I_{RMS} = \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} i^2(t) dt}$$

b) **RMS value of voltage**

b.1) Using Ohm Law derivate the power expression in DC:  $P = VI = \frac{V^2}{R}$ .

b.2) Calculate the expression for  $I_{RMS}$ , that satisfies  $P = VI = \frac{V_{RMS}^2}{R}$ .

$$P = \frac{V_{RMS}^2}{R} = \frac{1}{T} \int_{t_0}^{t_0+T} v(t)i(t) dt$$

$$\frac{V_{RMS}^2}{R} = \frac{1}{T} \int_{t_0}^{t_0+T} \frac{1}{R} v^2(t) dt$$

$$\cancel{1/R}V_{RMS}^2 = \cancel{1/R}\frac{1}{T} \int_{t_0}^{t_0+T} v^2(t) dt$$

$$V_{RMS} = \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} v^2(t) dt}$$

c) Check results with the  $P = VI$  formula. *I don't know how to prove it yet, or even if it is true*

$$P = VI = \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} v^2(t) dt} \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} i^2(t) dt}$$

$$P = \frac{1}{T} \sqrt{\int_{t_0}^{t_0+T} v^2(t) dt \cdot \int_{t_0}^{t_0+T} i^2(t) dt}$$

## 1 Signal Examples

### 1.1.3.1 Sinusoidal signal

$$s(t) = A \cdot \sin(\omega t + \varphi)$$

**Average value of the sinusoidal signal**

$$S_{AVG} = \frac{1}{T} \int_t^{t+T} A \cos(t) dt$$

$$S_{AVG} = \frac{A}{T} [\sin(t)]_t^{t+T} dt = 0$$

**RMS value of the sinusoidal signal**

$$S_{RMS} = \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} [A \cos(t)]^2 dt}$$

$$= \sqrt{\frac{1}{T} \int_{t_0}^{t_0+T} [A \cos(t)]^2 dt}$$

$$= \sqrt{\frac{A^2}{T} \int_{t_0}^{t_0+T} \frac{1 + \cos(2t)}{2} dt}$$

$$= \sqrt{\frac{A^2}{T} [1/2(t + 1/2 \sin(2t))]_t^{t+T}}$$

$$= \sqrt{\frac{A^2}{2T}} T = \sqrt{\frac{A^2}{2}} = \frac{A}{\sqrt{2}}$$

## 1 Average and RMS values table

Signal	Average value	Root Mean Square Value
Constant	$A$	$A$
Square Wave		
Sinusoidal Wave	0	$\frac{A}{\sqrt{2}}$

## 1 Periodic signal decomposition in Fourier Series

**Motivation** The phasor method can be used to solve circuits with sinusoidal signals (AC circuits), avoiding the necessity of solving the time-domain differential equations. A circuit with other type of waveforms cannot be analysed with this method, unless it is decomposed into its sinusoidal components. The Fourier series allows us to decompose any waveform to a series of sine and cosine functions. Then, we can solve each circuit (an AC circuit for each sinusoidal component of the wave) separately and, applying superposition, add up all the solutions to get the solution of the original

circuit.

**Fourier decomposition** Any periodic signal can be decomposed in a sum of a constant value plus a (possibly infinite) series of sine and cosine functions.

$$s(x) = S_{avg} + \sum_{n=1}^{\infty} A_n \cos(n\omega t) + \sum_{n=1}^{\infty} B_n \sin(n\omega t)$$

**Superposition theorem** The superposition theorem for electrical circuits states that for a linear system the response (voltage or current) in any branch of a bilateral linear circuit having more than one independent source equals the algebraic sum of the responses caused by each independent source acting alone, while all other independent sources are cancelled.

**Solving a circuit with a Fourier decomposed periodic signal** From the superposition theorem, we know that the response of the circuit can be derived from the contribution of many different signals ...

**Parseval formula** The Parseval formula expresses the RMS value of a signal in terms of the RMS values of the harmonic components of the signal

$$S_{RMS}^2 = S_{avg}^2 + S_{1RMS}^2 + S_{2RMS}^2 + S_{3RMS}^2 + \dots$$

- The squared RMS value of a signal is the sum of all the squared RMS values its sinusoidal components
- The RMS value of a signal is the geometric mean of the RMS values of its sinusoidal components

**Ripple RMS value** In constant signals, ripple are the harmonics other than the signal average value. According to Parseval formula, the RMS value of the ripple is the geometric mean of the RMS values of its sinusoidal components:

$$S_{RMSRipple}^2 = S_{1RMS}^2 + S_{2RMS}^2 + S_{3RMS}^2 + \dots$$

We can derive the ripple RMS value from the DC signal's Parseval formula:

$$S_{RMS}^2 = S_{avg}^2 + S_{1RMS}^2 + S_{2RMS}^2 + S_{3RMS}^2 + \dots = S_{avg}^2 + S_{RMSRipple}^2$$

$$S_{RMSRipple}^2 = S_{RMS}^2 - S_{avg}^2$$

$$S_{RMSRipple} = \sqrt{S_{RMS}^2 - S_{avg}^2}$$

**Average power from harmonics**

$$P = V_{avg}I_{avg} + V_{1RMS}I_{1RMS} \cos(\varphi_1) + V_{2RMS}I_{2RMS} \cos(\varphi_2) + \dots$$

- Only same frequency harmonics produce power.