



YouTube @CafecomDadoseGatos

Table of Contents

OpenClaw FULL on Docker + Ollama on Windows + WhatsApp + Telegram	2
Complete step-by-step (with 1008 fix).....	2
1) Windows prerequisites.....	2
2) Install OpenClaw FULL on WSL2 (Ubuntu)	2
3) Start and access the UI	3
4) Validate container connectivity to Ollama (Windows)	3
5) Issue: 1008 “device token mismatch” / “pairing required”	4
6) Apply patch to ~/.openclaw/openclaw.json (anti-1008 + Ollama)	4
7) Restart gateway (FULL compose)	6
8) Official health check	6
9) Test OpenClaw ↔ Ollama (OpenAI endpoint)	6
10) Final UI test	7
11) WhatsApp + Telegram (via onboard).....	7
12) Run onboard (FULL)	8

OpenClaw FULL on Docker + Ollama on Windows + WhatsApp + Telegram

Complete step-by-step (with 1008 fix)

Goal

Run OpenClaw (full version) inside Docker (via WSL2/Ubuntu) and use Ollama on Windows as the model provider — everything local, token-secured, no cloud, zero cost.

1) Windows prerequisites

1.1 Install and start Ollama

Install Ollama on Windows and confirm the service is running.

1.2 Download a model (example)

```
ollama pull qwen3:8b
```

There's a short on the channel showing how to install Ollama.

1.3 Confirm Ollama API

Use curl.exe (to avoid PowerShell prompt issues):

```
curl.exe http://127.0.0.1:11434/api/tags
```

2) Install OpenClaw FULL on WSL2 (Ubuntu)

In Ubuntu/WSL2:

2.1 Clone repo and run FULL setup

```
cd ~
rm -rf ~/openclaw
git clone https://github.com/openclaw/openclaw.git
cd openclaw
chmod +x ./docker-setup.sh
./docker-setup.sh
```

2.2 Onboarding wizard

When prompted, choose:

- Gateway bind: **lan**
- Gateway auth: **token**
- Tailscale exposure: **Off**
- Install Gateway daemon: **No**
- Model/auth provider: **Skip for now** (we'll configure Ollama later)

At the end it creates/updates:

- Config: ~/.openclaw/openclaw.json
 - FULL compose: /home/denise/openclaw/docker-compose.yml
 - Main container: openclaw-gateway (via compose)
-

3) Start and access the UI

Gateway runs mapped to host:

- UI:
- <http://localhost:18789/>
- UI with token:
- http://localhost:18789/#token=YOUR_TOKEN

Always use the token URL.

4) Validate container connectivity to Ollama (Windows)

In WSL:

```
cd ~/openclaw
docker compose exec openclaw-gateway sh -lc 'curl -sS
http://host.docker.internal:11434/api/version && echo'
```

Expected output:

```
{"version": "..."} 
```

This confirms the container can reach Ollama on Windows.

5) Issue: 1008 “device token mismatch” / “pairing required”

UI symptoms

- “Disconnected from gateway”
- disconnected (1008): unauthorized: device token mismatch
- disconnected (1008): pairing required

Typical cause (Docker Desktop + WSL2)

UI reaches gateway through internal Docker NAT/proxy and gateway does not trust the proxy.

Stable solution

- token auth enabled
 - enable control UI
 - allow insecure auth only for local UI
 - add Docker subnets to trustedProxies
 - configure Ollama provider in openclaw.json
-

6) Apply patch to ~/.openclaw/openclaw.json (anti-1008 + Ollama)

6.1 Install jq

```
sudo apt-get update && sudo apt-get install -y jq
```

6.2 Full patch (with backup + validation)

```
set -euo pipefail

cp -a ~/.openclaw/openclaw.json
~/.openclaw/openclaw.json.bak.$(date +%Y%m%d-%H%M%S)

TOKEN="$(jq -r '.gateway.auth.token' ~/.openclaw/openclaw.json) "
echo "TOKEN (JSON)={$TOKEN:0:8}...{$TOKEN: -6} "
```

```
jq --arg TOKEN "$TOKEN" '
  .gateway.auth.mode="token"
  | .gateway.auth.token=$TOKEN
  | .gateway.controlUi.enabled=true
  | .gateway.controlUi.allowInsecureAuth=true
  | .gateway.trustedProxies = ((.gateway.trustedProxies // [])
    +
["192.168.65.0/24","172.17.0.0/16","172.18.0.0/16","172.19.0.0/16
"]
    | unique)
  | .models.providers.ollama = {
    "baseUrl":"http://host.docker.internal:11434/v1",
    "apiKey":"ollama-local",
    "api":"openai-responses",

"models":[{"id":"qwen3:8b","name":"qwen3:8b","contextWindow":3276
8}]
  }
  | .agents.defaults.model.primary = "ollama/qwen3:8b"
' ~/.openclaw/openclaw.json > ~/.openclaw/openclaw.json.tmp

jq -e . ~/.openclaw/openclaw.json.tmp >/dev/null
mv ~/.openclaw/openclaw.json.tmp ~/.openclaw/openclaw.json
echo "patched ~/.openclaw/openclaw.json"
```

6.3 Verify config

```
jq -r '.gateway.auth.mode, .gateway.auth.token'
~/.openclaw/openclaw.json
jq -c '.gateway.trustedProxies' ~/.openclaw/openclaw.json
jq -r '.models.providers.ollama.baseUrl,
.agents.defaults.model.primary' ~/.openclaw/openclaw.json
```

Expected:

- token mode
- full token
- trustedProxies with docker subnets
- baseUrl host.docker.internal
- primary model ollama/qwen3:8b

7) Restart gateway (FULL compose)

```
cd ~/openclaw
docker compose restart openclaw-gateway
docker compose logs -f --tail 120 openclaw-gateway
```

Look for:

- agent model: ollama/qwen3:8b
- webchat connected client=openclaw-control-ui

This confirms 1008 is fixed.

8) Official health check

8.1 HTTP health

```
curl -fsS http://localhost:18789/_openclaw_/canvas/ >/dev/null && echo "HTTP OK"
```

8.2 WebSocket + token

Install wscat:

```
sudo apt-get update
sudo apt-get install -y node-ws
```

Connect:

```
TOKEN="$(jq -r '.gateway.auth.token' ~/.openclaw/openclaw.json) "
wscat -c ws://localhost:18789 -H "Authorization: Bearer $TOKEN"
```

Expected:

Connected

```
< {"type": "event", "event": "connect.challenge" ...}
```

9) Test OpenClaw ↔ Ollama (OpenAI endpoint)

Inside container:

```
cd ~/openclaw
```

```
docker compose exec openclaw-gateway sh -lc '  
curl -sS http://host.docker.internal:11434/v1/chat/completions \  
-H "Content-Type: application/json" \  
-d '  
{"model\":\"qwen3:8b\", \"messages\": [{\"role\":\"user\", \"conte  
nt\":\"Reply with one word:  
OK\"}], \"temperature\":0, \"stream\":false}" \  
| head -c 400 && echo  
'
```

Expected snippet:

```
{"model":"qwen3:8b"... "content":"OK"}
```

Confirms:

- container reaches Ollama
- OpenAI-compatible endpoint works
- model responds

10) Final UI test

Open:

http://localhost:18789/#token=YOUR_TOKEN

Ask:

Say Hi

11) WhatsApp + Telegram (via onboard)

Enable channels in FULL setup.

Backup first (recommended)

```
set -euo pipefail  
TS="$(date +%Y%m%d-%H%M%S)"  
mkdir -p ~/.openclaw/backup-$TS
```

```
cp -a ~/.openclaw/openclaw.json ~/.openclaw/backup-$TS/  
cp -a /home/denise/openclaw/docker-compose.yml  
~/.openclaw/backup-$TS/ 2>/dev/null || true  
cp -a ~/.openclaw/workspace ~/.openclaw/backup-$TS/ 2>/dev/null  
|| true  
  
echo "backup created"
```

12) Run onboard (FULL)

```
cd ~/openclaw  
docker compose run --rm openclaw-cli onboard
```

Wizard:

- Configure chat channels now? → Yes
- Telegram → paste TELEGRAM_TOKEN
- WhatsApp → Yes → scan QR
- Telegram DM policy → Pairing
- Skills → No
- Hooks → Skip

Final openclaw.json inside container

Read-only command:

```
cd ~/openclaw  
docker compose exec openclaw-gateway sh -lc '  
sed -n "1,260p" /home/node/.openclaw/openclaw.json  
'
```

You should see:

- channels.whatsapp
- channels.telegram

- plugins telegram + whatsapp enabled
- gateway token
- trustedProxies
- ollama provider baseUrl
- primary model ollama/qwen3:8b

This document was translated from Portuguese to English using AI.