



 @CafecomDadoseGatos

Table of Contents

OpenClaw FULL on Docker + WSL2 + Clouds: Ollama + OpenRouter	2
0. CLEAN EVERYTHING (fresh reinstall)	3
1. DOWNLOAD OFFICIAL OPENCLAW FULL	3
2. START FULL STACK	4
3. OPEN OPENCLAW UI	4
4. FIX ERROR 1008	4
5. START OLLAMA ON WINDOWS.....	5
6. OPEN WINDOWS FIREWALL (ESSENTIAL).....	5
7. TEST OPENCLAW → LOCAL OLLAMA.....	5
7.1 STEP 2 — Are you logged into Ollama Cloud?	6
7.2 STEP 3 — Add Ollama to OpenClaw	6

OpenClaw FULL on Docker + WSL2 + Clouds: Ollama + OpenRouter

✅ Prerequisites (what must be installed)

- Windows 10/11 (64-bit)
- WSL2 enabled
- Ubuntu on WSL2 (ex: Ubuntu 22.04 or 24.04)
- Docker Desktop installed using WSL2 backend
- Ollama for Windows (installed and running)
- OpenRouter account/API Key
- Ollama Cloud account/key (if using cloud models on Ollama)

✅ Machine requirements (recommended minimum)

- CPU-only works (no GPU required)
- Recommended RAM: 16 GB (8 GB works but very tight)
- Disk space: at least 15 GB free (OpenClaw FULL image may use ~6.9 GB)
- Internet connection to download images and/or use clouds

✅ Ports and networking (must be working)

- 18789 → OpenClaw Gateway/UI (localhost)
- 11434 → Ollama on Windows (localhost)
- From WSL/container: access to
<http://host.docker.internal:11434>

✅ Verification commands (before running)

PowerShell:

```
curl http://localhost:11434/api/version
```

WSL:

```
docker info
```

(Docker must respond correctly)

✅ Security / quick warning

- Do NOT expose port 11434 to the internet (keep local only).
 - If you run `docker system prune -a -f`, it cleans the entire Docker environment.
-

0. CLEAN EVERYTHING (fresh reinstall)

In WSL:

```
cd ~
docker compose down -v
docker system prune -a -f
rm -rf ~/openclaw
```

⚠ Attention

docker system prune -a -f performs a GLOBAL Docker cleanup.

It removes stopped containers, unused images, networks and build cache.

If you have other Docker projects, this will affect them too.

Use only if you really want a full cleanup.

👉 To clean only OpenClaw:

```
docker compose down -v
```

(inside project folder)

1. DOWNLOAD OFFICIAL OPENCLAW FULL

```
cd ~
git clone https://github.com/openclaw/openclaw.git
cd openclaw
chmod +x ./docker-setup.sh
./docker-setup.sh
```

This generates:

- .env
- token
- base openclaw.json

If you ever need to run onboard again:

```
cd ~/openclaw
docker compose run --rm openclaw-cli onboard
```

2. START FULL STACK

```
cd ~/openclaw
docker compose up -d
docker compose ps
```

You should see:

- openclaw-gateway Running
- openclaw-cli Created

3. OPEN OPENCLAW UI

Browser:

http://localhost:18789/#token=YOUR_TOKEN

4. FIX ERROR 1008

Run in WSL (single command):

```
docker compose exec -T openclaw-gateway sh -lc '
node - << "NODE"
const fs = require("fs");
const p = "/home/node/.openclaw/openclaw.json";
const j = JSON.parse(fs.readFileSync(p, "utf8"));

j.gateway = j.gateway || {};
j.gateway.controlUi = j.gateway.controlUi || {};
j.gateway.controlUi.enabled = true;
j.gateway.controlUi.allowInsecureAuth = true;

const add =
["192.168.65.0/24", "172.17.0.0/16", "172.18.0.0/16"];
const cur = Array.isArray(j.gateway.trustedProxies) ?
j.gateway.trustedProxies : [];
j.gateway.trustedProxies = Array.from(new Set([...cur,
...add]));

fs.writeFileSync(p, JSON.stringify(j, null, 2));
console.log("patched gateway.controlUi + trustedProxies");
NODE
'
```

Restart:

```
docker compose restart openclaw-gateway
```

Open again:

http://localhost:18789/#token=YOUR_TOKEN

5. START OLLAMA ON WINDOWS

Open Ollama on Windows.

Test in PowerShell:

```
curl http://localhost:11434/api/version
```

If version returns → OK.

6. OPEN WINDOWS FIREWALL (ESSENTIAL)

PowerShell (admin):

```
New-NetFirewallRule -DisplayName "Ollama 11434" -Direction  
Inbound -Action Allow -Protocol TCP -LocalPort 11434
```

7. TEST OPENCLAW → LOCAL OLLAMA

Paste full command in WSL:

```
docker compose exec -T openclaw-gateway sh -lc \  
'curl -sS http://host.docker.internal:11434/api/version &&  
echo'
```

If it returns:

```
{"version":"0.16.x"}
```

♥ CONNECTED.

7.1 STEP 2 — Are you logged into Ollama Cloud?

Windows PowerShell:

```
ollama signin
```

Then test:

```
ollama run gpt-oss:120b-cloud
```

If it responds → cloud OK.

7.2 STEP 3 — Add Ollama to OpenClaw

Open the **RAW mode** in the OpenClaw panel.

Before changing anything:

- Copy and save your current RAW as backup
- If something breaks, just paste it back

Then paste the code below and only change model IDs according to your enabled models (OpenRouter + Ollama).

```
{
  "meta": {
    "lastTouchedVersion": "2026.2.16",
    "lastTouchedAt": "2026-02-17T12:33:41.858Z"
  },
  "wizard": {
    "lastRunAt": "2026-02-17T12:33:41.853Z",
    "lastRunVersion": "2026.2.16",
    "lastRunCommand": "onboard",
    "lastRunMode": "local"
  },
  "auth": {
    "profiles": {
      "openrouter:default": {
        "provider": "openrouter",
        "mode": "api_key"
      }
    }
  },
  "models": {
```

```

"providers": {
  "ollama": {
    "baseUrl": "http://host.docker.internal:11434/v1",
    "apiKey": "sk_ollama",
    "api": "openai-responses",
    "models": [
      {
        "id": "gpt-oss:120b-cloud",
        "name": "gpt-oss:120b-cloud",
        "contextWindow": 65536,
        "maxTokens": 8192
      }
    ]
  }
},

"agents": {
  "defaults": {
    "model": {
      "primary": "openrouter/google/gemma-3-27b-it:free"
    },
    "models": {
      "openrouter/arcee-ai/trinity-mini:free": {},
      "openrouter/auto": {
        "alias": "OpenRouter"
      },
      "openrouter/google/gemma-3-27b-it:free": {},

      "ollama/gpt-oss:120b-cloud": {
        "alias": "Ollama Cloud"
      }
    },
    "workspace": "/home/node/.openclaw/workspace",
    "compaction": {
      "mode": "safeguard"
    },
    "maxConcurrent": 4,
    "subagents": {
      "maxConcurrent": 8
    }
  }
}

```

```
    }  
  }  
},  
  
"messages": {  
  "ackReactionScope": "group-mentions"  
},  
"commands": {  
  "native": "auto",  
  "nativeSkills": "auto"  
},  
"gateway": {  
  "port": 18789,  
  "mode": "local",  
  "bind": "lan",  
  "auth": {  
    "mode": "token",  
    "token": "__OPENCLAW_REDACTED__"  
  },  
  "tailscale": {  
    "mode": "off",  
    "resetOnExit": false  
  },  
  "nodes": {  
    "denyCommands": [  
      "camera.snap",  
      "camera.clip",  
      "screen.record",  
      "calendar.add",  
      "contacts.add",  
      "reminders.add"  
    ]  
  },  
  "controlUi": {  
    "enabled": true,  
    "allowInsecureAuth": true  
  },  
  "trustedProxies": [  
    "192.168.65.0/24",
```



```
        "172.17.0.0/16",  
        "172.18.0.0/16"  
    ]  
}  
}
```

Adjust models as needed

This example uses:

```
openrouter/google/gemma-3-27b-it:free  
openrouter/arcee-ai/trinity-mini:free  
ollama/gpt-oss:120b-cloud
```

Replace with the models you want to use.

This document was translated from Portuguese to English using AI.