



YouTube @CafecomDadoseGatos

Table of Contents

Remove OpenClaw via Docker Desktop	1
1) Stop and delete the “stack” (containers)	1
2) Delete OpenClaw volumes (full reset)	1
3) Remove images (free disk space)	2
4) Delete “Builds” (FULL build cache)	2
Info: Two ways to install OpenClaw (Docker)	2
Explaining each installation method in detail	3

Remove OpenClaw via Docker Desktop

1) Stop and delete the “stack” (containers)

1. Open Docker Desktop → **Containers**
2. Find the OpenClaw group/app (usually grouped by project name)
3. Click **Stop** on the group (or Stop on all containers)
4. Click **Delete / Remove** on the group

This removes the containers.

2) Delete OpenClaw volumes (full reset)

1. Go to **Volumes**
2. Look for volumes with the project name (common examples):
 - openclaw_*
 - openclaw-full_*

- <folder-name>_openclaw_data
- <folder-name>_workspace

3. Delete all OpenClaw volumes

This deletes: token/config, workspace, memory/history, and all persistent data.

If you don't remove volumes, many things will "come back the same" on the next installation.

3) Remove images (free disk space)

1. Go to **Images**
2. Search for: openclaw / clawdbot / ghcr.io/openclaw/
3. Remove images related to the stack

This frees a significant amount of disk space.

4) Delete "Builds" (FULL build cache)

1. Go to **Builds**
2. Look for builds/caches related to OpenClaw (sometimes shown by project/repo)
3. Delete / purge anything related

This clears leftover build cache that keeps occupying disk space.

Info: Two ways to install OpenClaw (Docker)

According to the official documentation, OpenClaw can be installed in Docker in two ways: **Quick Start (recommended)** — which I call **FULL** here because it's the most complete and guided path — and a more manual/compact flow, which I'll call **minimal** just to make it easier to understand.

In the "minimal" flow, the documentation shows that integrations and extras can be configured later. However, in practice, this may require more work: some features depend on rebuilding the image and adding extra dependencies (the container is security-focused and runs as a non-root user).

For this reason, I chose to use the **FULL installation**, which tends to be more predictable. Since OpenClaw is constantly evolving, this process may become simpler in future versions.

In the video “**OpenClaw on Docker + Ollama: CLEAN, SECURE and FREE LOCAL AI**”, I used the minimal installation.

In the video with **WhatsApp and Telegram integration**, I used the FULL installation.

Explaining each installation method in detail

1) FULL (Quick Start — recommended by documentation)

This is the “complete” flow recommended by the OpenClaw team for Docker. You run `./docker-setup.sh` at the repository root and it does everything for you:

- Builds the image
- Runs the onboarding wizard
- Starts the gateway via Docker Compose
- Generates the token and saves it in `.env`

This flow also supports advanced options, such as:

- Including system dependencies during build via `OPENCLAW_DOCKER_APT_PACKAGES`
- Persisting `/home/node` via `OPENCLAW_HOME_VOLUME`

2) Basic/Manual (Manual flow — via Compose)

This is the “manual” flow described in the docs:

You build the image and run onboarding and gateway commands explicitly (e.g., `docker build ...`, `docker compose ... onboard`, `docker compose up ...`).

It gives more control, but requires more steps and attention.

If you use `OPENCLAW_EXTRA_MOUNTS` or `OPENCLAW_HOME_VOLUME`, the docs mention that the setup may generate a `docker-compose.extra.yml` file that must be included.

Important note (from the docs, simplified):

The default container is **security-first**, runs as a non-root user, and this limits installing system dependencies “on the fly”.

Because of this, some extras must be added during the image build (for example via OPENCLAW_DOCKER_APT_PACKAGES).

More information (official documentation)

<https://docs.openclaw.ai/install/docker>

Translated from Portuguese to English by AI.