

Google Gemini Cloud Configuration in OpenClaw

Step-by-step guide validated via onboard and model testing through the CLI

Method that worked

openclaw onboard

Chosen Auth

Google Gemini API key

Chosen Google Model

google/gemini-2.5-flash

Validated CLI Test

openclaw models set google/gemini-2.5-flash

Expected Result

Google Gemini integrated and working in OpenClaw

1. Before starting

You must have a valid Google Gemini API key.

OpenClaw must already be installed and running in the local environment.

This guide uses the model google/gemini-2.5-flash.

2. Check your project limits in Google AI Studio

Before configuring the Google provider in OpenClaw, confirm in Google AI Studio that your project has access to the model that will be used.

Gemini API official pricing page — <https://ai.google.dev/gemini-api/docs/pricing?hl=pt-br>

Project rate limits page in Google AI Studio — <https://aistudio.google.com/rate-limit?timeRange=last-28-days>

Project usage page in AI Studio — <https://aistudio.google.com/>

Official rate limits documentation — <https://ai.google.dev/gemini-api/docs/rate-limits?hl=pt-br>

3. Understand RPM, TPM and RPD

These metrics help verify whether the chosen model supports bots, automations, and agentic workflows without hitting project limits too early.

RPM: maximum number of requests per minute.

TPM: maximum number of tokens processed per minute.

RPD: maximum number of requests per day.

4. Correctly interpret negative values in the dashboard

When the dashboard shows something like the example below, this does not represent debt or pending financial credit.

7 / 1K

-995

Use the following interpretation:

7 = usage already performed

1K = maximum limit

-995 = remaining margin before reaching the limit

5. Choose the correct model

For this guide, use the following model:

google/gemini-2.5-flash

This model was chosen because it appeared both in the OpenClaw available model list and in the list of models enabled in the Google AI Studio project. In addition, it is a balanced option in terms of speed, cost, and usage for agent-based systems.

6. Add Google in OpenClaw using onboard

In the terminal, run the command below:

```
openclaw onboard
```

During the wizard, make the following selections:

Screen / option

Selection

Model/auth provider

Google

Google auth method

Google Gemini API key

Default model

google/gemini-2.5-flash

Enable hooks

Skip for now

Install Gateway service

Yes

Gateway service runtime

Node (recommended)

7. Test the Google model through the CLI

After completing the onboard process, validate the Google integration by temporarily switching the active model in the CLI.

openclaw models set google/gemini-2.5-flash

If the command is accepted and the model responds correctly, this confirms:

the authentication with the Gemini API is working

OpenClaw can access the Google provider

the model is available in the configured project

8. Expected result

At the end of the process, Google Gemini should appear integrated and working in OpenClaw. The model selection can be adjusted through the panel or via CLI as needed for tests and agent workflows.

9. Essential commands

openclaw onboard

openclaw models set google/gemini-2.5-flash

Document translated from Portuguese to English by AI.