

# Aprendizado de Máquina e Reconhecimento de Padrões 2021.2



## The Bias-Variance Tradeoff

Based on videos from StatQuest, the course 'Machine Learning' from Andrew Ng, and the book 'Hands-on machine learning with Scikit-Learn, Keras and TensorFlow' from A. Géron

Prof. Dr. Samuel Martins (Samuka)

[samuel.martins@ifsp.edu.br](mailto:samuel.martins@ifsp.edu.br)



# Generalization Error

---

The **Generalization Error** for any machine learning algorithm can be broken down into three parts:

- Bias Error
- Variance Error
- Irreducible Error
  - This part is due to the noisiness of the data itself.
  - The only way to reduce this part of the error is to **clean up the data**
    - Fix the data sources (e.g., broken sensors), or
    - Detect and remove outliers.

# Generalization Error


---

The **Generalization Error** for any machine learning algorithm can be broken down into three parts:

- **Bias Error**
- **Variance Error**


Let's see these errors

- Irreducible Error
  - This part is due to the noisiness of the data itself.
  - The only way to reduce this part of the error is to **clean up the data**
    - Fix the data sources (e.g., broken sensors), or
    - Detect and remove outliers.




e.g., Linear Regression

## **Straight Line**



e.g., Linear Regression

## Straight Line




The **linear model** (straight line) **cannot** capture the **true relationship** between  $x_1$  and  $y$ .

In ML, this inability is called **bias**.

e.g., Linear Regression

## Straight Line



The **linear model** (straight line) **cannot** capture the **true relationship** between  $x_1$  and  $y$ .

In ML, this inability is called **bias**.

### Bias


Error associated to **wrong assumptions (simplifications)** made by a model (e.g., assuming that the data is linear when it is quadratic) to make it **easier to learn**.

### Bias

‘Average distance’ between **predictions** and the **truth**.

e.g., Linear Regression

## Straight Line



(relatively) **high bias**



The **linear model** (straight line) **cannot** capture the **true relationship** between  $x_1$  and  $y$ .

In ML, this inability is called **bias**.

### Bias

Error associated to **wrong assumptions (simplifications)** made by a model (e.g., assuming that the data is linear when it is quadratic) to make it **easier to learn**.


### Bias

‘Average distance’ between **predictions** and the **truth**.



e.g., Linear Regression

## Straight Line



A high-bias model is most likely to underfit the training data.

(relatively) high bias



The **linear model** (straight line) cannot capture the **true relationship** between  $x_1$  and  $y$ .


In ML, this inability is called **bias**.

### Bias

Error associated to **wrong assumptions (simplifications)** made by a model (e.g., assuming that the data is linear when it is quadratic) to make it **easier to learn**.


### Bias

‘Average distance’ between **predictions** and the **truth**.




a more complex model → e.g., high-degree polynomial model

## Squiggly Line



a more complex model → e.g., high-degree polynomial model


## Squiggly Line



The **model** (squiggly line) **can** capture the **true relationship** between  $x_1$  and  $y$ .

a more complex model → e.g., high-degree polynomial model

## Squiggly Line





(very) low bias

'Average distance' between  
**predictions** and the **truth** is  
close to zero.




The **model** (squiggly line) **can** capture  
the **true relationship** between  $x_1$  and  $y$ .



By considering only the **training set errors**, we would pick the **squiggly line** below.




**Straight Line**



(relatively) **high bias**

**Squiggly Line**




'Average distance' between **predictions** and the **truth** is close to zero.

(very) **low bias**


In contrast, the considered **straight line** fits the **validation set** (unseen data) **better** than squiggly line → **better generalization**



**Straight Line**




**Squiggly Line**






Great job fitting the **training set**




Terrible job fitting the **validation set** → not generalize well






In ML, the **difference in fits between datasets** is called **variance**.

**Great job** fitting the **training set**



**Terrible job** fitting the **validation set** → **not generalize well**






In ML, the **difference in fits between datasets** is called **variance**.

also


## Variance

The amount that the **estimate** of the model will **change** if **different training data** was used.

Great job fitting the **training set**



Terrible job fitting the **validation set** → not generalize well





In ML, the **difference in fits between datasets** is called **variance**.

also


## Variance

The amount that the **estimate** of the model will **change** if **different training data** was used.




A **high-variance model** is most likely to **overfit** the training data.



**Great job** fitting the **training set**




**Terrible job** fitting the **validation set** → **not generalize well**



## Squiggly Line



low **bias**  
high **variance**





● estimate

truth


## Straight Line

It cannot capture the **true relationship** between  $x_1$  and  $y$ .

But the **error is similar** for different sets.



(relatively)  
**high bias**  
**low variance**




low **variance**


high **variance**

● estimate

low  
bias




high  
bias



low **variance**

low **bias**




high **variance**

● estimate



high **bias**






# The Bias-Variance Trade-off

---

- Increasing  $\uparrow$  a model's complexity will typically:
  - increase  $\uparrow$  its **variance**
  - reduce  $\downarrow$  its **bias**.
- Reducing  $\downarrow$  a model's complexity will:
  - increases  $\uparrow$  its **bias**
  - reduces  $\downarrow$  its **variance**.

# The Bias-Variance Trade-off

---

- Increasing  $\uparrow$  a model's complexity will typically:
    - increase  $\uparrow$  its **variance**
    - reduce  $\downarrow$  its **bias**.
  - Reducing  $\downarrow$  a model's complexity will:
    - increases  $\uparrow$  its **bias**
    - reduces  $\downarrow$  its **variance**.
- or simply
- Increasing  $\uparrow$  **variance** reduce  $\downarrow$  **bias**, and vice versa.
  - Reducing  $\downarrow$  **variance** increase  $\uparrow$  **bias**, and vice versa.
- 

# The Bias-Variance Trade-off

---

- Increasing  $\uparrow$  a model's complexity will typically:
    - increase  $\uparrow$  its **variance**
    - reduce  $\downarrow$  its **bias**.
  - Reducing  $\downarrow$  a model's complexity will:
    - increases  $\uparrow$  its **bias**
    - reduces  $\downarrow$  its **variance**.
- or simply
- Increasing  $\uparrow$  **variance** reduce  $\downarrow$  **bias**, and vice versa.
  - Reducing  $\downarrow$  **variance** increase  $\uparrow$  **bias**, and vice versa.
- This is why it is called a **trade-off**.

# The Bias-Variance Trade-off

- Increasing  $\uparrow$  a model's complexity will typically:
    - increase  $\uparrow$  its **variance**
    - reduce  $\downarrow$  its **bias**.
  - Reducing  $\downarrow$  a model's complexity will:
    - increases  $\uparrow$  its **bias**
    - reduces  $\downarrow$  its **variance**.
- or simply
- Increasing  $\uparrow$  **variance** reduce  $\downarrow$  **bias**, and vice versa.
  - Reducing  $\downarrow$  **variance** increase  $\uparrow$  **bias**, and vice versa.
- This is why it is called a **trade-off**.




General trend:


- **Linear** ML algorithms often have a high **bias** but a low **variance**.
- **Nonlinear** ML algorithms often have a low **bias** but a high **variance**.

# **Diagnosing Bias vs Variance**

---




! These are hypothetical curves for hypothetical data.



! These are hypothetical curves for hypothetical data.

- Suppose your learning algorithm is performing less well than you were hoping.
- If  $J_{val}(\theta)$  is **high**, is it a **bias** problem or a **variance** problem?



! These are hypothetical curves for hypothetical data.



- Suppose your learning algorithm is performing less well than you were hoping.
- If  $J_{val}(\theta)$  is **high**, is it a **bias** problem or a **variance** problem?



### Bias (underfit):

$J_{train}(\theta)$  is high


$J_{train}(\theta) \approx J_{val}(\theta)$



### Variance (overfit):

$J_{train}(\theta)$  is low

$J_{train}(\theta) \gg J_{val}(\theta)$



These are hypothetical curves for hypothetical data.

- Suppose your learning algorithm is performing less well than you were hoping.
- If  $J_{val}(\theta)$  is **high**, is it a **bias** problem or a **variance** problem?



### Bias (underfit):

$J_{train}(\theta)$  is high


$J_{train}(\theta) \approx J_{val}(\theta)$



### Variance (overfit):

$J_{train}(\theta)$  is low

$J_{train}(\theta) \gg J_{val}(\theta)$



These are hypothetical curves for hypothetical data.

- Suppose your learning algorithm is performing less well than you were hoping.
- If  $J_{val}(\theta)$  is **high**, is it a **bias** problem or a **variance** problem?



### Bias (underfit):

$J_{train}(\theta)$  is high


$J_{train}(\theta) \approx J_{val}(\theta)$



### Variance (overfit):

$J_{train}(\theta)$  is low




$J_{train}(\theta) \gg J_{val}(\theta)$



In reality, we **cannot** calculate the real **bias** and **variance** error terms.



These are hypothetical curves for hypothetical data.





We want an **intermediate solution** between simple and overly complex one.


(relatively)

**low bias**

**low variance**



💡 Three commonly used strategies to find the intermediate model between simple and complex are: **regularization, boosting and bagging.**



💡 We want an **intermediate solution** between simple and overly complex one.

(relatively)  
**low bias**  
**low variance**

# Aprendizado de Máquina e Reconhecimento de Padrões 2021.2



## The Bias-Variance Tradeoff

Prof. Dr. Samuel Martins (Samuka)

[samuel.martins@ifsp.edu.br](mailto:samuel.martins@ifsp.edu.br)

