

CSCI 4830 / 5722

Computer Vision



University of Colorado **Boulder**

CSCI 4830 / 5722

Computer Vision



Dr. Ioana Fleming
Spring 2019
Lecture 15



University of Colorado **Boulder**

Reminders

Submissions:

- Homework 3: Sat 3/2 at 11 pm

Readings:

- Szeliski:
 - chapter 4.1 (Feature detection – Points and patches)
- P&F:
 - chapter 5 (Local features – corners, SIFT features)



University of Colorado **Boulder**

Today

- Interest Points and Corners
- Harris Corner Detection algorithm



University of Colorado **Boulder**

How do we build a panorama?


- We need to match (align) images
- Global methods sensitive to occlusion, lighting, parallax effects. So look for local features that match well.
- How would you do it by eye?



University of Colorado **Boulder**

Matching with Features


- Detect feature points in both images



University of Colorado **Boulder**

Matching with Features

- Detect feature points in both images
- Find corresponding pairs



University of Colorado **Boulder**

Matching with Features


- Detect feature points in both images
- Find corresponding pairs
- Use these pairs to align images



University of Colorado **Boulder**

Matching with Features

- Problem 1:
 - Detect the *same* point *independently* in both images



no chance to match!


We need a repeatable detector



University of Colorado **Boulder**

Matching with Features

- Problem 2:
 - For each point correctly recognize the corresponding one



We need a reliable and distinctive descriptor



University of Colorado **Boulder**

This week: interest points


- Note: “interest points” = “keypoints”, also sometimes called “features”
- Many applications
 - tracking: which points are good to track?
 - recognition: find patches likely to tell us something about object category
 - 3D reconstruction: find correspondences across different views



This week: interest points

- Suppose you have to click on some point, go away and come back after I deform the image, and click on the same points again.


- Which points would you choose?



Invariant Local Features


Image content is transformed into local feature coordinates that are invariant to translation, rotation, scale, and other imaging parameters

Features Descriptors



University of Colorado **Boulder**

Overview of Keypoint Matching



- 1. Find a set of distinctive keypoints**
- 2. Define a region around each keypoint**
- 3. Extract and normalize the region content**
- 4. Compute a local descriptor from the normalized region**
- 5. Match local descriptors**



Goals for Keypoints




Detect points that are *repeatable* and *distinctive*



University of Colorado **Boulder**

Characteristics of good features



- Repeatability
 - The same feature can be found in several images despite geometric and photometric transformations
- Saliency
 - Each feature is distinctive
- Compactness and efficiency
 - Many fewer features than image pixels
- Locality
 - A feature occupies a relatively small area of the image; robust to clutter and occlusion



University of Colorado **Boulder**

Many Existing Detectors Available

Hessian & Harris

[Beaudet '78], [Harris '88]

Laplacian, DoG

[Lindeberg '98], [Lowe 1999]

Harris-/Hessian-Laplace

[Mikolajczyk & Schmid '01]

Harris-/Hessian-Affine

[Mikolajczyk & Schmid '04]

EBR and IBR

[Tuytelaars & Van Gool '04]

MSER

[Matas '02]

Salient Regions

[Kadir & Brady '01]

SIFT

[Lowe 2004]

Others...



Feature extraction: Corners




University of Colorado **Boulder**


Slides from Rick Szeliski, Svetlana Lazebnik, and Kristin Grauman

Corners as distinctive interest points


- We should easily recognize the point by looking through a small window
- Shifting a window in *any direction* should give a *large change* in intensity



“flat” region:
no change in
all directions



“edge”: no
change along the
edge direction




“corner”:
significant change
in all directions



University of Colorado **Boulder**

Slide credit: Alyosha Efros, Darya Frolova, Denis Simakov

Finding Corners



“corner”

At a corner, we expect two important effects.

- there should be large gradients.
- in a small neighborhood, the gradient orientation should swing sharply.

We can identify corners by looking at variations in orientation within a window.

C.Harris and M.Stephens. ["A Combined Corner and Edge Detector."](#) *Proceedings of the 4th Alvey Vision Conference*: pages 147--151. 1988




University of Colorado **Boulder**

Harris corner detection: the math

Consider shifting the window W by (u, v)

- how do the pixels in W change?
- compare each pixel before and after by summing up the squared differences (SSD)
- this defines an SSD “error” $E(u, v)$:



$$E(u, v) = \sum_{(x,y) \in W} (I(x + u, y + v) - I(x, y))^2$$



Harris Detector: Mathematics

Window-averaged change of intensity induced by shifting the image data by $[u, v]$:


$$E(u, v) = \sum_{x, y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

Window function

Shifted intensity


Intensity

Window function $w(x, y) =$



1 in window, 0 outside

or



Gaussian



University of Colorado **Boulder**

Small motion assumption

Taylor Series expansion of I :

$$I(x+u, y+v) = I(x, y) + \frac{\partial I}{\partial x}u + \frac{\partial I}{\partial y}v + \text{higher order terms}$$

If the motion (u, v) is small, then first order approximation is good

$$\begin{aligned} I(x + u, y + v) &\approx I(x, y) + \frac{\partial I}{\partial x}u + \frac{\partial I}{\partial y}v \\ &\approx I(x, y) + [I_x \ I_y] \begin{bmatrix} u \\ v \end{bmatrix} \end{aligned}$$

shorthand: $I_x = \frac{\partial I}{\partial x}$

Plugging this into the formula on the previous slide...




University of Colorado **Boulder**

Harris corner detection: the math

Using the small motion assumption,
replace I with a linear approximation

(Shorthand: $I_x = \frac{\partial I}{\partial x}$)




$$\begin{aligned} E(u, v) &= \sum_{(x,y) \in W} (I(x+u, y+v) - I(x, y))^2 \\ &\approx \sum_{(x,y) \in W} (I(x, y) + I_x(x, y)u + I_y(x, y)v - I(x, y))^2 \\ &\approx \sum_{(x,y) \in W} (I_x(x, y)u + I_y(x, y)v)^2 \end{aligned}$$



Corner detection: the math

$$E(u, v) \approx \sum_{(x,y) \in W} (I_x(x, y)u + I_y(x, y)v)^2$$

$$\approx \sum_{(x,y) \in W} (I_x^2 u^2 + 2I_x I_y uv + I_y^2 v^2)$$



$$\approx Au^2 + 2Buv + Cv^2$$

$$A = \sum_{(x,y) \in W} I_x^2$$

$$B = \sum_{(x,y) \in W} I_x I_y$$

$$C = \sum_{(x,y) \in W} I_y^2$$

- Thus, $E(u,v)$ is locally approximated as a *quadratic form*



University of Colorado **Boulder**

The second moment matrix

The surface $E(u,v)$ is locally approximated by a quadratic form.

$$E(u, v) \approx Au^2 + 2Buv + Cv^2$$

$$\approx \begin{bmatrix} u & v \end{bmatrix} \begin{bmatrix} A & B \\ B & C \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix}$$


$$A = \sum_{(x,y) \in W} I_x^2$$

$\underbrace{}$

\mathbf{M}

$$B = \sum_{(x,y) \in W} I_x I_y$$

$$C = \sum_{(x,y) \in W} I_y^2$$



University of Colorado **Boulder**

Taylor series approx to shifted image

(Shorthand: $I_x = \frac{\partial I}{\partial x}$)

$$\begin{aligned} E(u,v) &\approx \sum_{x,y} w(x,y)[I(x,y) + uI_x + vI_y - I(x,y)]^2 \\ &= \sum_{x,y} w(x,y)[uI_x + vI_y]^2 \\ &= \sum_{x,y} w(x,y)(u-v)\begin{bmatrix} I_x I_x & I_x I_y \\ I_x I_y & I_y I_y \end{bmatrix} \begin{pmatrix} u \\ v \end{pmatrix} \end{aligned}$$



University of Colorado **Boulder**

Harris Detector: Mathematics

Expanding $I(x,y)$ in a Taylor series expansion, we have, for small shifts $[u,v]$, a *bilinear* approximation:

$$E(u, v) \cong [u, v] \ M \begin{bmatrix} u \\ v \end{bmatrix}$$

where M is a 2×2 matrix computed from image derivatives:

$$M = \sum_{x,y} w(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

M is also called “structure tensor”



University of Colorado **Boulder**

The second moment matrix

The surface $E(u,v)$ is locally approximated by a quadratic form.

$$\begin{aligned} E(u, v) &\approx Au^2 + 2Buv + Cv^2 \\ &\approx \begin{bmatrix} u & v \end{bmatrix} \begin{bmatrix} A & B \\ B & C \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} \end{aligned}$$

$$A = \sum_{(x,y) \in W} I_x^2$$




M

$$B = \sum_{(x,y) \in W} I_x I_y$$

$$C = \sum_{(x,y) \in W} I_y^2$$

Let's try to understand its shape.




University of Colorado **Boulder**

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} \underbrace{\begin{bmatrix} A & B \\ B & C \end{bmatrix}}_{\mathbf{M}} \begin{bmatrix} u \\ v \end{bmatrix}$$

$$A = \sum_{(x,y) \in W} I_x^2$$


$$B = \sum_{(x,y) \in W} I_x I_y$$

$$C = \sum_{(x,y) \in W} I_y^2$$



Horizontal edge: $I_x = 0$

$$\mathbf{M} = \begin{bmatrix} 0 & 0 \\ 0 & C \end{bmatrix}$$




University of Colorado **Boulder**

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} \underbrace{\begin{bmatrix} A & B \\ B & C \end{bmatrix}}_{\mathbf{M}} \begin{bmatrix} u \\ v \end{bmatrix}$$

$$A = \sum_{(x,y) \in W} I_x^2$$


$$B = \sum_{(x,y) \in W} I_x I_y$$

$$C = \sum_{(x,y) \in W} I_y^2$$



Vertical edge: $I_y = 0$

$$\mathbf{M} = \begin{bmatrix} A & 0 \\ 0 & 0 \end{bmatrix}$$



University of Colorado **Boulder**

Harris Detector: Mathematics

Intensity change in shifting window: eigenvalue analysis

The shape of M tells us something about the *distribution of gradients* around a pixel

We can visualize M as an ellipse with axis lengths determined by the *eigenvalues* of M and orientation determined by the *eigenvectors* of M


λ_{\max} , λ_{\min} : eigenvalues of M

Ellipse equation:

$$E(u, v) = \text{const}$$

$$E(u, v) \cong [u, v] M \begin{bmatrix} u \\ v \end{bmatrix}$$

Iso-intensity contour of $E(u, v)$






University of Colorado **Boulder**

Corners as distinctive interest points

$$M = \sum w(x, y) \begin{bmatrix} I_x I_x & I_x I_y \\ I_x I_y & I_y I_y \end{bmatrix}$$

2 x 2 matrix of image derivatives (averaged in neighborhood of a point).



Notation:

$$I_x \Leftrightarrow \frac{\partial I}{\partial x}$$

$$I_y \Leftrightarrow \frac{\partial I}{\partial y}$$


$$I_x I_y \Leftrightarrow \frac{\partial I}{\partial x} \frac{\partial I}{\partial y}$$



University of Colorado **Boulder**

What does this matrix reveal?

First, consider an axis-aligned corner:



University of Colorado **Boulder**

What does this matrix reveal?

First, consider an axis-aligned corner:

$$M = \sum \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix} \Rightarrow \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix}$$

This means dominant gradient directions align with x or y axis

Look for locations where **both** λ 's are large.

If either λ is close to 0, then this is **not** corner-like.


What if we have a corner that is not aligned with the image axes?



University of Colorado **Boulder**

What does this matrix reveal?

Since M is symmetric, we have $M = X \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} X^T$




The *eigenvalues* of M reveal the amount of intensity change in the two principal orthogonal gradient directions in the window.




University of Colorado **Boulder**

Corner response function




“edge”:

$$\begin{aligned}\lambda_1 &>> \lambda_2 \\ \lambda_2 &>> \lambda_1\end{aligned}$$



“corner”:

λ_1 and λ_2 are large,
 $\lambda_1 \sim \lambda_2$;



“flat” region

λ_1 and λ_2 are small;

$$f = \frac{\lambda_1 \lambda_2}{\lambda_1 + \lambda_2}$$




University of Colorado **Boulder**

Corner response function

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha(\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

R = “cornerness”




University of Colorado **Boulder**

Harris corner detector

- 1) Filter image with Gaussian window W .
- 2) Compute magnitude of the gradient everywhere.
- 3) Compute M matrix for each image window, using the same W Gaussian window function
- 4) Computer the *cornerness (R)* scores for each image window.
- 5) Find points whose surrounding window gave large corner response ($R > \text{threshold}$)
- 6) Take the points of local maxima (*non-maximum suppression*)



Non-Maximum Supression



University of Colorado **Boulder**


Example of Harris application



University of Colorado **Boulder**

Kristen Grauman

Example of Harris application



Compute corner response at every pixel.



University of Colorado **Boulder**

Kristen Grauman

Example of Harris application



University of Colorado **Boulder**

Kristen Grauman

Properties of the Harris corner detector

- Rotation invariant?

Yes $M = X \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} X^T$


- Scale invariant?



University of Colorado **Boulder**

Properties of the Harris corner detector

- Rotation invariant? Yes
- Scale invariant? No



All points will be
classified as **edges**

Corner !



University of Colorado **Boulder**