

## 33. Interval arithmetic

## Last time

- Spectral methods for ODE boundary-value problems

## Goals for today

- Interval arithmetic
- Need for interval arithmetic
- Basic properties

## Motivation: Ground state of atomic cluster

- $N$  atoms at positions  $\mathbf{x}_i \in \mathbb{R}^3$
- **Interaction potential**  $V(r_{ij})$  between pairs
- Ground state: Minimize **potential energy**

$$V(\mathbf{x}_1, \dots, \mathbf{x}_N) := \sum_{i=1}^N \sum_{j>i} V(r_{ij})$$

- $r_{ij} := \|\mathbf{x}_i - \mathbf{x}_j\|$  is distance between atoms  $i$  and  $j$

# Lennard-Jones potential

- Standard model of interaction between argon atoms:

$$V(r) := 4 \left( \frac{1}{r^{12}} - \frac{1}{r^6} \right)$$

- Problem: There are *lots* of local minima
- Estimated to grow like  $O(e^N)$
- To find the ground state we need **global optimization**

# Standard floats are not always good enough

- Example by Siegfried Rump: Calculate

$$f(a, b) = 333.75b^6 + a^2(11a^2b^2 - b^6 - 121b^4 - 2) + 5.5b^8 + a,$$

at  $a = 77617$  and  $b = 33096$

# Standard floats are not always good enough

- Example by Siegfried Rump: Calculate

$$f(a, b) = 333.75b^6 + a^2(11a^2b^2 - b^6 - 121b^4 - 2) + 5.5b^8 + a,$$

at  $a = 77617$  and  $b = 33096$

- Something weird happens when trying `Float32`, `Float64` and `BigFloat`

# Standard floats are not always good enough

- Example by Siegfried Rump: Calculate

$$f(a, b) = 333.75b^6 + a^2(11a^2b^2 - b^6 - 121b^4 - 2) + 5.5b^8 + a,$$

at  $a = 77617$  and  $b = 33096$

- Something weird happens when trying `Float32`, `Float64` and `BigFloat`
- Get totally different answers
- Which is correct?



## Standard floats are not always good enough II

- Example by William Kahan: Consider

$$f(x) = \frac{1}{50} \log |3(1 - x) + 1| + x^2 + 1$$

- Looks uncomplicated if you sample it at many points to draw it

## Standard floats are not always good enough II

- Example by William Kahan: Consider

$$f(x) = \frac{1}{50} \log |3(1 - x) + 1| + x^2 + 1$$

- Looks uncomplicated if you sample it at many points to draw it
- Is it really that uncomplicated?

## What is 0.1 anyway?

- When I type `0.1`, what does it mean?

## What is 0.1 anyway?

- When I type `0.1`, what does it mean?
- It's a floating-point `Float64` value. Which value?

## What is 0.1 anyway?

- When I type `0.1`, what does it mean?
- It's a floating-point `Float64` value. Which value?
- Look at its exact value:

```
big(0.1)
```

# What is 0.1 anyway?

- When I type `0.1`, what does it mean?
- It's a floating-point `Float64` value. Which value?
- Look at its exact value:

```
big(0.1)
```

- Look at its bits (binary representation):

```
bitstring(0.1)
```

## Calculating with sets

- Can we calculate with *sets* of real numbers instead?

## Calculating with sets

- Can we calculate with *sets* of real numbers instead?
- E.g. “small” sets containing non-representable numbers like 0.1 or  $\pi$



## Calculating with sets

- Can we calculate with *sets* of real numbers instead?
- E.g. “small” sets containing non-representable numbers like  $0.1$  or  $\pi$
- Or larger sets

## Calculating with sets

- Can we calculate with *sets* of real numbers instead?
- E.g. “small” sets containing non-representable numbers like  $0.1$  or  $\pi$
- Or larger sets
- What does it mean to “calculate with a set”?
- What are basic questions about function  $f$  on set  $X$ ?

## Range of a function

- Basic questions concern **range** of a function  $f$  on set  $X$

## Range of a function

- Basic questions concern **range** of a function  $f$  on set  $X$
- $\text{range}(f; X) := \{f(x) : x \in X\}$

## Range of a function

- Basic questions concern **range** of a function  $f$  on set  $X$
- $\text{range}(f; X) := \{f(x) : x \in X\}$
- Set of all possible output values for inputs in  $X$

## Range of a function

- Basic questions concern **range** of a function  $f$  on set  $X$
- $\text{range}(f; X) := \{f(x) : x \in X\}$
- Set of all possible output values for inputs in  $X$
- Mathematics assumes that the range is accessible

## Range of a function

- Basic questions concern **range** of a function  $f$  on set  $X$
- $\text{range}(f; X) := \{f(x) : x \in X\}$
- Set of all possible output values for inputs in  $X$
- Mathematics assumes that the range is accessible
- But can we **calculate** the range of a function?

## Range II

- Conceptually easy: Find minimum and maximum over  $X$



## Range II

- Conceptually easy: Find minimum and maximum over  $X$
- That is itself a difficult optimization problem!

## Range II

- Conceptually easy: Find minimum and maximum over  $X$
- That is itself a difficult optimization problem!
- Can we obtain *some* information about range more easily?

## Range II

- Conceptually easy: Find minimum and maximum over  $X$
- That is itself a difficult optimization problem!
- Can we obtain *some* information about range more easily?
- What would be most useful?
- What are simplest sets to think about?

# Intervals

- Range of real numbers
- Simplest: (closed) **interval** on real line:

$$X = [a..b] = \{a \leq x \leq b : x \in \mathbb{R}\}$$

- (Standard notation  $[a, b]$ )

# Intervals

- Range of real numbers
- Simplest: (closed) **interval** on real line:

$$X = [a..b] = \{a \leq x \leq b : x \in \mathbb{R}\}$$

- (Standard notation  $[a, b]$ )
- Infinite (uncountable) number of elements  $x$  in set  $X$

# Intervals

- Range of real numbers
- Simplest: (closed) **interval** on real line:

$$X = [a..b] = \{a \leq x \leq b : x \in \mathbb{R}\}$$

- (Standard notation  $[a, b]$ )
- Infinite (uncountable) number of elements  $x$  in set  $X$
- How can we represent an interval  $X$  in Julia?

# Intervals in Julia

- Define new SimpleInterval type:

```
struct SimpleInterval  
    inf::Float64  
    sup::Float64  
end
```

# Intervals in Julia

- Define new `SimpleInterval` type:

```
struct SimpleInterval  
    inf::Float64  
    sup::Float64  
end
```

- And set operations, e.g.

```
Base.in(a::Real, X::SimpleInterval) = X.inf ≤ a ≤ X.sup
```



# Intervals in Julia

- Define new `SimpleInterval` type:

```
struct SimpleInterval
    inf::Float64
    sup::Float64
end
```

- And set operations, e.g.

```
Base.in(a::Real, X::SimpleInterval) = X.inf ≤ a ≤ X.sup
```

- Can we define *arithmetic* on these *sets*?

# Functions on intervals

- Given an interval  $X$
- Suppose  $f$  is a function like  $f(x) = x^2$

# Functions on intervals

- Given an interval  $X$
- Suppose  $f$  is a function like  $f(x) = x^2$
- Can we define  $f(X)$ ?
- What should this mean?

# Functions on intervals

- Given an interval  $X$
- Suppose  $f$  is a function like  $f(x) = x^2$
- Can we define  $f(X)$ ?
- What should this mean?
- How should we calculate it?

# Functions on intervals

- Given an interval  $X$
- Suppose  $f$  is a function like  $f(x) = x^2$
- Can we define  $f(X)$ ?
- What should this mean?
- How should we calculate it?
- Goal: Find **range** of  $f$  over  $X$ , i.e. set of possible values

## Functions on intervals II

- Apply  $f$  to  $X$  by applying  $f$  to *each element of  $X$*
- Will give a new set as output
- Obviously *impossible* to do this since too many elements
- So instead use maths to calculate *what answer should be*

## Example: Squaring

- Let's think about  $f(x) = x^2$
- With  $X = [1..2]$
- What is result of squaring every element?
- So how can we define  $X^2$ ?
- What about  $[-1..2]^2$ ?

# Squaring II

■ General rule:

$$\begin{aligned} [a, b] &:= [a^2, b^2] && \text{if } a \geq 0 \\ &:= [0, \max(a^2, b^2)] && \text{if } a < 0 \text{ and } b > 0 \\ &:= [b^2, a^2] && \text{if } a < b < 0 \end{aligned}$$



## Example: Addition

- How should we define  $X + Y$  for intervals  $X$  and  $Y$ ?
- Want to add any  $x$  and  $y$  with  $x \in X$  and  $y \in Y$
- Problem: What is  $[0..1] - [0..1]$ ?

## Application: Finding roots

- Define  $f(x) = x^2 - 2$
- Calculate for  $X = [3..4]$
- Get  $f(X) = [7..14]$
- This does not contain 0
- Hence  $0 \notin \text{range}(f; X)$
- So *there is no root of  $f$  in  $X$*

# Review

- Defined arithmetic on intervals
- Applications to root finding and global optimization