

# DIGH 402 - Introduction to Digital Humanities Design and Programming

Spring Semester 2015

Week 7

# PHP and MySQL

### Week 6

- 1. Forking a repo
- 2. <u>GitHub 402framework</u>
- 3. testing with DB

DIGH 402 - Introduction to Digital Humanities Design and Programming



OOP way of including a file within a class etc

Parent to child

A method used for getting

A method used for setting

Variable value persistent across classes and not a scope

Process of placing data (data structure etc) with methods inside the same module, normally a class

Instance of a class

Functions within a class

Concept of setting members of a class as private etc

If included in a class it will always be called

A way of passing data to a method

Object created by a class

Represent essential features without including background details or explanations

#### Word Search - answers

Require / OOP way of including a file within a class etc

Inheritance / Parent to child

Getter / A method used for getting

Setter / A method used for setting

Constant / Variable value persistent across classes and not a scope

**Encapsulate** / Process of placing data (data structure etc) with methods inside the same module, normally a class

Object / Instance of a class

Methods / Functions within a class

Scope / Concept of setting members of a class as private etc

Constructor / If included in a class it will always be called

Parameters / A way of passing data to a method

Instance / Object created by a class

**Abstraction** / Represent essential features without including background details or explanations

# JQuery & JQuery UI

Framework plugins and Javascript

- how do we use JQuery and Javascript in the framework design
- plugin design and implementation
- Spring break work on JQuery and Javascript...

Object Oriented Programming - Abstract overview of current framework structure

#### <u>Initial Outline - next on our to-do list</u>

- send content to view before returning for output
  - allows us to introduce view plugins, viewers etc
- add some templating and design for our framework
- allow for greater flexibility and abstraction of content, format, and parameters
- add some more error checking and reporting...
- add default content handler for non controller/format/params URI requests including index.php

and so on...

Object Oriented Programming - Abstract overview of current framework structure

<u>Initial Outline - basic theme templates and views for the framework</u>

- added 'themes' directory to 'design' directory
  - updated directory.php constants for themes
- default template for framework includes both default theme, css, and javascript
- user themes will build on default template and replace default theme where necessary
  - css, javascript etc can be customised as required
- header metadata will be customised per use (eg: project installation)
  - meta settings in settings.php file
  - called in view.php draw\_head() method

Object Oriented Programming - Abstract overview of current framework structure

<u>Initial Outline - updated /system/library/loader.php file</u>

- we now need to initialise the theme using the init\_theme() method
- we require the view.php file to set the theme, theme dir, and allow us to check the current user select theme
- init\_theme() method and setters in view.php are used to check and set the user theme
- draw\_theme() method allows us to call various view.php methods to actually build and render our template and theme
- load\_controller() method now checks selected theme, and then uses the draw\_theme()
  method to draw the framework template with the user's selected content

Object Oriented Programming - Abstract overview of current framework structure

<u>Initial Outline - /frame/view/html\_builder.php file</u>

- parent class to view.php View class
  - allows abstracted HTML building for the framework viewer and template
- currently allows to build any specified HTML start and end element
  - two methods start\_element() and end\_element()
- start\_element() methods accepts two parameters for required HTML element with associated attributes and attribute values
- end\_element() method simply accepts one parameter for the required HTML element
- values are returned for output as required within template rendering, currently within View and Loader classes

Object Oriented Programming - Abstract overview of current framework structure

### <u>Initial Outline - /system/library/view.php file</u>

- View class is currently the main rendering class for the 402 framework
- View class extends BuildHTML class thereby allowing it to use the HTML building methods
- setters for selected user theme
- various draw methods for defined structural components of the framework's HTML template
- currently output start and end elements for each structural component (eg: head, body, header, footer...)
  - draw\_main() and draw\_middle() methods also accepts parameters for outputting content

Object Oriented Programming - Abstract overview of current framework structure

402framework - Database update for Week 7

- SQL Week 7
- Update local database for new weekly import
  - drop existing 402framework
  - import 402framework.sql from week7 on GitHub
  - set collation for DB to utf-8\_unicode
  - check privileges for 402 users and DB
  - test with existing framework

Object Oriented Programming - Abstract overview of current framework structure constants.php file

- updated for default html framework and CSS and JS
- added constants for default HTML elements used within template
  - used with loader, view, and htmlbuilder
  - allows abstraction of element names for HTML markup of framework template
- added constants for default CSS and JS files for framework template
  - frame and grid CSS
  - frame and JQuery js

Object Oriented Programming - Abstract overview of current framework structure

### /system/library/functions.php file

- class Functions stores methods (functions) for general framework wide usage
- required from loader.php file
- first function allows us to use an extended function of implode() to output attributes
- array\_implode() implodes an array of element attributes to output a string of attributes for use with a specified element
- other general functions will be added

Object Oriented Programming - Abstract overview of current framework structure

#### Initial Outline - default css and js file

- default css stylesheets and javascript functions for the framework
  - design/css/frame.css
  - design/css/grid.css
  - design/js/frame.js
- javascript will be built upon JQuery library
  - design/js/jquery.js
- selected personal theme will supplement and customise the default stylesheets and javascript functions
  - chosen theme added as parameter to init\_theme() method in bootstrap.php
- colours, javascript functions etc can be added in chosen theme directory
  - eg: design/themes/minimal etc

Object Oriented Programming - Abstract overview of current framework structure

### /design/css/frame.css

- basic css for structural elements of the framework
  - body
  - header
  - centre and node\_content
  - sidebar
  - footer
- basic css styling for framework layout including
  - body
  - headers (h1 to h6)
  - links

and so on...

Object Oriented Programming - Abstract overview of current framework structure

### /design/css/grid.css

- allows framework template to be organised using a grid
- grid can be up to 12 divisions horizontally
  - eg: a parent container specified as grid 12
    - two child divisions specified as grid 3 and grid 9
    - each grid is calculated as an approximate percentage upto 100%
    - small allowance for borders etc on each grids
    - required size of grid set as a value within the class attribute of the element

Initial Outline - framework so far...

- HTML template output Home Page
- HTML template output sample content