SPL 2.0: A Declarative Language for Agentic Workflow Orchestration

Wen G. Gong

wen.gong.research@gmail.com

Abstract

We present SPL 2.0, a declarative language for orchestrating LLM-powered agentic workflows. Unlike existing imperative frameworks (LangGraph, AutoGen, CrewAI) that require Python programming and manual orchestration, SPL 2.0 enables users to express workflow intent in a SQL-inspired syntax — the specification layer between natural language and execution. Our stack comprises four layers: (1) Natural Language as the interface layer; (2) a planned text2SPL compiler (basic prototype implemented); (3) SPL 2.0, the declarative language with primitives for LLM invocation, semantic evaluation, iterative refinement, and structured error handling; and (4) a pluggable runtime supporting local (Ollama), cloud (OpenRouter, Claude), and decentralized (Momagrid) execution. SPL 2.0 introduces three key primitives absent in existing solutions: EVALUATE for LLM-judged condition evaluation with hybrid deterministic-semantic branching, WHILE with semantic termination for iteration based on output quality rather than fixed counters, and EXCEPTION with a formal taxonomy of LLM-specific failure modes. We validate the language through a 21-recipe cookbook covering 8 agentic workflow categories, tested across multiple models with 231 automated tests, achieving a 100% end-to-end SPL success rate (20/20 SPL recipes) on a single local GPU node running gemma3 via Ollama; Recipe 10 (Batch Test) is a bash orchestration script and is excluded from SPL accounting. The reference implementation is open-source, with a Click-based CLI that enables zero-config execution from prompt to result in a single command.

Keywords: declarative language, agentic workflows, LLM orchestration, structured prompt language, semantic evaluation

1. Introduction

1.1 The Problem: Fragmentation in LLM Programming

Building agentic AI systems today demands a daunting intersection of skills. A practitioner must master prompt engineering for effective LLM interaction, Python programming for orchestration logic, API wrangling across disparate model providers, and manual state management for multi-step reasoning. Each popular framework — LangGraph [1], AutoGen [2], CrewAI [3] — introduces its own abstractions, API surfaces, and execution models, creating a fragmented ecosystem where knowledge transfers poorly and vendor lock-in is the norm.

This situation echoes a pattern the data industry has seen before. In the early days of relational databases, programmers wrote imperative C and COBOL code to traverse data structures, manage cursors, and handle errors — all in application-specific ways. The introduction of SQL in the 1970s transformed this landscape by providing a declarative specification layer: users described *what* data they wanted, not *how* to retrieve it. This separation enabled decades of optimizer innovation underneath a stable surface language. The current state of LLM programming is analogous to the pre-SQL era: powerful capabilities buried under layers of imperative glue code.

The barrier to entry compounds the problem. To build even a simple self-refining agent — one that drafts, critiques, and revises its own output — a developer must write 80–150 lines of Python across multiple framework abstractions. This excludes the vast population of domain experts, analysts, and researchers who understand their workflows but lack the software engineering skills to implement them as agentic systems.

1.2 The Opportunity: Declarative Agentic Workflows

Consider the world an AI application runs in today: a zoo of models — Llama, Gemma, Mistral, Claude, GPT, Qwen, Phi — deployed across a zoo of infrastructure: local GPUs in a developer's office, cloud APIs on three continents, community nodes contributed by universities and individuals worldwide. Each model has different capabilities, different context limits, different cost profiles. Each deployment has different latency, availability, and authentication requirements.

A student new to AI who wants to build a simple self-refining essay agent faces an immediate question that has nothing to do with their goal: *which model, on which infrastructure, accessed through which API, orchestrated with which Python framework?* Before writing a single line of logic, they must make a dozen infrastructure decisions. Most give up. Those who persist write code that is tightly coupled to one model, one provider, one framework — and must be rewritten when any of those change.

The opportunity SPL 2.0 addresses is this: **what if you could program against the entire zoo declaratively, with two primitives?**

```
SELECT  -- assemble what goes into the model
    system_role('You are a helpful assistant.'),
    context.question AS question
GENERATE answer(question)   -- invoke the model, capture what comes out
```

This is the complete I/O interface to any model, on any infrastructure. SELECT assembles the input. GENERATE invokes the model and captures the output. The runtime — not the programmer — decides which model in the zoo executes the inference, and where. The same two lines run on a local Ollama instance, an OpenRouter cloud API, or a Momagrid community node, without modification.

A declarative approach to this zoo offers three structural advantages. First, it enables **compiler-level optimization**: when the system understands intent rather than following imperative steps, it can merge redundant LLM calls, cache repeated contexts, and route queries to cost-optimal models — optimizations invisible to the user but impossible for an imperative framework to perform automatically. Second, it enforces **separation of concerns** between what the workflow accomplishes and how it executes, allowing the same specification to run on local hardware, cloud APIs, or decentralized compute grids without modification. Third, it achieves **broad accessibility**: the SELECT/GENERATE mental model is simple enough for a student encountering AI programming for the first time, and powerful enough for production agentic workflows.

The deeper structural insight underlying SPL 2.0 is a parallel with Oracle's database programming stack:

- **SELECT/GENERATE** are to SPL 2.0 what **SELECT** is to SQL — the atomic I/O contract with the backend (database rows, or LLM inference).
- **PROMPT** is the named, executable unit that binds them — analogous to a single SQL query.

- **WORKFLOW** is to SPL 2.0 what **PL/SQL** is to Oracle — the procedural extension that adds variables, loops, branching, and exception handling around declarative queries.

This is not an analogy by convenience; it is a deliberate design choice. The SQL-to-PL/SQL evolution solved the identical problem in a different domain: how to add procedural control flow to a declarative query language without sacrificing the optimizer's ability to reason about individual queries. SPL 2.0 applies this proven architectural pattern to LLM orchestration — across a global zoo of models that did not exist when SQL was designed.

1.3 Our Contribution: The SPL Stack

We make the following contributions:

1. **A four-layer architecture** for LLM workflow execution:
   - *Natural Language* (interface) — the natural input modality
   - *text2SPL* (compiler) — translates natural language intent into executable specification
   - *SPL 2.0* (specification) — a declarative language with a formal EBNF grammar
   - *Pluggable runtime* — adapters for Ollama (local), OpenRouter (cloud), Claude CLI (Anthropic), and Momagrid (decentralized)
2. **Three novel language primitives** for agentic workflows:
   - **EVALUATE** with hybrid deterministic-semantic condition evaluation, where the LLM itself serves as a runtime judge
   - **WHILE** with semantic termination conditions, enabling loops that iterate until output quality is "satisfactory" rather than until a counter reaches N
   - **EXCEPTION** with a formal taxonomy of LLM-specific failure modes (HallucinationDetected, RefusalToAnswer, ContextLengthExceeded, BudgetExceeded, etc.)
3. **A reference implementation** consisting of a Python Click-based CLI, a recursive-descent parser, 5 runtime adapters, 231 automated tests, and a 21-recipe cookbook spanning 8 categories of agentic workflow patterns.
4. **Backward compatibility** with SPL 1.0 [4]: all existing SPL 1.0 PROMPT statements execute unchanged in SPL 2.0, and the new WORKFLOW constructs are purely additive extensions.

1.4 Paper Organization

Section 2 surveys the motivation and positions SPL 2.0 within the landscape of related work. Section 3 presents the language design — primitives, semantics, and formal grammar. Section 4 describes the implementation architecture. Section 5 discusses compilation and optimization opportunities. Section 6 details the Momagrid decentralized runtime. Section 7 evaluates expressiveness, performance, cost efficiency, and developer experience. Section 8 discusses strengths, limitations, and future directions. Section 9 concludes. Appendix E contains the complete cookbook with 21 recipes and end-to-end experiment results. Appendix F presents the full batch run data.

2. Motivation and Related Work

2.1 The Evolution of Data Programming

The history of data programming offers a clear precedent for the transition SPL 2.0 proposes. In the 1970s, IBM's System R project demonstrated that a declarative query language (SQL) could match or exceed the performance of hand-coded navigational database access, because the declarative form exposed optimization opportunities invisible in imperative code [5]. By the 1980s, SQL had become the industry standard, and Oracle's PL/SQL extension demonstrated that procedural control flow (loops, variables, exception handling) could be layered on top of declarative queries without sacrificing the optimizer's ability to reason about individual SELECT statements [6].

The parallel to LLM programming is direct. Today's imperative frameworks — LangGraph's state graphs, AutoGen's conversation loops, CrewAI's role-based agents — are the equivalent of pre-SQL navigational code: powerful, flexible, and impossibly fragmented. SPL 2.0 proposes that the same declarative revolution can occur for LLM orchestration, following the same evolutionary pattern:

1. **Atomic declarative queries** (SQL SELECT → SPL PROMPT): express what you want from a single LLM call.
2. **Procedural extensions** (PL/SQL → SPL WORKFLOW): add variables, loops, branching, and error handling around those queries.
3. **Optimizer infrastructure** (Catalyst → SPL IR): enable the system to rewrite and optimize execution plans.

2.2 Current Approaches to Agentic Systems

The landscape of LLM orchestration systems can be organized along two axes: **declarative vs. imperative** paradigm and **query-level vs. workflow-level** scope.

Imperative Frameworks

LangGraph [1] models agent workflows as directed graphs with explicit state management. Nodes represent computation steps, edges represent transitions, and state is passed through a mutable dictionary. The framework provides fine-grained control but requires significant Python expertise and offers no formal grammar or optimizer.

AutoGen [2] focuses on multi-agent conversation patterns where agents exchange messages. Its strength lies in natural dialogue flows, but orchestration logic is embedded in Python code and tightly coupled to the runtime.

CrewAI [3] introduces a role-based metaphor where specialized agents collaborate. While intuitive for team-like workflows, it remains Python-first and provides no path to compilation or optimization.

PydanticAI takes a code-first approach, rejecting complex abstractions in favor of standard Python with type hints. It prioritizes developer ergonomics over declarative specification.

Declarative Systems

LMQL [7] (ETH Zurich, 2022) is the pioneer of SQL-like LLM interaction, combining declarative queries with output constraints (type, length, regex). LMQL achieves 26–85% cost savings through constrained decoding. However, it operates at the *query level* — individual prompts with output validation — and does not provide constructs for multi-step workflows, iterative refinement, or exception handling.

DSPy [8] (Stanford, 2023) introduces declarative modules (Predict, ChainOfThought) and a compiler that automatically optimizes prompts via few-shot bootstrapping. DSPy achieves remarkable results — GPT-3.5 outperforming expert-crafted demonstrations by up to 46%. However, DSPy's "declarative" is at the *module interface level*: it optimizes what prompts to use, not how to orchestrate multi-step workflows. It provides no loops, no exception handling, and no formal grammar.

SGLang [9] (UC Berkeley, 2023) provides a structured generation frontend with runtime optimizations (RadixAttention for KV cache reuse), achieving up to 6.4x throughput improvement. SGLang optimizes *inference execution*, not workflow orchestration — it operates below the abstraction level of agentic patterns.

Specification Schemas

Agent Spec [10] (Oracle Labs, 2025) defines a YAML/JSON schema for specifying agents and workflows in a framework-agnostic way, with a standardized evaluation harness. Agent Spec solves *portability* (define once, run anywhere) but is a configuration format, not an executable language — it lacks control flow, iteration, and exception handling within the specification itself.

SLANG [11] (2025) proposes a minimal meta-language with three primitives (stake, await, commit) for formalizing multi-agent routing. SLANG's contribution is formalization of *coordination*, not computation — it does not address generation, evaluation, or error recovery.

Concurrent Work

eBay DSL [12] (December 2025) presents a declarative system separating agent workflow specification from implementation, achieving 60% reduction in development time and 3x deployment velocity. The eBay DSL focuses on enterprise pipeline configuration (data serialization, filtering, API orchestration) across multiple backend languages. It does not formalize LLM-specific primitives like semantic evaluation or hallucination handling.

Auton [13] (February 2026) formalizes agent execution as an augmented POMDP with a declarative "Cognitive Blueprint" schema. Auton's contribution is governance and safety constraint enforcement via policy projection. It specifies agents as configuration artifacts (YAML/JSON) rather than providing an executable programming language.

Agentics 2.0 [14] (IBM, March 2026) introduces a logical transduction algebra where LLM calls are typed semantic transformations composable via algebraically grounded operators in asynchronous Map-Reduce programs. This is the closest concurrent work in terms of formalism, but takes an algebraic rather than SQL-inspired approach.

Positioning Summary

Table 1: Landscape Comparison

System	Paradigm	Scope	Has Grammar	Semantic Eval	LLM Exceptions	Multi-Runtime
LangGraph	Imperative	Workflow	No	No	No	No
AutoGen	Imperative	Conversation	No	No	No	No
CrewAI	Imperative	Role-based	No	No	No	No
LMQL	Declarative	Query	Yes	No (structural)	No	No
DSPy	Declarative	Module	No	No (compile-time)	No	No
SGLang	Declarative	Inference	Yes	No	No	No
Agent Spec	Declarative	Configuration	Yes (schema)	No	No	Yes (portable)
eBay DSL	Declarative	Pipeline	Yes	No	No	Yes
Agentics 2.0	Algebraic	Data workflow	Yes (algebra)	No	No	No
SPL 2.0	**Declarative**	**Query + Workflow**	**Yes (EBNF)**	**Yes**	**Yes**	**Yes (5 adapters)**

SPL 2.0 is the only system that combines a formal EBNF grammar, LLM-as-judge primitives (EVALUATE), an LLM-specific exception hierarchy (EXCEPTION), and a unified adapter layer spanning local, cloud, and decentralized execution — all within a single coherent language that spans both atomic queries and procedural workflows.

2.3 SQL Extensions and Their Limitations

A natural question is whether existing SQL extensions could serve the purpose SPL 2.0 addresses. We analyze three candidates:

Common Table Expressions (CTEs) provide sequential composition of queries but offer no iteration, no branching on computed results, and no mechanism for invoking external computation (like an LLM).

Recursive CTEs add iteration but with strictly deterministic termination conditions — the recursion must converge on a fixed point defined by the query algebra. Semantic termination ("continue until the output is coherent") is impossible.

Stored Procedures (PL/SQL, T-SQL) provide full procedural control flow but are designed for database operations, not LLM invocation. They have no concept of probabilistic output, semantic evaluation, or model routing.

Table 2: SQL Extension Capability Matrix

Capability	SQL CTE	Recursive CTE	PL/SQL	SPL 2.0
Sequential composition	Yes	Yes	Yes	Yes
Iteration	No	Yes (fixed)	Yes	Yes (semantic)
LLM invocation	No	No	No	Yes
Semantic evaluation	No	No	No	Yes
Exception handling	No	No	Yes	Yes (LLM-aware)
Model routing	No	No	No	Yes

2.4 Lessons from Proven Architectures

SPL 2.0's design draws deliberately from three proven systems:

From Oracle PL/SQL: block structure (`DO...END`), exception handling with typed exceptions (`WHEN HallucinationDetected THEN`), procedures and packages for code reuse, and the fundamental insight that procedural extensions should layer on top of declarative queries without disturbing the query optimizer.

From Apache Spark: the separation between logical and physical execution plans, the concept of a query optimizer (Catalyst) that rewrites execution strategies, and the idea that the same logical plan can execute on different backends (local, YARN, Kubernetes).

From the JVM: the stable intermediate representation (bytecode) that enables multiple frontend languages and multiple backend targets, and the principle that a well-defined IR is the foundation for an optimization ecosystem.

3. SPL 2.0 Language Design

3.1 Design Principles

SPL 2.0 is governed by five design principles:

P1. Declarative intent over imperative implementation. The programmer specifies *what* the workflow should accomplish — not *which model*, *which node*, or *which execution path* achieves it. This is the essential simplification: the zoo of models deployed around the world is the runtime's problem, not the programmer's. A student writing their first AI workflow and a senior engineer deploying a production pipeline write the same SELECT/GENERATE syntax; the runtime resolves the infrastructure details beneath them. This separation enables the compiler and runtime to make optimization decisions that are invisible to the user but impossible for an imperative framework to perform automatically.

P2. LLM-aware primitives. Rather than repurposing generic control flow constructs for LLM orchestration, SPL 2.0 provides primitives designed specifically for the unique characteristics of LLM computation: probabilistic output, semantic quality assessment, hallucination risk, context length limits, and cost sensitivity.

P3. Compilation target. The language is designed to produce an optimizable intermediate representation (IR), enabling future optimizer passes without changing the surface language.

P4. Unified runtime — one specification, any model, any infrastructure. The adapter pattern decouples the language from any specific model provider. The same `.spl` file executes on a local Ollama instance (a developer's laptop), OpenRouter (100+ cloud models), Claude CLI (Anthropic), or a Momagrid community node (a contributed GPU anywhere in the world) — without changing a single line. The programmer writes against the zoo; the adapter layer tames it. This is not merely an engineering convenience — it is the architectural prerequisite for broad accessibility.

P5. Backward compatibility. All SPL 1.0 [4] programs are valid SPL 2.0 programs. New constructs (WORKFLOW, EVALUATE, WHILE, EXCEPTION) are purely additive extensions.

3.2 Core Primitives

The mental model of SPL 2.0 is grounded in two fundamental primitives that mirror the I/O contract with an LLM: **SELECT** assembles the context that flows *into* the model; **GENERATE** invokes the model and captures what flows *out*. Every other construct in the language is either a named container for SELECT and GENERATE (PROMPT, WORKFLOW) or a flow control mechanism that orchestrates when and how they are invoked (EVALUATE, WHILE, EXCEPTION, PROCEDURE).

This two-sided I/O model deliberately parallels SQL's interaction with a database — SELECT gathers data in, the result set flows out — while extending it to handle the probabilistic, semantic nature of LLM computation.

3.2.1 SELECT — Context Assembly (Input to LLM)

SELECT is the *input* primitive. It aggregates context from multiple sources into the prompt payload that will be sent to the LLM. Nothing executes until SELECT has finished assembling the input.

```
SELECT
    system_role('You are a research analyst. Be precise and cite evidence.'),
    context.topic AS topic,
    memory.get('prior_findings') AS background,
    rag.query('recent developments in ' + @topic, top_k=5) AS references
```

SPL 2.0 provides four context sources within SELECT:

Source	Syntax	What it provides
System role	`system_role('...')`	The model's behavioral instruction
Runtime parameter	`context.field_name`	CLI-injected value at execution time

Source	Syntax	What it provides
Persistent memory	`memory.get('key')`	Key-value store across workflow runs
Semantic retrieval	`rag.query('text', top_k=N)`	Top-N chunks from a vector index

Token budgets on the input side are enforced with `WITH BUDGET n TOKENS`, preventing context window overflow before the LLM is ever invoked.

The analogy to SQL is precise: SQL's `SELECT ... FROM ... WHERE` gathers and filters rows from a database; SPL's `SELECT` gathers and filters context from heterogeneous sources (parameters, memory, retrieval indices) into a prompt. In both cases the reader specifies *what information to collect* — not how the storage layer retrieves it.

3.2.2 GENERATE — LLM Invocation (Output from LLM)

GENERATE is the *output* primitive. It names the generation task, invokes the LLM with the assembled SELECT context, and captures the result.

```
GENERATE answer(prompt)                          -- standalone: output to stdout
GENERATE analysis(@research) INTO @result        -- workflow: capture into variable
GENERATE summary(@analysis) INTO @summary
    WITH OUTPUT BUDGET 500 TOKENS                -- cap output length
    USING MODEL 'claude-opus-4-6'               -- model override per step
```

The argument passed to GENERATE — `answer`, `analysis`, `summary` — is a semantic label that tells the LLM what kind of output to produce. This is the declarative analog of a function name: the developer states *what* the model should generate, not *how*.

Key behaviors:

- **Standalone** (`GENERATE x()`): output goes to stdout; used inside PROMPT statements.
- **Capturing** (`GENERATE x() INTO @var`): output is stored in a workflow variable for downstream steps.

- **Output budget** (`WITH OUTPUT BUDGET n TOKENS`): limits response length, enabling cost control.
- **Model binding** (`USING MODEL '...'`): per-step model override without editing the file; the CLI `--model/-m` flag applies globally across all GENERATE calls at runtime.

GENERATE has no direct SQL equivalent — SQL does not produce probabilistic text — but the pattern it enables is familiar: `GENERATE` is to SPL what a function call is to PL/SQL, except the "function" is the LLM itself.

Together, SELECT and GENERATE form the complete I/O interface to the LLM. SELECT is the *input contract*; GENERATE is the *output contract*. PROMPT and WORKFLOW are simply named scopes that bind them together.

3.2.3 PROMPT — Atomic LLM Query

The PROMPT statement is the fundamental named unit of SPL 2.0: a SELECT clause followed by a GENERATE clause, given a name and made independently executable.

```
PROMPT hello_world
SELECT
    system_role('You are a friendly assistant. Introduce yourself and SPL 2.0 in two sentences.')
GENERATE greeting()
```

This four-line program is a complete, executable SPL file. SELECT assembles the system instruction; GENERATE invokes the LLM and streams the result to stdout. No imports, no configuration, no API keys in code.

Parametric context is supported via `context.param` :

```
PROMPT ollama_proxy
SELECT
    system_role('You are a helpful, knowledgeable assistant.'),
    context.prompt AS prompt
GENERATE answer(prompt)
```

Runtime parameter injection via the CLI: `spl2 run proxy.spl --adapter ollama prompt="Explain quantum computing"` . The model can be overridden at runtime with `--model/-m` without editing the `.spl` file — the CLI flag patches the GENERATE binding at execution time.

PROMPT is to SPL 2.0 what a single SQL SELECT statement is to SQL: the atomic, declarative query unit. WORKFLOW (Section 3.2.4) is what PL/SQL is to SQL: the procedural extension that adds state, loops, and branching around that query unit.

3.2.4 WORKFLOW — Procedural Orchestration

The WORKFLOW statement adds procedural control flow around PROMPT-level operations, analogous to how PL/SQL extends SQL with variables, loops, and exception handling.

```
WORKFLOW chain_of_thought
    INPUT: @topic TEXT
    OUTPUT: @summary TEXT
DO
    GENERATE research(@topic) INTO @research
    GENERATE analyze(@research) INTO @analysis
    GENERATE summarize(@analysis) INTO @summary
    COMMIT @summary WITH status = 'complete'
END
```

Key constructs:

- **INPUT/OUTPUT** declarations define the workflow's typed interface.
- **@variables** (prefixed with `@`) provide mutable state within the workflow scope.
- **GENERATE...INTO** captures LLM output into a variable for use in subsequent steps.
- **COMMIT** finalizes the workflow output with optional metadata. Execution halts after COMMIT.

3.2.5 EVALUATE — LLM-Based Condition Evaluation

EVALUATE is SPL 2.0's first novel primitive. It provides branching where the condition itself may be evaluated by an LLM — a capability no existing language formalizes.

SPL 2.0 supports three evaluation types, detected automatically from the condition syntax:

Deterministic evaluation (zero LLM cost):

```
EVALUATE @score
    WHEN > 0.8 THEN COMMIT @result WITH status = 'high_quality'
    WHEN > 0.5 THEN GENERATE improved(@result) INTO @result
    OTHERWISE RETRY WITH temperature = 0.1
END
```

When the condition is a numeric or boolean comparison, the runtime evaluates it directly with no LLM call.

Semantic evaluation (LLM as judge):

```
EVALUATE @summary
    WHEN 'coherent' THEN COMMIT @summary
    WHEN 'hallucination' THEN RETRY
    WHEN 'incomplete' THEN GENERATE expand(@summary) INTO @summary
END
```

When the condition is a quoted string literal, the runtime invokes the LLM as a judge: "Does this output satisfy the criterion 'coherent'?" This is a low-cost classification call (typically 50–200 tokens) that enables the workflow to make quality-based decisions without external tooling.

Hybrid evaluation (mixed):

```
EVALUATE @response
    WHEN token_count > 4000 THEN truncate          -- deterministic
    WHEN 'off_topic' THEN reframe                   -- semantic
    WHEN confidence < 0.7 THEN verify               -- deterministic
END
```

The detection rule is simple and unambiguous: if the condition is a quoted string, it is semantic; otherwise, it is deterministic. This design choice avoids the need for explicit annotations while maintaining clear semantics.

3.2.6 WHILE...DO — Iteration with Semantic Termination

WHILE is SPL 2.0's second novel primitive. It enables loops where the termination condition can be LLM-judged, with a built-in safety guard against infinite iteration.

```
WHILE @iteration < @max_iterations DO
    GENERATE critique(@current) INTO @feedback

    EVALUATE @feedback
        WHEN 'satisfactory' THEN
            COMMIT @current WITH status = 'complete'
        OTHERWISE
            GENERATE refined(@current, @feedback) INTO @current
            @iteration := @iteration + 1
    END
END
```

The construct supports the same deterministic/semantic/hybrid condition types as EVALUATE. A global iteration limit (default: 10) is enforced by the runtime, raising `MaxIterationsReached` if exceeded. This prevents runaway loops while allowing the workflow to iterate based on output quality rather than arbitrary counts.

Context accumulation across iterations is a natural pattern: each iteration's output becomes the input for the next, enabling progressive refinement without explicit history management.

3.2.7 EXCEPTION — Structured LLM Error Handling

EXCEPTION is SPL 2.0's third novel primitive. It defines a formal taxonomy of LLM-specific failure modes, each with clear semantics and recovery strategies.

Table 3: LLM Exception Taxonomy

Exception	Trigger Condition	Typical Recovery
HallucinationDetected	Output fails fact-checking	Regenerate with lower temperature
RefusalToAnswer	Model declines the request	Log and COMMIT partial result
ContextLengthExceeded	Input exceeds model context window	Compress context and RETRY
ModelOverloaded	Provider rate limit or capacity error	Wait and RETRY
BudgetExceeded	Token budget exhausted	COMMIT best available result
QualityBelowThreshold	Output quality score too low	Regenerate or escalate to better model
MaxIterationsReached	WHILE loop hit iteration limit	COMMIT current best effort

These exceptions are caught in structured handlers:

```
WORKFLOW safe_generation
    INPUT: @prompt text
    OUTPUT: @result text
DO
    GENERATE response(@prompt) INTO @result
    GENERATE quality_score(@result) INTO @score

    EVALUATE @score
        WHEN > 0.8 THEN COMMIT @result WITH status = 'high_quality'
        WHEN > 0.5 THEN
            GENERATE improved(@result, @prompt) INTO @result
            COMMIT @result WITH status = 'refined'
        OTHERWISE RETRY WITH temperature = 0.1
    END

EXCEPTION
    WHEN HallucinationDetected THEN
        GENERATE response(@prompt) INTO @result
            WITH TEMPERATURE 0.1
        COMMIT @result WITH status = 'conservative'
    WHEN ContextLengthExceeded THEN
        RETRY WITH temperature = 0.1
    WHEN RefusalToAnswer THEN
        COMMIT @prompt WITH status = 'refused'
    WHEN BudgetExceeded THEN
        COMMIT @result WITH status = 'truncated'
END
```

This 25-line workflow expresses a production-grade generation pattern — quality checking, iterative refinement, and graceful degradation across four failure modes — that would require 80–120 lines of Python in LangGraph with manual try/except blocks and custom error classes.

No existing language or framework formalizes LLM failure modes as a typed exception hierarchy. LangGraph and AutoGen rely on Python's generic exception mechanism; LMQL and DSPy have no error handling constructs at all.

3.2.8 PROCEDURE — Reusable Workflow Patterns

PROCEDUREs provide parameterized, reusable workflow components that can be composed via CALL:

```
PROCEDURE researcher(topic TEXT) RETURNS TEXT
DO
    GENERATE research_facts(topic) INTO @facts
    GENERATE identify_key_themes(@facts) INTO @themes
    @result := @facts + '\n\nKey Themes:\n' + @themes
    COMMIT @result
END
```

Procedures enable a standard library of agentic patterns: ReAct (reasoning + acting), Self-Refine (iterative improvement), Tree-of-Thought (branching exploration), and others can be implemented once and reused across workflows via `CALL researcher(@topic) INTO @result .`

3.3 Cross-Cutting Concerns

3.3.1 Context Management

SPL 2.0 provides four context sources within the SELECT clause:

Source	Syntax	Description
System role	`system_role('description')`	Sets the system prompt
Parameter	`context.field_name`	Runtime parameter via CLI
Memory	`memory.get('key')`	Persistent key-value store

Source	Syntax	Description
RAG	`rag.query('text', top_k=5)`	Semantic search over vector store

Token budgets can be specified at both input (`WITH BUDGET n TOKENS`) and output (`WITH OUTPUT BUDGET n TOKENS`) levels.

3.3.2 Security and Accounting

For deployments on untrusted infrastructure (e.g., Momagrid's decentralized grid), SPL 2.0 supports security classifications and accounting tags:

```
WORKFLOW sensitive_analysis
    INPUT: @data TEXT
    OUTPUT: @result TEXT
    SECURITY: CLASSIFICATION: confidential
    ACCOUNTING: BILLABLE_TO: 'project-alpha'
DO
    ...
END
```

These metadata blocks are preserved through the compilation pipeline and enforced by the runtime adapter.

3.4 Formal Grammar

The complete EBNF grammar is provided in Appendix A. The grammar defines 12 statement types, 3 condition types (deterministic, semantic, hybrid), 5 primitive types (text, number, boolean, chunk, json), composite types (list, map), and metadata blocks for security, accounting, and compression.

SPL 2.0 extends SPL 1.0 with 8 new statement types (WORKFLOW, EVALUATE, WHILE, COMMIT, RETRY, RAISE, assignment, PROCEDURE) and 1 new condition type (semantic). All SPL 1.0 productions remain unchanged.

4. Implementation

4.1 Architecture Overview

The SPL 2.0 reference implementation is organized as a four-layer stack:

```
┌──────────────────────────────────────────┐
│  Natural Language / .spl files           │  ← Interface
├──────────────────────────────────────────┤
│  spl2 CLI (Click)                        │  ← Tooling
│  ├── run / execute / explain / parse     │
│  ├── --adapter / --model / KEY=VALUE     │
│  └── init / memory / rag                 │
├──────────────────────────────────────────┤
│  Lexer → Parser → AST → IR (JSON)        │  ← Compiler
├──────────────────────────────────────────┤
│  Adapter Layer                           │  ← Runtime
│  ├── echo     (testing, no LLM)          │
│  ├── ollama   (local GPU)                │
│  ├── openrouter (cloud, 100+ models)     │
│  ├── claude_cli (Anthropic Claude)       │
│  └── momagrid  (decentralized grid)      │
└──────────────────────────────────────────┘
```

Figure 1: SPL 2.0 system architecture. The four layers correspond to the conceptual stack described in Section 1.3.

4.2 The spl2 CLI

The CLI is built on Python's Click framework, providing a consistent interface for all operations:

```
# Zero-config execution
spl2 run cookbook/01_hello_world/hello.spl

# With adapter and model override
spl2 run cookbook/02_ollama_proxy/proxy.spl --adapter ollama -m gemma3 \
    prompt="Explain quantum computing"

# Parse and validate syntax (no LLM needed)
spl2 parse cookbook/05_self_refine/self_refine.spl --json

# Show execution plan
spl2 explain cookbook/09_chain_of_thought/chain.spl
```

Key design decisions:

- **Trailing KEY=VALUE parameters** without a `-p` flag, using Click's UNPROCESSED argument handling. This makes the command line feel natural: `spl2 run file.spl topic="AI"` rather than `spl2 run file.spl -p topic="AI"`.
- **Runtime model override** via `--model/-m` patches the model binding on all PROMPT statements at execution time, allowing model comparison without editing `.spl` files.
- **Auto-initialization** creates workspace directories (`.spl2/` , memory store, RAG index) on first run.

4.3 Lexer and Parser

The compiler pipeline consists of a tokenizer and recursive-descent parser that produce an abstract syntax tree (AST).

The **tokenizer** handles SPL-specific challenges including keyword-as-identifier resolution (e.g., `context.prompt` where `prompt` is also a keyword), `@variable` prefixing, and the `:=` assignment operator. Comment support follows SQL convention (`--` for single-line).

The **parser** produces typed AST nodes: `PromptStatement` , `WorkflowStatement` , `GenerateClause` , `EvaluateClause` , `WhileStatement` , `ExceptionBlock` , `ProcedureDeclaration` , and others. Each node carries source location information for error reporting.

4.4 Adapter Architecture

Runtime adapters implement a common interface:

```
class BaseAdapter:
    def generate(self, prompt, system_role, model, **kwargs) -> Result
    def list_models(self) -> list[str]
    def count_tokens(self, text) -> int
```

New adapters are registered via `register_adapter(name, cls)` , allowing third-party extensions without modifying core code.

Table 4: Adapter Capabilities

Adapter	Generate	Streaming	List Models	Model Override	Auth
echo	Yes	No	Yes (static)	Yes	None
ollama	Yes	Planned	Yes (API)	Yes	None
openrouter	Yes	Planned	Yes (API)	Yes	API key
claude_cli	Yes	Planned	Yes (static)	Yes	CLI auth
momagrid	Yes	No	Yes (fallback)	Yes	API key

The **echo adapter** deserves special mention: it returns deterministic responses without invoking any LLM, enabling the entire test suite (231 tests) to run without GPU hardware or API credentials. This is critical for CI/CD and for validating the parser and execution engine in isolation.

4.5 Momagrid Runtime Integration

The Momagrid adapter connects SPL 2.0 to a decentralized compute grid where GPU nodes are contributed by independent operators. The adapter uses a hub-and-spoke protocol:

1. **Submit**: POST /tasks with the prompt, model, and node requirements (min_tier, min_vram_gb).
2. **Poll**: GET /tasks/{id} until the task reaches a terminal state.
3. **Retrieve**: Extract the generated text from the completed task.

The async httpx client supports configurable poll intervals and timeout limits. Health checks and agent listing are available via helper methods for monitoring grid availability.

5. Compilation and Optimization

5.1 The text2SPL Compiler

The top layer of the SPL stack — translating natural language intent into executable SPL 2.0 code — has a working prototype accessible via `spl2 text2spl`. The current prototype handles simple PROMPT pattern generation: given a natural language description, it produces a syntactically correct PROMPT statement with appropriate SELECT and GENERATE clauses.

The full compiler pipeline envisioned for production would:

1. Parse natural language descriptions of workflow intent.
2. Extract the agentic pattern (self-refine, ReAct, chain-of-thought, etc.).
3. Generate syntactically correct SPL 2.0 code, including full WORKFLOW structures.

Full WORKFLOW generation from natural language — "I want an agent that researches a topic, analyzes the findings, and writes a summary" — remains future work. The declarative form makes this tractable: because SPL 2.0 specifies intent rather than execution steps, the mapping from natural language to SPL is structurally simpler than generating imperative Python code.

5.2 Intermediate Representation (IR)

The current implementation compiles SPL 2.0 source to an AST, which is serialized as JSON via the `spl2 explain` command. The planned IR extends this with:

- **Execution cost annotations**: estimated token consumption per GENERATE node.
- **Dependency edges**: data flow between GENERATE steps for parallelism analysis.
- **Adapter hints**: preferred runtime for each node based on model requirements.

5.3 Optimization Rules

This section describes optimization strategies that are *structurally enabled* by the declarative form — not yet implemented, but architecturally possible in ways that are impossible in imperative frameworks where execution order is hard-coded by the programmer. The declarative form is the prerequisite; the optimizer is future work.

The key claim: an imperative framework cannot perform these optimizations because the programmer's control flow interleaves logic with execution sequence, eliminating the system's visibility into intent. SPL 2.0's separation of specification from execution preserves that visibility.

GENERATE merging: When consecutive GENERATE calls share the same context, they can be merged into a single LLM call with structured output parsing, reducing both latency and cost.

Deterministic condition hoisting: In a WHILE loop, deterministic conditions in EVALUATE blocks can be evaluated before invoking the LLM for semantic conditions, avoiding unnecessary LLM calls.

SELECT caching: When the same RAG query or memory lookup appears multiple times, the result can be cached and reused.

Model selection optimization: A cost-quality optimizer can route simple GENERATE calls to smaller, cheaper models while reserving large models for complex reasoning steps.

Parallel GENERATE: When consecutive GENERATE steps have no data dependencies (e.g., generating pro and con arguments in a debate), they can execute in parallel.

Table 5: Optimization Opportunity Analysis

Optimization	Applicable Patterns	Estimated Impact	Status
GENERATE merging	Chain-of-Thought, Multi-Agent	Reduce LLM calls	Planned
Condition hoisting	Self-Refine, Reflection	Reduce judge calls	Planned
SELECT caching	RAG Query	Eliminate redundant retrieval	Planned
Model downgrade	Hello World, Proxy	Cost reduction	Planned
Parallel GENERATE	Debate, Tree-of-Thought, Ensemble	Latency reduction	Planned

5.4 Logical Plan to Physical Plan

The `spl2 explain` command visualizes the execution plan for any `.spl` file, showing the sequence of operations, data dependencies, and estimated costs. This is directly analogous to SQL's EXPLAIN ANALYZE and provides transparency into how the runtime will execute the workflow.

6. Momagrid Runtime Architecture

SPL 2.0's adapter pattern supports a unique deployment model: decentralized execution on independently operated GPU nodes. This section describes the Momagrid runtime, which extends SPL 2.0's reach beyond the typical local/cloud dichotomy.

6.1 The Hub

The Momagrid Hub serves as the coordination layer for decentralized workflows:

- **Task submission**: Receives SPL-generated inference requests with model and hardware requirements.

- **Node selection**: Matches tasks to available GPU nodes based on min_tier, min_vram_gb, and geographic constraints.
- **State management**: Maintains global workflow context, enabling checkpointing and recovery for long-running workflows.

6.2 GPU Nodes

Each GPU node in the Momagrid network operates as a stateless executor:

- Receives encrypted task payloads from the Hub.
- Decrypts, performs inference, and encrypts the result.
- Reports completion status and resource consumption metrics.

Node selection criteria (min_tier, min_vram_gb) are specified in SPL 2.0's SECURITY metadata block, allowing workflows to express hardware requirements declaratively.

6.3 Compression, Encryption, Accounting

Three cross-cutting concerns are built into the Momagrid protocol:

Compression: Two levels — *semantic compression* reduces context length before transmission (preserving meaning while reducing tokens), and *transmission compression* (zstd, gzip) reduces network bandwidth.

Encryption: A zero-trust model with a three-level key hierarchy (Master → Session → Data) ensures that no single party — including the Hub — has access to both the prompt and the response in plaintext.

Accounting: The Moma Points system tracks resource consumption, with event logging and a reputation system for node operators. SPL 2.0's ACCOUNTING metadata block integrates with this system: `BUDGET_LIMIT: 1000 moma_points` enforces cost caps at the workflow level.

6.4 Hub-Node Protocol

The Hub-Node protocol defines:

- **Message formats**: JSON payloads with fields for task_id, model, prompt (encrypted), and node_requirements.
- **Encryption handshake**: Session key exchange before task submission.
- **Error propagation**: Node failures are surfaced as SPL exceptions (ModelOverloaded, NodeUnavailable), which can be caught by the workflow's EXCEPTION block.

7. Evaluation

7.1 Expressiveness

We compare SPL 2.0's expressiveness against imperative frameworks by measuring lines of code (LOC) required to implement common agentic patterns.

Table 6: Agentic Pattern Expressiveness (Lines of Code)

Pattern	SPL 2.0	LangGraph (est.)	AutoGen (est.)	CrewAI (est.)
Hello World	4	~15	~20	~25
LLM Proxy	5	~20	~25	~30
Parametric Context	6	~25	~30	~30
Chain of Thought	14	~50	~60	~55
Self-Refine	35	~100	~120	~110
ReAct Agent	43	~120	~100	~90
Safe Generation	37	~90	~110	N/A
RAG Query	7	~40	~45	~50

SPL 2.0 achieves 3–6x reduction in LOC compared to imperative alternatives. More significantly, the SPL code is *readable by non-programmers* — the SQL-like syntax is familiar to analysts, data scientists, and researchers who would not write Python framework code.

7.2 Performance

Table 7: Implementation Metrics

Metric	Value	Notes
Total unit tests	231	All passing
Cookbook recipes	21	19 .spl + 2 shell scripts
Recipe categories	8	basics, agentic, reasoning, safety, retrieval, multi-agent, application, benchmarking
Runtime adapters	5	echo, ollama, openrouter, claude_cli, momagrid
SPL 2.0 statement types	12	PROMPT, WORKFLOW, GENERATE, EVALUATE, WHILE, COMMIT, RETRY, RAISE, PROCEDURE, CALL, assignment, EXCEPTION
Cookbook success rate	20/20 SPL recipes (100%)	gemma3 via Ollama, single GTX 1080 Ti; recipe 10 is bash orchestration, excluded from SPL accounting
PROMPT recipe avg latency	3.4s	5 PROMPT recipes; range 391ms–11.1s depending on output length
WORKFLOW recipe avg latency	36.2s	14 WORKFLOW recipes; range 1.7s–123.0s
WORKFLOW avg LLM calls	9.3	Range 2–41; ReAct Agent (41 calls) demonstrates autonomous loop depth
Max tokens in/out (single run)	13,299 / 7,896	Reflection Agent (recipe 16); 13 LLM calls

Metric	Value	Notes
Fastest workflow	1.7s	Guardrails Pipeline (recipe 18); 3 LLM calls
Slowest workflow	123.0s	Reflection Agent (recipe 16); 13 calls, deep meta-cognition loop

7.3 Cost Efficiency

The declarative approach enables token savings through two mechanisms:

1. **Implicit context management**: SPL automatically constructs minimal prompts from SELECT clause elements, avoiding the verbose system prompts typical of manual prompt engineering.
2. **Budget enforcement**: `WITH BUDGET n TOKENS` and `WITH OUTPUT BUDGET n TOKENS` clauses enable explicit token accounting, preventing runaway costs.

Future optimizer passes (GENERATE merging, model downgrade) will provide additional cost reduction.

7.4 Developer Experience

Table 8: Barrier to Entry

Skill Required	SPL 2.0	LangGraph	AutoGen	CrewAI
Python programming	No	Yes	Yes	Yes
API knowledge	No	Yes	Yes	Yes
SQL familiarity	Helpful	not applicable	not applicable	not applicable
CLI usage	Basic	not applicable	not applicable	not applicable
Prompt engineering	Minimal	Full	Full	Full

SPL 2.0's zero-config CLI (`spl2 run file.spl --adapter ollama`) eliminates the setup friction that characterizes imperative frameworks: no virtual environments to configure, no API clients to instantiate, no state management classes to define.

8. Discussion

8.1 Strengths

Declarative form enables optimization. Because SPL 2.0 specifies *what* should happen rather than *how*, the compiler can analyze data dependencies, identify parallelism opportunities, and select cost-optimal models — optimizations that are structurally impossible in imperative code where the execution order is hard-coded.

Adapter pattern broadens reach. The same `.spl` file runs on local GPU (Ollama), cloud APIs (OpenRouter, Claude), and decentralized compute (Momagrid). No other system spans all three deployment models from a single specification.

SQL familiarity lowers the barrier. SQL is the most widely known programming language in the world. SPL 2.0's syntax leverages this familiarity, making agentic workflows accessible to data analysts, researchers, and domain experts who are fluent in SQL but not in Python framework APIs.

LLM-aware primitives address real failure modes. The EXCEPTION taxonomy (HallucinationDetected, RefusalToAnswer, BudgetExceeded, etc.) codifies failure patterns that every LLM application must handle but that no existing language formalizes.

8.2 Limitations

We acknowledge several limitations of the current work:

No optimizer yet. The optimization opportunities described in Section 5.3 are architectural possibilities enabled by the declarative form, not implemented features. The current system executes GENERATE statements sequentially without parallelism or model-routing optimizations.

text2SPL (basic prototype). The natural language to SPL compiler (Layer 2 of the stack) has a working prototype via `spl2 text2spl`, limited to simple PROMPT pattern generation. Full WORKFLOW generation from natural language — the complete vision for Layer 2 — remains future work.

Text-only modality. SPL 2.0 currently handles text input and output. Multi-modal support (images, audio, video) is planned for a future version.

No streaming. Adapters do not yet support token-by-token streaming of LLM output; results are returned in full at completion.

Single-node baseline. The cookbook experiments reported here were run on a single GTX 1080 Ti GPU via Ollama with gemma3. Multi-node Momagrid execution and cross-model comparative benchmarks are planned for a follow-up evaluation.

8.3 Comparison with Imperative Frameworks

The contrast between imperative and declarative approaches is most visible in the ReAct agent pattern. A LangGraph implementation requires approximately 100+ lines of Python: defining state classes, creating graph nodes, specifying edge conditions, configuring the state machine, and handling errors through try/except blocks. The equivalent SPL 2.0 implementation is 43 lines with the workflow logic, branching conditions, and error handling all expressed declaratively.

More importantly, the declarative form makes the *intent* immediately visible. A reader of the SPL code can see at a glance: "this agent reasons, decides on an action, executes it, and accumulates history — with handlers for hallucination and max iterations." The same understanding from the LangGraph implementation requires tracing through multiple function definitions, graph edge conditions, and state class hierarchies.

8.4 Future Work

text2SPL compiler. Natural language to SPL 2.0 translation would complete the four-layer stack, enabling zero-syntax access to agentic workflows.

Query optimizer. A cost-based optimizer that rewrites execution plans — merging GENERATE calls, parallelizing independent steps, routing to optimal models — is the highest-impact future contribution.

Visual workflow builder. A graphical interface for composing WORKFLOW blocks would complement the text-based CLI for users who prefer visual programming.

Multi-modal I/O. Extending GENERATE to handle images, audio, and video inputs/outputs, with corresponding context source types.

Extended procedure library. A standard library of validated PROCEDURE implementations for common patterns (ReAct, Tree-of-Thought, Self-Refine, Debate, Map-Reduce, etc.) would accelerate adoption.

Formal verification. Proving properties of workflow specifications — termination guarantees, budget bounds, safety constraints — through static analysis.

Momagrid production integration. End-to-end testing of the decentralized runtime with real GPU node operators.

9. Conclusion

SPL 2.0 represents a paradigm shift from imperative to declarative orchestration of LLM-powered agentic workflows. The language addresses a fundamental fragmentation in the current ecosystem — where building agents requires Python programming, API expertise, and framework-specific knowledge — by providing a SQL-inspired specification layer that separates *what* a workflow should accomplish from *how* it executes.

The core contribution is three novel primitives that no existing language formalizes:

- **EVALUATE** enables hybrid deterministic-semantic branching, where the LLM itself serves as a runtime judge.
- **WHILE** with semantic termination enables iteration based on output quality rather than arbitrary counters.
- **EXCEPTION** with a formal taxonomy of LLM failure modes enables structured error handling for hallucination, refusal, context overflow, and budget exhaustion.

These primitives, combined with the PROMPT/WORKFLOW layering (inspired by the SQL/PL/SQL architectural pattern), a formal EBNF grammar, and a pluggable adapter layer spanning local, cloud, and decentralized execution, form a coherent language design validated

through 231 automated tests and a 21-recipe cookbook covering 8 categories of agentic workflow patterns, with 20/20 SPL recipes passing on a single local GPU node.

The declarative form of SPL 2.0 is not merely a notational convenience — it is the structural prerequisite for a future ecosystem of compilers, optimizers, and visual tools that can reason about, transform, and improve agentic workflows in ways that imperative code fundamentally cannot support.

The reference implementation is open-source.

References

[1] LangGraph. LangChain, Inc. https://github.com/langchain-ai/langgraph

[2] Wu, Q., et al. "AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversation." arXiv:2308.08155, 2023.

[3] CrewAI. https://github.com/crewAIInc/crewAI

[4] Gong, W. G. "Structured Prompt Language: Declarative Context Management for LLMs." arXiv:2602.21257, 2026.

[5] Chamberlin, D. D. and Boyce, R. F. "SEQUEL: A Structured English Query Language." SIGFIDET Workshop, 1974.

[6] Oracle Corporation. "PL/SQL User's Guide and Reference." Oracle Database Documentation.

[7] Beurer-Kellner, L., Fischer, M., and Vechev, M. "Prompting Is Programming: A Query Language for Large Language Models." arXiv:2212.06094, 2022.

[8] Khattab, O., et al. "DSPy: Compiling Declarative Language Model Calls into Self-Improving Pipelines." arXiv:2310.03714, 2023.

[9] Zheng, L., et al. "SGLang: Efficient Execution of Structured Language Model Programs." arXiv:2312.07104, 2023.

[10] Agent Spec: Open Agent Specification. Oracle Labs. arXiv:2510.04173, 2025.

[11] SLANG: Standard Language for Agentic Workflows. https://dev.to/argonauta/why-we-need-a-standard-language-for-agentic-workflows-and-why-i-built-one-138

[12] "A Declarative Language for Building And Orchestrating LLM-Powered Agent Workflows." arXiv:2512.19769, 2025.

[13] "The Auton Agentic AI Framework: A Declarative Architecture for Specification, Governance, and Runtime Execution of Autonomous Agent Systems." arXiv:2602.23720, 2026.

[14] Gliozzo, A. M., Lee, J., and Defosse, N. "Agentics 2.0: Logical Transduction Algebra for Agentic Data Workflows." arXiv:2603.04241, 2026.

Appendix A: Complete SPL 2.0 Grammar (EBNF)

Productions are listed top-down. SPL 1.0 productions (unchanged) are marked †. New SPL 2.0 productions are unmarked. Keywords are case-insensitive. Comments use `--` (end-of-line).

```
(* Top-level *)
program             := statement+

statement           := prompt_stmt
                     | workflow_stmt
                     | procedure_stmt
                     | create_function_stmt
                     | explain_stmt      †
                     | execute_stmt      †

(* PROMPT — atomic LLM query  † extended with CTE block *)
prompt_stmt         := 'PROMPT' identifier
                        cte_block?
                        select_clause
                        generate_clause
                        store_clause?

cte_block           := 'WITH' cte_def (',' cte_def)*
cte_def             := identifier 'AS' '(' prompt_stmt ')'

select_clause       := 'SELECT' select_item (',' select_item)*
select_item         := expression ('AS' identifier)?
                        ('LIMIT' integer 'TOKENS')?

generate_clause     := 'GENERATE' identifier '(' argument_list? ')'
                        ('INTO' '@' identifier)?
                        ('WITH' generate_option (',' generate_option)*)?
                        ('USING' 'MODEL' string)?

generate_option     := 'OUTPUT' 'BUDGET' integer 'TOKENS'
                     | 'TEMPERATURE' float
```

```
store_clause        := 'STORE' 'RESULT' 'AS' string
                        ('CACHE' 'FOR' integer)?          †

(* WORKFLOW — procedural orchestration *)
workflow_stmt       := 'WORKFLOW' identifier
                        ('INPUT'  ':' param_list)?
                        ('OUTPUT' ':' param_list)?
                        security_block?
                        accounting_block?
                        do_block
                        'END'

(* PROCEDURE — reusable parameterized sub-workflow *)
procedure_stmt      := 'PROCEDURE' identifier
                        '(' param_list? ')'
                        ('RETURNS' identifier)?
                        security_block?
                        accounting_block?
                        do_block
                        'END'

(* DO block — shared by WORKFLOW and PROCEDURE *)
do_block            := 'DO' body_stmt+ exception_block?

body_stmt           := generate_into_stmt
                     | assignment_stmt
                     | evaluate_stmt
                     | while_stmt
                     | commit_stmt
                     | retry_stmt
                     | raise_stmt
                     | call_stmt
                     | select_into_stmt
```

```
generate_into_stmt := 'GENERATE' identifier '(' argument_list? ')'
                      'INTO' '@' identifier
                      ('WITH' generate_option (',' generate_option)*)?

assignment_stmt    := '@' identifier ':=' expression

evaluate_stmt      := 'EVALUATE' expression
                      when_clause+
                      ('OTHERWISE' body_stmt+)?
                      'END'

when_clause        := 'WHEN' condition 'THEN' body_stmt+

condition          := comparison_condition      (* deterministic *)
                    | semantic_condition         (* LLM-judged    *)
                    | expression

comparison_condition := comparison_op expression
comparison_op      := '>' | '<' | '>=' | '<=' | '=' | '!='

semantic_condition := string_literal            (* quoted string triggers LLM judge *)

while_stmt         := 'WHILE' condition 'DO' body_stmt+ 'END'

commit_stmt        := 'COMMIT' expression ('WITH' option_list)?

retry_stmt         := 'RETRY' ('WITH' option_list)?

raise_stmt         := 'RAISE' exception_type string?

call_stmt          := 'CALL' identifier '(' named_arg_list? ')'
                      ('INTO' '@' identifier)?
```

```
select_into_stmt   := 'SELECT' select_item (',' select_item)*
                      'INTO' '@' identifier

exception_block    := 'EXCEPTION' exception_handler+

exception_handler  := 'WHEN' exception_type 'THEN' body_stmt+

exception_type     := 'HallucinationDetected'  | 'RefusalToAnswer'
                    | 'ContextLengthExceeded'   | 'ModelOverloaded'
                    | 'BudgetExceeded'          | 'QualityBelowThreshold'
                    | 'MaxIterationsReached'    | 'NodeUnavailable'
                    | 'GenerationError'         | 'GenerationFailed'

(* CREATE FUNCTION — schema / constant definition *)
create_function_stmt := 'CREATE' 'FUNCTION' identifier
                        '(' param_list? ')'
                        'RETURNS' identifier
                        'AS' '$$' text '$$'

(* Expressions *)
expression         := literal
                    | param_ref
                    | dotted_name
                    | function_call
                    | binary_op
                    | select_source

select_source      := system_role | context_ref | rag_query | memory_get

system_role        := 'system_role' '(' string ')'
context_ref        := 'context' '.' identifier
rag_query          := 'rag' '.' 'query' '(' string (',' named_arg)* ')'
```

```
memory_get          := 'memory' '.' 'get' '(' string ')'

literal             := string_literal | integer_literal | float_literal
param_ref           := '@' identifier
dotted_name         := identifier ('.' identifier)+
function_call       := identifier '(' argument_list? ')'
binary_op           := expression ('+' | '-' | '*' | '/') expression

(* Parameter and argument lists *)
param_list          := param_def (',' param_def)*
param_def           := '@'? identifier identifier? ('DEFAULT' expression)?

argument_list       := argument (',' argument)*
argument            := named_arg | expression
named_arg           := identifier '=' expression

named_arg_list      := named_arg (',' named_arg)*

option_list         := option (',' option)*
option              := identifier '=' expression

(* Metadata blocks *)
security_block      := 'SECURITY' ':' 'CLASSIFICATION' ':' identifier
accounting_block    := 'ACCOUNTING' ':' 'BILLABLE_TO' ':' string
                        ('BUDGET_LIMIT' ':' integer identifier)?

(* Lexical *)
identifier          := [a-zA-Z_][a-zA-Z0-9_]*
string_literal      := '"' .* '"' | "'" .* "'"
integer_literal     := [0-9]+
float_literal       := [0-9]+ '.' [0-9]+
```

Type system. SPL 2.0 supports five primitive types: `TEXT`, `NUMBER` (integer or float), `BOOLEAN`, `JSON`, `CHUNK` (token-bounded text segment). Composite types: `LIST` (ordered sequence), `MAP` (key-value). Type annotations are optional; untyped parameters default to `TEXT`.

Condition type detection rule. If a `WHEN` condition is a quoted string literal, the runtime treats it as a semantic condition and invokes the LLM as a judge. Otherwise (numeric comparison, boolean expression) it is evaluated deterministically with no LLM call. This detection is unambiguous and requires no explicit annotation.

Appendix B: IR Specification (JSON Schema)

The SPL 2.0 Intermediate Representation (IR) is a JSON-serialized AST produced by `spl2 explain`. It is the portable format consumed by the Momagrid runtime, plan visualization tools, and future optimizer passes.

Program envelope

```
{
  "type": "Program",
  "statements": [ <statement>+ ]
}
```

Prompt plan (produced by `spl2 explain` for PROMPT statements)

```
{
  "type": "PromptPlan",
  "prompt_name": "string",
  "model": "string | null",
  "total_budget": "integer | null",
  "output_budget": "integer | null",
  "total_input_tokens": "integer",
  "buffer_tokens": "integer",
  "estimated_cost": "float",
  "optimizations": [ "string" ],
  "warnings": [ "string" ],
  "steps": [
    {
      "operation": "string",
      "source": "string",
      "alias": "string | null",
      "estimated_tokens": "integer",
      "limit_tokens": "integer | null",
      "allocated_tokens": "integer",
      "compressed": "boolean",
      "compression_ratio": "float",
      "cache_status": "string",
      "priority": "integer"
    }
  ]
}
```

Workflow plan (produced by `spl2 explain` for WORKFLOW statements)

```
{
  "type": "WorkflowPlan",
  "workflow_name": "string",
  "inputs": [ { "name": "string", "type": "string", "default": "<expr> | null" } ],
  "outputs": [ { "name": "string", "type": "string" } ],
  "security": { "classification": "string" } | null,
  "accounting": { "billable_to": "string" } | null,
  "total_estimated_llm_calls": "integer",
  "total_estimated_tokens": "integer",
  "steps": [ <workflow_step> ],
  "exception_handlers": [ <workflow_step> ]
}
```

Workflow step (recursive — branches and substeps are the same type)

```
{
  "step_type": "GenerateInto | Evaluate | While | Commit | Retry | Call | Assignment | ...",
  "description": "string",
  "estimated_llm_calls": "integer",
  "estimated_tokens": "integer",
  "substeps": [ <workflow_step> ] | null,
  "branches": [
    {
      "condition": "string",
      "condition_type": "semantic | deterministic | hybrid",
      "steps": [ <workflow_step> ]
    }
  ] | null,
  "exception_handlers": [ <workflow_step> ] | null
}
```

Condition node

```
{ "type": "SemanticCondition",   "value": "string" }
{ "type": "ComparisonCondition", "operator": "> | < | >= | <= | = | !=", "right": <expr> }
{ "type": "Condition",           "left": <expr>, "operator": "string", "right": <expr> }
```

Expression nodes (used in step arguments, conditions, assignments)

```
{ "type": "Literal",    "value": "string | integer | float" }
{ "type": "ParamRef",   "name": "string" }
{ "type": "ContextRef", "field_name": "string" }
{ "type": "DottedName", "parts": ["string"], "full_name": "string" }
{ "type": "SystemRole", "description": "string" }
{ "type": "RagQuery",   "query": "string", "source": "string | null", "top_k": "integer" }
{ "type": "MemoryGet",  "key": "string" }
{ "type": "FunctionCall","name": "string", "arguments": [ <expr> ] }
{ "type": "BinaryOp",   "op": "+ | - | * | /", "left": <expr>, "right": <expr> }
```

The IR is produced by the `spl2.ir` module and consumed by the executor (`spl2.executor`) and Momagrid adapter (`spl2.adapters.momagrid`). All field names are stable across SPL 2.0 patch releases; additions are backward-compatible.

Appendix C: Hub ↔ Node Protocol Specification

The Momagrid Hub-Node protocol is a REST-over-HTTPS request-response protocol. The SPL 2.0 Momagrid adapter (`spl2.adapters.momagrid`) implements the client (Hub) side using async `httpx` .

Task lifecycle

```
Client (SPL runtime)          Hub                       GPU Node
        |                      |                            |
        |── POST /tasks ──────>|                             |
        |                      |── dispatch ───────────────>|
        |<- 202 { task_id } ───|                            |
        |                      |                    (inference)
        |── GET /tasks/{id} ──>|                            |
        |<- 200 { pending } ───|                            |
        |                      |<── result ────────────────|
        |── GET /tasks/{id} ──>|                            |
        |<- 200 { complete } ──|                            |
```

POST /tasks — Submit inference request

```
Request body:
{
  "model":         "string",
  "prompt":        "string (plaintext or encrypted ciphertext)",
  "system_role":   "string | null",
  "temperature":   "float | null",
  "max_tokens":    "integer | null",
  "node_requirements": {
    "min_tier":    "integer (0-5)",
    "min_vram_gb": "float"
  },
  "session_key_id": "string | null"
}

Response 202:
{
  "task_id": "uuid",
  "status":  "pending",
  "eta_ms":  "integer | null"
}
```

GET /tasks/{task_id} — Poll task status

```
Response 200 (pending):
{ "task_id": "uuid", "status": "pending | running" }

Response 200 (complete):
{
  "task_id":    "uuid",
  "status":     "complete",
  "result":     "string (plaintext or encrypted ciphertext)",
  "tokens_in":  "integer",
  "tokens_out": "integer",
  "latency_ms": "integer",
  "node_id":    "string"
}

Response 200 (failed):
{
  "task_id": "uuid",
  "status":  "failed",
  "error":   "string",
  "code":    "node_unavailable | model_not_found | overloaded | timeout"
}
```

Error code → SPL exception mapping

HTTP / error code	SPL Exception raised
`overloaded` or HTTP 429	`ModelOverloaded`
`node_unavailable` or HTTP 503	`NodeUnavailable`
`timeout`	`NodeUnavailable`

HTTP / error code	SPL Exception raised
`context_exceeded`	`ContextLengthExceeded`
any other `failed` status	`GenerationError`

Encryption handshake (zero-trust mode)

When `SECURITY: CLASSIFICATION: confidential` is set in the SPL workflow, the adapter negotiates an ephemeral session key before task submission:

1. Client generates an ephemeral key pair (X25519).
2. Client sends the public key to `POST /session/init`.
3. Hub returns an encrypted session key, signed by the Hub's master key.
4. Subsequent task payloads (`prompt` , `result`) are encrypted with AES-256-GCM under the session key.
5. Session keys expire after 1 hour or 1000 tasks, whichever comes first.

In plaintext mode (default for development), the `session_key_id` field is omitted and `prompt` / `result` are transmitted unencrypted.

Accounting integration

When `ACCOUNTING: BILLABLE_TO: 'project-id'` is set, the Hub records a Moma Points debit against the project account on task completion. If `BUDGET_LIMIT` is exceeded, the Hub returns HTTP 402 and the adapter raises `BudgetExceeded`.

Appendix D: Exception Type Hierarchy

Exception	Trigger	Default Recovery
HallucinationDetected	Output fails fact-checking or contains fabricated information	Regenerate with temperature = 0.1

Exception	Trigger	Default Recovery
RefusalToAnswer	Model declines due to safety filters or content policy	Log refusal, COMMIT with status = 'refused'
ContextLengthExceeded	Combined input exceeds model's context window	Compress context, RETRY
ModelOverloaded	Provider returns 429 or capacity error	Exponential backoff, RETRY
BudgetExceeded	Token budget (input or output) exhausted	COMMIT best available result
QualityBelowThreshold	Generated output scores below configured minimum	Regenerate or escalate to larger model
MaxIterationsReached	WHILE loop reached iteration guard limit	COMMIT current result with status = 'partial'
NodeUnavailable	Momagrid GPU node unreachable or timed out *(Momagrid-specific)*	Route to alternative node, RETRY

Appendix E: Cookbook — Practical Validation

E.1 Recipe Design Philosophy

Each cookbook recipe is designed as a self-contained demonstration:

- A single `.spl` file with inline comments explaining the pattern.
- Usage examples as CLI commands in the file header.
- Progressive complexity from atomic queries to multi-agent workflows.
- Catalog-driven organization via `cookbook_catalog.json` and `run_all.py` batch runner.

E.2 Recipe Catalog

Table E-1: SPL 2.0 Cookbook — 21 Recipes

#	Recipe	Category	Pattern	LOC	Key SPL Features
01	Hello World	basics	PROMPT (atomic)	4	system_role, GENERATE
02	Ollama Proxy	basics	PROMPT + params	5	context.param, model override
03	Multilingual	basics	PROMPT + 2 params	6	Multiple context bindings
04	Model Showdown	benchmarking	Shell + PROMPT	sh	Cross-model comparison
05	Self-Refine	agentic	WORKFLOW + WHILE	35	Iterative improvement loop
06	ReAct Agent	agentic	WORKFLOW + EVALUATE	43	Tool-call branching, history
07	Safe Generation	safety	WORKFLOW + EXCEPTION	37	Quality scoring, error recovery
08	RAG Query	retrieval	PROMPT + rag.query	7	Vector search context
09	Chain of Thought	reasoning	WORKFLOW (3-step)	14	Sequential GENERATE pipeline
10	Batch Test	benchmarking	Shell + all recipes	sh	Automated regression testing
11	Debate Arena	multi-agent	WORKFLOW + adversarial	45	Multi-perspective, judge eval
12	Plan and Execute	agentic	WORKFLOW + re-planning	50	Dynamic plan adjustment
13	Map-Reduce Summarizer	application	WORKFLOW + chunking	40	Chunked GENERATE, reduce step
14	Multi-Agent Collab.	multi-agent	PROCEDURE + CALL	45	Role specialization, delegation
15	Code Review	application	WORKFLOW + multi-pass	50	Severity scoring, synthesis

#	Recipe	Category	Pattern	LOC	Key SPL Features
16	Reflection Agent	agentic	WORKFLOW + meta-cognition	45	Confidence scoring, correction
17	Tree of Thought	reasoning	WORKFLOW + branching	50	Path scoring, verification
18	Guardrails Pipeline	safety	WORKFLOW + multi-gate	55	PII detection, content filtering
19	Memory Conversation	application	WORKFLOW + memory	40	memory.get, fact extraction
20	Ensemble Voting	multi-agent	WORKFLOW + consensus	45	Multi-candidate scoring, voting
21	Multi-Model Pipeline	agentic	WORKFLOW + adapters	50	Cross-adapter routing, fallback

E.3 End-to-End Demonstrations

Experimental setup. All 21 recipes were executed via the batch runner (`python cookbook/run_all.py --adapter ollama --model gemma3`) on a single workstation equipped with a GTX 1080 Ti GPU running the Ollama inference server. No cloud API credits were consumed. The full run completed in approximately 505 seconds wall time.

Table E-2: Batch Run Results — gemma3 / Ollama / GTX 1080 Ti (2026-03-19)

#	Recipe	Category	Type	Status	Tokens in/out	Latency	LLM Calls
01	Hello World	basics	PROMPT	**OK**	45 / 54	2.2s	1
02	Ollama Proxy	basics	PROMPT	**OK**	47 / 27	484ms	1
03	Multilingual Greeting	basics	PROMPT	**OK**	54 / 21	391ms	1
04	Model Showdown	benchmarking	PROMPT	**OK**	48 / 708	11.1s	1
05	Self-Refine	agentic	WORKFLOW	**OK**	331 / 209	2.6s	3

#	Recipe	Category	Type	Status	Tokens in/out	Latency	LLM Calls
06	ReAct Agent	agentic	WORKFLOW	**OK**	8,318 / 1,923	27.5s	41
07	Safe Generation	safety	WORKFLOW	**OK**	899 / 778	10.5s	3
08	RAG Query	retrieval	PROMPT	**OK**	55 / 30	2.8s	1
09	Chain of Thought	reasoning	WORKFLOW	**OK**	1,275 / 1,355	19.1s	3
10	Batch Test	benchmarking	shell	N/A	—	—	—
11	Debate Arena	multi-agent	WORKFLOW	**OK**	12,808 / 5,345	89.7s	9
12	Plan and Execute	agentic	WORKFLOW	**OK**	941 / 2,819	37.8s	3
13	Map-Reduce Summarizer	application	WORKFLOW	**OK**	440 / 727	9.9s	4
14	Multi-Agent Collab.	multi-agent	WORKFLOW	**OK**	6,363 / 4,333	64.3s	8
15	Code Review	application	WORKFLOW	**OK**	3,376 / 2,250	29.9s	8
16	Reflection Agent	agentic	WORKFLOW	**OK**	13,299 / 7,896	123.0s	13
17	Tree of Thought	reasoning	WORKFLOW	**OK**	8,415 / 5,194	73.9s	14
18	Guardrails Pipeline	safety	WORKFLOW	**OK**	391 / 130	1.7s	3
19	Memory Conversation	application	WORKFLOW	**OK**	278 / 141	1.9s	4
20	Ensemble Voting	multi-agent	WORKFLOW	**OK**	6,110 / 3,210	47.8s	13
21	Multi-Model Pipeline	agentic	WORKFLOW	**OK**	565 / 519	8.9s	9

† Recipe 10 is a bash shell script that orchestrates the other recipes; it is infrastructure, not an SPL recipe, and is excluded from pass/fail accounting. The SPL success rate is computed over the 20 SPL recipes only.

Summary: 20/20 SPL recipes passed (100%). Recipe 10 (Batch Test) is a bash orchestration script, not an SPL workflow, and is excluded from SPL accounting. The overall table shows 21 entries to document the full cookbook; the SPL-specific result is 20/20.

Aggregate statistics:

Segment	Count	Avg Latency	Avg Tokens (in+out)	Avg LLM Calls
PROMPT recipes	5	3.4s	218	1
WORKFLOW recipes	15	36.2s	6,782	9.3
ReAct Agent (peak)	1	27.5s	10,241	41

Notable observations:

- **ReAct Agent (recipe 06)** executed 41 LLM calls autonomously — demonstrating the WHILE loop driving a genuine tool-reasoning loop without programmer intervention.
- **Safe Generation (recipe 07)** demonstrates EVALUATE with semantic conditions: `WHEN 'high_quality'` , `WHEN 'acceptable'` — the LLM serves as its own quality judge, with no numeric parsing required.
- **Reflection Agent (recipe 16)** consumed the most tokens (21,195 total) and took the longest (123s), reflecting its deep meta-cognition loop (13 LLM calls).
- **Guardrails Pipeline (recipe 18)** completed in 1.7s with 3 LLM calls — the fastest workflow, demonstrating that multi-gate safety checking adds minimal overhead for simple inputs.
- **Debate Arena (recipe 11)** and **Ensemble Voting (recipe 20)** both generated rich multi-perspective outputs within a single `spl2 run` command, with no Python orchestration code.

Appendix F: Full Experiment Results

Run configuration:

- Date: 2026-03-19

- Model: gemma3 (via Ollama)
- Hardware: GTX 1080 Ti (11 GB VRAM), single node
- Runner: `python cookbook/run_all.py --adapter ollama --model gemma3`
- Log directory: `cookbook/out/run_all-logs-20260319.md`
- Per-recipe logs: `cookbook/<recipe_dir>/<recipe>_<timestamp>.log`

Pass/fail breakdown by category:

Category	SPL Recipes	Passed	Failed	Notes
basics	3	3	0	
agentic	5	5	0	
reasoning	2	2	0	
safety	2	2	0	Recipe 07 fixed: numeric EVALUATE → semantic EVALUATE
retrieval	1	1	0	
multi-agent	3	3	0	
application	3	3	0	
benchmarking	1	1	0	Recipe 10 (bash) excluded from SPL accounting
Total (SPL)	**20**	**20**	**0**	**100%**

Recipe 07 fix note: The original recipe used numeric EVALUATE (`WHEN > 0.8 THEN`) to branch on a quality score, but `GENERATE quality_score()` returned a natural-language assessment string, not a bare float. The fix switches to semantic EVALUATE: `WHEN 'high_quality' THEN` / `WHEN 'acceptable' THEN` . The LLM now serves as its own quality judge via the semantic condition — which is exactly what EVALUATE's semantic mode is designed for. This is a better demonstration of the primitive than numeric scoring.

Planned follow-up experiments:

1. Run with `llama3.2` and `mistral` to measure cross-model variance
2. Run multi-node Momagrid execution (2× GTX 1080 Ti) to measure distributed overhead
3. Measure energy consumption (joules/token) via differential method for η_AI baseline
4. Quantify token savings of SPL implicit context management vs. manual prompting (Table 7.3)