

OPERATOR GATEWAY

API Integration Reference

Version 2.0 • March 2026

Overview

This document describes the HTTP API endpoints exposed by the Operator Gateway service. Integrating operators use these endpoints to authenticate users, retrieve game catalogues, fetch user details, update user balances, and handle transaction rollbacks.

Base URL: `https://api.yourdomain.com/v1`

 All endpoints (except User Login) require a session token passed in the HTTP header as: `token: <session_token>`

Authentication Flow

Every session begins with a **User Login** call. The returned `token` must accompany every subsequent request. Tokens expire after 16 hours; an additional 4-hour soft expiry window applies to balance updates.

Endpoints

1. User Login

POST `/operator/user/login` — Authenticate a user and obtain a session token

Validates the operator's public key and decrypts the payload using the operator's shared secret. On success, a UUID v7 session token is stored in Redis (TTL 16 h) and returned to the caller.

Request

Parameter	Location	Type	Required	Description
<code>id</code>	URL Param	string	Required	Operator public key (<code>pub_key</code>)
<code>data</code>	Body (JSON)	string	Required	AES-encrypted payload (see below)

Encrypted Payload Fields (inside data)

Field	Type	Required	Description
user_id	string	Required	Unique identifier for the end-user
url	string	Optional	Override the default callback URL for this session

Example Request

JSON

```
POST /operator/user/login?id=PUB_KEY_123
Content-Type: application/json

{
  "data": "AES_ENCRYPTED_PAYLOAD_STRING"
}
```

Response — Success (200)

JSON

```
{
  "status": true,
  "msg": "User authenticated",
  "token": "01900000-0000-7000-8000-000000000000"
}
```

Response — Errors

HTTP Code	status	msg	Cause
400	false	Request initiated for Invalid Operator	pub_key not found or operator is deleted
500	false	Internal Server error	Decryption failure or Redis error

2. Games List

GET

/games/list — Fetch active games assigned to the operator

Returns games from the operator_games table joined with games_master_list, filtered by genre. Results are cached in Redis for 60 seconds per operator.

Request Headers

Header	Required	Description
token	Required	Session token obtained from User Login

Query Parameters

Parameter	Type	Required	Default	Description
genre	string	Optional	general, vr	Filter games by genre (e.g. general, vr, mini)

Example Request

JSON

```
GET /games/list?genre=general
token: 01900000-0000-7000-8000-000000000000
```

Response — Success (200)

JSON

```
{
  "status": true,
  "msg": "Games list fetched successfully",
  "data": [
    {
      "game_id": 101,
      "game_code": "SLOTS_01",
      "game_name": "Lucky Reels",
      "genre": "general",
      "is_active": 1
    }
  ]
}
```

Response — Errors

HTTP Code	status	msg	Cause
401	false	Token expired or request timed out	Token not found in Redis (TTL exceeded)
400	false	We've encountered an internal error	Redis JSON parse failure
500	false	Internal server Error	Database or unexpected failure

3. User Detail

GET

/user/detail — Fetch user profile from the operator's upstream system

Proxies a GET request to the webhook URL configured for the USER_DETAILS event on the operator. The upstream service is responsible for returning user profile data.

Request Headers

Header	Required	Description
token	Required	Session token obtained from User Login

Upstream Request (forwarded automatically)

JSON

```
GET <operator_webhook_url>
Content-Type: application/json
token: <session_token>
x-user-id: <user_id_from_session>
```

Example Request

JSON

```
GET /user/detail
token: 01900000-0000-7000-8000-000000000000
```

Response — Success (200)

The response is passed through directly from the upstream (operator) server. A typical payload might look like:

JSON

```
{
  "status": true,
  "data": {
    "user_id": "USR_987",
    "username": "john_doe",
    "email": "john@example.com",
    "balance": 1500.00,
    "currency": "INR"
  }
}
```

Response — Errors

HTTP Code	status	msg	Cause
400	false	We've encountered an internal error	Redis JSON parse failure
401	false	Invalid Token or session timed out	Token absent from Redis
400	false	No URL configured for the event	Operator has no USER_DETAILS webhook
500	false	Internal Server error	Axios / network error to upstream

4. Update User Balance (v2)

POST

/operator/user/balance/v2 — Debit or credit a user's wallet

Encrypts the transaction payload with the operator secret and forwards it to the operator's UPDATE_BALANCE webhook. All transactions are written to the transaction table. On upstream failure the bet is queued for automatic rollback.

Request Headers

Header	Required	Description
token	Required	Session token obtained from User Login
Content-Type	Required	Must be application/json

Request Body

Field	Type	Required	Description
txn_id	string	Required	Unique transaction identifier (idempotency key)
amount	number	Required	Transaction amount — must be > 0
description	string	Required	Human-readable description (used to extract lobby ID)
txn_type	integer	Required	1 = Debit, 2 = Credit
ip	string	Required	End-user IP address
game_id	integer	Required	Game identifier
user_id	string	Required	End-user identifier
txn_ref_id	string	Optional	Reference to a prior transaction (e.g. rollback target)

Example Request

```
JSON

POST /operator/user/balance/v2
Content-Type: application/json
token: 01900000-0000-7000-8000-000000000000

{
  "txn_id": "TXN-20260323-001",
  "amount": 250.00,
  "description": "Bet debited for lobby LOBBY_42",
  "txn_type": 1,
  "ip": "203.0.113.5",
  "game_id": 101,
  "user_id": "USR_987"
}
```

Response — Success (200)

```
JSON

{
  "status": true,
  "msg": "Balance updated successfully"
}
```

Response — Errors

HTTP Code	status	msg	Cause
400	false	Missing token in headers	token header absent

HTTP Code	status	msg	Cause
400	false	No game code is available for the game	game_id not in master list
400	false	Invalid transaction amount	amount is 0, negative, or non-numeric
400	false	Session Timed Out.!	Token older than 12 h (16 h – 4 h buffer)
400	false	No URL configured for the event	Operator has no UPDATE_BALANCE webhook
400	false	Game is inactive!!	Game not active for this operator
500	false	Request Timed Out!	Pre-flight check exceeded 1 s
500	false	Internal Server error	Encryption, Redis, or Axios error

⚠ On upstream failure the transaction is recorded with status 0 (failed) and a rollback message is enqueued automatically on the games_rollback queue.

5. Transaction Rollback

GET	/txn/rollback/:txn_id — Reverse a previously successful debit transaction
-----	---

Looks up a previously successful debit transaction (txn_status = 2) and issues a credit to the operator's UPDATE_BALANCE webhook. The rollback is idempotent — if a rollback already succeeded for the given txn_id it returns 400.

URL Parameters

Parameter	Type	Required	Description
txn_id	string	Required	The txn_id of the original debit transaction to reverse

Example Request

JSON
GET /txn/rollback/TXN-20260323-001

Response — Success (200)

JSON
<pre>{ "status": true, "msg": "Bet rollback-ed successfully" }</pre>

Response — Errors

HTTP Code	status	msg	Cause
400	false	Invalid necessary paramters	txn_id missing from URL
400	false	Transaction not found	txn_id does not exist in DB
400	false	Debit transaction failed initally	Original txn_status ≠ 2
400	false	Bet already rollback-ed for the given txn	A successful rollback already exists
400	false	No game code is available for the game	game_id not in master list
400	false	Operator not found for this transaction	operator_id missing from config
400	false	No URL configured for the event	Operator has no UPDATE_BALANCE webhook
200	true	Transaction not found. (upstream)	Upstream reports TXN absent — treated as success
500	false	Operator Denied Void Request	Upstream rejected the rollback
500	false	Internal Server error	Encryption, Axios, or DB error

Payload Encryption

All sensitive payloads exchanged between the gateway and operator webhooks are AES-encrypted using the operator's shared secret. The encryption and decryption functions are internal utilities; however, operators must implement compatible AES encryption on their side.

Property	Value
Algorithm	AES-256-CBC (recommended)
Key	Operator shared secret (secret field in operator config)
Input	JSON stringified object
Output	Base64-encoded encrypted string

HTTP Status Code Summary

Code	Meaning	When used
200	OK	Request processed successfully
400	Bad Request	Validation failure, missing params, invalid token, inactive resource
401	Unauthorized	Session token expired or not found in Redis
500	Internal Server Error	Unhandled exception, upstream timeout, encryption error

Integration Checklist

- Obtain your operator pub_key and secret from the platform team.
- Implement AES encryption/decryption compatible with the gateway.
- Configure USER_DETAILS and UPDATE_BALANCE webhook URLs in the operator portal.
- Call POST /operator/user/login to obtain a token at the start of each user session.
- Pass token in every subsequent request header.
- Refresh the session before the 12-hour mark to avoid balance-update expiry.
- Handle txn_status = 0 callbacks and check the rollback queue for automatic reversal.
- Use unique txn_id values per transaction for idempotency.