O'REILLY

16
A Real-Time Speech-Text Conversion System Using Deep Learning Technique

K. Saranya[1] and P. Jeevananthan[2]*

[1]*Department of CSE, Sri Ramakrishna Institute of Technology, Coimbatore, Tamil Nadu, India*

[2]*Department of EEE, Karpagam College of Engineering, Coimbatore, Tamil Nadu, India*

Abstract

Conversion of the voice speech signal into writing using transcription is called automatic speech recognition (ASR). In today's computer revolution, ASR naturally plays a crucial role in improving user experience while communicating with the machines. Traditional equipment such as a computer and mouse is restricted, and the user can perform several tasks such as controlling the device and interacting with customer service. The importance of using speech detection models has increased sig-

nificantly. Speech control gained importance. In our research, we developed a word-tracking model using deep convolutional neuro-learning and speech recognition features. Ten command phrases are used (yes, no, up, down, right, left, on, off, off, and go). One second word for 65,000 samples were used. A convolutional neural network (CNN) is used as an advanced deep neural network to classify each word from our pooled dataset as a multi-class classification assignment. The deep neural network proposed a word classification accuracy score of 91.24% with an unknown speech sample. Broadband speech signals are utilized in the experiments, which effectively increases the system performance when the normal conventional methods are considered. Unlike many other papers, which mostly use pre-prepared and generally reliable data from a single part of speech, our work is different.

Keywords**:** Automatic speech recognition, deep learning, convolutional neural network, wideband speech signals, reliability, speech detection model

16.1 Introduction

Speech is the most important part of daily communication because it allows us to convey our thoughts in a specific language. Speech recognition, also known as word-by-word recognition, separates spoken words from previously recorded data and classifies the same features. For the sentence to be recognized, it must be submitted to further software for syntactic and semantic analysis. It is a similar method that evaluates voice characters and speech. For this to work, an audio sample needs to be recorded first and then converted to a waveform format. When a word is recognized, spectrum-based parameters are obtained.

The history of speech-to-text conversion has a rich history spanning decades, with significant advances driven by technological advances and scientific breakthroughs. Here’s a summary:

Early development (1950s–1970s): The origins of speech recognition can be traced back to the development of the first speech recognition in the 1950s. Early systems used simple acoustic models and pattern-matching

algorithms to separate numbers and words. A famous example is the "Audrey" system, which can find the numbers spoken by a speaker. Hidden Markov model (HMM) era (1980–1990): In the 1980s and 1990s, HMMs were widely used in speech recognition. HMMs provide a suitable technique for speech signal modeling and are widely used in acoustic modeling. This period saw major progress in independent speaker recognition and the development of limited speech guidelines (LVCSR) [14, 15].

Statistics and machine learning (2000s): The early 2000s marked the transition from speech recognition to statistics and machine learning. Gaussian mixed models (GMMs) and other statistical methods are combined with HMMs to develop acoustic models. In addition, support vector machine (SVM) and decision trees which are machine learning supervised algorithms have been incorporated into the ASR system to improve performance.

The deep learning revolution (2010s to present): The introduction of deep learning revolutionized speech recognition in the 2010s. Today's ASR is bound to deep learning techniques like deep neural networks (DNNs) and the most popularly used convolutional neural networks (CNNs) and recurrent neural networks (RNNs). These deep learning programs facilitate end-to-end training of ASR systems, eliminating the need for manual tools and achieving unprecedented levels of accuracy [16, 17].

Marketing and integration (2010s to present): Speech-to-text has become more common in recent years due to the marketing and integration of ASR technology for a variety of products and services. Virtual assistants such as Siri, Alexa, and Google Assistant leverage ASR for language understanding and interaction. Authoring services, subscriptions, and support tools have also benefited from advances in ASR technology. Speech recognition can be divided into several categories based on speech recognition, speech pattern, and pronunciation [18, 19].

Recent advancements in automatic speech recognition (ASR) systems are propelled by various influential factors. Firstly, the widespread adoption of deep learning methodologies, particularly DNNs and RNNs has revolutionized ASR by allowing models to learn intricate patterns directly from raw audio data, thus significantly enhancing recognition accuracy.

Secondly, the emergence of end-to-end models such as connectionist temporal classification (CTC) and attention-based architectures like Transformer has gained prominence, enabling simplified architectures and potentially improved accuracy by directly mapping audio input to text output without the need for multiple intermediate stages [20, 21].

Another significant trend is the increasing utilization of transfer learning and pre-trained models in ASR. By leveraging models pre-trained on extensive datasets, such as BERT and GPT, and fine-tuning them for specific ASR tasks, performance gains are achieved, particularly in scenarios with limited labeled data. Moreover, the integration of multimodal ASR approaches, incorporating additional modalities like lip movements and visual context alongside audio signals, has shown promise in boosting accuracy, especially in noisy environments or where audio input alone may be insufficient.

Additionally, there is a growing interest in addressing challenges related to low-resource and multilingual ASR, robustness, adaptability, online learning, and privacy concerns. Techniques such as data augmentation, unsupervised learning, adversarial training, and federated learning are being explored to enhance ASR performance across diverse real-world conditions while safeguarding user privacy. These trends collectively drive the development of more accurate, robust, and adaptable ASR systems, offering transformative applications in domains like virtual assistants, transcription services, healthcare, education, and beyond.

16.2 Related Works

This article investigates objective functions for learning discrimination in pattern recognition. It indicates an integrated system that will represent the target's work in good working form. Although the appropriate form of MMI is known a priori, this paper presents evidence similar to MCE and MPE/MWE. Importantly, this highlights that the useful information of objective functions differs from fixed weight measurement, which depends only on the descriptor sequence and is not independent of the processing method. This integrated approach allows the use of GT/EBW-based optimization in direct discrimination studies, solving problems previously en-

countered with MCE and MPE/MWE in the absence of such documentation. Specifically, the MMI model provides initial service recognition in terms of keyword recognition scale and development projects. In addition, research alternatives and modifications to the regression analysis model are discussed. The overall goal of this paper is to develop a simple business-level understanding of MMI, MCE, and MPE/MWE to support the development, optimization, and integration of other recognition models, such as technical process discrimination. He, X. *et al.* have discussed the limitations of the current discrimination learning paradigm [1].

This review provides a comprehensive study of all key DT technologies in ASR, providing insights from both theoretical and practical perspectives. The theoretical discussion first outlines various discriminant studies in ASR and then provides a unified framework for explaining the interactions between commonly used DT methods, initially proposed from various perspectives. Then, the basic development methods for developing these systems are explained and their components are discussed. Additionally, as part of recent developments, new discriminant learning techniques are proposed as a general strategy for paving the way for the development of various DT methods. Additionally, critical usage considerations for large ASR messages are addressed in the proposal, including strategies for effective language discrimination and action strategies for better DT target study at high altitudes. Finally, the article concludes and suggests promising avenues for future research in this field. Based on scientific research, this article provides a high-level review and discussion of all DT techniques and strategies without diving deeply into the complexity of the techniques or results [2].

Recent applications such as voice detection for creating messages on television was discussed by Dahl *et al.* in his research findings. ASR is a complex task that involves many levels of processing, from recognizing a word to identifying the tone in a sentence. DNNs are experts at classification tasks by predicting words that will appear in context and segmenting music into syllables. They are also good at extracting video using secret techniques to learn new representations from speech. However, these levels are mostly self-explanatory. This paper aims to solve this problem by presenting a modular DNN for acoustic unit classification that can in-

tegrate multiple classification methods. DNN is also recommended for word prediction of subwords. This article explores the use of multiple variables in the presentation of the demonstration of developments in the division of labor. It also explores the use of DNNs to select acoustic units, replacing the old method. Modular DNN leverages pre-trained feature extraction networks that adapt to various input features to improve classification. It is scalable and can combine various feature extraction networks. The results are compared with traditional DNNs using the same input features. In addition, this article addresses the difficulty of long compound words in German by using subwords with interword symbols. Neural networks are suitable for predicting meaningful words at the subword level. Finally, neural networks that combine prediction with modular DNN output are investigated, providing an effective approach to ASR [3].

Context-aware deep neural network hidden Markov model (CD-DNN-HMM) is demonstrated here which is a feature engineering process. In our recent work, we show that CD-DNN-HMM can reduce single-word errors in speaker-independent transcriptions, specifically calls from the NIST RT03S Fisher dataset. In particular, we observed a decrease from 27.4% (following a discrete Gaussian fusion of HMMs with HLDA features) to 18.5%. This improvement was achieved by training data for more than 300 hours from the Switchboard corpus, including more than 9000 triphone cases, and using up to 9 hidden layers in the neural network architecture [4, 5].

Deep belief networks (DBNs) are multilayer algorithms known for their ability to identify windows of speech coefficients. By training on these windows, DBN exposes multiple layers that capture the underlying structure of the data. These learned features can be effective in initializing hidden objects in subsequent neural networks, thus improving their performance in the central frame window. Compared to the initial weights, using DBN-based features can improve the performance of neural networks, especially in speech generation tasks. While DBNs have previously demonstrated success in phone recognition using mel cepstral coefficients (MFCCs) or filtering bank results, the proposed work shows that their performance is better when performing speech processing tasks for

adaptation, and discrimination. Experiments on the widely used TIMIT corpus yielded good results: a phonological error rate of 19.6% when using a monophonic HMM with large phoneme patterns, and a phonological error rate of 19.6% when used with a trilingual language model [7, 8].

This article provides an overview of speech recognition research over the last decade, focusing on the integration of the discrimination training debate. Specifically, it examines the application of several layers of preprocessing using hidden Markov models to determine the order of a word. The paper demonstrates the effectiveness of using multiple advanced technology streams in this context. Finally, this paper concludes that although deep processing can improve speech recognition, the selection of features and their integration patterns (including layer width) may also be important for thinking [6].

This article introduces the main concepts of ML, such as multivariate and discriminative learning along with the types of machine learning algorithms like supervised, unsupervised, and semi-supervised algorithms and operations, transform exchange and multitasking, and Bayesian learning, and discusses their implications for ASR.

16.3 Problem Definition

Over the past few years, speech recognition has made major advancements. Based on the model of speech, recognition of speech can be divided into two groups: live speaker and independent speaker. Speaker-based models are simpler, more accurate, and more flexible to create than standalone speaker models; Speaker-based models are more difficult to create and less accurate. Accents in particular can be extremely difficult to represent in speakerindependent models. For both devices, reaching and noisy environments are two common problems that could lower their accuracy [11]. A voice assistant needs data sources to be able to learn. These can only be created through a study that is funded or studied, which is a very limited approach. Providing data information is a big part of AI. Another one of these issues is time. Working with a voice program typically takes longer than working with a more traditional text-based program. The amount of vocabulary used by a voice recognition

system affects its complexity, accuracy, and processing requirements. Thirdly, these systems have several privacy issues. The processing demands, accuracy, and intricacy of a speech recognition system are influenced by the vocabulary size of the system. Small vocabulary (words with a single letter), Medium vocabulary (words with two or three letters), and large vocabulary are the three categories of vocabulary used in voice recognition systems that convert speech to writing.

In contrast to voice recognition, speech-to-text software is trained to comprehend and recognize spoken words. Software for voice recognition, on the other hand, concentrates on identifying unique voice patterns. The main areas where AI speech-to-text is in high demand are customer support, content search, electronic documentation, and content consumption. The adoption of speech-to-text technology is strongly supported by global content accessibility. There is a rising need for digital subtitles as online streaming replaces conventional forms of entertainment. Because the material is streamed globally to watchers with various linguistic backgrounds, real-time captioning has a sizable market. Modern users are renowned for being extremely picky and have very little patience for poor service and delays. The development of AI speech-to-text has been significantly accelerated by digital marketing, especially on mobile devices. To cut costs and enhance customer experience, many businesses use chatbots or AI assistants in customer support, at least as a first layer. Given that many users prefer voice chat, effective speech-to-text software can significantly enhance the experience of online customer support [9, 10].

16.4 System Specification

Dataset Description

Several steps need to be taken before building a neural network model on large-scale speech recognition data. The dataset used in this system contains 65,000 words. A total of 30 short sentences, one second long, with many sounds are given in this dataset. This dataset is intended for training simple machine-learning models. Audio files are placed in folders according to the words they contain. A collection of 64,727 audio files is ver-

sion 0.01, released on August 3, 2017. The process involved crowd-sourcing recordings using some open-source audio recording code instead of speaking complete sentences, participants were asked to say a single word for five minutes, collecting samples of people saying the same words. Most speakers repeat each of the twenty simple commands five times in the recording. “Yes,” “No,” “Up,” “Down,” “Left,” “Right,” “On,” “Off,” “Stop,” “Go,” “Zero,” “One,” Two,” “Three,” “Four,” “Five,” “Six,” “Seven,” “Eight,” and “Seven” are simple words. There are also ten paragraphs, most of which are said only once. Separate the unknown words. It contains “Bed,” “Bird,” “Cat,” “Monster,” “Happy,” “House,” “Marvin,” “Sheila,” “Tree,” and “Wow.” The file contains a total of 30 short words, but we use only 10 of them to build the speech-to-text model. These include “Yes,” “No,” “Up,” “Down,” “Left,” “Right,” “On,” “Off,” “Stop,” and “Next.” Table 16.1 shows the number of files for various classes.

Table 16.1 The number of files for various classes.

Class	Number of files
Up	21,157
Down	14,055
Left	18,775
Right	36,498
On	16,422
Off	30,639
Stop	38,878
Yes	28,282
No	23,532
Go	58,245

Performance Evaluation

The most accurate speech prediction is the best benchmark to evaluate the effectiveness of the model. Depending on the model selection, the speech or original voice will be correct.

- True Positive (TP): When the model correctly predicts the class it is called a true positive.
- True Negative Sample (TN): A true negative sample is the result of the model predicting the class incorrectly.
- False Positives (FP): These are cases where the model predicts the speech category but the actual results in the data differ from the prediction.

- False Negative (FN): False positive is the result of the model not predicting the class well.

Figure 16.1 below is a confusion matrix showing error types. Using this, other performance metrics such as precision, sensitivity, precision quality, and negative value can be calculated. There are 10 possible guesses and correct answers: “Yes,” “No,” “Up,” “Down,” “Left,” “Right,” “On,” “Off,” “Stop,” and “Go.” Therefore, the classifier made a total of nearly 4000 validation dataset predictions, which are equal to the actual results. The standard test is the accuracy of the algorithm’s prediction of whether the statement is true. This is done by training the model on training data and then making predictions (based on features). The result of training is the ability to measure the accuracy, practicality, and originality of the proposed method.




Figure 16.1 Confusion matrix.

Figure 16.2 shows the classification report of the signal data. The performance metrics that were used to evaluate the results are precision, recall, f1-score, and support.

	precision	recall	f1-score	support
0	0.85	0.87	0.86	430
1	0.83	0.75	0.78	420
2	0.84	0.72	0.78	433
3	0.80	0.84	0.82	420
4	0.83	0.83	0.83	429
5	0.81	0.90	0.85	421
6	0.94	0.87	0.91	431
7	0.91	0.84	0.87	435
8	0.83	0.78	0.81	412
9	0.75	0.94	0.84	432
accuracy			0.84	4263
macro avg	0.84	0.83	0.83	4263
weighted avg	0.84	0.84	0.83	4263

Figure 16.2 Classification report.

16.5 Methodology and Flowchart

The goal of this speech-to-text prediction system is to create an automated system that should be able to predict text input using user data. As a standalone online service, this word recognition technology will be available and integrated with all customer support software.

Figure 16.3 shows the CNN architecture that was referred from the journal [2] and it shows the architecture that has been utilized in this research work.

Konstantinos Demertzis *et al.* have utilized the architecture of CNN in their research, as shown in Figure 16.3. For our purposes, the input "shape" can be considered as a static spectrogram, delta, and delta-delta features (i.e., first and second temporal derivatives) playing the roles of red, green, and blue. However, as discussed below, there are several ways to accurately integrate these into feature maps. These spectrograms will be fed into the convolution layer, pool layer, fully connected hidden layer, and finally into the training and prediction process using activation func-

tion (sigmoid, tanh, or relu). Figure 16.4 shows the overall system methodology for ASR used in this project.

At the core of a CNN lies the convolutional layer, which plays a pivotal role. As interviews increasingly transition to online platforms, this layer effectively generates a matrix product by convolving a learning core with the surrounding receptive field. Unlike the image's overall dimensions, the base area processed by this layer is comparatively reduced in height and width but gains depth. For instance, in an image with three channels (RGB), while the dimensions shrink in height and width, the depth extends to encompass all three color channels.

The seeds move forward along the height and width of the image, creating an image of the captured area. Therefore, an image called the activation map of both sides of the image is created, showing the response of each area in the image. Stride is the name of the part of the kernel that can be traversed. The output size is determined by the equation given below:

$$Wout = \frac{W - F + 2P}{S} + 1 \tag{16.1}$$




Figure 16.3 Architecture of the CNN.




Figure 16.4 System design.

Equation 16.1 shows the output size. Because the parameters are shared, the layer of the convolutional neural network will be the same as a translational one. If we change the input in some way, the output is said to change accordingly.

Pool Layers

The pooling layer changes the network throughput at a given location by calculating neighbor statistics. This reduces the spatial dimension, thereby reducing the number and weight of calculations. Each representation becomes a separate process. The distance-weighted average is a combination of the function and average of the neighborhood and the population L2 standard. However, the maximum pressure, which reports the maximum value of the area, is the most commonly used method. Figure 16.5 shows the maximum pooling.




Figure 16.5 Max pooling.

If the model has a map of dimensions W D W, the core of the pool with spatial dimension F and step dimension S, the discharge dimension D can be determined by Equation 16.2 given below:

$$Wout = \frac{W - F}{S} + 1 \tag{16.2}$$

Therefore, the matrix can be calculated as usual using multiplication and balance effects. The FC layer provides a graphical representation of inputs and outputs.

Final CNN Architecture

Figure 16.6 shows the final CNN architecture which was discussed by Ossama *et al.* in their research paper [12]. First, it takes the spectrogram as input and goes through the convolution layer, pool layer (maximum pool), and the whole process. This is how CNN models are trained.

16.6 Audio Conversion

An audio signal provides a continuous description of changes over time, which could be as precise as picoseconds. However, analog signals are

memory-intensive due to their nondeterministic structure, making them computationally demanding. To facilitate easier processing, analog signals are converted into digital signals through a process called signal sampling, where a specific number of samples per second are selected.

Various techniques can be employed for feature extraction from audio signals. One such technique is time domain analysis, which represents the audio signal in terms of its amplitude over time. In simpler terms, this involves plotting amplitude against time, with the features being the amplitudes recorded at different points in time.




Figure 16.6 Final CNN architecture [12].




Figure 16.7 Time domain for the "YES" class.

Different feature extraction techniques for audio signals:

Time Domain

The audio signal is depicted based on its amplitude about time. Essentially, it involves creating a graph where the amplitude is plotted against time. These features correspond to the amplitudes captured at various points in time. Figure 16.7 shows the time domain features using the "YES" class.

Frequency Domain

In the frequency domain, an audio signal's amplitude is described relative to its frequency. This is illustrated through a graph showing the relationship between frequency and amplitude. Features in this context are the amplitudes registered at varying frequencies. Figure 16.8 shows the frequency domain features for the "yes" class.




Figure 16.8 "Yes class" frequency domain representation.




Figure 16.9 The "yes" class spectrogram.

Spectrogram

A spectrogram is a graphical representation of time versus frequency, where each point on the plot depicts the amplitude of a particular frequency at a specific moment, indicated by color intensity. Essentially, it visualizes the spectrum of frequencies (represented by different colors) evolving. In our database, each signal has a sampling rate of 16,000 Hz, but since the predominant speech frequencies are at 8000 Hz, resampling to this rate is necessary. Figure 16.9 shows the spectrogram of the “yes” class.

Figure 16.10 is a bar chart showing all 30 classes of audio samples. The X-axis represents the class and the Y-axis represents the total amount.




Figure 16.10 Total number of recordings.




Figure 16.11 Duration of recordings.

Figure 16.11 shows the number of records for the duration of 30 classes. The X-axis represents the duration and the Y-axis represents the number of audio files.

A graph that shows the performance of each distribution's classification model is known as the ROC curve which is the acronym for Receiver operating characteristic curve. This curve has two negatives:

- True Positive Rate
- False Positive Rate

ROC curves show different groups in TPR and FPR. Reducing the dispersion will distribute more positives than positives, thus making negatives and real positives. Figure 16.12 shows the ROC curve for multiclass architecture.

Precision and Recall Curve

The precision-return curve shows the trade-off between precision and return. A large area in the curve indicates high gain and high sensitivity, with high sensitivity associated with false positives and high gain with negative values. The number of true positives and the number of false positives is called the accuracy or precision. Figure 16.13 shows the precisionrecall curve.

$$\text{Precision} = \frac{True\ Positive}{True\ Positive + True\ Negative} \tag{16.3}$$




Figure 16.12 ROC curve.

Dividing the number of correct predictions versus the sum of true prediction and false prediction is called the recall metric and it is one of the evaluating measures.

$$\text{Recall} = \frac{True\ Positive}{True\ Positive + False\ Negative} \tag{16.4}$$

Model Accuracy & Loss Graph

The loss value represents how much worse or better the model is after each improvement [13]. Metrics are used to meaningfully measure the effectiveness of an algorithm. The accuracy is kept as one of the parameters to evaluate the model that has been used for classifying the given dataset. Figure 16.14 shows the model accuracy graph. Figure 16.15 shows the graph model loss.

16.7 Results and Discussion

From a total of 30 signals, 10 were selected and announced: “arrow,” “down,” “left,” “right,” “yes,” “no,” “stop,” “open,” “continue,” and “exit,” it began. There are a total of one million sound clips, each lasting one second. We cut clips shorter or longer than one second. All audio files in the file are downscaled from 44 kHz to 8 kHz, as speech models for neural training perform best at this rate. The model divides the test data set into training and test sets, which constitute 20% of the total length of the database. As per the training and testing ratio 20% test data is appointed and the other data sets are dismissed. Study and test data will be encrypted to ensure access by all parties. Also, the model evaluates the validation set every 400 steps. After training, the test set is estimated to get the accuracy of the test. Using the CNN model, we achieved 91.24% accuracy and 0.54% loss. We report accuracy, precision, recovery, and loss as our performance measures. We also plotted the ROC/AUV curve and the precisionrecall curve to illustrate the performance of the CNN model.




Figure 16.13 Precision-recall curve.




Figure 16.14 Model accuracy.




Figure 16.15 Model loss.

16.8 Conclusion

The study focused on the development of an ASR system using deep learning techniques, specifically convolutional neural networks (CNNs). The goal was to convert spoken words into written text accurately, which has numerous applications in enhancing humancomputer interactions, customer service, and accessibility. Key findings and achievements of the research include:

1. High Accuracy of Speech Recognition:
    1. The proposed model achieved a high word classification accuracy of 91.24% on unknown speech samples. This performance indicates the robustness and effectiveness of the deep learning approach, particularly CNNs, in recognizing and transcribing spoken words.
2. Dataset Utilization:

    1. The system was trained on a dataset containing 65,000 samples of short, one-second-long audio clips. These clips included both common command words (e.g., “yes,” “no,” “up,” and “down”) and other words used less frequently. The structured dataset helped in creating a reliable model capable of generalizing well to new data.
3. System Design and Methodology:
    1. The system’s architecture involved several stages, including the conversion of audio signals into spectrograms, feature extraction, and classification using CNNs. The use of spectrograms as input to the CNN allowed the model to capture essential audio features effectively.
    2. The CNN architecture included convolutional layers, pooling layers, and fully connected layers, which together processed the audio features and performed classification.
4. Performance Evaluation Metrics:
    1. The model’s performance was evaluated using various metrics, including true positive (TP), true negative (TN), false positive (FP), and false negative (FN) rates. These metrics helped in understanding the accuracy, precision, and recall of the system.
    2. The use of a confusion matrix provided a detailed insight into the types of errors made by the model and the distribution of predictions across different classes.
5. Advancements and Comparisons:
    1. The research highlighted the advancements in ASR technology from early systems using simple acoustic models to modern deep-learning approaches. The transition to deep learning, particularly CNNs, has significantly improved the accuracy and efficiency of ASR systems.
    2. Compared to traditional methods, the deep learning-based approach demonstrated superior performance in recognizing and transcribing spoken words, even in the presence of background noise and variations in speech.
6. Applications and Future Directions:
    1. The developed ASR system has potential applications in various domains, such as virtual assistants, transcription services, and customer support systems. By integrating this technology, businesses can enhance user experience and accessibility.

2. Future research could focus on expanding the vocabulary of the ASR system, improving its robustness to diverse accents and noisy environments, and exploring the integration of multimodal inputs (e.g., lip movements) to further enhance accuracy.

In conclusion, the study successfully demonstrated the effectiveness of deep learning techniques, particularly CNNs, in developing a high-accuracy ASR system. The results indicate that such systems can significantly improve human-computer interactions and have wide-ranging applications in various fields. Continued advancements in deep learning and ASR technology hold promise for even more sophisticated and accurate speech recognition systems in the future.

References

1. He, X., Deng, L., Chou, W., Discriminative learning in sequential pattern recognition—A unifying review for optimization-oriented speech recognition. *IEEE Signal Process Mag.*, 25, 5, 14–36, Sep. 2008.
2. Jiang, H., Discriminative training for automatic speech recognition: A survey. *Comput. Speech Lang.*, 24, 4, 589–608, 2010.
3. Dahl, G., Yu, D., Deng, L., Acero, A., Large vocabulary continuous speech recognition with context-dependent DBN-HMMs, in: *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process*, pp. 4688–4691, 2011.
4. Seide, F., Li, G., Chen, X., Yu, D., Feature engineering in context-dependent deep neural networks for conversational speech transcription, in: *Proc. IEEE Workshop Autom. Speech Recognition Understand. (ASRU)*, pp. 24–29, 2011.
5. Mohamed, Sainath, T., Dahl, G., Ramabhadran, B., Hinton, G., Picheny, M., Deep belief networks using discriminative features for phone recognition, in: *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, May 2011, pp. 5060–5063.
6. Morgan, N., Deep and wide: Multiple layers in automatic speech recognition. *IEEE Trans. Audio Speech Lang. Process.*, 20, 1, 7–13, Jan. 2012.
7. Deng, L. and Li, X., Machine learning paradigm for speech recognition: An overview. *IEEE Trans. Audio Speech Lang. Process.*, 21, 5, 1060–1089, May 2013.

8. Fuchs, A.K., Morales Cordovilla, J.A., Hagmuller, M., *IEEE workshop on "Automatic Speech Recognition and Understanding" 2013*.
9. Zarei-Jalalabadi, Mahboubeh, and Seyed Mohammad-Bagher Malaek. Modification of Unscented Kalman Filter Using a Set of Scaling Parameters. *IET Signal Process.*, 12, 4, 471–480, 2018, https://doi.org/10.1049/iet-spr.2017.0300. Accessed 14 Jan. 2025.
10. Orji, U.E., Ugwuishiwu, C.H., Nguemaleu, J.C.N., Ugwuanyi, P.N., Machine Learning Models for Predicting Bank Loan Eligibility. *International Conference on Disruptive Technologies for Sustainable Development (NIGERCON 2022).*
11. Demertzis, K., Rantos, K., Magafas, L., Iliadis, L., A Cross-Modal Dynamic Attention Neural Architecture to Detect Anomalies in Data Streams from Smart Communication Environments. *Appl. Sci.*, 13, 9648, 2023, https://doi.org/10.3390/app13179648.
12. Abdel-Hamid, O., *et al.*, Exploring convolutional neural network structures and optimization techniques for speech recognition. *Interspeech (2013)*.
13. Kłosowski, P., Polish language modelling for speech recognition application. *2017 Signal Processing: Algorithms, Architectures, Arrangements, and Applications (SPA)*, Poznan, Poland, pp. 313–318, 2017, doi: 10.23919/SPA.2017.8166885.
14. Rosdi, F., Mustafa, M.B., Salim, S.S., Assessing automatic speech recognition in measuring speech intelligibility: A study of malay speakers with speech impairments. *2017 6th International Conference on Electrical Engineering and Informatics (ICEEI)*, Langkawi, Malaysia, pp. 1–6, 2017, doi: 10.1109/ICEEI.2017.8312396.
15. Asadullah, Shaukat, A., Ali, H., Akram, U., Automatic Urdu Speech Recognition using Hidden Markov Model. *2016 International Conference on Image, Vision and Computing (ICIVC)*, Portsmouth, UK, pp. 135–139, 2016, doi: 10.1109/ICIVC.2016.7571287.
16. Fuchs, A.K., Morales-Cordovilla, J.A., Hagmüller, M., ASR for electro-laryngeal speech. *2013 IEEE Workshop on Automatic Speech Recognition and Understanding*, Olomouc, Czech Republic, pp. 234–238, 2013, doi: 10.1109/ASRU.2013.6707735.
17. Mitra, V., *et al.*, Joint modeling of articulatory and acoustic spaces for continuous speech recognition tasks. *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, New

Orleans, LA, USA, pp. 5205–5209, 2017, doi: 10.1109/ICASSP.2017.7953149.

18. Ferdiansyah, V. and Purwarianti, A., Indonesian automatic speech recognition system using English-based acoustic model. *Proceedings of the 2011 International Conference on Electrical Engineering and Informatics*, Bandung, Indonesia, pp. 1–4, 2011, doi: 10.1109/ICEEI.2011.6021583.
19. Kozierski, P., Sadalla, T., Drgas, S., Dąbrowski, A., Zietkiewicz, J., The impact of vocabulary size and language model order on the polish whispery speech recognition. *2017 22nd International Conference on Methods and Models in Automation and Robotics (MMAR)*, Miedzyzdroje, Poland, pp. 616–621, 2017, doi: 10.1109/MMAR.2017.8046899.
20. Saranya, K., *et al.*, Fractal Based Feature Extraction Technique for Classifying EEG Signal for Color Visualization Tasks. *J. Intell. Fuzzy Syst.*, 46, 2, 4315–4324, 2024. DOI: 10.3233/JIFS-235469.
21. K, S. and M., P., Certain Investigation on Eeg Signal Processing Using Auto Regression Feature for Various Colour Stimuli. *2023 International Conference on Intelligent Systems for Communication, IoT and Security (ICISCoIS)*, Coimbatore, India, pp. 247–252, 2023, doi: 10.1109/ICISCoIS56541.2023.10100447.

Note

1. *Corresponding author: thangappan@periyaruniversity.ac.in