

Auth Settings

Settings for django.contrib.auth.

AUTHENTICATION_BACKENDS

A list of authentication backend classes (as strings) to use when attempting to authenticate a user.

Default: ['django.contrib.auth.backends.ModelBackend']

AUTH_USER_MODEL

The model to use to represent a User.

Default: 'auth.User'

LOGIN_REDIRECT_URL

The URL or named URL pattern where requests are redirected after login when the LoginView doesn't get a next GET parameter.

Default: '/accounts/profile/'

Auth Settings

LOGIN_URL

The URL or named URL pattern where requests are redirected for login when using the `login_required()` decorator, `LoginRequiredMixin`, or `AccessMixin`.

Default: `'/accounts/login/'`

LOGOUT_REDIRECT_URL

The URL or named URL pattern where requests are redirected after logout if `LogoutView` doesn't have a `next_page` attribute.

If `None`, no redirect will be performed and the logout view will be rendered.

Default: `None`

Auth Settings

PASSWORD_RESET_TIMEOUT

The number of seconds a password reset link is valid for. Depending on when the link is generated, it will be valid for up to a day longer.

Used by the PasswordResetConfirmView.

Default: 259200 (3 days, in seconds)

PASSWORD_HASHERS

Default: [

'django.contrib.auth.hashers.PBKDF2PasswordHasher',
'django.contrib.auth.hashers.PBKDF2SHA1PasswordHasher',
'django.contrib.auth.hashers.Argon2PasswordHasher',
'django.contrib.auth.hashers.BCryptSHA256PasswordHasher',

]

Auth Settings

AUTH_PASSWORD_VALIDATORS

The list of validators that are used to check the strength of user's passwords.

Default: [] (Empty list)