Rapid Spanning Tree Protocol (RSTP) on Ring topology with Bluboxx managed switch(BBIES-M-8GE2GF) Configuration setting

Bluboxx managed switch(BBIES-M-8GE2GF) Configuration setting

Configuration

Current User:admin   Log Out

System Home

Quick Configuration

+ Port Management

− VLAN Management

   VLAN Management
   Voice VLAN
   Surveillance VLAN

− Fault / Safety

   Attack Prevention
   Path Detection
   DDOS Protection
   Loopback Detection
   STP
   Access Control
   IGMP
   MLD
   IEEE 802.1X

STP Global   STP Port Settings

STP Port Settings

Select a port to configure:

5 6 7 8
1 2 3 4 9 10

Optional port   Fixed port   Selected port   [1] Aggregation port   Select all   Select all others   Cancel

port Staue: Enabled   BPDU Filter: Disabled
BPDU Guard: Disabled   Root Guard: Disabled
Port Fast: Disabled   Port Priority: 128

Apply

Port List

Port	Port Fast	State	BPDU Filter	BPDU Guard	Root Guard	port Staue	Port Priority	Role	Edit
1	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
2	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
3	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	

Model name:Switch   Hardware Version: B1   Soft Version: 1.00.003

running-config.cfg   Show all

11:53
04-10-2022

Current User:admin   Log Out

   Path Detection
   DDOS Protection
   Loopback Detection
   STP
   Access Control
   IGMP
   MLD
   IEEE 802.1X
   AAA
   ERPS

+ System Management

+ QoS

+ EEE

Port Fast: Disabled   Port Priority: 128

Apply

Port List

Port	Port Fast	State	BPDU Filter	BPDU Guard	Root Guard	port Staue	Port Priority	Role	Edit
1	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
2	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
3	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
4	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
5	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
6	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
7	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
8	Disabled	Link down	Disabled	Disabled	Disabled	enabled	128	disabled	
9	Disabled	Forwarding	Disabled	Disabled	Disabled	enabled	128	designated	
10	Disabled	Forwarding	Disabled	Disabled	Disabled	enabled	128	designated	

First Previous [1] Next Last 1 / 1Page

Model name:Switch   Hardware Version: B1   Soft Version: 1.00.003

running-config.cfg   Show all

11:54
04-10-2022