Boring: 1

Project: Quick Quack Car Wash Facility
4-771 Kuhio Highway- Waipouli Town Center

Location: Kapaa, Kauai, Hawaii

Surface Elevation: Not Available

Depth to Water: 7.2' (3-9-26, 10:34am)

Date Completed: 3-9-26

F.G.E. Ltd.

File: 3609.01

Project Engineer: JN

Field Engineer: JN

Drafted by: KSL

Date of Drawing: May 2026

LAB TEST RESULTS	MOIST CONT. %	DRY DEN. PCF	BLOWS PER FT. *(x) See Legend	SAMPLE	DEPTH	CLASSIFICATION
					0	3.5" AC Pavement over 3.5" Tan Poorly-graded Beach Sand
pH= 7.5 Minimum Electrical Resistivity= 900ohm-cm	43	85	11 *(8)	1		Brown Clayey SILT (ML), very stff, damp
LL= 49, PI= 18	21	105	42 (29)	2		
					5	**(FILL)**
	24	100	30 (16)	3		Tan to Gray Well-graded SAND (SW-SM) with Silt, medium dense, damp **(BEACH SAND)**
Gradation: Gravel= 10% Sand= 76% Silt/Clay= 14%	16		21 (11)	4	10	Gray Silty Coral SAND (SM), medium dense, saturated
	43	80	7 (4)	5		At 13.0', grades very loose
					15	**(LAGOONAL)**
						BOH @ 15.0'
					20	
					25	
					30	
					35	

Figure 3

F.G.E. Ltd.

Boring: 2
Project: Quick Quack Car Wash Facility
4-771 Kuhio Highway- Waipouli Town Center
Location: Kapaa, Kauai, Hawaii
Surface Elevation: Not Available
Depth to Water: None Encountered (3-9-26, 12:07pm)
Date Completed: 3-9-26

File: 3609.01
Project Engineer: JN
Field Engineer: JN
Drafted by: KSL
Date of Drawing: May 2026

LAB TEST RESULTS	MOIST CONT. %	DRY DEN. PCF	BLOWS PER FT. *(x) See Legend	SAMPLE	DEPTH	CLASSIFICATION
					0	3.75" AC Pavement over 4.5" Tan Poorly-graded SAND with Coral Gravel
Swell= 0.3% Swell Index= 0.16	36	89	37 *(25)	1		Brown Clayey SILT (ML), very stiff, damp **(FILL)**
	22	91	45 (31)	2		Tan Well-graded Fine-grained SAND (SW-SM) with Silt, medium dense, damp
					5	
Gradation: Gravel= 16% Sand= 78% Silt/Clay= 6%	27		23 (13)	3		At 6.0', grades Medium-grained with Coral Gravel **(BEACH SAND)**
	18	114	20 (11)	4		Gray Silty Medium to Coarse Coral SAND (SM) with Coral Gravel, medium dense, wet
					10	
	30		5 (3)	5		At 13.0', grades very loose **(LAGOONAL)**
					15	**BOH @ 15.0'**
					20	
					25	
					30	
					35	

Figure 4

F.G.E. Ltd.

Boring: 3

Project: Quick Quack Car Wash Facility
4-771 Kuhio Highway- Waipouli Town Center

Location: Kapaa, Kauai, Hawaii

Surface Elevation: Not Available

Depth to Water: None Encountered (3-9-26, 2:41pm)

Date Completed: 3-9-26

File: 3609.01

Project Engineer: JN

Field Engineer: JN

Drafted by: KSL

Date of Drawing: May 2026

LAB TEST RESULTS	MOIST CONT. %	DRY DEN. PCF	BLOWS PER FT. *(x) See Legend	SAMPLE
LL= 67, PI= 29	45	79	26 *(18)	1
Direct Shear: C= 800psf Ø= 20° Swell= 0.0%	42	85	18 (13)	2
	43	81	60 (32)	3
			18 (10)	4
Gradation: Gravel= 47% Sand= 39% Silt/Clay= 14%	40	88	5 (3)	5

DEPTH: 5, 10, 15, 20, 25, 30, 35

CLASSIFICATION

- 4.5" AC Pavement over 3.5" Tan Poorly-graded Beach Sand
- Brown Clayey SILT (MH), very stiff, damp **(FILL)**
- Gray Well-graded Fine-grained Sand (SW-SM) with Silt, dense, damp **(BEACH SAND)**
- Gray Silty Medium-grained SAND (SM) with Gravel, loose, wet **(LAGOONAL)**
- Gray Silty Coral GRAVEL (GM) with Sand, very loose, wet **(LAGOONAL)**

BOH @ 15.0'

Figure 5