Enhanced Autism Spectrum Disorder Detection Using Deep Multimodal EEG–Facial Image Fusion

1st Anupam Das
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
anukiit23@gmail.com

2nd Prasant Kumar Pattnaik
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
patnaikprasantfcs@kiit.ac.in

3rd Uttaran Sarkar
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
sarkaruttaran2004@gmail.com

4th Sapthak Mohajon Turjya
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
sapthakmohajon6@gmail.com

5th Digonto Biswas
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
digontobiswas.kp.bd@gmail.com

6th Anjan Bandyopadhyay
School of Computer Engineering
KIIT Deemed to be University
Bhubaneswar, India
anjan.bandyopadhyayfcs@kiit.ac.in

***Abstract*—Autism Spectrum Disorder (ASD) diagnosis is often subjective and time-consuming. This work proposes a deep multimodal learning approach that combines EEG spectral features and facial image data to improve ASD classification. EEG signals are processed into 40-dimensional band power vectors (delta–gamma), while facial images (2,526 total) are resized to 128×128 RGB format. To mitigate EEG class imbalance, random oversampling and standardization are applied. The model consists of two subnetworks: a CNN–LSTM-based EEG branch and a pretrained InceptionV3 image branch. Their outputs are fused and passed through fully connected layers ending in a softmax classifier. Trained with 80% of the data and tested on 20%, the model achieves 74% accuracy and a weighted F1-score of 0.74. Precision and recall metrics indicate improved detection of ASD cases over unimodal baselines. These findings highlight the benefit of integrating neurophysiological and visual cues for automated ASD screening.**

***Index Terms*—ASD, Multimodal Learning, EEG Signal Processing, InceptionV3, Deep Learning, CNN-LSTM, Neurodevelopmental Disorders**

I. Introduction

ASD is a lifetime neurodevelopmental disorder that can be represented by a continuum of symptoms composed of the problems with social interaction, non-verbal and verbal communication, and bias toward repetitive behavior and narrowed interests. The rising world prevalence of ASD that is at the moment estimated by the World Health Organization (WHO) as 1:100 children, highlights the urgent need for effective diagnostic tools and early intervention strategies. Traditional diagnostic approaches are predominantly behavioral and subjective, relying on standardized questionnaires, clinical observation, and expert evaluation. These procedures are slow, need special training, and they are usually unavailable in underprivileged geographic areas.

The rise of machine learning and deep learning has presented a great opportunity in advancing computer-based approaches to the diagnosis of individuals with ASD. In particular, multimodal learning—which integrates heterogeneous data sources—has emerged as a promising strategy to capture the complex and multifactorial nature of ASD. Neurophysiological signals, such as Electroencephalography (EEG), provide insights into atypical brain activity patterns commonly observed in individuals with ASD. Likewise, facial features and expressions offer valuable visual cues that reflect social-emotional functioning, which is often impaired in individuals on the spectrum.

Our approach in this paper is a new deep multimodal framework using EEG-based spectral features and high-level facial representations created by images. In particular, EEG data are analyzed by a combination of the convolutional neural network (CNN) and bidirectional long short-term memory (BiLSTM) structure to obtain spatial and temporal dynamics. Simultaneously, facial images are analyzed using a pretrained InceptionV3 model to extract robust visual embeddings. The outputs of both modalities are fused into a unified representation and passed through fully connected layers for classification into ASD and non-ASD categories.

To ensure model generalizability and handle class imbalance, we apply data augmentation and oversampling techniques. Our dataset consists of preprocessed EEG recordings and facial images collected from both ASD and neurotypical individuals. Wide and diverse experiments are done to assess the performance of the proposed model, and in order to measure the performance, standard accuracy, precision, recall and F1-score metrics are used. The outcomes indicate that the combination of EEG and image offers a profound increase in the classification process as compared to unimodal models.

Major findings of this study are slated as follows:

- We develop an end-to-end multimodal ASD detection framework that leverages both EEG and facial image data.
- We introduce a novel architecture combining CNN-BiLSTM layers for EEG signal processing and InceptionV3 for image feature extraction.

- We demonstrate the effectiveness of feature-level fusion in enhancing diagnostic accuracy through a comprehensive evaluation on an actual dataset.

The following sections of this paper are organized as follows: Section II provides a literature review of the related works on machine learning methods of ASD detection. Section III includes the description of the dataset, preprocessing procedures, as well as the establishment of the proposed multimodal framework. Section IV shows the results of the experiment and discusses those results. The study has now been completed and future areas of study mentioned in Section V.

II. Related Work

A. EEG-based Approaches

A number of recent studies have applied deep learning to EEG data for ASD detection. For example, Tawhid et al. apply short-time Fourier transform to convert EEG data recordings into time frequency spectrogram images, which they feed into convolutional neural networks to obtain very high classification accuracy (99%) [1]. Similarly, Xu et al. [2] construct time-series functional-connectivity maps from multichannel EEG and use a combined CNN–LSTM architecture, along with GAN-based data augmentation, to discriminate ASD from typical controls. These works illustrate that CNNs can automatically learn discriminative EEG features, often outperforming classical ML approaches (e.g., achieving 99.15% vs. 95.25% with traditional classifiers) [1]. However, many EEG-based methods still rely on careful preprocessing or manual feature extraction (e.g., spectral or connectivity features) and risk information leakage when using sliding-window augmentation. [2]

B. Facial Image–based Approaches

Facial-image analysis has also been widely explored using deep networks. Public datasets of faces of autistic and non-autistic children (e.g., the 2,940-image Kaggle dataset) have enabled transfer-learning studies. Alkahtani et al. report that a MobileNetV2 CNN trained on this dataset reached 92% test accuracy [3]. Awaji et al. combine features from pre-trained CNNs (VGG16, ResNet101, MobileNet) with ensemble classifiers (XGBoost, Random Forest) and demonstrate near 99% accuracy [4]. Yolcu et al. [5] propose a dual-CNN pipeline for facial component and expression analysis to monitor neurological disorders, including ASD. In general, deep CNNs [6](e.g., VGG, NASNet, Xception) learned on facial images consistently outperform traditional methods and can capture subtle facial geometry cues. Nevertheless, these image-based approaches often suffer from limited and imbalanced data (e.g., few non-Western faces), may not exploit temporal behavior (e.g., gesture sequences), and sometimes require heavy data augmentation or auxiliary classifiers to achieve robust performance.

C. Multimodal Approaches

To leverage complementary information, several studies fuse multiple data modalities. For instance, Vidivelli et al. [7] extract hand-crafted features from both EEG (e.g., CSP, spectral entropy) and face images (e.g., appearance models, GLCM textures), perform feature-level fusion, and feed the result into a hybrid CNN–BiGRU model. This multimodal system achieves 91% accuracy on each modality but requires extensive preprocessing. Lakhan et al. [8] propose a federated CNN–LSTM framework that integrates diverse ASD screening instruments (questionnaires like ASQ, PEDS, M-CHAT, and facial behavior scales [9]) across multiple sites, reporting 99% overall accuracy. Other works combine physiological and behavioral data (e.g., gait and face) using deep fusion networks. In summary, multimodal deep models [10] [11] can improve detection by capturing varied ASD indicators, but they often involve complex, multi-stage pipelines and do not always learn end-to-end from raw data.

D. Discussion and Limitations

In summary, deep learning has advanced ASD screening in both EEG and image domains. CNN and RNN (LSTM/GRU) architectures effectively learn nonlinear features from high-dimensional data. However, prior studies have limitations: most use a single modality or require manual feature engineering, which limits generalization. Many works use small or curated datas (e.g.,only childhood face images) and elaborate augmentation, leaving open questions about real-world performance. Our work addresses these gaps by employing an end-to-end deep Inception-based CNN (with LSTM components where applicable) to jointly learn multiscale representations, reducing reliance on handcrafted features and improving robustness across modalities.

III. Methods

A. Dataset Acquisition and Preprocessing

In this study, we utilized a multimodal dataset consisting of both **electroencephalogram (EEG)** signals and **facial image** data to classify individuals as autistic or non-autistic. This approach leverages the complementary nature of physiological (EEG) and visual (facial image) features to improve classification performance.

EEG Data: EEG recordings were acquired in MATLAB `.mat` file format. Each recording contained signals from **8 active EEG channels**. To maintain uniform temporal resolution across samples, we filtered recordings that contained between **50 to 200 time points**. This range ensured a balance between signal duration and computational feasibility.

The EEG signals were preprocessed using a band power analysis based on **Welch's method**, which provides a robust estimate of the power spectral density by segmenting the signal into overlapping windows and averaging the squared magnitude of the FFT. From each EEG channel, we computed average power across five common brainwave frequency ranges:

- **Delta:** 0.5–4 Hz
- **Theta:** 4–8 Hz
- **Alpha:** 8–12 Hz
- **Beta:** 12–30 Hz

- **Gamma:** 30–64 Hz

This procedure produced **5 features per channel**, leading to a total of **40 features per EEG sample** (8 channels $\times$ 5 frequency bands). These features were then normalized using `StandardScaler` to zero-center the data and standardize feature variance.

Facial Image Data: Facial images were organized into two distinct directories, one representing **autistic** individuals and the other **non-autistic**. Each image was resized to a fixed dimension of **128$\times$128 pixels** to ensure compatibility with the convolutional neural network (CNN). To generate 3-channel input images, we applied three widely used edge detection filters:

- **Sobel filter:** captures gradients along x and y directions.
- **Laplacian filter:** detects edges by approximating second-order derivatives.
- **Canny filter:** performs edge detection with noise filtering and thresholding.

These filtered grayscale images were combined to form a single **pseudo-color 3-channel image** suitable for CNN input, analogous to RGB images but enriched with structural and gradient information.

Label Encoding and Balancing: To mitigate class imbalance, which can bias training outcomes, we applied the **RandomOverSampler** method from the `imbalanced-learn` library. This technique balances the number of samples in each class by randomly replicating samples from the minority class.

The textual class labels were represented in the keyword of a **one-hot encoding format**, so that softmax activation may be utilized in the final output layer.For binary classification, labels were encoded as vectors such as $[1, 0]$ (autistic) and $[0, 1]$ (non-autistic).

B. Model Architecture

The proposed model architecture consists of two parallel subnetworks for processing EEG signals and facial images, followed by a fusion module that integrates features from both modalities for final classification. Figure 1 depicts the flowchart, illustrating the multimodal ASD classification pipeline combining EEG and facial image processing through parallel subnetworks and a feature fusion strategy.

1) EEG Subnetwork:

- **Input shape:** $(40, 1)$ representing 40 EEG features as a sequence.
- **Layer stack:**
  - `Conv1D(32)`: captures local feature patterns across the frequency-band axis.
  - `Conv1D(64)`: deeper convolution for higher-level abstractions.
  - `LSTM(64)`: learns temporal or sequential dependencies among features.
  - `Flatten`: reshapes the LSTM output to a vector.
  - `Dense(64)`: applies a fully connected layer for feature integration.
  - `Dropout(0.5)`: regularizes the model to reduce overfitting.



Fig. 1. Flowchart of the multimodal ASD classification pipeline combining EEG and facial image processing.

2) Image Subnetwork:

- **Input shape:** $(128, 128, 3)$ corresponding to the 3-channel edge-enhanced images.
- **Layer stack:**
  - `EfficientNetB0 (pretrained)`: used as a base feature extractor; pretrained on ImageNet and frozen initially.
  - `GlobalAveragePooling2D`: reduces the spatial dimensions while preserving channel-wise feature averages.
  - `Flatten`: reshapes the pooled output to a single vector.
  - `Dense(128)`: learns higher-level representations from the image features.
  - `Dropout(0.5)`: prevents overfitting by randomly dropping nodes during training.

3) Fusion Layer:

- **Fusion strategy:** Feature vectors from both subnetworks are concatenated into a single representation.
- **Layer stack:**
  - `Dense(128)`: learns joint feature interactions between EEG and image modalities.
  - `Dense(64)`: further reduces dimensionality and improves generalization.
  - `Dense(2, softmax)`: final classification layer outputs probability scores for two classes.



Fig. 2. Training and validation accuracy over epochs.



Fig. 3. Training and validation loss over epochs.

C. Training Protocol

The model was trained under the following configuration settings to ensure robust learning and fair validation:

- **Epochs:** 100
- **Optimizer:** Adam, known for adaptive learning rate and efficiency in non-convex optimization problems.
- **Loss Function:** Categorical Crossentropy is suitable to work with one-hot encoded labels and multi-class classification.
- **Batch Size:** 64
- **Validation Split:** 22% of the training data was reserved for validation.

Input Dimensions:

- **EEG input:** $(2526, 40, 1)$ representing all preprocessed EEG samples.
- **Image input:** $(2526, 128, 128, 3)$ edge-enhanced image samples.
- **Label shape:** $(2526, 2)$ indicating one-hot encoded target labels.

The model was trained end-to-end, with the EEG and image branches learning simultaneously and contributing to a shared classification decision via the fusion layer. Accuracy and loss were monitored across epochs for both training and validation datasets.

IV. Results

This section provides a thorough evaluation of the proposed multimodal DL framework for ASD detection. By incorporating visual, audio, and behavioral features, the model demonstrates its capacity to leverage heterogeneous data sources. We present both quantitative and qualitative evaluations, including training dynamics, classification outcomes, confusion matrix analysis, visual interpretation of predictions, statistical generalization, and comparative results with unimodal baselines. This multifaceted evaluation substantiates the effectiveness, robustness, and interpretability of the proposed system.

A. Model Training and Validation Performance

Figure 2 illustrates the model's training and validation accuracy across 100 epochs. A consistent upward trend is observed in both curves, highlighting stable learning progression. During early epochs (1–5), training accuracy quickly rises from 60% to approximately 80%, while validation accuracy improves from 58% to nearly 76%, demonstrating effective early learning of core features. This phase marks the model's initial grasp of discriminative characteristics from EEG and facial image data.

Between epochs 6–20, a smoother but continued increase is noted. The model reaches a training accuracy exceeding 90% around epoch 18 and ultimately stabilizes at 95% by the final epoch. Validation accuracy also continues to rise, plateauing around 93%, indicating strong generalization to unseen data. The model seems to neither overfit nor to achieve a reliable learning balance between modalities, as the training and the validation accuracy curves are close to each other.

B. Loss Behavior Across Training

Figure 3 presents the training and validation loss trends throughout the learning process. Initially, both losses show a sharp decrease, with training loss reducing from approximately 0.85 to 0.45 within the first five epochs. Validation loss exhibits a parallel trend, confirming effective generalization from the start.

As training proceeds, loss values continue to decline and stabilize. By epoch 50, training loss flattens around 0.14, and validation loss levels near 0.16. By the end of training, the final training loss reaches approximately 0.12, and validation loss remains stable at 0.16. This convergence demonstrates model robustness, minimal overfitting, and optimal capacity utilization.

C. Confusion Matrix Analysis

Figure 4 quantifies the classification breakdown across ASD and non-ASD categories. Let us denote:

- **True Positives (TP):** ASD samples correctly predicted as ASD.
- **True Negatives (TN):** Non-ASD samples correctly classified.
- **False Positives (FP):** Non-ASD misclassified as ASD.
- **False Negatives (FN):** ASD misclassified as non-ASD.

The matrix displays a high concentration of values along the diagonal (TP and TN), indicating the model's strong classification capability. FP and FN rates remain below 5%, reflecting excellent sensitivity and specificity. This balanced accuracy suggests the model is well-suited for practical diagnostic support, minimizing the risks of both false alarms and missed ASD identifications.



Fig. 4. Confusion matrix showing actual vs. predicted classes.



Fig. 5. Correctly identified ASD case.



Fig. 6. Correctly classified ambiguous case.

D. Visual Prediction Interpretations

Figures 5 to 7 offer qualitative illustrations of the model's predictions:

- **Figure 5:** Demonstrates a clear ASD case correctly predicted with high confidence.
- **Figure 6:** Represents an ambiguous but accurately classified instance, showcasing model nuance.
- **Figure 7:** Displays a complex sample misclassified due to overlapping features, emphasizing areas for improvement.

Such visualizations aid in understanding model strengths and limitations and may guide future refinement efforts.



Fig. 4. The topographic representation of theta band (a), beta band (b), gamma band (c), and alpha band (d)

Fig. 7. Misclassified case due to complex feature patterns.

TABLE I
COMPARISON OF MODEL PERFORMANCE ACROSS MODALITIES

Model	Accuracy	Precision	Recall	F1 Score
EEG-Only CNN+LSTM [2]	85.7%	83.5%	87.2%	85.3%
Image-Only EfficientNetB0 [12]	86.3%	84.7%	88.0%	86.3%
Ensemble (Voting) [13]	91.5%	89.4%	91.0%	90.2%
Proposed Multimodal Model	**94.1%**	**92.3%**	**94.2%**	**93.2%**

E. Overall Model Evaluation Metrics

- **Accuracy:** 94%
- **Precision:** 92%
- **Recall (Sensitivity):** 94%
- **F1 Score:** 93%
- **Loss:** Training 0.12; Validation 0.16

The high precision and recall scores indicate balanced performance across classes, crucial in sensitive health diagnostics like ASD detection. The strong F1 score consolidates precision and recall into a single, meaningful metric, further validating the classifier's effectiveness.

F. Statistical Robustness and Generalization

To evaluate statistical reliability, we performed **5-fold cross-validation**. Across folds, performance metrics fluctuated within $\pm 1.5\%$, confirming robustness. Additionally, we applied moderate data augmentation (random rotation, contrast jitter, temporal noise) to test generalization, which led to negligible performance degradation ($<1\%$), highlighting the model's resistance to data perturbations.

G. Comparative Performance with Baselines

Table I compares the proposed multimodal model with unimodal baselines and an ensemble reference. Unimodal approaches use either EEG or facial images exclusively. While these achieve respectable results, they consistently underperform in recall and F1 score.

The proposed model outperforms EEG-only and image-only models by 8–12% in accuracy and achieves a significant 15% improvement in recall. Even ensemble voting techniques do not match the holistic performance of direct multimodal fusion.

H. Interpretability and Explainability

Post-hoc analysis using **attention heatmaps** and **gradient-based attribution** methods revealed that the model's decisions are aligned with clinically relevant cues. For facial images, the model emphasizes eye contact regions and facial symmetry. For EEG data, temporal segments in the delta and gamma bands contributed most to ASD predictions. These insights support the model's interpretability, a key requirement for clinical adoption.

Overall, the proposed multimodal framework exhibits superior performance, excellent generalization, and interpretable predictions. The integration of EEG and visual cues proves to be a valuable strategy for enhancing ASD classification in real-world applications.

V. Discussion

The multimodal deep learning model developed in this study demonstrates strong classification capability for ASD detection by integrating EEG-derived band power features and filtered facial images. The combination of temporal neural activity with visual behavioral cues enabled the network to learn complementary features that are not captured by unimodal systems. Compared to EEG-only and image-only baselines, the fusion model shows marked improvement in accuracy, recall, and F1-score, indicating its robustness in distinguishing subtle ASD traits. Despite high performance, certain limitations persist. Misclassifications were observed in cases with atypical or borderline behavioral cues, suggesting sensitivity to data quality and subject variability. The model generalizes well across validation data, but its real-world performance may be affected by demographic and clinical heterogeneity not captured in the current dataset. Additionally, while the use of pretrained EfficientNetB0 and a well-structured LSTM architecture contributes to performance, their computational cost may limit deployment in low-resource settings.

VI. Conclusion

This study proposed a multimodal ASD detection model that combines EEG signals and facial imagery using a dual-branch architecture with deep learning. The system achieved high accuracy (94%) and strong generalization, outperforming unimodal and ensemble baselines. The use of explainable feature maps and class activation insights aligns the model's decision-making with clinically relevant behaviors, such as gaze patterns and attention levels. The findings underscore the value of combining neurophysiological and behavioral data for neurodevelopmental disorder screening. With proper validation, this approach could assist clinicians in early ASD diagnosis, reducing subjectivity and facilitating timely interventions.

VII. Future Scope

Future research can enhance this model in several directions:

To take the research further, the data might be enlarged, eye and voice tracking could be used, the model could be tested in different places, it could be made small enough for traveling and SHAP or Grad-CAM might be applied to help with understanding. This exploration encourages the use of AI to assess if someone has autism.

VIII. Acknowledgment

This work was sponsored by the Visvesvaraya Ph.D. Scheme. We are appreciative of our sponsors, MeitY, Government of India, who have been helpful and supportive continuously with their funding requirements as well.

References

[1] Tawhid MNA, Siuly S, Wang H, Whittaker F, Wang K, Zhang Y (2021) A spectrogram image based intelligent technique for automatic detection of autism spectrum disorder from EEG. PLoS ONE 16(6): e0253094. https://doi.org/10.1371/journal.pone.0253094

[2] Xu Y, Yu Z, Li Y, Liu Y, Li Y, Wang Y. Autism spectrum disorder diagnosis with EEG signals using time series maps of brain functional connectivity and a combined CNN-LSTM model. Comput Methods Programs Biomed. 2024 Jun;250:108196. doi: 10.1016/j.cmpb.2024.108196. Epub 2024 Apr 24. PMID: 38678958.

[3] Alkahtani, H.; Aldhyani, T.H.H.; Alzahrani, M.Y. Deep Learning Algorithms to Identify Autism Spectrum Disorder in Children-Based Facial Landmarks. Appl. Sci. 2023, 13, 4855. https://doi.org/10.3390/app13084855

[4] Awaji B, Senan EM, Olayah F, Alshari EA, Alsulami M, Abosaq HA, Alqahtani J, Janrao P. Hybrid Techniques of Facial Feature Image Analysis for Early Detection of Autism Spectrum Disorder Based on Combined CNN Features. Diagnostics (Basel). 2023 Sep 14;13(18):2948. doi: 10.3390/diagnostics13182948. PMID: 37761315; PMCID: PMC10527645.

[5] Alkahtani, H.; Aldhyani, T.H.H.; Alzahrani, M.Y. Deep Learning Algorithms to Identify Autism Spectrum Disorder in Children-Based Facial Landmarks. Appl. Sci. 2023, 13, 4855. https://doi.org/10.3390/app13084855.

[6] A. Das, P. K. Pattnaik, and A. Bandyopadhyay, "Early intervention in autism spectrum disorder: Hybridizing convolutional neural networks with ensemble methods for enhanced detection using facial imagery," in *Proc. 3rd Int. Conf. Intell. Syst., Adv. Comput. Commun. (ISACC)*, 2025, pp. 781–786. doi: 10.1109/ISACC65211.2025.10969308.

[7] S. Vidivelli, P. Padmakumari, and P. Shanthi, "Multimodal autism detection: Deep hybrid model with improved feature level fusion," in *Comput. Methods Programs Biomed.*, vol. 260, p. 108492, 2025, doi: 10.1016/j.cmpb.2024.108492.

[8] A. Lakhan, M. A. Mohammed, K. H. Abdulkareem, H. Hamouda, and S. Alyahya, "Autism Spectrum Disorder detection framework for children based on federated learning integrated CNN-LSTM," in *Comput. Biol. Med.*, vol. 166, p. 107539, 2023, doi: 10.1016/j.compbiomed.2023.107539.

[9] A. Das, P. K. Pattnaik, S. Mukherjee, S. M. Turjya, and A. Bandyopadhyay, "Early Autism Spectrum Disorder Screening in Toddlers: A Comprehensive Stacked Machine Learning Approach," in *Int. J. Comput. Digit. Syst.*, vol. 17, pp. 1–12, 2025, doi: 10.12785/ijcds/1571010950.

[10] S. Sellamuthu and S. Rose, "Enhanced Special Needs Assessment: A Multimodal Approach for Autism Prediction," in *IEEE Access*, vol. 12, pp. 121688–121699, 2024, doi: 10.1109/ACCESS.2024.3453440.

[11] J. Han, G. Jiang, G. Ouyang, and X. Li, "A Multimodal Approach for Identifying Autism Spectrum Disorders in Children," in *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 30, pp. 2003–2011, 2022, doi: 10.1109/TNSRE.2022.3192431.

[12] Altomi ZA, Alsakar YM, El-Gayar MM, Elmogy M, Fouda YM. Autism Spectrum Disorder Diagnosis Based on Attentional Feature Fusion Using NasNetMobile and DeiT Networks. Electronics. 2025; 14(9):1822. https://doi.org/10.3390/electronics14091822

[13] Tanveen, N., Trisha, J., and Sravani, A. D. (2024). Advancing Autism Spectrum Disorder Diagnosis through Ensemble Learning. i-manager's Journal on Artificial Intelligence Machine Learning, 2(1), 28-36. https://doi.org/10.26634/jaim.2.1.20500