

DIHWorld Audio

Dynamics / Guard Manual

Current product versions, controls, presets, meters, and placement

DIHWorld Audio builds connected production systems around the Imhotep 369 Engine—a Triadic Harmonic Lattice—and Ma'at 357 / MomentumBend. Phi-derived control and the canonical Phi/2 ceiling preserve movement, balance, and musical intent without brickwall limiting.

This edition documents 4 current products. Release numbers are taken from the installed DIHWorld Audio Audio Units verified on 2026-10-05; they are product versions, not a shared catalog version.

Canon reference: normalized $\Phi/2 = 0.809016994$. MomentumBend shapes motion and containment; the ceiling is a canonical boundary, not permission for hard limiting.

Operating law: begin from reset or a purpose-matched preset, compare at equal loudness, change one system at a time, and judge the result in the full arrangement.

ANUBIS

RELEASE	FAMILY	PLACEMENT
v1.0.1	Dynamics / Guard	Insert Safe

Dynamics gate and guard with threshold, ratio, attack, hold, release, range, a named stereo host Sidechain bus, independent Sidechain Key and Sidechain Duck operation, protected I/O, and parallel mix.

Recommended use: guard/dynamics

Customer formats: AU, VST3, Standalone

Primary controls

Input • Mix • Output • Power • Threshold • Ratio • Attack • Hold • Release • Range • Channel Mode • Dual Mono Link

Factory starting points — source-derived purpose

TRANSPARENT PASS [Stereo]

TRANSPARENT PASS — Returns the gate to a transparent pass so Threshold and envelope behavior can be judged from the source. Stereo variant: keep the linked center intact and audition width in the full mix.

VOCAL BREATH GUARD [Stereo]

VOCAL BREATH GUARD — Keeps vocal breaths and consonants natural while the guard controls spill and room energy. Stereo variant: keep the linked center intact and audition width in the full mix.

KICK KEY GATE [Stereo]

KICK KEY GATE — Uses the key/duck detector to make kick or sidechain energy the envelope decision. Stereo variant: keep the linked center intact and audition width in the full mix.

TEHUTI DUCK GUARD [Stereo]

TEHUTI DUCK GUARD — Uses the key/duck detector to make kick or sidechain energy the envelope decision. Stereo variant: keep the linked center intact and audition width in the full mix.

KEY + DUCK LOCK [Stereo]

KEY + DUCK LOCK — Uses the key/duck detector to make kick or sidechain energy the envelope decision. Stereo variant: keep the linked center intact and audition width in the full mix.

DRUM TIGHT GUARD [Stereo]

DRUM TIGHT GUARD — Tightens drum spill with Attack/Hold/Release chosen to keep the hit intact. Stereo variant: keep the linked center intact and audition width in the full mix.

MONO WALL HOLD [Mono]

MONO WALL HOLD — Applies the guard to the selected channel layout while preserving the channel-mode decision. Mono variant: collapse the field and use it as a center-focused insert.

DUAL MONO LOCK [Dual Mono]

DUAL MONO LOCK — Applies the guard to the selected channel layout while preserving the channel-mode decision. Dual-mono variant: preserve independent left/right decisions for asymmetric sources.

Meters and visualizers

IN: Main-input RMS energy. Shows the program feeding the gate.

GATE: Current gate passage gain. OPEN is full passage; lower values mean attenuation.

KEY: External sidechain RMS energy. Moves only when a host sidechain is routed.

DUCK: Sidechain-driven gain reduction. More fill means deeper ducking of the main signal.

OUT: Post-gate RMS energy. Compare with IN to judge actual attenuation.

Transfer graph: Threshold, envelope, and Range floor. Shows where the signal opens and how far closure may fall.

Correlation waves: Left/right phase relationship. Gold is coherent, purple is spread, red warns of anti-phase risk.

OTIS

RELEASE	FAMILY	PLACEMENT
v1.0.1	Dynamics / Guard	Insert Safe

3-6-9 macro dynamics processor: Micro Peak controls short events, Meso Density shapes body, and Macro Level governs the long envelope.

Recommended use: dynamics support; secondary silver mastering-support dot

Customer formats: AU, VST3, Standalone

Primary controls

Micro Peak • Meso Density • Macro Level • Makeup Gain • Gain Match

Factory starting points — source-derived purpose

TRANSPARENT PASS [Stereo]

TRANSPARENT PASS — Returns the three timescales to a transparent pass for judging the source envelope. Stereo variant: keep the linked center intact and audition width in the full mix.

VOCAL LEVELER [Stereo]

VOCAL LEVELER — Lets Micro Peak catch consonant spikes while Meso Density and Macro Level keep the phrase even. Stereo variant: keep the linked center intact and audition width in the full mix.

DIALOG STEADY [Stereo]

DIALOG STEADY — Lets Micro Peak catch consonant spikes while Meso Density and Macro Level keep the phrase even. Stereo variant: keep the linked center intact and audition width in the full mix.

DRUM BUS CATCH [Stereo]

DRUM BUS CATCH — Catches drum peaks without erasing the hit; use Meso Density only as the bus settles. Stereo variant: keep the linked center intact and audition width in the full mix.

MIX BUS GLUE [Stereo]

MIX BUS GLUE — Applies gentle multi-timescale glue to a bus; keep Gain Match independent of this preset. Stereo variant: keep the linked center intact and audition width in the full mix.

TRANSIENT GUARD [Stereo]

TRANSIENT GUARD — Favors Micro Peak control and leaves the phrase-level Macro lane more open. Stereo variant: keep the linked center intact and audition width in the full mix.

MONO LEVEL HOLD [Mono]

MONO LEVEL HOLD — Uses the OTIS leveler in the selected channel layout; compare both channels at matched output. Mono variant: collapse the field and use it as a center-focused insert.

DUAL MONO CONTROL [Dual]

DUAL MONO CONTROL — Uses the OTIS leveler in the selected channel layout; compare both channels at matched output. Dual variant: keep channel decisions independent when the source is asymmetric.

Meters and visualizers

INPUT: Input peak in dB. Confirms level feeding all three time scales.

RESPONSE: Strongest active 3/6/9 reduction. Shows the greatest current reduction across Micro, Meso, or Macro.

OUTPUT: Output peak in dB. Use with INPUT and Gain Match for fair comparison.

3 / Micro activity: Fast transient reduction. Responds to short peaks and front edges.

6 / Meso activity: Body and phrase-density reduction. Responds to medium-duration energy.

9 / Macro activity: Long-envelope reduction. Responds to sustained level movement.

DeBo

RELEASE	FAMILY	PLACEMENT
v3.6.9	Dynamics / Guard	Insert Safe

Pressure-activated dynamics processor with intentional aggressive Drive excitation, pressure-dependent density, controlled Maximize gain, and ceiling containment. DEBO Output controls delivery after the drive/pressure stage, so deliberate distortion can remain while output is reduced. In the DEBO -> DEPTH_BOOST_PRO hybrid, DEBO creates and controls character first; Depth Boost Pro then places it through DIH Field State and can apply optional post-field Spatial Gain reduction.

Recommended use: pressure-activated dynamics, aggressive drive, density, and controlled output

Customer formats: AU, VST3, Standalone

Primary controls

Power • Flower of Life • Gain Match • Input • Drive • Maximize • Depth • Clarity • Output

Factory starting points — source-derived purpose

NO BRICKS [Stereo]

NO BRICKS — Open DEBO density with zero maximize gain: add Drive/Depth/Clarity while explicitly avoiding a brick-wall loudness target. Factory recipe: Drive 56%, Maximize Db 0 dB, Depth 52%, Clarity 58%. Stereo variant: keep the linked center intact and audition width in the full mix.

VOCAL HOLD [Stereo]

VOCAL HOLD — A vocal containment recipe with moderate Drive/Depth and only a small maximize lift, keeping the phrase stable without flattening it. Factory recipe: Drive 58%, Maximize Db 0.8 dB, Depth 60%, Clarity 46%. Stereo variant: keep the linked center intact and audition width in the full mix.

BRICK TAP [Stereo]

BRICK TAP — A measured first touch of maximize pressure for a source that needs forwardness but still has room to breathe. Factory recipe: Drive 58%, Maximize Db 0.5 dB, Depth 54%, Clarity 50%. Stereo variant: keep the linked center intact and audition width in the full mix.

WALL PRESSURE [Stereo]

WALL PRESSURE — Raises pressure and depth for a denser bus; use it when the mix needs a firmer wall, then check the vocal and kick. Factory recipe: Drive 60%, Maximize Db 0.8 dB, Depth 58%, Clarity 50%. Stereo variant: keep the linked center intact and audition width in the full mix.

SHOULDER CHECK [Stereo]

SHOULDER CHECK — A mid-strength density check that tests whether the arrangement can carry more edge without losing clarity. Factory recipe: Drive 62%, Maximize Db 1.1 dB, Depth 62%, Clarity 50%. Stereo variant: keep the linked center intact and audition width in the full mix.

NO SCISSORS [Stereo]

NO SCISSORS — Higher Drive/Depth with moderate maximize keeps peaks from feeling sharply clipped while the body becomes denser. Factory recipe: Drive 64%, Maximize Db 1.4 dB, Depth 66%, Clarity 48%. Stereo variant: keep the linked center intact and audition width in the full mix.

BREAKTHROUGH [Stereo]

BREAKTHROUGH — A strong forward push for a chorus or impact section; reduce Maximize if the transients begin to sound cut off. Factory recipe: Drive 66%, Maximize Db 1.8 dB, Depth 70%, Clarity 46%. Stereo variant: keep the linked center intact and audition width in the full mix.

RED LINE WATCH [Stereo]

RED LINE WATCH — The most assertive DEBO recipe: use it as a translation stress test or special-effect push, not as the default master. Factory recipe: Drive 68%, Maximize Db 2.2 dB, Depth 74%, Clarity 44%. Stereo variant: keep the linked center intact and audition width in the full mix.

PHI GUARD [Stereo]

PHI GUARD — Depth is set to the canonical Phi-derived guard point while maximize stays at zero; use it for controlled density without loudness chasing. Factory recipe: Drive 62%, Maximize Db 0 dB, Depth 81%, Clarity 48%. Stereo variant: keep the linked center intact and audition width in the full mix.

VOCAL ANCHOR [Stereo]

VOCAL ANCHOR — Use it to add pressure and forward motion without a brick-wall default: the recipes move from open containment to deliberate loudness support, with Clarity preserving the important edge. Use this DEBO program as a controlled starting recipe for "VOCAL ANCHOR"; adjust the exposed processor controls in small, level-matched moves and keep the source role named by the preset in view. Factory recipe: Drive 59%, Maximize Db 0.6 dB, Depth 62%, Clarity 42%. Stereo variant: keep the linked center intact and audition width in the full mix.

DRUM REINFORCE [Stereo]

DRUM REINFORCE — Use it to add pressure and forward motion without a brick-wall default: the recipes move from open containment to deliberate loudness support, with Clarity preserving the important edge. Use this DEBO program as a controlled starting recipe for "DRUM REINFORCE"; adjust the exposed processor controls in small, level-matched moves and keep the source role named by the preset in view. Factory recipe: Drive 64%, Maximize Db 1 dB, Depth 55%, Clarity 30%. Stereo variant: keep the linked center intact and audition width in the full mix.

MIX BUS SETTLE [Stereo]

MIX BUS SETTLE — Use it to add pressure and forward motion without a brick-wall default: the recipes move from open containment to deliberate

loudness support, with Clarity preserving the important edge. Use this DEBO program as a controlled starting recipe for "MIX BUS SETTLE"; adjust the exposed processor controls in small, level-matched moves and keep the source role named by the preset in view. Factory recipe: Drive 60%, Maximize Db 0.4 dB, Depth 52%, Clarity 38%. Stereo variant: keep the linked center intact and audition width in the full mix.

PARALLEL BREACH [Stereo]

PARALLEL BREACH — Use it to add pressure and forward motion without a brick-wall default: the recipes move from open containment to deliberate loudness support, with Clarity preserving the important edge. Use this DEBO program as a controlled starting recipe for "PARALLEL BREACH"; adjust the exposed processor controls in small, level-matched moves and keep the source role named by the preset in view. Factory recipe: Drive 68%, Maximize Db 2 dB, Depth 70%, Clarity 40%. Stereo variant: keep the linked center intact and audition width in the full mix.

MASTER FIELD [Stereo]

MASTER FIELD — Use it to add pressure and forward motion without a brick-wall default: the recipes move from open containment to deliberate loudness support, with Clarity preserving the important edge. Use this DEBO program as a controlled starting recipe for "MASTER FIELD"; adjust the exposed processor controls in small, level-matched moves and keep the source role named by the preset in view. Factory recipe: Drive 62%, Maximize Db 0.5 dB, Depth 58%, Clarity 34%. Stereo variant: keep the linked center intact and audition width in the full mix.

Meters and visualizers

RMS: Sustained signal body. Shows average energy driving the pressure model.

GUARD PRESSURE: Combined density/containment demand. Higher values mean DEBO is working harder.

PEAK: Fast peak relative to ceiling. Approaching the top warns of limited remaining space.

GOVERNOR: Gain held back by protection. More activity means stronger safety containment.

Pressure window / face: RMS-driven pressure stage. The visual advances with real pressure; red is the ceiling warning state.

LookOut

RELEASE	FAMILY	PLACEMENT
v1.0.1	Dynamics / Guard	Insert Safe

Dual-envelope transient/sustain shaper. Attack and Sustain directly move the level of the transient and sustain portions of the signal, up to +/-18 dB each, ahead of the DIH tone-color stage. Its Eye of Heru state also gives live advisory guidance on transient/sustain balance while it shapes.

Recommended use: dual-envelope transient/sustain shaper; Attack/Sustain directly move transient and sustain gain up to +/-18dB; Eye of Heru advisory guidance is secondary, not the primary function; cyan primary dot with green observation and silver mastering-support dots

Customer formats: AU, VST3, Standalone

Primary controls

Power • Attack • Sustain • Gain Match

Factory starting points — source-derived purpose

NEUTRAL SENTINEL [Stereo]
NEUTRAL SENTINEL — Attack and Sustain at unity: an observation reset for hearing the source before choosing peak or tail emphasis. Factory recipe: Attack 0%, Sustain 0%. Stereo variant: keep the linked center intact and audition width in the full mix.

VOCAL FRONT GUARD
VOCAL FRONT GUARD — Moderate Attack with a shorter Sustain watches vocal fronts while leaving phrase movement intact. Factory recipe: Attack 46, Sustain 18.

DRUM SNAP LOCK
DRUM SNAP LOCK — Fast Attack and negative Sustain protect the drum transient and stop the tail from smearing the next hit. Factory recipe: Attack 88, Sustain -64.

KICK BODY ANCHOR
KICK BODY ANCHOR — Negative Attack with strong positive Sustain favors the kick body and low envelope instead of the initial click. Factory recipe: Attack -62, Sustain 90.

PERCUSSION EDGE
PERCUSSION EDGE — High Attack and negative Sustain isolate percussion edges for crisp placement without a broad level lift. Factory recipe: Attack 74, Sustain -86.

ROOM TAIL WATCH
ROOM TAIL WATCH — Negative Attack with positive Sustain keeps an ear on room decay and tail build-up rather than only the first hit. Factory recipe: Attack -78, Sustain 72.

MIX BUS COMPOSURE
MIX BUS COMPOSURE — Moderate positive Attack/Sustain observes the bus as a whole and keeps movement calm without hard clamping. Factory recipe: Attack 28, Sustain 48.

FINAL PEAK SENTINEL
FINAL PEAK SENTINEL — High Attack with lightly reduced Sustain is a final peak watch; use it to find events, not to replace a limiter. Factory recipe: Attack 62, Sustain -18.

Meters and visualizers

Transient: Detected front-edge energy. Use to judge whether Attack is emphasizing or restraining hits.

Sustain: Detected body and tail energy. Use to judge Sustain changes to ring, room, and body.

Alert: Potential transient/sustain imbalance. Higher values suggest the balance needs attention.

Miss: Underrepresented event energy. Indicates material that may be disappearing.

Stress: Over-concentrated envelope pressure. Reduce shaping intensity when stress remains high.

Composure: Stable transient/sustain balance. Higher is calmer and more controlled.

Eye of Heru: Combined advisory state. It reports balance; it does not move controls automatically.