

# DIMENSIONAL IMPACT MOVE

## Dimension, width, impact, and motion

Shape depth, front-to-back position, movement, and spatial delay as a coordinated field.

**Included products:** Depth Impact Hybrid X, PARALLAX, NSR

**Recommended route:** Width/depth route: Depth Impact Hybrid X -> Parallax -> NSR.

**Family preset law:** Factory presets describe musical intent and expose the useful range of the plugin. They do not change protected Input, Mix, Output, Power, or final ceiling controls unless the plugin's explicit canon requires it. Cathedral and SacredVerb retain their protected preset behavior. Preset changes must remain clickless.

# Depth Impact Hybrid X



Six-mode spatial field for clarity, depth, low bloom, front push, hybrid pressure, fold, freeze, and source-to-horizon movement.

**Preferred placement:** Insert Safe. Use directly on a source or instrument channel and bypass-match before committing.

## Core controls

- Output
- Hybrid X Mode
- Horizon Fold
- Event Freeze
- Echo
- CPU Saver
- Bypass
- Gain Match
- spectralClarity

## Meter and visualizer guide

These displays observe audio or processing state. They do not move controls unless the product description explicitly says otherwise.

| Display                         | What it measures                        | How to read it                                                 |
|---------------------------------|-----------------------------------------|----------------------------------------------------------------|
| RMS FIELD                       | Overall sustained field energy          | Shows the body of the dimensional result.                      |
| LEFT / RIGHT                    | Per-channel output activity             | Use to spot unintended channel imbalance.                      |
| HORIZON                         | Depth and distant-field contribution    | Higher values indicate stronger rearward space.                |
| EVENT                           | Transient/front-push contribution       | Higher values indicate stronger forward impact.                |
| Immersion / Foundation / Motion | Three-part dimensional activity summary | Read together to distinguish depth, low support, and movement. |

Additional controls are mapped in the family technical manual.

## Working method

Load a purpose-matched preset or begin from reset, bypass-match the result, then move one control at a time. Presets are starting points; protected gain and final output remain user decisions unless the plugin canon explicitly states otherwise.

# PARALLAX



Bus-preferred width and depth field with focus, spread, axis core, link, mix, and output control.

**Preferred placement:** Bus Preferred. Use on a family, parallel, or purpose-built bus; audition on an insert only when the source calls for it.

## Core controls

- Width
- Depth
- Focus
- Stereo Spread
- Axis Core
- Mix
- Output
- Field Link
- Power

## Meter and visualizer guide

These displays observe audio or processing state. They do not move controls unless the product description explicitly says otherwise.

| Display          | What it measures                            | How to read it                                             |
|------------------|---------------------------------------------|------------------------------------------------------------|
| INPUT / OUTPUT   | Live pre/post level                         | Use for level matching around the width field.             |
| Field visualizer | Width, depth, focus, spread, and axis state | Motion shows spatial behavior; it is not a frequency plot. |

Additional controls are mapped in the family technical manual.

## Current factory programs detected

Deep Space; Wormhole; Nebula Shift; Stellar Grid; Planetary Orbits; Light Speed; Quantum Field; Dimensional Gate; Gravity Well; Ascension

## Working method

Load a purpose-matched preset or begin from reset, bypass-match the result, then move one control at a time. Presets are starting points; protected gain and final output remain user decisions unless the plugin canon explicitly states otherwise.

# NSR



Phi-ratio spatial delay and movement field combining travel, microphase, air, anchor, spread, time delay, flange, and mix.

**Preferred placement:** Bus Preferred. Use on a family, parallel, or purpose-built bus; audition on an insert only when the source calls for it.

## Core controls

- Gain Match
- travel
- microphase
- air
- anchor
- spread
- field
- timeDelay
- flange

## Meter and visualizer guide

These displays observe audio or processing state. They do not move controls unless the product description explicitly says otherwise.

| Display              | What it measures                        | How to read it                                                             |
|----------------------|-----------------------------------------|----------------------------------------------------------------------------|
| SPECTRUM             | Energy across displayed frequency bands | Shows tonal distribution of the current signal.                            |
| CORRELATION          | Left/right phase similarity             | +1 is mono-coherent, 0 is decorrelated, negative values risk cancellation. |
| L / R                | Channel activity                        | Use to detect imbalance before and after the field.                        |
| PHI FIELD VIEW       | Combined spatial-field intensity        | Shows overall activity of the responder.                                   |
| STEREO FIELD / WIDTH | Side-to-mid spatial width               | Check correlation whenever width stays high.                               |
| FIELD ACTIVITY       | Wet spatial-path energy                 | Shows how much processed field is actually active.                         |
| DRY / WET waveform   | Recent source and processed traces      | Compare timing, shape, and motion between paths.                           |
| Signal Path          | Activity at each processing stage       | Locates where energy enters, moves, feeds back, and is contained.          |

Additional controls are mapped in the family technical manual.

## Working method

Load a purpose-matched preset or begin from reset, bypass-match the result, then move one control at a time. Presets are starting points; protected gain and final output remain user decisions unless the plugin canon explicitly states otherwise.