

DIHWorld Audio

Meter & Visualizer Reference

What each diagnostic display measures and how to use it

This reference covers nonstandard meters and reactive visualizers. Input, output, peak, RMS, gain reduction, correlation, and crest are defined in context. Control-state graphics are explicitly identified so they are not mistaken for calibrated analyzers.

Reading law: meters observe; they do not improve audio by themselves. Compare before and after at matched level, check mono when width or correlation is involved, and treat warning/advisor displays as evidence to investigate rather than automatic commands.

Vocal Mic Source

Aegis Nova

Display	What it measures	How to read it
INPUT	Incoming peak activity	Confirms source level reaching the shield.
NOVA	Detected plosive/sibilant activity	More light means stronger shield intervention.

Dynamics Guard

ANUBIS

Display	What it measures	How to read it
IN	Main-input RMS energy	Shows the program feeding the gate.
GATE	Current gate passage gain	OPEN is full passage; lower values mean attenuation.
KEY	External sidechain RMS energy	Moves only when a host sidechain is routed.
DUCK	Sidechain-driven gain reduction	More fill means deeper ducking of the main signal.
OUT	Post-gate RMS energy	Compare with IN to judge actual attenuation.
Transfer graph	Threshold, envelope, and Range floor	Shows where the signal opens and how far closure may fall.
Correlation waves	Left/right phase relationship	Gold is coherent, purple is spread, red warns of anti-phase risk.

OTIS

Display	What it measures	How to read it
INPUT	Input peak in dB	Confirms level feeding all three time scales.
RESPONSE	Strongest active 3/6/9 reduction	Shows the greatest current reduction across Micro, Meso, or Macro.
OUTPUT	Output peak in dB	Use with INPUT and Gain Match for fair comparison.
3 / Micro activity	Fast transient reduction	Responds to short peaks and front edges.
6 / Meso activity	Body and phrase-density reduction	Responds to medium-duration energy.
9 / Macro activity	Long-envelope reduction	Responds to sustained level movement.

DEBO

Display	What it measures	How to read it
RMS	Sustained signal body	Shows average energy driving the pressure model.
GUARD PRESSURE	Combined density/containment demand	Higher values mean DEBO is working harder.
PEAK	Fast peak relative to ceiling	Approaching the top warns of limited remaining space.
GOVERNOR	Gain held back by protection	More activity means stronger safety containment.
Pressure window / face	RMS-driven pressure stage	The visual advances with real pressure; red is the ceiling warning state.

LOOKOUT

Display	What it measures	How to read it
Transient	Detected front-edge energy	Use to judge whether Attack is emphasizing or restraining hits.
Sustain	Detected body and tail energy	Use to judge Sustain changes to ring, room, and body.
Alert	Potential transient/sustain imbalance	Higher values suggest the balance needs attention.
Miss	Underrepresented event energy	Indicates material that may be disappearing.

Display	What it measures	How to read it
Stress	Over-concentrated envelope pressure	Reduce shaping intensity when stress remains high.
Composure	Stable transient/sustain balance	Higher is calmer and more controlled.
Eye of Heru	Combined advisory state	It reports balance; it does not move controls automatically.

Bass Low End

MARIANA

Display	What it measures	How to read it
DEPTH	Current trench-depth control state	Higher values extend the added low-end field deeper.
PRESSURE	Current sub-pressure control state	Higher values add more low-frequency pressure.
FOUNDATION	Current sustained-foundation control state	Higher values add more continuous low-end support.
IMPACT	Current kick-definition control state	Higher values preserve more front-edge definition.
LOW ENERGY	Detected low-frequency program energy	Shows the bass energy entering MARIANA's field.
BEDROCK	Detected sustained foundation energy	Shows the slower body underneath transient bass events.
KEY	Detected 35-160 Hz sidechain energy	Moves only when KEY is enabled and a host sidechain is routed.
DUCK GR	Reduction of MARIANA's added low-end layer	More activity means the external key is clearing more generated pressure; dry bass remains audible.

MONOLITH

Display	What it measures	How to read it
INPUT / OUTPUT	Live pre/post level	Use for bypass and level matching.
IMPACT	Low-end transient activity	Shows the punch component being produced.
WEIGHT	Sustained low-frequency body	Shows foundation rather than peak attack.
RESONANCE	Active resonant low-end energy	Persistent high readings warn of ringing.
REVERSE	Reverse-motion contribution	Shows how strongly the reverse path is active.
Monolith field	Combined low-end activity map	Reactive summary, not a spectrum analyzer.
KEY	Detected 40-180 Hz sidechain energy	Moves only when KEY is enabled and a host sidechain is routed.
STONE DUCK	Reduction of the added stone/weight layer	The original input impact remains outside this reduction.

Depth Boost Pro

Display	What it measures	How to read it
Touch sphere	Depth field plus live level	Water motion follows field/level activity; sphere position remains the output control.
Spatial field	Depth, field energy, and motion	A reactive placement view, not a calibrated spectrum.

NTRPL

Display	What it measures	How to read it
SOURCE	Original input contribution	Shows how much source survives into the main route.
REWRITE	Generated harmonic-rewrite activity	Shows the newly synthesized low-end material.
ALT OUT	Alternative new-signal output	Always represents the generated signal path.
MAIN	Final blended output	Use against SOURCE for level and blend context.

Display	What it measures	How to read it
Harmonic Rewriter	Live input-to-output contour	Shows source energy changing into rewritten energy.
Rewrite Map	Novelty, chord, interval, contour, motion, space, guard, and mix state	A live process map; it is not a frequency analyzer.
KEY	Detected 35-160 Hz sidechain energy	Moves only when KEY is enabled and a host sidechain is routed.
REWRITE DUCK	Reduction of the generated rewrite layer	The source bass path remains outside this reduction.

Drum Instrument

DIH Drum Morpher

Display	What it measures	How to read it
L / R output	Left and right output activity	Confirms stereo drum output and imbalance.
GOVERNOR	Output containment activity	More activity means protection is holding energy back.
MORPH	Current metamorphosis activity	Shows how strongly the active pads are transforming.
Pad waveform	Loaded sample amplitude over time	Use to identify attacks, tails, and silence in each pad.

BALLPARK

Display	What it measures	How to read it
IN	Input level	Confirms drum energy entering the stadium model.
GR	Gain reduction	Shows active impact containment.
OUT	Output level	Use with IN for level matching.
RMS / PEAK	Body level and fast peak	Their separation describes drum crest and punch.
Ceiling score / hit call	Composite impact, control, and ceiling score	Walk through Home Run describes response intensity, not sports prediction.

DrumKrushGlue

Display	What it measures	How to read it
IMPACT	Detected drum peak activity	Shows hit strength entering the impact path.
BODY	Sustained drum energy	Shows weight carried between hits.
REPAIR	Glue/control activity	Shows how strongly cohesion is correcting the bus.
CEILING	Protected output pressure	Persistent maximum activity means the chain is overdriven.
KEY	Detected 40-180 Hz sidechain energy	Moves only when KEY is enabled and a host sidechain is routed.
POCKET	Reduction of the added weight/glue layer	The original drum path remains outside this reduction.

Color Amp Tape

KHEPRI

Display	What it measures	How to read it
INPUT VU	Ballistic input level	Calibrated to the printed analog VU scale.
OUTPUT VU	Ballistic post-tape level	Compare with INPUT to avoid loudness bias.
Waveform	Recent live output samples	Shows real signal motion, not a decorative animation.
Reels / beetle glow	Tape motion and drive state	Operational feedback; not a calibrated level meter.

Dimensional Impact Move

Depth Impact Hybrid X

Display	What it measures	How to read it
RMS FIELD	Overall sustained field energy	Shows the body of the dimensional result.
LEFT / RIGHT	Per-channel output activity	Use to spot unintended channel imbalance.
HORIZON	Depth and distant-field contribution	Higher values indicate stronger rearward space.
EVENT	Transient/front-push contribution	Higher values indicate stronger forward impact.
Immersion / Foundation / Motion	Three-part dimensional activity summary	Read together to distinguish depth, low support, and movement.

PARALLAX

Display	What it measures	How to read it
INPUT / OUTPUT	Live pre/post level	Use for level matching around the width field.
Field visualizer	Width, depth, focus, spread, and axis state	Motion shows spatial behavior; it is not a frequency plot.

NSR

Display	What it measures	How to read it
SPECTRUM	Energy across displayed frequency bands	Shows tonal distribution of the current signal.
CORRELATION	Left/right phase similarity	+1 is mono-coherent, 0 is decorrelated, negative values risk cancellation.
L / R	Channel activity	Use to detect imbalance before and after the field.
PHI FIELD VIEW	Combined spatial-field intensity	Shows overall activity of the responder.
STEREO FIELD / WIDTH	Side-to-mid spatial width	Check correlation whenever width stays high.
FIELD ACTIVITY	Wet spatial-path energy	Shows how much processed field is actually active.
DRY / WET waveform	Recent source and processed traces	Compare timing, shape, and motion between paths.
Signal Path	Activity at each processing stage	Locates where energy enters, moves, feeds back, and is contained.

Fx Spatial

NTRSTLLR

Display	What it measures	How to read it
INPUT / OUTPUT	Weighted peak-plus-RMS level	Use for level matching around the spatial return.
TONE RESPONSE	Current low-to-high response shape	Shows tonal contour, not a mastering EQ recommendation.
WORMHOLE	Delay/warp-path energy	Shows active wormhole return strength.
NEBULA	Portal/diffusion-path energy	Shows active nebula tail strength.
SINGULARITY	Axis and pull concentration	Higher values indicate stronger inward focus.
PHI FIELD OBSERVATION	Combined macro-control activity	A spatial-state summary rather than loudness.
PHI ECHO / DELAY FIELD	Delay taps, orbit, and return motion	Use to understand tail movement and density.

Cathedral

Display	What it measures	How to read it
ENERGY	Current chamber RMS in dB	Shows how strongly the room is being excited.
DIFFUSION	3-6-9 node density	Higher values produce a denser, smoother tail.
WIDTH	Node density multiplied by wet mix	Shows audible spatial spread, not dry-source width.
RT60	Estimated mid-band decay time	Seconds required for the modeled room to decay by 60 dB.
ROOM RESONANCE	Modeled low/mid/high response	Use to identify room emphasis before printing.

SacredVerb

Display	What it measures	How to read it
Seven Hathor meters	Energy at enabled Solfeggio nodes	Each column shows its resonant band activity and peak hold.
Output meter	Current reverb-output peak	Use to keep the return controlled and level matched.
3-6-9 modulator	Active modulation/pattern state	Shows motion settings; it is not a loudness meter.

Harmonics Pitch

THOTH

Display	What it measures	How to read it
Spectrum bands	Live energy in each displayed EQ region	Use to see where harmonic energy is accumulating.
Shelf curves	Current low/high shelf response	These show the selected EQ shape, not measured level.
IN / OUT	Pre/post peak activity	Use for level-fair harmonic decisions.

TEHUTI

Display	What it measures	How to read it
INPUT	Main-program peak activity	Shows the signal being ducked.
SIDECHAIN SEND	External sidechain envelope	Confirms that the host sidechain is present.
LOW GR	Reduction below 162 Hz	Shows low-band ducking driven by the sidechain.
MID GR	Reduction from 162 Hz to 1.62 kHz	Shows mid-band ducking driven by the sidechain.
HIGH GR	Reduction above 1.62 kHz	Shows high-band ducking driven by the sidechain.
Duck curves	Expected reduction versus sidechain energy	The live dot shows the current operating point.
History	Recent sidechain and reduction motion	Use to judge pumping and release behavior.

Creative Transform

SlotMachine

Display	What it measures	How to read it
INPUT	Input peak	Confirms level entering the three chambers.
OUTPUT	Output peak	Use for level matching.
RMS	Average program body	Shows sustained density.
CREST	Peak-to-RMS relationship	Higher values mean sharper transients; lower values mean denser material.

Archaeologist X

Display	What it measures	How to read it
INPUT / OUTPUT	Live pre/post peak	Use for bypass and level matching.
EXCAVATION	Low/deep recovery activity	Shows energy being uncovered by excavation.
RECOVERY	Recovered-source contribution	Shows how much repaired material is active.
HARMONIC	Extracted harmonic activity	Shows reconstructed tonal information.
FORENSIC	Forensic layer/gate activity	Shows the selective analysis path at work.
Observation Field	Combined four-process activity	A process summary, not a spectrum.

SERQET

Display	What it measures	How to read it
RMS WIDTH	Input RMS feeding the width field	Shows source energy available for widening.
PRISM WIDTH	Measured side-field width	Higher values indicate a broader stereo prism.
OUTPUT FIELD	Post-process RMS energy	Use with RMS WIDTH for level context.
Prism visualizer	Width, motion, focus, and output state	The polygon is a spatial-state map, not a loudness target.

Mastering Core

ANKH

Display	What it measures	How to read it
INPUT LEVEL	Peak level entering ANKH	Use to verify healthy mastering-chain entry.
GAIN REDUCTION	Current optical/limiter attenuation	More fill means more level is being removed.
OUTPUT LEVEL	Peak level after containment	Compare with Input for level-fair decisions.

SPHYNX

Display	What it measures	How to read it
INPUT PEAK	Peak entering calibration	Confirms available headroom before normalization.
PROGRAM RMS	Average program energy	Use to understand body level, not final delivery loudness alone.
AUTO TRIM	Gain correction calculated by SPHYNX	Center is 0 dB; left cuts and right boosts.
OUTPUT PEAK	Peak after normalization	Verify headroom after calibration.
Crest / headroom	Peak-to-RMS and remaining space	Use together to avoid flattening transient structure.

MAAT

Display	What it measures	How to read it
TRUTH	Composite tonal/phase balance score	Higher values mean the current foundation/air balance is closer to the intended field.
INPUT / OUTPUT	Live pre/post level	Use for level matching.
FOUNDATION	Low-frequency contribution	Shows active foundation energy.
AIR	Upper-frequency contribution	Shows active air energy.

Horizon X

Display	What it measures	How to read it
LIVE SIGNAL	Per-channel input RMS on a -60 to 0 dBFS scale	Shows program energy entering the finalizer.
FIELD STATE	Combined Horizon/Event processing state	A process-state visualization, not a delivery-loudness meter.
OUTPUT LEVEL	Post-finalizer level on a -60 to 0 dBFS scale	Use with LIVE SIGNAL for level-fair review.

Master Field

IMHOTEP

Display	What it measures	How to read it
INPUT PEAK	Peak entering the master builder	Confirms headroom before macro shaping.
FIELD ACTIVITY	Combined foundation, architecture, dimension, and finish activity	Shows how strongly the macro field is engaged.
OUTPUT / PHI CEILING	Output level relative to containment	Persistent maximum readings mean less available headroom.

Utility Observation

SESHAT

Display	What it measures	How to read it
LUFS / BODY READ	Short-window perceptual loudness	Use for loudness context, not as the only delivery decision.
LEFT INPUT / RIGHT OUTPUT	Peak, RMS body, impact, and held peak	Shows entry and exit behavior; Hold Peaks retains the highest marker.
CORRELATION / MONO SAFETY	Left/right phase relationship	+1 is coherent, 0 is wide/uncorrelated, negative values risk cancellation.
SOLFEGGIO FREQUENCIES	Energy near the seven displayed resonant bands	Shows tonal concentration around 396 through 963 Hz.
IMPACT	Fast peak relative to the canon ceiling	Higher means stronger transient force.
FIELD	Body RMS plus stereo-side pressure	Higher means denser sustained spatial load.
MOMENTUM	Change in impact plus transient shape	Higher means faster, more active movement.
PHI ALIGNMENT	Proximity to DIH golden-ratio checkpoints	Higher means field pressure sits nearer a PHI reference point.
INTEGRITY	Similarity between impact and field pressure	Higher means transients and body remain proportionate.
CROWN	Weighted combined observation score	Summarizes impact, field, momentum, alignment, and integrity.
MOON	Transient shape plus momentum	Higher means stronger forward or launching behavior.
HF RISK	High-frequency energy imbalance	Higher values warn of potential harshness.
PHASE RISK	Correlation and side-energy danger	Higher values warn of mono cancellation.
LEVEL RISK	Peak/ceiling and transient danger	Higher values warn of insufficient headroom.
COMFORT	Alignment, integrity, and low-risk balance	Higher values indicate a more stable field.
ADVISOR	Combined risk recommendation	A diagnostic suggestion; it does not change audio.
REEL 1 - Impact	Transient-force rank	First reel; 396 is low and MOON is highest.
REEL 2 - Field	Sustained spatial-pressure rank	Second reel; numbers are symbolic stages, not Hz.
REEL 3 - Momentum	Motion/transient-change rank	Third reel; higher stages mean more movement.
REEL 4 - Alignment	PHI-alignment rank	Fourth reel; higher stages mean closer alignment.
REEL 5 - Moon	Forward-propulsion rank	Fifth reel; higher stages mean stronger launch.