

DIHWorld Audio Dot Protocol User Guide

Current: 2026-08-01
Authority: CURRENT_FAMILY_AUTHORITY.md, SMART_POSITION_CANON.md, ROUTING_PLACEMENT_CANON.md

Purpose

DIHWorld plugin interfaces use compact dots instead of long placement dialog. The dots let users scan family role, secondary function, and placement comfort without covering the artwork, meters, knobs, or preset shell.

Dot Colors

Gold	Vocal-first / source tone
Blue	Bus / group / parallel placement
Silver	Mastering / polish
Purple	Spatial / placement / depth
Red-orange	Saturation / color / amp / tape
Green	Analysis / metering / advisor
White	Utility / safety / protection
Brown / low-gold	Bass / low-end / foundation
Cyan	Dynamics / transient / guard

Dot States

Bright solid/glow	Properly placed, or the current signal confirms the role.
Dim	Role is available, but inactive or not confirmed by the current placement.
Slow pulse	Better placement or secondary role suggested.
Flashing/warning flicker	Risk detected: clipping, ringing, harshness, phase instability, excessive spread, or wrong placement.

Reading A Plugin Header

- The primary dot shows the plugin family.
- Secondary dots show useful alternate roles.
- A blue dot means bus, group, aux return, or parallel support.
- Bright means the current use fits.
- Dim means the role is present but not active.
- Pulse or flashing means check placement, gain, or routing before printing.

UI Law

No long Smart Position dialog should cover the background image. No placement text belongs in the bottom-right back-office/footer area. If text is needed, use the manual, tooltip, routing sheet, or a small status line outside the artwork.

User Examples

- DrumKrushGlue: red-orange primary with cyan dynamics support and blue bus/parallel support.

- MAAT: silver mastering identity with green observation behavior.
- Parallax and NSR: purple dimensional identity with blue bus/parallel support.
- Seshat: green observation only; it advises but does not alter audio.