

1. SOC Tasks	2
2. Threat intelligence based ransomware analysis reports	4
3. TH Reports	5
4. VPN brute force protection ASA threat detection	6
5. SIEM Log sources deletion process	7
6. SIEM parsing activity process	8
7. Threat Hunting Process	9
8. Threat intelligence based ransomware analysis process	10
9. SOC L1 FMC Immediate Blockage	11
10. VPN Blockage Automation	13
11. Incidents Follow-up integration/configuration	15
12. SOAR playbooks summary	16
13. Incident handling guide	18
14. Incident manual actions guide	29
15. Qradar certificate renewal procedure	32
16. SOC_L1_FMC_Immediate_Blacklisting technical guide	34
17. SOC onboarding	36

SOC Tasks

Regular tasks

Daily tasks

- Incidents handling
- Risk IOCs blocking ([Risk IOCs blocking process](#))
- Jira SOC and SIEM tickets (SOC project <https://atlassian.hbtf.com/jira/browse/SOC-19?jql=project%20%3D%20%2210600%22>) (SIEM: <https://atlassian.hbtf.com/jira/issues/?filter=14705>)

Weekly tasks

- Incidents follow-up ([Incidents Follow-up Process](#), [Incidents Follow-up integration/configuration](#))
- SIEM log sources coverage ([SIEM Log sources coverage process](#))
- SIEM updates ([SIEM auto and manual apps update >> SIEM auto and manual apps update history](#))

Monthly tasks

- Threat hunting activity > New rules if applicable ([Threat Hunting Process >> TH Reports](#))
- Empty siem group "To be deleted", disable reported retired servers and add to the same group ([SIEM Log sources deletion process](#)) - 25th
- Test use cases review ([New rules/use-cases test process](#))
- Team's performance report (>> [Team's performance reports](#))
- SOC L1 monthly report (>> [SOC L1 monthly reports](#))
- Threat intelligence based ransomware analysis ([Threat intelligence based ransomware analysis process >> Threat intelligence based ransomware analysis reports](#))

By quarterly tasks (3,6,9,12)

- Users review on all systems ([Users review process >> Users review history](#))
- Systems regular check ([Systems regular check process >> Systems regular check history](#))
- SIEM routing rules review

Semiannual tasks(6,12)

- Check and update all confluence documentations under "SOC"
- Systems upgrade if available
- SOAR apps updates check
- SIEM parsing activity ([SIEM parsing activity process](#))
- Active incidents review ([Active incidents review process](#))
- SOC L1 effectiveness assessment ([SOC L1 effectiveness assessment process >> SOC L1 effectiveness history](#))
- Data completeness process/Telemetry/Logging process
- Rule completeness process (>> [Rules coverage](#))

Yearly tasks (12)

- SIEM licenses expansion and consumption study (Aug)
- Budget for next year study
- Certificates renewal
- Service accounts password reset.
- SIEM log sources gap assessment

+++++

Regular tasks tracking sheet:

https://hbtf.sharepoint.com/:x:/r/sites/HBTF-SOCIR/_layouts/15/Doc.aspx?sourcedoc=%7B54f977e5-2ed3-41c8-b1be-e28b125725eb%7D&action=editnew

+++++

Irregular tasks

Include but not limited to:

- Audit
- Support cases
- New documents
- Red teaming
- Purple teaming
- SIEM rules testing
- New integrations
- New configurations
- Enhancements
- New detection rules
- New playbooks
- New systems
- Use cases review ([Adding new log source/Use Case Requirements Questionnaire](#) > [Use Case Requirements Questionnaire Responses](#))
- SIEM application integration ([SIEM application integration process](#) >> [SIEM application integration status](#))
- Adding/Deleting log sources on demand (If required/New system type: [Adding new log source/Use Case Requirements Questionnaire](#) > [Use Case Requirements Questionnaire Responses](#))
- Other

+++++

Irregular tasks tracking sheet:

https://hbtfs.sharepoint.com/:x:/r/sites/HBTF-SOCIR/_layouts/15/doc2.aspx?sourcedoc=%7B45adef4-47c9-4566-95fd-7bb7b1952496%7D&action=editnew

Threat intelligence based ransomware analysis reports

Threat intelligence based ransomware analysis reports

File	Modified
Microsoft Word Document TI-based ransomware analysis Apr-2026.docx	Apr 12, 2026 by Mohammad aldoulat
Microsoft Word Document APT Analysis Report - netrunner - Apr-2026.docx	Apr 12, 2026 by Mohammad aldoulat
Microsoft Word Document TI-BASED RANSOMWARE ANALYSIS MAY-2026.docx	May 13, 2026 by Abdelrahman Diknash
Microsoft Word Document APT ANALYSIS REPORT – EVEREST – MAY-2026.docx	May 13, 2026 by Abdelrahman Diknash

Drag and drop to upload or [browse for files](#)
[Download All](#)

TH Reports

Threat hunting reports.

File name: <yyyy-mm-dd> - TH - Report - <user_code> - <TTPs>

Summary:

TTPs	Related rules IDs	User code	Report
T1059.006	MS-DFE-0010, MS-DFE-0011, MS-DFE-0012	t1144	https://atlassian.hbtf.com/wiki/download/attachments/73793759/2025-09-07%20-%20TH%20-%20Report%20-%20t1144%20-%20T1059.006.docx?api=v2
T1569.002	MS-DFE-0015, MS-DFE-0016	t1199	https://atlassian.hbtf.com/wiki/download/attachments/73793759/2025-09-07%20TH%20-%20Report%20-%20T1199%20-%20T1569.002.docx?api=v2
T1059.001	MS-DFE-0002, MS-DFE-0013, MS-DFE-0014	e5330	
T1071	MS-DFE-0018, MS-DFE-0019, MS-DFE-0020	T1199	2025-10-07 TH - Report - T1199 - T1071.docx
T1070.003	MS-DFE-0022-HBTF Delete/Disable Powershell Logs, MS-DFE-0023-HBTF Delete/Disable Linux Terminal Logs	T3595	2026-02-24 TH - Report - T3595 - T1070.003 .docx
T1518.001	MS-DFE-0024-HBTF Defense Evasion: Security Tools Discovery	T1199	2026-02-28 TH - Report - T1199 - T1518.001.docx
T1070.005	MS-DFE-0025-HBTF Network Share Connection Removal	T3595	2026-03-29 TH - Report - T3595 - T1070.005 .docx
T1041	MS-DFE-0026-HBTF Possible Exfiltration Over C2 Channel	e5330	
T1059.007	MS-DFE-0027-HBTF Suspicious JavaScript Execution	T1199	
T1070.006	MS-DFE-0028-HBTF Suspicious File Timestamp Manipulation via Specialized Utilities or PowerShell	T3595	2026-05-31 TH - Report - T3595 - T1070.006.docx

File	Modified
Microsoft Word Document 2025-09-07 - TH - Report - t1144 - T1059.006.docx	Sep 18, 2025 by Mohammad aldoulat
Microsoft Word Document 2025-09-07 TH - Report - T1199 - T1569.002.docx	Sep 18, 2025 by Mohammad aldoulat
Microsoft Word Document 2025-10-07 TH - Report - T1199 - T1071.docx	Nov 19, 2025 by Majdi Bsharah
Microsoft Word Document 2026-02-24 TH - Report - T3595 - T1070.003 .docx	Feb 25, 2026 by Mohammad aldoulat
Microsoft Word Document 2026-02-28 TH - Report - T1199 - T1518.001.docx	Mar 09, 2026 by Majdi Bsharah
Microsoft Word Document 2026-03-29 TH - Report - T3595 - T1070.005 .docx	Apr 26, 2026 by Abdelrahman Diknash
Microsoft Word Document 2026-05-31 TH - Report - T3595 - T1070.006.docx	May 31, 2026 by Abdelrahman Diknash

Drag and drop to upload or [browse for files](#)
[Download All](#)

VPN brute force protection | ASA threat detection

Jordan and Palestine:

event manager applet VPN_BF_EEM


event timer watchdog time 600

action 1 cli command "clear shun"

output none

threat-detection service remote-access-authentication hold-down 10 threshold 4

Bahrain:



Based on the above, any public IP that attempts to authenticate to RA VPN more than **4 failed attempts** within **10 minutes** will be blocked for a maximum of 10 minutes.

SIEM Log sources deletion process

Every month, we receive an email from OA team for retired servers.

Based on this email, we disable the related log sources on SIEM, move them to group "To be deleted".

This group should be emptied on the 25th of each month.

SIEM parsing activity process

Threat Hunting Process

- Choose TTPs from [Threat profile](#).
- Start with the highest priorities (Based on "Usage count" value).
- Check if there are rules covering these TTPs or no. If yes, write down their names.
- Identify the systems/tools required to hunt for the selected TTPs.
- Prepare the required tools.
- Prepare your searches/queries.
- Coordinate with the team and take management approval to proceed.
- Collect the results under (\sms_it_cplx\SecOps\SOC Documents\Threat Hunting) in a new folder with name (<yyyy-mm-dd> - TH - <your-code>).
- Analyze the results.
- Set an action plan based on the results.
- Assess the existing rules covering the same TTPs that you identified previously. Append to the action plan accordingly.
- Confirm if new rules are required to cover these TTPs. Append to the action plan accordingly.
- Start building TH report according to the template ([General report Report Template](#)).
- Discuss the report with the team and management to confirm on the action plan.
- Proceed with the action plan accordingly.
- Once done, document all taken actions in your report.
- Attach the final report to [TH Reports](#).

Frequency: Every 2 weeks


Duration for each activity: 1 Week

Threat intelligence based ransomware analysis process

- On TI system, check latest ransomware attacks targeting our countries and industry
- Perform analysis on involved APTs
- Hunt for existence in the environment
- Block observed IOCs (if any)
- Write analysis report to [Threat intelligence based ransomware analysis reports](#)
- Send an email to CIO and risk team with the analysis, results and actions taken

SOC L1 FMC Immediate Blockage

This document describes the automated workflow for Blocking IPs through Qradar - FMC Integration.



Domain UUID : e276abec-e0f2-11e3-8169-6d9ed49b625f

Object ID JO : 3890A56F-0696-0ed3-0001-232656198820

Object ID Pal : 005056BC-03A7-0ed3-0000-335007538300

Automation Script Details

A Python script bridges the gap between QRadar's intelligence and the Firewalls' enforcement.

- **Path:** /store/scripts/SOC_L1_FMC_Immediate_Blacklist/SOC_L1_FMC_Immediate_Blacklist.py
- **Execution Frequency:** Every 1 minute via Cron.
- **Cron Entry:**
* * * * * /usr/bin/python3 /store/scripts/SOC_L1_FMC_Immediate_Blacklist/SOC_L1_FMC_Immediate_Blacklist.py
>> /store/scripts/SOC_L1_FMC_Immediate_Blacklist/cron_output.log 2>&1

Logic Flow

1. **Fetch Targets:** The script queries the QRadar API to retrieve all IPs currently residing in both reference sets.
2. **Fetch Current State:** The script queries the **Cisco FMC Dynamic Objects** (for both Palestine and Jordan regions) to see which IPs are currently blocked.

3. **Comparison Logic:**
 - **Release List:** IPs present in the FMC blacklist but *no longer* in the QRadar reference sets (TTL expired).
 - **Block List:** IPs present in the QRadar reference sets but *not yet* in the FMC blacklist.
4. **Enforcement:** The script issues API calls to FMC to remove the "Release List" IPs and add the "Block List" IPs.

Logging & Retention

To ensure auditability and troubleshooting, the script maintains detailed logs.

- **Log Directory:** /store/scripts/SOC_L1_FMC_Immediate_Blacklist/Logs
- **Naming Convention:** script_YYYY_MM_DD.txt (A new file is generated daily).
- **Retention Policy:** Logs are kept for **30 days**.
- **Cleanup Cron:**

```
0 0 * * * /usr/bin/find /store/scripts/SOC_L1_FMC_Immediate_Blacklist/Logs/ -name "script_*.txt" -type f -mtime +30 -delete
```




SOC_L1_FMC_Immediate_Blacklist.py

Related documents:

[SOC_L1_FMC_Immediate_Blacklisting technical guide](#)

VPN Blockage Automation

This document describes the automated workflow for detecting VPN brute-force attempts in QRadar and dynamically updating blocklists on Cisco Firepower Management Center (FMC) via a Python integration script.



QRadar Detection Logic

The system utilizes two specific correlation rules to identify suspicious activity based on failed login frequency.

Rule Name	Detection Criteria	Action	Reference Set TTL
Rule 1	8 failures within 3 hours	Add IP to 8_attempts_in_3_hours_list	30 Minutes
Rule 2	12 failures within 6 hours	Add IP to 12_attempts_in_6_hours_list	60 Minutes

Automation Script Details

A Python script bridges the gap between QRadar's intelligence and the Firewalls' enforcement.

- Path:** `/store/scripts/HBTF_VPN_BruteForce.py`
- Execution Frequency:** Every 1 minute via Cron.
- Cron Entry:**

```
* * * * * /usr/bin/python3 /store/scripts/HBTF_VPN_BruteForce.py >> /store/scripts/VPN_BruteForce_logs/cron_output.log 2>&1
```

Logic Flow

1. **Fetch Targets:** The script queries the QRadar API to retrieve all IPs currently residing in both reference sets.
2. **Fetch Current State:** The script queries the **Cisco FMC Dynamic Objects** (for both Palestine and Jordan regions) to see which IPs are currently blocked.
3. **Comparison Logic:**
 - **Release List:** IPs present in the FMC blocklist but *no longer* in the QRadar reference sets (TTL expired).
 - **Block List:** IPs present in the QRadar reference sets but *not yet* in the FMC blocklist.
4. **Enforcement:** The script issues API calls to FMC to remove the "Release List" IPs and add the "Block List" IPs.

Logging & Retention

To ensure auditability and troubleshooting, the script maintains detailed logs.

- **Log Directory:** /store/scripts/VPN_Bruteforce_logs/
- **Naming Convention:** script_YYYY_MM_DD.txt (A new file is generated daily).
- **Retention Policy:** Logs are kept for **30 days**.
- **Cleanup Cron:**

```
0 0 * * * /usr/bin/find /store/scripts/VPN_Bruteforce_logs/ -name "script_*.txt" -type f -mtime +30 -delete
```



VPN_Blocking_hbtf.py


Incidents Follow-up integration/configuration

SOAR Rules:

Rule Name	Process Type	Object Type	Conditions	Enabled	
HBTf -INC Follow Up Due Date is Passed	Automatic	Incident	Due Date TriggerINC Follow Up Due Date		
HBTf -Incident Clear Follow Up Flag and Due Date	Automatic	Incident	Pending status		
HBTf email follow up set due data per severity (SO) rule	Automatic	Incident	Pending status		

Kibana (172.31.74.203) Script:

/home/soar/soar_email_followup_script.py



SOAR playbooks summary

#	Year	Name	Type	Object type	Automation type	Description	Phase	Conditions	Result	Sub-Playbooks	Incident AddNote	Iterations	Plan
1	2024	HBTF MS Defender Enrichment	Playbook	Artifact	Automatic	Automated enrichment for artifacts from Microsoft Defender 1) Get file info and find machines by Hash (SHA-1 & SHA-256) 2) Find machines by IPv4 3) Find machines by System name or DNS name	Enrichment	Creation of one of the following artifacts: 1) DNS Name 2) System Name 3) Malware SHA-256 Hash 4) Malware SHA-1 Hash 5) IP Address	1) defender_machines data table 2) artifact.description	N/A	Yes	N/A	Append to artifact.description
2	2024	Defender Machine Update Information (PB)	Playbook	Data Table	Automatic	Find machine details on Microsoft Defender once row is added (with Machine ID) to Defender Machines (defender_machines) data table.	Enrichment	Row (with Machine ID) is created in Defender Machines (defender_machines) data table	defender_machines data table	N/A	Yes	N/A	
3	2024	HBTF Auto Enrichment from SIEM - Index	Playbook	Incident	Automatic	Automated enrichment for offense index from SIEM. Get events for offense index (Source IP, Destination IP, User ID, Username) +30 minutes of discovery time.	Enrichment	QR Offense Index Type & QR Offense Index Value have values Offense index is Source IP or Destination IP or User ID or Username	auto_enrichment_from_siem_index data table	N/A	Yes	N/A	
4	2024	HBTF Qualys VM: List Vulnerabilities of Host via IP - Automatic	Playbook	Artifact	Automatic	Get list of vulnerabilities affecting internal IP address from Qualys.	Enrichment	Creation of private IP Address artifact	Append to artifact.description	N/A	Yes	N/A	
5	2024	HBTF DDoS	Playbook	Incident	Automatic	Main playbook for DDoS incidents. It generates specific tasks for DDoS. Also, it keeps checking for arbor events for the target IP.	Main	Incident name contains "HBTF - NTW009 - Potential DDoS Activity Detected"	Incident tasks, sub-playbook and auto_enrichment_from_siem_ddos data table	Qradar DDoS arbor query	N/A	S-PB (Qradar DDoS arbor query): every 15 minutes for 3 times	
6	2024	HBTF VPN Brute Force (For Jordan)	Playbook	Incident	Automatic	Main playbook for VPN brute force from public IPs in Jordan. It sends emails automatically to affected users to confirm if this is legit or not.	Main	Incident name contains "HBTF_VPN Brute Force (For Jordan)"	Incident tasks and email conversation	N/A	Yes	N/A	
7	2024	HBTF Swift business users sla playbook	Playbook	Incident	Automatic	Main fully automated playbook created for specific 4 swift users. Whenever these users login to swift outside business hours, an email is sent automatically to their manager asking for approval. If approved, the incident is closed automatically. If not approved or not responded within 24 hours, the incident is escalated to be handled manually.	Main	Incident type equals "Swift business users"	Email conversation	N/A	Yes	N/A	
8	2024	Defender Find Machine by DNS name (PB)	Playbook	Artifact	Manual	Find machine details on Microsoft Defender from System Name and DNS Name artifacts and add results to defender_machines data table.	Enrichment	artifact.type equals DNS Name or System Name	defender_machines data table	N/A	Yes	N/A	
9	2024	Defender Find Machines by File Hash (PB)	Playbook	Artifact	Manual	Find machine details on Microsoft Defender from SHA-1 or SHA-256 hash artifacts and add results to defender_machines data table.	Enrichment	artifact.type equals Malware SHA-1 Hash or Malware SHA-256 Hash	defender_machines data table	N/A	Yes	N/A	Note on success to be added
10	2024	Defender Find Machines by Internal IP Address (PB)	Playbook	Artifact	Manual	Find machine details on Microsoft Defender from IP Address artifact and add results to defender_machines data table.	Enrichment	artifact.type equals IP Address	defender_machines data table	N/A	Yes	N/A	Note on success to be added
11	2024	Defender Get File Information (PB)	Playbook	Artifact	Manual	Get file information on Microsoft Defender from SHA-1 or SHA-256 hash artifacts and add results to artifact description	Enrichment	artifact.type equals Malware SHA-1 Hash or Malware SHA-256 Hash	artifact.description	N/A	Yes	N/A	Append to artifact.description, Note on success to be added
12	2024	Defender List Indicators (PB)	Playbook	Incident	Manual	Get a list of all Defender indicators. Optionally, specify a regex filter to limit the responses. Indicators can be queried based on title, description, type or value.	Enrichment	N/A	defender_indicators data table	N/A	Yes	N/A	Note on success to be added
13	2024	Defender Machine Collect Investigation Package (PB)	Playbook	Data Table	Manual	Trigger the collection of initial forensics investigation package on specific machine in defender_machines data table	Enrichment	Machine ID should exist in the data table row	Microsoft Defender Investigation Package run	N/A	No	N/A	Note on success and failure to be added
14	2024	Defender Machine Isolate Action (PB)	Playbook	Data Table	Manual	Isolate/Un-isolate machine on Microsoft Defender in defender_machines data table	Configuration	N/A	Microsoft Defender Isolate /Un-isolate machine run	N/A	Yes	N/A	
15	2024	Defender Machine Quarantine File (PB)	Playbook	Data Table	Manual	Quarantine detected file on machine on Microsoft Defender in defender_machines data table	Configuration	machine_file_hash has a value	Microsoft Defender Quarantine file run	N/A	Yes	N/A	

16	2024	Defender Machine Scan (PB)	Playbook	Default	Manual	Defender Machine Scan (PB)	Enrichment	defender_machine_id has a value defender_machine_sca ntype has a value	Defender Machines data table	N/A	Yes	N/A	Note on success to be added
17	2024	HBTF ThreatQ: Automatically Find Artifact Hits	Playbook	Artifact	Automatic	A playbook to automatically enrich an artifact with hits from ThreatQ. This will also populate the Artifact Hits data table in the ThreatQ incident tab.	Enrichment	Artifact is created	ThreatQ incident tab: threatq_indicator_hits artifact.hits	N/A	No	N/A	Note on success and failure to be added
18	2024	HBTF ThreatQ: Block Artifact	Playbook	Artifact	Manual	A playbook to let analysts block specific artifact via ThreatQ.	Contentment	N/A	ThreatQ indicator addition with score 8	N/A	Yes	N/A	Note on failure to be added
19	2024	HBTF ThreatQ: Bulk Block Artifacts	Playbook	Incident	Manual	A playbook to let analysts block multiple artifacts of the same type simultaneously.	Contentment	N/A	ThreatQ indicators addition with score 8	N/A	Yes	Timer 1 second with conditional iterations until all artifacts are blocked.	Note on failure to be added
20	2024	HBTF ThreatQ: Find Artifact Hits	Playbook	Artifact	Manual	A playbook allowing users to manually refresh the hits for a given artifact from ThreatQ. This will also populate the Artifact Hits data table in the ThreatQ incident tab.	Enrichment	N/A	ThreatQ incident tab: threatq_indicator_hits artifact.hits	N/A	No	N/A	Note on success and failure to be added
21	2025	HBTF Mandiant: Scan artifact (manual)	Playbook	Artifact	Manual	A playbook to enrich an artifact with hits from Mandiant TI.	Enrichment	artifact.type equals IP Address or URL or Malware MD5 Hash or DNS Name	artifact.hits	N/A	No	N/A	Note on success to be added
22	2025	HBTF Mandiant: Scan artifact (auto)	Playbook	Artifact	Automatic	A playbook to automatically enrich an artifact with hits from Mandiant TI.	Enrichment	Artifact is created and (artifact.type equals IP Address or URL or Malware MD5 Hash or DNS Name)	artifact.hits	N/A	No	N/A	Note on success to be added

Version	Published	Changed By	Comment
CURRENT (v. 11)	May 05, 2025 13:23	Mohammad aldoulat	
v. 10	Apr 27, 2025 12:07	Mohammad aldoulat	
v. 9	Apr 27, 2025 11:59	Mohammad aldoulat	
v. 8	Apr 27, 2025 11:53	Mohammad aldoulat	
v. 7	Apr 27, 2025 11:52	Mohammad aldoulat	
v. 6	Apr 27, 2025 11:51	Mohammad aldoulat	
v. 5	Jan 05, 2025 15:17	Mohammad aldoulat	
v. 4	Dec 09, 2024 15:18	Mohammad aldoulat	
v. 3	Dec 09, 2024 14:34	Mohammad aldoulat	
v. 2	Dec 03, 2024 13:29	Mohammad aldoulat	
v. 1	Dec 03, 2024 11:10	Mohammad aldoulat	

Incident handling guide

General notes:

- When incident is created on SOAR, its "Pending status" will be "New (N)" <rule: HBTF Set Pending Status to New if incident is created> and the owner will be "Administrators" group <Qradar SOAR plugin template>.
- Analyst should assign the incident using the incident action "HBTF Respond" <playbook: HBTF Respond>:

Pending status: Pending on incident owner (IO)

Owner: <Analyst>

Note: "Incident assigned to <analyst_email>"

TTR: timer stops

- Analyst should then proceed with the tasks on the incident. Tasks change according to the activated playbook. Details for each main playbook are explained in next section "IR Main Playbooks".
- If incident is duplicate, it can be directly closed as duplicate by filling the value of "Original Incident ID" in the first task of incident. as a result:

Pending status: Closed (C)

System owner: None

Resolution: Duplicate

Resolution summary: "Closing incident as duplicate for <Original incident ID>"

Note: "Closing incident as duplicate for <Original incident ID>"

TTA: Timer stops

- Once initial action is taken on the incident, analyst should click on incident action "HBTF Initial Action Taken" <playbook: HBTF Initial Action Taken>:

TTA: Timer stops

Note: action_taken

Pending status: should be set to correct status

System owner: should be set if applicable yet

Note: For the following main playbooks, Initial Action Taken is automatically set:

- HBTF Guardium playbook - on the completion of task "Validate description". Also:
 - Pending status: Pending on system owner (SO)
 - System owner: Cyber Security (Risk)
 - Note: "Email sent to Guardium admin"
- HBTF VPN Brute Force (For Jordan) - on the completion of task "Contact users to confirm VPN login legitimacy". Also:
 - Pending status: Pending on system owner (SO)
 - System owner: VPN User
 - Note: "An email has been sent to users to confirm the legitimacy of the failed login activity."
- HBTF Files Copied to USB - on the completion of task "Is the user authorized to use USB?". Also:
 - Pending status: Pending on system owner (SO) / Closed (C)
 - System owner: USB user / None
 - Note: "An email has been sent to the user to confirm the legitimacy of the USB usage activity" / "Closing incident as Normal user activity."
 - Resolution summary: null / "Not an issue. User is authorized to use USB."

- Resolution: null / "Normal user activity"

- HBTF user/group modification playbook. Also:
 - Pending status: Pending on system owner (SO)
 - Note: "User is authorized. Email sent to user to provide the reason and approval for the observed changes"

- Duplicate closure of incidents - on the completion of task "Review incident description, Name & Artifacts" when the field "Original Incident ID" has value. Also:
 - Pending status: Closed (C)
 - System owner: None
 - Resolution: Duplicate
 - Resolution summary: "Closing incident as duplicate for <Original incident ID>"
 - Note: "Closing incident as duplicate for <Original incident ID>"

▪ Updated incidents:

When there is an update on incident (email received), Its "Pending status" will become "Updated (U)" [<script: Generic email script \(App Exchange\)>](#). It is temp status and analyst have to check it and assign the correct status to it then.

IR Main Playbooks:

- Generic Incident:

Playbook:



Noteworthy tasks:

- **Generic IR task**
The task contains 5 fields, which are:
 1. **Close Incident**
 2. **Resolution**
 3. **Resolution Summary**

4. Incident Type

5. Original Incident ID


- Generic incidents can be handled within this task. You can check all required logs and enrichment data.
 - "Resolution Summary" field must be updated whenever there is an update on the incident.
 - "Pending status" and "System owner" fields must be updated whenever applicable.
 - Manually set "Initial action taken" once the initial action has been taken and the incident needs to be kept open.

- On closure:
 - Set "Close Incident" to yes.
 - If incident is duplicate, fill the "Original Incident ID" field. No need to fill the "Resolution Summary" field in this case only.
 - Otherwise, fill the "Resolution" and "Resolution Summary" fields.

- If tasks for other incident type is required, use "Incident Type" field anytime.

- Keep this task open till the end of the incident. In case you close this task without setting "Close Incident" or it was set to "No", then you will need to manually close the incident.
 - **USB Usage Incident:**

Playbook:



Supporting documents:

[USB-Authorized Feb.2025.xlsx](#)

Noteworthy tasks:

- **Is the user authorized to use USB?**
The task contains 3 fields, which are:
1. Is user authorized?

2. User email address

3. Original Incident ID

Scenario 1: **User is authorized to use USB** after finding the username in the above sheet Set the "Is user authorized?" value to "Yes", then "Complete and Close" the task. This will close the incident as "Normal User Activity".

Scenario 2: **User is not authorized to use USB** after not finding the username in the above sheet Set the "Is user authorized?" value to "No", then add the user's email address in the "User email address" field, then "Complete and Close" the task. This will trigger an automatic playbook which will send an email to the user in order to inquire about the reasoning behind the USB usage.

Scenario 3: **This incident is a duplicate incident** Add the original incident ID in the "Original Incident ID" field, then "Complete and Close" the task. This will close the incident as "Duplicate".

- **Was the USB usage legitimate?**


Confirm whether or not the USB usage was legitimate based on the response of the person in question. This task contains 1 field which is: "Not an issue".

Scenario 1: **USB usage is legitimate** Set the "Not an issue" value to "Yes", then "Complete and Close" the task. This will close the incident as "Normal User Activity".

Scenario 2: **USB usage is NOT legitimate** Set the "Not an issue" value to "No", then "Complete and Close" the task.

- **User/Group Modification Incident:**

Playbook:



Noteworthy tasks:

- **Is user authorized?**

The task contains 4 fields, which are:

1. Is user authorized?

2. **User email address**

3. **Original Incident ID**

4. **System owner**


Scenario 1: **User is authorized to perform User/Group modifications** Set the "Is user authorized?" value to "Yes", then add the user's email address in the "User email address" field, then "Complete and Close" the task. This will trigger an automatic playbook which will send an email to the user in order to inquire about the legitimacy and approval of the activity.

Scenario 2: **User is NOT authorized to perform User/Group modifications** Set the "Is user authorized?" value to "No", then "Complete and Close" the task. And proceed with the remaining Incident Response tasks accordingly.

Scenario 3: **This incident is a duplicate incident** Add the original incident ID in the "Original Incident ID" field, then "Complete and Close" the task. This will close the incident as "Duplicate".


- **Guardium Incident:**

Playbook:




Noteworthy tasks:

- **Validate description**
You highlight all the text inside the description of the incident, then click on the "Text Color" icon, and click "Reset":



Then, click on the "**Background Color**" icon, and click "**Reset**":



- **Validate response**


Confirm whether or not the reported Guardium activity was legitimate based on the response of the person in question. This task contains 1 field which is: "**Not an issue**".

Scenario 1: **Guardium activity is legitimate** Set the "**Not an issue**" value to "**Yes**", then "**Complete and Close**" the task. This will close the incident as "**Normal User Activity**".

Scenario 2: **Guardium activity is NOT legitimate** Set the "**Not an issue**" value to "**No**", then "**Complete and Close**" the task. And proceed with the remaining Incident Response tasks accordingly.

- **DDoS Incident:**

Playbook:




Noteworthy tasks:

- **Fill Public IP**
You add a comma separated list of the public IPs.
- **Enable DDoS mitigation**
Based on the monitoring, decide if DDoS mitigation is required. If yes, contact Arbor/Umniah team to enable it.
- **Block observed IPs if applicable**
Block the sources of the DDoS if applicable.

- **VPN Brute-force Incident:**

Playbook:



Noteworthy tasks:

- Contact users to confirm VPN login legitimacy**
 You add a comma separated list of the user(s) email address(es) in the "User email address" field, then "Complete and Close" the task. This will trigger an automatic playbook which will send an email to the user in order to inquire about the legitimacy of the activity. If the incident is duplicate, simply add the ID of the original incident in the "Original Incident ID" field, then "Complete and Close" the task. This will automatically close the incident as a duplicate incident.
- Was/were the VPN login(s) legitimate?**
 Set the correct value of the field "Not an issue", if set to "Yes", the incident will be closed automatically as "Normal user activity".

Incident manual actions guide

■ Incident level:

Name	Object type	Description	Related playbook /rule	Conditions	Result location
Defender List Indicators (PB)	Incident	Get a list of all Defender indicators. Optionally, specify a regex filter to limit the responses.	Playbook	N/A	Notes tab
Defender Refresh Incident (PB)	Incident	Get a Defender 365 Incident	Playbook	incident.properties.defender_incident_id has a value	Notes tab
HBTF Add Incident Review	Incident	Adds a review to an incident	Playbook	N/A	Reviews tab
HBTF - Approve Severity Change	Incident	Approves a severity change request	Playbook	incident.properties.requested_severity has a value	Notes tab
HBTF - Change Severity	Incident	Submits a severity change request	Playbook	N/A	Notes tab
HBTF DDoS query Arbor events	Incident	Query Arbor events	Playbook	N/A	Data table: "auto_enrichment_from_siem_ddos"
HBTF Initial Action Taken	Incident	Sets Initial Action Taken value to Yes. Also, analyst should set the fields "Pending Status" & "System Owner".	Playbook	N/A	Notes tab
HBTF Respond	Incident	Sets Initial Response value to Yes	Playbook	N/A	Notes tab
HBTF ThreatQ: Bulk Block Artifacts	Incident	Bulk block artifacts on ThreatQ	Playbook	N/A	Artifacts tab
HBTF Zones Isolation	Incident	Zone Isolation	Playbook	N/A	Property: "globals" Property: "Firewalls_IPs" Notes tab
MS Teams: Archive Team (PB)	Incident	Archive Team	Playbook	N/A	Notes tab
MS Teams: Create Team (PB)	Incident	Create Team	Playbook	N/A	Notes tab
Create Artifact from Assets info	Data Table	Create Artifact from Assets info	Rule	N/A	Artifacts tab
Create artifact from Destination IP info	Data Table	Create Artifact from Destination IP info	Rule	N/A	Artifacts tab
Create Artifact from Events info	Data Table	Create Artifact from Events info	Rule	N/A	Artifacts tab
Create artifact from Source IP info	Data Table	Create Artifact from Source IP info	Rule	N/A	Artifacts tab
Create Artifacts from Flows Info	Data Table	Create Artifact from Flows info	Rule	N/A	Artifacts tab
HBTF Outbound Email: Reply to Message	Data Table	Outbound Email: Reply to Message	Rule	N/A	Data Table: "Email Conversations"
QRadar Enhanced Data Refresh	Incident	Data Refresh	Rule	QRadar Destination has a value QR Offense Id has a value	Property: "Incident Last Updated time"
ThreatQ: Import Attachment	Attachment	Import Attachment	Rule	N/A	ThreatQ

■ Artifact level:

Name	Object type	Description	Related playbook /rule	Conditions	Result location
Defender Find Machine by DNS name (PB)	Artifact	Find machine by DNS name	Playbook	artifact.type has one of "DNS Name", "System Name"	Incident row: "defender_machines" Notes tab
Defender Find Machines by File Hash (PB)	Artifact	Find machine by file hash	Playbook	artifact.type has one of "Malware SHA-1 Hash", "Malware SHA-256 Hash"	Incident row: "defender_machines" Notes tab
Defender Find Machines by Internal IP Address (PB)	Artifact	Find machine by internal IP address	Playbook	artifact.type is equal to "IP Address"	Incident row: "defender_machines" Notes tab
Defender Get File Information (PB)	Artifact	Get file information	Playbook	artifact.type has one of "Malware SHA-1 Hash", "Malware SHA-256 Hash"	artifact.description
Defender Set Indicator (PB)	Artifact	Set indicator	Playbook	artifact.type has one of "DNS Name", "IP Address", "Malware SHA-1 Hash", "Malware SHA-256 Hash", "System Name", "URL", "URL Referer"	Incident row: "defender_indicators" Notes tab
HBTF Mandiant: Scan artifact (manual)	Artifact	Scan artifact	Playbook	IF artifact.type is equal to "IP Address" OR artifact.type is equal to "Malware MD5 Hash" OR artifact.type is equal to "DNS Name" OR artifact.type is equal to "URL"	Notes tab
HBTF Manual Enrichment from SIEM	Artifact	Manual enrichment from SIEM	Playbook	N/A	Property: "qradar_search" Incident row: "manual_enrichment_from_siem_artifact" Notes tab
HBTF Qualys VM: List Vulnerabilities of Host via IP - Manual	Artifact	List vulnerabilities of host via IP	Playbook	artifact.type is equal to "IP Address"	Property: "host_info" Notes tab
HBTF Qualys VM: Scan Launch - artifact	Artifact	Scan launch - artifact	Playbook	artifact.type is equal to "IP Address"	Notes tab
HBTF ThreatQ: Block Artifact	Artifact	Block Artifact	Playbook	N/A	Notes tab
HBTF ThreatQ: Find Artifact Hits	Artifact	Find artifact hits	Playbook	N/A	Artifacts tab
Parse Utilities: Email Parsing (Artifact) - Example (PB)	Artifact	Email parsing artifact	Playbook	artifact.type has one of "Email Attachment", "Other File", "RFC 822 Email Message File"	Artifacts tab Notes tab
Parse Utilities: Parse SSL Certificate - Example (PB)	Artifact	Parse SSL certificate	Playbook	artifact.type is equal to "X509 Certificate File"	Notes tab Property: "convert_json_to_rich_text"
Parse Utilities: PDFID (Artifact) - Example (PB)	Artifact	PDFID artifact	Playbook	artifact.attachment has a value	Notes tab
Parse Utilities: XML Transformation (Artifact) - Example (PB)	Artifact	XML transformation artifact	Playbook	artifact.type has one of "Email Attachment", "Log File", "Malware Sample", "Other File"	Notes tab
Find in QRadar Reference Set	Artifact	Find in QRadar reference set	Rule	N/A (not configured)	N/A (not configured)

■ Data Table level:

Name	Object type	Description	Related playbook /rule name	Conditions	Result location
Create Artifact from Indicator (PB)	Data Table	Create artifact from indicator	Playbook	N/A	Artifacts tab Notes tab

Delete Indicator (PB)	Data Table	Delete indicator	Playbook	defender_indicators.status is equal to "Active"	Notes tab
Update Indicator (PB)	Data Table	Update indicator	Playbook	defender_indicators.status is equal to "Active"	Notes tab
Defender Machine Collect Investigation Package (PB)	Data Table	Collect investigation package	Playbook	N/A	Helper
Defender Machine Isolate Action (PB)	Data Table	Machine isolate action	Playbook	defender_machines.machine_health_status does not contain "Isolate"	Notes tab
Defender Machine Quarantine File (PB)	Data Table	Machine quarantine file	Playbook	defender_machines.machine_file_hash has a value	Notes tab
Defender Machine Refresh Information (PB)	Data Table	Machine refresh information	Playbook	N/A	Notes tab
Defender Machine Scan (PB)	Data Table	Machine scan	Playbook	N/A	Notes tab

■ Task level:

Name	Object type	Description	Related playbook/rule name	Conditions	Result location
HBTF Send email	Task	Send email	Rule	Active is equal to Yes	Email conversation tab

Qradar certificate renewal procedure

* Generate CSR with SAN field:

```
openssl genrsa -out qradar.key 2048

cp /etc/pki/tls/openssl.cnf /opt/qradar/conf/trusted_certificates/openssl-san.cnf

vi /opt/qradar/conf/trusted_certificates/openssl-san.cnf
```

```
req_extensions = v3_req
subjectAltName = @alt_names
[ alt_names ]
DNS.1 = qradar-console.httf.com.jo
IP.1 = 172.31.74.70
```

```
openssl req -new -key qradar.key -out qradar.csr -config openssl-san.cnf

openssl req -in qradar.csr -noout -text

cat qradar.csr
```

* Import signed cert:

```
vi qradar.cer

copy - paste cert and save

openssl req -in qradar.cer -noout -text
```

* Install cert:

```
/opt/qradar/bin/install-ssl-cert.sh
```

```
[root@qradar-console trusted_certificates]# /opt/qradar/bin/install-ssl-cert.sh
Path to Public Key File (SSLCertificateFile): /opt/qradar/conf/trusted_certificates/qradar.cer
Path to Private Key File (SSLCertificateKeyFile): /opt/qradar/conf/trusted_certificates/qradar.key
```

You have specified the following:

```
SSLCertificateFile of /opt/qradar/conf/trusted_certificates/qradar.cer
SSLCertificateKeyFile of /opt/qradar/conf/trusted_certificates/qradar.key
```



```
Re-configure Apache now (includes restart of httpd) (Y/[N])? y
Mon Mar 17 19:22:43 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer has 729 days until it expires
Mon Mar 17 19:22:44 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer contains server host name qradar-console.hbt.com.
jo
Mon Mar 17 19:22:44 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer has a valid Signature Algorithm
Mon Mar 17 19:22:44 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer modulus matches key file /opt/qradar/conf
/trusted_certificates/qradar.key modulus
Mon Mar 17 19:22:44 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer chain is valid for CA file /etc/pki/tls/cert.pem
Mon Mar 17 19:22:44 +03 2025 [install-ssl-cert.sh] OK: /opt/qradar/conf/trusted_certificates/qradar.cer validation completed successfully
Backing up current SSL configuration ... (OK)
Installing user SSL certificate ... (OK)
Reloading httpd configuration:
- Restarting httpd service ... (OK)
Restarting running services:
- Stopping hostcontext ... (OK)
- Restarting Tomcat ... (OK)
- Starting hostcontext ... (OK)
Updating deployment:
- Copying certificate to managed hosts
* 172.31.74.81 ..... (OK)
* 192.168.223.12 .... (OK)
* 172.18.74.74 ..... (OK)
* 172.31.74.71 ..... (OK)
* 192.168.156.12 .... (OK)
* 172.31.92.91 ..... (OK)
* 172.31.92.102 ..... (OK)
- Restarting hostcontext on managed hosts
* 172.31.74.81 ..... (OK)
* 192.168.223.12 .... (OK)
* 172.18.74.74 ..... (OK)
* 172.31.74.71 ..... (OK)
* 192.168.156.12 .... (OK)
* 172.31.92.91 ..... (OK)
* 172.31.92.102 ..... (OK)
The event collection service must be restarted if WinCollect is used in your environment. Restart the event collection service now (y/[n])? y
- Restarting ecs-ec-ingress on managed hosts
* 172.31.74.81 ..... (OK)
* 192.168.223.12 .... (OK)
* 172.18.74.74 ..... (OK)
* 172.31.74.71 ..... (OK)
* 192.168.156.12 .... (OK)
* 172.31.92.91 ..... (OK)
* 172.31.92.102 ..... (OK)
- Restarting ecs-ec-ingress on console ... (OK)
Mon Mar 17 19:32:06 +03 2025 [install-ssl-cert.sh] OK: Install SSL Cert Completed
[root@qradar-console trusted_certificates]#
```

*** Verify services:**

/opt/qradar/upgrade/util/setup/upgrades/wait_for_start.sh

SOC_L1_FMC_Immediate_Blacklisting technical guide

- To immediately block malicious IP addresses on internet firewalls in Jordan, Bahrain and Palestine, add the IP address to the following reference set with proper description:

SOC_L1_FMC_Immediate_Blacklist

Value: IP address

Source: Description

SOC_L1_FMC_Immediate_Blacklist

Number of Elements: 0

Creation Time: 31/Mar/2026, 02:07:01 PM

Timeout Type: FIRST_SEEN

Time To Live: Forever

Default Value Type: IP

Value

Items per page: 100-0 of 0 items

Dependents

This ReferenceData appears to not have any data dependencies

Add Entry

Value

Source

Optional: A comment to add to the new data entry

Close

Save

- To released an IP that was blocked previously using the same reference set, remove the IP address from the same reference set:

SOC_L1_FMC_Immediate_Blacklist

Number of Elements: 1

Creation Time: 31/Mar/2026, 02:07:01 PM

Timeout Type: FIRST_SEEN

Time To Live: Forever

Default Value Type: IP

1 item selected

Delete

Cancel

☒	Value	First Seen	Last Seen	Source
☒	1.1.1.1	31/Mar/2026, 03:09:33 PM	31/Mar/2026, 03:09:33 PM	Port scan detected

Items per page: 101-1 of 1 items

1 of 1 pages

+++++

This reference set is replicated on internet firewall for permanent blocking every 1 minute through a cronjob configured on SIEM console.

Related documents:

SOC onboarding


- New employee access (**Security**):
 - SOAR (executer: **Security Operations**):

1- "Jordan G SOAR" on Active directory in order to get access to SOAR through LDAP.


2- "Analyst_Users" on SOAR script "Generic email script (App Exchange)".

```
633
634 # Create a suitable title for an incident based on the email
635 newIncidentTitle = "Incident generated from email \"{0}\" via mailbox {1}".format(
636     |  REPLY_PATTERN.sub("", subject), emailmessage.inbound_mailbox)
637
638 # Check to see if a similar incident already exists
639 # We will search for an incident which has the same name as we would give a new incident
640
641
642 text = emailmessage.subject
643 match = re.search(r"\\([d{1,6})\\]", text)
644 case_id = 3
645 if match:
646     |  case_id = match.group(1)
647
648 query_builder.equals(fields.incident.id, int(case_id))
649 query_builder.equals(fields.incident.plan_status, "Active")
650 query = query_builder.build()
651 incidents = helper.findIncidents(query)
652
653 Analyst_Users = ["oalamarneh@hbtbf.com.jo", "maldoulat@hbtbf.com.jo"]
654
655 if len(incidents) != 0:
656     # A similar incident already exists. Associate the email with this preexisting incident.
657     log.info(u"Associating with existing incident {0}".format(incidents[0].id))
658     emailmessage.associateWithIncident(incidents[0])
659     lowercasesender = emailmessage.sender.address.lower().casefold()
660
661     if lowercasesender not in Analyst_Users:
662         incident.properties.pending_status = "Updated (U)"
663         incident.addNote("Incident update recieved")
664     else:
665         incident.addNote("Email sent from analyst")
666     #Section for Email Follow up flag and due date -- starts
667
668     incident.properties.follow_up_flag = "NO"
669     # Sender_group = groups.findByName('lowercasesender')
```

3- "HBTf SOC Analysts" group on SOAR.



4) "HBTF SOC Analyst" rule on SOAR.



- SIEM (executer: Security Operations):

User should be added as follows:

User Details

User Name

code (ex: b000x)

User Description

full name

E-mail

email

Authentication

New Password

Confirm New Password

Local Only Account

☐

Permissions

User Role

SOC-Analyst

Manage User Roles

Security Profile

Admin

Manage Security Profiles

Session Settings

Override System Inactivity Timeout

☐

Cancel

Save

- ThreatQ (**executer: Security Operations**):

Create local account with admin privilege.

- MS defender (**executer: Office Automation**):

Contact Office Automation team to add the user on MS defender.

- Acalvio (**executer: Security Operations**):

Grant access through AD authentication.

- Mandiant (**executer: Security Operations**):

Non-admin access to be granted to him/her by Shadi Omar.

- Jira + Confluence (**executer: IT Quality Assurance**):

User should be granted access to IT Security space.

- PAM (**executer: Security Operations**):

After adding user to PAM AD group (by Helpdesk), invite user and add it to set "HBTF - SOC/IR".

- Firemon (**executer: Security Operations**):

Add to firemon group "SOC team"

+++++

- Jira ticket "IT Admin" should be submitted for the above required access. The following groups will be assigned based on this ticket:

```
*Domain Users          *MDM-Users
*Jordan G SecOps       *Jordan G MFA Users
*Jordan G IT SecOps    *Jordan G VPN Common S
*Jordan G VPN IT Admin*Jordan G PAM RDS User
*Jordan G WCF Professi*Jordan G IT Users
*Jordan G MDM Users    *Jordan G SOAR
```

Reference ticket: <https://atlassian.hbtf.com/jira/browse/UAM-789>

- Send to system support team to request **laptop**, keyboard, mouse and monitor.
- **Access card**: Take CIO approval > Send to CIO secretary to create a profile for the new employee on MTZ.
- **Fingerprint**: Contact HR team to add the new employee to the fingerprint system.
- Submit **firemon** ticket for access to the above systems on wired and VPN networks.
- Grant access through **PAM** to above systems. Take IT SecOps unit head approval and forward to helpdesk team. Then, contact SecOps for required access within PAM.
- Ensure **VPN** access is granted. Send email to CIO for approval and forward it to helpdesk team.
- Grant company portal access. Send email to CIO for approval and forward it to helpdesk team.
- Grant Jira and Confluence access. Submit UAM (UAM) and attach security senior manager's approval. User should be granted access to IT Security space.
- Grant professional internet access. Send to CIO for approval and forward it to helpdesk team.
- Assign fixed IP address on Infoblox within the range: [192.168.209.50-192.168.209.100](#)
- Contact network team for the IP phone.
- Grant access to ([\\sms_it_cplx\SecOps\SOC Documents](#)) & ([\\srvjcpldocp01\IT Infrastructure & Operations\Asset_Inventory](#))
- Subscribe to SOC calendar ([SOC Tasks](#))

+++++

Onboarding plan:

Phase 1 (3 weeks)

- General topics (2 day)
 - Network (A0) diagram
 - SecArch overview
 - SOC documents overview ([SOC](#))
 - Operational tasks overview ([SOC Tasks](#))

- SIEM (5 days)
 - General overview
 - Use cases management
 - Offenses management including tuning
 - Parsing management
 - Log source management
 - Upgrade
 - Log activity search (including AQL)
 - L1 activities
 - HBTF [SIEM](#) documents review

- MS Defender (2 days)
 - The following Microsoft trainings:
 - Intro to MS defender for endpoint - <https://learn.microsoft.com/en-us/training/modules/m365-introduction-defender-endpoint/>
 - Intro to MS XDR - <https://learn.microsoft.com/en-us/training/modules/introduction-microsoft-365-threat-protection/>
 - Manage MS defender for endpoint - <https://learn.microsoft.com/en-us/training/modules/manage-defender-endpoint/>
 - Mitigate incidents using MS defender - <https://learn.microsoft.com/en-us/training/modules/mitigate-incidents-microsoft-365-defender/>
 - Mitigate threats using MS defender for Endpoint - <https://learn.microsoft.com/en-us/training/paths/sc-200-mitigate-threats-using-microsoft-defender-for-endpoint/>
 - L1 activities
 - HBTF [MS defender](#) documents review

- SOAR (2 days)
 - HBTF [SOAR](#) documents review
 - [SOAR training labs](#)
 - L1 activities

- ThreatQ (2 days)
 - HBTF [TIP](#) documents review
 - L1 activities

- Incident response (2 day)
 - HBTF [Incident response framework](#)
 - HBTF [Incident handling guide](#)
 - HBTF [Incident manual actions guide](#)
 - HBTF [SOAR playbooks summary](#)
 - HBTF [IR Isolation Rules](#)
 - HBTF [Critical assets](#)

Phase 2 (3 days)

- Incidents shadowing
- Tasks shadowing

Phase 3 (3 weeks)

- Cherry (Low & Medium) incidents - Review before closure
- Cherry tasks under supervision

Phase 4 (3 weeks)

- Advanced tasks under supervision
- High and critical incidents under supervision with review before closure

+++++

Tracking sheet:



SOC_onboarding_tracking.xlsx