Операционные системы

Основы интерфейса взаимодействия пользователя с системой Unix на уровне командной строки

Костюк Дмитрий Иванович

2026-03-11

Содержание (i)

Цели и задачи работы

Процесс выполнения лабораторной работы

Выводы по проделанной работе

1. Цели и задачи работы

Цель лабораторной работы

Приобретение практических навыков взаимодействия пользователя с системой посредством командной строки.

Задачи лабораторной работы

1 Определить имя и путь домашнего каталога

2 Изучить команду ls.

3 Выполнить действия с каталогами.

4 Получить дополнительные сведения при помощи справки по командам.

5 Изучить команду history.

2. Процесс выполнения лабораторной работы

Имя и путь к домашнему каталогу



Рисунок 1: Путь к домашнему каталогу

Опции команды ls

```
dikostuk@dikostuk:~$ cd /tmp
dikostuk@dikostuk:/tmp$ ls
48f0056b-7f5c-4366-9b23-9cf33364fce3.zip
f162e14b-87fa-4d92-a9b4-18cf5ca0ba75.zip
happd.sock
snap-private-tmp
systemd-private-c88034596eb841c4b0965c74e5ef6acd-abrtd.service-rVH2BO
systemd-private-c88034596eb841c4b0965c74e5ef6acd-chronyd.service-IUU260
systemd-private-c88034596eb841c4b0965c74e5ef6acd-colord.service-zmHPlc
systemd-private-c88034596eb841c4b0965c74e5ef6acd-dbus-broker.service-7VNJzK
systemd-private-c88034596eb841c4b0965c74e5ef6acd-fwupd.service-mVZlfO
systemd-private-c88034596eb841c4b0965c74e5ef6acd-irqbalance.service-bbNbyV
systemd-private-c88034596eb841c4b0965c74e5ef6acd-low-memory-monitor.service-KCs6
7Z
systemd-private-c88034596eb841c4b0965c74e5ef6acd-ModemManager.service-BKZHWk
systemd-private-c88034596eb841c4b0965c74e5ef6acd-pcscd.service-yheyK6
systemd-private-c88034596eb841c4b0965c74e5ef6acd-polkit.service-F3yX2y
systemd-private-c88034596eb841c4b0965c74e5ef6acd-rtkit-daemon.service-OHQcke
systemd-private-c88034596eb841c4b0965c74e5ef6acd-switcheroo-control.service-t3Wb
mI
systemd-private-c88034596eb841c4b0965c74e5ef6acd-systemd-logind.service-EMS3Bo
systemd-private-c88034596eb841c4b0965c74e5ef6acd-systemd-resolved.service-Pjffpw
systemd-private-c88034596eb841c4b0965c74e5ef6acd-upower.service-2yeN0D
```

Рисунок 2: Команда ls

Опции команды ls

```
dikostuk@dikostuk:/tmp$ ls -a
.
..
48f0056b-7f5c-4366-9b23-9cf33364fce3.zip
f162e14b-87fa-4d92-a9b4-18cf5ca0ba75.zip
.font-unix
happd.sock
.ICE-unix
snap-private-tmp
systemd-private-c88034596eb841c4b0965c74e5ef6acd-abrtd.service-rVH2BO
systemd-private-c88034596eb841c4b0965c74e5ef6acd-chronyd.service-IUU26O
systemd-private-c88034596eb841c4b0965c74e5ef6acd-colord.service-zmHPlc
systemd-private-c88034596eb841c4b0965c74e5ef6acd-dbus-broker.service-7VNJzK
systemd-private-c88034596eb841c4b0965c74e5ef6acd-fwupd.service-mVZlfO
systemd-private-c88034596eb841c4b0965c74e5ef6acd-irqbalance.service-bbNbyV
systemd-private-c88034596eb841c4b0965c74e5ef6acd-low-memory-monitor.service-KCsG
7Z
systemd-private-c88034596eb841c4b0965c74e5ef6acd-ModemManager.service-BKZHWk
systemd-private-c88034596eb841c4b0965c74e5ef6acd-pcscd.service-yheyK6
systemd-private-c88034596eb841c4b0965c74e5ef6acd-polkit.service-F3yX2y
systemd-private-c88034596eb841c4b0965c74e5ef6acd-rtkit-daemon.service-OHQcke
systemd-private-c88034596eb841c4b0965c74e5ef6acd-switcheroo-control.service-t3Wb
mI
systemd-private-c88034596eb841c4b0965c74e5ef6acd-systemd-logind.service-EMS3Bo
```

Рисунок 3: Команда ls -a

Опции команды ls

```
dikostuk@dikostuk:/tmp$ ls -l
total 9708
-rw-r--r--. 1 dikostuk dikostuk 4182728 Mar 11 18:07 48f0056b-7f5c-4366-9b23-9cf33364fce3.zip
-rw-r--r--. 1 dikostuk dikostuk 4182728 Mar 11 18:08 f162e14b-87fa-4d92-a9b4-18cf5ca0ba75.zip
srw-rw-rw-. 1 root     root           0 Mar 11 18:05 happd.sock
drwx------. 2 root     root          40 Mar 11 18:04 snap-private-tmp
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-abrtd.service-rVH2BO
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-chronyd.service-IUU260
drwx------. 3 root     root          60 Mar 11 18:05 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-colord.service-zmHPlc
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-dbus-broker.service-7VNJzK
drwx------. 3 root     root          60 Mar 11 18:05 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-fwupd.service-mVZlfO
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-irqbalance.service-bbNbyV
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-low-memory-monitor.service-KCsG7Z
drwx------. 3 root     root          60 Mar 11 18:05 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-ModemManager.service-BKZHWk
drwx------. 3 root     root          60 Mar 11 18:05 systemd-private-c88034596eb841c4b0965c74
e5ef6acd-pcscd.service-yheyK6
drwx------. 3 root     root          60 Mar 11 18:04 systemd-private-c88034596eb841c4b0965c74
```

Рисунок 4: Команда ls -l

Опции команды ls

```
dikostuk@dikostuk:/tmp$ ls -f
.
..
f162e14b-87fa-4d92-a9b4-18cf5ca0ba75.zip
48f0056b-7f5c-436G-9b23-9cf33364fce3.zip
tmp-xa4.xpi
systemd-private-c88034596eb841c4b0965c74e5ef6acd-fwupd.service-mVZlfO
.X1-lock
.X0-lock
systemd-private-c88034596eb841c4b0965c74e5ef6acd-pcscd.service-yheyK6
systemd-private-c88034596eb841c4b0965c74e5ef6acd-colord.service-zmHPlc
happd.sock
systemd-private-c88034596eb841c4b0965c74e5ef6acd-ModemManager.service-BKZHWk
vmware-root_897-3979643105
systemd-private-c88034596eb841c4b0965c74e5ef6acd-systemd-logind.service-EMS3Bo
systemd-private-c88034596eb841c4b0965c74e5ef6acd-upower.service-2yeN0D
systemd-private-c88034596eb841c4b0965c74e5ef6acd-switcheroo-control.service-t3WbmI
systemd-private-c88034596eb841c4b0965c74e5ef6acd-rtkit-daemon.service-OHQcke
systemd-private-c88034596eb841c4b0965c74e5ef6acd-polkit.service-F3yX2y
systemd-private-c88034596eb841c4b0965c74e5ef6acd-low-memory-monitor.service-KCs67Z
systemd-private-c88034596eb841c4b0965c74e5ef6acd-chronyd.service-IUU260
systemd-private-c88034596eb841c4b0965c74e5ef6acd-irqbalance.service-bbNbyV
systemd-private-c88034596eb841c4b0965c74e5ef6acd-abrtd.service-rVH2B0
systemd-private-c88034596eb841c4b0965c74e5ef6acd-dbus-broker.service-7VNJzK
systemd-private-c88034596eb841c4b0965c74e5ef6acd-systemd-resolved.service-Pjffpw
.font-unix
.XIM-unix
.ICE-unix
```

Рисунок 5: Команда ls -f

Каталог /var/spool

```
dikostuk@dikostuk:/tmp$ cd /var/spool/
dikostuk@dikostuk:/var/spool$ ls -l
total 0
drwxr-x--x. 1 root abrt 15512 Mar 11 18:11 abrt
drwx------. 1 abrt abrt     0 Dec  4 03:00 abrt-upload
drwxr-xr-x. 1 root root    66 Oct 23 07:05 anacron
drwx------. 1 root root    18 Oct 23 07:07 at
drwx------. 1 root root     0 Aug  6  2025 cron
drwx--x---. 1 root lp       6 Dec 12 03:00 cups
drwxr-xr-x. 1 root root     0 Jul 30  2025 lpd
drwxrwxr-x. 1 root mail  1534 Mar 11 18:04 mail
drwxr-xr-x. 1 root root     0 Jan 27 03:00 plymouth
dikostuk@dikostuk:/var/spool$
```

Рисунок 6: Каталог /var/spool

Домашний каталог

```
dikostuk@dikostuk:/var/spool$ cd
dikostuk@dikostuk:~$ ls
Desktop  Documents  Downloads  Music  Pictures  Public  Templates  Videos  work
dikostuk@dikostuk:~$ ls -al
total 16
drwx------. 1 dikostuk dikostuk  284 Mar 11 18:10 .
drwxr-xr-x. 1 root     root     1534 Mar 11 18:04 ..
-rw-r--r--. 1 dikostuk dikostuk   18 Jul 23  2025 .bash_logout
-rw-r--r--. 1 dikostuk dikostuk  144 Jul 23  2025 .bash_profile
-rw-r--r--. 1 dikostuk dikostuk  522 Jul 23  2025 .bashrc
drwx------. 1 dikostuk dikostuk  354 Mar 11 18:06 .cache
drwx------. 1 dikostuk dikostuk  282 Mar 11 18:10 .config
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Desktop
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Documents
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Downloads
-rw-r--r--. 1 dikostuk dikostuk  231 Mar 11 18:09 .gitconfig
drwx------. 1 dikostuk dikostuk  136 Mar 11 18:09 .gnupg
drwx------. 1 dikostuk dikostuk   20 Mar 11 18:05 .local
drwxr-xr-x. 1 dikostuk dikostuk   34 Oct 23 07:05 .mozilla
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Music
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Pictures
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Public
drwx------. 1 dikostuk dikostuk  132 Mar 11 18:10 .ssh
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Templates
drwxr-xr-x. 1 dikostuk dikostuk    0 Mar 11 18:05 Videos
drwxr-xr-x. 1 dikostuk dikostuk   10 Mar 11 18:10 work
dikostuk@dikostuk:~$
```

Рисунок 7: Файлы в домашнем каталоге

Работа с каталогами

```
dikostuk@dikostuk:~$
dikostuk@dikostuk:~$ mkdir newdir
dikostuk@dikostuk:~$ mkdir newdir/morefun
dikostuk@dikostuk:~$ mkdir letters memos misk
dikostuk@dikostuk:~$ ls
Desktop    Downloads  memos  Music   Pictures  Templates  work
Documents  letters    misk   newdir  Public    Videos
dikostuk@dikostuk:~$ rm letters/ memos/ misk/
rm: cannot remove 'letters/': Is a directory
rm: cannot remove 'memos/': Is a directory
rm: cannot remove 'misk/': Is a directory
dikostuk@dikostuk:~$ rm -r letters/ memos/ misk/
dikostuk@dikostuk:~$ rm -r newdir/
dikostuk@dikostuk:~$ ls
Desktop  Documents  Downloads  Music  Pictures  Public  Templates  Videos  work
dikostuk@dikostuk:~$
```

Рисунок 8: Действия с каталогами

Опции команды ls

```
'./work/study/2025-2026/Операционные системы/2026-1--study--os-intro/template/report/report/i
mage':
solvay.jpg

'./work/study/2025-2026/Операционные системы/2026-1--study--os-intro/template/report/report/_
resources':
csl  tex

'./work/study/2025-2026/Операционные системы/2026-1--study--os-intro/template/report/report/_
resources/csl':
gost-r-7-0-5-2008-numeric.csl

'./work/study/2025-2026/Операционные системы/2026-1--study--os-intro/template/report/report/_
resources/tex':
preamble.tex

'./work/study/2025-2026/Операционные системы/2026-1--study--os-intro/template/report/scripts'
:
image-report  mpv-shot
dikostuk@dikostuk:~$ ls -t
work  Desktop  Documents  Downloads  Music  Pictures  Public  Templates  Videos
dikostuk@dikostuk:~$
```

Рисунок 9: Команда ls -R и ls -t

Справка по командам

```
BASH_BUILTINS(1)                General Commands Manual                BASH_BUILTINS(1)

NAME
       :, ., [, alias, bg, bind, break, builtin, caller, cd, command, compgen, complete, compopt,
       continue,  declare,  dirs,  disown, echo, enable, eval, exec, exit, export, false, fc, fg,
       getopts, hash, help, history, jobs, kill,  let,  local,  logout,  mapfile,  popd,  printf,
       pushd,  pwd,  read, readarray, readonly, return, set, shift, shopt, source, suspend, test,
       times, trap, true, type, typeset, ulimit, umask, unalias, unset, wait - bash built-in com-
       mands, see bash(1)

BASH BUILTIN COMMANDS
       Unless otherwise noted, each builtin command documented in this section as  accepting  op-
       tions preceded by - accepts -- to signify the end of the options.  The :, true, false, and
       test/[  builtins  do  not accept options and do not treat -- specially.  The exit, logout,
       return, break, continue, let, and shift builtins accept and  process  arguments  beginning
       with  -  without requiring --.  Other builtins that accept arguments but are not specified
       as accepting options interpret arguments beginning with - as invalid options  and  require
       -- to prevent this interpretation.

       : [arguments]
              No  effect;  the command does nothing beyond expanding arguments and performing any
              specified redirections.  The return status is zero.

       . [-p path] filename [arguments]
       source [-p path] filename [arguments]
              The . command (source) reads and execute commands  from  filename  in  the  current
              shell  environment  and  returns  the exit status of the last command executed from
              filename.
 Manual page cd(1) line 1 (press h for help or q to quit)
```

Рисунок 10: Справка по команде cd

Справка по командам

```
PWD(1)                                User Commands                                PWD(1)

NAME
       pwd - print name of current/working directory

SYNOPSIS
       pwd [OPTION]...

DESCRIPTION
       Print the full filename of the current working directory.

       -L, --logical
              use PWD from environment, even if it contains symlinks

       -P, --physical
              resolve all symlinks

       --help display this help and exit

       --version
              output version information and exit

       If no option is specified, -P is assumed.

       Your shell may have its own version of pwd, which usually supersedes the version described
       here.   Please  refer  to your shell's documentation for details about the options it sup-
       ports.

 Manual page pwd(1) line 1 (press h for help or q to quit)
```

Рисунок 11: Справка по команде pwd

Справка по командам

```
MKDIR(1)                                User Commands                                MKDIR(1)

NAME
       mkdir - make directories

SYNOPSIS
       mkdir [OPTION]... DIRECTORY...

DESCRIPTION
       Create the DIRECTORY(ies), if they do not already exist.

       Mandatory arguments to long options are mandatory for short options too.

       -m, --mode=MODE
              set file mode (as in chmod), not a=rwx - umask

       -p, --parents
              no  error if existing, make parent directories as needed, with their file modes un-
              affected by any -m option

       -v, --verbose
              print a message for each created directory

       -Z     set SELinux security context of each created directory to the default type

       --context[=CTX]
              like -Z, or if CTX is specified then set the SELinux or SMACK security  context  to
              CTX
 Manual page mkdir(1) line 1 (press h for help or q to quit)
```

Рисунок 12: Справка по команде mkdir

Справка по командам

```
RMDIR(1)                          User Commands                          RMDIR(1)

NAME
       rmdir - remove empty directories

SYNOPSIS
       rmdir [OPTION]... DIRECTORY...

DESCRIPTION
       Remove the DIRECTORY(ies), if they are empty.

       --ignore-fail-on-non-empty
              ignore each failure to remove a non-empty directory

       -p, --parents
              remove  DIRECTORY  and its ancestors; e.g., 'rmdir -p a/b' is similar to 'rmdir a/b
              a'

       -v, --verbose
              output a diagnostic for every directory processed

       --help display this help and exit

       --version
              output version information and exit

AUTHOR
       Written by David MacKenzie.
 Manual page rmdir(1) line 1 (press h for help or q to quit)
```

Рисунок 13: Справка по команде rmdir

Справка по командам

```
RM(1)                                User Commands                                RM(1)

NAME
       rm - remove files or directories

SYNOPSIS
       rm [OPTION]... [FILE]...

DESCRIPTION
       This manual page documents the GNU version of rm.  rm removes each specified file.  By de-
       fault, it does not remove directories.

       If  the  -I  or --interactive=once option is given, and there are more than three files or
       the -r, -R, or --recursive are given, then rm prompts the user for whether to proceed with
       the entire operation.  If the response is not affirmative, the entire command is aborted.

       Otherwise, if a file is unwritable, standard input is a terminal, and the  -f  or  --force
       option  is  not  given,  or the -i or --interactive=always option is given, rm prompts the
       user for whether to remove the file.  If the response is  not  affirmative,  the  file  is
       skipped.

OPTIONS
       Remove (unlink) the FILE(s).

       -f, --force
              ignore nonexistent files and arguments, never prompt

       -i     prompt before every removal
 Manual page rm(1) line 1 (press h for help or q to quit)
```

Рисунок 14: Справка по команде rm

История командной строки

```
276  cd /tmp
277  ls
278  ls -a
279  ls -l
280  ls -f
281  cd /var/spool/
282  ls -l
283  cd
284  ls
285  ls -al
286  mkdir newdir
287  mkdir newdir/morefun
288  mkdir letters memos misk
289  ls
290  rm letters/ memos/ misk/
291  rm -r letters/ memos/ misk/
292  rm -r newdir/
293  ls
294  ls -R
295  ls -t
296  help cd
297  man pwd
298  man mkdir
```

Рисунок 15: Команда history

3. Выводы по проделанной работе

Вывод

Мы приобрели практические навыки взаимодействия пользователя с системой посредством командной строки.