

KATALYST.

Full-Stack Learning & Mentorship Platform

Complete Source Code, System Architecture & File Documentation

PROJECT SUMMARY METRICS

Platform Version:	2.0.0 (Production Architecture)	Backend Framework:	Node.js 20+ / Express.js 5
Frontend Stack:	React 19, Vite, Tailwind CSS	Database:	MongoDB Atlas (Mongoose ORM)
Total Source Files:	99 files included	Security:	JWT Authentication & RBAC
Frontend Files:	52 modules & views	Backend Files:	45 controllers, routes, models

1. Executive Summary

Katalyst is a full-stack educational and mentorship platform engineered to connect students with professional mentors while facilitating structured technical training and career acceleration. The application features three distinct role-based portals (Student, Mentor, Admin), comprehensive training tracks with video lessons and quizzes, 1-on-1 meeting scheduling with Google Meet links, real-time notification drawers, AI-assisted career roadmaps, and resume evaluation.

2. Document Table of Contents

Section	Topic	Coverage
Section 1	Executive Summary & System Architecture	High-level overview & system design
Section 2	Technology Stack & Layer Mapping	Frontend, backend, database, and auth stack
Section 3	Complete File Directory Inventory	All project files categorized with paths & sizes
Section 4	Backend Architecture & Data Models	Mongoose schemas, controllers, and REST routes
Section 5	Frontend Architecture & Portal Pages	React components, state contexts, and routes
Section 6	API Reference & Access Control Matrix	All REST endpoints, request/response models
Section 7	Complete Source Code Listings	Full file contents and implementations

3. Architecture & Technology Stack

Layer	Technology	Role & Purpose
Frontend Core	React 19.0.0 + Vite 8.2.0	Fast modular SPA client with lightning HMR
Styling Framework	Tailwind CSS 3.4 + PostCSS	Custom theme tokens, glassmorphism UI, Dark mode
Routing & Nav	React Router v7	Declarative browser routing & protected role routes
State Management	React Context (Auth & Theme)	Global authentication persistence & theme switches
Data Visualization	Recharts 2.15	Interactive progress rings & readiness index charts
Icons & UI	Lucide React 1.31	Feather-style SVG icon system across all portals
Backend Runtime	Node.js 20+ / Express 5.2	Non-blocking RESTful API & middleware pipeline
Database Store	MongoDB Atlas / Mongoose 9.9	Schema validation, indexing, and object relations
Authentication	JWT (jsonwebtoken 9.0) + bcryptjs	Stateless bearer token authorization & password hashing
AI Services	Google Generative AI (Gemini 1.5)	Resume analysis, personalized roadmaps & chat
File Handling	Multer Middleware	Local disk storage for student PDF resumes
Containerization	Docker & Docker Compose	Multi-stage build Dockerfiles for full-stack isolation

4. Complete File Inventory List

Total registered source and configuration files in this build: 99

Category	Relative File Path	Size
Backend	backend/.env	0.3 KB
Backend	backend/.env.example	0.3 KB
Backend	backend/config/db.js	0.3 KB
Backend	backend/controllers/adminController.js	7.3 KB
Backend	backend/controllers/aiController.js	10.5 KB
Backend	backend/controllers/authController.js	9.1 KB
Backend	backend/controllers/createMentor.js	1.3 KB
Backend	backend/controllers/meetingController.js	6.6 KB
Backend	backend/controllers/mentorController.js	7.2 KB
Backend	backend/controllers/notificationController.js	1.8 KB
Backend	backend/controllers/progressController.js	3.0 KB
Backend	backend/controllers/studentController.js	5.1 KB
Backend	backend/controllers/trainingController.js	7.5 KB
Backend	backend/createMentor.js	0.0 KB
Backend	backend/Dockerfile	0.1 KB
Backend	backend/generate_all_files_pdf.js	22.3 KB
Backend	backend/generate_pdf.js	0.1 KB
Backend	backend/middleware/auth.js	0.6 KB

Category	Relative File Path	Size
Backend	backend/middleware/roleCheck.js	0.3 KB
Backend	backend/models/Admin.js	1.1 KB
Backend	backend/models/Certificate.js	0.7 KB
Backend	backend/models/Feedback.js	0.8 KB
Backend	backend/models/Meeting.js	1.1 KB
Backend	backend/models/Mentor.js	1.7 KB
Backend	backend/models/Notification.js	0.7 KB
Backend	backend/models/Progress.js	1.2 KB
Backend	backend/models/Student.js	1.6 KB
Backend	backend/models/Training.js	1.6 KB
Backend	backend/models/user.js	0.4 KB
Backend	backend/package.json	0.9 KB
Backend	backend/routes/admin.js	0.9 KB
Backend	backend/routes/ai.js	0.6 KB
Backend	backend/routes/auth.js	0.4 KB
Backend	backend/routes/meeting.js	0.9 KB
Backend	backend/routes/mentor.js	0.6 KB
Backend	backend/routes/notification.js	0.4 KB
Backend	backend/routes/progress.js	0.6 KB
Backend	backend/routes/student.js	1.3 KB
Backend	backend/routes/training.js	0.9 KB
Backend	backend/seed.js	3.9 KB
Backend	backend/server.js	2.7 KB
Backend	backend/utlis/generateToken.js	0.2 KB
Backend	backend/utlis/progressCalculator.js	1.5 KB
Backend	backend/utlis/progressService.js	1.7 KB
Backend	backend/utlis/sendEmail.js	2.5 KB
Root Config	docker-compose.yml	0.6 KB
Frontend	frontend/.env.example	0.0 KB
Frontend	frontend/capacitor.config.json	0.1 KB
Frontend	frontend/Dockerfile	0.2 KB
Frontend	frontend/eslint.config.js	0.6 KB
Frontend	frontend/index.html	0.4 KB
Frontend	frontend/package.json	0.5 KB
Frontend	frontend/postcss.config.js	0.1 KB
Frontend	frontend/public/Login.css	2.2 KB
Frontend	frontend/README.md	1.0 KB
Frontend	frontend/src/api.js	0.7 KB
Frontend	frontend/src/App.css	5.6 KB
Frontend	frontend/src/App.jsx	4.4 KB
Frontend	frontend/src/components/CalendarView.jsx	5.0 KB

Category	Relative File Path	Size
Frontend	frontend/src/components/ChatBot.jsx	3.1 KB
Frontend	frontend/src/components/layout/DashboardLayout.jsx	2.5 KB
Frontend	frontend/src/components/layout/Sidebar.jsx	5.6 KB
Frontend	frontend/src/components/NotificationPanel.jsx	2.6 KB
Frontend	frontend/src/components/NotificationsPage.jsx	4.4 KB
Frontend	frontend/src/components/ProtectedRoute.jsx	0.6 KB
Frontend	frontend/src/components/ThemeToggle.jsx	0.4 KB
Frontend	frontend/src/components/ui/StatCard.jsx	0.7 KB
Frontend	frontend/src/context/AuthContext.jsx	1.1 KB
Frontend	frontend/src/context/ThemeContext.jsx	0.7 KB
Frontend	frontend/src/index.css	3.8 KB
Frontend	frontend/src/Login.css	2.2 KB
Frontend	frontend/src/Login.jsx	2.4 KB
Frontend	frontend/src/main.jsx	0.2 KB
Frontend	frontend/src/NotificationDrawer.jsx	0.0 KB
Frontend	frontend/src/pages/admin/Dashboard.jsx	3.6 KB
Frontend	frontend/src/pages/admin/Meetings.jsx	5.3 KB
Frontend	frontend/src/pages/admin/Mentors.jsx	4.1 KB
Frontend	frontend/src/pages/admin/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/admin/Reports.jsx	3.5 KB
Frontend	frontend/src/pages/admin/Students.jsx	3.7 KB
Frontend	frontend/src/pages/admin/Trainings.jsx	6.5 KB
Frontend	frontend/src/pages/Home.jsx	4.7 KB
Frontend	frontend/src/pages/Login.jsx	9.1 KB
Frontend	frontend/src/pages/mentor/Dashboard.jsx	5.0 KB
Frontend	frontend/src/pages/mentor/Meetings.jsx	6.3 KB
Frontend	frontend/src/pages/mentor/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/mentor/Students.jsx	4.2 KB
Frontend	frontend/src/pages/Register.jsx	5.4 KB
Frontend	frontend/src/pages/student/AIHub.jsx	8.0 KB
Frontend	frontend/src/pages/student/Certificates.jsx	2.8 KB
Frontend	frontend/src/pages/student/Dashboard.jsx	6.9 KB
Frontend	frontend/src/pages/student/Meetings.jsx	8.9 KB
Frontend	frontend/src/pages/student/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/student/Profile.jsx	4.6 KB
Frontend	frontend/src/pages/student/TrainingDetail.jsx	7.0 KB
Frontend	frontend/src/pages/student/Trainings.jsx	3.1 KB
Frontend	frontend/tailwind.config.js	0.8 KB
Frontend	frontend/vite.config.js	0.2 KB
Root Config	README.md	2.6 KB

6. API Endpoints Reference

Method	Endpoint Route	Role	Description
POST	/api/auth/register	Public	Student registration with bcrypt hashing
POST	/api/auth/login	Public	Unified login for student, mentor, admin (JWT)
GET	/api/auth/me	Auth	Get active profile based on JWT token
GET	/api/students/profile	Student	Get current student profile & mentor details
PUT	/api/students/profile	Student	Update student bio, skills, and target role
POST	/api/students/resume	Student	Upload student resume PDF via Multer
GET	/api/trainings	Public/Auth	List all available trainings and courses
GET	/api/trainings/:id	Auth	Get course modules, lessons, and student progress
POST	/api/trainings/:id/enroll	Student	Enroll in a training track
POST	/api/trainings/:id/complete-video	Student	Mark video lesson completed & update progress
POST	/api/trainings/:id/submit-quiz	Student	Submit quiz responses & calculate score
GET	/api/meetings/student	Student	Get all meetings booked by student
POST	/api/meetings	Student	Book a new meeting with assigned mentor
GET	/api/meetings/mentor	Mentor	Get all meeting requests assigned to mentor
PUT	/api/meetings/:id/status	Mentor	Approve/Reject meeting and supply Meet link
GET	/api/notifications	Auth	Fetch user notifications list
PUT	/api/notifications/:id/read	Auth	Mark notification as read
POST	/api/ai/resume-analyze	Student	AI resume strength & improvement analysis
POST	/api/ai/career-roadmap	Student	AI personalized milestone career roadmap
POST	/api/ai/chatbot	Auth	AI chatbot assistant for student guidance
GET	/api/admin/stats	Admin	Fetch system-wide metrics, counts & analytics
GET	/api/admin/users	Admin	List and manage all registered users

7. Complete Project Source Code

The following sections contain the complete, verbatim source code for each file in the project organized by subsystem.

```
1 | PORT=5000
2 | MONGO_URI=mongodb://127.0.0.1:27017/katalyst
3 | JWT_SECRET=katalyst_super_secret_jwt_key_2026_change_in_production
4 | JWT_EXPIRES_IN=7d
5 | NODE_ENV=development
6 | CLIENT_URL=http://localhost:5173
7 | # Email (Optional - for notifications)
8 | EMAIL_USER=your_email@gmail.com
9 | EMAIL_PASS=your_app_password_here (0.3 KB)
10 | MONGO_URI=mongodb+srv://<username>:<password>@<cluster>.mongodb.net/katalyst?retryWrites=true&w=majority
11 | JWT_SECRET=supersecretkey
12 | JWT_EXPIRES_IN=7d
13 | CLIENT_URL=http://localhost:4173
14 | EMAIL_USER=youremail@example.com
15 | EMAIL_PASS=your-email-password
16 | NODE_ENV=development
17 | PORT=5000 (0.3 KB)
18 |
19 | const mongoose = require("mongoose");
20 | const connectDB = async () => {
21 |   try {
22 |     const conn = await mongoose.connect(process.env.MONGO_URI);
23 |     console.log(` MongoDB Connected: ${conn.connection.host}`);
24 |   } catch (error) {
25 |     console.error(` MongoDB Connection Error: ${error.message}`);
26 |     process.exit(1);
27 |   }
28 | };
29 | module.exports = connectDB; (7.3 KB)
30 |
31 | const Student = require("../models/Student");
32 | const Mentor = require("../models/Mentor");
33 | const Training = require("../models/Training");
34 | const Meeting = require("../models/Meeting");
35 | const Progress = require("../models/Progress");
36 | const Certificate = require("../models/Certificate");
37 | const Notification = require("../models/Notification");
38 | // @desc Admin dashboard analytics
39 | // @route GET /api/admin/dashboard
40 | const getDashboard = async (req, res) => {
41 |   try {
42 |     const [
43 |       totalStudents,
44 |       totalMentors,
45 |       totalTrainings,
46 |       totalMeetings,
47 |       completedMeetings,
48 |       pendingMeetings,
49 |       totalCertificates,
50 |     ] = await Promise.all([
51 |       Student.countDocuments(),
52 |       Mentor.countDocuments(),
53 |       Training.countDocuments(),
54 |       Meeting.countDocuments(),
55 |       Meeting.countDocuments({ status: "completed" }),
56 |       Meeting.countDocuments({ status: "pending" }),
57 |       Certificate.countDocuments(),
58 |     ]);
59 |
60 |     // Monthly student registrations (last 6 months)
61 |     const sixMonthsAgo = new Date();
62 |     sixMonthsAgo.setMonth(sixMonthsAgo.getMonth() - 6);
63 |     const monthlyStudents = await Student.aggregate([
64 |       { $match: { createdAt: { $gte: sixMonthsAgo } } },
65 |       {
66 |         $group: {
```



```
38 |         _id: { $month: "$createdAt" },
39 |         count: { $sum: 1 },
40 |     },
41 | },
42 | { $sort: { _id: 1 } },
43 | ]);
44 |
45 | // Training enrollment stats
46 | const trainingStats = await Training.aggregate([
47 |     {
48 |         $project: {
49 |             title: 1,
50 |             category: 1,
51 |             enrollments: { $size: "$enrolledStudents" },
52 |         },
53 |     },
54 |     { $sort: { enrollments: -1 } },
55 |     { $limit: 5 },
56 | ]);
57 |
58 | res.json({
59 |     stats: {
60 |         totalStudents,
61 |         totalMentors,
62 |         totalTrainings,
63 |         totalMeetings,
64 |         completedMeetings,
65 |         pendingMeetings,
66 |         totalCertificates,
67 |     },
68 |     monthlyStudents,
69 |     topTrainings: trainingStats,
70 | });
71 | } catch (error) {
72 |     res.status(500).json({ message: "Server error", error: error.message });
73 | }
74 | };
75 |
76 | // @desc Get all students
77 | // @route GET /api/admin/students
78 | const getAllStudents = async (req, res) => {
79 |     try {
80 |         const students = await Student.find()
81 |             .select("-password")
82 |             .populate("assignedMentor", "name email")
83 |             .sort({ createdAt: -1 });
84 |         res.json({ students });
85 |     } catch (error) {
86 |         res.status(500).json({ message: "Server error", error: error.message });
87 |     }
88 | };
89 |
90 | // @desc Toggle student active status
91 | // @route PUT /api/admin/students/:id
92 | const updateStudent = async (req, res) => {
93 |     try {
94 |         const { isActive } = req.body;
95 |         const student = await Student.findByIdAndUpdate(
96 |             req.params.id,
97 |             { isActive },
98 |             { new: true }
99 |         ).select("-password");
100 |         res.json({ message: "Student updated", student });
101 |     } catch (error) {
102 |         res.status(500).json({ message: "Server error", error: error.message });
103 |     }
104 | };
105 |
106 | // @desc Delete student
107 | // @route DELETE /api/admin/students/:id
108 | const deleteStudent = async (req, res) => {
109 |     try {
110 |         await Student.findByIdAndDelete(req.params.id);
111 |         await Progress.deleteOne({ studentId: req.params.id });
112 |         res.json({ message: "Student deleted" });
113 |     } catch (error) {
114 |         res.status(500).json({ message: "Server error", error: error.message });
```

```
115 |   }
116 | };
117 |
118 | // @desc Get all mentors
119 | // @route GET /api/admin/mentors
120 | const getAllMentors = async (req, res) => {
121 |   try {
122 |     const mentors = await Mentor.find().select("-password").sort({ createdAt: -1 });
123 |     res.json({ mentors });
124 |   } catch (error) {
125 |     res.status(500).json({ message: "Server error", error: error.message });
126 |   }
127 | };
128 |
129 | // @desc Create mentor (admin only)
130 | // @route POST /api/admin/mentors
131 | const createMentor = async (req, res) => {
132 |   try {
133 |     const { name, email, password, expertise, designation, company, bio } = req.body;
134 |     const exists = await Mentor.findOne({ email });
135 |     if (exists) return res.status(400).json({ message: "Email already registered" });
136 |     const mentor = await Mentor.create({
137 |       name, email, password,
138 |       expertise: expertise ? expertise.split(",").map((s) => s.trim()) : [],
139 |       designation, company, bio,
140 |     });
141 |     res.status(201).json({ message: "Mentor created", mentor: { ...mentor.toObject(), password: undefined } });
142 |   } catch (error) {
143 |     res.status(500).json({ message: "Server error", error: error.message });
144 |   }
145 | };
146 |
147 | // @desc Delete mentor
148 | // @route DELETE /api/admin/mentors/:id
149 | const deleteMentor = async (req, res) => {
150 |   try {
151 |     await Mentor.findByIdAndDelete(req.params.id);
152 |     res.json({ message: "Mentor deleted" });
153 |   } catch (error) {
154 |     res.status(500).json({ message: "Server error", error: error.message });
155 |   }
156 | };
157 |
158 | // @desc Assign mentor to student
159 | // @route POST /api/admin/assign-mentor
160 | const assignMentor = async (req, res) => {
161 |   try {
162 |     const { studentId, mentorId } = req.body;
163 |     const student = await Student.findByIdAndUpdate(
164 |       studentId,
165 |       { assignedMentor: mentorId },
166 |       { new: true }
167 |     ).select("-password");
168 |     await Mentor.findByIdAndUpdate(mentorId, {
169 |       $addToSet: { assignedStudents: studentId },
170 |     });
171 |     const mentor = await Mentor.findById(mentorId);
172 |     // Notify student
173 |     await Notification.create({
174 |       userId: studentId,
175 |       userRole: "student",
176 |       title: "Mentor Assigned! 🎉",
177 |       message: `${mentor.name} has been assigned as your mentor. Say hello!`,
178 |       type: "system",
179 |     });
180 |     res.json({ message: "Mentor assigned successfully", student });
181 |   } catch (error) {
182 |     res.status(500).json({ message: "Server error", error: error.message });
183 |   }
184 | };
185 |
186 | // @desc Get reports
187 | // @route GET /api/admin/reports
188 | const getReports = async (req, res) => {
189 |   try {
190 |     const progressData = await Progress.find()
```

```
197 |         .populate("studentId", "name email")
198 |         .sort({ overallScore: -1 });
200 |     const meetingReport = await Meeting.aggregate([
201 |         { $group: { _id: "$status", count: { $sum: 1 } } },
202 |     ]);
204 |     const categoryEnrollment = await Training.aggregate([
205 |         {
206 |             $group: {
207 |                 _id: "$category",
208 |                 totalEnrollments: { $sum: { $size: "$enrolledStudents" } },
209 |             },
210 |         },
211 |     ]);
213 |     res.json({ progressData, meetingReport, categoryEnrollment });
214 | } catch (error) {
215 |     res.status(500).json({ message: "Server error", error: error.message });
216 | }
217 | };
219 | // @desc Send notification to all users of a role
220 | // @route POST /api/admin/notify
221 | const sendBulkNotification = async (req, res) => {
222 |     try {
223 |         const { title, message, userRole } = req.body;
224 |         let users = [];
225 |         if (userRole === "student") users = await Student.find().select("_id");
226 |         else if (userRole === "mentor") users = await Mentor.find().select("_id");
227 |         else {
228 |             const students = await Student.find().select("_id");
229 |             const mentors = await Mentor.find().select("_id");
230 |             users = [...students, ...mentors];
231 |         }
233 |         const notifications = users.map((u) => ({
234 |             userId: u._id,
235 |             userRole: userRole === "all" ? "student" : userRole,
236 |             title,
237 |             message,
238 |             type: "system",
239 |         }));
241 |         await Notification.insertMany(notifications);
242 |         res.json({ message: `Notification sent to ${users.length} users` });
243 |     } catch (error) {
244 |         res.status(500).json({ message: "Server error", error: error.message });
245 |     }
246 | };
248 | module.exports = {
249 |     getDashboard,
250 |     getAllStudents,
251 |     updateStudent,
252 |     deleteStudent,
253 |     getAllMentors,
254 |     createMentor,
255 |     deleteMentor,
256 |     assignMentor,
257 |     getReports,
258 |     sendBulkNotification,
259 | };
260 |
```

KATALYST

Source Code: backend/controllers/aiController.js

Generated: 22/8/2026 | Backend

(10.5 KB)

```
1 | const Student = require("../models/Student");
2 | const Training = require("../models/Training");
3 | const Progress = require("../models/Progress");
4 | const { GoogleGenerativeAI } = require("@google/generative-ai");
5 |
6 | // Helper to initialize Gemini model
7 | const getGeminiModel = () => {
8 |   const apiKey = process.env.GEMINI_API_KEY;
9 |   if (!apiKey || apiKey.startsWith("your_") || apiKey.includes("change_in_production")) {
10 |     return null;
11 |   }
12 |   try {
13 |     const genAI = new GoogleGenerativeAI(apiKey);
14 |     return genAI.getGenerativeModel({ model: "gemini-1.5-flash" });
15 |   } catch (error) {
16 |     console.error("& p Failed to initialize Google Generative AI:", error.message);
17 |     return null;
18 |   }
19 | };
20 |
21 | // Helper to clean JSON response from Gemini
22 | const cleanJSONResponse = (text) => {
23 |   // Remove markdown block tags if present
24 |   let cleaned = text.trim();
25 |   if (cleaned.startsWith("```")) {
26 |     cleaned = cleaned.replace(/^```json\s*/i, "").replace(/```$/, "").trim();
27 |   }
28 |   return JSON.parse(cleaned);
29 | };
30 |
31 | // @desc Analyze student resume
32 | // @route POST /api/ai/resume-analyze
33 | const analyzeResume = async (req, res) => {
34 |   try {
35 |     const { content } = req.body;
36 |     if (!content) return res.status(400).json({ message: "Resume content is required" });
37 |
38 |     // Try Gemini first
39 |     const model = getGeminiModel();
40 |     if (model) {
41 |       try {
42 |         const prompt = `Analyze the following resume content and output a valid JSON object.
43 | Do NOT wrap the response in markdown blocks (e.g. do not use \`\`\`json). The JSON object must contain exactly
44 | 1. "strengths": An array of strings highlighting the key technical and soft skill strengths.
45 | 2. "improvementAreas": An array of strings listing gaps or areas where the resume or experience can be enhance
46 | 3. "actionItems": An array of actionable steps for the student to improve their placement readiness.
47 | Resume Content:
48 | ${content}`;
49 |
50 |         const result = await model.generateContent(prompt);
51 |         const parsed = cleanJSONResponse(result.response.text());
52 |         return res.json({
53 |           strengths: parsed.strengths || [],
54 |           improvementAreas: parsed.improvementAreas || [],
55 |           actionItems: parsed.actionItems || [],
56 |         });
57 |       } catch (err) {
58 |         console.error("& p Gemini resume analysis failed, falling back to rule-based:", err.message);
59 |       }
60 |     }
61 |
62 |     // Fallback rule-based analysis
63 |     const strengths = [];
64 |     const areas = [];
65 |     const recommendations = [];
66 |
67 |     if (/react|javascript|frontend|html|css/i.test(content)) strengths.push("Frontend development expertise");
68 |     if (/node|express|backend|api/i.test(content)) strengths.push("Backend and API development experience");
69 |     if (/data|sql|mongodb|database/i.test(content)) strengths.push("Data management and database skills");
70 |     if (/design|ui|ux/i.test(content)) strengths.push("UI/UX and product design awareness");
71 |     if (/project/i.test(content)) areas.push("Add project work or portfolio examples");
72 |     if (/github|github\.com/i.test(content)) areas.push("Include GitHub or code repository links");
73 |     if (/lead|team|mentor/i.test(content)) areas.push("Mention collaboration, leadership, or mentorship activ
74 |
75 |     if (/intern|junior|entry/i.test(content)) recommendations.push("Apply to junior and internship roles for f
76 |
77 |     if (!strengths.length) strengths.push("Strong foundational skills are visible.");
78 |     if (!areas.length) areas.push("Highlight measurable impact and completed projects.");
79 |
80 |     res.json({
81 |       strengths,
```

```
82 |     improvementAreas: areas,
83 |     actionItems: [
84 |       "Update resume with specific project accomplishments.",
85 |       "Add portfolio or GitHub links.",
86 |       "Share results and metrics for each learning milestone.",
87 |     ].concat(recommendations),
88 |   });
89 | } catch (error) {
90 |   res.status(500).json({ message: "Server error", error: error.message });
91 | }
92 | };
93 |
94 | // @desc Generate career roadmap
95 | // @route POST /api/ai/career-roadmap
96 | const careerRoadmap = async (req, res) => {
97 |   try {
98 |     const student = await Student.findById(req.user.id).select("name skills assignedMentor");
99 |     const progress = await Progress.findOne({ studentId: req.user.id });
100 |     const enrolledTrainings = await Training.find({ "enrolledStudents.studentId": req.user.id }).select("title
101 |
102 |     // Try Gemini first
103 |     const model = getGeminiModel();
104 |     if (model) {
105 |       try {
106 |         const prompt = `Generate a customized career roadmap for student "${student.name}".
107 | Skills: ${JSON.stringify(student.skills || [])}
108 | Enrolled Courses: ${JSON.stringify(enrolledTrainings.map(t => t.title))}
109 | Placement Readiness: ${progress?.placementReadiness || 0}%
110 |
111 | Output a valid JSON array of objects representing roadmap milestones.
112 | Do NOT wrap the response in markdown blocks (e.g. do not use ```json). Each object must have exactly these
113 | 1. "title": A short title for the milestone.
114 | 2. "description": A brief actionable description of what the student needs to do.
115 | 3. "daysFromNow": An integer representing how many days from today this milestone should ideally be completed.
116 |
117 | Return at least 3 milestones.`;
118 |
119 |         const result = await model.generateContent(prompt);
120 |         const parsed = cleanJSONResponse(result.response.text());
121 |         const roadmap = parsed.map(step => ({
122 |           title: step.title,
123 |           description: step.description,
124 |           dueDate: new Date(Date.now() + (step.daysFromNow || 14) * 24 * 60 * 60 * 1000),
125 |         }));
126 |
127 |         return res.json({
128 |           student: student.name,
129 |           skills: student.skills,
130 |           currentMentor: student.assignedMentor || null,
131 |           trainings: enrolledTrainings,
132 |           roadmap,
133 |         });
134 |       } catch (err) {
135 |         console.error("& p Gemini roadmap generation failed, falling back:", err.message);
136 |       }
137 |     }
138 |
139 |     // Fallback roadmap
140 |     const roadmap = [
141 |       {
142 |         title: "Strengthen foundational skills",
143 |         description: "Complete active trainings and finish remaining video modules.",
144 |         dueDate: new Date(Date.now() + 14 * 24 * 60 * 60 * 1000),
145 |       },
146 |       {
147 |         title: "Book mentor reviews",
148 |         description: "Schedule at least two mentoring sessions focused on projects and resume readiness.",
149 |         dueDate: new Date(Date.now() + 21 * 24 * 60 * 60 * 1000),
150 |       },
151 |       {
152 |         title: "Build a portfolio project",
153 |         description: "Create one end-to-end project using current learning topics and publish it on GitHub.",
154 |         dueDate: new Date(Date.now() + 35 * 24 * 60 * 60 * 1000),
155 |       },
156 |     ];
157 |
158 |     if (progress && progress.placementReadiness < 60) {
159 |       roadmap.push({
160 |         title: "Raise placement readiness",
```

```
161 |         description: "Focus on quizzes, mentor feedback, and resume improvements to reach 70+ readiness.",
162 |         dueDate: new Date(Date.now() + 45 * 24 * 60 * 60 * 1000),
163 |     });
164 | }
165 |
166 | res.json({
167 |     student: student.name,
168 |     skills: student.skills,
169 |     currentMentor: student.assignedMentor || null,
170 |     trainings: enrolledTrainings,
171 |     roadmap,
172 | });
173 | } catch (error) {
174 |     res.status(500).json({ message: "Server error", error: error.message });
175 | }
176 | };
177 |
178 | // @desc Scholarship recommendations
179 | // @route POST /api/ai/scholarships
180 | const scholarshipRecommendations = async (req, res) => {
181 |     try {
182 |         const { interests = [] } = req.body;
183 |         // Try Gemini first
184 |         const model = getGeminiModel();
185 |         if (model) {
186 |             try {
187 |                 const prompt = `Recommend targeted scholarships for a student with interests: ${JSON.stringify(interests)}
188 | Output a valid JSON array of objects representing recommended scholarships.
189 | Do NOT wrap the response in markdown blocks (e.g. do not use ```json). Each object must have exactly these
190 | 1. "name": The name of the scholarship.
191 | 2. "description": A description of the scholarship, eligibility requirements, and value.
192 | 3. "category": The scholarship category (e.g. Technology, Diversity, AI/ML, General).
193 | Return at least 3 recommendations.`;
194 |
195 |                 const result = await model.generateContent(prompt);
196 |                 const parsed = cleanJSONResponse(result.response.text());
197 |                 return res.json({ recommendations: parsed });
198 |             } catch (err) {
199 |                 console.error("& p Gemini scholarship search failed, falling back:", err.message);
200 |             }
201 |         }
202 |         // Fallback scholarship logic
203 |         const recommendations = [
204 |             {
205 |                 name: "Future Leaders Scholarship",
206 |                 description: "Designed for students building strong full-stack portfolios.",
207 |                 category: "Technology",
208 |             },
209 |             {
210 |                 name: "Women in Tech Assistance",
211 |                 description: "Support for female learners focusing on coding and mentorship.",
212 |                 category: "Diversity",
213 |             },
214 |             {
215 |                 name: "AI Learning Grant",
216 |                 description: "For students preparing for machine learning or data science pathways.",
217 |                 category: "AI/ML",
218 |             },
219 |         ];
220 |         const filtered = interests.length
221 |             ? recommendations.filter((r) =>
222 |                 interests.some((interest) => r.category.toLowerCase().includes(interest.toLowerCase()))
223 |             )
224 |             : recommendations;
225 |         res.json({ recommendations: filtered.length ? filtered : recommendations });
226 |     } catch (error) {
227 |         res.status(500).json({ message: "Server error", error: error.message });
228 |     }
229 | };
230 |
231 | // @desc AI Assistant Chatbot
232 | // @route POST /api/ai/chatbot
233 | const assistantChat = async (req, res) => {
234 |     try {
235 |         const { question } = req.body;
```

```
241 |     if (!question) return res.status(400).json({ message: "Question is required" });
243 |     // Try Gemini first
244 |     const model = getGeminiModel();
245 |     if (model) {
246 |         try {
247 |             const prompt = `You are "Katalyst AI", a helpful, friendly, and smart career and learning assistant on
248 | Provide a concise, encouraging, and actionable answer to the student's question under 120 words.
250 | Student Question: "${question}"`;
252 |             const result = await model.generateContent(prompt);
253 |             return res.json({ answer: result.response.text().trim() });
254 |         } catch (err) {
255 |             console.error("& p Gemini chatbot failed, falling back:", err.message);
256 |         }
257 |     }
259 |     // Fallback chatbot answer
260 |     const answer = `Hi there! I am Katalyst AI (fallback mode).
261 | To help with your query: "${question}" - we recommend scheduling a session with your assigned mentor, finishin
262 | res.json({ answer });
263 |     } catch (error) {
264 |         res.status(500).json({ message: "Server error", error: error.message });
265 |     }
266 | };
268 | module.exports = { analyzeResume, careerRoadmap, scholarshipRecommendations, assistantChat };
269 |
1 | const Student = require("../models/Student");
2 | const Mentor = require("../models/Mentor");
3 | const Admin = require("../models/Admin");
4 | const Progress = require("../models/Progress");
5 | const Notification = require("../models/Notification");
6 | const generateToken = require("../utils/generateToken");
8 | // =====
9 | // REGISTER STUDENT
10 | // POST /api/auth/register
11 | // =====
12 | // =====
13 | // REGISTER USER (Student, Mentor, or Admin)
14 | // POST /api/auth/register
15 | // =====
16 | const registerStudent = async (req, res) => {
17 |     try {
18 |         console.log("REGISTER REQUEST:", req.body);
20 |         const { name, email, password, phone, role = "student" } = req.body;
22 |         // Validate required fields
23 |         if (!name || !email || !password) {
24 |             return res.status(400).json({
25 |                 message: "Name, email and password are required",
26 |             });
27 |         }
29 |         // Clean email
30 |         const cleanEmail = email.trim().toLowerCase();
31 |         const targetRole = ["student", "mentor", "admin"].includes(role) ? role : "student";
33 |         // Check existing across all collections
34 |         const [existingStudent, existingMentor, existingAdmin] = await Promise.all([
35 |             Student.findOne({ email: cleanEmail }),
36 |             Mentor.findOne({ email: cleanEmail }),
37 |             Admin.findOne({ email: cleanEmail }),
38 |         ]);
40 |         if (existingStudent || existingMentor || existingAdmin) {
41 |             return res.status(400).json({
42 |                 message: "Email already registered",
43 |             });
44 |         }
46 |         let newUser;
48 |         if (targetRole === "admin") {
49 |             newUser = await Admin.create({
50 |                 name: name.trim(),
51 |                 email: cleanEmail,
52 |                 password,
53 |             });
54 |         } else if (targetRole === "mentor") {
```

```
55 |         newUser = await Mentor.create({
56 |             name: name.trim(),
57 |             email: cleanEmail,
58 |             password,
59 |             phone: phone || "",
60 |             expertise: ["Web Development", "Mentorship"],
61 |             designation: "Senior Mentor",
62 |             company: "Katalyst",
63 |         });
64 |     } else {
65 |         newUser = await Student.create({
66 |             name: name.trim(),
67 |             email: cleanEmail,
68 |             password,
69 |             phone: phone || "",
70 |         });
71 |         // Create progress & welcome notification for student
72 |         try {
73 |             await Progress.create({ studentId: newUser._id });
74 |         } catch (err) {}
75 |         try {
76 |             await Notification.create({
77 |                 userId: newUser._id,
78 |                 userRole: "student",
79 |                 title: "Welcome to Katalyst! 🎉",
80 |                 message: "Your account is ready. Start exploring trainings and book your first mentorship session!",
81 |                 type: "system",
82 |             });
83 |         } catch (err) {}
84 |     }
85 |     console.log("USER CREATED:", newUser._id, targetRole);
86 |     return res.status(201).json({
87 |         message: "Registration successful",
88 |         token: generateToken(newUser._id, targetRole),
89 |         user: {
90 |             id: newUser._id,
91 |             name: newUser.name,
92 |             email: newUser.email,
93 |             role: targetRole,
94 |             profilePic: newUser.profilePic || "",
95 |         },
96 |     });
97 | } catch (error) {
98 |     console.error("REGISTER ERROR:", error);
99 |     return res.status(500).json({
100 |         message: "Registration failed",
101 |         error: error.message,
102 |     });
103 | }
104 | };
105 |
106 | // =====
107 | // LOGIN (With Multi-Role Auto-Provisioning on Valid Password)
108 | // POST /api/auth/login
109 | // =====
110 | const login = async (req, res) => {
111 |     try {
112 |         console.log("LOGIN REQUEST:", req.body);
113 |         const { email, password, role } = req.body;
114 |         if (!email || !password) {
115 |             return res.status(400).json({
116 |                 message: "Email and password are required",
117 |             });
118 |         }
119 |         const cleanEmail = email.trim().toLowerCase();
120 |         const cleanPass = password.trim();
121 |         const targetRole = role || "student";
122 |         // 1. Search across all collections for existing account
123 |         let student = await Student.findOne({ email: cleanEmail });
124 |         let mentor = await Mentor.findOne({ email: cleanEmail });
125 |         let admin = await Admin.findOne({ email: cleanEmail });
126 |         let existingUser = student || mentor || admin;
```


KATALYST

Source Code: backend/controllers/authController.js (Cont.)

Generated: 22/8/2026 | Backend

```
137 | // Not found anywhere
138 | if (!existingUser) {
139 |   return res.status(401).json({
140 |     message: `No account registered with ${cleanEmail}. Please create an account first.`,
141 |   });
142 | }
143 |
144 | // 2. Check password against existing user
145 | if (!existingUser.matchPassword) {
146 |   return res.status(500).json({
147 |     message: "Password authentication misconfigured in user model",
148 |   });
149 | }
150 |
151 | const passwordCorrect = await existingUser.matchPassword(cleanPass);
152 |
153 | if (!passwordCorrect) {
154 |   return res.status(401).json({
155 |     message: "Incorrect password. Please try again or click Forgot Password.",
156 |   });
157 | }
158 |
159 | // 3. Password is valid! Provision/Resolve target role profile if needed
160 | let userToLogin = null;
161 | let actualRole = targetRole;
162 |
163 | if (targetRole === "admin") {
164 |   if (!admin) {
165 |     admin = await Admin.create({
166 |       name: existingUser.name,
167 |       email: cleanEmail,
168 |       password: cleanPass,
169 |     });
170 |   }
171 |   userToLogin = admin;
172 |   actualRole = "admin";
173 | } else if (targetRole === "mentor") {
174 |   if (!mentor) {
175 |     mentor = await Mentor.create({
176 |       name: existingUser.name,
177 |       email: cleanEmail,
178 |       password: cleanPass,
179 |       phone: existingUser.phone || "",
180 |       expertise: ["Web Development", "Mentorship"],
181 |       designation: "Senior Mentor",
182 |       company: "Katalyst",
183 |     });
184 |   }
185 |   userToLogin = mentor;
186 |   actualRole = "mentor";
187 | } else {
188 |   if (!student) {
189 |     student = await Student.create({
190 |       name: existingUser.name,
191 |       email: cleanEmail,
192 |       password: cleanPass,
193 |       phone: existingUser.phone || "",
194 |     });
195 |     try { await Progress.create({ studentId: student._id }); } catch (err) {}
196 |   }
197 |   userToLogin = student;
198 |   actualRole = "student";
199 | }
200 |
201 | // Check active state
202 | if (!userToLogin.isActive && actualRole !== "admin") {
203 |   return res.status(403).json({
204 |     message: "Account is deactivated",
205 |   });
206 | }
207 |
208 | // Update student last login
209 | if (actualRole === "student") {
210 |   userToLogin.lastLogin = new Date();
211 |   await userToLogin.save();
212 | }
213 |
214 | // Generate JWT with actualRole
215 | const token = generateToken(userToLogin._id, actualRole);
```

```
217 |     console.log("LOGIN SUCCESS:", userToLogin.email, actualRole);
219 |     return res.status(200).json({
220 |       message: "Login successful",
221 |       token,
222 |       user: {
223 |         id: userToLogin._id,
224 |         name: userToLogin.name,
225 |         email: userToLogin.email,
226 |         role: actualRole,
227 |         profilePic: userToLogin.profilePic || "",
228 |       },
229 |     });
230 |   } catch (error) {
231 |     console.error("LOGIN ERROR:", error);
232 |     return res.status(500).json({
233 |       message: "Login failed",
234 |       error: error.message,
235 |     });
236 |   }
237 | };
239 | // =====
240 | // GET CURRENT USER
241 | // GET /api/auth/me
242 | // =====
243 | const getMe = async (req, res) => {
244 |   try {
245 |     const { id, role } = req.user;
247 |     let user;
249 |     if (role === "student") {
250 |       user = await Student.findById(id)
251 |         .select("-password")
252 |         .populate(
253 |           "assignedMentor",
254 |           "name email expertise profilePic"
255 |         );
256 |     } else if (role === "mentor") {
257 |       user = await Mentor.findById(id).select("-password");
258 |     } else if (role === "admin") {
259 |       user = await Admin.findById(id).select("-password");
260 |     } else {
261 |       return res.status(400).json({
262 |         message: "Invalid user role",
263 |       });
264 |     }
266 |     if (!user) {
267 |       return res.status(404).json({
268 |         message: "User not found",
269 |       });
270 |     }
272 |     return res.status(200).json({
273 |       user: {
274 |         ...user.toObject(),
275 |         role,
276 |       },
277 |     });
278 |   } catch (error) {
279 |     console.error("GET ME ERROR:", error);
281 |     return res.status(500).json({
282 |       message: "Server error",
283 |       error: error.message,
284 |     });
285 |   }
286 | };
288 | // =====
289 | // RESET PASSWORD
290 | // POST /api/auth/reset-password
291 | // =====
292 | const resetPassword = async (req, res) => {
293 |   try {
294 |     const { email, newPassword } = req.body;
295 |     if (!email || !newPassword) {
```

```
296 |     return res.status(400).json({ message: "Email and new password are required" });
297 |   }
299 |   const cleanEmail = email.trim().toLowerCase();
301 |   const [student, mentor, admin] = await Promise.all([
302 |     Student.findOne({ email: cleanEmail }),
303 |     Mentor.findOne({ email: cleanEmail }),
304 |     Admin.findOne({ email: cleanEmail }),
305 |   ]);
307 |   const targetUser = student || mentor || admin;
309 |   if (!targetUser) {
310 |     return res.status(404).json({ message: "No account found with this email" });
311 |   }
313 |   targetUser.password = newPassword;
314 |   await targetUser.save();
316 |   return res.json({ message: "Password reset successful! You can now log in." });
317 | } catch (error) {
318 |   return res.status(500).json({ message: "Server error", error: error.message });
319 | }
320 | };
322 | module.exports = {
323 |   registerStudent,
324 |   login,
325 |   getMe,
326 |   resetPassword,
327 | }; (1.3 KB)

1 | const mongoose = require("mongoose");
2 | const Mentor = require("../models/Mentor");
3 | require("dotenv").config();
5 | async function createMentor() {
6 |   try {
7 |     await mongoose.connect(process.env.MONGO_URI);
9 |     console.log("MongoDB connected");
11 |     const email = "sarah@katalyst.io";
13 |     const existing = await Mentor.findOne({ email });
15 |     if (existing) {
16 |       console.log("Mentor already exists:", existing.email);
17 |       await mongoose.disconnect();
18 |       return;
19 |     }
21 |     const mentor = await Mentor.create({
22 |       name: "Sarah Mentor",
23 |       email: "sarah@katalyst.io",
24 |       password: "Mentor@123",
25 |       phone: "9876543210",
26 |       bio: "Experienced Katalyst mentor",
27 |       profilePic: "",
28 |       expertise: ["Web Development", "JavaScript", "React"],
29 |       designation: "Senior Mentor",
30 |       company: "Katalyst",
31 |       role: "mentor",
32 |       isActive: true,
33 |       assignedStudents: [],
34 |       rating: 0,
35 |       totalRatings: 0,
36 |       availability: [],
37 |     });
39 |     console.log("MENTOR CREATED");
40 |     console.log("Email:", mentor.email);
41 |     console.log("Password: Mentor@123");
43 |     await mongoose.disconnect();
44 |   } catch (error) {
45 |     console.error("L ERROR:", error.message);
46 |     process.exit(1);
47 |   }
48 | }
50 | createMentor();
```

(6.6 KB)

```
1 | const Meeting = require("../models/Meeting");
2 | const Mentor = require("../models/Mentor");
3 | const Student = require("../models/Student");
4 | const Notification = require("../models/Notification");
5 |
6 | // @desc Book a meeting
7 | // @route POST /api/meetings
8 | const bookMeeting = async (req, res) => {
9 |   try {
10 |     const { mentorId, topic, agenda, scheduledDate, scheduledTime, duration, meetLink } = req.body;
11 |     let resolvedMentorId = mentorId;
12 |     if (!resolvedMentorId) {
13 |       const student = await Student.findById(req.user.id);
14 |       resolvedMentorId = student?.assignedMentor;
15 |     }
16 |     if (!resolvedMentorId) {
17 |       // Fallback: pick the first available mentor in the DB
18 |       const fallbackMentor = await Mentor.findOne();
19 |       if (fallbackMentor) {
20 |         resolvedMentorId = fallbackMentor._id;
21 |       }
22 |     }
23 |   }
24 |   if (!resolvedMentorId) {
25 |     return res.status(400).json({ message: "No mentor available in platform. Please contact admin." });
26 |   }
27 |   const mentor = await Mentor.findById(resolvedMentorId);
28 |   if (!mentor) return res.status(404).json({ message: "Mentor not found" });
29 |   // Auto-generate Google Meet link if not provided
30 |   const randomCode = Math.random().toString(36).substring(2, 5) + "-" + Math.random().toString(36).substring(2, 5);
31 |   const generatedMeetLink = meetLink || `https://meet.google.com/${randomCode}`;
32 |   const meeting = await Meeting.create({
33 |     studentId: req.user.id,
34 |     mentorId: resolvedMentorId,
35 |     topic,
36 |     agenda,
37 |     scheduledDate,
38 |     scheduledTime,
39 |     duration: duration || 60,
40 |     meetLink: generatedMeetLink,
41 |     status: "accepted", // Auto-confirm with meet link
42 |   });
43 |   // Notify mentor with Google Meet link
44 |   await Notification.create({
45 |     userId: resolvedMentorId,
46 |     userRole: "mentor",
47 |     title: "New Meeting Scheduled ðŸ“œ",
48 |     message: `Meeting on "${topic}" scheduled. Google Meet: ${generatedMeetLink}`,
49 |     type: "meeting",
50 |   });
51 |   // Notify student with Google Meet link
52 |   await Notification.create({
53 |     userId: req.user.id,
54 |     userRole: "student",
55 |     title: "Meeting Confirmed & Google Meet Ready! ðŸ“œ",
56 |     message: `Your meeting on "${topic}" is set for ${scheduledDate} at ${scheduledTime}. Google Meet Link: ${generatedMeetLink}`,
57 |     type: "meeting",
58 |   });
59 |   res.status(201).json({ message: "Meeting scheduled with Google Meet link!", meeting });
60 | } catch (error) {
61 |   res.status(500).json({ message: "Server error", error: error.message });
62 | }
63 | };
64 |
65 | // @desc Get student meetings
66 | // @route GET /api/meetings/student
67 | const getStudentMeetings = async (req, res) => {
68 |   try {
69 |     const { status } = req.query;
70 |     const filter = { studentId: req.user.id };
71 |     if (status) filter.status = status;
72 |     const meetings = await Meeting.find(filter)
73 |       .populate("mentorId", "name email profilePic designation company")
74 |       .sort({ scheduledDate: -1 });
75 |   } catch (error) {
76 |     res.status(500).json({ message: "Server error", error: error.message });
77 |   }
78 | };
79 |
```

```
83 |     res.json({ meetings });
84 |   } catch (error) {
85 |     res.status(500).json({ message: "Server error", error: error.message });
86 |   }
87 | };
88 |
89 | // @desc Get mentor meetings
90 | // @route GET /api/meetings/mentor
91 | const getMentorMeetings = async (req, res) => {
92 |   try {
93 |     const { status } = req.query;
94 |     const filter = { mentorId: req.user.id };
95 |     if (status) filter.status = status;
96 |
97 |     const meetings = await Meeting.find(filter)
98 |       .populate("studentId", "name email profilePic phone")
99 |       .sort({ scheduledDate: -1 });
100 |
101 |     res.json({ meetings });
102 |   } catch (error) {
103 |     res.status(500).json({ message: "Server error", error: error.message });
104 |   }
105 | };
106 |
107 | // @desc Update meeting status
108 | // @route PUT /api/meetings/:id/status
109 | const updateMeetingStatus = async (req, res) => {
110 |   try {
111 |     const { status, rejectionReason, meetLink } = req.body;
112 |     const defaultMeetLink = meetLink || "https://meet.google.com/katalyst-session";
113 |     const updateObj = { status, rejectionReason: rejectionReason || "" };
114 |     if (status === "accepted") {
115 |       updateObj.meetLink = defaultMeetLink;
116 |     }
117 |
118 |     const meeting = await Meeting.findByIdAndUpdate(
119 |       req.params.id,
120 |       updateObj,
121 |       { new: true }
122 |     ).populate("mentorId", "name");
123 |
124 |     if (meeting) {
125 |       await Notification.create({
126 |         userId: meeting.studentId,
127 |         userRole: "student",
128 |         title: `Meeting ${status === "accepted" ? "Accepted" : status === "rejected" ? "Declined" : "Updated"}`,
129 |         message: `Your meeting "${meeting.topic}" has been ${status}${status === "accepted" ? ". Link: ${defaultMeetLink}" : ""}`,
130 |         type: "meeting",
131 |       });
132 |     }
133 |   }
134 |
135 |   res.json({ message: "Meeting updated", meeting });
136 | } catch (error) {
137 |   res.status(500).json({ message: "Server error", error: error.message });
138 | }
139 | };
140 |
141 | // @desc Submit student feedback for meeting
142 | // @route POST /api/meetings/:id/feedback
143 | const submitStudentFeedback = async (req, res) => {
144 |   try {
145 |     const { rating, comment } = req.body;
146 |     const meeting = await Meeting.findByIdAndUpdate(
147 |       req.params.id,
148 |       {
149 |         "studentFeedback.rating": rating,
150 |         "studentFeedback.comment": comment,
151 |         "studentFeedback.givenAt": new Date(),
152 |       },
153 |       { new: true }
154 |     );
155 |
156 |     // Update mentor rating
157 |     const mentor = await Mentor.findById(meeting.mentorId);
158 |     const newTotal = mentor.totalRatings + 1;
159 |     const newRating = ((mentor.rating * mentor.totalRatings) + rating) / newTotal;
160 |     await Mentor.findByIdAndUpdate(meeting.mentorId, {
161 |       rating: Math.round(newRating * 10) / 10,
162 |       totalRatings: newTotal,
163 |     });
164 |   }
165 | }
```

```
165 |     res.json({ message: "Feedback submitted", meeting });
166 |   } catch (error) {
167 |     res.status(500).json({ message: "Server error", error: error.message });
168 |   }
169 | };
171 | // @desc Cancel meeting
172 | // @route DELETE /api/meetings/:id
173 | const cancelMeeting = async (req, res) => {
174 |   try {
175 |     const meeting = await Meeting.findById(req.params.id);
176 |     if (!meeting) return res.status(404).json({ message: "Meeting not found" });
177 |     meeting.status = "cancelled";
178 |     await meeting.save();
179 |     res.json({ message: "Meeting cancelled" });
180 |   } catch (error) {
181 |     res.status(500).json({ message: "Server error", error: error.message });
182 |   }
183 | };
185 | // @desc Get all meetings (admin)
186 | // @route GET /api/meetings/admin
187 | const getAllMeetingsAdmin = async (req, res) => {
188 |   try {
189 |     const meetings = await Meeting.find({})
190 |       .populate("studentId", "name email profilePic")
191 |       .populate("mentorId", "name email profilePic designation")
192 |       .sort({ scheduledDate: -1 });
194 |     res.json({ meetings });
195 |   } catch (error) {
196 |     res.status(500).json({ message: "Server error", error: error.message });
197 |   }
198 | };
200 | module.exports = {
201 |   bookMeeting,
202 |   getStudentMeetings,
203 |   getMentorMeetings,
204 |   getAllMeetingsAdmin,
205 |   updateMeetingStatus,
206 |   submitStudentFeedback,
207 |   cancelMeeting,
208 | };
209 |
210 | const Mentor = require("../models/Mentor");
211 | const Student = require("../models/Student");
212 | const Meeting = require("../models/Meeting");
213 | const Progress = require("../models/Progress");
214 | const Feedback = require("../models/Feedback");
215 | const Notification = require("../models/Notification");
216 | const { sendEmail, meetingAcceptedEmail, meetingRejectedEmail } = require("../utils/sendEmail");
217 |
218 | // @desc Get mentor dashboard
219 | // @route GET /api/mentors/dashboard
220 | const getDashboard = async (req, res) => {
221 |   try {
222 |     const mentor = await Mentor.findById(req.user.id)
223 |       .select("-password")
224 |       .populate("assignedStudents", "name email profilePic lastLogin");
225 |     const pendingMeetings = await Meeting.find({
226 |       mentorId: req.user.id,
227 |       status: "pending",
228 |     })
229 |       .populate("studentId", "name email profilePic")
230 |       .sort({ createdAt: -1 });
231 |     const upcomingMeetings = await Meeting.find({
232 |       mentorId: req.user.id,
233 |       status: "accepted",
234 |       scheduledDate: { $gte: new Date() },
235 |     })
236 |       .populate("studentId", "name email profilePic")
237 |       .sort({ scheduledDate: 1 })
238 |       .limit(5);
239 |     const completedMeetings = await Meeting.countDocuments({
240 |       mentorId: req.user.id,
```

```
35 |         status: "completed",
36 |     });
37 |
38 |     res.json({
39 |         mentor,
40 |         pendingMeetings,
41 |         upcomingMeetings,
42 |         stats: {
43 |             totalStudents: mentor.assignedStudents.length,
44 |             pendingRequests: pendingMeetings.length,
45 |             completedMeetings,
46 |             rating: mentor.rating,
47 |         },
48 |     });
49 | } catch (error) {
50 |     res.status(500).json({ message: "Server error", error: error.message });
51 | }
52 | };
53 |
54 | // @desc Get assigned students with progress
55 | // @route GET /api/mentors/students
56 | const getStudents = async (req, res) => {
57 |     try {
58 |         const mentor = await Mentor.findById(req.user.id).populate(
59 |             "assignedStudents",
60 |             "name email profilePic phone skills bio lastLogin"
61 |         );
62 |         const studentsWithProgress = await Promise.all(
63 |             mentor.assignedStudents.map(async (student) => {
64 |                 const progress = await Progress.findOne({ studentId: student._id });
65 |                 return { ...student.toObject(), progress };
66 |             })
67 |         );
68 |         res.json({ students: studentsWithProgress });
69 |     } catch (error) {
70 |         res.status(500).json({ message: "Server error", error: error.message });
71 |     }
72 | };
73 |
74 | // @desc Accept or reject meeting
75 | // @route PUT /api/mentors/meeting/:id
76 | const respondToMeeting = async (req, res) => {
77 |     try {
78 |         const { status, rejectionReason } = req.body;
79 |         const meeting = await Meeting.findById(req.params.id).populate(
80 |             "studentId",
81 |             "name email"
82 |         );
83 |         if (!meeting) {
84 |             return res.status(404).json({ message: "Meeting not found" });
85 |         }
86 |         if (meeting.mentorId.toString() !== req.user.id) {
87 |             return res.status(403).json({ message: "Not authorized" });
88 |         }
89 |         meeting.status = status;
90 |         if (status === "rejected") meeting.rejectionReason = rejectionReason || "";
91 |         if (status === "accepted") {
92 |             meeting.meetLink = `https://meet.google.com/${Math.random().toString(36).substr(2, 10)}`;
93 |             await meeting.save();
94 |             if (status === "accepted") {
95 |                 await Progress.findOneAndUpdate(
96 |                     { studentId: meeting.studentId._id },
97 |                     { $inc: { totalMeetingsScheduled: 1 } },
98 |                     { upsert: true, new: true }
99 |                 );
100 |                 const { syncStudentProgress } = require("../utils/progressService");
101 |                 await syncStudentProgress(meeting.studentId._id);
102 |             }
103 |             const mentor = await Mentor.findById(req.user.id).select("name");
104 |             // Notify student
105 |             await Notification.create({
106 |                 userId: meeting.studentId._id,
107 |                 userRole: "student",
108 |                 title: status === "accepted" ? "Meeting Accepted! " : "Meeting Update",
109 |                 message:
```

KATALYST

Source Code: backend/controllers/mentorController.js (Cont.)

Generated: 22/8/2026 | Backend

```
117 |         status === "accepted"
118 |         ? `${mentor.name} accepted your meeting request. Check your schedule!`
119 |         : `Your meeting request was not accepted. Reason: ${rejectionReason || "Not specified"}`,
120 |         type: "meeting",
121 |     });
122 |     // Send email
123 |     if (status === "accepted") {
124 |         await sendEmail({
125 |             to: meeting.studentId.email,
126 |             subject: "Katalyst - Meeting Confirmed!",
127 |             html: meetingAcceptedEmail(
128 |                 meeting.studentId.name,
129 |                 mentor.name,
130 |                 new Date(meeting.scheduledDate).toDateString(),
131 |                 meeting.scheduledTime,
132 |                 meeting.meetLink
133 |             ),
134 |         });
135 |     } else if (status === "rejected") {
136 |         await sendEmail({
137 |             to: meeting.studentId.email,
138 |             subject: "Katalyst - Meeting Update",
139 |             html: meetingRejectedEmail(meeting.studentId.name, mentor.name, rejectionReason),
140 |         });
141 |     }
142 |     res.json({ message: `Meeting ${status}`, meeting });
143 | } catch (error) {
144 |     res.status(500).json({ message: "Server error", error: error.message });
145 | }
146 | };
147 |
148 | // @desc Add meeting notes
149 | // @route POST /api/mentors/meeting/:id/notes
150 | const addMeetingNotes = async (req, res) => {
151 |     try {
152 |         const { notes } = req.body;
153 |         const meeting = await Meeting.findById(req.params.id);
154 |         if (!meeting) return res.status(404).json({ message: "Meeting not found" });
155 |         meeting.notes = notes;
156 |         meeting.status = "completed";
157 |         await meeting.save();
158 |         // Update attendance
159 |         await Progress.findOneAndUpdate(
160 |             { studentId: meeting.studentId },
161 |             { $inc: { meetingsAttended: 1 } }
162 |         );
163 |         const { syncStudentProgress } = require("../utils/progressService");
164 |         await syncStudentProgress(meeting.studentId);
165 |         res.json({ message: "Notes added and meeting marked complete", meeting });
166 |     } catch (error) {
167 |         res.status(500).json({ message: "Server error", error: error.message });
168 |     }
169 | };
170 |
171 | // @desc Give feedback/rating to student
172 | // @route POST /api/mentors/feedback
173 | const giveFeedback = async (req, res) => {
174 |     try {
175 |         const { studentId, meetingId, rating, comment } = req.body;
176 |         const feedback = await Feedback.create({
177 |             fromId: req.user.id,
178 |             fromRole: "mentor",
179 |             toId: studentId,
180 |             toRole: "student",
181 |             meetingId,
182 |             rating,
183 |             comment,
184 |             type: "meeting",
185 |         });
186 |         // Save mentor feedback on meeting
187 |         await Meeting.findByIdAndUpdate(meetingId, {
188 |             "mentorFeedback.rating": rating,
189 |             "mentorFeedback.comment": comment,
```



```
198 |     "mentorFeedback.givenAt": new Date(),
199 |   });
200 |
201 |   await Notification.create({
202 |     userId: studentId,
203 |     userRole: "student",
204 |     title: "New Feedback Received +P",
205 |     message: `Your mentor has given you a ${rating}/5 rating. Check your feedback section.`,
206 |     type: "feedback",
207 |   });
208 |
209 |   const { syncStudentProgress } = require("../utils/progressService");
210 |   await syncStudentProgress(studentId);
211 |
212 |   res.json({ message: "Feedback submitted", feedback });
213 | } catch (error) {
214 |   res.status(500).json({ message: "Server error", error: error.message });
215 | }
216 | };
217 |
218 | // @desc Get all meetings for mentor
219 | // @route GET /api/mentors/meetings
220 | const getMeetings = async (req, res) => {
221 |   try {
222 |     const meetings = await Meeting.find({ mentorId: req.user.id })
223 |       .populate("studentId", "name email profilePic")
224 |       .sort({ scheduledDate: -1 });
225 |     res.json({ meetings });
226 |   } catch (error) {
227 |     res.status(500).json({ message: "Server error", error: error.message });
228 |   }
229 | };
230 |
231 | module.exports = {
232 |   getDashboard,
233 |   getStudents,
234 |   respondToMeeting,
235 |   addMeetingNotes,
236 |   giveFeedback,
237 |   getMeetings,
238 | };
239 |
240 | const Notification = require("../models/Notification");
241 |
242 | // @desc Get notifications for current user
243 | // @route GET /api/notifications
244 | const getNotifications = async (req, res) => {
245 |   try {
246 |     const { page = 1, limit = 20 } = req.query;
247 |     const notifications = await Notification.find({ userId: req.user.id })
248 |       .sort({ createdAt: -1 })
249 |       .skip((page - 1) * limit)
250 |       .limit(Number(limit));
251 |
252 |     const unreadCount = await Notification.countDocuments({
253 |       userId: req.user.id,
254 |       isRead: false,
255 |     });
256 |     res.json({ notifications, unreadCount });
257 |   } catch (error) {
258 |     res.status(500).json({ message: "Server error", error: error.message });
259 |   }
260 | };
261 |
262 | // @desc Mark single notification as read
263 | // @route PUT /api/notifications/:id/read
264 | const markAsRead = async (req, res) => {
265 |   try {
266 |     await Notification.findByIdAndUpdate(req.params.id, { isRead: true });
267 |     res.json({ message: "Marked as read" });
268 |   } catch (error) {
269 |     res.status(500).json({ message: "Server error", error: error.message });
270 |   }
271 | };
272 |
273 | // @desc Mark all as read
274 | // @route PUT /api/notifications/read-all
275 | const markAllAsRead = async (req, res) => {
276 |   try {
277 |     await Notification.updateMany({ userId: req.user.id, isRead: false }, { isRead: true });
278 |   }
279 | }
```

```
40 |     res.json({ message: "All notifications marked as read" });
41 |   } catch (error) {
42 |     res.status(500).json({ message: "Server error", error: error.message });
43 |   }
44 | });
45 |
46 | // @desc Delete a notification
47 | // @route DELETE /api/notifications/:id
48 | const deleteNotification = async (req, res) => {
49 |   try {
50 |     await Notification.findByIdAndDelete(req.params.id);
51 |     res.json({ message: "Notification deleted" });
52 |   } catch (error) {
53 |     res.status(500).json({ message: "Server error", error: error.message });
54 |   }
55 | };
56 |
57 | module.exports = { getNotifications, markAsRead, markAllAsRead, deleteNotification };
58 |
59 | const Progress = require("../models/Progress");
60 | const Training = require("../models/Training");
61 | const { calculateOverallProgress, calculatePlacementReadiness } = require("../utils/progressCalculator");
62 |
63 | const getStudentProgress = async (req, res) => {
64 |   try {
65 |     const progress = await Progress.findOne({ studentId: req.user.id });
66 |     if (!progress) return res.status(404).json({ message: "Progress record not found" });
67 |     res.json({ progress });
68 |   } catch (error) {
69 |     res.status(500).json({ message: "Server error", error: error.message });
70 |   }
71 | };
72 |
73 | const getDetailedStudentReport = async (req, res) => {
74 |   try {
75 |     const targetStudentId = req.params.studentId || req.user.id;
76 |     const student = await Student.findById(targetStudentId)
77 |       .select("-password")
78 |       .populate("assignedMentor", "name email designation company")
79 |       .populate("enrolledTrainings", "title category level duration lessons");
80 |     if (!student) return res.status(404).json({ message: "Student not found" });
81 |     let progress = await Progress.findOne({ studentId: targetStudentId });
82 |     if (!progress) {
83 |       progress = await Progress.create({ studentId: targetStudentId });
84 |     }
85 |     res.json({
86 |       student,
87 |       progress,
88 |     });
89 |   } catch (error) {
90 |     res.status(500).json({ message: "Server error", error: error.message });
91 |   }
92 | };
93 |
94 | const getPlacementReadiness = async (req, res) => {
95 |   try {
96 |     const progress = await Progress.findOne({ studentId: req.user.id });
97 |     if (!progress) return res.status(404).json({ message: "Progress record not found" });
98 |     const placementScore = calculatePlacementReadiness({
99 |       overallScore: progress.overallScore,
100 |       quizScores: progress.quizScores,
101 |       assignmentsSubmitted: progress.assignmentsSubmitted,
102 |       meetingsAttended: progress.meetingsAttended,
103 |       hasResume: progress.hasResume,
104 |     });
105 |     res.json({ placementReadiness: placementScore });
106 |   } catch (error) {
107 |     res.status(500).json({ message: "Server error", error: error.message });
108 |   }
109 | };
110 |
111 | const getAdminProgressReport = async (req, res) => {
112 |   try {
113 |     const progressData = await Progress.find()
114 |       .populate("studentId", "name email assignedMentor")
115 |       .sort({ overallScore: -1 });
116 |     const averageOverall =
```

```
65 |     progressData.length > 0
66 |     ?
67 |     progressData.reduce((sum, p) => sum + p.overallScore, 0) / progressData.length
68 |     : 0;
69 |
70 |     const averagePlacement =
71 |     progressData.length > 0
72 |     ?
73 |     progressData.reduce((sum, p) => sum + p.placementReadiness, 0) / progressData.length
74 |     : 0;
75 |
76 |     res.json({
77 |       progressData,
78 |       metrics: {
79 |         averageOverall: Math.round(averageOverall),
80 |         averagePlacement: Math.round(averagePlacement),
81 |         totalStudents: progressData.length,
82 |       },
83 |     });
84 |   } catch (error) {
85 |     res.status(500).json({ message: "Server error", error: error.message });
86 |   }
87 | };
88 |
89 | module.exports = {
90 |   getStudentProgress,
91 |   getDetailedStudentReport,
92 |   getPlacementReadiness,
93 |   getAdminProgressReport,
94 | }; View Source \(5.1 KB\)
95 |
96 | 1 | const Student = require("../models/Student");
97 | 2 | const Meeting = require("../models/Meeting");
98 | 3 | const Progress = require("../models/Progress");
99 | 4 | const Certificate = require("../models/Certificate");
100 | 5 | const Notification = require("../models/Notification");
101 | 6 | const Training = require("../models/Training");
102 | 7 | const path = require("path");
103 | 8 |
104 | 9 | // @desc Get student dashboard data
105 | 10 | // @route GET /api/students/dashboard
106 | 11 | const getDashboard = async (req, res) => {
107 | 12 |   try {
108 | 13 |     const student = await Student.findById(req.user.id)
109 | 14 |       .select("-password")
110 | 15 |       .populate("assignedMentor", "name email expertise profilePic designation company");
111 | 16 |
112 | 17 |     const progress = await Progress.findOne({ studentId: req.user.id });
113 | 18 |
114 | 19 |     const upcomingMeetings = await Meeting.find({
115 | 20 |       studentId: req.user.id,
116 | 21 |       status: "accepted",
117 | 22 |       scheduledDate: { $gte: new Date() },
118 | 23 |     })
119 | 24 |       .populate("mentorId", "name profilePic designation")
120 | 25 |       .sort({ scheduledDate: 1 })
121 | 26 |       .limit(3);
122 | 27 |
123 | 28 |     const enrolledTrainings = await Training.find({
124 | 29 |       "enrolledStudents.studentId": req.user.id,
125 | 30 |     }).select("title category thumbnail enrolledStudents");
126 | 31 |
127 | 32 |     const notifications = await Notification.find({
128 | 33 |       userId: req.user.id,
129 | 34 |       isRead: false,
130 | 35 |     })
131 | 36 |       .sort({ createdAt: -1 })
132 | 37 |       .limit(5);
133 | 38 |
134 | 39 |     const certificates = await Certificate.find({ studentId: req.user.id });
135 | 40 |
136 | 41 |     res.json({
137 | 42 |       student,
138 | 43 |       progress,
139 | 44 |       upcomingMeetings,
140 | 45 |       enrolledTrainings: enrolledTrainings.map((t) => {
141 | 46 |         const enrollment = t.enrolledStudents.find(
142 | 47 |           (e) => e.studentId.toString() === req.user.id
143 | 48 |         );
144 | 49 |         return {
145 | 50 |           _id: t._id,
```

```
51 |         title: t.title,
52 |         category: t.category,
53 |         thumbnail: t.thumbnail,
54 |         isCompleted: enrollment?.isCompleted || false,
55 |         completedVideos: enrollment?.completedVideos?.length || 0,
56 |         quizScore: enrollment?.quizScore || 0,
57 |     });
58 | },
59 |     unreadNotifications: notifications.length,
60 |     certificates: certificates.length,
61 | });
62 | } catch (error) {
63 |     res.status(500).json({ message: "Server error", error: error.message });
64 | }
65 | };
66 |
67 | // @desc Get/Update student profile
68 | // @route GET|PUT /api/students/profile
69 | const getProfile = async (req, res) => {
70 |     try {
71 |         const student = await Student.findById(req.user.id)
72 |             .select("-password")
73 |             .populate("assignedMentor", "name email profilePic designation company");
74 |         res.json({ student });
75 |     } catch (error) {
76 |         res.status(500).json({ message: "Server error", error: error.message });
77 |     }
78 | };
79 |
80 | const updateProfile = async (req, res) => {
81 |     try {
82 |         const { name, phone, bio, skills } = req.body;
83 |         const updated = await Student.findByIdAndUpdate(
84 |             req.user.id,
85 |             {
86 |                 name,
87 |                 phone,
88 |                 bio,
89 |                 skills: Array.isArray(skills)
90 |                     ? skills
91 |                     : skills
92 |                     ? skills.split(",").map((s) => s.trim()).filter(Boolean)
93 |                     : [],
94 |             },
95 |             { new: true }
96 |         ).select("-password");
97 |         res.json({ message: "Profile updated", student: updated });
98 |     } catch (error) {
99 |         res.status(500).json({ message: "Server error", error: error.message });
100 |     }
101 | };
102 |
103 | // @desc Upload resume
104 | // @route POST /api/students/resume
105 | const uploadResume = async (req, res) => {
106 |     try {
107 |         if (!req.file) return res.status(400).json({ message: "No file uploaded" });
108 |         const resumeUrl = `/uploads/resumes/${req.file.filename}`;
109 |         await Student.findByIdAndUpdate(req.user.id, { resumeUrl });
110 |         // Mark as having resume in Progress and sync
111 |         await Progress.findOneAndUpdate(
112 |             { studentId: req.user.id },
113 |             { hasResume: true }
114 |         );
115 |         const { syncStudentProgress } = require("../utils/progressService");
116 |         await syncStudentProgress(req.user.id);
117 |         res.json({ message: "Resume uploaded", resumeUrl });
118 |     } catch (error) {
119 |         res.status(500).json({ message: "Server error", error: error.message });
120 |     }
121 | };
122 |
123 | // @desc Get student certificates
124 | // @route GET /api/students/certificates
125 | const getCertificates = async (req, res) => {
126 |     try {
```

```
129 |     const certs = await Certificate.find({ studentId: req.user.id }).populate(
130 |       "trainingId",
131 |       "title category"
132 |     );
133 |     res.json({ certificates: certs });
134 |   } catch (error) {
135 |     res.status(500).json({ message: "Server error", error: error.message });
136 |   }
137 | };
138 |
139 | // @desc Get student progress
140 | // @route GET /api/students/progress
141 | const getProgress = async (req, res) => {
142 |   try {
143 |     const progress = await Progress.findOne({ studentId: req.user.id }).populate(
144 |       "quizScores.trainingId",
145 |       "title"
146 |     );
147 |     res.json({ progress });
148 |   } catch (error) {
149 |     res.status(500).json({ message: "Server error", error: error.message });
150 |   }
151 | };
152 |
153 | // @desc Get all meetings for student
154 | // @route GET /api/students/meetings
155 | const getMeetings = async (req, res) => {
156 |   try {
157 |     const meetings = await Meeting.find({ studentId: req.user.id })
158 |       .populate("mentorId", "name profilePic email designation")
159 |       .sort({ scheduledDate: -1 });
160 |     res.json({ meetings });
161 |   } catch (error) {
162 |     res.status(500).json({ message: "Server error", error: error.message });
163 |   }
164 | };
165 |
166 | module.exports = {
167 |   getDashboard,
168 |   getProfile,
169 |   updateProfile,
170 |   uploadResume,
171 |   getCertificates,
172 |   getProgress,
173 |   getMeetings,
174 | };
175 |
176 | const Training = require("../models/Training");
177 | const Certificate = require("../models/Certificate");
178 | const Progress = require("../models/Progress");
179 | const Notification = require("../models/Notification");
180 | const { calculateOverallProgress } = require("../utils/progressCalculator");
181 |
182 | // @desc Get all trainings
183 | // @route GET /api/trainings
184 | const getAllTrainings = async (req, res) => {
185 |   try {
186 |     const { category, level } = req.query;
187 |     const filter = { isPublished: true };
188 |     if (category) filter.category = category;
189 |     if (level) filter.level = level;
190 |
191 |     const trainings = await Training.find(filter).select(
192 |       "title description category thumbnail level duration instructor tags enrolledStudents createdAt"
193 |     );
194 |
195 |     const trainingsWithCount = trainings.map((t) => ({
196 |       ...t.toObject(),
197 |       enrollmentCount: t.enrolledStudents.length,
198 |       enrolledStudents: undefined,
199 |     }));
200 |     res.json({ trainings: trainingsWithCount });
201 |   } catch (error) {
202 |     res.status(500).json({ message: "Server error", error: error.message });
203 |   }
204 | };
205 |
206 | // @desc Get training details
```

```
33 | // @route GET /api/trainings/:id
34 | const getTrainingById = async (req, res) => {
35 |   try {
36 |     const training = await Training.findById(req.params.id);
37 |     if (!training) return res.status(404).json({ message: "Training not found" });
38 |     let userEnrollment = null;
39 |     if (req.user) {
40 |       userEnrollment = training.enrolledStudents.find(
41 |         (e) => e.studentId.toString() === req.user.id
42 |       );
43 |     }
44 |     res.json({
45 |       training: {
46 |         ...training.toObject(),
47 |         enrollmentCount: training.enrolledStudents.length,
48 |       },
49 |       userEnrollment,
50 |     });
51 |   } catch (error) {
52 |     res.status(500).json({ message: "Server error", error: error.message });
53 |   }
54 | };
55 |
56 | // @desc Enroll in training
57 | // @route POST /api/trainings/:id/enroll
58 | const enrollTraining = async (req, res) => {
59 |   try {
60 |     const training = await Training.findById(req.params.id);
61 |     if (!training) return res.status(404).json({ message: "Training not found" });
62 |     const alreadyEnrolled = training.enrolledStudents.find(
63 |       (e) => e.studentId.toString() === req.user.id
64 |     );
65 |     if (alreadyEnrolled)
66 |       return res.status(400).json({ message: "Already enrolled" });
67 |     training.enrolledStudents.push({ studentId: req.user.id });
68 |     await training.save();
69 |     await Notification.create({
70 |       userId: req.user.id,
71 |       userRole: "student",
72 |       title: `Enrolled in ${training.title} ðŸŽŽ`,
73 |       message: `You're now enrolled. Start learning and track your progress!`,
74 |       type: "training",
75 |     });
76 |     res.json({ message: "Enrolled successfully" });
77 |   } catch (error) {
78 |     res.status(500).json({ message: "Server error", error: error.message });
79 |   }
80 | };
81 |
82 | // @desc Mark video as completed
83 | // @route POST /api/trainings/:id/complete-video
84 | const completeVideo = async (req, res) => {
85 |   try {
86 |     const { videoIndex } = req.body;
87 |     const training = await Training.findById(req.params.id);
88 |     if (!training) return res.status(404).json({ message: "Training not found" });
89 |     const enrollment = training.enrolledStudents.find(
90 |       (e) => e.studentId.toString() === req.user.id
91 |     );
92 |     if (!enrollment) return res.status(400).json({ message: "Not enrolled" });
93 |     if (!enrollment.completedVideos.includes(videoIndex)) {
94 |       enrollment.completedVideos.push(videoIndex);
95 |     }
96 |     // Check if all videos completed
97 |     const allCompleted =
98 |       training.videos.length > 0 &&
99 |       enrollment.completedVideos.length === training.videos.length;
100 |     if (allCompleted) {
101 |       enrollment.isCompleted = true;
102 |       enrollment.completedAt = new Date();
103 |       // Issue certificate
104 |       const cert = await Certificate.create({
```

```
116 |         studentId: req.user.id,
117 |         trainingId: training._id,
118 |         trainingTitle: training.title,
119 |     });
120 |
121 |     await Notification.create({
122 |         userId: req.user.id,
123 |         userRole: "student",
124 |         title: "Certificate Earned! 🎉",
125 |         message: `Congratulations! You completed "${training.title}" and earned a certificate.`,
126 |         type: "certificate",
127 |     });
128 | }
129 |
130 | await training.save();
131 |
132 | // Update progress
133 | const allTrainings = await Training.find({
134 |     "enrolledStudents.studentId": req.user.id,
135 | });
136 | const completedCount = allTrainings.filter((t) =>
137 |     t.enrolledStudents.find(
138 |         (e) => e.studentId.toString() === req.user.id && e.isCompleted
139 |     )
140 | ).length;
141 | const trainingCompletion =
142 |     allTrainings.length > 0
143 |     ? Math.round((completedCount / allTrainings.length) * 100)
144 |     : 0;
145 |
146 | await Progress.findOneAndUpdate(
147 |     { studentId: req.user.id },
148 |     { trainingCompletion }
149 | );
150 |
151 | const { syncStudentProgress } = require("../utils/progressService");
152 | await syncStudentProgress(req.user.id);
153 |
154 | res.json({
155 |     message: allCompleted
156 |     ? "Training completed! Certificate issued."
157 |     : "Video marked complete",
158 |     isCompleted: allCompleted,
159 | });
160 | } catch (error) {
161 |     res.status(500).json({ message: "Server error", error: error.message });
162 | }
163 | });
164 |
165 | // @desc Submit quiz
166 | // @route POST /api/trainings/:id/submit-quiz
167 | const submitQuiz = async (req, res) => {
168 |     try {
169 |         const { answers } = req.body; // [{ questionIndex, selectedOption }]
170 |         const training = await Training.findById(req.params.id);
171 |         if (!training) return res.status(404).json({ message: "Training not found" });
172 |
173 |         let score = 0;
174 |         const maxScore = training.quizzes.reduce((s, q) => s + (q.points || 10), 0);
175 |         answers.forEach(({ questionIndex, selectedOption }) => {
176 |             const quiz = training.quizzes[questionIndex];
177 |             if (quiz && quiz.correctAnswer === selectedOption) {
178 |                 score += quiz.points || 10;
179 |             }
180 |         });
181 |     } catch (error) {
182 |         // Handle error
183 |     }
184 |
185 |     const enrollment = training.enrolledStudents.find(
186 |         (e) => e.studentId.toString() === req.user.id
187 |     );
188 |     if (enrollment) enrollment.quizScore = score;
189 |     await training.save();
190 |
191 |     await Progress.findOneAndUpdate(
192 |         { studentId: req.user.id },
193 |         {
194 |             $push: {
195 |                 quizScores: {
196 |                     trainingId: training._id,
197 |                     score,
```

```
198 |     },
199 |   }
200 | );
202 | const { syncStudentProgress } = require("../utils/progressService");
203 | await syncStudentProgress(req.user.id);
205 | res.json({ score, maxScore, percentage: Math.round((score / maxScore) * 100) });
206 | } catch (error) {
207 |   res.status(500).json({ message: "Server error", error: error.message });
208 | }
209 | };
211 | // @desc Create training (admin)
212 | // @route POST /api/trainings
213 | const createTraining = async (req, res) => {
214 |   try {
215 |     const training = await Training.create(req.body);
216 |     res.status(201).json({ message: "Training created", training });
217 |   } catch (error) {
218 |     res.status(500).json({ message: "Server error", error: error.message });
219 |   }
220 | };
222 | // @desc Update training (admin)
223 | // @route PUT /api/trainings/:id
224 | const updateTraining = async (req, res) => {
225 |   try {
226 |     const training = await Training.findByIdAndUpdate(req.params.id, req.body, { new: true });
227 |     res.json({ message: "Training updated", training });
228 |   } catch (error) {
229 |     res.status(500).json({ message: "Server error", error: error.message });
230 |   }
231 | };
233 | // @desc Delete training (admin)
234 | // @route DELETE /api/trainings/:id
235 | const deleteTraining = async (req, res) => {
236 |   try {
237 |     await Training.findByIdAndDelete(req.params.id);
238 |     res.json({ message: "Training deleted" });
239 |   } catch (error) {
240 |     res.status(500).json({ message: "Server error", error: error.message });
241 |   }
242 | };
244 | module.exports = {
245 |   getAllTrainings,
246 |   getTrainingById,
247 |   enrollTraining,
248 |   completeVideo,
249 |   submitQuiz,
250 |   createTraining,
251 |   updateTraining,
252 |   deleteTraining,
253 | };
254 | View Backend/controllers/trainingController.js \(0.0 KB\)
254 | View Backend/controllers/trainingController.js \(0.1 KB\)
1 |
1 | FROM node:20-alpine
3 | WORKDIR /usr/src/app
5 | COPY package*.json ./
6 | RUN npm install --production
8 | COPY . .
10 | EXPOSE 5000
12 | CMD ["npm", "start"]
13 |
```


KATALYST

Source Code: backend/generate_all_files_pdf.js

Generated: 22/8/2026 | Backend

(22.3 KB)

```
1 | const PDFDocument = require("pdfkit");
2 | const fs = require("fs");
3 | const path = require("path");
4 |
5 | const rootDir = path.resolve(__dirname, "..");
6 | const frontendDir = path.join(rootDir, "frontend");
7 | const backendDir = path.join(rootDir, "backend");
8 |
9 | // Folders to ignore
10 | const IGNORE_DIRS = new Set([
11 |   "node_modules",
12 |   ".git",
13 |   "dist",
14 |   "build",
15 |   ".vscode",
16 |   "android",
17 |   "uploads",
18 |   "StudentLearningApp_CURRENT_BACKUP",
19 |   "assets"
20 | ]);
21 |
22 | const ALLOWED_EXTS = new Set([
23 |   ".js",
24 |   ".jsx",
25 |   ".json",
26 |   ".css",
27 |   ".html",
28 |   ".md",
29 |   ".yaml",
30 |   ".yml",
31 |   ".example"
32 | ]);
33 |
34 | function getFilesRecursively(dir, baseDir = dir) {
35 |   let results = [];
36 |   try {
37 |     const list = fs.readdirSync(dir);
38 |     for (const file of list) {
39 |       const fullPath = path.join(dir, file);
40 |       const relPath = path.relative(baseDir, fullPath).replace(/\\/g, "/");
41 |       const stat = fs.statSync(fullPath);
42 |
43 |       if (stat.isDirectory()) {
44 |         if (!IGNORE_DIRS.has(file)) {
45 |           results = results.concat(getFilesRecursively(fullPath, baseDir));
46 |         }
47 |       } else {
48 |         const ext = path.extname(file);
49 |         const isEnv = file.startsWith(".env");
50 |         const isDockerfile = file === "Dockerfile";
51 |
52 |         if (ALLOWED_EXTS.has(ext) || isEnv || isDockerfile) {
53 |           if (!file.endsWith("package-lock.json") && !file.endsWith(".log") && !file.endsWith(".exe") && file
54 |             results.push({
55 |               fullPath,
56 |               relPath,
57 |               size: stat.size,
58 |               name: file,
59 |               category: relPath.startsWith("backend") ? "Backend" : relPath.startsWith("frontend") ? "Frontend
60 |             });
61 |           }
62 |         }
63 |       }
64 |     }
65 |   } catch (err) {
66 |     console.error("Error reading dir:", err.message);
67 |   }
68 |   return results;
69 | }
70 |
71 | function generateCompletePDF(outputPath) {
72 |   console.log(`Starting PDF compilation to: ${outputPath}...`);
73 |
74 |   const doc = new PDFDocument({
75 |     margin: 40,
76 |     size: "A4",
77 |     bufferPages: true,
78 |   });
79 |
80 |   const stream = fs.createWriteStream(outputPath);
```

KATALYST

Source Code: backend/generate_all_files_pdf.js (Cont.)

Generated: 22/8/2026 | Backend

```
81 | doc.pipe(stream);
83 | // Styling Palette
84 | const primaryColor = "#db2777"; // Tailwind pink-600
85 | const secondaryColor = "#4f46e5"; // Tailwind indigo-600
86 | const darkBg = "#0f172a"; // Slate 900
87 | const textColor = "#1e293b"; // Slate 800
88 | const mutedText = "#64748b"; // Slate 500
89 | const borderLight = "#e2e8f0"; // Slate 200
91 | function drawHeaderBanner(title, subtitle) {
92 |   doc.rect(0, 0, 595, 110).fill(darkBg);
93 |   doc
94 |     .fillColor("#ffffff")
95 |     .fontSize(22)
96 |     .font("Helvetica-Bold")
97 |     .text("KATALYST", 40, 28, { continued: true })
98 |     .fillColor(primaryColor)
99 |     .text(".", { continued: false });
101 |   doc
102 |     .fillColor("#e2e8f0")
103 |     .fontSize(11)
104 |     .font("Helvetica")
105 |     .text(title, 40, 58);
107 |   doc
108 |     .fillColor("#94a3b8")
109 |     .fontSize(8.5)
110 |     .text(`Generated: ${new Date().toLocaleDateString()} | ${subtitle}`, 40, 78);
112 |   doc.y = 130;
113 | }
115 | function addSectionHeading(title) {
116 |   if (doc.y > 680) doc.addPage();
117 |   doc.moveDown(0.5);
118 |   doc
119 |     .fillColor(primaryColor)
120 |     .fontSize(14)
121 |     .font("Helvetica-Bold")
122 |     .text(title)
123 |     .moveDown(0.2);
125 |   doc
126 |     .strokeColor(primaryColor)
127 |     .lineWidth(1.5)
128 |     .moveTo(40, doc.y)
129 |     .lineTo(555, doc.y)
130 |     .stroke()
131 |     .moveDown(0.5);
132 | }
134 | function addSubHeading(title) {
135 |   if (doc.y > 700) doc.addPage();
136 |   doc
137 |     .fillColor(secondaryColor)
138 |     .fontSize(11)
139 |     .font("Helvetica-Bold")
140 |     .text(title)
141 |     .moveDown(0.3);
142 | }
144 | // --- COVER / TITLE PAGE ---
145 | doc.rect(0, 0, 595, 842).fill(darkBg);
147 | doc
148 |   .fillColor("#ffffff")
149 |   .fontSize(36)
150 |   .font("Helvetica-Bold")
151 |   .text("KATALYST", 50, 180, { continued: true })
152 |   .fillColor(primaryColor)
153 |   .text(".", { continued: false });
155 | doc
156 |   .fillColor("#f472b6")
157 |   .fontSize(18)
158 |   .font("Helvetica-Bold")
159 |   .text("Full-Stack Learning & Mentorship Platform", 50, 235);
161 | doc
162 |   .fillColor("#cbd5e1")
163 |   .fontSize(12)
```

```
164 |     .font("Helvetica")
165 |     .text("Complete Source Code, System Architecture & File Documentation", 50, 265, { width: 495 });
167 | doc
168 |     .strokeColor(primaryColor)
169 |     .lineWidth(2)
170 |     .moveTo(50, 310)
171 |     .lineTo(545, 310)
172 |     .stroke();
174 | // Cover stats box
175 | const allFiles = getFilesRecursively(rootDir, rootDir);
176 | const backendFiles = allFiles.filter(f => f.category === "Backend");
177 | const frontendFiles = allFiles.filter(f => f.category === "Frontend");
179 | doc
180 |     .rect(50, 340, 495, 140)
181 |     .fillAndStroke("#1e293b", "#334155");
183 | doc
184 |     .fillColor("#ffffff")
185 |     .fontSize(11)
186 |     .font("Helvetica-Bold")
187 |     .text("PROJECT SUMMARY METRICS", 70, 360);
189 | const metrics = [
190 |     ["Platform Version:", "2.0.0 (Production Architecture)", "Backend Framework:", "Node.js 20+ / Express.js 5
191 |     ["Frontend Stack:", "React 19, Vite, Tailwind CSS", "Database:", "MongoDB Atlas (Mongoose ORM)"],
192 |     ["Total Source Files:", `${allFiles.length} files included`, "Security:", "JWT Authentication & RBAC"],
193 |     ["Frontend Files:", `${frontendFiles.length} modules & views`, "Backend Files:", `${backendFiles.length} c
194 | ];
196 | let mY = 385;
197 | metrics.forEach(m => {
198 |     doc.font("Helvetica-Bold").fontSize(9).fillColor("#94a3b8").text(m[0], 70, mY, { width: 110 });
199 |     doc.font("Helvetica").fontSize(9).fillColor("#f8f9fa").text(m[1], 180, mY, { width: 140 });
200 |     doc.font("Helvetica-Bold").fontSize(9).fillColor("#94a3b8").text(m[2], 330, mY, { width: 100 });
201 |     doc.font("Helvetica").fontSize(9).fillColor("#f8f9fa").text(m[3], 430, mY, { width: 110 });
202 |     mY += 20;
203 | });
205 | doc
206 |     .fillColor("#94a3b8")
207 |     .fontSize(9.5)
208 |     .font("Helvetica")
209 |     .text(`Compiled on: ${new Date().toLocaleDateString('en-US', { weekday: 'long', year: 'numeric', month: 'l
210 |     .text("Confidential & Proprietary - Katalyst Development Team", 50, 735);
212 | // --- PAGE 2: TABLE OF CONTENTS & EXECUTIVE SUMMARY ---
213 | doc.addPage();
214 | drawHeaderBanner("Executive Summary & Table of Contents", "System Overview");
216 | addSectionHeading("1. Executive Summary");
217 | doc
218 |     .fillColor(textColor)
219 |     .fontSize(9.5)
220 |     .font("Helvetica")
221 |     .text(
222 |         "Katalyst is a full-stack educational and mentorship platform engineered to connect students with profes
223 |         { align: "justify", lineGap: 3 }
224 |     )
225 |     .moveDown(1);
227 | addSectionHeading("2. Document Table of Contents");
229 | const tocItems = [
230 |     ["Section 1", "Executive Summary & System Architecture", "High-level overview & system design"],
231 |     ["Section 2", "Technology Stack & Layer Mapping", "Frontend, backend, database, and auth stack"],
232 |     ["Section 3", "Complete File Directory Inventory", "All project files categorized with paths & sizes"],
233 |     ["Section 4", "Backend Architecture & Data Models", "Mongoose schemas, controllers, and REST routes"],
234 |     ["Section 5", "Frontend Architecture & Portal Pages", "React components, state contexts, and routes"],
235 |     ["Section 6", "API Reference & Access Control Matrix", "All REST endpoints, request/response models"],
236 |     ["Section 7", "Complete Source Code Listings", "Full file contents and implementations"]
237 | ];
239 | let tocY = doc.y;
240 | doc.rect(40, tocY, 515, 20).fill("#f1f5f9");
241 | doc.font("Helvetica-Bold").fontSize(9).fillColor(darkBg);
242 | doc.text("Section", 50, tocY + 5, { width: 80 });
243 | doc.text("Topic", 130, tocY + 5, { width: 200 });
244 | doc.text("Coverage", 330, tocY + 5, { width: 215 });
246 | tocY += 20;
```

```
247 | doc.font("Helvetica").fontSize(8.5);
248 | tocItems.forEach((item, idx) => {
249 |   const bg = idx % 2 === 0 ? "#ffffff" : "#f8fafc";
250 |   doc.rect(40, tocY, 515, 18).fill(bg);
251 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(item[0], 50, tocY + 4, { width: 80 });
252 |   doc.fillColor(darkBg).font("Helvetica-Bold").text(item[1], 130, tocY + 4, { width: 200 });
253 |   doc.fillColor(mutedText).font("Helvetica").text(item[2], 330, tocY + 4, { width: 215 });
254 |   tocY += 18;
255 | });
256 |
257 | doc.y = tocY + 15;
258 |
259 | // --- PAGE 3: TECH STACK ARCHITECTURE ---
260 | doc.addPage();
261 | drawHeaderBanner("Technology Stack & Architecture", "Architecture Blueprint");
262 |
263 | addSectionHeading("3. Architecture & Technology Stack");
264 |
265 | const techStackDetails = [
266 |   ["Frontend Core", "React 19.0.0 + Vite 8.2.0", "Fast modular SPA client with lightning HMR"],
267 |   ["Styling Framework", "Tailwind CSS 3.4 + PostCSS", "Custom theme tokens, glassmorphism UI, Dark mode"],
268 |   ["Routing & Nav", "React Router v7", "Declarative browser routing & protected role routes"],
269 |   ["State Management", "React Context (Auth & Theme)", "Global authentication persistence & theme switches"],
270 |   ["Data Visualization", "Recharts 2.15", "Interactive progress rings & readiness index charts"],
271 |   ["Icons & UI", "Lucide React 1.31", "Feather-style SVG icon system across all portals"],
272 |   ["Backend Runtime", "Node.js 20+ / Express 5.2", "Non-blocking RESTful API & middleware pipeline"],
273 |   ["Database Store", "MongoDB Atlas / Mongoose 9.9", "Schema validation, indexing, and object relations"],
274 |   ["Authentication", "JWT (jsonwebtoken 9.0) + bcryptjs", "Stateless bearer token authorization & password h"],
275 |   ["AI Services", "Google Generative AI (Gemini 1.5)", "Resume analysis, personalized roadmaps & chat"],
276 |   ["File Handling", "Multer Middleware", "Local disk storage for student PDF resumes"],
277 |   ["Containerization", "Docker & Docker Compose", "Multi-stage build Dockerfiles for full-stack isolation"]
278 | ];
279 |
280 | let tsY = doc.y;
281 | doc.rect(40, tsY, 515, 20).fill("#fce7f3");
282 | doc.font("Helvetica-Bold").fontSize(9).fillColor(darkBg);
283 | doc.text("Layer", 50, tsY + 5, { width: 110 });
284 | doc.text("Technology", 160, tsY + 5, { width: 170 });
285 | doc.text("Role & Purpose", 330, tsY + 5, { width: 215 });
286 |
287 | tsY += 20;
288 | doc.font("Helvetica").fontSize(8);
289 | techStackDetails.forEach((row, idx) => {
290 |   const bg = idx % 2 === 0 ? "#ffffff" : "#fdf2f8";
291 |   doc.rect(40, tsY, 515, 17).fill(bg);
292 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(row[0], 50, tsY + 4, { width: 110 });
293 |   doc.fillColor(darkBg).font("Helvetica").text(row[1], 160, tsY + 4, { width: 170 });
294 |   doc.fillColor(mutedText).font("Helvetica").text(row[2], 330, tsY + 4, { width: 215 });
295 |   tsY += 17;
296 | });
297 |
298 | doc.y = tsY + 20;
299 |
300 | // --- COMPLETE DIRECTORY INVENTORY TABLE ---
301 | addSectionHeading("4. Complete File Inventory List");
302 | doc
303 |   .fillColor(mutedText)
304 |   .fontSize(8.5)
305 |   .font("Helvetica")
306 |   .text(`Total registered source and configuration files in this build: ${allFiles.length}`)
307 |   .moveDown(0.5);
308 |
309 | let fileTableY = doc.y;
310 | doc.rect(40, fileTableY, 515, 18).fill("#f1f5f9");
311 | doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
312 | doc.text("Category", 48, fileTableY + 4, { width: 75 });
313 | doc.text("Relative File Path", 125, fileTableY + 4, { width: 310 });
314 | doc.text("Size", 445, fileTableY + 4, { width: 100, align: "right" });
315 |
316 | fileTableY += 18;
317 | doc.font("Helvetica").fontSize(7.5);
318 |
319 | allFiles.forEach((f, idx) => {
320 |   if (fileTableY > 750) {
321 |     doc.addPage();
322 |     drawHeaderBanner("Complete File Inventory List (Cont.)", "File Inventory");
323 |     fileTableY = doc.y;
324 |     doc.rect(40, fileTableY, 515, 18).fill("#f1f5f9");
325 |     doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
326 |     doc.text("Category", 48, fileTableY + 4, { width: 75 });
327 |     doc.text("Relative File Path", 125, fileTableY + 4, { width: 310 });
328 |     doc.text("Size", 445, fileTableY + 4, { width: 100, align: "right" });
```

```
329 |         fileTableY += 18;
330 |         doc.font("Helvetica").fontSize(7.5);
331 |     }
332 |     const bg = idx % 2 === 0 ? "ffffff" : "#f8fafc";
333 |     doc.rect(40, fileTableY, 515, 15).fill(bg);
334 |     const catColor = f.category === "Backend" ? secondaryColor : f.category === "Frontend" ? primaryColor : "#f8f8f8";
335 |     doc.fillColor(catColor).font("Helvetica-Bold").text(f.category, 48, fileTableY + 3, { width: 75 });
336 |     doc.fillColor(darkBg).font("Helvetica").text(f.relPath, 125, fileTableY + 3, { width: 310 });
337 |     doc.fillColor(mutedText).text(`${(f.size / 1024).toFixed(1)} KB`, 445, fileTableY + 3, { width: 100, align: "right" });
338 |     fileTableY += 15;
339 | });
340 | doc.y = fileTableY + 20;
341 | // --- SECTION 5: BACKEND DATA MODELS & SCHEMAS ---
342 | doc.addPage();
343 | drawHeaderBanner("Backend Data Models & Architecture", "Database Design");
344 | addSectionHeading("5. Database Models & Schema Specifications");
345 | const modelsSummary = [
346 |     {
347 |         name: "Student (models/Student.js)",
348 |         fields: "name, email, password, role ('student'), bio, skills (Array), resumeUrl, assignedMentor (Object)",
349 |         desc: "Stores learner profiles, credentials, skills matrix, resume links, and assigned mentor associations",
350 |     },
351 |     {
352 |         name: "Mentor (models/Mentor.js)",
353 |         fields: "name, email, password, role ('mentor'), company, designation, expertise (Array), bio, assignedStudents (Array)",
354 |         desc: "Maintains industry professional mentor records, company background, mentee limits, and assigned learners",
355 |     },
356 |     {
357 |         name: "Admin (models/Admin.js)",
358 |         fields: "name, email, password, role ('admin'), permissions (Array), department, activeStatus",
359 |         desc: "Superuser entity with full platform permissions to manage courses, assign mentors, and generate reports",
360 |     },
361 |     {
362 |         name: "Training (models/Training.js)",
363 |         fields: "title, description, category, level, duration, thumbnail, modules (Array of {title, videos: [{title, content}]}",
364 |         desc: "Course catalog containing structured learning modules, video lessons, quiz assessments, and completion tracking",
365 |     },
366 |     {
367 |         name: "Meeting (models/Meeting.js)",
368 |         fields: "studentId, mentorId, title, agenda, scheduledDate, startTime, endTime, status ('pending'|'approved'|'cancelled')",
369 |         desc: "1-on-1 mentor meeting requests, schedule slots, Google Meet links, mentor acceptance status, and meeting history",
370 |     },
371 |     {
372 |         name: "Progress (models/Progress.js)",
373 |         fields: "studentId, trainingId, completedVideos (Array), quizScores (Array), placementReadiness (0-100)",
374 |         desc: "Tracks video lesson completions, quiz results, placement readiness formula index, and certificate eligibility",
375 |     },
376 |     {
377 |         name: "Notification (models/Notification.js)",
378 |         fields: "recipientId, senderId, title, message, type ('meeting'|'course'|'system'), isRead, actionUrl, createdAt",
379 |         desc: "In-app notifications delivering meeting approvals, course updates, feedback, and reminders to use platform features",
380 |     }
381 | ];
382 | modelsSummary.forEach(m => {
383 |     if (doc.y > 660) {
384 |         doc.addPage();
385 |         drawHeaderBanner("Backend Data Models & Architecture (Cont.)", "Database Design");
386 |     }
387 |     addSubHeading(m.name);
388 |     doc
389 |         .rect(40, doc.y, 515, 45)
390 |         .fillAndStroke("#f8f8f8", "borderLight");
391 |     doc
392 |         .fillColor(darkBg)
393 |         .fontSize(8)
394 |         .font("Helvetica-Bold")
395 |         .text("Schema Fields:", 48, doc.y - 40)
396 |         .font("Helvetica")
397 |         .text(m.fields, 125, doc.y - 40, { width: 420 });
398 |     doc
399 |         .font("Helvetica-Bold")
400 |         .text(m.desc, 160, doc.y - 40, { width: 420 });
401 | });
```

```
410 |     .text("Description:", 48, doc.y - 20)
411 |     .font("Helvetica")
412 |     .fillColor(mutedText)
413 |     .text(m.desc, 125, doc.y - 20, { width: 420 });
415 |     doc.y += 10;
416 | });
418 | // --- SECTION 6: API REFERENCE & ACCESS MATRIX ---
419 | doc.addPage();
420 | drawHeaderBanner("RESTful API Routes & Access Matrix", "API Endpoints");
422 | addSectionHeading("6. API Endpoints Reference");
424 | const fullApiList = [
425 |   ["POST", "/api/auth/register", "Public", "Student registration with bcrypt hashing"],
426 |   ["POST", "/api/auth/login", "Public", "Unified login for student, mentor, admin (JWT)"],
427 |   ["GET", "/api/auth/me", "Auth", "Get active profile based on JWT token"],
428 |   ["GET", "/api/students/profile", "Student", "Get current student profile & mentor details"],
429 |   ["PUT", "/api/students/profile", "Student", "Update student bio, skills, and target role"],
430 |   ["POST", "/api/students/resume", "Student", "Upload student resume PDF via Multer"],
431 |   ["GET", "/api/trainings", "Public/Auth", "List all available trainings and courses"],
432 |   ["GET", "/api/trainings/:id", "Auth", "Get course modules, lessons, and student progress"],
433 |   ["POST", "/api/trainings/:id/enroll", "Student", "Enroll in a training track"],
434 |   ["POST", "/api/trainings/:id/complete-video", "Student", "Mark video lesson completed & update progress"],
435 |   ["POST", "/api/trainings/:id/submit-quiz", "Student", "Submit quiz responses & calculate score"],
436 |   ["GET", "/api/meetings/student", "Student", "Get all meetings booked by student"],
437 |   ["POST", "/api/meetings", "Student", "Book a new meeting with assigned mentor"],
438 |   ["GET", "/api/meetings/mentor", "Mentor", "Get all meeting requests assigned to mentor"],
439 |   ["PUT", "/api/meetings/:id/status", "Mentor", "Approve/Reject meeting and supply Meet link"],
440 |   ["GET", "/api/notifications", "Auth", "Fetch user notifications list"],
441 |   ["PUT", "/api/notifications/:id/read", "Auth", "Mark notification as read"],
442 |   ["POST", "/api/ai/resume-analyze", "Student", "AI resume strength & improvement analysis"],
443 |   ["POST", "/api/ai/career-roadmap", "Student", "AI personalized milestone career roadmap"],
444 |   ["POST", "/api/ai/chatbot", "Auth", "AI chatbot assistant for student guidance"],
445 |   ["GET", "/api/admin/stats", "Admin", "Fetch system-wide metrics, counts & analytics"],
446 |   ["GET", "/api/admin/users", "Admin", "List and manage all registered users"]
447 | ];
449 | let apiY = doc.y;
450 | doc.rect(40, apiY, 515, 18).fill("#fce7f3");
451 | doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
452 | doc.text("Method", 48, apiY + 4, { width: 50 });
453 | doc.text("Endpoint Route", 100, apiY + 4, { width: 175 });
454 | doc.text("Role", 280, apiY + 4, { width: 70 });
455 | doc.text("Description", 355, apiY + 4, { width: 195 });
457 | apiY += 18;
458 | doc.font("Helvetica").fontSize(7.5);
460 | fullApiList.forEach((row, idx) => {
461 |   if (apiY > 760) {
462 |     doc.addPage();
463 |     drawHeaderBanner("RESTful API Routes & Access Matrix (Cont.)", "API Endpoints");
464 |     apiY = doc.y;
465 |     doc.rect(40, apiY, 515, 18).fill("#fce7f3");
466 |     doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
467 |     doc.text("Method", 48, apiY + 4, { width: 50 });
468 |     doc.text("Endpoint Route", 100, apiY + 4, { width: 175 });
469 |     doc.text("Role", 280, apiY + 4, { width: 70 });
470 |     doc.text("Description", 355, apiY + 4, { width: 195 });
471 |     apiY += 18;
472 |     doc.font("Helvetica").fontSize(7.5);
473 |   }
475 |   const bg = idx % 2 === 0 ? "#ffffff" : "#fdf2f8";
476 |   doc.rect(40, apiY, 515, 15).fill(bg);
478 |   const mColor = row[0] === "POST" ? "#0284c7" : row[0] === "GET" ? "#16a34a" : "#d97706";
479 |   doc.fillColor(mColor).font("Helvetica-Bold").text(row[0], 48, apiY + 3, { width: 50 });
480 |   doc.fillColor(darkBg).font("Helvetica").text(row[1], 100, apiY + 3, { width: 175 });
481 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(row[2], 280, apiY + 3, { width: 70 });
482 |   doc.fillColor(mutedText).font("Helvetica").text(row[3], 355, apiY + 3, { width: 195 });
483 |   apiY += 15;
484 | });
486 | doc.y = apiY + 20;
488 | // --- SECTION 7: SOURCE CODE OF ALL FILES ---
489 | doc.addPage();
490 | drawHeaderBanner("Complete Source Code Listings", "Full Project Files");
492 | addSectionHeading("7. Complete Project Source Code");
```

```
493 | doc
494 |   .fillColor(mutedText)
495 |   .fontSize(8.5)
496 |   .font("Helvetica")
497 |   .text("The following sections contain the complete, verbatim source code for each file in the project orga
498 |   .moveDown(1);
500 | // Print all files with code
501 | allFiles.forEach((fileObj, fIdx) => {
502 |   let content = "";
503 |   try {
504 |     content = fs.readFileSync(fileObj.fullPath, "utf-8");
505 |   } catch (e) {
506 |     content = `// Error reading file: ${e.message}`;
507 |   }
509 |   // New file header
510 |   if (doc.y > 640) {
511 |     doc.addPage();
512 |     drawHeaderBanner("Source Code: " + fileObj.relPath, fileObj.category);
513 |   }
515 |   doc.moveDown(0.5);
516 |   doc
517 |     .rect(40, doc.y, 515, 24)
518 |     .fill(darkBg);
520 |   doc
521 |     .fillColor("#ffffff")
522 |     .fontSize(9.5)
523 |     .font("Helvetica-Bold")
524 |     .text(`File ${fIdx + 1} of ${allFiles.length}: ${fileObj.relPath}`, 50, doc.y - 18, { continued: true })
525 |     .fillColor("#94a3b8")
526 |     .fontSize(8)
527 |     .text(` ${fileObj.size / 1024}.toFixed(1)} KB`, { continued: false });
529 |   doc.moveDown(0.6);
531 |   // Print file lines
532 |   const lines = content.split(/\r?\n/);
533 |   doc.font("Courier").fontSize(7).fillColor("#1e293b");
535 |   for (let i = 0; i < lines.length; i++) {
536 |     if (doc.y > 770) {
537 |       doc.addPage();
538 |       drawHeaderBanner("Source Code: " + fileObj.relPath + " (Cont.)", fileObj.category);
539 |       doc.font("Courier").fontSize(7).fillColor("#1e293b");
540 |     }
542 |     const lineNum = String(i + 1).padStart(4, " ");
543 |     const lineText = lines[i];
544 |     // Draw background for code line
545 |     const lineBg = i % 2 === 0 ? "ffffff" : "f8f9fa";
546 |     doc.rect(40, doc.y, 515, 9.5).fill(lineBg);
548 |     doc
549 |       .fillColor("#94a3b8")
550 |       .text(lineNum + " | ", 42, doc.y + 1, { continued: true })
551 |       .fillColor("#0f172a")
552 |       .text(lineText.substring(0, 110), { continued: false });
554 |     doc.y += 0.5;
555 |   }
557 |   doc.moveDown(0.8);
558 | });
560 | // --- FOOTERS & NUMBERING ON ALL PAGES ---
561 | const range = doc.bufferedPageRange();
562 | for (let i = 0; i < range.start + range.count; i++) {
563 |   doc.switchToPage(i);
565 |   // Skip cover page footer
566 |   if (i === 0) continue;
568 |   doc
569 |     .strokeColor(borderLight)
570 |     .lineWidth(0.5)
571 |     .moveTo(40, 805)
572 |     .lineTo(555, 805)
573 |     .stroke();
575 |   doc
576 |     .fillColor("#94a3b8")
577 |     .fontSize(8)
```



```
578 |     .font("Helvetica")
579 |     .text("KATALYST - Full-Stack Student Learning & Mentorship Platform", 40, 812, { continued: true })
580 |     .text(`Page ${i + 1} of ${range.count}`, { align: "right" });
581 | }
582 |
583 | doc.end();
584 |
585 | stream.on("finish", () => {
586 |     console.log(` Complete PDF compiled successfully: ${outputPath} (${range.count} pages)`);
587 | });
588 | }
589 |
590 | // Target Paths
591 | const projectPdfPath = path.join(rootDir, "Student_Learning_App_Complete_Documentation.pdf");
592 | const standardPdfPath = path.join(rootDir, "Student_Learning_App_Documentation.pdf");
593 | generateCompletePDF(projectPdfPath);
594 | generateCompletePDF(standardPdfPath); (0.1 KB)
595 |
596 | 1 | // Forwarding to generate_all_files_pdf.js
597 | 2 | require("../generate_all_files_pdf.js"); (0.6 KB)
598 | 3 |
599 | 1 | const jwt = require("jsonwebtoken");
600 | 2 |
601 | 3 | const protect = (req, res, next) => {
602 | 4 |     let token;
603 | 5 |     if (
604 | 6 |         req.headers.authorization &&
605 | 7 |         req.headers.authorization.startsWith("Bearer")
606 | 8 |     ) {
607 | 9 |         try {
608 | 10 |             token = req.headers.authorization.split(" ")[1];
609 | 11 |             const decoded = jwt.verify(token, process.env.JWT_SECRET);
610 | 12 |             req.user = decoded; // { id, role }
611 | 13 |             next();
612 | 14 |         } catch (err) {
613 | 15 |             return res.status(401).json({ message: "Not authorized, token failed" });
614 | 16 |         }
615 | 17 |     }
616 | 18 |     if (!token) {
617 | 19 |         return res.status(401).json({ message: "Not authorized, no token" });
618 | 20 |     }
619 | 21 | };
620 |
621 | 22 | module.exports = { protect }; (0.3 KB)
622 | 23 |
623 | 1 | const allowRoles = (...roles) => {
624 | 2 |     return (req, res, next) => {
625 | 3 |         if (!req.user || !roles.includes(req.user.role)) {
626 | 4 |             return res.status(403).json({
627 | 5 |                 message: `Access denied. Required role: ${roles.join(" or ")}`,
628 | 6 |             });
629 | 7 |         }
630 | 8 |         next();
631 | 9 |     };
632 | 10 | };
633 |
634 | 11 | module.exports = { allowRoles }; (1.1 KB)
635 | 12 |
636 | 1 | const mongoose = require("mongoose");
637 | 2 | const bcrypt = require("bcryptjs");
638 | 3 | const adminSchema = new mongoose.Schema(
639 | 4 |     {
640 | 5 |         name: {
641 | 6 |             type: String,
642 | 7 |             required: true,
643 | 8 |             trim: true,
644 | 9 |         },
645 | 10 |         email: {
646 | 11 |             type: String,
647 | 12 |             required: true,
648 | 13 |             unique: true,
649 | 14 |             lowercase: true,
650 | 15 |             trim: true,
651 | 16 |         },
652 | 17 |         password: {
653 | 18 |             type: String,
654 | 19 |             required: true,
```



```
23 |     minlength: 6,
24 |   },
25 |   profilePic: {
26 |     type: String,
27 |     default: "",
28 |   },
29 |   role: {
30 |     type: String,
31 |     default: "admin",
32 |   },
33 |   isActive: {
34 |     type: Boolean,
35 |     default: true,
36 |   },
37 | },
38 | {
39 |   timestamps: true,
40 | }
41 | );
42 |
43 | // Hash password before saving
44 | adminSchema.pre("save", async function () {
45 |   if (!this.isModified("password")) {
46 |     return;
47 |   }
48 |   const salt = await bcrypt.genSalt(10);
49 |   this.password = await bcrypt.hash(this.password, salt);
50 | });
51 |
52 | // Check password
53 | adminSchema.methods.matchPassword = async function (enteredPassword) {
54 |   return await bcrypt.compare(enteredPassword, this.password);
55 | };
56 |
57 | module.exports = mongoose.model("Admin", adminSchema);
58 |
59 | const mongoose = require("mongoose");
60 | const { v4: uuidv4 } = require("uuid");
61 | const certificateSchema = new mongoose.Schema(
62 |   {
63 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true },
64 |     trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training", required: true },
65 |     studentName: String,
66 |     trainingTitle: String,
67 |     issuedDate: { type: Date, default: Date.now },
68 |     certificateUrl: { type: String, default: "" },
69 |     uniqueId: { type: String, default: () => uuidv4().slice(0, 12).toUpperCase() },
70 |     isValid: { type: Boolean, default: true },
71 |   },
72 |   { timestamps: true }
73 | );
74 |
75 | module.exports = mongoose.model("Certificate", certificateSchema);
76 |
77 | const mongoose = require("mongoose");
78 | const feedbackSchema = new mongoose.Schema(
79 |   {
80 |     fromId: { type: mongoose.Schema.Types.ObjectId, required: true, refPath: "fromRole" },
81 |     fromRole: { type: String, enum: ["student", "mentor"], required: true },
82 |     toId: { type: mongoose.Schema.Types.ObjectId, required: true, refPath: "toRole" },
83 |     toRole: { type: String, enum: ["student", "mentor"], required: true },
84 |     meetingId: { type: mongoose.Schema.Types.ObjectId, ref: "Meeting" },
85 |     trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training" },
86 |     rating: { type: Number, min: 1, max: 5, required: true },
87 |     comment: { type: String, default: "" },
88 |     type: { type: String, enum: ["meeting", "training", "general"], default: "meeting" },
89 |   },
90 |   { timestamps: true }
91 | );
92 |
93 | module.exports = mongoose.model("Feedback", feedbackSchema);
```

(1.1 KB)

```
1 | const mongoose = require("mongoose");
3 | const meetingSchema = new mongoose.Schema(
4 |   {
5 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true },
6 |     mentorId: { type: mongoose.Schema.Types.ObjectId, ref: "Mentor", required: true },
7 |     topic: { type: String, required: true },
8 |     agenda: { type: String, default: "" },
9 |     scheduledDate: { type: Date, required: true },
10 |     scheduledTime: { type: String, required: true },
11 |     duration: { type: Number, default: 60 }, // minutes
12 |     status: {
13 |       type: String,
14 |       enum: ["pending", "accepted", "rejected", "completed", "cancelled"],
15 |       default: "pending",
16 |     },
17 |     meetLink: { type: String, default: "" },
18 |     notes: { type: String, default: "" },
19 |     studentFeedback: {
20 |       rating: { type: Number, min: 1, max: 5 },
21 |       comment: String,
22 |       givenAt: Date,
23 |     },
24 |     mentorFeedback: {
25 |       rating: { type: Number, min: 1, max: 5 },
26 |       comment: String,
27 |       givenAt: Date,
28 |     },
29 |     rejectionReason: { type: String, default: "" },
30 |   },
31 |   { timestamps: true }
32 | );
34 | module.exports = mongoose.model("Meeting", meetingSchema);
```

(1.7 KB)

```
1 | const mongoose = require("mongoose");
2 | const bcrypt = require("bcryptjs");
4 | const mentorSchema = new mongoose.Schema(
5 |   {
6 |     name: {
7 |       type: String,
8 |       required: true,
9 |       trim: true,
10 |     },
12 |     email: {
13 |       type: String,
14 |       required: true,
15 |       unique: true,
16 |       lowercase: true,
17 |       trim: true,
18 |     },
20 |     password: {
21 |       type: String,
22 |       required: true,
23 |       minlength: 6,
24 |     },
26 |     phone: {
27 |       type: String,
28 |       default: "",
29 |     },
31 |     bio: {
32 |       type: String,
33 |       default: "",
34 |     },
36 |     profilePic: {
37 |       type: String,
38 |       default: "",
39 |     },
41 |     expertise: [
42 |       {
43 |         type: String,
44 |       },
45 |     ],

```

```
47 |     designation: {
48 |       type: String,
49 |       default: "",
50 |     },
52 |     company: {
53 |       type: String,
54 |       default: "",
55 |     },
57 |     assignedStudents: [
58 |       {
59 |         type: mongoose.Schema.Types.ObjectId,
60 |         ref: "Student",
61 |       },
62 |     ],
64 |     rating: {
65 |       type: Number,
66 |       default: 0,
67 |       min: 0,
68 |       max: 5,
69 |     },
71 |     totalRatings: {
72 |       type: Number,
73 |       default: 0,
74 |     },
76 |     role: {
77 |       type: String,
78 |       default: "mentor",
79 |     },
81 |     isActive: {
82 |       type: Boolean,
83 |       default: true,
84 |     },
86 |     availability: [
87 |       {
88 |         day: String,
89 |         slots: [String],
90 |       },
91 |     ],
92 |   },
93 |   {
94 |     timestamps: true,
95 |   }
96 | );
98 | // Hash password before saving
99 | mentorSchema.pre("save", async function () {
100 |   if (!this.isModified("password")) {
101 |     return;
102 |   }
104 |   const salt = await bcrypt.genSalt(10);
105 |   this.password = await bcrypt.hash(this.password, salt);
106 | });
108 | // Check password
109 | mentorSchema.methods.matchPassword = async function (enteredPassword) {
110 |   return await bcrypt.compare(enteredPassword, this.password);
111 | };
113 | module.exports = mongoose.model("Mentor", mentorSchema);
```

(0.7 KB)

```
1 | const mongoose = require("mongoose");
3 | const notificationSchema = new mongoose.Schema(
4 |   {
5 |     userId: { type: mongoose.Schema.Types.ObjectId, required: true },
6 |     userRole: { type: String, enum: ["student", "mentor", "admin"], required: true },
7 |     title: { type: String, required: true },
8 |     message: { type: String, required: true },
9 |     type: {
10 |       type: String,
11 |       enum: ["meeting", "training", "feedback", "system", "certificate", "general"],
12 |       default: "general",
13 |     },
14 |     isRead: { type: Boolean, default: false },
15 |     link: { type: String, default: "" },
16 |     icon: { type: String, default: "bell" },
17 |   },
18 |   { timestamps: true }
19 | );
```

```
23 | module.exports = mongoose.model("Notification", notificationSchema);
```

(1.2 KB)

```
1 | const mongoose = require("mongoose");
3 | const progressSchema = new mongoose.Schema(
4 |   {
5 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true, unique: true },
6 |     trainingCompletion: { type: Number, default: 0, min: 0, max: 100 }, // %
7 |     meetingsAttended: { type: Number, default: 0 },
8 |     totalMeetingsScheduled: { type: Number, default: 0 },
9 |     quizScores: [
10 |       {
11 |         trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training" },
12 |         score: Number,
13 |         maxScore: Number,
14 |         attemptedAt: { type: Date, default: Date.now },
15 |       },
16 |     ],
17 |     assignmentsSubmitted: { type: Number, default: 0 },
18 |     attendanceRate: { type: Number, default: 0, min: 0, max: 100 }, // %
19 |     overallScore: { type: Number, default: 0, min: 0, max: 100 }, // weighted composite
20 |     placementReadiness: { type: Number, default: 0, min: 0, max: 100 },
21 |     lastUpdated: { type: Date, default: Date.now },
22 |     milestones: [
23 |       {
24 |         title: String,
25 |         achievedAt: Date,
26 |         type: { type: String, enum: ["training", "meeting", "quiz", "certificate"] },
27 |       },
28 |     ],
29 |   },
30 |   { timestamps: true }
31 | );
```

```
33 | module.exports = mongoose.model("Progress", progressSchema);
```

(1.6 KB)

```
1 | const mongoose = require("mongoose");
2 | const bcrypt = require("bcryptjs");
4 | const studentSchema = new mongoose.Schema(
5 |   {
6 |     name: {
7 |       type: String,
8 |       required: true,
9 |       trim: true,
10 |     },
12 |     email: {
13 |       type: String,
14 |       required: true,
15 |       unique: true,
16 |       lowercase: true,
17 |       trim: true,
18 |     },
20 |     password: {
21 |       type: String,
22 |       required: true,
```

```
23 |         minlength: 6,
24 |     },
25 |     phone: {
26 |         type: String,
27 |         default: "",
28 |     },
29 |     bio: {
30 |         type: String,
31 |         default: "",
32 |     },
33 |     profilePic: {
34 |         type: String,
35 |         default: "",
36 |     },
37 |     resumeUrl: {
38 |         type: String,
39 |         default: "",
40 |     },
41 |     skills: [
42 |         {
43 |             type: String,
44 |         },
45 |     ],
46 |     assignedMentor: {
47 |         type: mongoose.Schema.Types.ObjectId,
48 |         ref: "Mentor",
49 |         default: null,
50 |     },
51 |     enrolledTrainings: [
52 |         {
53 |             type: mongoose.Schema.Types.ObjectId,
54 |             ref: "Training",
55 |         },
56 |     ],
57 |     role: {
58 |         type: String,
59 |         default: "student",
60 |     },
61 |     isActive: {
62 |         type: Boolean,
63 |         default: true,
64 |     },
65 |     lastLogin: {
66 |         type: Date,
67 |     },
68 | },
69 | {
70 |     timestamps: true,
71 | }
72 | );
73 | // Hash password before saving
74 | studentSchema.pre("save", async function () {
75 |     if (!this.isModified("password")) {
76 |         return;
77 |     }
78 |     const salt = await bcrypt.genSalt(10);
79 |     this.password = await bcrypt.hash(this.password, salt);
80 | });
81 | // Check password
82 | studentSchema.methods.matchPassword = async function (enteredPassword) {
83 |     return await bcrypt.compare(enteredPassword, this.password);
84 | };
85 | module.exports = mongoose.model("Student", studentSchema);
```

(1.6 KB)

```
1 | const mongoose = require("mongoose");
3 | const videoSchema = new mongoose.Schema({
4 |   title: String,
5 |   url: String,
6 |   duration: String,
7 |   order: Number,
8 | });
10 | const quizSchema = new mongoose.Schema({
11 |   question: String,
12 |   options: [String],
13 |   correctAnswer: Number,
14 |   points: { type: Number, default: 10 },
15 | });
17 | const assignmentSchema = new mongoose.Schema({
18 |   title: String,
19 |   description: String,
20 |   dueDate: Date,
21 |   maxScore: { type: Number, default: 100 },
22 | });
24 | const trainingSchema = new mongoose.Schema(
25 |   {
26 |     title: { type: String, required: true, trim: true },
27 |     description: { type: String, required: true },
28 |     category: {
29 |       type: String,
30 |       enum: ["Web Development", "Data Science", "DSA", "Cloud", "AI/ML", "Soft Skills", "Other"],
31 |       default: "Other",
32 |     },
33 |     thumbnail: { type: String, default: "" },
34 |     level: { type: String, enum: ["Beginner", "Intermediate", "Advanced"], default: "Beginner" },
35 |     duration: { type: String, default: "" },
36 |     videos: [videoSchema],
37 |     quizzes: [quizSchema],
38 |     assignments: [assignmentSchema],
39 |     enrolledStudents: [
40 |       {
41 |         studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student" },
42 |         enrolledAt: { type: Date, default: Date.now },
43 |         completedVideos: [Number],
44 |         quizScore: { type: Number, default: 0 },
45 |         isCompleted: { type: Boolean, default: false },
46 |         completedAt: Date,
47 |       },
48 |     ],
49 |     certificateTemplate: { type: String, default: "default" },
50 |     isPublished: { type: Boolean, default: true },
51 |     instructor: { type: String, default: "" },
52 |     tags: [String],
53 |   },
54 |   { timestamps: true }
55 | );
57 | module.exports = mongoose.model("Training", trainingSchema);
58 |
1 | const mongoose = require("mongoose");
3 | const userSchema = new mongoose.Schema(
4 |   {
5 |     name: {
6 |       type: String,
7 |       required: true,
8 |     },
10 |     email: {
11 |       type: String,
12 |       required: true,
13 |       unique: true,
14 |     },
16 |     password: {
17 |       type: String,
18 |       required: true,
19 |     },
20 |   },
21 |   {
```

KATALYST

Source Code: backend/models/user.js (Cont.)

Generated: 22/8/2026 | Backend

```
22 |     timestamps: true,
23 |   }
24 | });
25 | module.exports = mongoose.model("User", UserSchema);
26 |
27 |
28 |
29 |
30 |
31 |
32 |
33 |
34 |
35 |
36 |
37 |
38 |
39 |
40 | }
41 |
42 |
43 |
44 |
45 |
46 |
47 |
48 |
49 |
50 |
51 |
52 |
53 |
54 |
55 |
56 |
57 |
58 |
59 |
60 |
61 |
62 |
63 |
64 |
65 |
66 |
67 |
68 |
69 |
70 |
71 |
72 |
73 |
74 |
75 |
76 |
77 |
78 |
79 |
80 |
81 |
82 |
83 |
84 |
85 |
86 |
87 |
88 |
89 |
90 |
91 |
92 |
93 |
94 |
95 |
96 |
97 |
98 |
99 |
100 |
101 |
102 |
103 |
104 |
105 |
106 |
107 |
108 |
109 |
110 |
111 |
112 |
113 |
114 |
115 |
116 |
117 |
118 |
119 |
120 |
121 |
122 |
123 |
124 |
125 |
126 |
127 |
128 |
129 |
130 |
131 |
132 |
133 |
134 |
135 |
136 |
137 |
138 |
139 |
140 |
141 |
142 |
143 |
144 |
145 |
146 |
147 |
148 |
149 |
150 |
151 |
152 |
153 |
154 |
155 |
156 |
157 |
158 |
159 |
160 |
161 |
162 |
163 |
164 |
165 |
166 |
167 |
168 |
169 |
170 |
171 |
172 |
173 |
174 |
175 |
176 |
177 |
178 |
179 |
180 |
181 |
182 |
183 |
184 |
185 |
186 |
187 |
188 |
189 |
190 |
191 |
192 |
193 |
194 |
195 |
196 |
197 |
198 |
199 |
200 |
201 |
202 |
203 |
204 |
205 |
206 |
207 |
208 |
209 |
210 |
211 |
212 |
213 |
214 |
215 |
216 |
217 |
218 |
219 |
220 |
221 |
222 |
223 |
224 |
225 |
226 |
227 |
228 |
229 |
230 |
231 |
232 |
233 |
234 |
235 |
236 |
237 |
238 |
239 |
240 |
241 |
242 |
243 |
244 |
245 |
246 |
247 |
248 |
249 |
250 |
251 |
252 |
253 |
254 |
255 |
256 |
257 |
258 |
259 |
260 |
261 |
262 |
263 |
264 |
265 |
266 |
267 |
268 |
269 |
270 |
271 |
272 |
273 |
274 |
275 |
276 |
277 |
278 |
279 |
280 |
281 |
282 |
283 |
284 |
285 |
286 |
287 |
288 |
289 |
290 |
291 |
292 |
293 |
294 |
295 |
296 |
297 |
298 |
299 |
300 |
301 |
302 |
303 |
304 |
305 |
306 |
307 |
308 |
309 |
310 |
311 |
312 |
313 |
314 |
315 |
316 |
317 |
318 |
319 |
320 |
321 |
322 |
323 |
324 |
325 |
326 |
327 |
328 |
329 |
330 |
331 |
332 |
333 |
334 |
335 |
336 |
337 |
338 |
339 |
340 |
341 |
342 |
343 |
344 |
345 |
346 |
347 |
348 |
349 |
350 |
351 |
352 |
353 |
354 |
355 |
356 |
357 |
358 |
359 |
360 |
361 |
362 |
363 |
364 |
365 |
366 |
367 |
368 |
369 |
370 |
371 |
372 |
373 |
374 |
375 |
376 |
377 |
378 |
379 |
380 |
381 |
382 |
383 |
384 |
385 |
386 |
387 |
388 |
389 |
390 |
391 |
392 |
393 |
394 |
395 |
396 |
397 |
398 |
399 |
400 |
401 |
402 |
403 |
404 |
405 |
406 |
407 |
408 |
409 |
410 |
411 |
412 |
413 |
414 |
415 |
416 |
417 |
418 |
419 |
420 |
421 |
422 |
423 |
424 |
425 |
426 |
427 |
428 |
429 |
430 |
431 |
432 |
433 |
434 |
435 |
436 |
437 |
438 |
439 |
440 |
441 |
442 |
443 |
444 |
445 |
446 |
447 |
448 |
449 |
450 |
451 |
452 |
453 |
454 |
455 |
456 |
457 |
458 |
459 |
460 |
461 |
462 |
463 |
464 |
465 |
466 |
467 |
468 |
469 |
470 |
471 |
472 |
473 |
474 |
475 |
476 |
477 |
478 |
479 |
480 |
481 |
482 |
483 |
484 |
485 |
486 |
487 |
488 |
489 |
490 |
491 |
492 |
493 |
494 |
495 |
496 |
497 |
498 |
499 |
500 |
501 |
502 |
503 |
504 |
505 |
506 |
507 |
508 |
509 |
510 |
511 |
512 |
513 |
514 |
515 |
516 |
517 |
518 |
519 |
520 |
521 |
522 |
523 |
524 |
525 |
526 |
527 |
528 |
529 |
530 |
531 |
532 |
533 |
534 |
535 |
536 |
537 |
538 |
539 |
540 |
541 |
542 |
543 |
544 |
545 |
546 |
547 |
548 |
549 |
550 |
551 |
552 |
553 |
554 |
555 |
556 |
557 |
558 |
559 |
560 |
561 |
562 |
563 |
564 |
565 |
566 |
567 |
568 |
569 |
570 |
571 |
572 |
573 |
574 |
575 |
576 |
577 |
578 |
579 |
580 |
581 |
582 |
583 |
584 |
585 |
586 |
587 |
588 |
589 |
590 |
591 |
592 |
593 |
594 |
595 |
596 |
597 |
598 |
599 |
600 |
601 |
602 |
603 |
604 |
605 |
606 |
607 |
608 |
609 |
610 |
611 |
612 |
613 |
614 |
615 |
616 |
617 |
618 |
619 |
620 |
621 |
622 |
623 |
624 |
625 |
626 |
627 |
628 |
629 |
630 |
631 |
632 |
633 |
634 |
635 |
636 |
637 |
638 |
639 |
640 |
641 |
642 |
643 |
644 |
645 |
646 |
647 |
648 |
649 |
650 |
651 |
652 |
653 |
654 |
655 |
656 |
657 |
658 |
659 |
660 |
661 |
662 |
663 |
664 |
665 |
666 |
667 |
668 |
669 |
670 |
671 |
672 |
673 |
674 |
675 |
676 |
677 |
678 |
679 |
680 |
681 |
682 |
683 |
684 |
685 |
686 |
687 |
688 |
689 |
690 |
691 |
692 |
693 |
694 |
695 |
696 |
697 |
698 |
699 |
700 |
701 |
702 |
703 |
704 |
705 |
706 |
707 |
708 |
709 |
710 |
711 |
712 |
713 |
714 |
715 |
716 |
717 |
718 |
719 |
720 |
721 |
722 |
723 |
724 |
725 |
726 |
727 |
728 |
729 |
730 |
731 |
732 |
733 |
734 |
735 |
736 |
737 |
738 |
739 |
740 |
741 |
742 |
743 |
744 |
745 |
746 |
747 |
748 |
749 |
750 |
751 |
752 |
753 |
754 |
755 |
756 |
757 |
758 |
759 |
760 |
761 |
762 |
763 |
764 |
765 |
766 |
767 |
768 |
769 |
770 |
771 |
772 |
773 |
774 |
775 |
776 |
777 |
778 |
779 |
780 |
781 |
782 |
783 |
784 |
785 |
786 |
787 |
788 |
789 |
790 |
791 |
792 |
793 |
794 |
795 |
796 |
797 |
798 |
799 |
800 |
801 |
802 |
803 |
804 |
805 |
806 |
807 |
808 |
809 |
810 |
811 |
812 |
813 |
814 |
815 |
816 |
817 |
818 |
819 |
820 |
821 |
822 |
823 |
824 |
825 |
826 |
827 |
828 |
829 |
830 |
831 |
832 |
833 |
834 |
835 |
836 |
837 |
838 |
839 |
840 |
841 |
842 |
843 |
844 |
845 |
846 |
847 |
848 |
849 |
850 |
851 |
852 |
853 |
854 |
855 |
856 |
857 |
858 |
859 |
860 |
861 |
862 |
863 |
864 |
865 |
866 |
867 |
868 |
869 |
870 |
871 |
872 |
873 |
874 |
875 |
876 |
877 |
878 |
879 |
880 |
881 |
882 |
883 |
884 |
885 |
886 |
887 |
888 |
889 |
890 |
891 |
892 |
893 |
894 |
895 |
896 |
897 |
898 |
899 |
900 |
901 |
902 |
903 |
904 |
905 |
906 |
907 |
908 |
909 |
910 |
911 |
912 |
913 |
914 |
915 |
916 |
917 |
918 |
919 |
920 |
921 |
922 |
923 |
924 |
925 |
926 |
927 |
928 |
929 |
930 |
931 |
932 |
933 |
934 |
935 |
936 |
937 |
938 |
939 |
940 |
941 |
942 |
943 |
944 |
945 |
946 |
947 |
948 |
949 |
950 |
951 |
952 |
953 |
954 |
955 |
956 |
957 |
958 |
959 |
960 |
961 |
962 |
963 |
964 |
965 |
966 |
967 |
968 |
969 |
970 |
971 |
972 |
973 |
974 |
975 |
976 |
977 |
978 |
979 |
980 |
981 |
982 |
983 |
984 |
985 |
986 |
987 |
988 |
989 |
990 |
991 |
992 |
993 |
994 |
995 |
996 |
997 |
998 |
999 |
1000 |
```

```
29 | router.post("/notify", sendBulkNotification);
30 | module.exports = router; (0.6 KB)
31 |
32 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   analyzeResume,
7 |   careerRoadmap,
8 |   scholarshipRecommendations,
9 |   assistantChat,
10 | } = require("../controllers/aiController");
11 | router.use(protect);
12 | router.post("/chatbot", assistantChat);
13 | router.use(allowRoles("student"));
14 | router.post("/resume-analyze", analyzeResume);
15 | router.post("/career-roadmap", careerRoadmap);
16 | router.post("/scholarships", scholarshipRecommendations);
17 | module.exports = router; (0.4 KB)
18 |
19 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { registerStudent, login, getMe, resetPassword } = require("../controllers/authController");
4 | const { protect } = require("../middleware/auth");
5 |
6 | router.post("/register", registerStudent);
7 | router.post("/login", login);
8 | router.post("/reset-password", resetPassword);
9 | router.get("/me", protect, getMe);
10 | module.exports = router; (0.9 KB)
11 |
12 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   bookMeeting,
7 |   getStudentMeetings,
8 |   getMentorMeetings,
9 |   getAllMeetingsAdmin,
10 |   updateMeetingStatus,
11 |   submitStudentFeedback,
12 |   cancelMeeting,
13 | } = require("../controllers/meetingController");
14 | router.use(protect);
15 | router.post("/", allowRoles("student"), bookMeeting);
16 | router.get("/student", allowRoles("student"), getStudentMeetings);
17 | router.get("/mentor", allowRoles("mentor"), getMentorMeetings);
18 | router.get("/admin", allowRoles("admin"), getAllMeetingsAdmin);
19 | router.put("/:id/status", allowRoles("mentor", "admin"), updateMeetingStatus);
20 | router.post("/:id/feedback", allowRoles("student"), submitStudentFeedback);
21 | router.delete("/:id", allowRoles("student", "admin"), cancelMeeting);
22 | module.exports = router; (0.6 KB)
23 |
24 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getDashboard,
7 |   getStudents,
8 |   respondToMeeting,
9 |   addMeetingNotes,
10 |   giveFeedback,
11 |   getMeetings,
12 | } = require("../controllers/mentorController");
13 | router.use(protect, allowRoles("mentor"));
14 | router.get("/dashboard", getDashboard);
15 | router.get("/students", getStudents);
16 | router.get("/meetings", getMeetings);
17 | router.put("/meeting/:id", respondToMeeting);
```



```
20 | router.post("/meeting/:id/notes", addMeetingNotes);
21 | router.post("/feedback", giveFeedback);
22 | module.exports = router; (0.4 KB)
24 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const {
5 |   getNotifications,
6 |   markAsRead,
7 |   markAllAsRead,
8 |   deleteNotification,
9 | } = require("../controllers/notificationController");
11 | router.use(protect);
13 | router.get("/", getNotifications);
14 | router.put("/read-all", markAllAsRead);
15 | router.put("/:id/read", markAsRead);
16 | router.delete("/:id", deleteNotification);
17 | module.exports = router; (0.6 KB)
19 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getStudentProgress,
7 |   getPlacementReadiness,
8 |   getAdminProgressReport,
9 | } = require("../controllers/progressController");
11 | router.use(protect);
13 | router.get("/", allowRoles("student"), getStudentProgress);
14 | router.get("/placement", allowRoles("student"), getPlacementReadiness);
15 | router.get("/admin", allowRoles("admin"), getAdminProgressReport);
17 | module.exports = router; (1.3 KB)
18 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const multer = require("multer");
4 | const path = require("path");
5 | const { protect } = require("../middleware/auth");
6 | const { allowRoles } = require("../middleware/roleCheck");
7 | const {
8 |   getDashboard,
9 |   getProfile,
10 |   updateProfile,
11 |   uploadResume,
12 |   getCertificates,
13 |   getProgress,
14 |   getMeetings,
15 | } = require("../controllers/studentController");
17 | // Multer setup for resume upload
18 | const storage = multer.diskStorage({
19 |   destination: (req, file, cb) => cb(null, "uploads/resumes/"),
20 |   filename: (req, file, cb) =>
21 |     cb(null, `${req.user.id}-${Date.now()}${path.extname(file.originalname)}`),
22 | });
23 | const upload = multer({
24 |   storage,
25 |   limits: { fileSize: 5 * 1024 * 1024 }, // 5MB
26 |   fileFilter: (req, file, cb) => {
27 |     const allowed = [".pdf", ".doc", ".docx"];
28 |     if (!allowed.includes(path.extname(file.originalname).toLowerCase()))
29 |       return cb(new Error("Only PDF/DOC files allowed"));
30 |     cb(null, true);
31 |   },
32 | });
34 | router.use(protect, allowRoles("student"));
36 | router.get("/dashboard", getDashboard);
37 | router.get("/profile", getProfile);
38 | router.put("/profile", updateProfile);
39 | router.post("/resume", upload.single("resume"), uploadResume);
```

KATALYST.

Source Code: backend/routes/student.js (Cont.)

Generated: 22/8/2026 | Backend

```
40 | router.get("/certificates", getCertificates);
41 | router.get("/progress", getProgress);
42 | router.get("/meetings", getMeetings);
43 | module.exports = router; (0.9 KB)
45 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getAllTrainings,
7 |   getTrainingById,
8 |   enrollTraining,
9 |   completeVideo,
10 | submitQuiz,
11 | createTraining,
12 | updateTraining,
13 | deleteTraining,
14 | } = require("../controllers/trainingController");
16 | // Public
17 | router.get("/", getAllTrainings);
18 | router.get("/:id", protect, getTrainingById);
20 | // Student
21 | router.post("/:id/enroll", protect, allowRoles("student"), enrollTraining);
22 | router.post("/:id/complete-video", protect, allowRoles("student"), completeVideo);
23 | router.post("/:id/submit-quiz", protect, allowRoles("student"), submitQuiz);
25 | // Admin
26 | router.post("/", protect, allowRoles("admin"), createTraining);
27 | router.put("/:id", protect, allowRoles("admin"), updateTraining);
28 | router.delete("/:id", protect, allowRoles("admin"), deleteTraining);
29 | module.exports = router; (3.9 KB)
31 |
1 | const mongoose = require("mongoose");
2 | const dotenv = require("dotenv");
3 | const bcrypt = require("bcryptjs");
4 | const connectDB = require("../config/db");
5 | const Student = require("../models/Student");
6 | const Mentor = require("../models/Mentor");
7 | const Admin = require("../models/Admin");
8 | const Training = require("../models/Training");
9 | const Progress = require("../models/Progress");
10 | const Notification = require("../models/Notification");
11 | const Certificate = require("../models/Certificate");
13 | dotenv.config();
15 | const seed = async () => {
16 |   try {
17 |     await connectDB();
18 |     await Promise.all([
19 |       Student.deleteMany(),
20 |       Mentor.deleteMany(),
21 |       Admin.deleteMany(),
22 |       Training.deleteMany(),
23 |       Progress.deleteMany(),
24 |       Notification.deleteMany(),
25 |       Certificate.deleteMany(),
26 |     ]);
28 |     const admin = await Admin.create({
29 |       name: "System Admin",
30 |       email: "admin@katalyst.io",
31 |       password: "Admin@123",
32 |     });
34 |     const mentor1 = await Mentor.create({
35 |       name: "Dr. Sarah Jenkins",
36 |       email: "sarah@katalyst.io",
37 |       password: "Mentor@123",
38 |       expertise: ["Web Development", "React", "Career Coaching"],
39 |       designation: "Senior Mentor",
40 |       company: "Katalyst Labs",
41 |       bio: "Guiding students to build scalable web apps and strong career roadmaps.",
42 |     });
44 |     const student1 = await Student.create({
```

```
45 |     name: "Diksha Sharma",
46 |     email: "diksha@katalyst.io",
47 |     password: "Student@123",
48 |     phone: "1234567890",
49 |     bio: "Full Stack student learning modern web development.",
50 |     skills: ["HTML", "CSS", "JavaScript"],
51 |     assignedMentor: mentor1._id,
52 |   });
53 |
54 |   const training1 = await Training.create({
55 |     title: "Web Development Masterclass",
56 |     description: "Learn HTML, CSS, JavaScript and React in a project-based path.",
57 |     category: "Web Development",
58 |     level: "Beginner",
59 |     duration: "6 weeks",
60 |     thumbnail: "https://i.imgur.com/Ua7I9qH.png",
61 |     instructor: "Katalyst Mentors",
62 |     tags: ["web", "frontend", "react"],
63 |     videos: [
64 |       { title: "HTML Basics", url: "https://youtu.be/example", duration: "12m", order: 1 },
65 |       { title: "CSS Essentials", url: "https://youtu.be/example", duration: "20m", order: 2 },
66 |       { title: "JavaScript Fundamentals", url: "https://youtu.be/example", duration: "25m", order: 3 },
67 |       { title: "React UI Components", url: "https://youtu.be/example", duration: "30m", order: 4 },
68 |     ],
69 |     quizzes: [
70 |       { question: "What does HTML stand for?", options: ["Hypertext Markup Language", "Hyperlinks and Text M
71 |     ],
72 |     assignments: [
73 |       { title: "Build Portfolio Homepage", description: "Create a responsive portfolio landing page.", dueDa
74 |     ],
75 |     enrolledStudents: [{ studentId: student1._id },
76 |   });
77 |
78 |   await Progress.create({
79 |     studentId: student1._id,
80 |     trainingCompletion: 25,
81 |     meetingsAttended: 1,
82 |     totalMeetingsScheduled: 2,
83 |     quizScores: [{ trainingId: training1._id, score: 8, maxScore: 10 }],
84 |     assignmentsSubmitted: 1,
85 |     attendanceRate: 80,
86 |     overallScore: 66,
87 |     placementReadiness: 60,
88 |     hasResume: false,
89 |   });
90 |
91 |   await Notification.create({
92 |     userId: student1._id,
93 |     userRole: "student",
94 |     title: "Welcome to Katalyst!",
95 |     message: "Your student dashboard is ready. Start your first training now.",
96 |     type: "system",
97 |   });
98 |
99 |   await Certificate.create({
100 |     studentId: student1._id,
101 |     trainingId: training1._id,
102 |     studentName: student1.name,
103 |     trainingTitle: training1.title,
104 |   });
105 |
106 |   console.log("Seed data created successfully");
107 |   process.exit();
108 | } catch (error) {
109 |   console.error("Seed error:", error.message);
110 |   process.exit(1);
111 | }
112 | };
113 |
114 | seed();
115 |
```

KATALYST

Source Code: backend/server.js

Generated: 22/8/2026 | Backend

(2.7 KB)

```
1 | const express = require("express");
2 | const cors = require("cors");
3 | const helmet = require("helmet");
4 | const rateLimit = require("express-rate-limit");
5 | const path = require("path");
6 | require("dotenv").config();
7 |
8 | const connectDB = require("../config/db");
9 |
10 | // Routes
11 | const authRoutes = require("../routes/auth");
12 | const studentRoutes = require("../routes/student");
13 | const mentorRoutes = require("../routes/mentor");
14 | const adminRoutes = require("../routes/admin");
15 | const trainingRoutes = require("../routes/training");
16 | const meetingRoutes = require("../routes/meeting");
17 | const notificationRoutes = require("../routes/notification");
18 | const progressRoutes = require("../routes/progress");
19 | const aiRoutes = require("../routes/ai");
20 |
21 | const app = express();
22 |
23 | // Connect to MongoDB
24 | connectDB();
25 |
26 | // Security middleware
27 | app.use(helmet());
28 | app.use(
29 |   cors({
30 |     origin: [
31 |       "http://localhost:5173",
32 |     ],
33 |     credentials: true,
34 |   })
35 | );
36 |
37 | // Rate limiting
38 | const limiter = rateLimit({
39 |   windowMs: 15 * 60 * 1000, // 15 min
40 |   max: 100,
41 |   message: { message: "Too many requests, please try again later." },
42 | });
43 | app.use("/api/", limiter);
44 |
45 | // Auth rate limit (stricter)
46 | const authLimiter = rateLimit({
47 |   windowMs: 15 * 60 * 1000,
48 |   max: 20,
49 |   message: { message: "Too many login attempts, please try again later." },
50 | });
51 | app.use("/api/auth/", authLimiter);
52 |
53 | // Body parsing
54 | app.use(express.json({ limit: "10mb" }));
55 | app.use(express.urlencoded({ extended: true, limit: "10mb" }));
56 |
57 | // Static files (uploaded resumes)
58 | app.use("/uploads", express.static(path.join(__dirname, "uploads")));
59 |
60 | // Health check
61 | app.get("/", (req, res) => {
62 |   res.json({
63 |     message: "ðŸš€ Katalyst API is running!",
64 |     version: "1.0.0",
65 |     timestamp: new Date().toISOString(),
66 |   });
67 | });
68 |
69 | // API Routes
70 | app.use("/api/auth", authRoutes);
71 | app.use("/api/students", studentRoutes);
72 | app.use("/api/mentors", mentorRoutes);
73 | app.use("/api/admin", adminRoutes);
74 | app.use("/api/trainings", trainingRoutes);
75 | app.use("/api/meetings", meetingRoutes);
76 | app.use("/api/notifications", notificationRoutes);
77 | app.use("/api/progress", progressRoutes);
78 | app.use("/api/ai", aiRoutes);
79 |
80 | // 404 handler
81 | app.use((req, res) => {
```

KATALYST

Source Code: backend/server.js (Cont.)

Generated: 22/8/2026 | Backend

```
83 |   res.status(404).json({ message: "Route not found" });
84 | });
85 | // Global error handler
86 | app.use((err, req, res, next) => {
87 |   console.error("ðŸ’¥ Error:", err.stack);
88 |   res.status(err.status || 500).json({
89 |     message: err.message || "Internal Server Error",
90 |     ...(process.env.NODE_ENV === "development" && { stack: err.stack }),
91 |   });
92 | });
93 | });
94 | const PORT = process.env.PORT || 5000;
95 | app.listen(PORT, () => {
96 |   console.log(`ðŸš€ Katalyst server running on port ${PORT}`);
97 |   console.log(`ðŸš€ Environment: ${process.env.NODE_ENV || "development"}`);
98 | });
99 | });
```

100 | module.exports = app; (0.2 KB)

```
1 | const jwt = require("jsonwebtoken");
2 | const generateToken = (id, role) => {
3 |   return jwt.sign({ id, role }, process.env.JWT_SECRET, {
4 |     expiresIn: process.env.JWT_EXPIRES_IN || "7d",
5 |   });
6 | };
7 | 
```

8 | module.exports = generateToken; (1.5 KB)

```
10 | /**
11 |  * Calculate overall progress score (weighted composite)
12 |  * Weights: Training 40%, Meetings 30%, Quiz 20%, Attendance 10%
13 |  */
14 | const calculateOverallProgress = ({
15 |   trainingCompletion = 0,
16 |   meetingsAttended = 0,
17 |   totalMeetingsScheduled = 0,
18 |   quizScores = [],
19 |   attendanceRate = 0,
20 | }) => {
21 |   const meetingRate =
22 |     totalMeetingsScheduled > 0
23 |       ? (meetingsAttended / totalMeetingsScheduled) * 100
24 |       : 0;
25 |   const avgQuizScore =
26 |     quizScores.length > 0
27 |       ? quizScores.reduce((sum, q) => sum + (q.score / q.maxScore) * 100, 0) /
28 |         quizScores.length
29 |       : 0;
30 |   const overall =
31 |     trainingCompletion * 0.4 +
32 |     meetingRate * 0.3 +
33 |     avgQuizScore * 0.2 +
34 |     attendanceRate * 0.1;
35 |   return Math.round(Math.min(overall, 100));
36 | };
37 | /**
38 |  * Calculate placement readiness score
39 |  */
40 | const calculatePlacementReadiness = ({
41 |   overallScore = 0,
42 |   quizScores = [],
43 |   assignmentsSubmitted = 0,
44 |   meetingsAttended = 0,
45 |   hasResume = false,
46 | }) => {
47 |   const quizAvg =
48 |     quizScores.length > 0
49 |       ? quizScores.reduce((s, q) => s + (q.score / q.maxScore) * 100, 0) /
50 |         quizScores.length
51 |       : 0;
52 |   const resumeBonus = hasResume ? 10 : 0;
53 |   const meetingBonus = Math.min(meetingsAttended * 5, 20);
54 |   const assignmentBonus = Math.min(assignmentsSubmitted * 5, 15);
55 |   const score =
```

```
53 |     overallScore * 0.4 + quizAvg * 0.3 + resumeBonus + meetingBonus + assignmentBonus;
55 |     return Math.round(Math.min(score, 100));
56 | };
58 | module.exports = { calculateOverallProgress, calculatePlacementReadiness };
59 |
1 | const Progress = require("../models/Progress");
2 | const Training = require("../models/Training");
3 | const { calculateOverallProgress, calculatePlacementReadiness } = require("./progressCalculator");
5 | const syncStudentProgress = async (studentId) => {
6 |     const progress =
7 |         (await Progress.findOne({ studentId })) ||
8 |         new Progress({ studentId, trainingCompletion: 0, meetingsAttended: 0, totalMeetingsScheduled: 0, attendanc
10 |     const trainings = await Training.find({ "enrolledStudents.studentId": studentId });
11 |     const completedCount = trainings.filter((training) => {
12 |         const enrollment = training.enrolledStudents.find(
13 |             (item) => item.studentId.toString() === studentId.toString()
14 |         );
15 |         return enrollment?.isCompleted;
16 |     }).length;
18 |     progress.trainingCompletion = trainings.length
19 |         ? Math.round((completedCount / trainings.length) * 100)
20 |         : 0;
22 |     // Calculate attendanceRate based on meetings
23 |     const meetingRate = progress.totalMeetingsScheduled > 0
24 |         ? Math.round((progress.meetingsAttended / progress.totalMeetingsScheduled) * 100)
25 |         : 100; // default to 100 if no meetings are scheduled yet
26 |     progress.attendanceRate = Math.min(meetingRate, 100);
28 |     progress.overallScore = calculateOverallProgress(progress.toObject());
29 |     progress.placementReadiness = calculatePlacementReadiness({
30 |         overallScore: progress.overallScore,
31 |         quizScores: progress.quizScores,
32 |         assignmentsSubmitted: progress.assignmentsSubmitted,
33 |         meetingsAttended: progress.meetingsAttended,
34 |         hasResume: progress.hasResume,
35 |     });
36 |     progress.lastUpdated = new Date();
38 |     return progress.save();
39 | };
41 | module.exports = { syncStudentProgress };
42 |
1 | const nodemailer = require("nodemailer");
3 | const transporter = nodemailer.createTransport({
4 |     service: "gmail",
5 |     auth: {
6 |         user: process.env.EMAIL_USER,
7 |         pass: process.env.EMAIL_PASS, // App password
8 |     },
9 | });
11 | const sendEmail = async ({ to, subject, html }) => {
12 |     try {
13 |         const info = await transporter.sendMail({
14 |             from: `Katalyst Platform <${process.env.EMAIL_USER}>`,
15 |             to,
16 |             subject,
17 |             html,
18 |         });
19 |         console.log(`Email sent:`, info.messageId);
20 |         return { success: true };
21 |     } catch (error) {
22 |         console.error("Email failed:", error.message);
23 |         return { success: false, error: error.message };
24 |     }
25 | };
27 | // Email templates
28 | const meetingAcceptedEmail = (studentName, mentorName, date, time, meetLink) => `
29 | <div style="font-family: Arial, sans-serif; max-width: 600px; margin: 0 auto;">
30 |   <div style="background: linear-gradient(135deg, #1e3a8a, #3b82f6); padding: 30px; border-radius: 12px 12px
31 |     <h1 style="color: white; margin: 0;">Katalyst</h1>
32 |   </div>
33 |   <div style="background: #f8fafc; padding: 30px; border-radius: 0 0 12px 12px;">
34 |     <h2>Meeting Confirmed! <B%</h2>
```

```
35 |         <p>Hi <strong>${studentName}</strong>, </p>
36 |         <p>Your meeting with <strong>${mentorName}</strong> has been accepted.</p>
37 |         <div style="background: white; padding: 20px; border-radius: 8px; border-left: 4px solid #3b82f6;">
38 |             <p><strong>🕒 Date:</strong> ${date}</p>
39 |             <p><strong>🕒 Time:</strong> ${time}</p>
40 |             <p><strong>🔗 Meet Link:</strong> <a href="${meetLink}">${meetLink}</a></p>
41 |         </div>
42 |         <p style="color: #6b7280; font-size: 14px;">Best of luck with your mentorship session!</p>
43 |     </div>
44 | </div>
45 | `;
46 |
47 | const meetingRejectedEmail = (studentName, mentorName, reason) => `
48 |     <div style="font-family: Arial, sans-serif; max-width: 600px; margin: 0 auto;">
49 |         <div style="background: linear-gradient(135deg, #1e3a8a, #3b82f6); padding: 30px; border-radius: 12px 12px
50 |             <h1 style="color: white; margin: 0;">Katalyst</h1>
51 |         </div>
52 |         <div style="background: #f8fafc; padding: 30px; border-radius: 0 0 12px 12px;">
53 |             <h2>Meeting Update</h2>
54 |             <p>Hi <strong>${studentName}</strong>, </p>
55 |             <p>Your meeting request with <strong>${mentorName}</strong> was not accepted at this time.</p>
56 |             ${reason ? `<p><strong>Reason:</strong> ${reason}</p>` : ""}
57 |             <p>Please book another slot or contact the admin for assistance.</p>
58 |         </div>
59 |     </div>
60 | `;
61 |
62 | module.exports = { sendEmail, meetingAcceptedEmail, meetingRejectedEmail };
63 |
64 | {
65 |   version: "3.9"
66 | }
67 |
68 | {
69 |   services:
70 |     backend:
71 |       build:
72 |         context: ./backend
73 |         dockerfile: Dockerfile
74 |         env_file:
75 |           - ./backend/.env.example
76 |         ports:
77 |           - "5000:5000"
78 |         volumes:
79 |           - ./backend/uploads:/usr/src/app/uploads
80 |         depends_on:
81 |           - mongo
82 |       frontend:
83 |         build:
84 |           context: ./frontend
85 |           dockerfile: Dockerfile
86 |           env_file:
87 |             - ./frontend/.env.example
88 |           ports:
89 |             - "4173:4173"
90 |           depends_on:
91 |             - backend
92 |       mongo:
93 |         image: mongo:7.0
94 |         restart: unless-stopped
95 |         ports:
96 |           - "27017:27017"
97 |         volumes:
98 |           - mongo-data:/data/db
99 |       volumes:
100 |         mongo-data:
```

(0.0 KB)

1 | VITE_API_URL=http://localhost:5000/api (0.1 KB)

1 | {
2 | "appId": "com.katalyst.student",
3 | "appName": "Katalyst 2.0",
4 | "webDir": "dist"
5 | } (0.2 KB)

6 |
1 | FROM node:20-alpine
3 | WORKDIR /usr/src/app
5 | COPY package*.json ./
6 | RUN npm install
8 | COPY . .
10 | RUN npm run build
12 | EXPOSE 4173
14 | CMD ["npm", "run", "preview", "--", "0.0.0.0", "0.0.0.0"] (0.3 KB)

15 |
1 | import js from '@eslint/js'
2 | import globals from 'globals'
3 | import reactHooks from 'eslint-plugin-react-hooks'
4 | import reactRefresh from 'eslint-plugin-react-refresh'
5 | import { defineConfig, globalIgnores } from 'eslint/config'
7 | export default defineConfig([
8 | globalIgnores(['dist']),
9 | {
10 | files: ['**/*.js,jsx'],
11 | extends: [
12 | js.configs.recommended,
13 | reactHooks.configs.flat.recommended,
14 | reactRefresh.configs.vite,
15 |],
16 | languageOptions: {
17 | globals: globals.browser,
18 | parserOptions: { ecmaFeatures: { jsx: true } },
19 | },
20 | },
21 |])
22 | (0.4 KB)

1 | <!doctype html>
2 | <html lang="en">
3 | <head>
4 | <meta charset="UTF-8" />
5 | <link rel="icon" type="image/svg+xml" href="/favicon.svg" />
6 | <meta name="viewport" content="width=device-width, initial-scale=1.0" />
7 | <title>frontend</title>
8 | </head>
9 | <body>
10 | <div id="root"></div>
11 | <script type="module" src="/src/main.jsx"></script>
12 | </body>
13 | </html> (0.5 KB)

14 |
1 | {
2 | "name": "katalyst-frontend",
3 | "private": true,
4 | "version": "2.0.0",
5 | "type": "module",
6 | "scripts": {
7 | "dev": "vite",
8 | "build": "vite build",
9 | "preview": "vite preview"
10 | },
11 | "dependencies": {
12 | "@vitejs/plugin-react": "^5.0.0",
13 | "axios": "^1.19.0",
14 | "lucide-react": "^1.31.0",
15 | "react": "^19.0.0",
16 | "react-dom": "^19.0.0",
17 | "react-router-dom": "^7.18.2",
18 | "recharts": "^2.15.4",
19 | "vite": "^8.2.0"
20 | },
21 | }


```
21 |   "devDependencies": {
22 |     "autoprefixer": "^10.4.21",
23 |     "postcss": "^8.5.3",
24 |     "tailwindcss": "3.4.17"
25 |   }
26 | } // frontend/public/css/normalize (0.1 KB)
27 |
1 | export default {
2 |   plugins: {
3 |     tailwindcss: {},
4 |     autoprefixer: {},
5 |   },
6 | }, // frontend/public/Login.css (2.2 KB)
7 |
1 | .login-page {
2 |   min-height: 100vh;
3 |   background: #09090b;
4 |   display: flex;
5 |   justify-content: center;
6 |   align-items: center;
7 |   padding: 30px;
8 |   position: relative;
9 | }
10 |
11 | .back-button {
12 |   position: absolute;
13 |   top: 30px;
14 |   left: 5%;
15 |   background: transparent;
16 |   border: none;
17 |   color: #a1a1aa;
18 |   font-size: 15px;
19 |   cursor: pointer;
20 | }
21 |
22 | .back-button:hover {
23 |   color: white;
24 | }
25 |
26 | .login-card {
27 |   width: 100%;
28 |   max-width: 480px;
29 |   padding: 45px;
30 |   background: #111114;
31 |   border: 1px solid #27272a;
32 |   border-radius: 20px;
33 |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
34 | }
35 |
36 | .login-logo {
37 |   font-size: 22px;
38 |   font-weight: 800;
39 |   letter-spacing: 2px;
40 |   margin-bottom: 35px;
41 | }
42 |
43 | .login-logo span {
44 |   color: #8b5cf6;
45 | }
46 |
47 | .login-card h1 {
48 |   font-size: 38px;
49 |   margin-bottom: 10px;
50 | }
51 |
52 | .login-subtitle {
53 |   color: #71717a;
54 |   margin-bottom: 30px;
55 | }
56 |
57 | .role-options {
58 |   display: flex;
59 |   flex-direction: column;
60 |   gap: 12px;
61 | }
62 |
63 | .role-card {
64 |   width: 100%;
65 |   padding: 17px;
66 |   background: #18181b;
```

```
67 | border: 1px solid #27272a;
68 | border-radius: 12px;
69 | color: white;
70 | display: flex;
71 | align-items: center;
72 | gap: 15px;
73 | text-align: left;
74 | cursor: pointer;
75 | }
77 | .role-card:hover {
78 |   border-color: #7c3aed;
79 | }
81 | .role-card.selected {
82 |   border-color: #8b5cf6;
83 |   background: #1c1729;
84 | }
86 | .role-icon {
87 |   width: 42px;
88 |   height: 42px;
89 |   display: flex;
90 |   align-items: center;
91 |   justify-content: center;
92 |   background: #27272a;
93 |   border-radius: 10px;
94 |   font-size: 20px;
95 | }
97 | .role-card h3 {
98 |   margin-bottom: 4px;
99 | }
101 | .role-card p {
102 |   color: #71717a;
103 |   font-size: 12px;
104 | }
106 | .continue-button {
107 |   width: 100%;
108 |   padding: 14px;
109 |   margin-top: 25px;
110 |   border: none;
111 |   border-radius: 8px;
112 |   background: #7c3aed;
113 |   color: white;
114 |   font-size: 15px;
115 |   cursor: pointer;
116 | }
118 | .continue-button:hover {
119 |   background: #8b5cf6;
120 | }
122 | .demo-button {
123 |   width: 100%;
124 |   padding: 13px;
125 |   margin-top: 10px;
126 |   border: 1px solid #3f3f46;
127 |   border-radius: 8px;
128 |   background: transparent;
129 |   color: white;
130 |   cursor: pointer;
131 | }
133 | .login-footer {
134 |   text-align: center;
135 |   color: #52525b;
136 |   font-size: 11px;
137 |   line-height: 1.6;
138 |   margin-top: 30px;
139 | }
140 |
```

(1.0 KB)

```
1 | # React + Vite
3 | This template provides a minimal setup to get React working in Vite with HMR and some ESLint rules.
5 | Currently, two official plugins are available:
7 | - [vitejs/plugin-react](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugin-react) uses [Ox
8 | - [vitejs/plugin-react-swc](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugin-react-swc)
10 | ## React Compiler
12 | The React Compiler is not enabled on this template because of its impact on dev & build performances. To add i
14 | ## Expanding the ESLint configuration
16 | If you are developing a production application, we recommend using TypeScript with type-aware lint rules enabl
17 |
1 | import axios from "axios";
3 | const API = axios.create({
4 |   baseURL: import.meta.env.VITE_API_URL || "http://localhost:5000/api",
5 | });
7 | API.interceptors.request.use((config) => {
8 |   const token = localStorage.getItem("token");
9 |   if (token) config.headers.Authorization = `Bearer ${token}`;
10 |   return config;
11 | });
13 | API.interceptors.response.use(
14 |   (res) => res,
15 |   (err) => {
16 |     if (err.response?.status === 401) {
17 |       localStorage.removeItem("token");
18 |       localStorage.removeItem("user");
19 |       if (!window.location.pathname.includes("/login")) {
20 |         window.location.href = "/login";
21 |       }
22 |     }
23 |     return Promise.reject(err);
24 |   }
25 | );
27 | export default API;
```

(5.6 KB)

```
28 |
1 | * {
2 |   margin: 0;
3 |   padding: 0;
4 |   box-sizing: border-box;
5 | }
7 | html {
8 |   scroll-behavior: smooth;
9 | }
11 | body {
12 |   font-family: Arial, Helvetica, sans-serif;
13 |   background: #09090b;
14 |   color: #ffffff;
15 | }
17 | button {
18 |   font-family: inherit;
19 |   cursor: pointer;
20 | }
22 | .app {
23 |   min-height: 100vh;
24 |   background: transparent;
25 |   position: relative;
26 | }
28 | /* NAVBAR */
30 | .navbar {
31 |   height: 80px;
32 |   padding: 0 7%;
33 |   display: flex;
34 |   align-items: center;
35 |   justify-content: space-between;
36 |   border-bottom: 1px solid #202024;
37 | }
39 | .logo {
40 |   font-size: 22px;
41 |   font-weight: 800;
42 |   letter-spacing: 2px;
```

```
43 | }
45 | .logo span {
46 |   color: #8b5cf6;
47 | }
49 | .nav-links {
50 |   display: flex;
51 |   gap: 35px;
52 | }
54 | .nav-links a {
55 |   color: #a1a1aa;
56 |   text-decoration: none;
57 |   font-size: 14px;
58 | }
60 | .nav-links a:hover {
61 |   color: white;
62 | }
64 | .nav-buttons {
65 |   display: flex;
66 |   gap: 12px;
67 | }
69 | .login-btn,
70 | .signup-btn {
71 |   padding: 10px 18px;
72 |   border-radius: 8px;
73 |   font-size: 14px;
74 | }
76 | .login-btn {
77 |   background: transparent;
78 |   color: white;
79 |   border: 1px solid #333338;
80 | }
82 | .signup-btn {
83 |   background: #7c3aed;
84 |   color: white;
85 |   border: none;
86 | }
88 | /* HERO */
90 | .hero {
91 |   min-height: 700px;
92 |   padding: 90px 7%;
93 |   display: grid;
94 |   grid-template-columns: 1fr 1fr;
95 |   gap: 80px;
96 |   align-items: center;
97 | }
99 | .badge {
100 |   display: inline-block;
101 |   padding: 8px 13px;
102 |   border: 1px solid #302456;
103 |   border-radius: 50px;
104 |   color: #a78bfa;
105 |   font-size: 11px;
106 |   letter-spacing: 1px;
107 |   margin-bottom: 25px;
108 | }
110 | .hero h1 {
111 |   font-size: clamp(60px, 7vw, 100px);
112 |   line-height: 0.9;
113 |   letter-spacing: -5px;
114 |   margin-bottom: 30px;
115 | }
117 | .hero h1 span {
118 |   color: #8b5cf6;
119 | }
121 | .hero-content > p {
122 |   max-width: 520px;
123 |   color: #a1a1aa;
124 |   font-size: 17px;
125 |   line-height: 1.7;
126 | }
```

```
128 | .hero-buttons {
129 |   margin-top: 35px;
130 |   display: flex;
131 |   gap: 15px;
132 | }
133 |
134 | .primary-btn,
135 | .secondary-btn {
136 |   padding: 14px 24px;
137 |   border-radius: 8px;
138 |   font-size: 15px;
139 | }
140 |
141 | .primary-btn {
142 |   border: none;
143 |   background: #7c3aed;
144 |   color: white;
145 | }
146 |
147 | .secondary-btn {
148 |   background: transparent;
149 |   border: 1px solid #3f3f46;
150 |   color: white;
151 | }
152 |
153 | /* DASHBOARD PREVIEW */
154 |
155 | .dashboard-preview {
156 |   padding: 25px;
157 |   border: 1px solid #27272a;
158 |   border-radius: 20px;
159 |   background: #111114;
160 |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
161 | }
162 |
163 | .preview-header {
164 |   display: flex;
165 |   justify-content: space-between;
166 |   align-items: center;
167 |   margin-bottom: 25px;
168 | }
169 |
170 | .preview-header small,
171 | .progress-card small,
172 | .meeting-card small {
173 |   color: #71717a;
174 |   font-size: 10px;
175 |   letter-spacing: 1px;
176 | }
177 |
178 | .preview-header h3 {
179 |   margin-top: 6px;
180 | }
181 |
182 | .profile-circle {
183 |   width: 40px;
184 |   height: 40px;
185 |   border-radius: 50%;
186 |   background: #7c3aed;
187 |   display: flex;
188 |   justify-content: center;
189 |   align-items: center;
190 |   font-weight: bold;
191 | }
192 |
193 | .progress-card {
194 |   padding: 22px;
195 |   border: 1px solid #27272a;
196 |   border-radius: 14px;
197 |   background: #18181b;
198 | }
199 |
200 | .progress-top {
201 |   display: flex;
202 |   justify-content: space-between;
203 |   align-items: center;
204 | }
205 |
206 | .progress-top h2 {
207 |   font-size: 38px;
208 |   margin-top: 5px;
209 | }
```

```
211 | .progress-ring {
212 |   width: 65px;
213 |   height: 65px;
214 |   border: 5px solid #7c3aed;
215 |   border-radius: 50%;
216 |   display: flex;
217 |   align-items: center;
218 |   justify-content: center;
219 |   font-size: 13px;
220 | }
221 |
222 | .progress-bar {
223 |   height: 6px;
224 |   background: #27272a;
225 |   border-radius: 10px;
226 |   margin-top: 20px;
227 |   overflow: hidden;
228 | }
229 |
230 | .progress-fill {
231 |   width: 75%;
232 |   height: 100%;
233 |   background: #8b5cf6;
234 | }
235 |
236 | /* STATS */
237 |
238 | .stats {
239 |   display: grid;
240 |   grid-template-columns: 1fr 1fr;
241 |   gap: 12px;
242 |   margin-top: 12px;
243 | }
244 |
245 | .stat-card {
246 |   padding: 18px;
247 |   border-radius: 14px;
248 |   background: #18181b;
249 |   border: 1px solid #27272a;
250 | }
251 |
252 | .stat-card span {
253 |   display: block;
254 |   font-size: 10px;
255 |   color: #71717a;
256 | }
257 |
258 | .stat-card strong {
259 |   display: block;
260 |   font-size: 25px;
261 |   margin: 8px 0;
262 | }
263 |
264 | .stat-card small {
265 |   color: #a1a1aa;
266 | }
267 |
268 | /* MEETING */
269 |
270 | .meeting-card {
271 |   margin-top: 12px;
272 |   padding: 18px;
273 |   border-radius: 14px;
274 |   background: #18181b;
275 |   border: 1px solid #27272a;
276 |   display: flex;
277 |   justify-content: space-between;
278 |   align-items: center;
279 | }
280 |
281 | .meeting-card h4 {
282 |   margin: 7px 0;
283 | }
284 |
285 | .meeting-card p {
286 |   color: #71717a;
287 |   font-size: 13px;
288 | }
289 |
290 | .meeting-card button {
291 |   border: none;
292 |   background: transparent;
293 |   color: #a78bfa;
```

```
294 | }
295 | /* ABOUT */
296 | .about-section {
297 |   padding: 120px 7%;
298 |   border-top: 1px solid #202024;
299 | }
300 | .section-label {
301 |   color: #8b5cf6;
302 |   font-size: 11px;
303 |   letter-spacing: 2px;
304 |   margin-bottom: 20px;
305 | }
306 | .about-section h2 {
307 |   font-size: 60px;
308 |   line-height: 1;
309 |   letter-spacing: -3px;
310 | }
311 | .about-section h2 span {
312 |   color: #71717a;
313 | }
314 | .section-description {
315 |   max-width: 600px;
316 |   color: #a1a1aa;
317 |   line-height: 1.7;
318 |   margin-top: 25px;
319 | }
320 | /* FEATURES */
321 | .features-section {
322 |   padding: 0 7% 120px;
323 |   display: grid;
324 |   grid-template-columns: repeat(3, 1fr);
325 |   gap: 20px;
326 | }
327 | .feature-card {
328 |   padding: 35px;
329 |   border: 1px solid #27272a;
330 |   border-radius: 16px;
331 |   background: #111114;
332 | }
333 | .feature-number {
334 |   color: #8b5cf6;
335 |   font-size: 13px;
336 |   margin-bottom: 45px;
337 | }
338 | .feature-card h3 {
339 |   margin-bottom: 15px;
340 | }
341 | .feature-card p {
342 |   color: #71717a;
343 |   line-height: 1.6;
344 |   font-size: 14px;
345 | }
346 | /* FOOTER */
347 | footer {
348 |   padding: 50px 7%;
349 |   border-top: 1px solid #202024;
350 | }
351 | footer p {
352 |   color: #71717a;
353 |   margin: 12px 0 25px;
354 | }
355 | footer small {
356 |   color: #52525b;
357 | }
358 | /* RESPONSIVE */
359 | @media (max-width: 900px) {
360 |   .nav-links {
361 |     display: none;
362 |   }
363 | }
```

```
382 | .hero {
383 |   grid-template-columns: 1fr;
384 |   padding-top: 60px;
385 | }
387 | .features-section {
388 |   grid-template-columns: 1fr;
389 | }
390 | }
392 | @media (max-width: 500px) {
393 |   .navbar {
394 |     padding: 0 5%;
395 |   }
397 |   .signup-btn {
398 |     display: none;
399 |   }
401 |   .hero {
402 |     padding: 50px 5%;
403 |   }
405 |   .hero h1 {
406 |     font-size: 65px;
407 |   }
409 |   .about-section {
410 |     padding: 80px 5%;
411 |   }
413 |   .about-section h2 {
414 |     font-size: 45px;
415 |   }
417 |   .features-section {
418 |     padding: 0 5% 80px;
419 |   }
420 | }
421 | }
422 | }
423 | }
424 | }
425 | }
426 | }
427 | }
428 | }
429 | }
430 | }
431 | }
432 | }
433 | }
434 | }
435 | }
436 | }
437 | }
438 | }
439 | }
440 | }
441 | }
442 | }
443 | }
444 | }
445 | }
446 | }
447 | }
448 | }
449 | }
450 | }
451 | }
452 | }
453 | }
454 | }
455 | }
456 | }
457 | }
458 | }
459 | }
460 | }
461 | }
462 | }
463 | }
464 | }
465 | }
466 | }
467 | }
468 | }
469 | }
470 | }
471 | }
472 | }
473 | }
474 | }
475 | }
476 | }
477 | }
478 | }
479 | }
480 | }
481 | }
482 | }
483 | }
484 | }
485 | }
486 | }
487 | }
488 | }
489 | }
490 | }
491 | }
492 | }
493 | }
494 | }
495 | }
496 | }
497 | }
498 | }
499 | }
500 | }
501 | }
502 | }
503 | }
504 | }
505 | }
506 | }
507 | }
508 | }
509 | }
510 | }
511 | }
512 | }
513 | }
514 | }
515 | }
516 | }
517 | }
518 | }
519 | }
520 | }
521 | }
522 | }
523 | }
524 | }
525 | }
526 | }
527 | }
528 | }
529 | }
530 | }
531 | }
532 | }
533 | }
534 | }
535 | }
536 | }
537 | }
538 | }
539 | }
540 | }
541 | }
542 | }
543 | }
544 | }
545 | }
546 | }
547 | }
548 | }
549 | }
550 | }
551 | }
552 | }
553 | }
554 | }
555 | }
556 | }
557 | }
558 | }
559 | }
560 | }
561 | }
562 | }
563 | }
564 | }
565 | }
566 | }
567 | }
568 | }
569 | }
570 | }
571 | }
572 | }
573 | }
574 | }
575 | }
576 | }
577 | }
578 | }
579 | }
580 | }
581 | }
582 | }
583 | }
584 | }
585 | }
586 | }
587 | }
588 | }
589 | }
590 | }
591 | }
592 | }
593 | }
594 | }
595 | }
596 | }
597 | }
598 | }
599 | }
600 | }
601 | }
602 | }
603 | }
604 | }
605 | }
606 | }
607 | }
608 | }
609 | }
610 | }
611 | }
612 | }
613 | }
614 | }
615 | }
616 | }
617 | }
618 | }
619 | }
620 | }
621 | }
622 | }
623 | }
624 | }
625 | }
626 | }
627 | }
628 | }
629 | }
630 | }
631 | }
632 | }
633 | }
634 | }
635 | }
636 | }
637 | }
638 | }
639 | }
640 | }
641 | }
642 | }
643 | }
644 | }
645 | }
646 | }
647 | }
648 | }
649 | }
650 | }
651 | }
652 | }
653 | }
654 | }
655 | }
656 | }
657 | }
658 | }
659 | }
660 | }
661 | }
662 | }
663 | }
664 | }
665 | }
666 | }
667 | }
668 | }
669 | }
670 | }
671 | }
672 | }
673 | }
674 | }
675 | }
676 | }
677 | }
678 | }
679 | }
680 | }
681 | }
682 | }
683 | }
684 | }
685 | }
686 | }
687 | }
688 | }
689 | }
690 | }
691 | }
692 | }
693 | }
694 | }
695 | }
696 | }
697 | }
698 | }
699 | }
700 | }
701 | }
702 | }
703 | }
704 | }
705 | }
706 | }
707 | }
708 | }
709 | }
710 | }
711 | }
712 | }
713 | }
714 | }
715 | }
716 | }
717 | }
718 | }
719 | }
720 | }
721 | }
722 | }
723 | }
724 | }
725 | }
726 | }
727 | }
728 | }
729 | }
730 | }
731 | }
732 | }
733 | }
734 | }
735 | }
736 | }
737 | }
738 | }
739 | }
740 | }
741 | }
742 | }
743 | }
744 | }
745 | }
746 | }
747 | }
748 | }
749 | }
750 | }
751 | }
752 | }
753 | }
754 | }
755 | }
756 | }
757 | }
758 | }
759 | }
760 | }
761 | }
762 | }
763 | }
764 | }
765 | }
766 | }
767 | }
768 | }
769 | }
770 | }
771 | }
772 | }
773 | }
774 | }
775 | }
776 | }
777 | }
778 | }
779 | }
780 | }
781 | }
782 | }
783 | }
784 | }
785 | }
786 | }
787 | }
788 | }
789 | }
790 | }
791 | }
792 | }
793 | }
794 | }
795 | }
796 | }
797 | }
798 | }
799 | }
800 | }
801 | }
802 | }
803 | }
804 | }
805 | }
806 | }
807 | }
808 | }
809 | }
810 | }
811 | }
812 | }
813 | }
814 | }
815 | }
816 | }
817 | }
818 | }
819 | }
820 | }
821 | }
822 | }
823 | }
824 | }
825 | }
826 | }
827 | }
828 | }
829 | }
830 | }
831 | }
832 | }
833 | }
834 | }
835 | }
836 | }
837 | }
838 | }
839 | }
840 | }
841 | }
842 | }
843 | }
844 | }
845 | }
846 | }
847 | }
848 | }
849 | }
850 | }
851 | }
852 | }
853 | }
854 | }
855 | }
856 | }
857 | }
858 | }
859 | }
860 | }
861 | }
862 | }
863 | }
864 | }
865 | }
866 | }
867 | }
868 | }
869 | }
870 | }
871 | }
872 | }
873 | }
874 | }
875 | }
876 | }
877 | }
878 | }
879 | }
880 | }
881 | }
882 | }
883 | }
884 | }
885 | }
886 | }
887 | }
888 | }
889 | }
890 | }
891 | }
892 | }
893 | }
894 | }
895 | }
896 | }
897 | }
898 | }
899 | }
900 | }
901 | }
902 | }
903 | }
904 | }
905 | }
906 | }
907 | }
908 | }
909 | }
910 | }
911 | }
912 | }
913 | }
914 | }
915 | }
916 | }
917 | }
918 | }
919 | }
920 | }
921 | }
922 | }
923 | }
924 | }
925 | }
926 | }
927 | }
928 | }
929 | }
930 | }
931 | }
932 | }
933 | }
934 | }
935 | }
936 | }
937 | }
938 | }
939 | }
940 | }
941 | }
942 | }
943 | }
944 | }
945 | }
946 | }
947 | }
948 | }
949 | }
950 | }
951 | }
952 | }
953 | }
954 | }
955 | }
956 | }
957 | }
958 | }
959 | }
960 | }
961 | }
962 | }
963 | }
964 | }
965 | }
966 | }
967 | }
968 | }
969 | }
970 | }
971 | }
972 | }
973 | }
974 | }
975 | }
976 | }
977 | }
978 | }
979 | }
980 | }
981 | }
982 | }
983 | }
984 | }
985 | }
986 | }
987 | }
988 | }
989 | }
990 | }
991 | }
992 | }
993 | }
994 | }
995 | }
996 | }
997 | }
998 | }
999 | }
```



```
45 |         <Route path="/student/trainings/:id" element={<ProtectedRoute roles={["student"]} ><TrainingDetail
46 |         <Route path="/student/meetings" element={<ProtectedRoute roles={["student"]} ><StudentMeetings /></
47 |         <Route path="/student/notifications" element={<ProtectedRoute roles={["student"]} ><StudentNotifica
48 |         <Route path="/student/certificates" element={<ProtectedRoute roles={["student"]} ><StudentCertifica
49 |         <Route path="/student/ai" element={<ProtectedRoute roles={["student"]} ><StudentAIHub /></Protected
50 |         <Route path="/student/profile" element={<ProtectedRoute roles={["student"]} ><StudentProfile /></Pr
52 |         { /* Mentor Routes */ }
53 |         <Route path="/mentor" element={<ProtectedRoute roles={["mentor"]} ><MentorDashboard /></ProtectedRo
54 |         <Route path="/mentor/students" element={<ProtectedRoute roles={["mentor"]} ><MentorStudents /></Pro
55 |         <Route path="/mentor/meetings" element={<ProtectedRoute roles={["mentor"]} ><MentorMeetings /></Pro
56 |         <Route path="/mentor/notifications" element={<ProtectedRoute roles={["mentor"]} ><MentorNotificatio
57 |         <Route path="/mentor/profile" element={<ProtectedRoute roles={["mentor"]} ><StudentProfile /></Prot
59 |         { /* Admin Routes */ }
60 |         <Route path="/admin" element={<ProtectedRoute roles={["admin"]} ><AdminDashboard /></ProtectedRoute
61 |         <Route path="/admin/students" element={<ProtectedRoute roles={["admin"]} ><AdminStudents /></Prot
62 |         <Route path="/admin/mentors" element={<ProtectedRoute roles={["admin"]} ><AdminMentors /></Protecte
63 |         <Route path="/admin/trainings" element={<ProtectedRoute roles={["admin"]} ><AdminTrainings /></Prot
64 |         <Route path="/admin/meetings" element={<ProtectedRoute roles={["admin"]} ><AdminMeetings /></Prot
65 |         <Route path="/admin/notifications" element={<ProtectedRoute roles={["admin"]} ><AdminNotifications
66 |         <Route path="/admin/reports" element={<ProtectedRoute roles={["admin"]} ><AdminReports /></Protecte
68 |         <Route path="" element={<Navigate to="/" replace /> } />
69 |     </Routes>
70 |     </BrowserRouter>
71 |     </AuthProvider>
72 |     </ThemeProvider>
73 |   );
74 | }
76 | export default App; src/components/CalendarViews \(5.0 KB\)
77 |
78 | import { useState } from "react";
79 | import { ChevronLeft, ChevronRight, Calendar as CalendarIcon, Clock, Video, User } from "lucide-react";
80 |
81 | export default function CalendarView({ events = [], onSelectDate, userRole = "student" }) {
82 |   const [currentDate, setCurrentDate] = useState(new Date());
83 |
84 |   const year = currentDate.getFullYear();
85 |   const month = currentDate.getMonth();
86 |
87 |   const monthNames = [
88 |     "January", "February", "March", "April", "May", "June",
89 |     "July", "August", "September", "October", "November", "December"
90 |   ];
91 |
92 |   const firstDayOfMonth = new Date(year, month, 1).getDay();
93 |   const daysInMonth = new Date(year, month + 1, 0).getDate();
94 |
95 |   const prevMonth = () => setCurrentDate(new Date(year, month - 1, 1));
96 |   const nextMonth = () => setCurrentDate(new Date(year, month + 1, 1));
97 |
98 |   // Match events to days
99 |   const getEventsForDay = (day) => {
100 |     return events.filter((e) => {
101 |       const eDate = new Date(e.scheduledDate || e.date || e.createdAt);
102 |       return (
103 |         eDate.getDate() === day &&
104 |         eDate.getMonth() === month &&
105 |         eDate.getFullYear() === year
106 |       );
107 |     });
108 |   };
109 |
110 |   const statusColors = {
111 |     accepted: "bg-green-500 text-white",
112 |     pending: "bg-amber-500 text-white",
113 |     rejected: "bg-red-500 text-white",
114 |     completed: "bg-purple-600 text-white",
115 |   };
116 |
117 |   return (
118 |     <div className="glass-card p-6">
119 |       { /* Calendar Header */ }
120 |       <div className="flex items-center justify-between mb-6">
121 |         <div className="flex h-10 w-10 items-center justify-center rounded-xl bg-katalyst-500 text-white">
122 |           <CalendarIcon className="h-5 w-5" />
123 |         </div>
124 |         <div>
125 |           <h2 className="text-xl font-bold">
126 |             {monthNames[month]} {year}
127 |           </h2>
128 |         </div>
129 |       </div>
130 |     </div>
131 |   );
132 | }
```

```
51 |         </h2>
52 |         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
53 |             Interactive Schedule & Meeting Calendar ({userRole.toUpperCase()})
54 |         </p>
55 |     </div>
56 | </div>
57 |
58 |     <div className="flex items-center gap-2">
59 |         <button onClick={prevMonth} className="btn-secondary !p-2">
60 |             <ChevronLeft className="h-4 w-4" />
61 |         </button>
62 |         <button onClick={() => setCurrentDate(new Date())} className="btn-secondary !py-1.5 text-xs font-sem
63 |             Today
64 |         </button>
65 |         <button onClick={nextMonth} className="btn-secondary !p-2">
66 |             <ChevronRight className="h-4 w-4" />
67 |         </button>
68 |     </div>
69 | </div>
70 |
71 |     {/* Weekday headers */}
72 |     <div className="grid grid-cols-7 gap-1 text-center font-bold text-xs mb-2 text-gray-500 uppercase tracki
73 |         <span>Sun</span>
74 |         <span>Mon</span>
75 |         <span>Tue</span>
76 |         <span>Wed</span>
77 |         <span>Thu</span>
78 |         <span>Fri</span>
79 |         <span>Sat</span>
80 |     </div>
81 |
82 |     {/* Days Grid */}
83 |     <div className="grid grid-cols-7 gap-2">
84 |         {/* Empty padding days for previous month */}
85 |         {Array.from({ length: firstDayOfMonth }).map((_, i) => (
86 |             <div key={`empty-${i}`} className="h-24 rounded-xl bg-gray-50/30 dark:bg-gray-800/10 opacity-30" />
87 |         ))}
88 |
89 |         {/* Month Days */}
90 |         {Array.from({ length: daysInMonth }).map((_, i) => {
91 |             const day = i + 1;
92 |             const dayEvents = getEventsForDay(day);
93 |             const isToday =
94 |                 day === new Date().getDate() &&
95 |                 month === new Date().getMonth() &&
96 |                 year === new Date().getFullYear();
97 |
98 |             return (
99 |                 <div
100 |                     key={day}
101 |                     onClick={() => onSelectDate && onSelectDate(new Date(year, month, day))}
102 |                     className={`h-24 rounded-xl border p-2 flex flex-col justify-between transition-all cursor-point
103 |                         isToday ? "border-katalyst-500 bg-katalyst-500/10 font-bold" : "border-gray-200 dark:border-gr
104 |                     `}
105 |                 >
106 |                     <div className="flex justify-between items-center">
107 |                         <span className={`text-xs ${isToday ? "text-katalyst-500 font-bold" : ""}`}>
108 |                             {day}
109 |                         </span>
110 |                         {dayEvents.length > 0 && (
111 |                             <span className="h-2 w-2 rounded-full bg-katalyst-500 animate-pulse" />
112 |                         )}
113 |                     </div>
114 |
115 |                     {/* Day Events Badge List */}
116 |                     <div className="space-y-1 overflow-y-auto max-h-14">
117 |                         {dayEvents.map((ev, idx) => (
118 |                             <div
119 |                                 key={idx}
120 |                                 className={`truncate rounded px-1.5 py-0.5 text-[10px] font-semibold ${
121 |                                     statusColors[ev.status] || "bg-katalyst-500 text-white"
122 |                                 `}
123 |                                 title={`${ev.topic || ev.title} - ${ev.scheduledTime || ""}`}
124 |                             >
125 |                                 {ev.scheduledTime ? `${ev.scheduledTime}` : ""}
126 |                                 {ev.topic || ev.title}
127 |                             </div>
128 |                         ))}
129 |                     </div>
130 |                 </div>
131 |             )}
132 |         )}
```

```
129 |         </div>
130 |     </div>
131 |     );
132 |   })}
133 | </div>
134 | </div>
135 | );
136 | } View Source Code for frontend/src/components/CalendarView.jsx \(3.1 KB\)
137 |
1 | import { useState } from "react";
2 | import API from "../api";
4 | export default function ChatBot() {
5 |   const [open, setOpen] = useState(false);
6 |   const [messages, setMessages] = useState([
7 |     { role: "bot", text: "Hi! I'm Katalyst AI. Ask me about trainings, mentors, or career tips!" },
8 |   ]);
9 |   const [input, setInput] = useState("");
10 |   const [loading, setLoading] = useState(false);
12 |   const send = async (e) => {
13 |     e.preventDefault();
14 |     if (!input.trim()) return;
15 |     const question = input.trim();
16 |     setInput("");
17 |     setMessages((m) => [...m, { role: "user", text: question }]);
18 |     setLoading(true);
19 |     try {
20 |       const res = await API.post("/ai/chatbot", { question });
21 |       setMessages((m) => [...m, { role: "bot", text: res.data.answer }]);
22 |     } catch {
23 |       setMessages((m) => [
24 |         ...m,
25 |         { role: "bot", text: "Sorry, I couldn't process that. Please try again." },
26 |       ]);
27 |     } finally {
28 |       setLoading(false);
29 |     }
30 |   };
32 |   return (
33 |     <>
34 |       <button
35 |         onClick={() => setOpen(!open)}
36 |         className="fixed bottom-6 right-6 z-50 flex h-14 w-14 items-center justify-center rounded-full text-2x
37 |         style={{ background: "linear-gradient(135deg, var(--accent), var(--accent-dark))" }}
38 |       >
39 |         {open ? "x" : "ðŸ’¬"}
40 |       </button>
42 |       {open && (
43 |         <div className="fixed bottom-24 right-6 z-50 flex w-80 flex-col overflow-hidden rounded-2xl border sha
44 |         style={{ background: "var(--bg-glass)", borderColor: "var(--border)", backdropFilter: "blur(16px)" }}
45 |         >
46 |           <div className="border-b p-4" style={{ borderColor: "var(--border)" }}>
47 |             <h3 className="font-semibold">Katalyst AI Assistant</h3>
48 |             <p className="text-xs" style={{ color: "var(--text-muted)" }}>Always here to help</p>
49 |           </div>
50 |           <div className="flex max-h-64 flex-col gap-2 overflow-y-auto p-4">
51 |             {messages.map((msg, i) => (
52 |               <div
53 |                 key={i}
54 |                 className={`max-w-[85%] rounded-xl px-3 py-2 text-sm ${
55 |                   msg.role === "user"
56 |                     ? "ml-auto bg-katalyst-500 text-white"
57 |                     : "mr-auto"
58 |                 }}
59 |                 style={msg.role === "bot" ? { background: "var(--accent-light)", color: "var(--text-primary)" }
60 |               >
61 |                 {msg.text}
62 |               </div>
63 |             ))}
64 |             {loading && (
65 |               <div className="mr-auto rounded-xl px-3 py-2 text-sm" style={{ background: "var(--accent-light)"
66 |                 Thinking...
67 |               </div>
```

```

68 |     })
69 |   </div>
70 |   <form onSubmit={send} className="flex gap-2 border-t p-3" style={{ borderColor: "var(--border)" }}>
71 |     <input
72 |       value={input}
73 |       onChange={(e) => setInput(e.target.value)}
74 |       placeholder="Ask anything..."
75 |       className="input-field !py-2 text-sm"
76 |     />
77 |     <button type="submit" className="btn-primary !px-3 !py-2 text-sm">!'/</button>
78 |   </form>
79 | </div>
80 | })
81 | </>
82 | );
83 | }
84 |
(2.5 KB)
85 |
86 | import { useState, useEffect } from "react";
87 | import NotificationPanel from "../NotificationPanel";
88 | import ChatBot from "../ChatBot";
89 | import Sidebar from "../Sidebar";
90 | import { useAuth } from "../../context/AuthContext";
91 | import API from "../../api";
92 | export default function DashboardLayout({ title, subtitle, children, actions }) {
93 |   const { user } = useAuth();
94 |   const [mobileOpen, setMobileOpen] = useState(false);
95 |   const [showNotifs, setShowNotifs] = useState(false);
96 |   const [unreadCount, setUnreadCount] = useState(0);
97 |   useEffect(() => {
98 |     API.get("/notifications")
99 |       .then((res) => setUnreadCount(res.data.unreadCount || 0))
100 |      .catch(() => {});
101 |   }, [showNotifs]);
102 |   return (
103 |     <div className="flex min-h-screen" style={{ background: "var(--bg-primary)" }}>
104 |       <Sidebar role={user?.role || "student"} mobileOpen={mobileOpen} onClose={() => setMobileOpen(false)} />
105 |       <div className="flex flex-1 flex-col min-w-0">
106 |         {/* Top bar */}
107 |         <header
108 |           className="sticky top-0 z-30 flex h-16 items-center justify-between border-b px-4 lg:px-8"
109 |           style={{ borderColor: "var(--border)", background: "var(--bg-glass)", backdropFilter: "blur(16px)" }}
110 |         >
111 |           <div className="flex items-center gap-3">
112 |             <button
113 |               className="btn-secondary !p-2 lg:hidden"
114 |               onClick={() => setMobileOpen(true)}
115 |             >
116 |               ☰
117 |             </button>
118 |             <div>
119 |               {subtitle} && <p className="section-subtitle">{subtitle}</p>
120 |               <h1 className="text-lg font-bold lg:text-xl">{title}</h1>
121 |             </div>
122 |           </div>
123 |           <div className="flex items-center gap-3">
124 |             {actions}
125 |             <div className="relative">
126 |               <button
127 |                 onClick={() => setShowNotifs(!showNotifs)}
128 |                 className="btn-secondary !rounded-full !p-2.5 text-lg relative"
129 |               >
130 |                 ⦿=Ÿ
131 |                 {unreadCount > 0 && (
132 |                   <span className="absolute -top-1 -right-1 flex h-4 w-4 items-center justify-center rounded-f
133 |                     {unreadCount}
134 |                   </span>
135 |                 )}
136 |               </button>
137 |               {showNotifs && <NotificationPanel onClose={() => setShowNotifs(false)} />}
138 |             </div>
139 |           </div>
140 |         </header>

```

```
62 |         <main className="flex-1 p-4 lg:p-8 animate-fade-in">{children}</main>
63 |       </div>
64 |     <ChatBot />
65 |   </div>
66 | );
67 | }
68 | } // frontend/src/components/layout/Sidebar.jsx (5.6 KB)
69 |
70 | import React from "react";
71 | import { NavLink } from "react-router-dom";
72 | import {
73 |   LayoutDashboard,
74 |   BookOpen,
75 |   CalendarDays,
76 |   Bell,
77 |   User,
78 |   Settings,
79 |   Logout,
80 |   Users,
81 |   GraduationCap,
82 |   ShieldCheck,
83 |   X,
84 | } from "lucide-react";
85 |
86 | const Sidebar = ({ role = "student", mobileOpen = false, onClose }) => {
87 |   const studentLinks = [
88 |     { name: "Dashboard", path: "/student", icon: LayoutDashboard },
89 |     { name: "Trainings", path: "/student/trainings", icon: BookOpen },
90 |     { name: "Calendar & Meetings", path: "/student/meetings", icon: CalendarDays },
91 |     { name: "Notifications", path: "/student/notifications", icon: Bell },
92 |     { name: "Profile", path: "/student/profile", icon: User },
93 |   ];
94 |
95 |   const mentorLinks = [
96 |     { name: "Dashboard", path: "/mentor", icon: LayoutDashboard },
97 |     { name: "Students", path: "/mentor/students", icon: Users },
98 |     { name: "Calendar & Meetings", path: "/mentor/meetings", icon: CalendarDays },
99 |     { name: "Notifications", path: "/mentor/notifications", icon: Bell },
100 |    { name: "Profile", path: "/mentor/profile", icon: User },
101 |  ];
102 |
103 |   const adminLinks = [
104 |     { name: "Dashboard", path: "/admin", icon: LayoutDashboard },
105 |     { name: "Students", path: "/admin/students", icon: GraduationCap },
106 |     { name: "Mentors", path: "/admin/mentors", icon: Users },
107 |     { name: "Trainings", path: "/admin/trainings", icon: BookOpen },
108 |     { name: "Calendar & Meetings", path: "/admin/meetings", icon: CalendarDays },
109 |     { name: "Notifications", path: "/admin/notifications", icon: Bell },
110 |   ];
111 |
112 |   let links = studentLinks;
113 |   if (role === "mentor") links = mentorLinks;
114 |   if (role === "admin") links = adminLinks;
115 |
116 |   const handleLogout = () => {
117 |     localStorage.removeItem("token");
118 |     localStorage.removeItem("user");
119 |     window.location.href = "/login";
120 |   };
121 |
122 |   const sidebarContent = (
123 |     <aside className="flex h-full w-64 flex-col border-r border-gray-200 bg-white">
124 |       <div className="flex h-16 items-center justify-between border-b border-gray-200 px-5">
125 |         <div className="flex items-center gap-3">
126 |           <GraduationCap className="h-5 w-5 text-white" />
127 |         </div>
128 |         <div>
129 |           <h1 className="text-lg font-bold text-purple-600">Katalyst</h1>
130 |           <p className="text-[10px] text-gray-500">Learning Platform</p>
131 |         </div>
132 |       </div>
133 |       <div>
134 |         <div className="flex h-9 w-9 items-center justify-center rounded-xl bg-purple-600">
135 |           <GraduationCap className="h-5 w-5 text-white" />
136 |         </div>
137 |         <div>
138 |           <h1 className="text-lg font-bold text-purple-600">Katalyst</h1>
139 |           <p className="text-[10px] text-gray-500">Learning Platform</p>
140 |         </div>
141 |       </div>
142 |       <div>
143 |         <div className="flex h-9 w-9 items-center justify-center rounded-xl bg-purple-600">
144 |           <GraduationCap className="h-5 w-5 text-white" />
145 |         </div>
146 |         <div>
147 |           <h1 className="text-lg font-bold text-purple-600">Katalyst</h1>
148 |           <p className="text-[10px] text-gray-500">Learning Platform</p>
149 |         </div>
150 |       </div>
151 |     </aside>
152 |   );
153 |
154 |   return (
155 |     <div>
156 |       <div>
157 |         <div>
158 |           <div>
159 |             <div>
160 |               <div>
161 |                 <div>
162 |                   <div>
163 |                     <div>
164 |                       <div>
165 |                         <div>
166 |                           <div>
167 |                             <div>
168 |                               <div>
169 |                                 <div>
170 |                                   <div>
```

```
71 |         <X className="h-5 w-5" />
72 |       </button>
73 |     </div>
74 |   { /* Role Badge */}
75 |   <div className="px-4 pt-4">
76 |     <div className="flex items-center gap-3 rounded-xl bg-purple-50 px-3 py-2.5">
77 |       <div className="flex h-8 w-8 items-center justify-center rounded-lg bg-purple-100">
78 |         {role === "admin" ? (
79 |           <ShieldCheck className="h-4 w-4 text-purple-600" />
80 |         ) : role === "mentor" ? (
81 |           <Users className="h-4 w-4 text-purple-600" />
82 |         ) : (
83 |           <User className="h-4 w-4 text-purple-600" />
84 |         )}
85 |       </div>
86 |       <div className="min-w-0">
87 |         <p className="text-[10px] text-gray-500">Logged in as</p>
88 |         <p className="truncate text-sm font-semibold capitalize text-gray-800">{role}</p>
89 |       </div>
90 |     </div>
91 |   </div>
92 | </div>
93 | { /* Navigation */}
94 | <nav className="flex-1 overflow-y-auto px-4 py-5">
95 |   <p className="mb-2 px-3 text-[10px] font-semibold uppercase tracking-wider text-gray-400">Menu</p>
96 |   <div className="space-y-1">
97 |     {links.map((item) => {
98 |       const Icon = item.icon;
99 |       return (
100 |         <NavLink
101 |           key={item.path}
102 |           to={item.path}
103 |           end={item.path === `/${role}`}
104 |           onClick={onClose}
105 |           className={({ isActive }) =>
106 |             `flex items-center gap-3 rounded-xl px-4 py-2.5 text-sm font-medium transition-all ${
107 |               isActive
108 |                 ? "bg-purple-600 text-white shadow-md"
109 |                 : "text-gray-600 hover:bg-purple-50 hover:text-purple-600"
110 |             }`
111 |           >
112 |             <Icon className="h-5 w-5 shrink-0" />
113 |             <span>{item.name}</span>
114 |           </NavLink>
115 |         );
116 |       })}
117 |   </div>
118 | </nav>
119 | { /* Bottom: Logout */}
120 | <div className="border-t border-gray-200 p-4">
121 |   <button
122 |     type="button"
123 |     onClick={handleLogout}
124 |     className="flex w-full items-center gap-3 rounded-xl px-4 py-2.5 text-sm font-medium text-gray-600"
125 |   >
126 |     <LogOut className="h-5 w-5" />
127 |     <span>Logout</span>
128 |   </button>
129 | </div>
130 | </aside>
131 | );
132 | return (
133 |   <>
134 |     { /* Desktop sidebar – always visible, takes up space in flow */}
135 |     <div className="hidden lg:block lg:w-64 lg:shrink-0">
136 |       <div className="fixed left-0 top-0 z-40 h-screen w-64">
137 |         {sidebarContent}
138 |       </div>
139 |     </div>
140 |     { /* Mobile sidebar – slide-in drawer with backdrop */}
141 |     {mobileOpen && (
142 |       <div className="fixed inset-0 z-50 lg:hidden">
```

```
148 |         {/* Backdrop */}
149 |         <div className="absolute inset-0 bg-black/40" onClick={onClose} />
150 |         {/* Drawer */}
151 |         <div className="relative h-full w-64 animate-fade-in">
152 |             {sidebarContent}
153 |         </div>
154 |     </div>
155 |     )}
156 | </>
157 | );
158 | };
159 |
160 | export default Sidebar; components/NotificationPanel (2.6 KB)

1 | import { useState, useEffect } from "react";
2 | import API from "../api";
3 |
4 | export default function NotificationPanel({ onClose }) {
5 |     const [notifications, setNotifications] = useState([]);
6 |     const [loading, setLoading] = useState(true);
7 |
8 |     useEffect(() => {
9 |         API.get("/notifications")
10 |            .then((res) => setNotifications(res.data.notifications || []))
11 |            .catch(() => {})
12 |            .finally(() => setLoading(false));
13 |     }, []);
14 |
15 |     const markAllRead = async () => {
16 |         await API.put("/notifications/read-all");
17 |         setNotifications((n) => n.map((item) => ({ ...item, isRead: true })));
18 |     };
19 |
20 |     const markRead = async (id) => {
21 |         await API.put(`/notifications/${id}/read`);
22 |         setNotifications((n) =>
23 |             n.map((item) => (item._id === id ? { ...item, isRead: true } : item))
24 |         );
25 |     };
26 |
27 |     return (
28 |         <div className="absolute right-0 top-12 z-50 w-80 glass-card animate-fade-in overflow-hidden">
29 |             <div className="flex items-center justify-between border-b p-4" style={{ borderColor: "var(--border)" }}>
30 |                 <h3 className="font-semibold">Notifications</h3>
31 |                 <div className="flex gap-2">
32 |                     <button onClick={markAllRead} className="text-xs text-katalyst-500 hover:underline">
33 |                         Mark all read
34 |                     </button>
35 |                     <button onClick={onClose} className="text-lg leading-none opacity-60 hover:opacity-100">
36 |                         x
37 |                     </button>
38 |                 </div>
39 |             </div>
40 |             <div className="max-h-80 overflow-y-auto">
41 |                 {loading ? (
42 |                     <p className="p-4 text-center text-sm" style={{ color: "var(--text-muted)" }}>
43 |                         Loading...
44 |                     </p>
45 |                 ) : notifications.length === 0 ? (
46 |                     <p className="p-6 text-center text-sm" style={{ color: "var(--text-muted)" }}>
47 |                         No notifications yet
48 |                     </p>
49 |                 ) : (
50 |                     notifications.map((n) => (
51 |                         <div
52 |                             key={n._id}
53 |                             onClick={() => !n.isRead && markRead(n._id)}
54 |                             className={
55 |                                 { cursor: "pointer", border: "1px solid", padding: "4px", transition: "background-color 0.2s",
56 |                                   hover: "bg-katalyst-50", dark: { hover: "bg-kat
57 |                                     !n.isRead ? "bg-katalyst-50/50 dark:bg-katalyst-900/10" : ""
58 |                                 }
59 |                             }
60 |                             style={{ borderColor: "var(--border)" }}
61 |                         >
62 |                             <p className="text-sm font-medium">{n.title}</p>
63 |                             <p className="mt-1 text-xs" style={{ color: "var(--text-secondary)" }}>
64 |                                 {n.message}
65 |                             </p>
66 |                             <span className="mt-1 block text-xs" style={{ color: "var(--text-muted)" }}>
67 |                                 {new Date(n.createdAt).toLocaleDateString()}
68 |                             </span>
69 |                         </div>
70 |                     )
71 |                 )
72 |             </div>
73 |         </div>
74 |     );
75 | }
```

```
65 |         </span>
66 |     </div>
67 |
68 |     ))
69 |   }
70 | </div>
71 | </div>
72 | );
73 | } (4.4 KB)
74 |
75 | import { useState, useEffect } from "react";
76 | import DashboardLayout from "../layout/DashboardLayout";
77 | import API from "../api";
78 | import { Bell, CheckCircle2, Trash2, Calendar, BookOpen, Trophy } from "lucide-react";
79 |
80 | export default function NotificationsPage({ userRole = "student" }) {
81 |   const [notifications, setNotifications] = useState([]);
82 |   const [loading, setLoading] = useState(true);
83 |
84 |   const fetchNotifications = () => {
85 |     API.get("/notifications")
86 |       .then((res) => setNotifications(res.data.notifications || []))
87 |       .catch(console.error)
88 |       .finally(() => setLoading(false));
89 |   };
90 |
91 |   useEffect(() => {
92 |     fetchNotifications();
93 |   }, []);
94 |
95 |   const markAllRead = async () => {
96 |     await API.put("/notifications/read-all");
97 |     fetchNotifications();
98 |   };
99 |
100 |   const markRead = async (id) => {
101 |     await API.put(`/notifications/${id}/read`);
102 |     fetchNotifications();
103 |   };
104 |
105 |   const deleteNotification = async (id) => {
106 |     await API.delete(`/notifications/${id}`);
107 |     fetchNotifications();
108 |   };
109 |
110 |   const getIcon = (type) => {
111 |     switch (type) {
112 |       case "meeting": return <Calendar className="h-5 w-5 text-blue-500" />;
113 |       case "training": return <BookOpen className="h-5 w-5 text-green-500" />;
114 |       case "certificate": return <Trophy className="h-5 w-5 text-yellow-500" />;
115 |       default: return <Bell className="h-5 w-5 text-katalyst-500" />;
116 |     }
117 |   };
118 |
119 |   return (
120 |     <DashboardLayout
121 |       title="Notifications Center"
122 |       subtitle={` ${userRole.toUpperCase()} PORTAL `}
123 |       actions={
124 |         <button onClick={markAllRead} className="btn-secondary !py-2 text-xs font-semibold">
125 |           ' Mark All as Read
126 |         </button>
127 |       }
128 |     >
129 |       {loading ? (
130 |         <div className="flex h-40 items-center justify-center">
131 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
132 |             </div>
133 |         ) : notifications.length === 0 ? (
134 |           <div className="glass-card p-12 text-center">
135 |             <Bell className="mx-auto h-12 w-12 text-gray-400" />
136 |             <h3 className="mt-4 font-bold text-lg">No Notifications</h3>
137 |             <p className="text-sm mt-1" style={{ color: "var(--text-muted)" }}>
138 |               You're all caught up! Updates regarding meetings and courses will appear here.
139 |             </p>
140 |           </div>
141 |         ) : (
142 |           <div className="space-y-3">
143 |             {notifications.map((n) => (
144 |               <div
```



```
71 |         key={n._id}
72 |         className={`glass-card p-5 flex items-start justify-between gap-4 transition-all ${
73 |           !n.isRead ? "border-l-4 border-l-katalyst-500 bg-katalyst-50/20" : ""
74 |         }`}
75 |       >
76 |         <div className="flex items-start gap-4">
77 |           <div className="p-2.5 rounded-xl bg-gray-100 dark:bg-gray-800">
78 |             {getIcon(n.type)}
79 |           </div>
80 |           <div>
81 |             <h4 className="font-bold flex items-center gap-2">
82 |               {n.title}
83 |               {!n.isRead && (
84 |                 <span className="rounded-full bg-katalyst-500 px-2 py-0.5 text-[10px] text-white font-se
85 |                   NEW
86 |                 </span>
87 |               )}
88 |             </h4>
89 |             <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
90 |               {n.message}
91 |             </p>
92 |             <span className="text-xs mt-2 block" style={{ color: "var(--text-muted)" }}>
93 |               {new Date(n.createdAt).toLocaleString()}
94 |             </span>
95 |           </div>
96 |         </div>
97 |         <div className="flex items-center gap-2">
98 |           {!n.isRead && (
99 |             <button
100 |               onClick={() => markRead(n._id)}
101 |               className="p-2 rounded-lg text-gray-500 hover:bg-gray-100 hover:text-green-600"
102 |               title="Mark as read"
103 |             >
104 |               <CheckCircle2 className="h-4 w-4" />
105 |             </button>
106 |           )}
107 |           <button
108 |             onClick={() => deleteNotification(n._id)}
109 |             className="p-2 rounded-lg text-gray-500 hover:bg-gray-100 hover:text-red-600"
110 |             title="Delete notification"
111 |           >
112 |             <Trash2 className="h-4 w-4" />
113 |           </button>
114 |         </div>
115 |       </div>
116 |     </div>
117 |   )}
118 | </div>
119 | )}
120 | </DashboardLayout>
121 | );
122 | }
123 | }

import { Navigate } from "react-router-dom";
import { useAuth } from "../context/AuthContext";

export default function ProtectedRoute({ children, roles }) {
  const { user, loading } = useAuth();

  if (loading) {
    return (
      <div className="flex min-h-screen items-center justify-center">
        <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500" />
      </div>
    );
  }

  if (!user) return <Navigate to="/login" replace />;
  if (roles && !roles.includes(user.role))
    return <Navigate to={`/${user.role}`} replace />;
  return children;
}
```

(0.4 KB)

```
1 | import { useTheme } from "../context/ThemeContext";
3 | export default function ThemeToggle() {
4 |   const { darkMode, toggleTheme } = useTheme();
6 |   return (
7 |     <button
8 |       onClick={toggleTheme}
9 |       className="btn-secondary !rounded-full !p-2.5 text-lg"
10 |       title={darkMode ? "Switch to light mode" : "Switch to dark mode"}
11 |     >
12 |       {darkMode ? "& p " : "ð<ß "}
13 |     </button>
14 |   );
15 | }
```

(0.7 KB)

```
16 | export default function StatCard({ title, value, subtitle, icon }) {
17 |   return (
18 |     <div className="glass-card animate-fade-in p-5 transition-transform hover:-translate-y-1">
19 |       <div className="mb-3 flex items-center justify-between">
20 |         <p className="text-sm font-medium" style={{ color: "var(--text-secondary)" }}>
21 |           {title}
22 |         </p>
23 |         {icon && <span className="text-2xl">{icon}</span>}
24 |       </div>
25 |       <h3 className="text-3xl font-bold" style={{ color: "var(--text-primary)" }}>
26 |         {value}
27 |       </h3>
28 |       {subtitle && (
29 |         <p className="mt-1 text-sm font-medium text-katalyst-500">{subtitle}</p>
30 |       )}
31 |     </div>
32 |   );
33 | }
```

(1.1 KB)

```
1 | import { createContext, useContext, useState, useEffect } from "react";
2 | import API from "../api";
4 | const AuthContext = createContext();
6 | export const AuthProvider = ({ children }) => {
7 |   const [user, setUser] = useState(
8 |     () => JSON.parse(localStorage.getItem("user")) || "null"
9 |   );
10 |   const [loading, setLoading] = useState(true);
12 |   useEffect(() => {
13 |     const token = localStorage.getItem("token");
14 |     if (token && user) {
15 |       API.get("/auth/me")
16 |         .then((res) => setUser(res.data.user))
17 |         .catch(() => logout())
18 |         .finally(() => setLoading(false));
19 |     } else {
20 |       setLoading(false);
21 |     }
22 |   }, []);
24 |   const login = (userData, token) => {
25 |     localStorage.setItem("token", token);
26 |     localStorage.setItem("user", JSON.stringify(userData));
27 |     setUser(userData);
28 |   };
30 |   const logout = () => {
31 |     localStorage.removeItem("token");
32 |     localStorage.removeItem("user");
33 |     setUser(null);
34 |   };
36 |   return (
37 |     <AuthContext.Provider value={{ user, login, logout, loading }}>
38 |       {children}
39 |     </AuthContext.Provider>
40 |   );
41 | };
43 | export const useAuth = () => useContext(AuthContext);
44 |
```

KATALYST

Source Code: frontend/src/context/ThemeContext.jsx

Generated: 22/8/2026 | Frontend

(0.7 KB)

```
1 | import { createContext, useContext, useState, useEffect } from "react";
2 |
3 | const ThemeContext = createContext();
4 |
5 | export const ThemeProvider = ({ children }) => {
6 |   const [darkMode, setDarkMode] = useState(
7 |     () => localStorage.getItem("theme") === "dark"
8 |   );
9 |
10 |  useEffect(() => {
11 |    document.documentElement.classList.toggle("dark", darkMode);
12 |    localStorage.setItem("theme", darkMode ? "dark" : "light");
13 |  }, [darkMode]);
14 |
15 |  const toggleTheme = () => setDarkMode((prev) => !prev);
16 |
17 |  return (
18 |    <ThemeContext.Provider value={{ darkMode, toggleTheme }}>
19 |      {children}
20 |    </ThemeContext.Provider>
21 |  );
22 | };
23 |
24 | export const useTheme = () => useContext(ThemeContext);
25 |
26 | @import url("https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap");
27 |
28 | @tailwind base;
29 | @tailwind components;
30 | @tailwind utilities;
31 |
32 | :root {
33 |   --bg-primary: #f8fafc;
34 |   --bg-secondary: #ffffff;
35 |   --bg-glass: rgba(255, 255, 255, 0.85);
36 |   --text-primary: #0f172a;
37 |   --text-secondary: #475569;
38 |   --text-muted: #94a3b8;
39 |   --accent: #2563eb;
40 |   --accent-light: #eff6ff;
41 |   --accent-dark: #1d4ed8;
42 |   --border: rgba(226, 232, 240, 0.8);
43 |   --shadow: 0 10px 30px rgba(37, 99, 235, 0.08);
44 |   --sidebar-width: 260px;
45 | }
46 |
47 | .dark {
48 |   --bg-primary: #0b1120;
49 |   --bg-secondary: #0f172a;
50 |   --bg-glass: rgba(15, 23, 42, 0.85);
51 |   --text-primary: #f8fafc;
52 |   --text-secondary: #94a3b8;
53 |   --text-muted: #64748b;
54 |   --accent: #3b82f6;
55 |   --accent-light: #1e293b;
56 |   --accent-dark: #2563eb;
57 |   --border: rgba(51, 65, 85, 0.7);
58 |   --shadow: 0 10px 30px rgba(0, 0, 0, 0.5);
59 | }
60 |
61 | * {
62 |   margin: 0;
63 |   padding: 0;
64 |   box-sizing: border-box;
65 | }
66 |
67 | html {
68 |   scroll-behavior: smooth;
69 | }
70 |
71 | body {
72 |   font-family: "Inter", system-ui, -apple-system, sans-serif;
73 |   background: var(--bg-primary);
74 |   color: var(--text-primary);
75 |   min-height: 100vh;
76 |   transition: background 0.3s cubic-bezier(0.4, 0, 0.2, 1), color 0.3s cubic-bezier(0.4, 0, 0.2, 1);
77 | }
78 |
79 | @layer components {
80 |   .glass-card {
81 |     @apply rounded-2xl border backdrop-blur-glass transition-all duration-200;
82 |     background: var(--bg-glass);
83 |     border-color: var(--border);
```

```
59 |     box-shadow: var(--shadow);
60 | }
61 |
62 | .glass-card:hover {
63 |     box-shadow: 0 12px 36px rgba(37, 99, 235, 0.12);
64 | }
65 |
66 | .btn-primary {
67 |     @apply inline-flex items-center justify-center gap-2 rounded-xl px-5 py-2.5 font-semibold text-white trans
68 |     background: linear-gradient(135deg, var(--accent), var(--accent-dark));
69 |     box-shadow: 0 4px 16px rgba(37, 99, 235, 0.3);
70 | }
71 |
72 | .btn-primary:hover {
73 |     transform: translateY(-1px);
74 |     box-shadow: 0 6px 20px rgba(37, 99, 235, 0.4);
75 | }
76 |
77 | .btn-secondary {
78 |     @apply inline-flex items-center justify-center gap-2 rounded-xl border px-5 py-2.5 font-medium transition-
79 |     border-color: var(--border);
80 |     background: var(--bg-secondary);
81 |     color: var(--text-primary);
82 | }
83 |
84 | .btn-secondary:hover {
85 |     border-color: var(--accent);
86 |     color: var(--accent);
87 |     background: var(--accent-light);
88 | }
89 |
90 | .input-field {
91 |     @apply w-full rounded-xl border px-4 py-2.5 outline-none transition-all duration-200;
92 |     border-color: var(--border);
93 |     background: var(--bg-secondary);
94 |     color: var(--text-primary);
95 | }
96 |
97 | .input-field:focus {
98 |     border-color: var(--accent);
99 |     box-shadow: 0 0 0 3px rgba(37, 99, 235, 0.15);
100 | }
101 |
102 | .progress-bar {
103 |     @apply h-2.5 overflow-hidden rounded-full;
104 |     background: var(--accent-light);
105 | }
106 |
107 | .progress-bar-fill {
108 |     @apply h-full rounded-full transition-all duration-500;
109 |     background: linear-gradient(90deg, #3b82f6, #1d4ed8);
110 | }
111 |
112 | .badge {
113 |     @apply inline-block rounded-full px-3 py-1 text-xs font-semibold uppercase tracking-wider;
114 |     background: var(--accent-light);
115 |     color: var(--accent-dark);
116 | }
117 |
118 | .section-title {
119 |     @apply text-2xl font-bold tracking-tight;
120 |     color: var(--text-primary);
121 | }
122 |
123 | .section-subtitle {
124 |     @apply text-sm font-medium uppercase tracking-wider;
125 |     color: var(--text-muted);
126 | }
127 | }
128 |
129 | /* Scrollbar */
130 | ::-webkit-scrollbar {
131 |     width: 6px;
132 |     height: 6px;
133 | }
134 | ::-webkit-scrollbar-track {
135 |     background: transparent;
136 | }
137 | ::-webkit-scrollbar-thumb {
138 |     background: var(--accent);
139 |     border-radius: 9999px;
140 | }
141 |
142 | /* Animations */
```

```
143 | @keyframes fadeIn {
144 |   from { opacity: 0; transform: translateY(8px); }
145 |   to { opacity: 1; transform: translateY(0); }
146 | }
147 | .animate-fade-in {
148 |   animation: fadeIn 0.3s ease-out forwards;
149 | }
151 | @keyframes pulse-blue {
152 |   0%, 100% { box-shadow: 0 0 0 0 rgba(37, 99, 235, 0.4); }
153 |   50% { box-shadow: 0 0 0 8px rgba(37, 99, 235, 0); }
154 | }
155 | .pulse-blue {
156 |   animation: pulse-blue 2s infinite;
157 | }
158 |                                     (2.2 KB)
1   | .login-page {
2   |   min-height: 100vh;
3   |   background: #09090b;
4   |   display: flex;
5   |   justify-content: center;
6   |   align-items: center;
7   |   padding: 30px;
8   |   position: relative;
9   | }
11  | .back-button {
12  |   position: absolute;
13  |   top: 30px;
14  |   left: 5%;
15  |   background: transparent;
16  |   border: none;
17  |   color: #a1a1aa;
18  |   font-size: 15px;
19  |   cursor: pointer;
20  | }
22  | .back-button:hover {
23  |   color: white;
24  | }
26  | .login-card {
27  |   width: 100%;
28  |   max-width: 480px;
29  |   padding: 45px;
30  |   background: #111114;
31  |   border: 1px solid #27272a;
32  |   border-radius: 20px;
33  |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
34  | }
36  | .login-logo {
37  |   font-size: 22px;
38  |   font-weight: 800;
39  |   letter-spacing: 2px;
40  |   margin-bottom: 35px;
41  | }
43  | .login-logo span {
44  |   color: #8b5cf6;
45  | }
47  | .login-card h1 {
48  |   font-size: 38px;
49  |   margin-bottom: 10px;
50  |   color: white;
51  | }
53  | .login-subtitle {
54  |   color: #71717a;
55  |   margin-bottom: 30px;
56  | }
58  | .role-options {
59  |   display: flex;
60  |   flex-direction: column;
61  |   gap: 12px;
62  | }
64  | .role-card {
65  |   width: 100%;
```

```
66 | padding: 17px;
67 | background: #18181b;
68 | border: 1px solid #27272a;
69 | border-radius: 12px;
70 | color: white;
71 | display: flex;
72 | align-items: center;
73 | gap: 15px;
74 | text-align: left;
75 | cursor: pointer;
76 | }
77 |
78 | .role-card:hover {
79 |   border-color: #7c3aed;
80 | }
81 |
82 | .role-card.selected {
83 |   border-color: #8b5cf6;
84 |   background: #1c1729;
85 | }
86 |
87 | .role-icon {
88 |   width: 42px;
89 |   height: 42px;
90 |   display: flex;
91 |   align-items: center;
92 |   justify-content: center;
93 |   background: #27272a;
94 |   border-radius: 10px;
95 |   font-size: 20px;
96 | }
97 |
98 | .role-card h3 {
99 |   margin-bottom: 4px;
100 | }
101 |
102 | .role-card p {
103 |   color: #71717a;
104 |   font-size: 12px;
105 | }
106 |
107 | .continue-button {
108 |   width: 100%;
109 |   padding: 14px;
110 |   margin-top: 25px;
111 |   border: none;
112 |   border-radius: 8px;
113 |   background: #7c3aed;
114 |   color: white;
115 |   font-size: 15px;
116 |   cursor: pointer;
117 | }
118 |
119 | .continue-button:hover {
120 |   background: #8b5cf6;
121 | }
122 |
123 | .demo-button {
124 |   width: 100%;
125 |   padding: 13px;
126 |   margin-top: 10px;
127 |   border: 1px solid #3f3f46;
128 |   border-radius: 8px;
129 |   background: transparent;
130 |   color: white;
131 |   cursor: pointer;
132 | }
133 |
134 | .login-footer {
135 |   text-align: center;
136 |   color: #52525b;
137 |   font-size: 11px;
138 |   line-height: 1.6;
139 |   margin-top: 30px;
140 | }
```

KATALYST

Source Code: frontend/src/Login.jsx

Generated: 22/8/2026 | Frontend

(2.4 KB)

```
1 | import { useState } from "react";
2 | import { Link, useNavigate } from "react-router-dom";
3 |
4 | function Login() {
5 |   const [role, setRole] = useState("student");
6 |
7 |   const [email, setEmail] = useState("");
8 |   const [password, setPassword] = useState("");
9 |
10 |   const navigate = useNavigate();
11 |
12 |   const handleLogin = (e) => {
13 |     e.preventDefault();
14 |
15 |     if (role === "student") {
16 |       navigate("/student-dashboard");
17 |     } else if (role === "mentor") {
18 |       navigate("/mentor-dashboard");
19 |     } else if (role === "admin") {
20 |       navigate("/admin-dashboard");
21 |     }
22 |   };
23 |
24 |   return (
25 |     <div className="auth-page">
26 |       <div className="auth-card">
27 |         <Link to="/" className="back-link">
28 |           !• KATALYST
29 |         </Link>
30 |
31 |         <h1>
32 |           Welcome <span>Back.</span>
33 |         </h1>
34 |
35 |         <p className="auth-subtitle">
36 |           Login to continue your Katalyst journey.
37 |         </p>
38 |
39 |         <div className="role-container">
40 |
41 |           <button
42 |             type="button"
43 |             className={role === "student" ? "role active" : "role"}
44 |             onClick={() => setRole("student")}
45 |           >
46 |             Ø<ß" Student
47 |           </button>
48 |
49 |           <button
50 |             type="button"
51 |             className={role === "mentor" ? "role active" : "role"}
52 |             onClick={() => setRole("mentor")}
53 |           >
54 |             Ø=Üh Ø<ßë Mentor
55 |           </button>
56 |
57 |           <button
58 |             type="button"
59 |             className={role === "admin" ? "role active" : "role"}
60 |             onClick={() => setRole("admin")}
61 |           >
62 |             Ø=Þáp Admin
63 |           </button>
64 |
65 |         </div>
66 |
67 |         <form onSubmit={handleLogin}>
68 |           <label>Email</label>
69 |
70 |           <input
71 |             type="email"
72 |             placeholder="Enter your email"
73 |             value={email}
74 |             onChange={(e) => setEmail(e.target.value)}
75 |             required
76 |           />
77 |
78 |           <label>Password</label>
79 |
80 |           <input
81 |             type="password"
82 |             placeholder="Enter your password"
83 |             value={password}
84 |             onChange={(e) => setPassword(e.target.value)}
85 |             required
86 |           />
87 |
88 |         </form>
89 |       </div>
90 |     </div>
91 |   );
92 | }
```

```
90 |         <button type="submit" className="login-button">
91 |             Login as {role} !'
92 |         </button>
93 |     </form>
94 |     <p className="demo-text">
95 |         Demo mode – any valid email and password will continue.
96 |     </p>
97 | </div>
98 | </div>
99 | );
100 | };
101 | }
102 | export default Login; (0.2 KB)
103 |
104 | import React from "react";
105 | import ReactDOM from "react-dom/client";
106 | import App from "./App";
107 | import "./index.css";
108 | ReactDOM.createRoot(document.getElementById("root")).render(
109 |     <React.StrictMode>
110 |         <App />
111 |     </React.StrictMode>
112 | ); (0.0 KB)
113 | (3.6 KB)
114 |
115 | import { useEffect, useState } from "react";
116 | import { Link } from "react-router-dom";
117 | import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer, PieChart, Pie, Cell } from "recharts";
118 | import DashboardLayout from "../../components/layout/DashboardLayout";
119 | import StatCard from "../../components/ui/StatCard";
120 | import API from "../../api";
121 |
122 | const COLORS = ["#ec4899", "#f472b6", "#fbcfe8", "#db2777", "#be185d"];
123 |
124 | export default function AdminDashboard() {
125 |     const [data, setData] = useState(null);
126 |     const [loading, setLoading] = useState(true);
127 |
128 |     useEffect(() => {
129 |         API.get("/admin/dashboard")
130 |             .then((res) => setData(res.data))
131 |             .catch(console.error)
132 |             .finally(() => setLoading(false));
133 |     }, []);
134 |
135 |     if (loading) {
136 |         return (
137 |             <DashboardLayout title="Dashboard" subtitle="Admin Portal">
138 |                 <div className="flex h-64 items-center justify-center">
139 |                     <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-5">
140 |                     </div>
141 |                 </DashboardLayout>
142 |             );
143 |         }
144 |
145 |     const stats = data?.stats || {};
146 |     const pieData = [
147 |         { name: "Completed", value: stats.completedMeetings || 0 },
148 |         { name: "Pending", value: stats.pendingMeetings || 0 },
149 |         { name: "Other", value: Math.max(0, (stats.totalMeetings || 0) - (stats.completedMeetings || 0) - (stats.p
150 |     ];
151 |
152 |     return (
153 |         <DashboardLayout title="Admin Dashboard" subtitle="Admin Portal">
154 |             <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
155 |                 <StatCard title="Total Students" value={stats.totalStudents || 0} icon="ðŸŒŒ" />
156 |                 <StatCard title="Total Mentors" value={stats.totalMentors || 0} icon="ðŸŒŒ" />
157 |                 <StatCard title="Trainings" value={stats.totalTrainings || 0} icon="ðŸŒŒ" />
158 |                 <StatCard title="Certificates" value={stats.totalCertificates || 0} icon="ðŸŒŒ" />
159 |             </div>
160 |             <div className="grid gap-6 lg:grid-cols-2">
161 |                 <div className="glass-card p-6">
162 |                     <h3 className="section-title mb-4">Top Trainings by Enrollment</h3>
163 |                     <ResponsiveContainer width="100%" height={250}>
164 |                         <BarChart data={data?.topTrainings || []}>
165 |                             <XAxis dataKey="title" tick={{ fontSize: 10 }} />
166 |                             <YAxis tick={{ fontSize: 12 }} />
167 |                             <Tooltip />
168 |                         </BarChart>
169 |                     </div>
170 |                 </div>
171 |             </div>
172 |         </DashboardLayout>
173 |     );
174 | }
```



```
55 |         <Bar dataKey="enrollments" fill="#ec4899" radius={[6, 6, 0, 0]} />
56 |     </BarChart>
57 | </ResponsiveContainer>
58 | </div>
59 |
60 | <div className="glass-card p-6">
61 |     <h3 className="section-title mb-4">Meeting Status</h3>
62 |     <ResponsiveContainer width="100%" height={250}>
63 |         <PieChart>
64 |             <Pie data={pieData} cx="50%" cy="50%" outerRadius={80} dataKey="value" label>
65 |                 {pieData.map((_, i) => <Cell key={i} fill={COLORS[i % COLORS.length]} />)}
66 |             </Pie>
67 |             <Tooltip />
68 |         </PieChart>
69 |     </ResponsiveContainer>
70 | </div>
71 | </div>
72 |
73 | <div className="glass-card mt-6 p-6">
74 |     <h3 className="section-title mb-4">Quick Actions</h3>
75 |     <div className="grid gap-3 sm:grid-cols-2 lg:grid-cols-4">
76 |         {[
77 |             { to: "/admin/students", label: "ðŸ‘Œ Manage Students" },
78 |             { to: "/admin/mentors", label: "ðŸ‘Œ Manage Mentors" },
79 |             { to: "/admin/trainings", label: "ðŸ‘Œ Manage Trainings" },
80 |             { to: "/admin/reports", label: "ðŸ‘Œ View Reports" },
81 |         ].map((a) => (
82 |             <Link key={a.to} to={a.to} className="btn-secondary text-left !py-4">{a.label}</Link>
83 |         ))}
84 |     </div>
85 | </div>
86 | </DashboardLayout>
87 | );
88 | } <!-- End of Admin Meetings --> (5.3 KB)
89 |
90 | import { useEffect, useState } from "react";
91 | import DashboardLayout from "../../components/layout/DashboardLayout";
92 | import CalendarView from "../../components/CalendarView";
93 | import API from "../../api";
94 |
95 | export default function AdminMeetings() {
96 |     const [meetings, setMeetings] = useState([]);
97 |     const [loading, setLoading] = useState(true);
98 |     const [tab, setTab] = useState("calendar");
99 |
100 |     const fetchMeetings = () => {
101 |         API.get("/meetings/admin")
102 |             .then((res) => setMeetings(res.data.meetings || []))
103 |             .catch(console.error)
104 |             .finally(() => setLoading(false));
105 |     };
106 |
107 |     useEffect(() => {
108 |         fetchMeetings();
109 |     }, []);
110 |
111 |     const updateStatus = async (id, status) => {
112 |         await API.put(`/meetings/${id}/status`, { status });
113 |         fetchMeetings();
114 |     };
115 |
116 |     const statusColor = {
117 |         pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
118 |         accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
119 |         rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
120 |         completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
121 |     };
122 |
123 |     return (
124 |         <DashboardLayout title="Platform Calendar & Meetings" subtitle="Admin Portal">
125 |             <div className="mb-6 flex gap-2">
126 |                 {[
127 |                     { id: "calendar", label: "ðŸ“… Master Platform Calendar" },
128 |                     { id: "list", label: "ðŸ“… All Scheduled Sessions" },
129 |                 ].map((t) => (
130 |                     <button
131 |                         key={t.id}
132 |                         onClick={() => setTab(t.id)}
133 |                         className={`rounded-full px-4 py-1.5 text-sm font-medium ${
```



```
119 |         })
120 |       </div>
121 |     </div>
122 |   )}
123 | </div>
124 | })
125 | </DashboardLayout>
126 | );
127 | } (4.1 KB)
128 |
1   import { useEffect, useState } from "react";
2   import DashboardLayout from "../../components/layout/DashboardLayout";
3   import API from "../../api";
4
5   export default function AdminMentors() {
6     const [mentors, setMentors] = useState([]);
7     const [loading, setLoading] = useState(true);
8     const [showCreate, setShowCreate] = useState(false);
9     const [form, setForm] = useState({ name: "", email: "", password: "", expertise: "", designation: "", compan
11  const fetchMentors = () => {
12     API.get("/admin/mentors")
13       .then((res) => setMentors(res.data.mentors || []))
14       .catch(console.error)
15       .finally(() => setLoading(false));
16   };
17
18   useEffect(() => { fetchMentors(); }, []);
19
20   const createMentor = async (e) => {
21     e.preventDefault();
22     await API.post("/admin/mentors", {
23       ...form,
24       expertise: form.expertise.split(",").map((s) => s.trim()).filter(Boolean),
25     });
26     setShowCreate(false);
27     fetchMentors();
28   };
29
30   const deleteMentor = async (id) => {
31     if (!confirm("Delete this mentor?")) return;
32     await API.delete(`/admin/mentors/${id}`);
33     fetchMentors();
34   };
35
36   return (
37     <DashboardLayout
38       title="Manage Mentors"
39       subtitle="Admin Portal"
40       actions=<button onClick={() => setShowCreate(true)} className="btn-primary !py-2 text-sm">+ Add Mentor<
41     >
42     {loading ? (
43       <div className="flex h-40 items-center justify-center">
44         <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
45       </div>
46     ) : (
47       <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
48         {mentors.map((m) => (
49           <div key={m._id} className="glass-card p-5">
50             <div className="flex items-center gap-3">
51               <div className="flex h-12 w-12 items-center justify-center rounded-full bg-katalyst-500 text-l
52                 {m.name?.charAt(0)}
53             </div>
54             <div>
55               <p className="font-bold">{m.name}</p>
56               <p className="text-xs" style={{ color: "var(--text-muted)" }}>{m.designation}</p>
57             </div>
58           </div>
59           <p className="mt-3 text-sm" style={{ color: "var(--text-secondary)" }}>{m.email}</p>
60           <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>
61             Students: {m.assignedStudents?.length || 0} · Rating: {m.rating || 5}/5
62           </p>
63           <div className="mt-3 flex flex-wrap gap-1">
64             {m.expertise?.slice(0, 3).map((e) => (
65               <span key={e} className="badge !text-[10px]">{e}</span>
66             ))}
67           </div>
68           <button onClick={() => deleteMentor(m._id)} className="btn-secondary mt-4 w-full !py-2 text-sm !
```

```
69 |         Delete
70 |       </button>
71 |     </div>
72 |   )}}
73 | </div>
74 | }}
75 | {showCreate && (
76 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
77 |     <div className="glass-card w-full max-w-md p-6 max-h-[90vh] overflow-y-auto">
78 |       <h3 className="text-xl font-bold">Create Mentor</h3>
79 |       <form onSubmit={createMentor} className="mt-4 space-y-3">
80 |         {[ "name", "email", "password", "designation", "company"].map((f) => (
81 |           <input key={f} className="input-field" placeholder={f} type={f === "password" ? "password" : "
82 |             value={form[f]} onChange={(e) => setForm({ ...form, [f]: e.target.value })} required={f !==
83 |             ))}
84 |         <input className="input-field" placeholder="Expertise (comma separated)" value={form.expertise}
85 |           onChange={(e) => setForm({ ...form, expertise: e.target.value })} />
86 |         <div className="flex gap-2">
87 |           <button type="button" onClick={() => setShowCreate(false)} className="btn-secondary flex-1">Ca
88 |           <button type="submit" className="btn-primary flex-1">Create</button>
89 |         </div>
90 |       </form>
91 |     </div>
92 |   </div>
93 | </div>
94 |   )}}
95 | </DashboardLayout>
96 | );
97 | }
98 | }
99 |
100 | import NotificationsPage from "../../components/NotificationsPage";
101 | export default function AdminNotifications() {
102 |   return <NotificationsPage userRole="admin" />;
103 | }
104 | }
105 |
106 | import { useEffect, useState } from "react";
107 | import DashboardLayout from "../../components/layout/DashboardLayout";
108 | import API from "../../api";
109 | export default function AdminReports() {
110 |   const [reports, setReports] = useState(null);
111 |   const [loading, setLoading] = useState(true);
112 |   const [notifyMsg, setNotifyMsg] = useState({ title: "", message: "", targetRole: "student" });
113 |   useEffect(() => {
114 |     API.get("/admin/reports")
115 |       .then((res) => setReports(res.data))
116 |       .catch(console.error)
117 |       .finally(() => setLoading(false));
118 |   }, []);
119 |   const sendNotification = async (e) => {
120 |     e.preventDefault();
121 |     await API.post("/admin/notify", notifyMsg);
122 |     alert("Notification sent!");
123 |     setNotifyMsg({ title: "", message: "", targetRole: "student" });
124 |   };
125 |   return (
126 |     <DashboardLayout title="Reports & Notifications" subtitle="Admin Portal">
127 |       {loading ? (
128 |         <div className="flex h-40 items-center justify-center">
129 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
130 |         </div>
131 |       ) : (
132 |         <div className="grid gap-6 lg:grid-cols-2">
133 |           <div className="glass-card p-6">
134 |             <h3 className="section-title mb-4">Platform Summary</h3>
135 |             <div className="space-y-3">
136 |               <div className="flex justify-between rounded-lg p-3" style={{ background: "var(--accent-light)"
137 |                 <span className="text-sm">Students Tracked</span>
138 |                 <span className="font-bold text-katalyst-500">{reports?.progressData?.length || 0}</span>
139 |               </div>
140 |               {reports?.meetingReport || []}.map((item) => (
141 |                 <div key={item._id} className="flex justify-between rounded-lg p-3" style={{ background: "var(
142 |                   <span className="text-sm capitalize">Meetings: {item._id}</span>
143 |                   <span className="font-bold text-katalyst-500">{item.count}</span>
```

```
43 |         </div>
44 |     )}
45 |     {(reports?.categoryEnrollment || []).map((item) => (
46 |         <div key={item._id} className="flex justify-between rounded-lg p-3" style={{ background: "var(
47 |             <span className="text-sm">{item._id}</span>
48 |             <span className="font-bold text-katalyst-500">{item.totalEnrollments} enrollments</span>
49 |         </div>
50 |     )}
51 | </div>
52 | </div>
53 |
54 | <div className="glass-card p-6">
55 |     <h3 className="section-title mb-4">Send Bulk Notification</h3>
56 |     <form onSubmit={sendNotification} className="space-y-3">
57 |         <select className="input-field" value={notifyMsg.targetRole}
58 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, targetRole: e.target.value })}>
59 |             <option value="student">All Students</option>
60 |             <option value="mentor">All Mentors</option>
61 |             <option value="all">Everyone</option>
62 |         </select>
63 |         <input className="input-field" placeholder="Title" value={notifyMsg.title}
64 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, title: e.target.value })} required />
65 |         <textarea className="input-field" rows={3} placeholder="Message" value={notifyMsg.message}
66 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, message: e.target.value })} required />
67 |         <button type="submit" className="btn-primary w-full">Send Notification</button>
68 |     </form>
69 | </div>
70 | </div>
71 | )}
72 | </DashboardLayout>
73 | );
74 | } <!-- frontend/src/pages/admin/Students.jsx (3.7 KB) -->
75 |
76 | import { useEffect, useState } from "react";
77 | import DashboardLayout from "../../components/layout/DashboardLayout";
78 | import API from "../../api";
79 |
80 | export default function AdminStudents() {
81 |     const [students, setStudents] = useState([]);
82 |     const [mentors, setMentors] = useState([]);
83 |     const [loading, setLoading] = useState(true);
84 |
85 |     useEffect(() => {
86 |         Promise.all([API.get("/admin/students"), API.get("/admin/mentors")])
87 |             .then(async ([s, m]) => {
88 |                 setStudents(s.data.students || []);
89 |                 setMentors(m.data.mentors || []);
90 |             })
91 |             .catch(console.error)
92 |             .finally(() => setLoading(false));
93 |     }, []);
94 |
95 |     const assignMentor = async (studentId, mentorId) => {
96 |         await API.post("/admin/assign-mentor", { studentId, mentorId });
97 |         const res = await API.get("/admin/students");
98 |         setStudents(res.data.students || []);
99 |     };
100 |
101 |     const toggleActive = async (id, isActive) => {
102 |         await API.put(`/admin/students/${id}`, { isActive: !isActive });
103 |         const res = await API.get("/admin/students");
104 |         setStudents(res.data.students || []);
105 |     };
106 |
107 |     const deleteStudent = async (id) => {
108 |         if (!confirm("Delete this student?")) return;
109 |         await API.delete(`/admin/students/${id}`);
110 |         setStudents(students.filter((s) => s._id !== id));
111 |     };
112 |
113 |     return (
114 |         <DashboardLayout title="Manage Students" subtitle="Admin Portal">
115 |             {loading ? (
116 |                 <div className="flex h-40 items-center justify-center">
117 |                     <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500" />
118 |                 </div>
119 |             ) : (
120 |                 <div className="glass-card overflow-x-auto">
```

```
46 |         <table className="w-full text-sm">
47 |           <thead>
48 |             <tr className="border-b" style={{ borderColor: "var(--border)" }}>
49 |               {[ "Name", "Email", "Mentor", "Status", "Actions" ].map((h) => (
50 |                 <th key={h} className="p-4 text-left font-semibold">{h}</th>
51 |               ))}
52 |             </tr>
53 |           </thead>
54 |           <tbody>
55 |             {students.map((s) => (
56 |               <tr key={s._id} className="border-b" style={{ borderColor: "var(--border)" }}>
57 |                 <td className="p-4 font-medium">{s.name}</td>
58 |                 <td className="p-4" style={{ color: "var(--text-secondary)" }}>{s.email}</td>
59 |                 <td className="p-4">
60 |                   <select
61 |                     value={s.assignedMentor?._id || ""}
62 |                     onChange={(e) => e.target.value && assignMentor(s._id, e.target.value)}
63 |                     className="input-field !py-1.5 text-xs"
64 |                   >
65 |                     <option value="">Assign mentor</option>
66 |                     {mentors.map((m) => (
67 |                       <option key={m._id} value={m._id}>{m.name}</option>
68 |                     ))}
69 |                   </select>
70 |                 </td>
71 |                 <td className="p-4">
72 |                   <span className={`badge ${s.isActive ? "!bg-green-100 !text-green-700" : "!bg-red-100 !tex
73 |                     {s.isActive ? "Active" : "Inactive"}
74 |                   </span>
75 |                 </td>
76 |                 <td className="p-4">
77 |                   <div className="flex gap-2">
78 |                     <button onClick={() => toggleActive(s._id, s.isActive)} className="btn-secondary !py-1 t
79 |                       {s.isActive ? "Deactivate" : "Activate"}
80 |                     </button>
81 |                     <button onClick={() => deleteStudent(s._id)} className="btn-secondary !py-1 text-xs !tex
82 |                       Delete
83 |                     </button>
84 |                   </div>
85 |                 </td>
86 |               </tr>
87 |             ))}
88 |           </tbody>
89 |         </table>
90 |       </div>
91 |     )}
92 |   </DashboardLayout>
93 | );
94 | } // frontend/src/pages/admin/Students.jsx (6.5 KB)
95 |
96 | import { useEffect, useState } from "react";
97 | import DashboardLayout from "../../components/layout/DashboardLayout";
98 | import API from "../../api";
99 |
100 | export default function AdminTrainings() {
101 |   const [trainings, setTrainings] = useState([]);
102 |   const [loading, setLoading] = useState(true);
103 |   const [showCreate, setShowCreate] = useState(false);
104 |   const [form, setForm] = useState({
105 |     title: "", description: "", category: "", level: "Beginner", duration: "", instructor: "",
106 |   });
107 |
108 |   const [videos, setVideos] = useState([
109 |     { title: "", url: "", duration: "15m" }
110 |   ]);
111 |
112 |   const fetchTrainings = () => {
113 |     API.get("/trainings")
114 |       .then((res) => setTrainings(res.data.trainings || []))
115 |       .catch(console.error)
116 |       .finally(() => setLoading(false));
117 |   };
118 |
119 |   useEffect(() => { fetchTrainings(); }, []);
120 |
121 |   const addVideoField = () => {
122 |     setVideos([...videos, { title: "", url: "", duration: "15m" }]);
123 |   };
124 |
125 |   const updateVideo = (index, field, value) => {
```

```
29 |     const updated = [...videos];
30 |     updated[index][field] = value;
31 |     setVideos(updated);
32 |   };
33 |   const removeVideoField = (index) => {
34 |     setVideos(videos.filter((_, i) => i !== index));
35 |   };
36 |   const createTraining = async (e) => {
37 |     e.preventDefault();
38 |     const formattedVideos = videos
39 |       .filter((v) => v.title.trim())
40 |       .map((v, idx) => ({ ...v, order: idx + 1 }));
41 |     try {
42 |       await API.post("/trainings", {
43 |         ...form,
44 |         videos: formattedVideos,
45 |         quizzes: [
46 |           { question: `What is the primary topic of ${form.title}?`, options: [form.category || "General", "Ot
47 |         ],
48 |         assignments: []
49 |       });
50 |       setShowCreate(false);
51 |       setForm({ title: "", description: "", category: "", level: "Beginner", duration: "", instructor: "" });
52 |       setVideos([{}]);
53 |       fetchTrainings();
54 |       alert("Training created successfully!");
55 |     } catch (err) {
56 |       alert(err.response?.data?.message || "Failed to create training");
57 |     }
58 |   };
59 |   const deleteTraining = async (id) => {
60 |     if (!confirm("Delete this training?")) return;
61 |     await API.delete(`/trainings/${id}`);
62 |     fetchTrainings();
63 |   };
64 |   return (
65 |     <DashboardLayout
66 |       title="Manage Trainings"
67 |       subtitle="Admin Portal"
68 |       actions=<button onClick={() => setShowCreate(true)} className="btn-primary !py-2 text-sm">+ Add Trainin
69 |     >
70 |     {loading ? (
71 |       <div className="flex h-40 items-center justify-center">
72 |         <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
73 |       </div>
74 |     ) : (
75 |       <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
76 |         {trainings.map((t) => (
77 |           <div key={t._id} className="glass-card p-5">
78 |             <span className="badge">{t.category}</span>
79 |             <h3 className="mt-2 font-bold">{t.title}</h3>
80 |             <p className="mt-1 line-clamp-2 text-sm" style={{ color: "var(--text-secondary)" }}>{t.descripti
81 |             <div className="mt-3 flex gap-3 text-xs" style={{ color: "var(--text-muted)" }}>
82 |               <span>{t.level}</span>
83 |               <span>{t.duration}</span>
84 |               <span>{t.enrolledStudents?.length || 0} enrolled</span>
85 |             </div>
86 |             <button onClick={() => deleteTraining(t._id)} className="btn-secondary mt-4 w-full !py-2 text-sm
87 |               Delete
88 |             </button>
89 |           </div>
90 |         ))}
91 |       </div>
92 |     )}
93 |     {showCreate && (
94 |       <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4 overflow-y-auto">
95 |         <div className="glass-card w-full max-w-lg p-6 max-h-[90vh] overflow-y-auto my-8">
96 |           <h3 className="text-xl font-bold">Create New Training</h3>
97 |           <form onSubmit={createTraining} className="mt-4 space-y-3">
98 |             {[
99 |               "title",
100 |               "description",
101 |               "category",
102 |               "duration",
103 |               "instructor"
104 |             ].map((f) => (
105 |               <input key={f} className="input-field capitalize" placeholder={f} value={form[f]}
106 |                 onChange={(e) => setForm({ ...form, [f]: e.target.value })} required />
```

```
107 |         )))
108 |         <select className="input-field" value={form.level}
109 |             onChange={(e) => setForm({ ...form, level: e.target.value })}>
110 |             {["Beginner", "Intermediate", "Advanced"].map((l) => <option key={l}>{l}</option>)}
111 |         </select>
112 |         { /* Video Lessons Section */ }
113 |         <div className="pt-2 border-t mt-4" style={{ borderColor: "var(--border)" }}>
114 |             <div className="flex justify-between items-center mb-2">
115 |                 <h4 className="font-semibold text-sm">ð Course Lessons / Videos</h4>
116 |                 <button type="button" onClick={addVideoField} className="text-xs text-katalyst-500 hover:und
117 |                     + Add Lesson
118 |                 </button>
119 |             </div>
120 |             {videos.map((vid, idx) => (
121 |                 <div key={idx} className="space-y-2 mb-3 p-3 rounded-lg border text-xs" style={{ borderColor
122 |                     <div className="flex justify-between items-center">
123 |                         <span className="font-medium">Lesson #{idx + 1}</span>
124 |                         {videos.length > 1 && (
125 |                             <button type="button" onClick={() => removeVideoField(idx)} className="text-red-500 ho
126 |                                 Remove
127 |                             </button>
128 |                         )}
129 |                     </div>
130 |                     <input className="input-field !py-1.5 text-xs" placeholder="Lesson Title (e.g. Introductio
131 |                         onChange={(e) => updateVideo(idx, "title", e.target.value)} required />
132 |                     <input className="input-field !py-1.5 text-xs" placeholder="Video URL (e.g. https://youtu.
133 |                         onChange={(e) => updateVideo(idx, "url", e.target.value)} />
134 |                     <input className="input-field !py-1.5 text-xs" placeholder="Duration (e.g. 20m)" value={vi
135 |                         onChange={(e) => updateVideo(idx, "duration", e.target.value)} />
136 |                     </div>
137 |                 )))
138 |             </div>
139 |             <div className="flex gap-2 pt-3">
140 |                 <button type="button" onClick={() => setShowCreate(false)} className="btn-secondary flex-1">Ca
141 |                 <button type="submit" className="btn-primary flex-1">Create Training</button>
142 |             </div>
143 |         </form>
144 |     </div>
145 | </div>
146 | </div>
147 | </div>
148 | ))
149 | </DashboardLayout>
150 | );
151 | }
152 | } (4.7 KB)
153 |
154 | 1 | import { Link } from "react-router-dom";
155 | 2 | import ThemeToggle from "../components/ThemeToggle";
156 | 3 |
157 | 4 | export default function Home() {
158 | 5 |     return (
159 | 6 |         <div className="min-h-screen" style={{ background: "var(--bg-primary)" }}>
160 | 7 |             <nav className="flex items-center justify-between border-b px-6 py-5 lg:px-12"
161 | 8 |                 style={{ borderColor: "var(--border)", background: "var(--bg-glass)", backdropFilter: "blur(16px)" }}
162 | 9 |                 >
163 |10 |                 <h1 className="text-2xl font-bold tracking-wider lg:text-3xl">
164 |11 |                     KATALYST<span className="text-katalyst-500">.</span>
165 |12 |                 </h1>
166 |13 |                 <div className="flex items-center gap-3">
167 |14 |                     <ThemeToggle />
168 |15 |                     <Link to="/login" className="btn-secondary">Login</Link>
169 |16 |                     <Link to="/register" className="btn-primary hidden sm:inline-flex">Get Started !'</Link>
170 |17 |                 </div>
171 |18 |             </nav>
172 |19 |
173 |20 |             <section className="mx-auto max-w-6xl px-6 py-16 lg:py-24">
174 |21 |                 <div className="badge mb-8">Student • Mentor • Growth</div>
175 |22 |                 <h2 className="text-5xl font-extrabold leading-tight tracking-tight lg:text-7xl">
176 |23 |                     Learn.<br />
177 |24 |                     Connect.<br />
178 |25 |                     <span className="text-katalyst-500">Grow.</span>
179 |26 |                 </h2>
180 |27 |                 <p className="mt-8 max-w-xl text-lg leading-relaxed" style={{ color: "var(--text-secondary)" }}>
181 |28 |                     Katalyst is your all-in-one student-mentor learning platform. Track progress,
182 |29 |                     book mentorship sessions, earn certificates, and unlock AI-powered career insights.
183 |30 |                 </p>
184 |31 |
185 |32 |             </section>
186 |33 |         </div>
187 |34 |     );
188 |35 | }
```



```
34 |         <div className="mt-10 flex flex-wrap items-center gap-4">
35 |             <Link to="/register" className="btn-primary text-lg">Start Learning !</Link>
36 |             <Link to="/login" className="btn-secondary text-lg">Try Demo Accounts </Link>
37 |         </div>
38 |
39 |         { /* Instant Demo Quick-Access for New Users */ }
40 |         <div className="glass-card mt-12 p-6 border-l-4 border-l-katalyst-500">
41 |             <h3 className="font-bold text-lg flex items-center gap-2">
42 |                 <span>'</span> Instant Demo Access for New Users
43 |             </h3>
44 |             <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
45 |                 Explore the platform instantly with zero setup using pre-configured role demos:
46 |             </p>
47 |             <div className="mt-4 flex flex-wrap gap-3">
48 |                 <Link to="/login" className="btn-primary !py-2 text-xs">
49 |                     <span> Try Student Portal Demo
50 |                 </Link>
51 |                 <Link to="/login" className="btn-secondary !py-2 text-xs">
52 |                     <span> Try Mentor Portal Demo
53 |                 </Link>
54 |                 <Link to="/login" className="btn-secondary !py-2 text-xs">
55 |                     <span> Try Admin Portal Demo
56 |                 </Link>
57 |             </div>
58 |         </div>
59 |
60 |         { /* Feature cards */ }
61 |         <div className="mt-16 grid gap-6 sm:grid-cols-2 lg:grid-cols-3">
62 |             { [
63 |                 { icon: "ðŸ“Œ", title: "Structured Trainings", desc: "Videos, quizzes, assignments & certificates" },
64 |                 { icon: "ðŸ“Œ", title: "Expert Mentorship", desc: "Book sessions, get feedback & track growth" },
65 |                 { icon: "ðŸ“Œ", title: "AI Career Tools", desc: "Resume analyzer, roadmap & scholarship finder" },
66 |                 { icon: "ðŸ“Œ", title: "Progress Analytics", desc: "Real-time placement readiness scoring" },
67 |                 { icon: "ðŸ“Œ", title: "Certificates", desc: "Earn & download completion certificates" },
68 |                 { icon: "ðŸ“Œ", title: "Smart Notifications", desc: "Stay updated on meetings & milestones" },
69 |             ].map((f) => (
70 |                 <div key={f.title} className="glass-card p-6 transition-transform hover:-translate-y-1">
71 |                     <span className="text-3xl">{f.icon}</span>
72 |                     <h3 className="mt-4 text-lg font-bold">{f.title}</h3>
73 |                     <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>{f.desc}</p>
74 |                 </div>
75 |             ))
76 |         </div>
77 |
78 |         { /* Portal preview */ }
79 |         <div className="glass-card mt-16 flex flex-col items-start justify-between gap-6 p-8 sm:flex-row sm:it
80 |             <div>
81 |                 <p className="section-subtitle">Platform Portals</p>
82 |                 <h3 className="mt-2 text-2xl font-bold lg:text-3xl">Multi-Role Learning & Mentorship</h3>
83 |                 <p className="mt-3 max-w-md" style={{ color: "var(--text-secondary)" }}>
84 |                     Students learn and grow. Mentors guide and track. Admins manage the entire ecosystem.
85 |                 </p>
86 |             </div>
87 |             <div className="flex gap-4">
88 |                 { ["ðŸ“Œ", "ðŸ“Œ", "ðŸ“Œ"].map((e, i) => (
89 |                     <div key={i} className="flex h-16 w-16 items-center justify-center rounded-2xl bg-katalyst-500 t
90 |                         {e}
91 |                     </div>
92 |                 ))
93 |             </div>
94 |         </div>
95 |     </section>
96 | </div>
97 | );
98 | }
99 |
```

(9.1 KB)

```
1 | import { useState } from "react";
2 | import { Link, useNavigate } from "react-router-dom";
3 | import { useAuth } from "../context/AuthContext";
4 | import API from "../api";
5 | import ThemeToggle from "../components/ThemeToggle";
6 |
7 | export default function Login() {
8 |   const [role, setRole] = useState("student");
9 |   const [email, setEmail] = useState("");
10 |   const [password, setPassword] = useState("");
11 |   const [error, setError] = useState("");
12 |   const [loading, setLoading] = useState(false);
13 |
14 |   // Reset password state
15 |   const [showReset, setShowReset] = useState(false);
16 |   const [resetEmail, setResetEmail] = useState("");
17 |   const [newPassword, setNewPassword] = useState("");
18 |   const [resetMessage, setResetMessage] = useState("");
19 |
20 |   const { login } = useAuth();
21 |   const navigate = useNavigate();
22 |
23 |   const handleQuickDemo = async (demoRole) => {
24 |     setError("");
25 |     setLoading(true);
26 |     let demoEmail = "";
27 |     let demoPass = "";
28 |
29 |     if (demoRole === "student") {
30 |       demoEmail = "diksha@katalyst.io";
31 |       demoPass = "Student@123";
32 |     } else if (demoRole === "mentor") {
33 |       demoEmail = "sarah@katalyst.io";
34 |       demoPass = "Mentor@123";
35 |     } else if (demoRole === "admin") {
36 |       demoEmail = "admin@katalyst.io";
37 |       demoPass = "Admin@123";
38 |     }
39 |
40 |     setEmail(demoEmail);
41 |     setPassword(demoPass);
42 |     setRole(demoRole);
43 |
44 |     try {
45 |       const res = await API.post("/auth/login", {
46 |         email: demoEmail,
47 |         password: demoPass,
48 |         role: demoRole
49 |       });
50 |       login(res.data.user, res.data.token);
51 |       navigate(`/${res.data.user.role}`);
52 |     } catch (err) {
53 |       setError(err.response?.data?.message || "Demo login failed");
54 |     } finally {
55 |       setLoading(false);
56 |     }
57 |   };
58 |
59 |   const handleSubmit = async (e) => {
60 |     e.preventDefault();
61 |     setError("");
62 |     setLoading(true);
63 |
64 |     try {
65 |       const res = await API.post("/auth/login", {
66 |         email: email.trim().toLowerCase(),
67 |         password: password.trim(),
68 |         role
69 |       });
70 |       login(res.data.user, res.data.token);
71 |       navigate(`/${res.data.user.role}`);
72 |     } catch (err) {
73 |       setError(err.response?.data?.message || "Login failed");
74 |     } finally {
75 |       setLoading(false);
76 |     }
77 |   };
78 |
79 |   const handleResetPassword = async (e) => {
80 |     e.preventDefault();
81 |     setResetMessage("");
```

```
82 |     try {
83 |       const res = await API.post("/auth/reset-password", {
84 |         email: resetEmail.trim().toLowerCase(),
85 |         newPassword: newPassword.trim(),
86 |       });
87 |       setResetMessage(res.data.message);
88 |       setEmail(resetEmail);
89 |       setPassword(newPassword);
90 |       setTimeout(() => {
91 |         setShowReset(false);
92 |         setResetMessage("");
93 |       }, 2000);
94 |     } catch (err) {
95 |       setResetMessage(err.response?.data?.message || "Reset failed");
96 |     }
97 |   };
98 |
99 |   const roles = [
100 |     { id: "student", label: "ð<ß" Student" },
101 |     { id: "mentor", label: "ð=Üh ð<ßë Mentor" },
102 |     { id: "admin", label: "ð=Þáp Admin" },
103 |   ];
104 |
105 |   return (
106 |     <div className="flex min-h-screen items-center justify-center p-4" style={{ background: "var(--bg-primary)"
107 |       <div className="absolute right-6 top-6"><ThemeToggle /></div>
108 |
109 |       <div className="glass-card w-full max-w-md p-8 animate-fade-in">
110 |         <Link to="/" className="text-sm font-medium text-katalyst-500 hover:underline">
111 |           !• Back to Katalyst
112 |         </Link>
113 |
114 |         <h1 className="mt-6 text-3xl font-bold">
115 |           Welcome <span className="text-katalyst-500">Back.</span>
116 |         </h1>
117 |         <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>
118 |           Login to continue your Katalyst journey.
119 |         </p>
120 |
121 |         { /* 1-Click Instant Demo Login */ }
122 |         <div className="mt-5 rounded-xl border p-3" style={{ borderColor: "var(--border)", background: "rgba(2
123 |           <p className="text-xs font-bold text-center mb-2 text-katalyst-500 uppercase tracking-wider">
124 |             ð=Þë One-Click Instant Demo Login
125 |           </p>
126 |           <div className="grid grid-cols-3 gap-2">
127 |             <button
128 |               type="button"
129 |               onClick={() => handleQuickDemo("student")}
130 |               className="btn-primary !py-1.5 text-xs font-semibold"
131 |             >
132 |               ð<ß" Student Demo
133 |             </button>
134 |             <button
135 |               type="button"
136 |               onClick={() => handleQuickDemo("mentor")}
137 |               className="btn-primary !py-1.5 text-xs font-semibold"
138 |             >
139 |               ð=Üh ð<ßë Mentor Demo
140 |             </button>
141 |             <button
142 |               type="button"
143 |               onClick={() => handleQuickDemo("admin")}
144 |               className="btn-primary !py-1.5 text-xs font-semibold"
145 |             >
146 |               ð=Þáp Admin Demo
147 |             </button>
148 |           </div>
149 |         </div>
150 |
151 |         <div className="mt-6 grid grid-cols-3 gap-2">
152 |           {roles.map((r) => (
153 |             <button
154 |               key={r.id}
155 |               type="button"
156 |               onClick={() => setRole(r.id)}
157 |               className={`rounded-xl border px-2 py-3 text-sm font-medium transition-all ${
158 |                 role === r.id
159 |                   ? "border-katalyst-500 bg-katalyst-500 text-white"
```

```
160 |         : "border-transparent hover:border-katalyst-300"
161 |       `}`
162 |       style={role !== r.id ? { background: "var(--bg-secondary)" } : {}}
163 |     >
164 |       {r.label}
165 |     </button>
166 |   )))
167 | </div>
168 |
169 | <form onSubmit={handleSubmit} className="mt-6 space-y-4">
170 |   <div>
171 |     <label className="mb-1 block text-sm font-medium">Email</label>
172 |     <input type="email" value={email} onChange={(e) => setEmail(e.target.value)}
173 |       className="input-field" placeholder="you@email.com" required />
174 |   </div>
175 |   <div>
176 |     <div className="flex items-center justify-between mb-1">
177 |       <label className="text-sm font-medium">Password</label>
178 |       <button
179 |         type="button"
180 |         onClick={() => { setResetEmail(email); setShowReset(true); }}
181 |         className="text-xs text-katalyst-500 hover:underline"
182 |       >
183 |         Forgot Password?
184 |       </button>
185 |     </div>
186 |     <input type="password" value={password} onChange={(e) => setPassword(e.target.value)}
187 |       className="input-field" placeholder="....." required />
188 |   </div>
189 |   {error && (
190 |     <div className="rounded-lg bg-red-100 p-3 text-sm text-red-600 dark:bg-red-900/30 dark:text-red-30"
191 |       >{error}</div>
192 |   )}
193 |   <button type="submit" disabled={loading} className="btn-primary w-full">
194 |     {loading ? "Signing in..." : `Login as ${role} !`}
195 |   </button>
196 | </form>
197 |
198 | <p className="mt-4 text-center text-sm" style={{ color: "var(--text-muted)" }}>
199 |   New here?{" "}
200 |   <Link to="/register" className="font-medium text-katalyst-500 hover:underline">
201 |     Create account
202 |   </Link>
203 | </p>
204 | </div>
205 |
206 | {showReset && (
207 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
208 |     <div className="glass-card w-full max-w-md p-6 animate-fade-in">
209 |       <h3 className="text-xl font-bold">Reset Password</h3>
210 |       <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
211 |         Enter your email and a new password below.
212 |       </p>
213 |       <form onSubmit={handleResetPassword} className="mt-4 space-y-3">
214 |         <div>
215 |           <label className="text-xs font-medium">Account Email</label>
216 |           <input
217 |             type="email"
218 |             className="input-field mt-1"
219 |             placeholder="registered@email.com"
220 |             value={resetEmail}
221 |             onChange={(e) => setResetEmail(e.target.value)}
222 |             required
223 |           />
224 |         </div>
225 |         <div>
226 |           <label className="text-xs font-medium">New Password</label>
227 |           <input
228 |             type="password"
229 |             className="input-field mt-1"
230 |             placeholder="New password (min 6 characters)"
231 |             minLength={6}
232 |             value={newPassword}
233 |             onChange={(e) => setNewPassword(e.target.value)}
234 |           />
235 |         </div>
236 |       </form>
237 |     </div>
238 |   </div>
239 | )}
```

```
237 |         required
238 |       />
239 |     </div>
241 |     {resetMessage && (
242 |       <p className="text-xs font-semibold text-katalyst-500">{resetMessage}</p>
243 |     )}
245 |     <div className="flex gap-2 pt-2">
246 |       <button type="button" onClick={() => setShowReset(false)} className="btn-secondary flex-1">
247 |         Cancel
248 |       </button>
249 |       <button type="submit" className="btn-primary flex-1">
250 |         Update Password
251 |       </button>
252 |     </div>
253 |   </form>
254 | </div>
255 | </div>
256 |   )}
257 | </div>
258 | );
259 | }
260 | }                                     (5.0 KB)
261 |
1 | import { useEffect, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer } from "recharts";
4 | import DashboardLayout from "../../components/layout/DashboardLayout";
5 | import StatCard from "../../components/ui/StatCard";
6 | import API from "../../api";
7 | import { useAuth } from "../../context/AuthContext";
8 |
9 | export default function MentorDashboard() {
10 |   const { user } = useAuth();
11 |   const [data, setData] = useState(null);
12 |   const [loading, setLoading] = useState(true);
13 |
14 |   useEffect(() => {
15 |     API.get("/mentors/dashboard")
16 |       .then((res) => setData(res.data))
17 |       .catch(console.error)
18 |       .finally(() => setLoading(false));
19 |   }, []);
20 |
21 |   const respond = async (id, status) => {
22 |     try {
23 |       await API.put(`/mentors/meeting/${id}`, { status });
24 |       const res = await API.get("/mentors/dashboard");
25 |       setData(res.data);
26 |     } catch (err) {
27 |       alert(err.response?.data?.message || "Failed");
28 |     }
29 |   };
30 |
31 |   if (loading) {
32 |     return (
33 |       <DashboardLayout title="Dashboard" subtitle="Mentor Portal">
34 |         <div className="flex h-64 items-center justify-center">
35 |           <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
36 |             </div>
37 |         </div>
38 |       </DashboardLayout>
39 |     );
40 |   }
41 |
42 |   const stats = data?.stats || {};
43 |   const chartData = (data?.mentor?.assignedStudents || []).slice(0, 5).map((s) => ({
44 |     name: s.name?.split(" ")[0] || "Student",
45 |     progress: Math.floor(Math.random() * 40 + 60),
46 |   }));
47 |
48 |   return (
49 |     <DashboardLayout title={`Welcome, ${user?.name?.split(" ")[0] || "Mentor"}`} subtitle="Mentor Portal">
50 |       <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
51 |         <StatCard title="Total Students" value={stats.totalStudents || 0} icon="👤" />
52 |         <StatCard title="Pending Requests" value={stats.pendingRequests || 0} subtitle="Need action" icon="#0" />
53 |         <StatCard title="Completed Meetings" value={stats.completedMeetings || 0} icon="🗓️" />
54 |         <StatCard title="Rating" value={`${stats.rating || 5}/5`} icon="⭐" />
55 |       </div>
56 |       <div className="grid gap-6 lg:grid-cols-2">
```

```
57 |         {/* Pending requests */}
58 |         <div className="glass-card p-6">
59 |             <div className="mb-4 flex items-center justify-between">
60 |                 <h3 className="section-title">Pending Requests</h3>
61 |                 <Link to="/mentor/meetings" className="text-sm text-katalyst-500 hover:underline">View all !'</Link>
62 |             </div>
63 |             {(data?.pendingMeetings || []).length === 0 ? (
64 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No pending requests.</p>
65 |             ) : (
66 |                 data.pendingMeetings.slice(0, 3).map((m) => (
67 |                     <div key={m._id} className="mb-3 rounded-xl border p-4" style={{ borderColor: "var(--border)" }}>
68 |                         <p className="font-medium">{m.topic}</p>
69 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
70 |                             {m.studentId?.name} · {new Date(m.scheduledDate).toLocaleDateString()} {m.scheduledTime}
71 |                         </p>
72 |                         <div className="mt-3 flex gap-2">
73 |                             <button onClick={() => respond(m._id, "accepted")} className="btn-primary !py-1.5 text-xs">A
74 |                             <button onClick={() => respond(m._id, "rejected")} className="btn-secondary !py-1.5 text-xs"
75 |                         </div>
76 |                     </div>
77 |                 ))
78 |             )}
79 |         </div>
80 |
81 |         {/* Upcoming meetings */}
82 |         <div className="glass-card p-6">
83 |             <h3 className="section-title mb-4">Upcoming Meetings</h3>
84 |             {(data?.upcomingMeetings || []).length === 0 ? (
85 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No upcoming meetings.</p>
86 |             ) : (
87 |                 data.upcomingMeetings.map((m) => (
88 |                     <div key={m._id} className="mb-3 rounded-xl p-3" style={{ background: "var(--accent-light)" }}>
89 |                         <p className="font-medium">{m.topic}</p>
90 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
91 |                             {m.studentId?.name} · {new Date(m.scheduledDate).toLocaleDateString()}
92 |                         </p>
93 |                         {m.meetLink && (
94 |                             <a href={m.meetLink} target="_blank" rel="noreferrer" className="text-xs text-katalyst-500 h
95 |                                 Join Meet !'
96 |                             </a>
97 |                         )}
98 |                     </div>
99 |                 ))
100 |             )}
101 |         </div>
102 |     </div>
103 |
104 |     {chartData.length > 0 && (
105 |         <div className="glass-card mt-6 p-6">
106 |             <h3 className="section-title mb-4">Student Progress Overview</h3>
107 |             <ResponsiveContainer width="100%" height={250}>
108 |                 <BarChart data={chartData}>
109 |                     <XAxis dataKey="name" tick={{ fontSize: 12 }} />
110 |                     <YAxis domain={[0, 100]} tick={{ fontSize: 12 }} />
111 |                     <Tooltip />
112 |                     <Bar dataKey="progress" fill="#ec4899" radius={[6, 6, 0, 0]} />
113 |                 </BarChart>
114 |             </ResponsiveContainer>
115 |         </div>
116 |     )}
117 | </DashboardLayout>
118 | );
119 | }
120 |
```

(6.3 KB)

```
1 | import { useEffect, useState } from "react";
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
3 | import CalendarView from "../../components/CalendarView";
4 | import API from "../../api";
5 |
6 | export default function MentorMeetings() {
7 |   const [meetings, setMeetings] = useState([]);
8 |   const [loading, setLoading] = useState(true);
9 |   const [notesModal, setNotesModal] = useState(null);
10 |   const [notes, setNotes] = useState("");
11 |   const [tab, setTab] = useState("calendar");
12 |
13 |   const fetchMeetings = () => {
14 |     API.get("/meetings/mentor")
15 |       .then((res) => setMeetings(res.data.meetings || []))
16 |       .catch(console.error)
17 |       .finally(() => setLoading(false));
18 |   };
19 |
20 |   useEffect(() => { fetchMeetings(); }, []);
21 |
22 |   const respond = async (id, status) => {
23 |     await API.put(`/meetings/${id}/status`, { status });
24 |     fetchMeetings();
25 |   };
26 |
27 |   const addNotes = async () => {
28 |     await API.put(`/meetings/${notesModal}/status`, { mentorNotes: notes });
29 |     setNotesModal(null);
30 |     setNotes("");
31 |     fetchMeetings();
32 |   };
33 |
34 |   const completeMeeting = async (id) => {
35 |     await API.put(`/meetings/${id}/status`, { status: "completed" });
36 |     fetchMeetings();
37 |   };
38 |
39 |   const statusColor = {
40 |     pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
41 |     accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
42 |     rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
43 |     completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
44 |   };
45 |
46 |   return (
47 |     <DashboardLayout title="Calendar & Meetings" subtitle="Mentor Portal">
48 |       <div className="mb-6 flex gap-2">
49 |         {[
50 |           { id: "calendar", label: "📅 Interactive Calendar" },
51 |           { id: "requests", label: "📝 Meeting Requests" },
52 |         ]}.map((t) => (
53 |           <button key={t.id} onClick={() => setTab(t.id)}
54 |             className={`rounded-full px-4 py-1.5 text-sm font-medium ${
55 |               tab === t.id ? "bg-katalyst-500 text-white" : "border"
56 |             }`}
57 |             style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
58 |           >
59 |             {t.label}
60 |           </button>
61 |         )))
62 |       </div>
63 |       {loading ? (
64 |         <div className="flex h-40 items-center justify-center">
65 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
66 |             </div>
67 |         </div>
68 |       ) : tab === "calendar" ? (
69 |         <div className="space-y-6">
70 |           <CalendarView events={meetings} userRole="mentor" />
71 |           <div>
72 |             <div className="glass-card p-6">
73 |               <h3 className="section-title mb-4">Scheduled Mentorship Sessions</h3>
74 |               <div className="space-y-3">
75 |                 {meetings.length === 0 ? (
76 |                   <p className="text-sm" style={{ color: "var(--text-muted)" }}>No sessions scheduled.</p>
77 |                 ) : (
78 |                   meetings.map((m) => (
79 |                     <div key={m._id} className="flex flex-wrap items-center justify-between gap-3 rounded-xl bor
80 |                       <div>
```

```
82 |         <p className="font-bold">{m.topic}</p>
83 |         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
84 |             Student: {m.studentId?.name || "Student"} · {new Date(m.scheduledDate).toLocaleDateStr
85 |         </p>
86 |     </div>
87 |     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.
88 |         {m.status}
89 |     </span>
90 | </div>
91 | ))
92 | }}
93 | </div>
94 | </div>
95 | </div>
96 | ) : (
97 |     <div className="space-y-4">
98 |         {meetings.map((m) => (
99 |             <div key={m._id} className="glass-card p-5">
100 |                 <div className="flex flex-wrap items-start justify-between gap-3">
101 |                     <div>
102 |                         <h3 className="font-bold">{m.topic}</h3>
103 |                         <p className="text-sm" style={{ color: "var(--text-secondary)" }}>
104 |                             Student: {m.studentId?.name} ({m.studentId?.email}) · {new Date(m.scheduledDate).toLocaleD
105 |                         </p>
106 |                         {m.agenda && <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>Agenda: {m.a
107 |                     </div>
108 |                     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.stat
109 |                         {m.status}
110 |                     </span>
111 |                 </div>
112 |                 <div className="mt-4 flex flex-wrap gap-2">
113 |                     {m.status === "pending" && (
114 |                         <>
115 |                             <button onClick={() => respond(m._id, "accepted")} className="btn-primary !py-1.5 text-xs"
116 |                             <button onClick={() => respond(m._id, "rejected")} className="btn-secondary !py-1.5 text-x
117 |                         </>
118 |                     )}
119 |                     {m.status === "accepted" && (
120 |                         <>
121 |                             {m.meetLink && (
122 |                                 <a href={m.meetLink} target="_blank" rel="noreferrer" className="btn-primary !py-1.5 tex
123 |                             )}
124 |                             <button onClick={() => setNotesModal(m._id)} className="btn-secondary !py-1.5 text-xs">Add
125 |                             <button onClick={() => completeMeeting(m._id)} className="btn-secondary !py-1.5 text-xs">M
126 |                         </>
127 |                     )}
128 |                 </div>
129 |             </div>
130 |         )})
131 |     </div>
132 | )}
133 | {notesModal && (
134 |     <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
135 |         <div className="glass-card w-full max-w-md p-6">
136 |             <h3 className="font-bold">Meeting Notes</h3>
137 |             <textarea className="input-field mt-3" rows={4} value={notes}
138 |                 onChange={(e) => setNotes(e.target.value)} placeholder="Add meeting notes..." />
139 |             <div className="mt-3 flex gap-2">
140 |                 <button onClick={() => setNotesModal(null)} className="btn-secondary flex-1">Cancel</button>
141 |                 <button onClick={addNotes} className="btn-primary flex-1">Save Notes</button>
142 |             </div>
143 |         </div>
144 |     </div>
145 | )}
146 | </DashboardLayout>
147 | );
148 | }
149 | }
150 |
```


(0.2 KB)

```
1 | import NotificationsPage from "../../components/NotificationsPage";
```

```
3 | export default function MentorNotifications() {
```

```
4 |   return <NotificationsPage userRole="mentor" />;
```

```
5 | }
```

(4.2 KB)

```
1 | import { useEffect, useState } from "react";
```

```
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
```

```
3 | import API from "../../api";
```

```
5 | export default function MentorStudents() {
```

```
6 |   const [students, setStudents] = useState([]);
```

```
7 |   const [loading, setLoading] = useState(true);
```

```
8 |   const [selected, setSelected] = useState(null);
```

```
9 |   const [feedback, setFeedback] = useState({ rating: 5, comment: "", category: "general" });
```

```
11 |   useEffect(() => {
```

```
12 |     API.get("/mentors/students")
```

```
13 |       .then((res) => setStudents(res.data.students || []))
```

```
14 |       .catch(console.error)
```

```
15 |       .finally(() => setLoading(false));
```

```
16 |   }, []);
```

```
18 |   const giveFeedback = async (studentId) => {
```

```
19 |     try {
```

```
20 |       await API.post("/mentors/feedback", { studentId, ...feedback });
```

```
21 |       alert("Feedback submitted!");
```

```
22 |       setSelected(null);
```

```
23 |     } catch (err) {
```

```
24 |       alert(err.response?.data?.message || "Failed");
```

```
25 |     }
```

```
26 |   };
```

```
28 |   return (
```

```
29 |     <DashboardLayout title="My Students" subtitle="Mentor Portal">
```

```
30 |       {loading ? (
```

```
31 |         <div className="flex h-40 items-center justify-center">
```

```
32 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
```

```
33 |             />
```

```
34 |         ) : students.length === 0 ? (
```

```
35 |           <div className="glass-card p-12 text-center">
```

```
36 |             <p className="text-4xl">ðŸ’Š</p>
```

```
37 |             <p className="mt-4">No students assigned yet.</p>
```

```
38 |           </div>
```

```
39 |         ) : (
```

```
40 |           <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
```

```
41 |             {students.map((s) => (
```

```
42 |               <div key={s._id} className="glass-card p-5">
```

```
43 |                 <div className="flex items-center gap-3">
```

```
44 |                   <div className="flex h-12 w-12 items-center justify-center rounded-full bg-katalyst-500 text-l
```

```
45 |                     {s.name?.charAt(0)}</div>
```

```
46 |                   </div>
```

```
47 |                   <div>
```

```
48 |                     <p className="font-bold">{s.name}</p>
```

```
49 |                     <p className="text-xs" style={{ color: "var(--text-muted)" }}>{s.email}</p>
```

```
50 |                   </div>
```

```
51 |                 </div>
```

```
52 |               {s.progress && (
```

```
53 |                 <div className="mt-4">
```

```
54 |                   <div className="flex justify-between text-sm">
```

```
55 |                     <span>Progress</span>
```

```
56 |                     <span className="font-bold text-katalyst-500">{s.progress.overallScore || 0}%</span>
```

```
57 |                   </div>
```

```
58 |                   <div className="progress-bar mt-1">
```

```
59 |                     <div className="progress-bar-fill" style={{ width: `${s.progress.overallScore || 0}%` }} /
```

```
60 |                   </div>
```

```
61 |                 </div>
```

```
62 |               )}
```

```
63 |             {s.skills?.length > 0 && (
```

```
64 |               <div className="mt-3 flex flex-wrap gap-1">
```

```
65 |                 {s.skills.slice(0, 3).map((sk) => (
```

```
66 |                   <span key={sk} className="badge !text-[10px]">{sk}</span>
```

```
67 |                 )}
```

```
68 |               </div>
```

```
69 |             )}
```

```
70 |           <button onClick={() => setSelected(s._id)} className="btn-secondary mt-4 w-full !py-2 text-sm">
```

```
71 |             Give Feedback
```

```
72 |         </button>
73 |     </div>
74 |     )}}
75 | </div>
76 | })
77 | {selected && (
78 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
79 |     <div className="glass-card w-full max-w-md p-6">
80 |       <h3 className="text-xl font-bold">Give Feedback</h3>
81 |       <div className="mt-4 space-y-3">
82 |         <div>
83 |           <label className="text-sm">Rating (1-5)</label>
84 |           <input type="number" min={1} max={5} className="input-field" value={feedback.rating}
85 |             onChange={(e) => setFeedback({ ...feedback, rating: Number(e.target.value) })} />
86 |         </div>
87 |         <textarea className="input-field" rows={3} placeholder="Your feedback..."
88 |           value={feedback.comment} onChange={(e) => setFeedback({ ...feedback, comment: e.target.value }
89 |         </div>
90 |         <div className="flex gap-2">
91 |           <button onClick={() => setSelected(null)} className="btn-secondary flex-1">Cancel</button>
92 |           <button onClick={() => giveFeedback(selected)} className="btn-primary flex-1">Submit</button>
93 |         </div>
94 |       </div>
95 |     </div>
96 |   </div>
97 | )}
98 | </DashboardLayout>
99 | );
100 | } <!-- mentor/src/pages/Students --> (5.4 KB)
101 |
102 | 1 | import { useState } from "react";
103 | 2 | import { Link, useNavigate } from "react-router-dom";
104 | 3 | import { useAuth } from "../context/AuthContext";
105 | 4 | import API from "../api";
106 | 5 | import ThemeToggle from "../components/ThemeToggle";
107 | 6 |
108 | 7 | export default function Register() {
109 | 8 |   const [role, setRole] = useState("student");
110 | 9 |   const [form, setForm] = useState({
111 |10 |     name: "",
112 |11 |     email: "",
113 |12 |     password: "",
114 |13 |     phone: "",
115 |14 |   });
116 |15 |   const [error, setError] = useState("");
117 |16 |   const [loading, setLoading] = useState(false);
118 |17 |   const { login } = useAuth();
119 |18 |   const navigate = useNavigate();
120 |19 |   const handleChange = (e) => {
121 |20 |     setForm({
122 |21 |       ...form,
123 |22 |       [e.target.name]: e.target.value,
124 |23 |     });
125 |24 |   };
126 |25 |   const handleSubmit = async (e) => {
127 |26 |     e.preventDefault();
128 |27 |     setError("");
129 |28 |     setLoading(true);
130 |29 |     try {
131 |30 |       const res = await API.post("/auth/register", {
132 |31 |         name: form.name.trim(),
133 |32 |         email: form.email.trim().toLowerCase(),
134 |33 |         password: form.password,
135 |34 |         phone: form.phone.trim(),
136 |35 |         role,
137 |36 |       });
138 |37 |       if (!res.data.token || !res.data.user) {
139 |38 |         throw new Error("Server did not return token or user data");
140 |39 |       }
141 |40 |       login(res.data.user, res.data.token);
142 |41 |       navigate(`/${res.data.user.role}`);
143 |42 |     } catch (err) {
144 |43 |       console.error("REGISTER ERROR:", err);
145 |44 |     }
146 |45 |   };
147 |46 | }
```

```
53 |         if (err.response?.data?.message) {
54 |             setError(err.response.data.message);
55 |         } else if (err.message) {
56 |             setError(err.message);
57 |         } else {
58 |             setError("Registration failed");
59 |         }
60 |     } finally {
61 |         setLoading(false);
62 |     }
63 | };
64 |
65 | const roles = [
66 |   { id: "student", label: "ð<ß" Student" },
67 |   { id: "mentor", label: "ð=Üh ð<ßë Mentor" },
68 |   { id: "admin", label: "ð=Þáp Admin" },
69 | ];
70 |
71 | return (
72 |   <div
73 |     className="flex min-h-screen items-center justify-center p-4"
74 |     style={{ background: "var(--bg-primary)" }}
75 |   >
76 |     <div className="absolute right-6 top-6">
77 |       <ThemeToggle />
78 |     </div>
79 |
80 |     <div className="glass-card w-full max-w-md p-8 animate-fade-in">
81 |       <Link
82 |         to="/"
83 |         className="text-sm font-medium text-katalyst-500 hover:underline"
84 |       >
85 |         !• Back to Katalyst
86 |       </Link>
87 |
88 |       <h1 className="mt-6 text-3xl font-bold">
89 |         Join <span className="text-katalyst-500">Katalyst.</span>
90 |       </h1>
91 |
92 |       <p
93 |         className="mt-2 text-sm"
94 |         style={{ color: "var(--text-secondary)" }}
95 |       >
96 |         Create your account as {role} and start learning.
97 |       </p>
98 |
99 |       <div className="mt-6 grid grid-cols-3 gap-2">
100 |         {roles.map((r) => (
101 |           <button
102 |             key={r.id}
103 |             type="button"
104 |             onClick={() => setRole(r.id)}
105 |             className={`rounded-xl border px-2 py-3 text-sm font-medium transition-all ${
106 |               role === r.id
107 |                 ? "border-katalyst-500 bg-katalyst-500 text-white"
108 |                 : "border-transparent hover:border-katalyst-300"
109 |             }}
110 |             style={role !== r.id ? { background: "var(--bg-secondary)" } : {}}
111 |           >
112 |             {r.label}
113 |           </button>
114 |         ))}
115 |       </div>
116 |
117 |       <form onSubmit={handleSubmit} className="mt-6 space-y-4">
118 |         <div>
119 |           <label className="mb-1 block text-sm font-medium">Name</label>
120 |           <input
121 |             type="text"
122 |             name="name"
123 |             value={form.name}
124 |             onChange={handleChange}
125 |             className="input-field"
126 |             placeholder="Your full name"
127 |             required
128 |           />
129 |         </div>
130 |
131 |       </div>
```

```
132 |         <label className="mb-1 block text-sm font-medium">Email</label>
133 |         <input
134 |           type="email"
135 |           name="email"
136 |           value={form.email}
137 |           onChange={handleChange}
138 |           className="input-field"
139 |           placeholder="you@email.com"
140 |           required
141 |         />
142 |       </div>
144 |       <div>
145 |         <label className="mb-1 block text-sm font-medium">Password</label>
146 |         <input
147 |           type="password"
148 |           name="password"
149 |           value={form.password}
150 |           onChange={handleChange}
151 |           className="input-field"
152 |           placeholder="Minimum 6 characters"
153 |           minLength={6}
154 |           required
155 |         />
156 |       </div>
158 |       <div>
159 |         <label className="mb-1 block text-sm font-medium">Phone</label>
160 |         <input
161 |           type="text"
162 |           name="phone"
163 |           value={form.phone}
164 |           onChange={handleChange}
165 |           className="input-field"
166 |           placeholder="Optional"
167 |         />
168 |       </div>
170 |       {error && (
171 |         <div className="rounded-lg bg-red-100 p-3 text-sm text-red-600">
172 |           {error}
173 |         </div>
174 |       )}
176 |       <button
177 |         type="submit"
178 |         disabled={loading}
179 |         className="btn-primary w-full"
180 |       >
181 |         {loading ? "Creating account..." : `Register as ${role} !`}
182 |       </button>
183 |     </form>
185 |     <p
186 |       className="mt-4 text-center text-sm"
187 |       style={{ color: "var(--text-muted)" }}
188 |     >
189 |       Already have an account?{" "}
190 |       <Link
191 |         to="/login"
192 |         className="font-medium text-katalyst-500 hover:underline"
193 |       >
194 |         Sign in
195 |       </Link>
196 |     </p>
197 |   </div>
198 | </div>
199 | );
200 | }
```

(8.0 KB)

```
1 | import { useState } from "react";
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
3 | import API from "../../api";
4 |
5 | export default function StudentAIHub() {
6 |   const [tab, setTab] = useState("roadmap");
7 |   const [roadmap, setRoadmap] = useState(null);
8 |   const [resumeResult, setResumeResult] = useState(null);
9 |   const [scholarships, setScholarships] = useState(null);
10 |   const [resumeText, setResumeText] = useState("");
11 |   const [interests, setInterests] = useState("");
12 |   const [loading, setLoading] = useState(false);
13 |   const [progress, setProgress] = useState(null);
14 |
15 |   const loadRoadmap = async () => {
16 |     setLoading(true);
17 |     try {
18 |       const res = await API.post("/ai/career-roadmap");
19 |       setRoadmap(res.data);
20 |     } catch (err) {
21 |       alert(err.response?.data?.message || "Failed to load roadmap");
22 |     } finally {
23 |       setLoading(false);
24 |     }
25 |   };
26 |
27 |   const analyzeResume = async () => {
28 |     if (!resumeText.trim()) return alert("Paste your resume content");
29 |     setLoading(true);
30 |     try {
31 |       const res = await API.post("/ai/resume-analyze", { content: resumeText });
32 |       setResumeResult(res.data);
33 |     } catch (err) {
34 |       alert(err.response?.data?.message || "Analysis failed");
35 |     } finally {
36 |       setLoading(false);
37 |     }
38 |   };
39 |
40 |   const getScholarships = async () => {
41 |     setLoading(true);
42 |     try {
43 |       const res = await API.post("/ai/scholarships", {
44 |         interests: interests.split(",").map((s) => s.trim()).filter(Boolean),
45 |       });
46 |       setScholarships(res.data.recommendations);
47 |     } catch (err) {
48 |       alert(err.response?.data?.message || "Failed");
49 |     } finally {
50 |       setLoading(false);
51 |     }
52 |   };
53 |
54 |   const loadProgress = async () => {
55 |     setLoading(true);
56 |     try {
57 |       const res = await API.get("/students/progress");
58 |       setProgress(res.data);
59 |     } catch (err) {
60 |       alert(err.response?.data?.message || "Failed");
61 |     } finally {
62 |       setLoading(false);
63 |     }
64 |   };
65 |
66 |   const tabs = [
67 |     { id: "roadmap", label: "ðŸ“š Career Roadmap", action: loadRoadmap },
68 |     { id: "resume", label: "ðŸ“š Resume Analyzer", action: null },
69 |     { id: "scholarships", label: "ðŸ“š Scholarships", action: null },
70 |     { id: "readiness", label: "ðŸ“š Placement Readiness", action: loadProgress },
71 |   ];
72 |
73 |   return (
74 |     <DashboardLayout title="AI Hub" subtitle="Student Portal">
75 |       <div className="mb-6 flex flex-wrap gap-2">
76 |         {tabs.map((t) => (
77 |           <button key={t.id} onClick={() => { setTab(t.id); t.action?.(); }}
78 |             className={`rounded-full px-4 py-2 text-sm font-medium transition-all $`
```

KATALYST.

Source Code: frontend/src/pages/student/AIHub.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```
79 |         tab === t.id ? "bg-katalyst-500 text-white" : "border"
80 |     }`
81 |     style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
82 |     >
83 |     {t.label}
84 |   </button>
85 |   )))
86 | </div>
87 |
88 | {loading && (
89 |   <div className="flex h-20 items-center justify-center">
90 |     <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500"
91 |   </div>
92 | )}
93 |
94 | {!loading && tab === "roadmap" && (
95 |   <div className="space-y-4">
96 |     {!roadmap ? (
97 |       <div className="glass-card p-8 text-center">
98 |         <button onClick={loadRoadmap} className="btn-primary">Generate Career Roadmap</button>
99 |       </div>
100 |     ) : (
101 |       <>
102 |         <div className="glass-card p-6">
103 |           <h3 className="font-bold">Skills: {roadmap.skills?.join(", ") || "None yet"}</h3>
104 |         </div>
105 |         {roadmap.roadmap?.map((step, i) => (
106 |           <div key={i} className="glass-card p-5">
107 |             <div className="flex items-start gap-4">
108 |               <span className="flex h-8 w-8 shrink-0 items-center justify-center rounded-full bg-katalys"
109 |                 {i + 1}
110 |             </span>
111 |             <div>
112 |               <h4 className="font-bold">{step.title}</h4>
113 |               <p className="mt-1 text-sm" style={{ color: "var(--text-secondary)" }}>{step.description}
114 |               <p className="mt-2 text-xs text-katalyst-500">Target: {new Date(step.dueDate).toLocaleDa
115 |             </div>
116 |           </div>
117 |         </div>
118 |       )))
119 |     </>
120 |   )}
121 | </div>
122 | )}
123 |
124 | {!loading && tab === "resume" && (
125 |   <div className="glass-card p-6">
126 |     <h3 className="section-title mb-4">Paste Your Resume Content</h3>
127 |     <textarea className="input-field mb-4" rows={8} value={resumeText}
128 |       onChange={(e) => setResumeText(e.target.value)} placeholder="Paste resume text here..." />
129 |     <button onClick={analyzeResume} className="btn-primary">Analyze Resume</button>
130 |     {resumeResult && (
131 |       <div className="mt-6 grid gap-4 sm:grid-cols-3">
132 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
133 |           <h4 className="font-bold text-green-700">Strengths</h4>
134 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.strengths?.map((s, i) => <li key={i}>• {s
135 |         </div>
136 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
137 |           <h4 className="font-bold text-orange-600">Improve</h4>
138 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.improvementAreas?.map((s, i) => <li key={
139 |         </div>
140 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
141 |           <h4 className="font-bold text-katalyst-600">Actions</h4>
142 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.actionItems?.map((s, i) => <li key={i}>•
143 |         </div>
144 |       </div>
145 |     )}
146 |   </div>
147 | )}
148 |
149 | {!loading && tab === "scholarships" && (
150 |   <div className="glass-card p-6">
151 |     <input className="input-field mb-4" placeholder="Interests (e.g. Technology, AI/ML)"
152 |       value={interests} onChange={(e) => setInterests(e.target.value)} />
153 |     <button onClick={getScholarships} className="btn-primary">Find Scholarships</button>
154 |     {scholarships && (
```

```
155 |         <div className="mt-6 space-y-4">
156 |             {scholarships.map((s, i) => (
157 |                 <div key={i} className="rounded-xl border p-4" style={{ borderColor: "var(--border)" }}>
158 |                     <h4 className="font-bold">{s.name}</h4>
159 |                     <span className="badge mt-1">{s.category}</span>
160 |                     <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>{s.description}</p>
161 |                 </div>
162 |             )})
163 |         </div>
164 |     )}
165 | </div>
166 | )}
167 |
168 | {!loading && tab === "readiness" && progress && (
169 |     <div className="glass-card p-8 text-center">
170 |         <p className="text-6xl font-bold text-katalyst-500">{progress.progress?.placementReadiness || 0}%</p>
171 |         <p className="mt-2 text-lg font-medium">Placement Readiness Score</p>
172 |         <div className="progress-bar mx-auto mt-6 max-w-md">
173 |             <div className="progress-bar-fill" style={{ width: `${progress.progress?.placementReadiness || 0}%` }}>
174 |             </div>
175 |         <div className="mt-8 grid gap-4 sm:grid-cols-2 lg:grid-cols-4 text-left">
176 |             {[
177 |                 { label: "Training", val: progress.progress?.trainingCompletion },
178 |                 { label: "Meetings", val: progress.progress?.meetingsAttended },
179 |                 { label: "Assignments", val: progress.progress?.assignmentsSubmitted },
180 |                 { label: "Attendance", val: progress.progress?.attendanceRate },
181 |             ].map((item) => (
182 |                 <div key={item.label} className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
183 |                     <p className="text-sm" style={{ color: "var(--text-muted)" }}>{item.label}</p>
184 |                     <p className="text-2xl font-bold">{item.val || 0}{item.label === "Meetings" || item.label ===
185 |                     </div>
186 |                 )})
187 |             </div>
188 |         </div>
189 |     )}
190 | </DashboardLayout>
191 | );
192 | }
193 |
194 | </StudentCertificates> (2.8 KB)
195 |
196 | import { useEffect, useState } from "react";
197 | import DashboardLayout from "../../components/layout/DashboardLayout";
198 | import API from "../../api";
199 |
200 | export default function StudentCertificates() {
201 |     const [certificates, setCertificates] = useState([]);
202 |     const [loading, setLoading] = useState(true);
203 |     useEffect(() => {
204 |         API.get("/students/certificates")
205 |             .then((res) => setCertificates(res.data.certificates || []))
206 |             .catch(console.error)
207 |             .finally(() => setLoading(false));
208 |     }, []);
209 |     return (
210 |         <DashboardLayout title="Certificates" subtitle="Student Portal">
211 |             {loading ? (
212 |                 <div className="flex h-40 items-center justify-center">
213 |                     <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
214 |                     </div>
215 |                 ) : certificates.length === 0 ? (
216 |                     <div className="glass-card p-12 text-center">
217 |                         <p className="text-5xl">0</p>
218 |                         <p className="mt-4 font-medium">No certificates yet</p>
219 |                         <p className="mt-2 text-sm" style={{ color: "var(--text-muted)" }}>
220 |                             Complete trainings to earn certificates!
221 |                         </p>
222 |                     </div>
223 |                 ) : (
224 |                     <div className="grid gap-6 sm:grid-cols-2 lg:grid-cols-3">
225 |                         {certificates.map((cert) => (
226 |                             <div key={cert._id} className="glass-card overflow-hidden text-center transition-transform hover:-
227 |                             <div className="bg-gradient-to-br from-katalyst-400 to-katalyst-600 p-8 text-white">
228 |                                 <p className="text-4xl">0</p>
229 |                                 <h3 className="mt-3 text-lg font-bold">{cert.trainingTitle}</h3>
230 |                                 <p className="mt-1 text-sm opacity-80">{cert.studentName}</p>
231 |                             </div>
232 |                         )})
233 |                     </div>
234 |                 )}
235 |             </DashboardLayout>
236 |         );
237 |     }
238 | }
```

```
38 |         </div>
39 |         <div className="p-4">
40 |             <p className="text-xs" style={{ color: "var(--text-muted)" }}>
41 |                 Issued: {new Date(cert.issuedAt).toLocaleDateString()}
42 |             </p>
43 |             <p className="mt-1 font-mono text-xs text-katalyst-500">{cert.certificateId}</p>
44 |             <button
45 |                 onClick={() => {
46 |                     const content = `Katalyst Certificate\n\n${cert.studentName}\n${cert.trainingTitle}\nID: $
47 |                     const blob = new Blob([content], { type: "text/plain" });
48 |                     const url = URL.createObjectURL(blob);
49 |                     const a = document.createElement("a");
50 |                     a.href = url;
51 |                     a.download = `certificate-${cert.certificateId}.txt`;
52 |                     a.click();
53 |                 }}
54 |                 className="btn-primary mt-3 w-full !py-2 text-sm"
55 |             >
56 |                 Download Certificate
57 |             </button>
58 |         </div>
59 |     </div>
60 |     )}}
61 | </div>
62 | }}
63 | </DashboardLayout>
64 | );
65 | }
66 | }
67 |
68 | (6.9 KB)
69 |
70 | import { useEffect, useState } from "react";
71 | import { Link } from "react-router-dom";
72 | import { PieChart, Pie, Cell, ResponsiveContainer } from "recharts";
73 | import DashboardLayout from "../../components/layout/DashboardLayout";
74 | import StatCard from "../../components/ui/StatCard";
75 | import API from "../../api";
76 | import { useAuth } from "../../context/AuthContext";
77 |
78 | const COLORS = ["#ec4899", "#f472b6", "#fbcfe8", "#fce7f3"];
79 |
80 | export default function StudentDashboard() {
81 |     const { user } = useAuth();
82 |     const [data, setData] = useState(null);
83 |     const [loading, setLoading] = useState(true);
84 |
85 |     useEffect(() => {
86 |         API.get("/students/dashboard")
87 |             .then((res) => setData(res.data))
88 |             .catch(console.error)
89 |             .finally(() => setLoading(false));
90 |     }, []);
91 |
92 |     if (loading) {
93 |         return (
94 |             <DashboardLayout title="Dashboard" subtitle="Student Portal">
95 |                 <div className="flex h-64 items-center justify-center">
96 |                     <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-5
97 |                 </div>
98 |             </DashboardLayout>
99 |         );
100 |     }
101 |
102 |     const progress = data?.progress || {};
103 |     const overall = progress.overallScore || 0;
104 |
105 |     const chartData = [
106 |         { name: "Training", value: progress.trainingCompletion || 0 },
107 |         { name: "Meetings", value: progress.meetingsAttended / Math.max(progress.totalMeetings, 1) },
108 |         { name: "Quiz", value: progress.quizScores?.length ? progress.quizScores.reduce((a, q) => a + (q.score / q
109 |         { name: "Attendance", value: progress.attendanceRate || 0 },
110 |     ];
111 |
112 |     return (
113 |         <DashboardLayout title={`Welcome, ${user?.name?.split(" ")[0] || "Student"}`} subtitle="Student Portal">
114 |             <div className="/* Overall progress */>
115 |                 <div className="glass-card mb-6 flex flex-col items-center gap-6 p-6 sm:flex-row">
116 |                     <div className="h-36 w-36">
117 |                         <ResponsiveContainer>
118 |                             <PieChart>
```



```
50 |         <Pie data={[{ value: overall }, { value: 100 - overall }]} cx="50%" cy="50%"
51 |             innerRadius={45} outerRadius={60} dataKey="value" startAngle={90} endAngle={-270}>
52 |             <Cell fill="#ec4899" />
53 |             <Cell fill="#fce7f3" />
54 |         </Pie>
55 |     </PieChart>
56 | </ResponsiveContainer>
57 | <div className="mt-[88px] text-center">
58 |     <p className="text-2xl font-bold">{overall}%</p>
59 |     <p className="text-xs" style={{ color: "var(--text-muted)" }}>Overall</p>
60 | </div>
61 | </div>
62 | <div className="flex-1">
63 |     <h2 className="text-xl font-bold">Your Learning Progress</h2>
64 |     <p className="mt-1 text-sm" style={{ color: "var(--text-secondary)" }}>
65 |         Placement Readiness: <strong className="text-katalyst-500">{progress.placementReadiness || 0}%</st
66 |     </p>
67 |     <div className="progress-bar mt-4">
68 |         <div className="progress-bar-fill" style={{ width: `${overall}%` }} />
69 |     </div>
70 | </div>
71 | </div>
72 |
73 | <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
74 |     <StatCard title="Training Progress" value={`${progress.trainingCompletion || 0}%`} subtitle="Keep goin
75 |     <StatCard title="Meetings" value={`${progress.meetingsAttended || 0}/${progress.totalMeetingsScheduled
76 |     <StatCard title="Certificates" value={data?.certificates || 0} subtitle="Earned" icon="📜" />
77 |     <StatCard title="Notifications" value={data?.unreadNotifications || 0} subtitle="Unread" icon="🔔" />
78 | </div>
79 |
80 | <div className="grid gap-6 lg:grid-cols-2">
81 |     /* Enrolled trainings */
82 |     <div className="glass-card p-6">
83 |         <div className="mb-4 flex items-center justify-between">
84 |             <h3 className="section-title">Your Trainings</h3>
85 |             <Link to="/student/trainings" className="text-sm text-katalyst-500 hover:underline">View all !</Li
86 |         </div>
87 |         <div className="space-y-3">
88 |             {(data?.enrolledTrainings || []).length === 0 ? (
89 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No trainings enrolled yet.</p>
90 |             ) : (
91 |                 data.enrolledTrainings.map((t) => (
92 |                     <div key={t._id} className="flex items-center justify-between rounded-xl p-3"
93 |                         style={{ background: "var(--accent-light)" }}>
94 |                         <div>
95 |                             <p className="font-medium">{t.title}</p>
96 |                             <p className="text-xs" style={{ color: "var(--text-muted)" }}>{t.category}</p>
97 |                         </div>
98 |                         <span className="font-bold text-katalyst-500">
99 |                             {t.isCompleted ? "Done" : `${t.completedVideos} videos`}
100 |                         </span>
101 |                     </div>
102 |                 ))
103 |             )}
104 |         </div>
105 |     </div>
106 |
107 |     /* Upcoming meetings */
108 |     <div className="glass-card p-6">
109 |         <div className="mb-4 flex items-center justify-between">
110 |             <h3 className="section-title">Upcoming Meetings</h3>
111 |             <Link to="/student/meetings" className="text-sm text-katalyst-500 hover:underline">View all !</Lin
112 |         </div>
113 |         <div className="space-y-3">
114 |             {(data?.upcomingMeetings || []).length === 0 ? (
115 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No upcoming meetings.</p>
116 |             ) : (
117 |                 data.upcomingMeetings.map((m) => (
118 |                     <div key={m._id} className="rounded-xl border p-3" style={{ borderColor: "var(--border)" }}>
119 |                         <p className="font-medium">{m.topic}</p>
120 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
121 |                             with {m.mentorId?.name} · {new Date(m.scheduledDate).toLocaleDateString()} {m.scheduledTim
122 |                         </p>
123 |                         {m.meetLink && (
124 |                             <a href={m.meetLink} target="_blank" rel="noreferrer">
```

```
125 |         className="mt-2 inline-block text-xs text-katalyst-500 hover:underline">
126 |             Join Google Meet !'
127 |     </a>
128 |   })
129 | </div>
130 |   ))
131 | })
132 | </div>
133 | </div>
134 | </div>
135 | { /* Progress breakdown chart */ }
136 | <div className="glass-card mt-6 p-6">
137 |   <h3 className="section-title mb-4">Progress Breakdown</h3>
138 |   <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-4">
139 |     {chartData.map((item, i) => (
140 |       <div key={item.name}>
141 |         <div className="mb-1 flex justify-between text-sm">
142 |           <span>{item.name}</span>
143 |           <span className="font-bold text-katalyst-500">{Math.round(item.value)}%</span>
144 |         </div>
145 |         <div className="progress-bar">
146 |           <div className="progress-bar-fill" style={{ width: `${item.value}%`, background: COLORS[i] }}>
147 |         </div>
148 |       </div>
149 |     ))}
150 |   </div>
151 | </div>
152 | </DashboardLayout>
153 | );
154 | }
155 | }                                     (8.9 KB)
156 |
1  | import { useEffect, useState } from "react";
2  | import DashboardLayout from "../../components/layout/DashboardLayout";
3  | import CalendarView from "../../components/CalendarView";
4  | import API from "../../api";
5  |
6  | export default function StudentMeetings() {
7  |   const [meetings, setMeetings] = useState([]);
8  |   const [mentors, setMentors] = useState([]);
9  |   const [loading, setLoading] = useState(true);
10 |   const [showBook, setShowBook] = useState(false);
11 |   const [form, setForm] = useState({ mentorId: "", topic: "", scheduledDate: "", scheduledTime: "", duration:
12 |   const [tab, setTab] = useState("calendar");
13 |
14 |   const fetchMeetings = () => {
15 |     API.get("/meetings/student")
16 |       .then((res) => setMeetings(res.data.meetings || []))
17 |       .catch(console.error)
18 |       .finally(() => setLoading(false));
19 |   };
20 |
21 |   const fetchMentors = () => {
22 |     API.get("/mentors")
23 |       .then((res) => setMentors(res.data.mentors || []))
24 |       .catch(console.error);
25 |   };
26 |
27 |   useEffect(() => {
28 |     fetchMeetings();
29 |     fetchMentors();
30 |   }, []);
31 |
32 |   const bookMeeting = async (e) => {
33 |     e.preventDefault();
34 |     try {
35 |       await API.post("/meetings", form);
36 |       setShowBook(false);
37 |       setForm({ mentorId: "", topic: "", scheduledDate: "", scheduledTime: "", duration: 30, agenda: "" });
38 |       alert("Meeting requested successfully!");
39 |       fetchMeetings();
40 |     } catch (err) {
41 |       alert(err.response?.data?.message || "Booking failed");
42 |     }
43 |   };
44 |
45 |   const cancelMeeting = async (id) => {
46 |     if (!confirm("Cancel this meeting?")) return;
```

```
47 |     await API.delete(`/meetings/${id}`);
48 |     fetchMeetings();
49 |   };
51 |   const submitFeedback = async (id) => {
52 |     const rating = prompt("Rate 1-5:");
53 |     const comment = prompt("Your feedback:");
54 |     if (!rating) return;
55 |     await API.post(`/meetings/${id}/feedback`, { rating: Number(rating), comment });
56 |     fetchMeetings();
57 |   };
59 |   const now = new Date();
60 |   const filtered = meetings.filter((m) => {
61 |     const date = new Date(m.scheduledDate);
62 |     if (tab === "upcoming") return date >= now && ![ "cancelled", "rejected", "completed" ].includes(m.status);
63 |     if (tab === "past") return date < now || [ "completed", "cancelled", "rejected" ].includes(m.status);
64 |     return true;
65 |   });
67 |   const statusColor = {
68 |     pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
69 |     accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
70 |     rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
71 |     completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
72 |     cancelled: "bg-gray-100 text-gray-600 dark:bg-gray-800 dark:text-gray-400",
73 |   };
75 |   return (
76 |     <DashboardLayout
77 |       title="Calendar & Meetings"
78 |       subtitle="Student Portal"
79 |       actions={
80 |         <button onClick={() => setShowBook(true)} className="btn-primary !py-2 text-sm">
81 |           + Book Meeting
82 |         </button>
83 |       }
84 |     >
85 |       <div className="mb-6 flex gap-2">
86 |         {[
87 |           { id: "calendar", label: "📅 Interactive Calendar" },
88 |           { id: "upcoming", label: "📅 Upcoming Meetings" },
89 |           { id: "past", label: "📅 Meeting History" },
90 |         ].map((t) => (
91 |           <button key={t.id} onClick={() => setTab(t.id)}
92 |             className={`rounded-full px-4 py-1.5 text-sm font-medium ${
93 |               tab === t.id ? "bg-katalyst-500 text-white" : "border"
94 |             }`}
95 |             style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
96 |           >
97 |             {t.label}
98 |           </button>
99 |         ))}
100 |       </div>
102 |       {loading ? (
103 |         <div className="flex h-40 items-center justify-center">
104 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
105 |             </div>
106 |         ) : tab === "calendar" ? (
107 |           <div className="space-y-6">
108 |             <CalendarView events={meetings} userRole="student" />
109 |             { /* Quick List under Calendar */ }
110 |             <div className="glass-card p-6">
111 |               <h3 className="section-title mb-4">Scheduled Sessions</h3>
112 |               <div className="space-y-3">
113 |                 {meetings.length === 0 ? (
114 |                   <p className="text-sm" style={{ color: "var(--text-muted)" }}>No meetings scheduled yet.</p>
115 |                 ) : (
116 |                   meetings.map((m) => (
117 |                     <div key={m._id} className="flex flex-wrap items-center justify-between gap-3 rounded-xl bor
118 |                       <div>
119 |                         <p className="font-bold">{m.topic}</p>
120 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
121 |                           with {m.mentorId?.name || "Mentor"} · {new Date(m.scheduledDate).toLocaleDateString()}
122 |                         </p>
123 |                       </div>
124 |                     </div>
```

```
125 |         <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.  
126 |             {m.status}  
127 |         }`}>  
128 |     </span>  
129 | </div>  
130 | ))  
131 | )}  
132 | </div>  
133 | </div>  
134 | ) : filtered.length === 0 ? (  
135 |     <div className="glass-card p-12 text-center">  
136 |         <p className="text-4xl">0</p>  
137 |         <p className="mt-4 font-medium">No {tab} meetings</p>  
138 |         <button onClick={() => setShowBook(true)} className="btn-primary mt-4">Book your first meeting</butt  
139 |     </div>  
140 | ) : (  
141 |     <div className="space-y-4">  
142 |         {filtered.map((m) => (  
143 |             <div key={m._id} className="glass-card p-5">  
144 |                 <div className="flex flex-wrap items-start justify-between gap-3">  
145 |                     <div>  
146 |                         <h3 className="font-bold">{m.topic}</h3>  
147 |                         <p className="text-sm" style={{ color: "var(--text-secondary)" }}>  
148 |                             with {m.mentorId?.name || "Mentor"} · {new Date(m.scheduledDate).toLocaleDateString()} at  
149 |                         </p>  
150 |                         {m.agenda && <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>{m.agenda}</  
151 |                     </div>  
152 |                     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.stat  
153 |                         {m.status}  
154 |                     }`}>  
155 |                 </span>  
156 |                 <div className="mt-4 flex flex-wrap gap-2">  
157 |                     {m.meetLink && m.status === "accepted" && (  
158 |                         <a href={m.meetLink} target="_blank" rel="noreferrer" className="btn-primary !py-1.5 text-xs  
159 |                             Join Google Meet  
160 |                     </a>  
161 |                     )}  
162 |                     {m.status === "pending" && (  
163 |                         <button onClick={() => cancelMeeting(m._id)} className="btn-secondary !py-1.5 text-xs">Cance  
164 |                     )}  
165 |                     {m.status === "completed" && !m.studentFeedback?.rating && (  
166 |                         <button onClick={() => submitFeedback(m._id)} className="btn-secondary !py-1.5 text-xs">Give  
167 |                     )}  
168 |                 </div>  
169 |             </div>  
170 |         )})  
171 |     </div>  
172 | )}  
173 | {showBook && (  
174 |     <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">  
175 |         <div className="glass-card w-full max-w-md p-6 animate-fade-in">  
176 |             <h3 className="text-xl font-bold">Book Mentor Meeting</h3>  
177 |             <form onSubmit={bookMeeting} className="mt-4 space-y-3">  
178 |                 {mentors.length > 0 && (  
179 |                     <select  
180 |                         className="input-field"  
181 |                         value={form.mentorId}  
182 |                         onChange={(e) => setForm({ ...form, mentorId: e.target.value })}  
183 |                     >  
184 |                         <option value="">Assigned / Default Mentor</option>  
185 |                         {mentors.map((m) => (  
186 |                             <option key={m._id} value={m._id}>{m.name} ({m.expertise?.join(", ") || "Mentor"})</option  
187 |                         )})  
188 |                     </select>  
189 |                 )}  
190 |                 <input className="input-field" placeholder="Topic (e.g. Code Review & Career Guidance)" value={f  
191 |                     onChange={(e) => setForm({ ...form, topic: e.target.value })} required />  
192 |                 <input type="date" className="input-field" value={form.scheduledDate}  
193 |                     onChange={(e) => setForm({ ...form, scheduledDate: e.target.value })} required />  
194 |                 <input type="time" className="input-field" value={form.scheduledTime}  
195 |                     onChange={(e) => setForm({ ...form, scheduledTime: e.target.value })} required />  
196 |                 <textarea className="input-field" placeholder="Agenda (optional)" rows={3} value={form.agenda}>  
197 |
```

```
198 |         onChange={(e) => setForm({ ...form, agenda: e.target.value })} />
199 |         <div className="flex gap-2">
200 |           <button type="button" onClick={() => setShowBook(false)} className="btn-secondary flex-1">Canc
201 |           <button type="submit" className="btn-primary flex-1">Book Meeting</button>
202 |         </div>
203 |       </form>
204 |     </div>
205 |   </div>
206 | )}
207 | </DashboardLayout>
208 | );
209 | }
210 | } (0.2 KB)
211 |
212 | import NotificationsPage from "../../components/NotificationsPage";
213 | export default function StudentNotifications() {
214 |   return <NotificationsPage userRole="student" />;
215 | } (4.6 KB)
216 |
217 | import { useEffect, useState } from "react";
218 | import DashboardLayout from "../../components/layout/DashboardLayout";
219 | import API from "../../api";
220 | export default function StudentProfile() {
221 |   const [profile, setProfile] = useState(null);
222 |   const [form, setForm] = useState({ name: "", phone: "", bio: "", skills: "" });
223 |   const [saving, setSaving] = useState(false);
224 |   const [resumeFile, setResumeFile] = useState(null);
225 |   useEffect(() => {
226 |     API.get("/students/profile")
227 |       .then((res) => {
228 |         const s = res.data.student;
229 |         setProfile(s);
230 |         setForm({ name: s.name, phone: s.phone || "", bio: s.bio || "", skills: (s.skills || []).join(", ") })
231 |       })
232 |       .catch(console.error);
233 |   }, []);
234 |   const saveProfile = async (e) => {
235 |     e.preventDefault();
236 |     setSaving(true);
237 |     try {
238 |       const res = await API.put("/students/profile", {
239 |         ...form,
240 |         skills: form.skills.split(",").map((s) => s.trim()).filter(Boolean),
241 |       });
242 |       setProfile(res.data.student);
243 |       alert("Profile updated!");
244 |     } catch (err) {
245 |       alert(err.response?.data?.message || "Update failed");
246 |     } finally {
247 |       setSaving(false);
248 |     }
249 |   };
250 |   const uploadResume = async () => {
251 |     if (!resumeFile) return;
252 |     const fd = new FormData();
253 |     fd.append("resume", resumeFile);
254 |     try {
255 |       const res = await API.post("/students/resume", fd, { headers: { "Content-Type": "multipart/form-data" } });
256 |       setProfile({ ...profile, resumeUrl: res.data.resumeUrl });
257 |       alert("Resume uploaded!");
258 |     } catch (err) {
259 |       alert(err.response?.data?.message || "Upload failed");
260 |     }
261 |   };
262 |   return (
263 |     <DashboardLayout title="Profile" subtitle="Student Portal">
264 |       <div className="grid gap-6 lg:grid-cols-2">
265 |         <div className="glass-card p-6">
266 |           <h3 className="section-title mb-4">Personal Information</h3>
267 |           <form onSubmit={saveProfile} className="space-y-4">
268 |             {[ "name", "phone" ].map((f) => (
269 |               <div key={f}>
270 |                 <label className="mb-1 block text-sm font-medium capitalize">{f}</label>
271 |                 <input type="text" value={form[f]} />
272 |               </div>
273 |             ))}
274 |           </form>
275 |         </div>
276 |         <div>
277 |           <h3>Notifications</h3>
278 |           <NotificationsPage userRole="student" />
279 |         </div>
280 |       </div>
281 |     </DashboardLayout>
282 |   );
283 | }
```

```
60 |         <input className="input-field" value={form[f]}
61 |           onChange={(e) => setForm({ ...form, [f]: e.target.value })} />
62 |       </div>
63 |     )))
64 |     <div>
65 |       <label className="mb-1 block text-sm font-medium">Bio</label>
66 |       <textarea className="input-field" rows={3} value={form.bio}
67 |         onChange={(e) => setForm({ ...form, bio: e.target.value })} />
68 |     </div>
69 |     <div>
70 |       <label className="mb-1 block text-sm font-medium">Skills (comma separated)</label>
71 |       <input className="input-field" value={form.skills}
72 |         onChange={(e) => setForm({ ...form, skills: e.target.value })} />
73 |     </div>
74 |     <button type="submit" disabled={saving} className="btn-primary">
75 |       {saving ? "Saving..." : "Save Changes"}
76 |     </button>
77 |   </form>
78 | </div>
79 |
80 |   <div className="space-y-6">
81 |     <div className="glass-card p-6">
82 |       <h3 className="section-title mb-4">ðŸ“œ Resume</h3>
83 |       {profile?.resumeUrl ? (
84 |         <a href={` ${import.meta.env.VITE_API_URL?.replace("/api", "")} || "http://localhost:5000" }${profile?.resumeUrl}`
85 |           className="text-katalyst-500 hover:underline text-sm">
86 |           View current resume !
87 |         </a>
88 |       ) : (
89 |         <p className="text-sm" style={{ color: "var(--text-muted)" }}>No resume uploaded yet.</p>
90 |       )}
91 |     <div className="mt-4">
92 |       <input type="file" accept=".pdf,.doc,.docx" onChange={(e) => setResumeFile(e.target.files[0])}
93 |         className="text-sm" />
94 |       <button onClick={uploadResume} disabled={!resumeFile} className="btn-primary mt-3 !py-2 text-sm">
95 |         Upload Resume
96 |       </button>
97 |     </div>
98 |   </div>
99 |
100 |   {profile?.assignedMentor && (
101 |     <div className="glass-card p-6">
102 |       <h3 className="section-title mb-4">ðŸ“œ ðŸ‘œ Assigned Mentor</h3>
103 |       <p className="font-bold">{profile.assignedMentor.name}</p>
104 |       <p className="text-sm" style={{ color: "var(--text-secondary)" }}>
105 |         {profile.assignedMentor.designation} . {profile.assignedMentor.company}
106 |       </p>
107 |       <p className="mt-2 text-xs" style={{ color: "var(--text-muted)" }}>
108 |         {profile.assignedMentor.expertise?.join(", ")}
109 |       </p>
110 |     </div>
111 |   )}
112 | </div>
113 | </div>
114 | </DashboardLayout>
115 | );
116 | } <a href="#">Download frontend/src/pages/student/Profile.jsx (7.0 KB)</a>
117 |
1 | import { useEffect, useState } from "react";
2 | import { useParams } from "react-router-dom";
3 | import DashboardLayout from "../../../components/layout/DashboardLayout";
4 | import API from "../../../api";
5 |
6 | export default function TrainingDetail() {
7 |   const { id } = useParams();
8 |   const [training, setTraining] = useState(null);
9 |   const [loading, setLoading] = useState(true);
10 |   const [quizAnswers, setQuizAnswers] = useState({});
11 |   const [quizResult, setQuizResult] = useState(null);
12 |   const [userEnrollment, setUserEnrollment] = useState(null);
13 |
14 |   const fetchTrainingDetails = () => {
15 |     API.get(`/trainings/${id}`)
16 |       .then((res) => {
17 |         setTraining(res.data.training);
18 |         setUserEnrollment(res.data.userEnrollment);
19 |       })
20 |   }
```

```
20 |     })
21 |     .catch(console.error)
22 |     .finally(() => setLoading(false));
23 |   };
24 |
25 |   useEffect(() => {
26 |     fetchTrainingDetails();
27 |   }, [id]);
28 |
29 |   const completeVideo = async (videoIndex) => {
30 |     try {
31 |       const res = await API.post(`/trainings/${id}/complete-video`, { videoIndex });
32 |       alert(res.data.message || "Video marked complete!");
33 |       fetchTrainingDetails();
34 |     } catch (err) {
35 |       alert(err.response?.data?.message || "Failed to mark video as completed");
36 |     }
37 |   };
38 |
39 |   const submitQuiz = async () => {
40 |     const formattedAnswers = Object.entries(quizAnswers).map(([qIdx, optIdx]) => ({
41 |       questionIndex: Number(qIdx),
42 |       selectedOption: Number(optIdx),
43 |     }));
44 |     try {
45 |       const res = await API.post(`/trainings/${id}/submit-quiz`, { answers: formattedAnswers });
46 |       setQuizResult(res.data);
47 |       alert(`Quiz Submitted! Score: ${res.data.score}/${res.data.maxScore}`);
48 |       fetchTrainingDetails();
49 |     } catch (err) {
50 |       alert(err.response?.data?.message || "Quiz submission failed");
51 |     }
52 |   };
53 |
54 |   if (loading) {
55 |     return (
56 |       <DashboardLayout title="Training" subtitle="Student Portal">
57 |         <div className="flex h-40 items-center justify-center">
58 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
59 |             </div>
60 |         </div>
61 |       </DashboardLayout>
62 |     );
63 |   }
64 |
65 |   if (!training) {
66 |     return (
67 |       <DashboardLayout title="Not Found" subtitle="Student Portal">
68 |         <p>Training not found.</p>
69 |       </DashboardLayout>
70 |     );
71 |   }
72 |
73 |   const completedVideos = userEnrollment?.completedVideos || [];
74 |
75 |   return (
76 |     <DashboardLayout title={training.title} subtitle={training.category}>
77 |       <div className="grid gap-6 lg:grid-cols-3">
78 |         <div className="lg:col-span-2 space-y-6">
79 |           <div>
80 |             <div className="glass-card p-6">
81 |               <div className="flex items-center justify-between mb-4">
82 |                 <h3 className="section-title">00 Video Lessons</h3>
83 |                 <span className="text-xs font-semibold text-katalyst-500">
84 |                   {completedVideos.length} / {training.videos?.length || 0} Completed
85 |                 </span>
86 |               </div>
87 |               <div className="space-y-3">
88 |                 {(training.videos || []).map((v, i) => {
89 |                   const isCompleted = completedVideos.includes(i);
90 |                   return (
91 |                     <div key={i} className="flex items-center justify-between rounded-xl border p-4"
92 |                       style={{ borderColor: "var(--border)", backgroundColor: isCompleted ? "rgba(16, 185, 129, 0.1)" : "var(--background)" }}
93 |                     >
94 |                       <p className="font-medium flex items-center gap-2">
95 |                         {isCompleted && <span className="text-green-500">'</span>}
96 |                         {v.title}
97 |                       </p>
98 |                       <p className="text-xs" style={{ color: "var(--text-muted)" }}>{v.duration}</p>
```

```
99 |         </div>
100 |         <div className="flex gap-2">
101 |             {v.url && (
102 |                 <a href={v.url} target="_blank" rel="noreferrer" className="btn-secondary !py-1.5 text
103 |                     Watch Video
104 |                 </a>
105 |             )}
106 |             <button
107 |                 onClick={() => completeVideo(i)}
108 |                 disabled={isCompleted}
109 |                 className={`!py-1.5 text-xs ${isCompleted ? "btn-secondary opacity-60 cursor-not-allow
110 |                 }
111 |                 {isCompleted ? "Completed" : "Mark Done"}
112 |             </button>
113 |         </div>
114 |     </div>
115 |     );
116 |     }}}
117 | </div>
118 | </div>
119 |
120 | /* Quiz */
121 | {(training.quizzes || []).length > 0 && (
122 |     <div className="glass-card p-6">
123 |         <h3 className="section-title mb-4">ðŸ’¼ Quiz</h3>
124 |         {training.quizzes.map((q, qi) => (
125 |             <div key={qi} className="mb-4">
126 |                 <p className="font-medium">{q.question}</p>
127 |                 <div className="mt-2 space-y-2">
128 |                     {q.options.map((opt, oi) => (
129 |                         <label key={oi} className="flex items-center gap-2 rounded-lg border p-3 cursor-pointer
130 |                             style={{ borderColor: "var(--border)" }}>
131 |                             <input type="radio" name={`q${qi}`}
132 |                                 onChange={() => setQuizAnswers({ ...quizAnswers, [qi]: oi })} />
133 |                             {opt}
134 |                         </label>
135 |                     ))}
136 |                 </div>
137 |             </div>
138 |         ))}
139 |         <button onClick={submitQuiz} className="btn-primary">Submit Quiz</button>
140 |         {quizResult && (
141 |             <p className="mt-3 text-sm font-semibold text-katalyst-500">
142 |                 Result: {quizResult.score}/{quizResult.maxScore} ({quizResult.percentage}%)
143 |             </p>
144 |         )}
145 |     </div>
146 | )}
147 | </div>
148 |
149 | /* Sidebar info */
150 | <div className="space-y-4">
151 |     <div className="glass-card p-6">
152 |         <h3 className="font-bold">Course Info</h3>
153 |         <div className="mt-4 space-y-2 text-sm" style={{ color: "var(--text-secondary)" }}>
154 |             <p>ðŸŒŠ Level: {training.level}</p>
155 |             <p>#ðŸ’š Duration: {training.duration}</p>
156 |             <p>ðŸŒŠ ðŸ‘Œ Instructor: {training.instructor}</p>
157 |             <p>ðŸŒŠ Videos: {training.videos?.length || 0}</p>
158 |             <p>ðŸŒŠ Assignments: {training.assignments?.length || 0}</p>
159 |         </div>
160 |     </div>
161 |
162 |     {(training.assignments || []).length > 0 && (
163 |         <div className="glass-card p-6">
164 |             <h3 className="font-bold mb-3">ðŸŒŠ Assignments</h3>
165 |             {training.assignments.map((a, i) => (
166 |                 <div key={i} className="mb-3 rounded-lg p-3" style={{ background: "var(--accent-light)" }}>
167 |                     <p className="font-medium text-sm">{a.title}</p>
168 |                     <p className="text-xs mt-1" style={{ color: "var(--text-muted)" }}>{a.description}</p>
169 |                     <p className="text-xs mt-1 text-katalyst-500">Due: {new Date(a.dueDate).toLocaleDateString()}
170 |                 </div>
171 |             ))}
172 |         </div>
173 |     )}
```



```
174 |     </div>
175 |   </div>
176 | </DashboardLayout>
177 | );
178 | } <!-- frontend/src/pages/student/trainings (3.1 KB)
179 |
1 | import { useEffect, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import DashboardLayout from "../../components/layout/DashboardLayout";
4 | import API from "../../api";
5 |
6 | export default function StudentTrainings() {
7 |   const [trainings, setTrainings] = useState([]);
8 |   const [loading, setLoading] = useState(true);
9 |   const [filter, setFilter] = useState("all");
10 |
11 |   useEffect(() => {
12 |     API.get("/trainings")
13 |       .then((res) => setTrainings(res.data.trainings || []))
14 |       .catch(console.error)
15 |       .finally(() => setLoading(false));
16 |   }, []);
17 |
18 |   const categories = ["all", ...new Set(trainings.map((t) => t.category))];
19 |   const filtered = filter === "all" ? trainings : trainings.filter((t) => t.category === filter);
20 |   const enroll = async (id) => {
21 |     try {
22 |       await API.post(`/trainings/${id}/enroll`);
23 |       alert("Enrolled successfully!");
24 |     } catch (err) {
25 |       alert(err.response?.data?.message || "Enrollment failed");
26 |     }
27 |   };
28 |
29 |   return (
30 |     <DashboardLayout title="Trainings" subtitle="Student Portal">
31 |       <div className="mb-6 flex flex-wrap gap-2">
32 |         {categories.map((cat) => (
33 |           <button key={cat} onClick={() => setFilter(cat)}
34 |             className={`rounded-full px-4 py-1.5 text-sm font-medium capitalize transition-all ${
35 |               filter === cat ? "bg-katalyst-500 text-white" : "border"
36 |             }`}
37 |             style={filter !== cat ? { borderColor: "var(--border)" } : {}}
38 |           >
39 |             {cat}
40 |           </button>
41 |         ))}
42 |       </div>
43 |       {loading ? (
44 |         <div className="flex h-40 items-center justify-center">
45 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500" />
46 |         </div>
47 |       ) : (
48 |         <div className="grid gap-6 sm:grid-cols-2 xl:grid-cols-3">
49 |           {filtered.map((t) => (
50 |             <div key={t._id} className="glass-card overflow-hidden transition-transform hover:-translate-y-1">
51 |               {t.thumbnail && (
52 |                 <img src={t.thumbnail} alt={t.title} className="h-40 w-full object-cover" />
53 |               )}
54 |               <div className="p-5">
55 |                 <span className="badge">{t.category}</span>
56 |                 <h3 className="mt-3 text-lg font-bold">{t.title}</h3>
57 |                 <p className="mt-2 line-clamp-2 text-sm" style={{ color: "var(--text-secondary)" }}>
58 |                   {t.description}
59 |                 </p>
60 |                 <div className="mt-3 flex gap-3 text-xs" style={{ color: "var(--text-muted)" }}>
61 |                   <span>ðŸšš {t.level}</span>
62 |                   <span>#âšŸ {t.duration}</span>
63 |                   <span>ðŸ‘Œ {t.enrolledStudents?.length || 0}</span>
64 |                 </div>
65 |                 <div className="mt-4 flex gap-2">
66 |                   <Link to={`/student/trainings/${t._id}`} className="btn-primary flex-1 !py-2 text-sm text-ce" />
67 |                   View Details
68 |                   </Link>
69 |                   <button onClick={() => enroll(t._id)} className="btn-secondary !py-2 text-sm">
70 |                     Enroll
71 |                   </button>
72 |                 </div>

```

KATALYST.

Source Code: frontend/src/pages/student/Trainings.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```
73 |         </button>
74 |     </div>
75 | </div>
76 | </div>
77 |     )})
78 | </div>
79 | })
80 | </DashboardLayout>
81 | );
82 | } // frontend/src/pages/student/Trainings.jsx (0.8 KB)
83 |
1 | /** @type {import('tailwindcss').Config} */
2 | export default {
3 |   content: ["../index.html", "./src/**/*.{js,ts,jsx,tsx}"],
4 |   darkMode: "class",
5 |   theme: {
6 |     extend: {
7 |       colors: {
8 |         catalyst: {
9 |           50: "#eff6ff",
10 |           100: "#dbeafe",
11 |           200: "#b2dfdb",
12 |           300: "#93c5fd",
13 |           400: "#60a5fa",
14 |           500: "#3b82f6",
15 |           600: "#2563eb",
16 |           700: "#1d4ed8",
17 |           800: "#1e40af",
18 |           900: "#1e3a8a",
19 |           950: "#172554",
20 |         },
21 |       },
22 |       fontFamily: {
23 |         sans: ["Inter", "system-ui", "sans-serif"],
24 |       },
25 |       boxShadow: {
26 |         glass: "0 8px 32px rgba(37, 99, 235, 0.08)",
27 |         "glass-lg": "0 16px 48px rgba(37, 99, 235, 0.14)",
28 |       },
29 |       backdropBlur: {
30 |         glass: "16px",
31 |       },
32 |     },
33 |   },
34 |   plugins: [],
35 | }; // frontend/src/pages/student/Trainings.jsx (0.2 KB)
36 |
1 | import { defineConfig } from 'vite'
2 | import react from '@vitejs/plugin-react'
3 |
4 | // https://vite.dev/config/
5 | export default defineConfig({
6 |   plugins: [react()],
7 | }) // frontend/vite.config.js (2.6 KB)
8 |
1 | # Catalyst – Student-Mentor Learning Platform
2 |
3 | Catalyst is a multi-role learning platform built with React, Tailwind CSS, Node.js, Express, and MongoDB Atlas
4 |
5 | ## Key Features
6 |
7 | - Role-based application for Students, Mentors, and Admins
8 | - JWT authentication with secure role-based access control
9 | - Training module with videos, quizzes, assignments, progress tracking, certificates
10 | - Meeting module with scheduling, Google Meet links, mentor responses, feedback, and notes
11 | - Progress analytics with placement readiness and career roadmap support
12 | - Notifications, resume upload, certificate downloads, email notifications
13 | - Docker support for backend, frontend, and MongoDB
14 |
15 | ## Folder Structure
16 |
17 | - `backend/` – Express API, models, controllers, middleware, uploads, Docker config
18 | - `frontend/` – React application, Tailwind CSS, pages, components
19 |
20 | ## Setup
21 |
22 | ### Backend
23 |
24 | 1. Copy `.env.example` to `.env` in `backend/`
25 | 2. Fill values for `MONGO_URI`, `JWT_SECRET`, `EMAIL_USER`, and `EMAIL_PASS`
```

```
26 | 3. Install dependencies:
27 |     ``bash
28 |     cd backend
29 |     npm install
30 |     ``
31 | 4. Start development server:
32 |     ``bash
33 |     npm run dev
34 |     ``
36 | ### Frontend
38 | 1. Copy `.env.example` to `.env` in `frontend/`
39 | 2. Install dependencies:
40 |     ``bash
41 |     cd frontend
42 |     npm install
43 |     ``
44 | 3. Start development server:
45 |     ``bash
46 |     npm run dev
47 |     ``
49 | ## Docker
51 | Run the app using Docker Compose:
53 |     ``bash
54 |     docker-compose up --build
55 |     ``
57 | ## Seed Data
59 | To create starter data for the backend:
61 |     ``bash
62 |     cd backend
63 |     npm run seed
64 |     ``
66 | ## Environment Variables
68 | Backend `.env` variables:
70 | - `MONGO_URI`
71 | - `JWT_SECRET`
72 | - `JWT_EXPIRES_IN`
73 | - `CLIENT_URL`
74 | - `EMAIL_USER`
75 | - `EMAIL_PASS`
76 | - `NODE_ENV`
77 | - `PORT`
79 | Frontend `.env` variables:
81 | - `VITE_API_URL`
83 | ## APIs
85 | - `POST /api/auth/register` - Student registration
86 | - `POST /api/auth/login` - Login for student, mentor, admin
87 | - `GET /api/students/*` - Student dashboard and profile routes
88 | - `GET /api/mentors/*` - Mentor dashboard and meeting routes
89 | - `GET /api/admin/*` - Admin analytics, user management, reports
90 | - `GET /api/trainings/*` - Training discovery and enrollment
91 | - `GET /api/meetings/*` - Meeting scheduling and status
92 | - `GET /api/notifications/*` - Notification management
93 | - `GET /api/progress/*` - Progress analytics and readiness
94 | - `POST /api/ai/*` - AI-assisted resume analysis and roadmap suggestions
96 | ## Notes
98 | The platform is designed for production readiness with secure middleware, rate limiting, and role-based access
99 |
```


